

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415030
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Cook; Steven B. et al.

Insulin patch pump

Abstract

A user-wearable patch pump system for delivery of insulin or other medicament can include a pump and an attachment portion that attaches the pump to a user's body. The pump can include a drive unit and a disposable cartridge containing a medicament with the drive unit configured to cause the pump to deliver the medicament in the cartridge to the user. The attachment portion can include a retention frame configured to selectively retain the pump therein and an adhesive patch configured to be attached to the user's body. The pump can be selectively attached to the retention frame and used to deliver medicament either through a cannula to an infusion site directly beneath the retention frame or through tubing to an infusion site displaced from the retention frame.

Inventors: Cook; Steven B. (Oceanside, CA), Michaud; Michael (San Diego, CA), Lamb; Philip (San Diego, CA)

Applicant: Tandem Diabetes Care, Inc. (San Diego, CA)

Family ID: 1000008820774

Assignee: TANDEM DIABETES CARE, INC. (San Diego, CA)

Appl. No.: 17/319867

Filed: May 13, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210293810 A1	Sep. 23, 2021

Related U.S. Application Data

continuation parent-doc US 16398402 20190430 US 11033677 child-doc US 17319867
continuation parent-doc US 14707851 20150508 US 10279106 20190507 child-doc US 16398402
us-provisional-application US 61990501 20140508

Publication Classification

Int. Cl.: A61M5/142 (20060101); G01N33/543 (20060101); G01N33/558 (20060101)

U.S. Cl.:

CPC A61M5/14248 (20130101); G01N33/54386 (20130101); G01N33/558 (20130101); A61M2005/14252 (20130101); A61M2005/14268 (20130101)

Field of Classification Search

CPC: A61M (2005/14252); A61M (2005/14268); A61M (5/14248); A61M (5/002); G01N (33/54386); G01N (33/558)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4908017	12/1989	Howson et al.	N/A	N/A
5050612	12/1990	Matsumura	N/A	N/A
5053189	12/1990	Chrise et al.	N/A	N/A
5665065	12/1996	Colman et al.	N/A	N/A
6280408	12/2000	Sipin	N/A	N/A
6295506	12/2000	Heinonen et al.	N/A	N/A
6551276	12/2002	Mann et al.	N/A	N/A
6554798	12/2002	Mann et al.	N/A	N/A
6589229	12/2002	Connelly et al.	N/A	N/A
6641533	12/2002	Causey, III et al.	N/A	N/A
6699218	12/2003	Flaherty et al.	N/A	N/A
6702779	12/2003	Connelly et al.	N/A	N/A
6813519	12/2003	Lebel et al.	N/A	N/A
6872200	12/2004	Mann et al.	N/A	N/A
6936029	12/2004	Mann et al.	N/A	N/A
6940209	12/2004	Henderson	N/A	N/A
6952604	12/2004	Denuzzio et al.	N/A	N/A
6955819	12/2004	Zhang et al.	N/A	N/A
6979326	12/2004	Mann et al.	N/A	N/A
6997920	12/2005	Mann et al.	N/A	N/A
7008399	12/2005	Larsen et al.	N/A	N/A
7056179	12/2005	Courtney	N/A	N/A
7109878	12/2005	Mann et al.	N/A	N/A
7170214	12/2006	Henderson et al.	N/A	N/A
7250037	12/2006	Shermer et al.	N/A	N/A
7309943	12/2006	Henderson et al.	N/A	N/A
7339306	12/2007	Henderson	N/A	N/A
7426408	12/2007	Denuzzio et al.	N/A	N/A
7429258	12/2007	Angel et al.	N/A	N/A
7455663	12/2007	Bikovsky	N/A	N/A

7464010	12/2007	Yang et al.	N/A	N/A
7534226	12/2008	Mernoe et al.	N/A	N/A
7569050	12/2008	Moberg et al.	N/A	N/A
7632247	12/2008	Adams	N/A	N/A
7641649	12/2009	Moberg et al.	N/A	N/A
7682338	12/2009	Griffin	N/A	N/A
7686787	12/2009	Moberg et al.	N/A	N/A
7699833	12/2009	Moberg et al.	N/A	N/A
7708717	12/2009	Estes et al.	N/A	N/A
7713262	12/2009	Adams et al.	N/A	N/A
7717903	12/2009	Estes et al.	N/A	N/A
7736338	12/2009	Kavazov et al.	N/A	N/A
7736344	12/2009	Moberg et al.	N/A	N/A
7744589	12/2009	Mounce et al.	N/A	N/A
7776030	12/2009	Estes et al.	N/A	N/A
7782192	12/2009	Jeckelmann et al.	N/A	N/A
7786648	12/2009	Xu et al.	N/A	N/A
7789857	12/2009	Moberg et al.	N/A	N/A
7794426	12/2009	Briones et al.	N/A	N/A
7794427	12/2009	Estes et al.	N/A	N/A
7794428	12/2009	Estes et al.	N/A	N/A
7794434	12/2009	Mounce	N/A	N/A
7806868	12/2009	De Polo et al.	N/A	N/A
7811262	12/2009	Moberg et al.	N/A	N/A
7815609	12/2009	Hines et al.	N/A	N/A
7819343	12/2009	Paul et al.	N/A	N/A
7828528	12/2009	Estes et al.	N/A	N/A
7828764	12/2009	Moberg et al.	N/A	N/A
7833196	12/2009	Estes	N/A	N/A
7875022	12/2010	Wenger et al.	N/A	N/A
7879026	12/2010	Estes et al.	N/A	N/A
7887511	12/2010	Mernøe et al.	N/A	N/A
7887512	12/2010	Estes et al.	N/A	N/A
7892199	12/2010	Mhatre et al.	N/A	N/A
7905868	12/2010	Moberg et al.	N/A	N/A
7933780	12/2010	De La Huerga	N/A	N/A
7935076	12/2010	Estes et al.	N/A	N/A
7935105	12/2010	Miller et al.	N/A	N/A
7938797	12/2010	Estes	N/A	N/A
7938803	12/2010	Mernoe et al.	N/A	N/A
7945452	12/2010	Fathallah et al.	N/A	N/A
7955305	12/2010	Moberg et al.	N/A	N/A
7959598	12/2010	Estes	N/A	N/A
7959715	12/2010	Kavazov et al.	N/A	N/A
7963954	12/2010	Kavazov	N/A	N/A
7976500	12/2010	Adams et al.	N/A	N/A
7976505	12/2010	Hines et al.	N/A	N/A
7981076	12/2010	Sullivan et al.	N/A	N/A
7981084	12/2010	Estes et al.	N/A	N/A

7981102	12/2010	Patel et al.	N/A	N/A
7999674	12/2010	Kamen	N/A	N/A
8032226	12/2010	Miller et al.	N/A	N/A
8062256	12/2010	Carter et al.	N/A	N/A
8078983	12/2010	Davis et al.	N/A	N/A
8095123	12/2011	Gray	N/A	N/A
8105279	12/2011	Mernoe et al.	N/A	N/A
8109921	12/2011	Estes et al.	N/A	N/A
8114350	12/2011	Silver et al.	N/A	N/A
8115600	12/2011	Stevenson et al.	N/A	N/A
8117481	12/2011	Anselmi et al.	N/A	N/A
8126728	12/2011	Dicks et al.	N/A	N/A
8128597	12/2011	Cross et al.	N/A	N/A
8187228	12/2011	Bikovsky	N/A	N/A
8211062	12/2011	Estes et al.	N/A	N/A
8211093	12/2011	Miller et al.	N/A	N/A
8217533	12/2011	Jones et al.	N/A	N/A
8221385	12/2011	Estes	N/A	N/A
8231572	12/2011	Carter et al.	N/A	N/A
8234126	12/2011	Estes	N/A	N/A
8277435	12/2011	Estes	N/A	N/A
8282601	12/2011	Mernoe et al.	N/A	N/A
8285328	12/2011	Caffey et al.	N/A	N/A
8287487	12/2011	Estes	N/A	N/A
8287495	12/2011	Michaud et al.	N/A	N/A
8287514	12/2011	Miller et al.	N/A	N/A
8299733	12/2011	Sattler et al.	N/A	N/A
8304960	12/2011	Sattler et al.	N/A	N/A
8323188	12/2011	Tran	N/A	N/A
8328754	12/2011	Estes et al.	N/A	N/A
8343092	12/2012	Rush et al.	N/A	N/A
8344847	12/2012	Moberg et al.	N/A	N/A
8361030	12/2012	Carter	N/A	N/A
8409142	12/2012	Causey	N/A	N/A
8414523	12/2012	Blomquist et al.	N/A	N/A
8414563	12/2012	Kamen et al.	N/A	N/A
8444595	12/2012	Brukalo et al.	N/A	N/A
8448824	12/2012	Diperna	N/A	N/A
8449523	12/2012	Brukalo et al.	N/A	N/A
8450905	12/2012	Guidarelli et al.	N/A	N/A
8451230	12/2012	Celentano et al.	N/A	N/A
8452953	12/2012	Buck et al.	N/A	N/A
8454557	12/2012	Qi et al.	N/A	N/A
8454562	12/2012	Sims	N/A	N/A
8454575	12/2012	Estes et al.	N/A	N/A
8454581	12/2012	Estes et al.	N/A	N/A
8466637	12/2012	Guidarelli et al.	N/A	N/A
8469920	12/2012	Mernoe et al.	N/A	N/A
8502662	12/2012	Pohlman et al.	N/A	N/A
8517991	12/2012	Clemente	N/A	N/A

8573027	12/2012	Rosinko et al.	N/A	N/A
8601465	12/2012	Bernstein et al.	N/A	N/A
8728034	12/2013	Yodfat et al.	N/A	N/A
8740847	12/2013	Levesque	N/A	N/A
8801655	12/2013	Mernoe	N/A	N/A
8852152	12/2013	Tverskoy	N/A	N/A
8986253	12/2014	Diperna	N/A	N/A
9101714	12/2014	Miyazaki	N/A	N/A
9114210	12/2014	Estes	N/A	N/A
9259531	12/2015	Kamen	N/A	N/A
9308319	12/2015	Mernoe	N/A	N/A
9362851	12/2015	Xu et al.	N/A	N/A
9968729	12/2017	Estes	N/A	N/A
9993595	12/2017	Michaud et al.	N/A	N/A
10279106	12/2018	Cook et al.	N/A	N/A
10279107	12/2018	Michaud	N/A	N/A
10357603	12/2018	Michaud et al.	N/A	N/A
11033677	12/2020	Cook	N/A	G01N 33/558
2003/0199378	12/2002	Saviano	N/A	N/A
2004/0092865	12/2003	Flaherty et al.	N/A	N/A
2005/0177111	12/2004	Ozeri et al.	N/A	N/A
2006/0229557	12/2005	Fathallah et al.	N/A	N/A
2006/0250260	12/2005	Albert	N/A	N/A
2006/0253086	12/2005	Moberg et al.	N/A	N/A
2007/0073236	12/2006	Mernoe et al.	N/A	N/A
2007/0156092	12/2006	Estes et al.	N/A	N/A
2007/0167905	12/2006	Estes et al.	N/A	N/A
2007/0167912	12/2006	Causey et al.	N/A	N/A
2007/0173762	12/2006	Estes et al.	N/A	N/A
2007/0179444	12/2006	Causey et al.	N/A	N/A
2007/0219480	12/2006	Kamen et al.	N/A	N/A
2007/0219496	12/2006	Kamen et al.	N/A	N/A
2007/0219597	12/2006	Kamen et al.	N/A	N/A
2007/0228071	12/2006	Kamen et al.	N/A	N/A
2007/0233051	12/2006	Hohl	604/500	A61B 5/1486
2008/0045902	12/2007	Estes et al.	N/A	N/A
2008/0045903	12/2007	Estes et al.	N/A	N/A
2008/0045904	12/2007	Estes et al.	N/A	N/A
2008/0045931	12/2007	Estes et al.	N/A	N/A
2008/0051697	12/2007	Mounce et al.	N/A	N/A
2008/0051698	12/2007	Mounce et al.	N/A	N/A
2008/0051709	12/2007	Mounce et al.	N/A	N/A
2008/0051711	12/2007	Mounce et al.	N/A	N/A
2008/0051716	12/2007	Stutz	N/A	N/A
2008/0051727	12/2007	Moberg et al.	N/A	N/A
2008/0051765	12/2007	Mounce	N/A	N/A
2008/0097291	12/2007	Hanson et al.	N/A	N/A
2008/0097327	12/2007	Bente et al.	N/A	N/A

2008/0097375	12/2007	Moberg et al.	N/A	N/A
2008/0215035	12/2007	Yodfat et al.	N/A	N/A
2008/0269680	12/2007	Ibranyan et al.	N/A	N/A
2008/0269681	12/2007	Kavazov et al.	N/A	N/A
2008/0269682	12/2007	Kavazov et al.	N/A	N/A
2008/0294094	12/2007	Mhatre et al.	N/A	N/A
2008/0294108	12/2007	Briones et al.	N/A	N/A
2008/0294109	12/2007	Estes et al.	N/A	N/A
2008/0294142	12/2007	Patel et al.	N/A	N/A
2009/0036870	12/2008	Mounce et al.	N/A	N/A
2009/0067989	12/2008	Estes et al.	N/A	N/A
2009/0069745	12/2008	Estes et al.	N/A	N/A
2009/0069746	12/2008	Miller et al.	N/A	N/A
2009/0069749	12/2008	Miller et al.	N/A	N/A
2009/0069784	12/2008	Estes et al.	N/A	N/A
2009/0069785	12/2008	Miller et al.	N/A	N/A
2009/0082728	12/2008	Estes et al.	N/A	N/A
2009/0124994	12/2008	Roe	N/A	N/A
2009/0156990	12/2008	Wenger et al.	N/A	N/A
2009/0171324	12/2008	Chong et al.	N/A	N/A
2009/0177142	12/2008	Blomquist et al.	N/A	N/A
2009/0177991	12/2008	Davis et al.	N/A	N/A
2009/0254037	12/2008	Bryant, Jr. et al.	N/A	N/A
2009/0259183	12/2008	Chong et al.	N/A	N/A
2009/0259198	12/2008	Chong et al.	N/A	N/A
2009/0259209	12/2008	Mounce et al.	N/A	N/A
2009/0275887	12/2008	Estes	N/A	N/A
2009/0287180	12/2008	Diperna	N/A	N/A
2009/0326458	12/2008	Chong et al.	N/A	N/A
2010/0008795	12/2009	Diperna	N/A	N/A
2010/0010647	12/2009	Schroeder et al.	N/A	N/A
2010/0049164	12/2009	Estes	N/A	N/A
2010/0071446	12/2009	Brown	N/A	N/A
2010/0094251	12/2009	Estes	N/A	N/A
2010/0152658	12/2009	Hanson et al.	N/A	N/A
2010/0152674	12/2009	Kavazov et al.	N/A	N/A
2010/0174266	12/2009	Estes	N/A	N/A
2010/0185142	12/2009	Kamen et al.	N/A	N/A
2010/0185175	12/2009	Kamen et al.	N/A	N/A
2010/0198183	12/2009	Lanigan et al.	N/A	N/A
2010/0218586	12/2009	Rosinko et al.	N/A	N/A
2010/0228186	12/2009	Estes et al.	N/A	N/A
2010/0241065	12/2009	Moberg et al.	N/A	N/A
2010/0256565	12/2009	Mernøe	N/A	N/A
2010/0261987	12/2009	Kamath et al.	N/A	N/A
2010/0331824	12/2009	Moberg et al.	N/A	N/A
2011/0006876	12/2010	Moberg et al.	N/A	N/A
2011/0009725	12/2010	Hill et al.	N/A	N/A
2011/0009813	12/2010	Rankers	N/A	N/A
2011/0009815	12/2010	Chong et al.	N/A	N/A

2011/0009823	12/2010	Chong et al.	N/A	N/A
2011/0030845	12/2010	Chong et al.	N/A	N/A
2011/0040247	12/2010	Mandro et al.	N/A	N/A
2011/0040251	12/2010	Blomquist et al.	N/A	N/A
2011/0047499	12/2010	Mandro et al.	N/A	N/A
2011/0060280	12/2010	Caffey et al.	N/A	N/A
2011/0082439	12/2010	Wenge et al.	N/A	N/A
2011/0105955	12/2010	Yudovsky et al.	N/A	N/A
2011/0112504	12/2010	Causey et al.	N/A	N/A
2011/0118662	12/2010	Mhatre et al.	N/A	N/A
2011/0160650	12/2010	Chong et al.	N/A	N/A
2011/0160654	12/2010	Hason et al.	N/A	N/A
2011/0160666	12/2010	Hanson et al.	N/A	N/A
2011/0160678	12/2010	Chong et al.	N/A	N/A
2011/0178461	12/2010	Chong et al.	N/A	N/A
2011/0190694	12/2010	Lanier, Jr. et al.	N/A	N/A
2011/0190700	12/2010	Kavazov et al.	N/A	N/A
2011/0192478	12/2010	Chong et al.	N/A	N/A
2011/0213306	12/2010	Hanson et al.	N/A	N/A
2011/0213329	12/2010	Yodfat	604/154	A61M 5/14248
2012/0029708	12/2011	Millwe et al.	N/A	N/A
2012/0123230	12/2011	Brown et al.	N/A	N/A
2012/0185267	12/2011	Kamen et al.	N/A	N/A
2012/0203178	12/2011	Tverskoy	N/A	N/A
2012/0221778	12/2011	Doatmas et al.	N/A	N/A
2012/0302991	12/2011	Blomquist	N/A	N/A
2013/0012917	12/2012	Miller et al.	N/A	N/A
2013/0053816	12/2012	Diperna et al.	N/A	N/A
2013/0117696	12/2012	Robertson	N/A	N/A
2013/0159456	12/2012	Daoud et al.	N/A	N/A
2013/0231711	12/2012	Kaib	N/A	N/A
2013/0283196	12/2012	Farnan et al.	N/A	N/A
2013/0306191	12/2012	Metzmaker et al.	N/A	N/A
2013/0324920	12/2012	Kohli et al.	N/A	N/A
2013/0324928	12/2012	Kruse	N/A	N/A
2013/0331790	12/2012	Brown et al.	N/A	N/A
2013/0332874	12/2012	Rosinko et al.	N/A	N/A
2014/0012511	12/2013	Mensing et al.	N/A	N/A
2014/0054883	12/2013	Lanigan et al.	N/A	N/A
2014/0273042	12/2013	Saint	N/A	N/A
2014/0276409	12/2013	Rosinko et al.	N/A	N/A
2014/0276419	12/2013	Rosinko et al.	N/A	N/A
2014/0276420	12/2013	Rosinko	N/A	N/A
2014/0276423	12/2013	Lecanu-Fayet	N/A	N/A
2014/0276531	12/2013	Walsh	N/A	N/A
2014/0276533	12/2013	Rosinko et al.	N/A	N/A
2014/0276537	12/2013	Kruse	N/A	N/A
2014/0276538	12/2013	Michaud	N/A	N/A

2014/0276556	12/2013	Saint et al.	N/A	N/A
2014/0276569	12/2013	Kruse	N/A	N/A
2014/0276570	12/2013	Saint	N/A	N/A
2014/0276571	12/2013	Ludolph	N/A	N/A
2014/0276574	12/2013	Saint	N/A	N/A
2014/0296784	12/2013	Lopez	N/A	N/A
2014/0378898	12/2013	Rosinko	N/A	N/A
2015/0073337	12/2014	Saint et al.	N/A	N/A
2015/0077261	12/2014	Swanson	N/A	N/A
2015/0182695	12/2014	Rosinko	N/A	N/A
2016/0136357	12/2015	Yang	N/A	N/A
2016/0157759	12/2015	Yang	N/A	N/A
2016/0157765	12/2015	Zhu	N/A	N/A
2016/0158436	12/2015	Yang	N/A	N/A
2016/0199572	12/2015	Yang	N/A	N/A
2016/0256622	12/2015	Day	N/A	N/A
2016/0339197	12/2015	Meyerhoff et al.	N/A	N/A
2017/0049957	12/2016	Michaud	N/A	N/A
2017/0173261	12/2016	O'Connor	N/A	N/A
2017/0290976	12/2016	Murphy et al.	N/A	N/A
2018/0071454	12/2017	Betts et al.	N/A	N/A
2018/0093039	12/2017	Este	N/A	N/A
2018/0137252	12/2017	Mairs	N/A	N/A
2018/0137938	12/2017	Vaddiraju	N/A	N/A
2018/0161498	12/2017	Este	N/A	N/A
2018/0264189	12/2017	Michaud et al.	N/A	N/A
2018/0336208	12/2017	Kim	N/A	N/A
2019/0240398	12/2018	Seitz et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101745163	12/2012	CN	N/A
1980929	12/2007	EP	A45F 5/02
WO-2008080237	12/2007	WO	A61M 5/1413
2008103175	12/2007	WO	N/A
2008144693	12/2007	WO	N/A
2008144695	12/2007	WO	N/A
2008144697	12/2007	WO	N/A
2008144698	12/2007	WO	N/A
2009013736	12/2008	WO	N/A
2009016636	12/2008	WO	N/A
2009032399	12/2008	WO	N/A
2009032400	12/2008	WO	N/A
2009032402	12/2008	WO	N/A
2009035759	12/2008	WO	N/A

OTHER PUBLICATIONS

Primary Examiner: Bouchelle; Laura A

Attorney, Agent or Firm: Merchant & Gould P.C.

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of application Ser. No. 16/398,402 filed Apr. 30, 2019, which in turn is a continuation of application Ser. No. 14/707,851 filed May 8, 2015, now U.S. Pat. No. 10,279,106 issued May 7, 2019, which claims the benefit of U.S. Provisional Application No. 61/990,501 filed May 8, 2014, each of which is incorporated herein in its entirety by reference.

FIELD OF THE INVENTION

(1) The present invention relates to medical pumps for delivering medicament to a patient and, more specifically, to a user-wearable insulin patch pump for delivering insulin to a patient.

BACKGROUND OF THE INVENTION

(2) There are many applications in academic, industrial, and medical fields that benefit from devices and methods that are capable of accurately and controllably delivering fluids, such as liquids and gases, that have a beneficial effect when administered in known and controlled quantities. Such devices and methods can be particularly useful in the medical field where treatments for many patients include the administration of a known amount of a substance at predetermined intervals.

(3) One category of devices for delivering such fluids is that of pumps that have been developed for the administration of insulin and other medicaments for those suffering from both type I and type II diabetes. Some pumps configured as portable infusion devices can provide continuous subcutaneous medicament injection and/or infusion therapy for the treatment of diabetes. Such therapy may include, e.g., the regular and/or continuous injection or infusion of insulin into the skin of a person suffering from diabetes and offer an alternative to multiple daily injections of insulin by an insulin syringe or an insulin pen. Such pumps can be ambulatory/portable infusion pumps that are worn by the user and may use replaceable cartridges. Examples of such pumps and various features that can be associated with such pumps include those disclosed in U.S. patent application Ser. No. 13/557,163, U.S. patent application Ser. No. 12/714,299, U.S. patent application Ser. No. 12/538,018, U.S. patent application Ser. No. 13/838,617, U.S. patent application Ser. No. 13/827,707 and U.S. patent Ser. No. 8,287,495, each of which is hereby incorporated herein by reference in its entirety.

(4) One type of pump that has been developed is a patch pump, or micro pump. Patch pumps are small pumps, typically ambulatory, that are carried directly on the skin under the user's clothing. Such a pump generally is situated directly on the injection site such that no tubing is required to deliver the insulin or other medicament to the patient. Patch pumps typically are at least in part disposable, meant to be worn for a day or two and then discarded for a new patch pump.

SUMMARY

(5) A user-wearable patch pump system for delivery of insulin or other medicament can include a pump and an attachment portion that attaches the pump to a user's body. The pump can include a drive unit and a disposable cartridge containing a medicament with the drive unit configured to

cause the pump to deliver the medicament in the cartridge to the user. The attachment portion can include a retention frame configured to selectively retain the pump therein and an adhesive patch configured to be attached to the user's body.

(6) In one embodiment, the user-wearable patch pump system can include both tubing configured to extend between the retention frame and an infusion site displaced from the retention frame and a cannula configured to extending into an infusion site directly beneath the retention frame. In such an embodiment, the pump can be selectively attached to the retention frame and used to deliver medicament either through the cannula to the infusion site directly beneath the retention frame or through the tubing to the infusion site displaced from the retention frame. Such a configuration provides the user with the flexibility of using multiple infusion sites with a single point of attachment of the pump on the body.

(7) In some embodiments, the retention frame can include a sealing membrane. The sealing membrane can provide an opening through the frame configured to receive a removable needle for insertion of a cannula that can be used to deliver medicament. In other embodiments, the retention frame can include a receiving slot configured to receive a connector of a standard infusion set. In such embodiments, the cannula of the infusion set can then be used to deliver medicament.

(8) In various embodiments, the pump can attach to and be retained by the frame in a variety of different ways. In some embodiments, the pump is mated with the retention frame in a generally vertical manner to cause one or more tabs on the frame to snap into engagement with one or more recesses on the pump. In one such embodiment, the frame includes a first tab configured as a hook portion and a second tab configured as a snap portion. The pump can be engaged with the frame by first inserting a first recess in the pump onto the hook portion and then rotating the pump downwardly about the hook portion to engage a second recess in the pump with the snap portion.

(9) In other embodiments, the pump can be generally horizontally, slidably received by the frame, such as by engaging elongate recesses along the sides of the pump with elongate tabs on the frame or by engaging an elongate recess on a bottom of the pump with an elongate upwardly extending projection on the frame. In a further embodiment, the frame can include a rotatable cleat such that engaging a recess on the pump with the cleat and then turning the pump on the cleat locks the pump onto the frame.

(10) Certain embodiments are described further in the following description, examples, claims, and drawings. These embodiments will become more apparent from the following detailed description when taken in conjunction with the accompanying exemplary drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. 1A-1F are perspective views of portions of a patch pump system according to an embodiment of the present invention.
- (2) FIGS. 2A-2F are perspective views of portions of a patch pump system according to an embodiment of the present invention.
- (3) FIGS. 3A-3F are perspective views of portions of a patch pump system according to an embodiment of the present invention.
- (4) FIGS. 4A-4F are perspective views of portions of a patch pump system according to an embodiment of the present invention.
- (5) FIGS. 5A-5D are perspective views of portions of a patch pump system according to an embodiment of the present invention.
- (6) FIGS. 6A-6E are perspective views of portions of a patch pump system according to an embodiment of the present invention.
- (7) FIG. 7 is a screen shot of a control screen for a control device for controlling a patch pump

according to an embodiment of the present invention.

(8) FIGS. **8A-8F** are views of portions of a patch pump system according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

(9) FIGS. **1A-1F** depict a patch pump **100** according to one embodiment of the invention. Patch pump **100** includes a pump **102** and an attachment portion **104** that enables the attachment of the pump **104** to the user.

(10) The attachment portion **104** of patch pump, depicted most clearly in FIGS. **1A** and **1B**, includes a retention frame **106** affixed to an adhesive patch **108** and a removable needle **110**. In one embodiment, the retention frame **106** is preattached to the adhesive patch **108** with, for example, glue or other suitable adhesive or technique. In other embodiments, the retention frame **106** can be removably attachable with the adhesive patch **108** or can be permanently attached to the retention frame **106** by the user. In certain embodiments, the retention frame **106** can comprise polypropylene, polycarbonate or Cyclic Insulin Copolymer (COC). In general, retention frame **106** can comprise any flexible and fatigue-resistant material.

(11) In this embodiment, the retention frame **106** includes a seal membrane **112** near an end of the frame **106**, a pair of tabs **114** along each side of the frame **106** and a removable needle **110**. The sealing membrane **112** initially interfaces with the removable needle **110**. When the attachment portion **104** is positioned on the user's body, the removable needle **110**, as extended through the sealing membrane **112**, penetrates the user's skin to insert a cannula **130** (shown in FIG. **1F**) through the user's skin. The removable needle **110** can then be removed and discarded. As will be described herein, the sealing membrane **112** will interface with the pump for delivering medicament such as, e.g., insulin, from the pump **102** to the patient through the cannula **130**.

(12) The pump **102** includes a cartridge **116** and a drive unit **118** that mate together to form the pump **102**. Cartridge **116** is generally a disposable unit containing medicament such as insulin and a drive unit **118** in operation interfaces with cartridge **116** to cause medicament such as insulin from the cartridge to be delivered to the patient. As can be seen in FIG. **1C**, cartridge **116** can include an electrical contact **120** for electrically connecting the cartridge **116** and the drive unit **118** and a drive mechanism **122** that mechanically interconnects the cartridge **116** with the drive unit **118** to enable to drive unit **118** to cause insulin to be delivered from the cartridge **116**. The drive unit, as shown in FIG. **1F**, can include corresponding recesses **124**, **126** for accepting the electrical contact **120** and the drive mechanism **122**, respectively. Cartridge also includes an opening **128** in a bottom of the cartridge that is aligned with the sealing membrane **112** of the retention frame **106**, thereby aligning a cartridge cannula **132** with cannula **130** of the attachment portion **104**. In certain embodiments, the drive unit and cartridge can be comprised of, for example, polypropylene, polycarbonate COC, or any other flexible and fatigue-resistant material. Although pump **102** may generally be controlled with a remote device such as, e.g., a smartphone, as described herein, pump **102** may also include a bolus key **140**, shown here presented on the drive unit **118**, for delivering a predetermined quantity of insulin with each push of the key **140**.

(13) As shown in FIG. **1D**, pump **102** is mated with the retention frame **106** by aligning the pump **102** with the retention frame **106** and pushing it downward onto the frame. Tabs **114** of frame include smaller inner wings **134** and larger outer wings **136**. When the pump **102** is pressed downwardly onto the frame **106**, the inner wings **134** snap into corresponding recesses **138** on the sides of the pump **102**, mechanically locking the pump **102** in place on the frame **106** so it will not inadvertently become dislodged. This snapping action may create an audible “clicking” sound to indicate to the user that the pump **102** is properly mated to the frame **106**. As shown, the recesses **138** may be on the drive unit **118**. Alternatively, the recesses **138** can be positioned on the cartridge **116**. In a further alternative, the recesses **138** can be partially on each of the drive unit **118** and cartridge **116**, thereby serving not only to retain the pump **102** on the retention frame **106**, but also to provide a further measure holding the two aspects of the pump **102** together. To remove the

pump **102** from the cartridge, the outer wings **136** can be pressed downwardly, which will cause the inner wings **134** to slide out from the recesses **138**, releasing the pump.

(14) FIGS. **2A-2F** depict a patch pump **200** according to another embodiment of the present invention. Patch pump **200** includes similar components to patch pump **100** of FIGS. **1A-1F**, and therefore, as with the further embodiments described herein, identical components and functions may not be further described with respect to this embodiment. In this embodiment, the retention frame **206** comprises a surface **207** sized to accommodate the pump **202** and a half clamshell retaining feature **209**. The retention frame **206** includes a sealing membrane **212** having a different configuration from sealing membrane **112** of FIGS. **1A-1F** and a removable needle **210** shaped to interface with the sealing membrane **212**. Note that when the pump **202** is mated with the retention frame **206**, the cartridge cannula **232** extends longitudinally into a cartridge opening **211** of the sealing membrane **212** that is different from and aligned perpendicularly to the needle opening **213** through which the needle is inserted.

(15) The pump **202** is attached to the retention frame **206** in this embodiment by a horizontal sliding motion, rather than a vertical motion as with pump **102** and retention frame **106** of the previous embodiment. Retention frame **206** includes a plurality of inwardly projecting tabs **214**. These tabs **214** mate with corresponding recesses **238** in the cartridge **216** and/or drive unit **218** of the pump **202** to retain the pump **202** on the retention frame **206**. Cartridge **216** can include an undercut portion **217** that slidably mates with the upper rim **205** of retention frame, which creates a smooth outer profile for the combination of the pump **202** and retention frame **206**. In other embodiments, the undercut portion **217** can extend onto a portion of drive unit **218** as well. Pump **202** is therefore retained on retention frame **206** primarily by a friction fit, so the pump **202** can be removed by a horizontal force in the opposite direction that overcomes this friction.

(16) Referring now to FIGS. **3A-3F**, there can be seen an insulin patch pump **300** according to another embodiment of the invention. In this embodiment, the sealing membrane **312** is positioned generally centrally on a generally flat retention frame **306**. After the insertion needle **310** is removed, a quarter-turn cleat **313** of the sealing membrane **312** is exposed. The pump **302** is mated to the quarter-turn cleat **313** of the sealing membrane **312** by a twisting motion in which the pump **302** is initially a quarter-turn offset from the retention frame **306**, as shown in FIG. **3D**, and is then turned to lock the pump **302** in alignment with the frame **306**, as shown in FIG. **3E**. A similar turn in the opposite direction would be used to detach the pump **302** from the frame **306**. Note that although described as a “quarter-turn” cleat, the degree of angular rotation required to lock and unlock the pump **302** from the retention frame can vary. In one embodiment, as depicted in FIG. **3F**, the cartridge **316** can include a cleat **317** for mating with the cleat **313** of the sealing membrane **312** and the drive unit **318** can include a corresponding recess **319** to accommodate the cleat **317** when the cartridge **316** and drive unit **318** are mated. Alternatively, the drive unit **318** can include the cleat and the cartridge **316** can define the recess. In a further embodiment, the cleats **313**, **317** could further include mating tabbed features that require downward pressure to engage and upward pressure to disengage during rotation of the pump **302**, to ensure that an accidental torque on the pump **302** does not dislodge the pump **302** from the frame **306**. The connection described in this embodiment utilizing the turnable cleat improves the reliability of the seal between the pump and the frame/infusion site by creating a wiping effect on the water ingress seal located on the cartridge/pump. This connection also preloads the cartridge to bias the cartridge against the pump such that any excessive compliance between the pump and the cartridge is eliminated. This increases the accuracy of the system because any compliance, looseness, or flexing in the connection between the cartridge and the drive unit can lead to delivery inaccuracy in such syringe/lead screw drive pumps.

(17) FIGS. **4A-4F** depict another embodiment of an insulin patch pump **400** according to an embodiment of the present invention. In this embodiment, the retention frame **406** is again generally flat and includes a rail **407** onto which the pump **402** is slidably inserted. The rail **407**

terminates at the sealing membrane **412** to properly align the pump **402** with the sealing membrane **412**. As can be seen in FIG. **4F**, both the cartridge **416** and the drive unit **418** can include slots **417**, **419** that mate with rail **407**. Rail **407** can include a leading section **409** that is narrower than the rest of rail **407** to enable the pump **402** to be more easily mated with the retention frame **406**. Because the slots **417**, **419** of the pump **402** can generally be of constant width, the slot **417** at the leading end of the cartridge **416** will be significantly wider than the leading section **409** of the rail, such that far less precision is needed to initially align the rail **407** with the slots **417**, **419**. As depicted, pump **402** is held onto retention frame **406** via friction and can be removed with a force applied in the opposite horizontal direction. In some embodiments, retention frame **406** can be provided with tabs that mate with recesses in pump **402**, similar to any of the previous embodiments.

(18) FIGS. **5A-5D** depict an insulin patch pump **500** according to an embodiment of the present invention in which the location of the infusion site is displaced from the location of the pump **502** and retention frame **506**. In this embodiment, a standard infusion set **550** is applied to the skin and the patch pump **500** is affixed nearby with adhesive patch **508**. A length of tubing **507** extends between the retention frame **506** and the infusion set **550** through which insulin is delivered from the pump **502** to the set **550**. In one embodiment, the tubing **507** is preattached to the retention frame **506**. In another embodiment, the tubing **507** is preattached to the cartridge **516** of the pump **502**. Such an embodiment would enable the pump **502**, when desired, to be used while not being connected to the retention frame **506**. In such an embodiment, the retention frame **506** and corresponding adhesive patch **508** could be considered optional. Patch pump **500** can provide the user with the flexibility of applying the infusion set **550** and the patch pump **500** in different locations on the skin or not affixing the patch pump **500** to the skin at all. Although this embodiment is depicted as including features for mating the pump **502** and the retention frame **506** similar to those of FIGS. **2A-2F**, it should be understood that the mating features of any of the embodiments described herein could be employed.

(19) Referring now to FIGS. **6A-6E**, an embodiment of an insulin patch pump **600** is depicted that is adapted to interface directly with a standard infusion set **650**. Initially, the infusion set **650** is applied to the patient's skin. The retention frame **606** of the patch pump **600** defines a receiving slot **607** that interfaces directly with the connector **652** of the infusion set **650** to deliver medicament through a cannula of the infusion set. The receiving slot **607** is therefore then mated with the connector **652** and the adhesive patch **608** of the patch pump **600** is affixed to the skin adjacent the infusion set **650**. The pump **602** can then be slid onto the retention frame **606** and mated with both the retention frame **606** and the infusion set connector **652**. Again, although this embodiment depicts the pump **602** mating with the frame **606** utilizing features similar to those depicted in FIGS. **2A-2F**, it should be understood that any of the mating features described herein could be used, though features that utilize a horizontal sliding action to mate the pump to the frame are advantageous in aligning the cartridge cannula with the infusion set **650**. In some embodiments, the retainer frame **606** can be identical to the retainer frame **506**, such that the same retainer frame can be used interchangeably either displaced from the infusion site or directly on the infusion site, whether with a standard infusion set or an infusion set as disclosed in previous embodiments. The retainer frames of any other embodiments disclosed herein could similarly be used in an interchangeable fashion between local and remote infusion sites.

(20) FIGS. **8A-8F** depict a patch pump **800** including a pump **802** and an attachment portion **804** according to another embodiment of the invention. Retention frame **806** of attachment portion **804** includes an insertion portion **812** through which a disposable needle can be inserted to penetrate a sealing membrane and insert a cannula for medicament delivery, as described previously herein. Drive unit **818** of pump includes a drive mechanism **822** that mates with a recess **824** in disposable cartridge **816** to attach the cartridge **816** to the drive unit **818** and provide for delivery of medicament such as insulin from the cartridge **816** to a user through the cannula.

(21) Retention frame **806** in this embodiment also includes a hook portion **814** adjacent one end of the frame and a snap portion **815** adjacent an opposing end of the frame. To mate the pump **802** with the corresponding attachment portion **804**, initially hook portion **814** on retention frame **806** is inserted, or hooked, into a recess **838** in the drive unit **818**, as shown in FIGS. **8C** and **8D**. To complete the insertion and mating process, the pump **802** is pivoted downwardly about the hook portion **814** to mate a recess **839** in cartridge **816** with snap portion **815**, as shown in FIGS. **8E** and **8F**. Snap portion **815** can be flexible and resilient such that when the cartridge **816** is mated with the snap portion **815**, the snap portion **815** is initially pushed away from the pump **802** and then snaps into place when aligned with the recess **839** to cause an audible clicking or snapping sound that provides an indication to the user that the pump **802** is properly mated to the attachment portion **806**. Pump **802** can be released from attachment portion **804** to, for example, enable a user to exchange the cartridge, with one or more tabs **836**, which can be depressed to cause one or both of hook portion **814** and snap portion **815** to withdraw from its corresponding recess in pump **802**.

(22) Although various embodiments of the insulin patch pumps described herein include a bolus key **140** for delivering a controlled amount of insulin to the user, in certain embodiments it is primarily intended that such patch pumps will be controlled with a remote device. Remote device can include, for example, a smartphone, an electronic tablet, a computer or a dedicated remote controller. In the case of a smartphone and/or an electronic tablet, a dedicated software application may be provided for control of patch pump. One embodiment of a screen shot of a control screen **700** for a patch pump is depicted in FIG. **7**. Control screen **700** can include various information and control functions. The control screen may include, for example, a battery life indicator **702**, an indicator **704** that indicates the amount of medicament such as, e.g., insulin remaining in the cartridge, a time and date **706** and an indicator **708** that indicates, in this example, an estimate of the amount of insulin remaining in the user's system as well as the amount of time it will take for that insulin to take effect on the user's blood glucose. One control function available from the control screen **700** is a bolus function **710**, the selection of which initiates a programmable bolus delivery with the corresponding patch pump. An options function **712** can allow entry into a menu of additional pump options. Various other information and functions that can be incorporated into and/or utilized by control device are disclosed in the various patents and patent applications incorporated by reference herein.

(23) The embodiments described herein generally include a cartridge and drive unit attached to each other in a generally back-to-back relation such that a body of the cartridge and a body of the drive unit are positioned adjacent to each other to each form all or a portion of the outer housing of the pump. It should be noted, however, that various other attachment configurations of the cartridge and housing are within the scope of the present invention. For example, a body of the cartridge and/or drive unit could be attached by being partially or wholly inserted into or partially or wholly contained within the corresponding component. In one specific embodiment, the cartridge can be wholly contained within the drive unit, and can be accessed through, e.g., a latched cover on the drive unit.

(24) Although the embodiments herein are specifically described with respect to the delivery of insulin, delivery of other medicaments, singly or in combination with one another or with insulin, including, for example, glucagon, pramlintide, etc., as well as other applications are also contemplated. Device and method embodiments discussed herein may be used for pain medication, chemotherapy, iron chelation, immunoglobulin treatment, dextrose or saline IV delivery, treatment of various conditions including, e.g., pulmonary hypertension, or any other suitable indication or application. Non-medical applications are also contemplated.

(25) With regard to the above detailed description, like reference numerals used therein may refer to like elements that may have the same or similar dimensions, materials, and configurations. While particular forms of embodiments have been illustrated and described, it will be apparent that various modifications can be made without departing from the spirit and scope of the embodiments

herein. Accordingly, it is not intended that the invention be limited by the foregoing detailed description.

(26) The entirety of each patent, patent application, publication, and document referenced herein is hereby incorporated by reference. Citation of the above patents, patent applications, publications and documents is not an admission that any of the foregoing is pertinent prior art, nor does it constitute any admission as to the contents or date of these documents.

(27) Also incorporated herein by reference in their entirety are commonly owned U.S. Pat. Nos. 8,287,495; 8,408,421 and 8,448,824; commonly owned U.S. Patent Publication Nos. 2009/0287180; 2010/0008795; 2010/0071446; 2010/0218586; 2012/0123230; 2013/0053816; 2013/0159456; and 2013/0306191 commonly owned U.S. patent application Ser. Nos. 14/583,274; 14/581,461; 14/581,398; 14/482,521; 14/479,994; 13/800,387; 13/800,453; 13/800,595; 13/801,230; 13/801,274; 13/827,383; 13/827,707; 13/828,958; 13/829,115; 13/832,531; 13/832,841; 13/837,661; 13/837,777; 13/838,084; 13/838,617; 13/841,028; 13/841,432; 13/842,005; 13/842,990; 13/923,556; and commonly owned U.S. Provisional Application Ser. Nos. 61/874,428, 61/875,979, 61/911,576, 61/920,902, 61/920,914, 61/920,923, 61/920,932 and 61/920,940.

(28) Further incorporated by reference herein in their entirety are U.S. Pat. Nos. 8,601,465; 8,502,662; 8,452,953; 8,451,230; 8,449,523; 8,444,595; 8,343,092; 8,285,328; 8,126,728; 8,117,481; 8,095,123; 7,999,674; 7,819,843; 7,782,192; 7,109,878; 6,997,920; 6,979,326; 6,936,029; 6,872,200; 6,813,519; 6,641,533; 6,554,798; 6,551,276; 6,295,506; and 5,665,065. Modifications may be made to the foregoing embodiments without departing from the basic aspects of the technology. Although the technology may have been described in substantial detail with reference to one or more specific embodiments, changes may be made to the embodiments specifically disclosed in this application, yet these modifications and improvements are within the scope and spirit of the technology. The technology illustratively described herein may suitably be practiced in the absence of any element(s) not specifically disclosed herein. The terms and expressions which have been employed are used as terms of description and not of limitation and use of such terms and expressions do not exclude any equivalents of the features shown and described or portions thereof and various modifications are possible within the scope of the technology claimed. Although the present technology has been specifically disclosed by representative embodiments and optional features, modification and variation of the concepts herein disclosed may be made, and such modifications and variations may be considered within the scope of this technology.

Claims

1. A user-wearable infusion pump system, comprising: a user-wearable infusion pump configured to contain a medicament, the user-wearable infusion pump including a button disposed on an outer perimeter of the user-wearable infusion pump configured to selectively cause the user-wearable infusion pump to initiate a medicament delivery operation when the button is pressed; a retention frame configured to selectively retain the user-wearable infusion pump therein, the retention frame including a frame base having a first side and an opposing second side and a first end and opposing second end defining a frame perimeter having a shape generally matching the outer perimeter of the user-wearable infusion pump, wherein the retention frame includes a retention wall extending upwardly from the frame base around an entirety of the frame perimeter to contact and limit horizontal movement of the user-wearable infusion pump relative to the retention frame; and a retention member extending inwardly from the frame perimeter, the retention member configured to interface with an upwardly facing surface of the user-wearable infusion pump to limit vertical movement of the user-wearable infusion pump relative to the retention frame, wherein the button is accessible when the user-wearable infusion pump is retained in the retention frame through an

opening disposed adjacent the frame perimeter.

2. The user-wearable infusion pump system of claim 1, wherein a distance between the first end and the second end of the frame base is greater than a distance between the first side and the second side of the frame base.
 3. The user-wearable infusion pump system of claim 2, wherein the button is accessible when the user-wearable infusion pump is retained in the retention frame at one of the first end or the second end of the frame base.
 4. The user-wearable infusion pump system of claim 2, wherein the retention member extends inwardly from at least one of the first side and the second side of the retention frame.
 5. The user-wearable infusion pump system of claim 1, wherein the retention member comprises an inwardly projecting tab.
 6. The user-wearable infusion pump system of claim 1, wherein the retention frame is configured to slidably receive the user-wearable infusion pump within the retention wall.
 7. The user-wearable infusion pump system of claim 1, further comprising tubing configured to extend between the user-wearable infusion pump and an infusion site displaced from a location of the retention frame.
 8. The user-wearable infusion pump system of claim 1, further comprising an adhesive patch configured to attach the retention frame to a body of a user.
 9. The user-wearable infusion pump system of claim 1, further comprising a remote control device configured to control operation of the user-wearable infusion pump.
 10. The user-wearable infusion pump system of claim 9, wherein the remote control device is a smartphone.
 11. The user-wearable infusion pump system of claim 9, wherein the remote control device is a dedicated remote controller.
 12. A retention frame for selectively retaining a user-wearable infusion pump, comprising: a frame base having a first side and an opposing second side and a first end and opposing second end defining a frame perimeter having a shape generally matching an outer perimeter of a user-wearable infusion pump to be retained therein; a retention wall extending upwardly from the frame base around an entirety of the frame perimeter to contact and limit horizontal movement of the user-wearable infusion pump relative to the retention frame; a retention member extending inwardly from the frame perimeter, the retention member configured to interface with an upwardly facing surface of the user-wearable infusion pump to limit vertical movement of the user-wearable infusion pump relative to the retention frame; and an opening disposed adjacent the frame perimeter configured to enable access to a button disposed on an outer perimeter of the user-wearable infusion pump when the user-wearable infusion pump is disposed on the frame base.
 13. The retention frame of claim 12, wherein a distance between the first end and the second end of the frame base is greater than a distance between the first side and the second side of the frame base.
 14. The retention frame of claim 13, wherein the button is accessible when the user-wearable infusion pump is retained in the retention frame at one of the first end or the second end of the frame base.
 15. The retention frame of claim 13, wherein the retention member extends inwardly from at least one of the first side and the second side of the retention frame.
 16. The retention frame of claim 12, wherein the retention member comprises an inwardly projecting tab.
-