

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415465
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kim; Untae

Door handle of a vehicle

Abstract

A door handle of a vehicle includes a handle housing installed on a door of the vehicle and on which an insertion groove is formed, a handle inner member inserted into the insertion groove of the handle housing and operable to protrude from the insertion groove, and a camera module installed on the handle inner member to be exposed when the handle inner member protrudes.

Inventors: Kim; Untae (Suwon-si, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Family ID: 1000008820802

Assignee: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Appl. No.: 18/196055

Filed: May 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240017679 A1	Jan. 18, 2024

Foreign Application Priority Data

KR	10-2022-0088025	Jul. 18, 2022
----	-----------------	---------------

Publication Classification

Int. Cl.: B60R11/04 (20060101); B60R11/00 (20060101); E05B85/10 (20140101); G02B27/00 (20060101); G03B17/56 (20210101)

U.S. Cl.:

CPC **B60R11/04** (20130101); **E05B85/107** (20130101); **G02B27/0006** (20130101);
G03B17/561 (20130101); B60R2011/004 (20130101)

Field of Classification Search

CPC: B60R (11/04); B60R (2011/004); E05B (85/107); G02B (27/0006); G03B (17/561)

USPC: 396/428

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9476231	12/2015	Park	N/A	E05B 81/20
10179571	12/2018	Matesic	N/A	G03B 17/08
11173839	12/2020	Wilson	N/A	H04N 7/18
11525292	12/2021	Jeong	N/A	N/A
2008/0072393	12/2007	Tanaka	15/250.03	A47L 1/02
2011/0170305	12/2010	Tanaka	16/412	E05B 17/10
2014/0223975	12/2013	Park	292/144	E05B 81/20
2016/0130845	12/2015	Park	292/336.3	E05B 77/06
2018/0272958	12/2017	Brouwer	N/A	G01S 7/027
2019/0329719	12/2018	Brouwer	N/A	B60S 1/56
2019/0329720	12/2018	Brouwer	N/A	H04N 23/51
2022/0154500	12/2021	Jeong	N/A	E05B 77/42
2024/0017679	12/2023	Kim	N/A	E05B 85/103

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
211313755	12/2019	CN	N/A
3437930	12/2018	EP	B60R 1/00
4882370	12/2011	JP	E05B 81/78
2012111390	12/2011	JP	N/A
2022533489	12/2021	JP	B60J 5/04
19980021354	12/1997	KR	E05B 1/00
100461412	12/2003	KR	N/A
20050106602	12/2004	KR	B60J 5/04
20080072393	12/2007	KR	G09G 3/20
101173839	12/2008	KR	G02B 5/02
20100021922	12/2009	KR	B60J 5/00
20110011932	12/2010	KR	N/A
101220593	12/2011	KR	B60J 5/04
20180102462	12/2017	KR	N/A
20210128327	12/2020	KR	N/A
20220154500	12/2021	KR	G06Q 50/04
WO-2021210713	12/2020	WO	E05B 77/42

Primary Examiner: Bloss; Stephanie E

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application claims the benefit of and priority to Korean Patent Application No. 10-2022-0088025, filed on Jul. 18, 2022, the entire contents of which are incorporated herein by reference.

FIELD

(2) The present disclosure relates to a door handle of a vehicle, and more particularly, to a door handle installed on the door of the vehicle and protruding from the door manually or automatically.

BACKGROUND

(3) The statements in this section merely provide background information related to the present disclosure and may not constitute prior art.

(4) Generally, a vehicle is provided with one or more doors for occupants to get in and out of the vehicle. Such doors include external door handle for opening and closing the doors from the outside and an internal door handle for opening and closing the doors from the inside.

(5) For example, an external door handle is installed on an outer panel of the door to protrude to the outside of the vehicle, and may have a shape that may be easily gripped by an occupant. However, as the external door handle protrudes to the outside of the vehicle, the external door handle has a disadvantage in that it hinders the appearance of the vehicle, causes noise due to air resistance when driving, and reduces driving performance.

(6) Accordingly, a flush door handle has recently been developed. Such a flush door handle is accommodated in an outer panel of the door while the vehicle is parking or driving, and the flush door handle pops out and protrudes from the outer panel of the door when the door is opened/closed. The flush door handle is equipped with a motor and may be operated automatically.

SUMMARY

(7) An embodiment of the present disclosure provides a door handle of a vehicle equipped with a camera capable of photographing surroundings of the vehicle. In particular, the camera is provided on a flush door handle of the vehicle.

(8) Additional embodiments of the disclosure are set forth in part in the description which follows and, in part, should be understood from the description, or may be learned by practice of the disclosure.

(9) In accordance with an embodiment of the present disclosure, a door handle of a vehicle includes a handle housing installed on a door of the vehicle and an insertion groove is formed in the handle housing. The door handle further includes a handle inner member inserted into the insertion groove of the handle housing and operable to protrude from the insertion groove, and a camera module installed on the handle inner member to be exposed to an outside of the handle housing when the handle inner member protrudes from the insertion groove.

(10) The camera module may be rotatably installed on the handle inner member.

(11) The door handle may further include a motor module operable to rotate the camera module.

(12) The motor module may further include a motor body, a link screw connected to the motor body and rotated by an operation of the motor body, and a screw bar. One end of the screw bar is connected to the camera module and the other end of the screw bar is connected to the link screw, and thus the screw bar may move according to a rotation of the link screw.

(13) A position at which the screw bar is coupled to the camera module may be disposed to be spaced apart from a rotation axis of the camera module by a predetermined distance.

- (14) A camera mounting groove to mount the camera module and a motor insertion groove to receive the motor module may be formed in the handle inner member.
 - (15) The handle inner member may have a predetermined length, and the camera module may be disposed on one end of the handle inner member.
 - (16) The handle inner member may be further configured to operate to be protruded from the insertion groove in response to a speed of the vehicle when exceeding a predetermined speed.
 - (17) The handle inner member may be further configured to protrude from the insertion groove or maintain in an inserted state according to a signal of a turn signal switch of the vehicle.
 - (18) The handle inner member may be further configured to protrude from the insertion groove or maintain in an inserted state according to a position of a shift lever of the vehicle.
 - (19) The door handle may further include a handle outer member coupled to the handle inner member in such a way that the camera module is not externally exposed thereto.
 - (20) The handle outer member may further include an outer body in which a groove is formed to cover the handle inner member and an outer rotation protrusion formed to protrude from an outer surface of the outer body and caught on the handle housing. In particular, the outer body is rotated around the outer rotation protrusion within the handle housing. In other words, the outer rotation protrusion functions as a rotation axis of the outer body.
 - (21) The handle inner member may operate to be protruded from the insertion groove as the outer body rotates within the handle housing.
 - (22) The door handle may further include a cleaner installed inside the handle housing and configured to clean a lens of the camera module.
 - (23) The camera module may be installed in the handle inner member so that the lens of the camera module is rotated in a state in which the lens of the camera module is in contact with the cleaner.
 - (24) The handle inner member may be further configured to be rotated and protruded from the handle housing so as to expose the camera module.
 - (25) The handle inner member may be further configured to be slid and protruded from the handle housing so as to expose the camera module.
 - (26) The handle inner member may further include a handle hole into which a hand of a user is inserted.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order that the disclosure may be well understood, there are now described various forms thereof, given by way of example, reference being made to the accompanying drawings, in which:
- (2) FIG. 1 is a view illustrating a state in which a door handle of a vehicle installed on a door of the vehicle according to an embodiment of the present disclosure;
- (3) FIG. 2 is a view illustrating a door handle of the vehicle according to an embodiment of the present disclosure;
- (4) FIG. 3 is a view illustrating a state in which a door handle of the vehicle pops out according to an embodiment of the present disclosure;
- (5) FIG. 4 is an exploded view illustrating a door handle of the vehicle according to an embodiment of the present disclosure;
- (6) FIG. 5 is a view illustrating a state in which a camera disposed on a door handle of the vehicle is rotated according to an embodiment of the present disclosure;
- (7) FIG. 6 is a view illustrating a state in which a camera of a door handle of the vehicle is installed according to an embodiment of the present disclosure;
- (8) FIG. 7 is a view illustrating a state in which a camera of a door handle of the vehicle is rotated according to an embodiment of the present disclosure;

- (9) FIGS. **8A** to **8C** are views illustrating an operation for cleaning a camera of a door handle of the vehicle according to an embodiment of the present disclosure;
- (10) FIG. **9** is a view illustrating a state in which a door handle of a vehicle according to another embodiment of the present disclosure is installed on a door of the vehicle;
- (11) FIG. **10** is a view illustrating a door handle of the vehicle according to another embodiment of the present disclosure;
- (12) FIG. **11** is a view illustrating a state in which a door handle of the vehicle according to another embodiment of the present disclosure pops out;
- (13) FIG. **12** is an exploded view illustrating a door handle of the vehicle according to another embodiment of the present disclosure;
- (14) FIG. **13** is an enlarged view of the area A of FIG. **11**;
- (15) FIG. **14** is a view illustrating a state in which a camera of a door handle of the vehicle according to another embodiment of the present disclosure is rotated; and
- (16) FIG. **15** is an enlarged view of the area B of FIG. **14**.

DETAILED DESCRIPTION

- (17) Reference is made below in detail to the embodiments of the disclosure, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout. This specification does not describe all elements of the disclosed embodiments and detailed descriptions of what is well known in the art or redundant descriptions on substantially the same configurations have been omitted. The terms ‘part’, ‘module’, ‘member’, ‘block’ and the like as used in the specification may be implemented in software or hardware. Further, a plurality of ‘part’, ‘module’, ‘member’, ‘block’ and the like may be embodied as one component. It is also possible that one ‘part’, ‘module’, ‘member’, ‘block’ and the like includes a plurality of components.
- (18) Throughout the specification, when an element is referred to as being “connected to” another element, it may be directly or indirectly connected to the other element and the “indirectly connected to” includes being connected to the other element via a wireless communication network.
- (19) Also, it is to be understood that the terms “include” and “have” are intended to indicate the existence of elements disclosed in the specification, and are not intended to preclude the possibility that one or more other elements may exist or may be added.
- (20) Throughout the specification, when a member is located “on” another member, this includes not only when one member is in contact with another member but also when another member is present between the two members.
- (21) The terms first, second, and the like are used to distinguish one component from another component, and the component is not limited by the terms described above.
- (22) An expression used in the singular encompasses the expression of the plural, unless it has a clearly different meaning in the context.
- (23) The reference numerals used in operations are used for descriptive convenience and are not intended to describe the order of operations and the operations may be performed in a different order unless otherwise stated.
- (24) When a component, device, element, or the like of the present disclosure is described as having a purpose or performing an operation, function, or the like, the component, device, or element should be considered herein as being “configured to” meet that purpose or to perform that operation or function.
- (25) Hereinafter, embodiments of the disclosure are described in detail with reference to the accompanying drawings.
- (26) FIGS. **1** to **8** illustrate a door handle **100** of a vehicle according to an embodiment of the present disclosure. The door handle **100** is installed on a door **200** of the vehicle and includes a handle housing **110**, a handle inner member **120**, a camera module **130**, a motor module **140**, a

handle outer member **150**, and a cleaner **160**.

(27) The handle housing **110** is inserted into the door **200** of the vehicle and coupled to the door **200**. In particular, the handle housing **110** is provided with an insertion groove **112** into which the handle inner member **120** and the handle outer member **150** may be inserted. In one embodiment, the handle housing **110** has a substantially rectangular parallelepiped shape, and the insertion groove **112** is formed on one surface of the handle housing **110**. When the handle housing **110** is inserted into the door **200** of the vehicle, the surface on which the insertion groove **112** is formed may be disposed to be exposed to an outer panel of the door **200**.

(28) The handle inner member **120** is inserted into the insertion groove **112** of the handle housing **110**, and the camera module **130** and the motor module **140** may be mounted on the handle inner member **120**. In one embodiment, the handle inner member **120** may include an inner body **122**, and a camera mounting groove **124** and a motor insertion groove **126** may be formed in the inner body **122**.

(29) The inner body **122** has a substantially rectangular parallelepiped shape and may be inserted into the insertion groove **112** of the handle housing **110**. The camera mounting groove **124** is formed at one end of the inner body **122**. Referring to FIG. 4, the camera mounting groove **124** may be open on three sides at the end of the inner body **122**. In one embodiment, the camera mounting groove **124** is formed by two plates disposed at one end of the inner body **122**. In other words, the camera mounting groove **124** is formed between the two plates which are spaced apart from each other. The camera module **130** may be installed rotatably at a predetermined angle in the camera mounting groove **124**.

(30) Furthermore, the motor insertion groove **126** is formed in the inner body **122**. The motor insertion groove **126** is formed on one surface of the inner body **122** and extends from the camera mounting groove **124**. The motor module **140** connected to the camera module **130** may be inserted into the motor insertion groove **126**.

(31) The camera module **130** may be coupled to the inner body **122** and may be rotated and operated by driving the motor module **140**. The camera module **130** may include a camera body **132** and a camera rotation protrusion **134**.

(32) The camera body **132** may be operated by a power supplied from the outside, and may be rotatably coupled to the camera mounting groove **124** of the inner body **122**. The camera body **132** may be operated all the time, but may be operated by receiving power when the handle inner member **120** protrudes from the handle housing **110**.

(33) In addition, a screw groove **136** may be formed in the camera body **132**. The screw groove **136** may be disposed at a rear part of the camera body **132** which is opposite to a front part at which lens of the camera body **132** is disposed. A screw bar **146** of the motor module **140** may be coupled to the screw groove **136**. The screw groove **136** may be disposed to be biased toward one side from the rear of the camera body **132**.

(34) The camera rotation protrusion **134** may have a shape protruding from the camera body **132** in both lateral directions. The camera rotation protrusion **134** may be disposed to be caught in the camera mounting groove **124** formed in the inner body **122** of the handle inner member **120**, and accordingly, the camera body **132** may be rotated in the camera mounting groove **124** by using the camera rotation protrusion **134** as a rotation axis.

(35) Herein, the camera rotation protrusion **134** may be disposed at a position spaced apart from a position where the screw groove **136** is formed by a predetermined distance.

(36) The motor module **140** may be operated by power supplied from the outside, and may allow the camera body **132** to be rotated. The motor module **140** may include a motor body **142** and a link screw **144**.

(37) The motor body **142** is operated by power supplied from the outside, and as the motor body **142** is operated, the link screw **144** may be rotated.

(38) The link screw **144** is rotated by the operation of the motor body **142**, and the screw bar **146**

that moves according to the rotation of the link screw **144** may be disposed therein. The screw bar **146** has a predetermined length, and one end thereof is rotatably coupled to the screw groove **136** formed in the camera body **132** and the other end thereof is coupled to the link screw **144**.

(39) Because a thread is formed at the other end of the screw bar **146**, as the link screw **144** is rotated, the screw bar **146** may be moved in a longitudinal direction by the rotation of the link screw **144**. Accordingly, as the screw bar **146** moves, a pushing or pulling force may be applied to the camera body **132**. Herein, the screw groove **136** formed in the camera body **132** is formed to be biased toward one rear side of the camera body **132**, and the positions of the camera rotation protrusion **134** and the screw groove **136** are spaced apart from each other, so that the camera body **132** may be rotated in a predetermined angle range with the camera rotation protrusion **134** as a rotation axis by a force generated when the screw bar **146** is moved in the longitudinal direction. In other words, the camera rotation protrusion **134**, which is the rotation axes of the camera body **132**, and the screw bar **146** are spaced apart, so that the camera body **132** may be rotated along the rotation axis.

(40) At this time, the rotation direction of the link screw **144** may change according to a current of the electric power supplied to the motor body **142**. For example, the screw bar **146** may be moved in one of both directions in the longitudinal direction according to the rotation direction of the link screw **144**.

(41) The handle outer member **150** is coupled to the handle inner member **120** to cover the handle inner member **120** so that the camera module **130** and the motor module **140** coupled to the handle inner member **120** are not exposed to the outside. The handle outer member **150** may include an outer body **152** and an outer rotation protrusion **154**.

(42) The outer body **152** has a groove into which the handle inner member **120** may be inserted, and may have a substantially rectangular parallelepiped shape. Even though the outer body **152** is coupled to the handle inner member **120**, the camera module **130** which is coupled to the handle inner member **120** may be exposed to outside.

(43) The outer rotation protrusion **154** may have a shape protruding from the outer body **152** in both lateral directions. The outer rotation protrusion **154** may be disposed to be caught in the handle housing **110**, and accordingly, the outer body **152** may be rotated in the handle housing **110** by using the outer rotation protrusion **154** as a rotation axis. In other words, the handle outer member **150** and the handle inner member **120** may be inserted into the insertion groove **112** formed in the handle housing **110** in a coupled state.

(44) In other words, as shown in FIGS. 2 and 3, the handle outer member **150** and the handle inner member **120** may be operated to be inserted or protruded from the handle housing **110** by rotating around the outer rotation protrusion **154** of the handle outer member **150** in a coupled state. Herein, the handle inner member **120** may be manually or electrically inserted or protruded from the handle housing **110**.

(45) In an embodiment, although not shown separately, a switch for electronically opening and closing the door **200** of the vehicle may be disposed on the inner handle. Alternatively, a switch configured for opening the door **200** of the vehicle when a user applies force to the inner handle in an outward direction while the handle outer member **150** protrudes from the handle housing **110** may be disposed on the handle housing **110**.

(46) The cleaner **160** may be disposed at one end of the insertion groove **112** of the handle housing **110**. The cleaner **160** is disposed to clean the lens of the camera body **132**, and a sponge or the like may be used to remove foreign substances attached to the lens of the camera body **132**.

(47) The cleaner **160** is disposed in the handle housing **110** so that the handle inner member **120** may be maintained in contact with the lens of the camera body **132** in a state in which the handle inner member **120** is inserted into the handle housing **110**. Accordingly, the lens of the camera body **132** may be cleaned while the handle inner member **120** operates to be inserted or protruded from the handle housing **110**.

(48) Alternatively, as shown in FIG. 8, in a state in which the handle inner member 120 is inserted into the handle housing 110, if a motor is driven manually or automatically, the camera body 132 is rotated. As the camera body 132 rotates, the lens of the camera body 132 may be cleaned while the position where the lens of the camera body 132 is in contact with the cleaner 160 is changed. More specifically, as shown in FIG. 8A, in a state in which the handle inner member 120 is inserted into the handle housing 110, as shown in FIG. 8B, when the motor is driven, the screw bar 146 may be moved in one direction to rotate the camera body 132. In addition, as shown in FIG. 8C, by driving the motor to rotate in the opposite direction, the screw bar 146 is moved in the other direction to rotate the camera body 132. As such, in a state in which the handle inner member 120 is inserted into the handle housing 110, by rotating the camera body 132, the lens of the camera body 132 may be cleaned by being in contact with the cleaner 160.

(49) The door handle 100 of the vehicle as described above may be respectively installed in the doors 200 on both sides of the vehicle, for example, may be installed in the door 200 on a driver seat side and the door 200 on a front passenger seat side, respectively. In addition, the camera module 130 may be disposed to photograph the rear side and rear left and right sides of the vehicle. Accordingly, when the driver drives the vehicle, the handle inner member 120 may protrude from the handle housing 110 according to the situation.

(50) The door handle 100 may pop out (the handle inner member 120 protrudes from the handle housing 110) or be retracted (the handle inner member 120 is inserted into the handle housing 110) based on a speed of the vehicle. For example, when the speed of the vehicle is 40 km/h or more, the door handle 100 may pop out.

(51) Furthermore, when the driver turns on a turn signal switch, the door handle 100 at the corresponding position may pop out and the other door handle 100 may remain closed. For example, when the driver turns on a left turn signal switch, the left door handle 100 (driver seat side) pops out, and when the driver turns on a right turn signal switch, the right door handle 100 (front passenger side) pops out.

(52) As described above, when the door handle 100 pops out, the camera module 130 is exposed through the pop-out of the door handle 100, so that an image captured by the camera module 130 may be displayed on a display installed inside the vehicle. The display installed inside the vehicle may be disposed on the left and right sides, respectively.

(53) In addition, the door handle 100 may pop out according to a transmission position of the vehicle. For example, when a shift lever (or the transmission) of the vehicle is located in reverse R, the door handle 100 may pop up, and when the shift lever of the vehicle is located in parking P, the door handle 100 may be retracted.

(54) Referring to FIGS. 9 to 15, the door handle 100 of the vehicle according to another embodiment of the present disclosure is described. The door handle 100 may include the handle housing 110, the handle inner member 120, the camera module 130, the motor module 140, the handle outer member 150, and the cleaner 160. While describing the door handle 100 of the vehicle according to another embodiment of the present disclosure, the same descriptions as in an embodiment have been omitted.

(55) The handle housing 110 has a substantially rectangular parallelepiped shape and is formed in the insertion groove 112 on one surface thereof. In this embodiment, the handle housing 110 may have a relatively larger size than in the above embodiment, for example, the depth of the insertion groove 112 may be formed deeper than in the above embodiment.

(56) The handle inner member 120 has a substantially rectangular shape and may include the inner body 122. The inner body 122 has a substantially rectangular shape, and as in the above embodiment, the camera mounting groove 124 and the motor insertion groove 126 are formed on one surface thereof, and a handle hole 128 may be formed in the middle thereof.

(57) In this embodiment, the size of the inner body 122 may be larger than in the above embodiment, and the handle hole 128 may be formed in the middle of the inner body 122 to have a

predetermined length and penetrate in the vertical direction. The handle hole **128** may have a length and width so that a user's hand may be inserted.

(58) The camera mounting groove **124** may be formed at one end of the inner body **122**, and may have a shape in which two surfaces of the inner body **122** are open. The camera module **130** may be installed in the camera mounting groove **124** to be rotated at a predetermined angle. In addition, the motor insertion groove **126** formed in the inner body **122** may be formed as in the above embodiment.

(59) The camera module **130** is rotatably coupled to the camera mounting groove **124** of the inner body **122**, and the camera module **130** in this embodiment is the same as in the above embodiment, so a detailed description has been omitted. However, the shape of the screw groove **136** formed in the camera body **132** of the camera module **130** may be modified as needed. For example, instead of the screw groove **136** being formed, a ring to which the screw bar **146** is coupled to the camera body **132** may be formed on the rear left and right sides of the camera body **132**.

(60) The motor module **140** is installed in the motor insertion groove **126** of the inner body **122**. In this embodiment, the motor module **140** is the same as in the above embodiment, and accordingly a detailed description thereof has been omitted.

(61) The handle outer member **150** is coupled to the handle inner member **120** to cover the handle inner member **120** so that the camera module **130** and the motor module **140** coupled to the handle inner member **120** are not exposed to the outside. In this embodiment, the handle outer member **150** may include the outer body **152**.

(62) The outer body **152** has a groove into which the handle inner member **120** may be inserted, and may have a substantially rectangular parallelepiped shape. In addition, a separate protrusion shape on the outer surface of the outer body **152** may be omitted.

(63) In this embodiment, in a state in which the handle outer member **150** and the handle inner member **120** are coupled, the handle inner member **120** may be inserted into or protruded from the handle housing **110**. In other words, the handle inner member **120** may slide and move in a depth direction of the insertion groove **112** in the handle housing **110** to be inserted into or protruded from the insertion groove **112**. Herein, when the handle inner member **120** protrudes from the handle housing **110**, the handle inner member **120** protrudes and moves from the handle housing **110** so that the handle hole **128** formed in the handle inner member **120** is completely exposed.

(64) The cleaner **160** is disposed at one end of the insertion groove **112** of the handle housing **110**, and may be disposed to clean the lens of the camera body **132**. The cleaner **160** is the same as in the above embodiment, so a detailed description thereof has been omitted. The process of cleaning the lens of the camera body **132** using the cleaner **160** may be operated in the same manner as in the above embodiment.

(65) As is apparent from the above, according to various embodiments of the present disclosure, the camera is mounted on the door handle of the vehicle and operates to be protruded while driving or parking, so that the driver may secure a field of view surroundings of the vehicle.

(66) Further, various embodiments of the present disclosure may replace a side mirror of the vehicle that identifies the rear of the vehicle, so wind noise generated by the side mirror on which the vehicle is traveling may be eliminated, and improve aerodynamics and fuel efficiency because the door handle does not protrude from the side of the vehicle.

(67) Further, according to various embodiments of the present disclosure, the lens of the camera may be cleaned when the door handle is accommodated in the outer panel of the door, so that foreign substances may be removed easily from the lens of the camera.

(68) Although embodiments of the disclosure have been shown and described, it would be appreciated by those having ordinary skill in the art that changes may be made in these embodiments without departing from the principles and spirit of the disclosure, the scope of which is defined in the claims and their equivalents.

Claims

1. A door handle of a vehicle, the door handle comprising: a handle housing installed on a door of the vehicle and including an insertion groove; a handle inner member inserted into the insertion groove of the handle housing and configured to protrude from the insertion groove, wherein the handle inner member includes an inner body including a camera mounting groove; a camera module installed on the handle inner member and configured to be exposed to an outside of the handle housing when the handle inner member protrudes from the insertion groove, wherein the camera module includes a camera body rotatably coupled to the camera mounting groove; and a motor module connected to the camera body, wherein when the inner body protrudes from the handle housing, the camera body rotates.
2. The door handle of claim 1, wherein the motor module is configured to rotate the camera module.
3. The door handle of claim 2, wherein the motor module comprises: a motor body; a link screw connected to the motor body and rotated by an operation of the motor body; and a screw bar having a first end connected to the camera module and a second end connected to the link screw, the screw bar configured to move according to a rotation of the link screw.
4. The door handle of claim 3, wherein a position at which the screw bar is coupled to the camera module is disposed to be spaced apart from a rotation axis of the camera module by a predetermined distance.
5. The door handle of claim 2, wherein a motor insertion groove to receive the motor module is formed in the handle inner member.
6. The door handle of claim 1, wherein the handle inner member has a predetermined length, and the camera module is disposed on one end of the handle inner member.
7. The door handle of claim 1, wherein the handle inner member is further configured to operate to be protruded from the insertion groove in response to a speed of the vehicle when exceeding a predetermined speed.
8. The door handle of claim 1, wherein the handle inner member is further configured to protrude from the insertion groove or maintain in an inserted state according to a signal of a turn signal switch of the vehicle.
9. The door handle of claim 1, wherein the handle inner member is further configured to protrude from the insertion groove or maintain in an inserted state according to a position of a shift lever of the vehicle.
10. The door handle of claim 1, further comprising a handle outer member coupled to the handle inner member such that the camera module is not externally exposed thereto.
11. The door handle of claim 10, wherein the handle outer member further comprises: an outer body in which a groove is formed to cover the handle inner member; and an outer rotation protrusion formed to protrude from an outer surface of the outer body and caught on the handle housing; wherein the outer body is configured to rotate about the outer rotation protrusion.
12. The door handle of claim 11, wherein the handle inner member is configured to operate to be protruded from the insertion groove as the outer body rotates within the handle housing.
13. The door handle of claim 1, further comprising a cleaner installed inside the handle housing and configured to clean a lens of the camera module.
14. The door handle of claim 13, wherein the camera module is installed in the handle inner member so that the lens of the camera module is rotated in a state in which the lens of the camera module is in contact with the cleaner.
15. The door handle of claim 1, wherein the handle inner member is further configured to be rotated and protruded from the handle housing so as to expose the camera module.
16. The door handle of claim 1, wherein the handle inner member is further configured to be slid

and protruded from the handle housing so as to expose the camera module.

17. The door handle of claim 16, wherein the handle inner member further includes a handle hole into which a hand of a user is inserted.
