

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276525

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

YAMADA; MOTOKI et al.

LIQUID EJECTING APPARATUS, CONTROL METHOD OF LIQUID EJECTING APPARATUS AND MEDIUM STORING CONTROL PROGRAM FOR LIQUID EJECTING APPARATUS

Abstract

A liquid ejecting apparatus includes: a liquid ejecting head having an ejection surface; a cap for covering the ejection surface; a suction pump; a cleaning liquid tank; and a switching valve having a fixed member, a rotation member, and a channel member. The fixed member has: a main body supporting the channel member; a cleaning liquid upstream port connected to the cleaning liquid tank; a cleaning liquid downstream port and a waste liquid port each connected to the cap; and an intake port connected to a tube in which the suction pump is disposed. The rotation member rotates with respect to the fixed member, and has a first cleaning liquid path. The channel member is attached to the rotation member and configured to rotate together with the rotation member with respect to the fixed member, and has: a second cleaning liquid path; and a waste liquid path.

Inventors: YAMADA; MOTOKI (Nagoya, JP), OKUWA; HIROYA (Tajimi, JP), WANG; RUI (Nagoya, JP), HIRANO; MIKIO (Okazaki, JP)

Applicant: BROTHER KOGYO KABUSHIKI KAISHA (Nagoya, JP)

Family ID: 96881742

Appl. No.: 19/058281

Filed: February 20, 2025

Foreign Application Priority Data

JP	2024-029877	Feb. 29, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: B41J2/165 (20060101); C09D11/30 (20140101)

Background/Summary

REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority from Japanese Patent Application No. 2024-029877 filed on Feb. 29, 2024. The entire content of the priority application is incorporated herein by reference.

BACKGROUND ART

[0002] Conventionally, a liquid ejecting apparatus including a liquid ejecting head and a maintenance unit is known. The liquid ejecting head has a nozzle which ejects ink, and an ejection surface in which the nozzle is open. The maintenance unit has a cap which covers the ejection surface, a suction pump which performs suction inside the cap, a waste liquid tank, and a switching valve.

SUMMARY

[0003] In the above-described liquid ejecting apparatus, the switching valve performs switching between communication and shutting-off among the cap, the suction pump, and the waste liquid tank, thereby performing a suction purge in which the suction pump performs the suction inside the cap covering the ejection surface. Since the ink is discharged from the nozzle by the suction purge, the ink might adhere, in some cases, to the ejection surface in which the nozzle is open. In a case where ink having a satisfactory fixing property is used and where the ink adheres to the ejection surface and dries, the ink which has adhered and dried might cause unsatisfactory ejection of the ink from the nozzle.

[0004] In view of the above-described situation, the present disclosure aims to provide a liquid ejecting apparatus, a control method of the liquid ejecting apparatus, and a medium storing a control program for the liquid ejecting apparatus each of which is capable of reducing the unsatisfactory ejection of the liquid from the nozzle caused by an adhered substance in the ejection surface.

[0005] A liquid ejecting apparatus according to the present disclosure includes: a liquid ejecting head having an ejection surface with nozzles opening therein; a cap configured to cover the ejection surface; a suction pump; a cleaning liquid tank configured to store cleaning liquid; and a switching valve having a fixed member, a rotation member, and a channel member. The fixed member has: a main body configured to support the channel member; a cleaning liquid upstream port being a hollow protrusion protruding from the main body and communicating with the cleaning liquid tank via a tube; a cleaning liquid downstream port and a waste liquid port each being a hollow protrusion protruding from the main body and communicating with the cap via a tube; and an intake port being a hollow protrusion shape protruding from the main body and communicating with a tube having the suction pump disposed therein. The rotation member is configured to rotate with respect to the fixed member, and has a first cleaning liquid path. The channel member is attached to the rotation member and configured to rotate together with the rotation member with respect to the fixed member. The channel member has: a second cleaning liquid path connected to the first cleaning liquid path to form a cleaning liquid path communicating the cleaning liquid upstream port and the cleaning liquid downstream port with each other; and a waste liquid path communicating the waste liquid port and the intake port with each other.

[0006] A control method according to the present disclosure is a control method of a liquid ejecting apparatus including: a liquid ejecting head having an ejection surface with nozzles opening therein;

a cap configured to cover the ejection surface; a suction pump; a cleaning liquid tank configured to store cleaning liquid; and a switching valve having a fixed member, a rotation member, and a channel member. The fixed member has: a main body configured to support the channel member; and ports including a cleaning liquid upstream port being a hollow protrusion protruding from the main body and communicating with the cleaning liquid tank via a tube, a cleaning liquid downstream port and a waste liquid port each being a hollow protrusion protruding from the main body and communicating with the cap via a tube, and an intake port being a hollow protrusion protruding from the main body and communicating with a tube having the suction pump disposed therein. The rotation member is configured to rotate with respect to the fixed member, and has a first cleaning liquid path. The channel member is attached to the rotation member and is configured to rotate together with the rotation member with respect to the fixed member. The channel member has: a second cleaning liquid path connected to the first cleaning liquid path to form a cleaning liquid path communicating the cleaning liquid upstream port and the cleaning liquid downstream port with each other; and a waste liquid path communicating the waste liquid port and the intake port with each other. The control method includes changing a communication state between the ports and the cleaning liquid path and between the ports and the waste liquid path by rotation of the rotation member.

[0007] A non-transitory medium according to the present disclosure is a non-transitory medium storing a control program for a liquid ejecting apparatus. The liquid ejecting apparatus includes: a liquid ejecting head having an ejection surface with nozzles opening therein; a cap configured to cover the ejection surface; a suction pump; a cleaning liquid tank configured to store cleaning liquid; a switching valve having a fixed member, a rotation member, and a channel member; and a controller. The fixed member has: a main body configured to support the channel member; and ports including: a cleaning liquid upstream port being a hollow protrusion protruding from the main body and communicating with the cleaning liquid tank via a tube; a cleaning liquid downstream port and a waste liquid port each being a hollow protrusion protruding from the main body and communicating with the cap via a tube; and an intake port being a hollow protrusion protruding from the main body and communicating with a tube having the suction pump disposed therein. The rotation member is configured to rotate with respect to the fixed member, and has a first cleaning liquid path, and the channel member is attached to the rotation member and is configured to rotate together with the rotation member with respect to the fixed member. The channel member has: a second cleaning liquid path connected to the first cleaning liquid path to form a cleaning liquid path communicating the cleaning liquid upstream port and the cleaning liquid downstream port with each other; and a waste liquid path communicating the waste liquid port and the intake port. The control program causes the controller to change a communication state between the ports and the cleaning liquid path and between the ports and the waste liquid path by rotation of the rotation member.

[0008] According to the present disclosure, the rotation member and the channel member are rotated with respect to the fixed member. As a result, the cleaning liquid path communicates with the cleaning liquid upstream port and the cleaning liquid downstream port, and the waste liquid path communicates with the waste liquid port and the intake port. In a case where the suction pump is driven in this state, the suction is performed inside the cap via the intake port, the waste liquid path, and the waste liquid port. Further, the cleaning liquid is sucked from the cleaning liquid tank via the cleaning liquid downstream port, the cleaning liquid path, and the cleaning liquid upstream port which communicate with the cap, and the cleaning liquid flows into the cap. The ejection surface covered by the cap is cleaned by the cleaning liquid, thereby removing the liquid adhered to the ejection surface. Therefore, the unsatisfactory ejection, of the liquid from the nozzle, which is caused due to the adhered substance in the ejection surface can be reduced.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0009] FIG. 1 is a schematic view of a liquid ejecting apparatus according to an embodiment of the present disclosure, as seen from above.

[0010] FIG. 2 is a block diagram depicting the configuration of the liquid ejecting apparatus.

[0011] FIG. 3 is a schematic view depicting a maintenance unit.

[0012] FIG. 4 is a perspective view depicting a switching valve in a partially cut state.

[0013] FIG. 5A is a schematic view depicting a switching valve in which a cleaning liquid path communicates a first cleaning liquid upstream port and a first cleaning liquid downstream port with each other, and FIG. 5B is a schematic view depicting the switching valve in which a waste liquid path communicates a first waste liquid port and an intake port with each other.

[0014] FIG. 6 is a cross-sectional view depicting the switching valve in which a rotation member is located at a standby position.

[0015] FIG. 7A is a cross-sectional view depicting the switching valve in which the rotation member is located at a first purge position, and FIG. 7B is a cross-sectional view depicting the switching valve in which the rotation member is located at a first cleaning position.

[0016] FIG. 8A is a cross-sectional view depicting the switching valve in which the rotation member is located at a first pressure-boosting position, and FIG. 8B is a cross-sectional view depicting the switching valve in which the rotation member is located at a first idle suction position.

[0017] FIG. 9A is a cross-sectional view depicting the switching valve in which the rotation member is located at a second purge position, and FIG. 9B is a cross-sectional view depicting the switching valve in which the rotation member is located at a second cleaning position.

[0018] FIG. 10A is a cross-sectional view depicting the switching valve in which the rotation member is located at a second pressure-boosting position, and FIG. 10B is a cross-sectional view depicting the switching valve in which the rotation member is located at a second idle suction position.

[0019] FIG. 11A is a cross-sectional view depicting the switching valve in which the rotation member is located at an exhaust-purge position, and FIG. 11B is a cross-sectional view depicting the switching valve in which the rotation member is located at an exhaust-idle suction position.

[0020] FIG. 12 is a flow chart indicating an example of a maintenance process in the liquid ejecting apparatus.

[0021] FIG. 13 is a flow chart indicating an example of a maintenance process in a liquid ejecting apparatus according to a first modification.

DESCRIPTION

(Liquid Ejecting Apparatus)

[0022] A liquid ejecting apparatus **10** according to an embodiment of the present disclosure is an apparatus configured to eject a liquid, as depicted in FIG. 1. In the following, a case where the liquid ejecting apparatus **10** is used in an inkjet printer which ejects an ink as the liquid will be described, but the liquid ejecting apparatus **10** is not limited to this.

[0023] The liquid ejecting apparatus **10** includes a liquid ejecting head **20** which ejects a liquid. The liquid ejecting head **20** includes a channel forming body **21** and a plurality of driving circuits **22** (FIG. 2). A plurality of nozzles is formed in the channel forming body **21**, and the plurality of nozzles includes a first nozzle **23a** and a second nozzle **23b**.

[0024] Each of the plurality of driving circuits **22** is a piezoelectric element, a heating element, an electrostatic actuator, etc., and is disposed to correspond to each of the first and second nozzles **23a** and **23b**, and applies pressure to the liquid in the liquid ejecting head **20** to thereby eject a droplet of the liquid (liquid droplet) from each of the first and second nozzles **23a** and **23b**. A pressure

wave generated as described above acts on the meniscus of the liquid formed in each of the first and second nozzles **23a** and **23b**, thereby causing the liquid to be ejected from each of the first and second nozzles **23a** and **23b**. The liquid ejecting head **20** will be described in detail later.

[0025] The liquid ejecting apparatus **10** further includes a platen **11**. The platen **11** is positioned below the liquid ejecting head **20** at a predetermined distance, and the upper surface of the platen **11** faces the lower surface of the channel forming body **21** of the liquid ejecting head **20** and supports a print medium A from below.

[0026] The liquid ejecting apparatus **10** further includes a cartridge **12** and a buffer tank **13** (FIG. 3). The cartridge **12** is detachably installed in a casing of the liquid ejecting apparatus **10**, and the cartridge **12** is included in the liquid ejecting apparatus **10** as cartridges **12** of which number is equal to the number of types of liquid ejected from the liquid ejecting head **20** (four in the example of FIG. 1). Each of the cartridges **12** store the liquid and supplies the liquid to a buffer tank **13** disposed on the liquid ejecting head **20**. The buffer tank **13** will be described in detail later.

[0027] The liquid ejecting apparatus **10** further includes a maintenance unit **30** which performs maintenance of the liquid ejecting head **20**. The maintenance unit **30** is disposed, for example, in the left-right direction, in a maintenance range to the right of a print range in which the platen **11** is disposed. The maintenance unit **30** will be described in detail later.

[0028] The liquid ejecting apparatus **10** further includes a movable device **14** which is configured to move the liquid ejecting head **20** in the left-right direction, and a conveyor **15** which is configured to convey the print medium A in the front-rear direction. The movable device **14** moves the liquid ejecting head **20** over the print range and the maintenance range. The conveyor **15** conveys the print medium A in the front-rear direction on the platen **11**.

[0029] As depicted in FIG. 2, the liquid ejecting apparatus **10** further includes a controller **40**. The controller **40** is electrically connected to a communication interface **43**, and the controller **40** is also electrically connected to the plurality of driving circuits **22** of the liquid ejecting head **20** via a head driving circuit **44**, to the movable device **14** via a movement driving circuit **45**, to the conveyor **15** via a conveyance driving circuit **46**, and to a displacement device **32**, a suction pump **36** and a rotation device **38** which are disposed in the maintenance unit **30**, via, respectively, a displacement driving circuit **47**, a pump driving circuit **48** and a rotation driving circuit **49**. The communication interface **43** is capable of communicating with an external device such as a computer, a portable terminal device, etc., and the communication interface **43** is configured to transmit and receive data between the communication interface **43** and the external device.

[0030] The controller **40** is constructed, for example, of a computer, and has an arithmetic part **41** and a memory **42**. The memory **42** is a memory accessible from the arithmetic part **41**, and includes, for example, a RAM, a ROM, etc. The memory **42** stores data input from the communication interface **43**, as well as a computer program and various data which are to be used for data processing by the arithmetic part **41**. The data includes image data, such as raster data, etc., which represent an object image of a printing process.

[0031] The arithmetic part **41** includes, for example, a processor such as a CPU, etc., an integrated circuit such as an ASIC, etc., or both; and the like. The arithmetic part **41** executes a computer program while referring to data stored in the memory **42**, and thus the controller **40** controls the operation of the respective parts of the liquid ejecting apparatus **10**. With this, the liquid ejecting apparatus **10** executes various processes such as a printing process of printing an image, and a maintenance process of the liquid ejecting head **20**, etc. These processes will be described later.

[0032] Further, the controller **40** may be constructed of a single device, or the controller **40** may be constructed of a plurality of devices distributed and configured to cooperate with each other to perform the operation of the controller **40**. For example, the liquid ejecting apparatus **10** may be constructed as an information processing part of a personal computer, a portable terminal device, etc., and as a liquid ejection executing part having the liquid ejecting head **20**. The information processing part and the liquid ejection executing part are constructed as separate bodies capable of

communicating with each other. In this case, the controller **40** may be constructed of a controller of the information processing part and a controller of the liquid ejection executing part. These controllers cooperate with each other to perform the operation of the controller **40** of the liquid ejecting apparatus **10**.

(Liquid Ejecting Head)

[0033] As depicted in FIG. **1** and FIG. **3**, the plurality of nozzles includes a plurality of first nozzles **23a** which eject a first liquid, and a plurality of second nozzles **23b** which eject a second liquid. For example, the first liquid may be a color ink, such as a cyan ink, a magenta ink, and a yellow ink. The second liquid may be a liquid different from the first liquid, such as a black ink. The first liquid and the second liquid will be described in detail later.

[0034] The first and second nozzles **23a** and **23b** are open in an ejection surface which is the lower surface of the channel forming body **21**. The ejection surface includes a first ejection surface **21a** in which the plurality of first nozzles **23a** are open, and a second ejection surface **21b** in which the plurality of second nozzles **23b** are open (see FIG. **3**). For example, the second ejection surface **21b** is disposed to the right of the first ejection surface **21a**.

[0035] In the first ejection surface **21a**, the plurality of first nozzles **23a** are aligned in the front-rear direction to form a first nozzle row, and a plurality of first nozzle rows including the first nozzle row are disposed side by side in the left-right direction. The plurality of first nozzle rows includes a row of first nozzles **23a** which eject the cyan ink, a row of first nozzles **23a** which eject the magenta ink, and a row of first nozzles **23a** which eject the yellow ink. In the second ejection surface **21b**, the plurality of second nozzles **23b** are aligned in the front-rear direction to form a second nozzle row, and the second nozzle row is disposed, for example, to the right of the plurality of first nozzle rows.

(First Liquid and Second Liquid)

[0036] Each of the first liquid and the second liquid is, for example, an ink such as a water-based ink, etc., and contains resin fine particles, a solid content of a colorant, an organic solvent, a surfactant, and water. In this case, the ink has wettability with respect to a hydrophobic recording medium such as a coated paper sheet, plastic, film, an OHP sheet, etc. The ink, however, is not limited to this, and may be an ink suitable for recording an image, for example, on a recording medium other than the hydrophobic recording medium, such as a regular paper sheet, a glossy paper sheet, a matte paper sheet, etc. The term “coated paper sheet” means, for example, high-quality printing paper sheet, medium-quality printing paper sheet, etc., which is plain paper sheet having pulp as a main constituent element thereof and having a coating agent applied thereon for a purpose of improving the smoothness, whiteness, glossiness, etc. Specifically, the coated paper sheet is exemplified by high-quality coated paper sheet, medium-quality coated paper sheet, etc.

[0037] As the resin fine particles, for example, resin fine particles including at least one of methacrylic acid and acrylic acid as a monomer can be used. For example, a commercially available product may be used as the resin fine particles. The resin fine particles may further include, as the monomer, styrene, vinyl chloride, etc. The resin fine particles may be, for example, resin fine particles included in an emulsion. The emulsion is composed, for example, of resin fine particles and a dispersion medium (for example, water, etc.). The resin fine particles are dispersed with respect to the dispersion medium with a specific range of a particle diameter, not being in a dissolved state. The resin fine particles are exemplified, for example, by fine particles of: a resin based on acrylic acid, a resin based on maleate ester, a resin based on vinyl acetate, a resin based on carbonate, a resin based on polycarbonate, a resin based on styrene, a resin based on ethylene, a resin based on polyethylene, a resin based on propylene, a resin based on polypropylene, a resin based on urethane, a resin based on polyurethane, a resin based on polyester, and a resin of copolymer of the above-described resins, etc.; the resin fine particles, however, are preferably fine particles of an acrylic resin.

[0038] As the resin fine particles, for example, a resin having a glass-transition temperature (T_g) in

a range of 0° C. to 200° C. inclusive is used. The glass transition temperature (Tg) is more preferably in a range of 20° C. to 180° C. inclusive, and further more preferably in a range of 30° C. to 150° C. inclusive.

[0039] As the emulsion, for example, a commercially available product may be used. The commercially available product is exemplified, for example, by “SUPERFLEX (“SUPERFLEX” is a registered trademark of DKS CO., LTD (DAI-ICHI KOGYO SEIYAKU CO., LTD)) 870” (Tg: 71° C.), “SUPERFLEX 150” (Tg: 40° C.) manufactured by DKS CO., LTD; “Mowinyl (“Mowinyl” is a registered trademark of Japan Coating Resin Co., Ltd.) 6760” (Tg: -28° C.) and “Mowinyl DM774” (Tg: 33° C.) manufactured by Japan Coating Resin Co., Ltd.; “Polysor (“Polysor” is a registered trademark of Resonac Holdings Corporation) AP-3270N” (Tg: 27° C.) manufactured by Resonac Holding Corporation; “HILOS-X (“HILOS-X” is a registered trademark of SEIKO PMC CORPORATION) KE-1062” (Tg: 112° C.), and “HILOS-X QE-1042” (Tg: 69° C.) manufactured by SEIKO PMC CORPORATION; etc.

[0040] The average particle diameter of the resin fine particles is, for example, in a range of 30 nm to 200 nm inclusive. The average particle diameter can be measured by, for example, by using a dynamic light scattering particle diameter distribution measuring apparatus “LB-550” (trade name) manufactured by HORIBA, Ltd., as an arithmetic average diameter.

[0041] A content amount (R) of the resin fine particles in the entire amount of the ink is, for example, preferably in a range of 0.1 wt % to 30 wt % inclusive, more preferably in a range of 0.5 wt % to 20 wt % inclusive, further more preferably in a range of 1.0 wt % to 15 wt % inclusive. As the resin fine particles, one kind of the resin fine particles may be used singly, or 2 (two) kinds or more of the resin fine particles may be used in combination.

[0042] The colorant is, for example, a pigment which is dispersible in water by, for example, a resin for dispersing pigment (resin dispersant). The colorant is exemplified, for example, by carbon black, an inorganic pigment, an organic pigment, etc. The carbon black is exemplified, for example, by furnace black, lamp black, acetylene black, channel black, etc. The inorganic pigment is exemplified, for example, by titanium oxide, inorganic pigments based on iron oxide, inorganic pigments based on carbon black, etc. The organic pigment is exemplified, for example, by azo-pigments such as azo lake, insoluble azo-pigment, condensed azo-pigment, chelate azo-pigment, etc.; polycyclic pigments such as phthalocyanine pigment, perylene and perinone pigments, anthraquinone pigment, quinacridone pigment, dioxadine pigment, thioindigo pigment, isoindolinone pigment, quinophthalone pigment etc.; dye lake pigments such as basic dye type lake pigment, acid dye type lake pigment, etc.; nitro pigment; nitroso pigment; aniline black daylight fluorescent pigment; and the like.

[0043] A solid content amount of the colorant (colorant solid component amount) in the entire amount of the ink is not particularly limited, and may be appropriately determined according to, for example, desired optical density or chromaticness, etc. The colorant solid component amount is, for example, preferably in a range of 0.1 wt % to 20.0 wt % inclusive, more preferably in a range of 1.0 wt % to 15.0 wt % inclusive. The colorant solid component amount is the weight only of the pigment, and does not include the weight of the resin fine particles. One kind of the colorant may be used singly, or two or more kinds of the colorant may be used in combination.

[0044] The organic solvent is not particularly limited, and any organic solvent is usable. The organic solvent is exemplified, for example, by: propylene glycol, ethylene glycol, 1,2-butanediol, propylene glycol monobutyl ether, dipropylene glycol monopropyl ether, triethylene glycol monobutyl ether, 1,2-hexanediol, 1,6-hexanediol, etc.; and glycol ether having a propylene oxide group is preferred. Examples of other organic solvent include, for example, alkylalcohols having a carbon number of 1 to 4 such as: methyl alcohol, ethyl alcohol, n-propyl alcohol, isopropyl alcohol, n-butyl alcohol, sec-butyl alcohol, tert-butyl alcohol, etc.; alkylene glycols in each of which an alkylene group includes 2 to 6 carbon atoms such as: ethylene glycol, propylene glycol, butylene glycol, triethylene glycol, 1,2,6-hexanetriol, thiodiglycol, hexylene glycol, diethylene glycol, etc.;

lower alkyl ethers of alkylene glycols such as: glycerin, ethylene glycol monomethyl (or ethyl, propyl, butyl) ether, diethylene glycol monomethyl (or ethyl, propyl, butyl) ether, triethylene glycol monomethyl (or ethyl, propyl, butyl, hexyl) ether, tetraethylene glycol monomethyl (or ethyl, propyl, butyl, hexyl) ether, propylene glycol monomethyl (or ethyl, propyl, butyl) ether, dipropylene glycol monomethyl (or ethyl, propyl, butyl) ether, tripropylene glycol monomethyl (or ethyl, propyl, butyl) ether, tetra propylene glycol monomethyl (or ethyl) ether; N-methyl-2-pyrrolidone; 2-pyrrolidone; 1,3-dimethyl 2-imidazolidinone; etc.

[0045] A content amount of the organic solvent in the entire amount of the ink is preferred that an organic solvent which exists, as a simple substance, as a liquid at 25° C. is preferably 50 wt % or less, more preferably 40 wt % or less, with respect to the entire amount of the ink. The water is preferably ion-exchange water or purified water (pure water). A content amount of the water with respect to the entire amount of the ink is, for example, preferably within a range of 15 wt % to 95 wt % inclusive, more preferably within a range of 25 wt % to 85 wt % inclusive. The content amount of the water may be, for example, a balance of the other components.

[0046] The ink may further include a conventionally known additive, as necessary. The additive is exemplified, for example, by surfactants, pH-adjusting agents, viscosity-adjusting agents, surface tension-adjusting agents, antiseptics, fungicides, leveling agents, antifoaming agents, light stabilizing agents, antioxidants, drying preventive agents for nozzle, polymer components such as emulsion, dye, etc. The surfactants may further include cationic surfactants, anionic surfactants or nonionic surfactants. A commercially available product may be used as these surfactants, which is exemplified, by: “OLFIN (“OLFIN” is a registered trademark of Nissin Chemical Industry Co., Ltd.) E1010”, “OLFIN E1006”, and “OLFIN E1004”, “SILFACE (“SILFACE” is a registered trademark of Nissin Chemical Industry Co., Ltd.) SAG503A”, “SILFACE SAG002” manufactured by Nissin Chemical Industry Co., Ltd. The content amount of the surfactant in the entire amount of the ink is, for example, 5 wt % or less, 3 wt % or less, and in a range of 0.1 wt % to 2 wt % inclusive. The viscosity-adjusting agents are exemplified, for example, by polyvinyl alcohol, cellulose, water-soluble resin, etc.

[0047] The ink can be prepared, for example, by uniformly mixing the resin fine particles, the colorant, the organic solvent, the water, and an optionally other additive(s) as necessary, by a conventionally known method, and then removing any non-dissolved matter with a filter, etc. (Buffer Tank)

[0048] The buffer tank **13** is provided as buffer tanks **13** each of which is connected to a corresponding cartridge **12** among the cartridges **12** (FIG. **1**) by a tube, etc., and the liquid is supplied to each of the buffer tanks **13** from one of the cartridges **12**. Further, each of the buffer tanks **13** is disposed on the liquid ejecting head **20** and communicates with the first nozzles **23a** or the second nozzles **23b** by a liquid channel. A filter **13a** is disposed in the liquid channel. The liquid passes through the filter **13a**, flows through the liquid channel, and is supplied to the first nozzle **23a** or the second nozzle **23b**. In a case where the liquid passes through the filter **13a**, an air bubble contained in the liquid is separated and retained in an upper portion of each of the buffer tanks **13**. (Maintenance Unit)

[0049] The maintenance unit **30** includes a cap which is configured to cover the ejection surface of the liquid ejecting head **20**. The cap includes a first cap **31a** configured to cover the first ejection surface **21a**, and a second cap **31b** configured to cover the second ejection surface **21b**. The first cap **31a** and the second cap **31b** are each made of an elastic material such as silicon rubber, etc., and are integrally formed. Each of the first cap **31a** and the second cap **31b** has a shape of a box of which upper portion is open, includes a through hole, and is connected to a tube **39** via the through hole.

[0050] Further, the maintenance unit **30** includes a displacement device **32** (FIG. **2**) configured to displace the caps **31a**, **31b**. The displacement device **32** displaces each of the caps **31a**, **31b** between a contact position and a separate position. Accordingly, each of the caps **31a**, **31b** changes

the state thereof between a capping state and an uncapping state.

[0051] That is, in the capping state, the first cap **31a** makes contact with the first ejection surface **21a** at the contact position to cover the first nozzles **23a** which are open in the first ejection surface **21a**. In the capping state, the second cap **31b** makes contact with the second ejection surface **21b** at the contact position to cover the second nozzles **23b** which are open in the second ejection surface **21b**. This reduces drying of the first liquid from the first nozzles **23a** and drying of the second liquid from the second nozzles **23b**. On the other hand, in the uncapping state, the first cap **31a** is away from the first ejection surface **21a** at the separate position to expose the first ejection surface **21a**. In the uncapping state, the second cap **31b** is away from the second ejection surface **21b** at the separate position to expose the second ejection surface **21b**.

[0052] Furthermore, the maintenance unit **30** has an exhaust path **33a**, an exhaust body **33b**, and an exhaust cap **33c**. The exhaust path **33a** is connected to the upper portion of each of the buffer tanks **13**, and is open in an exhaust surface **33b1**, which is the lower surface of the exhaust body **33b**. Air bubbles accumulated in the upper portion of each of the buffer tanks **13** pass through the exhaust path **33a** and are exhausted from each of the buffer tanks **13**. The exhaust cap **33c** is made of an elastic material such as silicon rubber, has a shape of a box of which upper portion is open, and has a through hole via which the exhaust cap **33c** is connected to the tube **39**.

[0053] The exhaust cap **33c** is configured to be displaceable between a contact position and a separate position by the displacement device **32**. Accordingly, the exhaust cap **33c** changes the state thereof between a capping state and an uncapping state. In the capping state, the exhaust cap **33c** makes contact with the exhaust surface **33b1** at the contact position and covers the opening of the exhaust path **33a**. On the other hand, in the separate position, the exhaust cap **33c** is away from the exhaust surface **33b1** and the opening of the exhaust path **33a** is exposed to the outside.

[0054] Further, the maintenance unit **30** includes a cleaning liquid tank **34** configured to store a cleaning liquid, a waste liquid tank **35** configured to store waste liquid, and a suction pump **36**. The cleaning liquid tank **34** stores the cleaning liquid and supplies the cleaning liquid to the caps **31a** and **31b**. The cleaning liquid is a liquid which can clean (dilute) the first liquid and the second liquid, does not contain a solid component, and contains, for example, an organic solvent, a surfactant, and a water-soluble solvent including water, etc. In other words, the cleaning liquid may be a liquid obtained by removing the resin fine particles and the colorant from the first liquid and the second liquid. The waste liquid tank **35** has a space configured to store the waste liquid which is the liquid exhausted from the first and second nozzles **23a** and **23b** and the caps **31a** and **31b**, and the space is open to the atmosphere.

[0055] The suction pump **36** is, for example, a tube pump, and is disposed in a tube **39** (tube **39a**) which is connected to a switching valve **37** and the waste liquid tank **35**. The suction pump **36** performs suction from the switching valve **37** to the waste liquid tank **35** in a case where a roller rotates while being pressed against the tube **39a**. In a state that the roller is not pressed against the tube **39a**, the suction pump **36** is in an atmospheric open state in which the tube **39a** is open to the atmosphere via the waste liquid tank **35**.

[0056] The maintenance unit **30** further includes the switching valve **37** and the rotation device **38** (FIG. 2). The switching valve **37** has a fixed member **50** (FIG. 4) and a rotation member **60** (FIG. 4), and is configured to communicate with each of the first cap **31a**, the second cap **31b**, the exhaust cap **33c**, the suction pump **36**, the cleaning liquid tank **34**, and the waste liquid tank **35** by one of the tubes **39**. The rotation device **38** rotates the rotation member **60** with respect to the fixed member **50**, to thereby change a communication state among the first cap **31a**, the second cap **31b**, the exhaust cap **33c**, the suction pump **36**, the cleaning liquid tank **34**, and the waste liquid tank **35**. (Switching Valve)

[0057] As depicted in FIG. 4, the switching valve **37** has the fixed member **50**, the rotation member **60**, and a channel member **70**. The rotation member **60** is made, for example, of resin, and has a gear part **61** and a path part **62**. The gear part **61** has a shape of a disc, and is connected to the

rotation device **38** (FIG. 2). The rotation device **38** is driven to cause the rotation member **60** to rotate with respect to the fixed member **50**. The central axis of the rotation member **60** and the central axis of the fixed member **50** coincide with each other, and the rotation member **60** rotates around the central axis.

[0058] The path part **62** has a columnar shape, has a central axis which coincides with the central axis of the gear part **61**, and protrudes downward from the gear part **61**. The path part **62** has a first cleaning liquid path **64**. The first cleaning liquid path **64** extends linearly along the radial direction of the path part **62**, penetrates the path part **62**, and is open in the outer circumferential surface of the path part **62**. Further, the path part **62** includes a plurality of protruding parts **65** protruding from the outer circumferential surface. Each of the plurality of protruding parts **65** extends in a direction parallel to the central axis of the path part **62**, for example, in the up-down direction.

[0059] The channel member **70** is made of an elastic material such as rubber and has a second main body **71**. The second main body **71** includes a second side wall **71a** and a second bottom wall **71b**. The second side wall **71a** has a cylindrical shape, and the path part **62** is inserted inside the second side wall **71a**. The central axis of the second side wall **71a** coincides with the central axis of the path part **62**, and the inner circumferential surface of the second side wall **71a** contacts the outer circumferential surface of the path part **62** in a watertight manner.

[0060] Further, recessed parts **73** are defined in the outer circumferential surface of the second side wall **71a**. Each of the recessed parts **73** extends in a direction parallel to the central axis of the second side wall **71a**, for example, along the up-down direction. Each of the plurality of protruding parts **65** of the path part **62** is fitted into one of the recessed parts **73**, of the second side wall **71a**, corresponding thereto, and thus the channel member **70** is attached to the rotation member **60**. The channel member **70** rotates together with the rotation member **60** with respect to the fixed member **50** by engaging with the path part **62** in the circumferential direction around the central axis.

[0061] Furthermore, two second cleaning liquid paths **74** are defined in the second side wall **71a**. Each of the two second cleaning liquid paths **74** extends along the radial direction of the second side wall **71a** and penetrates the second side wall **71a**. As depicted in FIG. 5A and FIG. 6, the first cleaning liquid path **64** is located between the two second cleaning liquid paths **74**, and these paths (the two second cleaning liquid paths and the first cleaning liquid path **64**) extend along the same straight line. In the radial direction of the channel member **70**, an opening of each of the two second cleaning liquid paths **74** and one of the openings of the first cleaning liquid path **64** face each other, and the two second cleaning liquid paths **74** are connected to the first cleaning liquid path **64**. With this, the first cleaning liquid path **64** and the two second cleaning liquid paths **74** form a cleaning liquid path **75**. The cleaning liquid path **75** extends linearly along the radial direction of the channel member **70** and is open in the outer circumferential surface of the channel member **70**.

[0062] As depicted in FIG. 5B and FIG. 6, a plurality of grooves are defined in the outer circumferential surface of the second side wall **71a** and the lower surface of the second bottom wall **71b**. The plurality of grooves define a plurality of waste liquid paths, for example, a first waste liquid path **76a**, a second waste liquid path **76b**, a third waste liquid path **76c**, and a fourth waste liquid path **76d**. These first to fourth waste liquid paths **76a** to **76d** extend from the center of the lower surface of the second bottom wall **71b** to the outer circumferential surface of the second side wall **71a**, along the radial direction of the lower surface of the second bottom wall **71b**, and further extend upward from the lower surface of the second bottom wall **71b** at the outer circumferential surface of the second side wall **71a**.

[0063] As a result, the first to fourth waste liquid paths **76a** to **76d** overlap and communicate with one another at the center of the lower surface of the channel member **70**. Further, the first to fourth waste liquid paths **76a** to **76d** are located so as to be shifted from one another in the circumferential direction of the central axis of the channel member **70** on the outer circumferential surface of the second bottom wall **71b**. Furthermore, the first to fourth waste liquid paths **76a** to **76d** are located

below the cleaning liquid path 75 in the up-down direction, and therefore do not communicate with the cleaning liquid path 75.

[0064] As depicted in FIG. 4, the fixing member 50 has a first main body 51 which supports the channel member 70. The first main body 51 is made, for example, of resin, and has a first side wall 51a and a first bottom wall 51b. The first side wall 51a has a cylindrical shape; the first bottom wall 51b has a circular shape, and covers a lower opening of the first side wall 51a.

[0065] The channel member 70 is accommodated inside the first side wall 51a, and the central axis of the first side wall 51a coincides with the central axis of the channel member 70. The inner circumferential surface of the first side wall 51a contacts the outer circumferential surface of the second side wall 71a in a watertight manner so that the channel member 70 is rotatable with respect to the first side wall 51a. Further, the upper surface of the first bottom wall 51b contacts the lower surface of the second bottom wall 71b in a watertight manner. As a result, the first to fourth waste liquid paths 76a to 76d defined in the outer circumferential surface of the second side wall 71a and the lower surface of the second bottom wall 71b of the channel member 70 are covered by the inner circumferential surface of the first side wall 51a and the upper surface of the first bottom wall 51b of the fixed member 50.

[0066] Further, the fixed member 50 has a cleaning liquid upstream port. As depicted in FIG. 6, the cleaning liquid upstream port includes a first cleaning liquid upstream port 52a and a second cleaning liquid upstream port 52b. Each of the first and second cleaning liquid upstream ports 52a and 52b has a tubular shape, penetrates the first side wall 51a of the main body, and is open in the inner circumferential surface of the first side wall 51a. The first cleaning liquid upstream port 52a and the second cleaning liquid upstream port 52b are disposed at the same height in the up-down direction, and the opening of the first cleaning liquid upstream port 52a and the opening of the second cleaning liquid upstream port 52b face each other in the radial direction of the first side wall 51a.

[0067] Each of the first and second cleaning liquid upstream ports 52a and 52b is a hollow protrusion protruding from the outer circumferential surface of the first side wall 51a. Each of the first and second cleaning liquid upstream ports 52a and 52b is connected to one end of a tube 39, and the other end of the tube 39 is connected to the cleaning liquid tank 34. As a result, each of the first and second cleaning liquid upstream ports 52a and 52b communicates with the cleaning liquid tank 34 via the tube 39.

[0068] Furthermore, the fixed member 50 has a cleaning liquid downstream port. As depicted in FIG. 4 and FIG. 6, the cleaning liquid downstream port includes a first cleaning liquid downstream port 53a and a second cleaning liquid downstream port 53b. Each of the first and second cleaning liquid downstream ports 53a and 53b has a tubular shape, penetrates the first side wall 51a of the main body, and is open in the inner circumferential surface of the first side wall 51a. The first cleaning liquid downstream port 53a and the second cleaning liquid downstream port 53b are disposed at the same height in the up-down direction, and the opening of the first cleaning liquid downstream port 53a and the opening of the second cleaning liquid downstream port 53b face each other in the radial direction of the first side wall 51a.

[0069] Each of the first and second cleaning liquid downstream ports 53a and 53b is a hollow protrusion protruding from the outer circumferential surface of the first side wall 51a. The first cleaning liquid downstream port 53a is connected to one end of a tube 39, and the other end of this tube 39 is connected to the first cap 31a. As a result, the first cleaning liquid downstream port 53a communicates with the first cap 31a via the tube 39. Further, the second cleaning liquid downstream port 53b is connected to one end of a tube 39, and the other end of this tube 39 is connected to the second cap 31b. As a result, the second cleaning liquid downstream port 53b communicates with the second cap 31b via the tube 39.

[0070] The first and second cleaning liquid upstream ports 52a and 52b and the first and second cleaning liquid downstream ports 53a and 53b are disposed at the same height in the up-down

direction as the cleaning liquid path 75 of the rotation member 60 and the channel member 70. The rotation member 60 and the channel member 70 rotate with respect to the fixed member 50, thereby changing a communication state between the cleaning liquid path 75 and each of the first and second cleaning liquid upstream ports 52a and 52b and the first and second cleaning liquid downstream ports 53a and 53b.

[0071] That is, as depicted in FIGS. 5A and 7B, the cleaning liquid path 75 is aligned on the same straight line with the first cleaning liquid upstream port 52a and the first cleaning liquid downstream port 53a. Further, in the radial direction of the channel member 70, the openings of the cleaning liquid path 75 face, respectively, the opening of the first cleaning liquid upstream port 52a and the opening of the first cleaning liquid downstream port 53a. As a result, the cleaning liquid path 75 communicates with the first cleaning liquid upstream port 52a and the first cleaning liquid downstream port 53a. In this case, the cleaning liquid path 75 does not communicate with the second cleaning liquid upstream port 52b and the second cleaning liquid downstream port 53b.

[0072] Further, as depicted in FIG. 5A and FIG. 9B, the cleaning liquid path 75 is aligned on the same straight line with the second cleaning liquid upstream port 52b and the second cleaning liquid downstream port 53b. Further, in the radial direction of the channel member 70, the openings of the cleaning liquid path 75 face, respectively, the opening of the second cleaning liquid upstream port 52b and the opening of the second cleaning liquid downstream port 53b. As a result, the cleaning liquid path 75 communicates with the second cleaning liquid upstream port 52b and the second cleaning liquid downstream port 53b. In this case, the cleaning liquid path 75 does not communicate with the first cleaning liquid upstream port 52a and the first cleaning liquid downstream port 53a.

[0073] Furthermore, as depicted in FIG. 4, FIG. 5B, and FIG. 6, the fixed member 50 has the intake port 54. The intake port 54 has a substantially tubular shape and penetrates the center of the first bottom wall 51b in the up-down direction. At the center of the second bottom wall 71b which faces the center of the first bottom wall 51b, the intake port 54 is connected to the first to fourth waste liquid paths 76a to 76d defined in the lower surface of the second bottom wall 71b.

[0074] Moreover, the intake port 54 is a hollow protrusion protruding from the lower surface of the first bottom wall 51b of the main body. The intake port 54 extends from the center of the first bottom wall 51b along the radial direction of the first bottom wall 51b beyond the outer circumferential surface of the first side wall 51a. The intake port 54 is connected to one end of a tube 39, and the other end of the tube 39 is connected to the waste liquid tank 35. As a result, the intake port 54 communicates with the waste liquid tank 35 by the tube 39. The suction pump 36 is disposed in the tube 39a located between the intake port 54 and the waste liquid tank 35.

[0075] Further, the fixed member 50 has a waste liquid port. The waste liquid port includes a first waste liquid port 55a and a second waste liquid port 55b. Each of the first and second waste liquid ports 55a and 55b has a tubular shape, penetrates the first side wall 51a, and is open in the inner circumferential surface of the first side wall 51a.

[0076] The first waste liquid port 55a is a hollow protrusion protruding from the outer circumferential surface of the first side wall 51a, and is connected to one end of a tube 39. The other end of the tube 39 is connected to the first cap 31a, thereby causing the first waste liquid port 55a to communicate with the first cap 31a via the tube 39. The second waste liquid port 55b is a hollow protrusion protruding from the outer circumferential surface of the first side wall 51a, and is connected to one end of a tube 39. The other end of the tube 39 is connected to the second cap 31b, thereby causing the second waste liquid port 55b to communicate with the second cap 31b via the tube 39.

[0077] Furthermore, the fixed member 50 has an exhaust port 57. The exhaust port 57 has a tubular shape, penetrates the first side wall 51a of the main body, and is open in the inner circumferential surface of the first side wall 51a. The exhaust port 57 is a hollow protrusion protruding from the outer circumferential surface of the first side wall 51a, and is connected to one end of a tube 39.

The other end of the tube **39** is connected to the exhaust cap **33c**, thereby causing the exhaust port **57** to communicate with the exhaust cap **33c** via the tube **39**.

[0078] Moreover, the fixed member **50** has an atmosphere port **56**. The atmosphere port **56** has a tubular shape, penetrates the first side wall **51a** of the main body, and is open in the inner circumferential surface of the first side wall **51a**. The atmosphere port **56** is a hollow protrusion protruding from the outer circumferential surface of the first side wall **51a**, and is connected to one end of a tube **39**. This tube **39** is connected to the waste liquid tank **35** which is open to the atmosphere. In a case where the intake port **54** disposed in this tube **39** is in an atmospheric open state, the atmosphere port **56** is open to the atmosphere via the tube **39** and the waste liquid tank **35**.

[0079] The first and second waste liquid ports **55a** and **55b**, the exhaust port **57**, and the atmosphere port **56** are disposed below the first and second cleaning liquid upstream ports **52a** and **52b** and the first and second cleaning liquid downstream ports **53a** and **53b** in the up-down direction. These ports **55a** to **57** are open in the inner circumferential surface of the first side wall **51a** at mutually different positions in the circumferential direction of the first side wall **51a**.

Further, the first to fourth waste liquid paths **76a** to **76d** of the channel member **70** are open in the outer circumferential surface of the second side wall **71a** at mutually different positions in the circumferential direction of the second side wall **71a**.

[0080] The rotation member **60** and the channel member **70** rotate with respect to the fixed member **50** in a state that the inner circumferential surface of the first side wall **51a** and the outer circumferential surface of the second side wall **71a** face each other. This changes a communication state between the ports **55a** to **57** and the first to fourth waste liquid paths **76a** to **76d**. Note that the communication state between one opening of each of the first to fourth waste liquid paths **76a** to **76d** and the ports **55a** to **57** changes in accordance with the rotation of the rotation member **60**, whereas the other opening of each of the first to fourth waste liquid paths **76a** to **76d** is connected to the intake port **54** regardless of the rotation of the rotation member **60**.

[0081] That is, as depicted in FIG. 5B, FIG. 7A, and FIG. 7B, the opening of the second waste liquid path **76b** faces the opening of the first waste liquid port **55a** in the radial direction of the channel member **70**. As a result, the second waste liquid path **76b** communicates with the first waste liquid port **55a**. Therefore, the first cap **31a** communicates with the waste liquid tank **35** via the tube **39**, the first waste liquid port **55a**, the second waste liquid path **76b**, and the intake port **54**.

[0082] Further, as depicted in FIG. 5B, FIG. 9A, and FIG. 9B, the opening of the third waste liquid path **76c** faces the opening of the second waste liquid port **55b** in the radial direction of the channel member **70**. As a result, the third waste liquid path **76c** communicates with the second waste liquid port **55b**. Therefore, the second cap **31b** communicates with the waste liquid tank **35** via the tube **39**, the second waste liquid port **55b**, the third waste liquid path **76c**, and the intake port **54**.

[0083] Furthermore, as depicted in FIG. 5B and FIG. 10A, the opening of the fourth waste liquid path **76d** faces the opening of the atmosphere port **56** in the radial direction of the channel member **70**. As a result, the fourth waste liquid path **76d** communicates with the atmosphere port **56**. Therefore, the waste liquid tank **35** communicates with the waste liquid tank **35** via the tube **39**, the atmosphere port **56**, the fourth waste liquid path **76d**, and the intake port **54**.

[0084] Moreover, as depicted in FIG. 5B and FIG. 11B, the opening of the fourth waste liquid path **76d** faces the opening of the exhaust port **57** in the radial direction of the channel member **70**. As a result, the fourth waste liquid path **76d** communicates with the exhaust port **57**. Therefore, the exhaust cap **33c** communicates with the waste liquid tank **35** via the tube **39**, the exhaust port **57**, the fourth waste liquid path **76d**, and the intake port **54**.

[0085] As depicted in FIG. 7A and FIG. 7B, a size B of the second waste liquid path **76b** in a direction orthogonal to a direction parallel to the radial direction and the central axis of the channel member **70** is equal to or greater than a total size (C+D) of a size C of the first waste liquid port **55a** and a size D of the first cleaning liquid downstream port **53a** in a direction orthogonal to the direction parallel to the radial direction and the central axis of the fixed member **50**. For example,

the size B of the second waste liquid path **76b** is 2.0 mm, and each of the size C of the first waste liquid port **55a** and the size D of the first cleaning liquid downstream port **53a** is 0.8 mm. Therefore, in a case that the rotation member **60** is rotated by, for example, 6°, the communication state can be changed between a state that the cleaning liquid path **75** does not communicate with the first cleaning liquid downstream port **53a** as depicted in FIG. 7A and a state that the cleaning liquid path **75** communicates with the first cleaning liquid downstream port **53a** as depicted in FIG. 7B, while maintaining a state that the second waste liquid path **76b** communicates with the first waste liquid port **55a**.

[0086] Further, as depicted in FIGS. 9A and 9B, a size E of the third waste liquid path **76c** in the direction orthogonal to the direction parallel to the radial direction and the central axis of the channel member **70** is equal to or greater than a total size (F+G) of a size F of the second waste liquid port **55b** and a size G of the second cleaning liquid downstream port **53b** in the direction orthogonal to the direction parallel to the radial direction and the central axis of the fixed member **50**. For example, the size E of the third waste liquid path **76c** is 2.0 mm, and each of the size F of the second waste liquid port **55b** and the size G of the second cleaning liquid downstream port **53b** is 0.8 mm. Therefore, in a case that the rotation member **60** is rotated by, for example, 6°, the communication state can be changed between a state that the cleaning liquid path **75** does not communicate with the second cleaning liquid downstream port **53b** as depicted in FIG. 9A and a state that the cleaning liquid path **75** communicates with the second cleaning liquid downstream port **53b** as depicted in FIG. 9B, while maintaining a state that the third waste liquid path **76c** communicates with the second waste liquid port **55b**.

(Printing Process)

[0087] The controller **40** obtains image data of the object image of the printing process from the memory **42** or the communication interface **43**, and executes the printing process based on the image data. In this printing process, the controller **40** executes a pass operation based on partial image data of the image data, and causes the liquids to be ejected from the first and second nozzles **23a** and **23b** of the liquid ejecting head **20** to the print medium A while causing the liquid ejecting head **20** to move rightward or leftward. Further, the controller **40** executes a conveying operation of conveying the print medium A forward. In this way, the controller **40** executes the pass operation and the conveying operation, thereby forming a plurality of partial images along the front-rear direction, and printing an image constructed of the plurality of partial images on the print medium A.

(Maintenance Process)

[0088] A maintenance process of the liquid ejecting head **20** is executed by the controller **40** in accordance with the flowchart of FIG. 12. This maintenance process is executed, for example, periodically or in response to a command from an input device or the external device capable of communicating with the controller **40**.

[0089] In a case that the liquid ejecting apparatus **10** is in a standby state in which neither the printing process nor the maintenance process is being performed, each of the first cap **31a**, the second cap **31b**, and the exhaust cap **33c** is in the capping state. Further, the rotation member **60** is located at the standby position depicted in FIG. 6. In this standby position, the first waste liquid path **76a** communicates with the first waste liquid port **55a**, and the second waste liquid path **76b** communicates with the second waste liquid port **55b**. Furthermore, the suction pump **36** is in the atmospheric open state.

[0090] This causes the first cap **31a** and the second cap **31b** to be open to the atmosphere via the suction pump **36** and the waste liquid tank **35**. This reduces the variation in pressure inside the first cap **31a** and the second cap **31b**, thereby preventing the liquids from being unnecessarily ejected from the first nozzles **23a** and the second nozzles **23b**.

[0091] In the maintenance process, the controller **40** executes a first purge process (step S10). In the first purge process, the controller **40** rotates the rotation member **60** from the standby position

to the first purge position in FIG. 7A. When the rotation member **60** is located at the first purge position, the second waste liquid path **76b** communicates with the first waste liquid port **55a** and the intake port **54**, and the cleaning liquid path **75** does not communicate with the first cleaning liquid upstream port **52a** and the first cleaning liquid downstream port **53a**. Further, each of the first, third and fourth waste liquid paths **76a**, **76c** and **76d** does not communicate with any of the second waste liquid port **55b**, the atmosphere port **56** and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the second cleaning liquid upstream port **52b** and the second cleaning liquid downstream port **53b**. In this case, the first cap **31a** communicates with the tube **39a** in which the suction pump **36** is disposed.

[0092] Then, the controller **40** drives the suction pump **36** in a state that the first cap **31a** is in the capping state and that the rotation member **60** is located at the first purge position. With this, the suction is performed inside the first cap **31a** covering the first ejection surface **21a**, thereby sucking the first liquid from the first nozzles **23a** which are open in the first ejection surface **21a**. This first liquid flows from the first cap **31a** through the tube **39**, the first waste liquid port **55a**, the second waste liquid path **76b**, the intake port **54**, and the tube **39a** in this order, and is exhausted into and stored in the waste liquid tank **35**. By such a first purge process, the first liquid which has dried and thereby become viscous is exhausted from the first nozzles **23a**, thereby reducing the unsatisfactory ejection from the first nozzles **23a**.

[0093] After executing the first purge process, the controller **40** executes a first cleaning process (step **S11**). In the first cleaning process, the controller **40** rotates the rotation member **60** from the first purge position to a first cleaning position depicted in FIG. 7B. When the rotation member **60** is located at the first cleaning position, the second waste liquid path **76b** communicates with the first waste liquid port **55a** and the intake port **54**, and the cleaning liquid path **75** communicates with the first cleaning liquid upstream port **52a** and the first cleaning liquid downstream port **53a**. Further, each of the first, third and fourth waste liquid paths **76a**, **76c** and **76d** does not communicate with any of the second waste liquid port **55b**, the atmosphere port **56** and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the second cleaning liquid upstream port **52b** and the second cleaning liquid downstream port **53b**. In this case, the first cap **31a** communicates with the tube **39a** in which the suction pump **36** is disposed, and the first cap **31** also communicates with the cleaning liquid tank **34**.

[0094] Then, in a state that the first cap **31a** is in the capping state and that the rotation member **60** is located at the first cleaning position, the controller **40** drives the suction pump **36**. With this, the suction is performed inside the first cap **31a** covering the first ejection surface **21a**, and negative pressure is generated in a space surrounded by the first ejection surface **21a** and the first cap **31a**.

[0095] The diameter of the first nozzle **23a** which is open in the first ejection surface **21a** is smaller than the diameters, respectively, of the tube **39**, the first cleaning liquid upstream port **52a**, the first cleaning liquid downstream port **53a**, and the cleaning liquid path **75** each of which communicates with the first cap **31a**. Therefore, the channel resistance of the first nozzle **23a** is high, and the cleaning liquid is sucked from the cleaning liquid tank **34** more easily as compared with a case that the first liquid is sucked from the first nozzles **23a** into the first cap **31a**. In other words, the cleaning liquid flows easily into the first cap **31a** from the cleaning liquid tank **34**. Therefore, in a state that the first liquid is prevented from flowing into the first cap **31a** from the first nozzles **23a**, the cleaning liquid flows from the cleaning liquid tank **34** through the tube **39**, the first cleaning liquid upstream port **52a**, the cleaning liquid path **75**, the first cleaning liquid downstream port **53a**, and the tube **39** in this order, and then flows into the first cap **31a**.

[0096] Further, the cleaning liquid is accumulated up to the first ejection surface **21a** covered by the first cap **31a** and contacts the first ejection surface **21a**. For example, in a case where the first liquid solidified on the first ejection surface **21a** is present, the first liquid solidified on the first ejection surface **21a** contacts the cleaning liquid having a similar composition to the composition of the first liquid, and thus the solidified first liquid is easily dissolved in the cleaning liquid. Even

in a case where the substance adhered on the first ejection surface **21a** is insoluble in the cleaning liquid, the substance adhered to the first ejection surface **21a** may move from the first ejection surface **21a** to the cleaning liquid. In other words, this cleans the first ejection surface **21a**. The cleaning liquid then flows from the first cap **31a** through the tube **39**, the first waste liquid port **55a**, the second waste liquid path **76b**, the intake port **54**, and the tube **39a** in this order, and is exhausted into and stored in the waste liquid tank **35**. By such a first cleaning process, the substance adhered to the first ejection surface **21a** is removed by the cleaning liquid, thereby preventing the unsatisfactory ejection of the first liquid from the first nozzles **23a** otherwise caused due to the substance adhered to the first ejection surface **21a**.

[0097] After executing the first cleaning process, the controller **40** executes a first pressure-boosting process (step **S12**). In the first pressure-boosting process, the controller **40** rotates the rotation member **60** from the first cleaning position to a first pressure-boosting position depicted in FIG. **8A**. As a result, each of the first to fourth waste liquid paths **76a** to **76d** does not communicate with any of the first waste liquid port **55a**, the second waste liquid port **55b**, the atmosphere port **56** and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the first cleaning liquid upstream port **52a**, the second cleaning liquid upstream port **52b**, the first cleaning liquid downstream port **53a** and the second cleaning liquid downstream port **53b**.

[0098] Then, the controller **40** causes the suction pump **36** to be in the atmospheric open state, in a state that the first cap **31a** is in the capping state and the rotation member **60** is located at the first pressure-boosting position. As a result, the air flows from the waste liquid tank **35** through the tube **39a**, in which the suction pump **36** is disposed, and the intake port **54**, and flows into the first to fourth waste liquid paths **76a** to **76d**. Then, the pressure of the first to fourth waste liquid paths **76a** to **76d** becomes the atmospheric pressure or approaches atmospheric pressure. In some cases, the first to fourth waste liquid paths **76a** to **76d** may temporarily communicate with the second waste liquid port **55b** while the channel member **70** is being rotated. Even in such a case, the second liquid can be prevented from being unnecessarily sucked from the second nozzles **23b** covered by the second cap **31b** which communicates with the second waste liquid port **55b**.

[0099] After executing the first pressure-boosting process, the controller **40** executes a first idle suction process (step **S13**). In the first idle suction process, the controller **40** rotates the rotation member **60** from the first pressure-boosting position to a first idle suction position depicted in FIG. **8B**. As a result, the third waste liquid path **76c** communicates with the first waste liquid port **55a** and the intake port **54**, and the cleaning liquid path **75** does not communicate with the first cleaning liquid upstream port **52a** and the first cleaning liquid downstream port **53a**. Further, each of the first, second and fourth waste liquid paths **76a**, **76b** and **76d** does not communicate with any of the second waste liquid port **55b**, the atmosphere port **56** and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the second cleaning liquid upstream port **52b** and the second cleaning liquid downstream port **53b**. In this case, the first cap **31a** communicates with the tube **39a** in which the suction pump **36** is disposed.

[0100] Then, the controller **40** changes the state of the first cap **31a** from the capping state to the uncapping state, and drives the suction pump **36** in a state that the rotation member **60** is located at the first idle suction position. With this, the first liquid and the cleaning liquid remaining in the first cap **31a** pass, together with the air, from the first cap **31a** through the tube **39**, the first waste liquid port **55a**, the third waste liquid path **76c**, the intake port **54** and the tube **39a**, and are exhausted to the waste liquid tank **35**. This reduces the first liquid which is dried in the first cap **31a**, thereby preventing the absorption of the water from the first liquid of the first nozzles **23a** due to a dried substance (of the first liquid), and preventing the first liquid from drying due to the absorption of water and preventing the unsatisfactory ejection of the first liquid from the first nozzles **23a** accompanying with the drying of the first liquid.

[0101] After executing the first idle suction process, the controller **40** executes a second purge process (step **S14**). In the second purge process, the controller **40** rotates the rotation member **60**

from the first idle suction position to a second purge position depicted in FIG. 9A. When the rotation member **60** is located at the second purge position, the third waste liquid path **76c** communicates with the second waste liquid port **55b** and the intake port **54**, and the cleaning liquid path **75** does not communicate with the second cleaning liquid upstream port **52b** and the second cleaning liquid downstream port **53b**. Further, each of the first, second and fourth waste liquid paths **76a**, **76b** and **76d** does not communicate with any of the first waste liquid port **55a**, the atmosphere port **56** and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the first cleaning liquid upstream port **52a** and the first cleaning liquid downstream port **53a**. In this case, the second cap **31b** communicates with the tube **39a** in which the suction pump **36** is disposed.

[0102] Then, the controller **40** drives the suction pump **36** in a state that the second cap **31b** is in the capping state and that the rotation member **60** is located at the second purge position. With this, the suction is performed inside the second cap **31b** covering the second ejection surface **21b**, thereby sucking the second liquid from the second nozzles **23b** which are open in the second ejection surface **21b**. This second liquid flows from the second cap **31b** through the tube **39**, the second waste liquid port **55b**, the third waste liquid path **76c**, the intake port **54**, and the tube **39a** in this order, and the second liquid is exhausted into and retrained in the waste liquid tank **35**. By such a second purge process, the second liquid which has dried and thereby become viscous is exhausted from the second nozzles **23b**, thereby reducing the unsatisfactory ejection from the second nozzles **23b**.

[0103] After executing the second purge process, the controller **40** executes a second cleaning process (step **S15**). In the second cleaning process, the controller **40** rotates the rotation member **60** from the second purge position to a second cleaning position depicted in FIG. 9B. When the rotation member **60** is located at the second cleaning position, the third waste liquid path **76c** communicates with the second waste liquid port **55b** and the intake port **54**, and the cleaning liquid path **75** communicates with the second cleaning liquid upstream port **52b** and the second cleaning liquid downstream port **53b**. Further, each of the first, second and fourth waste liquid paths **76a**, **76b** and **76d** does not communicate with any of the first waste liquid port **55a**, the atmosphere port **56** and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the first cleaning liquid upstream port **52a** and the first cleaning liquid downstream port **53a**. In this case, the second cap **31b** communicates with the tube **39a**, in which the suction pump **36** is disposed, and with the cleaning liquid tank **34**.

[0104] Then, the controller **40** drives the pump **36** in a state that the second cap **31b** is in the capping state and the rotation member **60** is located at the second cleaning position. With this, the suction is performed inside the second cap **31b** covering the second ejection surface **21b**, and the negative pressure is generated in a space surrounded by the second ejection surface **21b** and the second cap **31b**.

[0105] The diameter of the second nozzle **23b** which is open in the second ejection surface **21b** is smaller than the diameter of each of the tube **39**, the first cleaning liquid upstream port **52a** and the first cleaning liquid downstream port **53a**, and the cleaning liquid path **75** which communicate with the second cap **31b**. For this reason, the channel resistance of the second nozzle **23b** is high, and the cleaning liquid is sucked from the cleaning liquid tank **34** more easily as compared with a case that the second liquid is sucked from the second nozzles **23b** into the second cap **31b**. In other words, the cleaning liquid flows easily into the second cap **31b** from the cleaning liquid tank **34**.

Therefore, in a state that the second liquid is prevented from flowing into the second cap **31b** from the second nozzles **23b**, the cleaning liquid flows from the cleaning liquid tank **34** through the tube **39**, the second cleaning liquid upstream port **52b**, the cleaning liquid path **75**, the second cleaning liquid downstream port **53b**, and the tube **39** in this order, and flows into the second cap **31b**.

[0106] Further, the cleaning liquid is accumulated up to the second ejection surface **21b** covered by the second cap **31b** and contacts the second ejection surface **21b**. For example, in a case where the

second liquid solidified on the second ejection surface **21b** is present, the second liquid solidified on the second ejection surface **21b** contacts the cleaning liquid having a similar composition to the composition of the second liquid, and thus the solidified second liquid is easily dissolved in the cleaning liquid. Even in a case where the substance adhered on the second ejection surface **21b** is insoluble in the cleaning liquid, the substance adhered to the second ejection surface **21b** may move from the second ejection surface **21b** to the cleaning liquid. In other words, this cleans the second ejection surface **21b** covered by the second cap **31b**. The cleaning liquid then flows from the second cap **31b** through the tube **39**, the second waste liquid port **55b**, the third waste liquid path **76c**, the intake port **54**, and the tube **39a** in this order, and is exhausted into and retrained in the waste liquid tank **35**. By such a second cleaning process, the substance adhered to the second ejection surface **21b** is removed by the cleaning liquid, thereby preventing the unsatisfactory ejection of the liquid from the second nozzles **23b** otherwise caused due to the substance adhered to the second ejection surface **21b**.

[0107] After executing the second cleaning process, the controller **40** executes a second pressure-boosting process (step **S16**). In the second pressure-boosting process, the controller **40** rotates the rotation member **60** from the second cleaning position to a second pressure-boosting position depicted in FIG. **10A**. As a result, the fourth waste liquid path **76d** communicates with the atmosphere port **56**, each of the first, second and third waste liquid paths **76a**, **76b** and **76c** does not communicate with any of the first waste liquid port **55a**, the second waste liquid port **55b**, and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the first cleaning liquid upstream port **52a**, the second cleaning liquid upstream port **52b**, the first cleaning liquid downstream port **53a** and the second cleaning liquid downstream port **53b**.

[0108] Then, the controller **40** causes the suction pump **36** to be in the atmospheric open state, in a state that the second cap **31b** is in the capping state and that the rotation member **60** is located at the second pressure-boosting position. As a result, the air flows from the waste liquid tank **35** through the tube **39** and the atmosphere port **56** into the first to fourth waste liquid paths **76a** to **76d**. Further, the air flows from the waste liquid tank **35** through the tube **39a**, in which the suction pump **36** is disposed, and through the intake port **54** and flows into the first to fourth waste liquid paths **76a** to **76d**. Then, the pressure of the first to fourth waste liquid paths **76a** to **76d** becomes the atmospheric pressure or approaches the atmospheric pressure. In some cases, the first to fourth waste liquid paths **76a** to **76d** may temporarily communicate with the first waste liquid port **55a** while the channel member **70** is being rotated. Even in such a case, the first liquid can be prevented from being unnecessarily sucked from the first nozzles **23b** covered by the first cap **31a** which communicates with the first waste liquid port **55a**.

[0109] After executing the second pressure-boosting process, the controller **40** executes a second idle suction process (step **S17**). In the second idle suction process, the controller **40** rotates the rotation member **60** from the second pressure-boosting position to a second idle suction position depicted in FIG. **10B**. As a result, the fourth waste liquid path **76d** communicates with the second waste liquid port **55b** and the intake port **54**, and each of the first, second and third waste liquid paths **76a**, **76b** and **76c** does not communicate with any of the first waste liquid port **55a**, the atmosphere port **56** and the exhaust port **57**, and the cleaning liquid path **75** does not communicate with any of the first cleaning liquid upstream port **52a**, the second cleaning liquid upstream port **52b**, the first cleaning liquid downstream port **53a** and the second cleaning liquid downstream port **53b**. In this case, the second cap **31b** communicates with the tube **39a** in which the suction pump **36** is disposed.

[0110] Then, the controller **40** drives the suction pump **36** in a state that the second cap **31b** is changed from the capping state to the uncapping state, and that the rotation member **60** is located at the second idle suction position. With this, the second liquid and the cleaning liquid remaining in the second cap **31b** pass, together with the air, from the second cap **31b** through the tube **39**, the second waste liquid port **55b**, the fourth waste liquid path **76d** and the tube **39a**, and are exhausted

to the waste liquid tank **35**. This reduces the second liquid which is dried in the second cap **31b**, thereby preventing the absorption of the water from the second liquid of the second nozzles **23b** due to a dried substance (of the second liquid), and preventing the second liquid from drying due to the absorption of the water and preventing the unsatisfactory ejection of the second liquid from the second nozzles **23b** accompanying with the drying of the second liquid.

[0111] After executing the second idle suction process, the controller **40** executes an exhaust-purge process (step **S18**). In the exhaust-purge process, the controller **40** rotates the rotation member **60** from the second idle suction position to an exhaust-purge position depicted in FIG. **11A**. As a result, the second waste liquid path **76b** communicates with the exhaust port **57** and the intake port **54**, and each of the first, third and fourth waste liquid paths **76a**, **76c** and **76d** does not communicate with any of the first waste liquid port **55a**, the second waste liquid port **55b** and the atmosphere port **56**, and the cleaning liquid path **75** does not communicate with any of the first cleaning liquid upstream port **52a**, the second cleaning liquid upstream port **52b**, the first cleaning liquid downstream port **53a** and the second cleaning liquid downstream port **53b**. In this case, the exhaust cap **33c** communicates with the tube **39a** in which the suction pump **36** is disposed.

[0112] Then, the controller **40** drives the suction pump **36** in a state that the exhaust cap **33c** is in the capping state and that the rotation member **60** is located at the exhaust-purge position. With this, as depicted in FIG. **3** and FIG. **11A**, the suction is performed inside the exhaust cap **33c** covering the exhaust surface **33b1**, and the negative pressure is generated in a space surrounded by the exhaust surface **33b1** and the exhaust cap **33c**. The air bubble retained in the upper portion of the buffer tank **13** is sucked by the exhaust path **33a** which is open in the exhaust surface **33b1**. Then, the air bubble flows from the buffer tank **13** through the exhaust path **33a**, the exhaust cap **33c**, the tube **39**, the exhaust port **57**, the second waste liquid path **76b**, the intake port **54**, and the tube **39a** in this order, and is exhausted into the waste liquid tank **35**. By this exhaust-purge process, the air bubble is exhausted from the liquid ejecting head **20**, thereby reducing the unsatisfactory ejection from the liquid ejecting head **20** otherwise caused due to the air bubble.

[0113] After executing the exhaust-purge process, the controller **40** executes an exhaust-idle suction process (step **S19**). In the exhaust-idle suction process, the controller **40** rotates the rotation member **60** from the exhaust-purge position to an exhaust-idle suction position depicted in FIG. **11B**. As a result, the fourth waste liquid path **76d** communicates with the exhaust port **57** and the intake port **54**, and each of the first, second and third waste liquid paths **76a**, **76b** and **76c** does not communicate with any of the first waste liquid port **55a**, the second waste liquid port **55b** and the atmosphere port **56**, and the cleaning liquid path **75** does not communicate with any of the first cleaning liquid upstream port **52a**, the second cleaning liquid upstream port **52b**, the first cleaning liquid downstream port **53a** and the second cleaning liquid downstream port **53b**. In this case, the exhaust cap **33c** communicates with the tube **39a** in which the suction pump **36** is disposed.

[0114] Further, the controller **40** drives the suction pump **36** in a state that the state of the exhaust cap **33c** is changed from the capping state to the uncapping state, and that the rotation member **60** is located at the exhaust-idle suction position. With this, the liquid discharged from the liquid ejecting head **20** together with the air bubble and remaining in the exhaust cap **33c** passes, together with the air, from the exhaust cap **33c** through the tube **39**, the exhaust port **57**, the fourth waste liquid path **76d**, the intake port **54**, and the tube **39a**, and is exhausted to the waste liquid tank **35**.

First Modification

[0115] In a liquid ejecting apparatus **10** according to a first modification, the controller **40** further executes, in the above-described embodiment, a first preliminary cleaning process and a second preliminary cleaning process. For example, the controller **40** executes the maintenance process according to the flowchart depicted in FIG. **13**. In the flowchart of FIG. **13**, the controller **40** executes the first preliminary cleaning process of step **S20** before the first purge process of step **S10** in the flowchart of FIG. **12**. Further, in the flowchart of FIG. **13**, the controller **40** executes the second preliminary cleaning process of step **S21** before the second purge process of step **S14** in the

flowchart of FIG. 12.

[0116] Specifically, the controller **40** executes the first preliminary cleaning process (step **S20**) before executing the first purge process (step **S10**). In the first preliminary cleaning process, the controller **40** rotates the rotation member **60** from the standby position in FIG. **6** to the first cleaning position depicted in FIG. **7B**. Then, the controller **40** drives the suction pump **36** in the state that the first cap **31a** is in the capping state and that the rotation member **60** is located at the first cleaning position. With this, the suction is performed inside the first cap **31a** covering the first ejection surface **21a**, and the negative pressure is generated in the space surrounded by the first ejection surface **21a** and the first cap **31a**.

[0117] Therefore, the cleaning liquid flows from the cleaning liquid tank **34** through the first cleaning liquid upstream port **52a**, the cleaning liquid path **75**, and the first cleaning liquid downstream port **53a** in this order, and then flows into the first cap **31a**. Then, the cleaning liquid flows from the first cap **31a** through the first waste liquid port **55a**, the second waste liquid path **76b**, and the intake port **54** in this order, and is exhausted into the waste liquid tank **35**. By this first preliminary cleaning process, the cleaning liquid adheres to the inside of the first cap **31a** and the inside of the waste liquid channel including the first waste liquid port **55a**, the second waste liquid path **76b**, and the intake port **54**. In this way, by causing the cleaning liquid to adhere to the inside of the first cap **31a** covering the first ejection surface **21a** and the inside of the waste liquid channel in the first preliminary cleaning process, the cleaning liquid is dispersed in the inside of the first cap **31a** and the inside of the waste liquid channel; in a case where the first liquid contacts the cleaning liquid, the first liquid is diluted by the cleaning liquid. In a case that the first liquid is diluted, the first liquid thus becomes less likely to solidify, thereby making the first liquid less likely to solidify in the first cap **31a** and the waste liquid channel.

[0118] Therefore, even in a case where the first liquid is sucked into the first cap **31a** by the first purge process (step **S10**) executed after the first preliminary cleaning process has been executed, the first liquid is not firmly fixed to inside the first cap **31a** and the inside of the waste liquid channel, and is easily exhausted from the first cap **31a** via the waste liquid channel. Note that the first liquid may be exhausted from the first cap **31a** without being accumulated up to the first ejection surface **21a** in the first cap **31a**. This shortens the time required for the first preliminary cleaning process.

[0119] Further, the controller **40** executes the second preliminary cleaning process (step **S21**) after executing the first idle suction process (step **S13**) and before executing the second purge process (step **S14**). In the second preliminary cleaning process, the controller **40** rotates the rotation member **60** from the standby position to the second cleaning position depicted in FIG. **9B**. Then, the controller **40** drives the suction pump **36** in the state that the second cap **31b** is in the capping state and the rotation member **60** is located at the second cleaning position. With this, the suction is performed inside the second cap **31b** covering the second ejection surface **21b**, and the negative pressure is generated in the space surrounded by the second ejection surface **21b** and the second cap **31b**.

[0120] Therefore, the cleaning liquid flows from the cleaning liquid tank **34** through the second cleaning liquid upstream port **52b**, the cleaning liquid path **75**, and the second cleaning liquid downstream port **53b** in this order, and then flows into the second cap **31b**. The cleaning liquid then flows from the second cap **31b** through the second waste liquid port **55b**, the third waste liquid path **76c**, and the intake port **54** in this order, and is exhausted into the waste liquid tank **35**. This second preliminary cleaning process causes the cleaning liquid to adhere to the inside of the second cap **31b** and the inside of the waste liquid channel which includes the second waste liquid port **55b**, the third waste liquid path **76c** and the intake port **54**. By causing the cleaning liquid to preliminarily adhere to the inside of the second cap **31b** and the inside of the waste liquid channel, the cleaning liquid is dispersed in the inside of the second cap **31b** and the inside of the waste liquid channel; in a case where the second liquid contacts the cleaning liquid, the second liquid is diluted by the

cleaning liquid. In a case that the second liquid is diluted, the second liquid thus becomes less likely to solidify, thereby making the second liquid less likely to solidify in the second cap **31b** and the waste liquid channel.

[0121] Therefore, even in a case where the second liquid is sucked into the second cap **31b** by the second purge process (step **S14**) executed after the second preliminary cleaning process has been executed, the second liquid is not firmly fixed to the inside of the second cap **31b** and the inside of the waste liquid channel, and is easily exhausted from the second cap **31b** through the waste liquid channel. Note that the second liquid may be exhausted from the second cap **31b**, without being accumulated up to the second ejection surface **21b** in the second cap **31b**. This shortens the time required for the second preliminary cleaning process.

Second Modification

[0122] In a liquid ejecting apparatus **10** according to a second modification, the suction pump **36** performs the suction with a first suction force or a second suction force which is greater than the first suction force. For example, as depicted in FIG. **2**, the suction pump **36** has a pump motor **36a**. The suction force of the suction pump **36** can be increased by increasing the rotation amount of the pump motor **36a**. The rotation amount of the pump motor **36a** is controlled by the controller **40**. The controller **40** drives the suction pump **36** to perform the suction with the first suction force, by driving the pump motor **36a** at a first rotation amount. Further, the controller **40** drives the suction pump **36** to perform the suction with the second suction force which is greater than the first suction force, by driving the pump motor **36a** at a second rotation amount which is greater than the first rotation amount.

[0123] In a case where the controller **40** executes the first preliminary cleaning process in step **S20** in the flowchart of the example (second modification) of FIG. **13**, the controller **40** drives the suction pump **36** to perform the suction with the first suction force, by driving the pump motor **36a** at the first rotation amount. This causes the cleaning liquid to flow from the cleaning liquid tank **34** into the first cap **31a**, to clean the first cap **31a**, and then to be exhausted to the waste liquid tank **35**. This cleaning liquid does not contain a solid component and has a lower viscosity than the viscosity of the first liquid which contains the solid component. Therefore, the first cap **31a** can be cleaned by causing the cleaning liquid to flow by the suction of the suction pump **36** with the first suction force which is small, while reducing the electrical power consumption by driving the pump motor **36a** at the first rotation amount which is small.

[0124] Further, in a case where the controller **40** executes the first purge process in step **S10** after step **S20**, the controller **40** drives the pump motor **36a** at the second rotation amount and causes the suction pump **36** to perform the suction with the second suction force. The first liquid contains the solid component, and this solid component contains the resin fine particles and the solid component of the colorant. For example, the first liquid contains the resin fine particles at a content amount in the range of 0.1 wt % to 30 wt %, and the solid component of the colorant at a content amount in the range of 0.1 wt % to 20 wt %. The viscosity of this first liquid is higher than the viscosity of the cleaning liquid. Even in such a case, by causing the suction pump **36a** to perform the suction with the second suction force which is great, the first liquid can be sucked from the first nozzles **23a** and into the first cap **31a**, and can be exhausted from the first cap **31a** to the waste liquid tank **35**.

[0125] Furthermore, in a case where the controller **40** executes the second preliminary cleaning process in step **S21**, the controller **40** drives the suction pump **36** to perform the suction with the first suction force, by driving the pump motor **36a** at the first rotation amount. As a result, the cleaning liquid flows from the cleaning liquid tank **34** into the second cap **31b**, cleans the second cap **31b**, and then is exhausted to the waste liquid tank **35**. This cleaning liquid does not contain the solid component and has the lower viscosity than the viscosity of the second liquid which contains the solid component. Therefore, the second cap **31b** can be cleaned by causing the cleaning liquid to flow by the suction of the suction pump **36** with the first suction force which is small, while reducing the electrical power consumption by driving the pump motor **36a** at the first rotation

amount which is small.

[0126] Moreover, in a case where the controller **40** executes the second purge process in step **S14** after step **S21**, the controller **40** drives the suction pump **36** to perform the suction with the second suction force, by driving the pump motor **36a** at the second rotation amount. The second liquid contains the solid content, and this solid content includes the resin fine particles and the solid content of the colorant. For example, the second liquid contains the resin fine particles at a content amount in the range of 0.1 wt % to 30 wt %, and contains the solid content of the colorant at a content amount in the range of 0.1 wt % to 20 wt %. The viscosity of this second liquid is higher than the viscosity of the cleaning liquid. Even in such a case, by causing the suction pump **36a** to perform the suction with the second suction force which is great, the second liquid can be sucked from the second nozzles **23b** and into the second cap **31b**, and can be exhausted from the second cap **31b** to the waste liquid tank **35**.

Other Modifications

[0127] In the above-described embodiment and the first modification, the first to fourth waste liquid paths **76a** to **76d** are open to the atmosphere via the intake port **54** in the first pressure-boosting process, and the first to fourth waste liquid paths **76a** to **76d** are open to the atmosphere via the atmosphere port **56** in the second pressure-boosting process. However, the method of opening the first to fourth waste liquid paths **76a** to **76d** to the atmosphere in the first pressure-boosting process and the second pressure-boosting process is not limited to this. For example, in the first pressure-boosting process, the first to fourth waste liquid paths **76a** to **76d** may be open to the atmosphere via the atmosphere port **56**, and in the second pressure-boosting process, the first to fourth waste liquid paths **76a** to **76d** may be open to the atmosphere via the intake port **54**.

Alternatively, in both the first pressure-boosting process and the second pressure-boosting process, the first to fourth waste liquid paths **76a** to **76d** may be open to the atmosphere via the intake port **54**, or the first to fourth waste liquid paths **76a** to **76d** may be open to the atmosphere via the atmosphere port **56**.

[0128] In the above-described embodiment and the modifications, an open/close valve **33d** (see FIG. **3**) which is configured to open and close the exhaust path **33a** may be disposed in the exhaust body **33b**. In this case, a cam **61a** (see FIG. **4**) which is configured to open and close the open/close valve **33d** may be disposed in the gear part **61** of the rotation member **60**. In a case where the cam **61a** rotates due to the rotation of the rotation member **60** to thereby close the open/close valve **33d**, the exhaust path **33a** is shut off (blocked). This prevents the air from entering the buffer tank **13** and the liquid ejecting head **20** via the exhaust path **33a**.

[0129] On the other hand, in a case where the cam **61a** rotates by the rotation of the rotation member **60** to thereby open the open/close valve **33d**, the exhaust path **33a** is released. With this, in the capping state that the exhaust surface **33b1** in which the exhaust path **33a** is open is covered by the exhaust cap **33c**, the buffer tank **13** and the exhaust cap **33c** communicate with each other via the exhaust path **33a**. Since the exhaust cap **33c** communicates with the tube **39a** in which the suction pump **36** is disposed, the controller **40** executes the exhaust-purge process by driving the suction pump **36**. This exhaust-purge process can reduce the unnecessary exhaust of the liquid while shortening the processing time, as compared to the method of discharging the air bubble by the suction of the liquid. Further, since the cam **61a** is disposed in the rotation member **60**, the communication state among the first cleaning liquid upstream port **52a**, the second cleaning liquid upstream port **52b**, the first cleaning liquid downstream port **53a**, the second cleaning liquid downstream port **53b**, the first waste liquid port **55a**, the second waste liquid port **55b**, the atmosphere port **56**, the exhaust port **57**, and the cleaning liquid path **75** and the first to fourth waste liquid paths **76a** to **76d** can be changed, and the open/close valve **33d** can be opened and closed.

Claims

1. A liquid ejecting apparatus, comprising: a liquid ejecting head having an ejection surface with nozzles opening therein; a cap configured to cover the ejection surface; a suction pump; a cleaning liquid tank configured to store cleaning liquid; and a switching valve having a fixed member, a rotation member, and a channel member, wherein the fixed member has: a main body configured to support the channel member; a cleaning liquid upstream port being a hollow protrusion protruding from the main body and connected to the cleaning liquid tank via a tube; a cleaning liquid downstream port and a waste liquid port each being a hollow protrusion protruding from the main body and connected to the cap via a tube; and an intake port being a hollow protrusion protruding from the main body and connected to a tube having the suction pump disposed therein, the rotation member is configured to rotate with respect to the fixed member, and has a first cleaning liquid path, and the channel member is attached to the rotation member and configured to rotate together with the rotation member with respect to the fixed member, the channel member having: a second cleaning liquid path connected to the first cleaning liquid path to form a cleaning liquid path communicating the cleaning liquid upstream port and the cleaning liquid downstream port with each other; and a waste liquid path communicating the waste liquid port and the intake port with each other.
2. The liquid ejecting apparatus according to claim 1, wherein the nozzles include a first nozzle configured to eject first liquid and a second nozzle configured to eject second liquid, the ejection surface includes a first ejection surface and a second ejection surface, the cap includes a first cap configured to cover the first ejection surface and a second cap configured to cover the second ejection surface, the cleaning liquid upstream port includes a first cleaning liquid upstream port and a second cleaning liquid upstream port each communicating with the cleaning liquid tank, the cleaning liquid downstream port includes a first cleaning liquid downstream port communicating with the first cap and a second cleaning liquid downstream port communicating with the second cap, and the waste liquid port includes a first waste liquid port communicating with the first cap and a second waste liquid port communicating with the second cap.
3. The liquid ejecting apparatus according to claim 2, wherein when the rotation member is located at a first cleaning position, the waste liquid path communicates with the first waste liquid port and the intake port and the cleaning liquid path communicates with the first cleaning liquid upstream port and the first cleaning liquid downstream port.
4. The liquid ejecting apparatus according to claim 2, wherein when the rotation member is located at a first purge position, the waste liquid path communicates with the first waste liquid port and the intake port and the cleaning liquid path does not communicate with the first cleaning liquid upstream port and the first cleaning liquid downstream port.
5. The liquid ejecting apparatus according to claim 2, wherein a size of the waste liquid path in a direction orthogonal to a radial direction of the channel member is equal to or greater than a total size of a size of the first waste liquid port in a direction orthogonal to a radial direction of the fixed member and a size of the first cleaning liquid downstream port in the direction orthogonal to the radial direction of the fixed member.
6. The liquid ejecting apparatus according to claim 2, wherein the when rotation member is located at a second cleaning position, the waste liquid path communicates with the second waste liquid port and the intake port and the cleaning liquid path communicates with the second cleaning liquid upstream port and the second cleaning liquid downstream port.
7. The liquid ejecting apparatus according to claim 2, wherein when the rotation member is located at a second purge position, the waste liquid path communicates with the second waste liquid port and the intake port and the cleaning liquid path does not communicate with the second cleaning liquid upstream port and the second cleaning liquid downstream port.

8. The liquid ejecting apparatus according to claim 2, wherein a size of the waste liquid path in a direction orthogonal to a radial direction of the channel member is equal to or greater than a total size of a size of the second waste liquid port in a direction orthogonal to a radial direction of the fixed member and a size of the second cleaning liquid downstream port in the direction orthogonal to the radial direction of the fixed member.

9. The liquid ejecting apparatus according to claim 3, further comprising: a rotation device configured to rotate the rotation member with respect to the fixed member; and a controller, wherein the controller is configured to drive the suction pump, in a state that the rotation member is located at the first cleaning position, to execute a first cleaning process of cleaning the first ejection surface covered by the first cap.

10. The liquid ejecting apparatus according to claim 9, wherein the controller is configured to drive the suction pump, before the controller executes the first cleaning process and in a state that the rotation member is located at a first purge position, the waste liquid path communicating with the first waste liquid port and the intake port at the first purge position, and the cleaning liquid path not communicating with the first cleaning liquid upstream port and the first cleaning liquid downstream port at the first purge position, to execute a first purge process of performing suction inside the first cap covering the first ejection surface, and the controller is configured to drive the suction pump, before the controller executes the first purge process and in a state that the rotation member is located at the first cleaning position, to execute a first preliminary cleaning process of causing the cleaning liquid to adhere to the first cap covering the first ejection surface.

11. The liquid ejecting apparatus according to claim 9, wherein the first liquid contains a solid content, the solid content includes resin fine particles and a solid content of a colorant, the resin fine particles are contained in the first liquid in a range of 0.1 wt % to 30 wt % inclusive, the solid content of the colorant is contained in the first liquid in a range of 0.1 wt % to 20 wt % inclusive, the cleaning liquid does not contain the solid content, the suction pump is configured to be driven by a first suction force or a second suction force greater than the first suction force, the controller is configured to drive the suction pump, before the controller executes the first cleaning process and in a state that the rotation member is located at a first purge position, the waste liquid path communicating with the first waste liquid port and the intake port at the first purge position, and the cleaning liquid path not communicating with the first cleaning liquid upstream port and the first cleaning liquid downstream port at the first purge position, to execute a first purge process of performing suction inside the first cap covering the first ejection surface, the controller is configured to drive the suction pump, before the controller executes the first purge process and in a state that the rotation member is located at the first cleaning position, to execute a first preliminary cleaning process of cleaning the first cap covering the first ejection surface, and the suction pump is configured to be driven by the first suction force in a case where the controller executes the first preliminary cleaning process, and the suction pump is configured to be driven by the second suction force in a case where the controller executes the first purge process.

12. The liquid ejecting apparatus according to claim 6, further comprising: a rotation device configured to rotate the rotation member with respect to the fixed member; and a controller, wherein the controller is configured to drive the suction pump, in a state that the rotation member is located at the second cleaning position, to execute a second cleaning process of cleaning the second ejection surface covered by the second cap.

13. The liquid ejecting apparatus according to claim 12, wherein the controller is configured to drive the suction pump, before the controller executes the second cleaning process and in a state that the rotation member is located at a second purge position, the waste liquid path communicating with the second waste liquid port and the intake port at the second purge position, and the cleaning liquid path not communicating with the second cleaning liquid upstream port and the second cleaning liquid downstream port at the second purge position, to execute a second purge process of performing suction inside the second cap covering the second ejection surface, and the controller is

configured to drive the suction pump, before the controller executes the second purge process and in a state that the rotation member is located at the second cleaning position, to execute a second preliminary cleaning process of causing the cleaning liquid to adhere to the second cap covering the second ejection surface.

14. The liquid ejecting apparatus according to claim 12, wherein the second liquid contains a solid content, the solid content includes resin fine particles and a solid content of a colorant, the resin fine particles are contained in the second liquid in a range of 0.1 wt % to 30 wt % inclusive, the solid content of the colorant is contained in the second liquid in a range of 0.1 wt % to 20 wt % inclusive, the cleaning liquid does not contain the solid content, the suction pump is configured to be driven by a first suction force or a second suction force greater than the first suction force, the controller is configured to drive the suction pump, before the controller executes the second cleaning process and in a state that the rotation member is located at a second purge position, the waste liquid path communicating with the second waste liquid port and the intake port at the second purge position, and the cleaning liquid path not communicating with the second cleaning liquid upstream port and the second cleaning liquid downstream port at the second purge position, to execute a second purge process of performing suction inside the second cap covering the second ejection surface, the controller is configured to drive the suction pump, before the controller executes the second purge process and in a state that the rotation member is located at the second cleaning position, to execute a second preliminary cleaning process of causing the cleaning liquid to adhere to the inside of the second cap covering the second ejection surface, and the suction pump is configured to be driven by the first suction force in a case where the controller executes the second preliminary cleaning process, and the suction pump is configured to be driven by the second suction force in a case where the controller executes the second purge process.

15. A control method of a liquid ejecting apparatus, the liquid ejecting apparatus including: a liquid ejecting head having an ejection surface with nozzles opening therein; a cap configured to cover the ejection surface; a suction pump; a cleaning liquid tank configured to store cleaning liquid; and a switching valve having a fixed member, a rotation member, and a channel member, the fixed member having: a main body configured to support the channel member; and ports including a cleaning liquid upstream port being a hollow protrusion protruding from the main body and connected to the cleaning liquid tank via a tube, a cleaning liquid downstream port and a waste liquid port each being a hollow protrusion protruding from the main body and connected to the cap via a tube, and an intake port being a hollow protrusion protruding from the main body and connected to a tube having the suction pump disposed therein, the rotation member being configured to rotate with respect to the fixed member, and having a first cleaning liquid path, the channel member being attached to the rotation member and configured to rotate together with the rotation member with respect to the fixed member, the channel member having: a second cleaning liquid path connected to the first cleaning liquid path to form a cleaning liquid path communicating the cleaning liquid upstream port and the cleaning liquid downstream port with each other; and a waste liquid path communicating the waste liquid port and the intake port with each other, the control method comprising changing a communication state between the ports and the cleaning liquid path and between the ports and the waste liquid path by rotation of the rotation member.

16. A non-transitory medium storing a control program for a liquid ejecting apparatus, the liquid ejecting apparatus including: a liquid ejecting head having an ejection surface with nozzles opening therein; a cap configured to cover the ejection surface; a suction pump; a cleaning liquid tank configured to store cleaning liquid; a switching valve having a fixed member, a rotation member, and a channel member; and a controller, the fixed member having: a main body configured to support the channel member; and ports including: a cleaning liquid upstream port being a hollow protrusion protruding from the main body and connected to the cleaning liquid tank via a tube; a cleaning liquid downstream port and a waste liquid port each being a hollow protrusion protruding from the main body and connected to the cap via a tube; and an intake port being a hollow

protrusion protruding from the main body and connected to a tube having the suction pump disposed therein, the rotation member being configured to rotate with respect to the fixed member, and having a first cleaning liquid path, and the channel member being attached to the rotation member and configured to rotate together with the rotation member with respect to the fixed member, the channel member having: a second cleaning liquid path connected to the first cleaning liquid path to form a cleaning liquid path communicating the cleaning liquid upstream port and the cleaning liquid downstream port with each other; and a waste liquid path communicating the waste liquid port and the intake port, the control program causing the controller to change a communication state between the ports and the cleaning liquid path and between the ports and the waste liquid path by rotation of the rotation member.
