

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276547

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

HASHIMOTO; Yu et al.

TIRE

Abstract

A tire has a tread portion including a middle land portion defined between a crown circumferential groove and a shoulder circumferential groove. The middle land portion is provided with communicating sipes, axially inner sipes and axially outer sipes. The communicating sipes include a first communicating sipe comprising a first linear portion extending from the crown circumferential groove, and a first curved portion extending from an end of the first linear portion to the shoulder circumferential groove in a curved manner.

Inventors: HASHIMOTO; Yu (Kobe-shi, JP), KAWAGOE; Yoshifumi (Kobe-shi, JP), IKEDA; Kohei (Kobe-shi, JP)

Applicant: Sumitomo Rubber Industries, Ltd. (Kobe-shi, JP)

Family ID: 96881752

Assignee: Sumitomo Rubber Industries, Ltd. (Kobe-shi, JP)

Appl. No.: 19/044342

Filed: February 03, 2025

Foreign Application Priority Data

JP	2024-031596	Mar. 01, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: B60C11/03 (20060101); B60C11/12 (20060101)

U.S. Cl.:

CPC B60C11/0306 (20130101); B60C11/0304 (20130101); B60C11/12 (20130101); B60C2011/0341 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates to a tire.

BACKGROUND ART

[0002] Patent Document 1 listed below discloses a tire in which a land portion of the tread portion is provided with linearly-extending first and second inclined sipes, and the first and second inclined sipes are each provided with a deep bottom portion and a shallow bottom portion in hopes of being improved in steering stability on dry road surfaces and on-snow/ice performance. [0003] Patent Document 1: Japanese Patent Application Publication No. 2022-064106

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

[0004] In recent years, since performances of the automobile have been improved, the tires are also required to be further improved in performance on snowy and icy roads. As shown in Patent Document 1, sipes extending linearly over the entire lengths, tend to generate frictional force only in a specific direction. Therefore, there is a need to improve cornering performance (especially steering responsiveness) on snowy and icy roads.

[0005] On the other hand, even in tires designed for driving on snowy and icy roads, it is necessary to maintain the travelling performance on dry roads (hereinafter, simply referred to as the “dry performance”).

[0006] The present disclosure was therefore, made in view of the above circumstances, and a primary objective of the present disclosure is to provide a tire which can exert excellent on-snow/ice performance while maintaining dry performance.

Means for Solving the Problems

[0007] According to the present disclosure, a tire comprises a tread portion comprising a plurality of circumferential grooves extending continuously in the tire circumferential direction, and a plurality of land portions axially divided by the plurality of circumferential grooves, wherein [0008] the circumferential grooves include a crown circumferential groove, and a shoulder circumferential groove disposed axially outside the crown circumferential groove adjacently thereto, [0009] the land portions include a middle land portion disposed between the crown circumferential groove and the shoulder circumferential groove, [0010] the middle land portion is provided with a plurality of communicating sipes extending from the crown circumferential groove to the shoulder circumferential groove, a plurality of inner sipes extending axially outwards from the crown circumferential groove and terminated without reaching the shoulder circumferential groove, and a plurality of outer sipes extending axially inwards from the shoulder circumferential groove and terminated without reaching the crown circumferential groove, and [0011] the communicating sipes include a plurality of first communicating sipes each comprising a first linear portion extending linearly axially outward from the crown circumferential groove, and a first curved portion extending curvedly from an axially outer end of the first linear portion toward the shoulder circumferential groove.

Effects of the Invention

[0012] In the present disclosure, by adopting the above configuration, the tire is able to demonstrate excellent on-snow/ice performance while maintaining dry performance.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 is a developed partial view of a tread portion of a tire as an embodiment of the

present disclosure.

[0014] FIG. 2 is a top view of a part of the middle land portion of the tire shown in FIG. 1.

[0015] FIG. 3 is an enlarged view showing the first communicating sipe and its surroundings in FIG. 2.

[0016] FIG. 4 is an enlarged view showing a second communicating sipe and its surroundings in FIG. 2.

[0017] FIG. 5 is a cross-sectional view taken along line A-A in FIG. 3.

[0018] FIG. 6 is a top view of a part of the crown land portion of the tire shown in FIG. 1.

[0019] FIG. 7 is a cross-sectional view taken along line B-B in FIG. 6.

[0020] FIG. 8 is a top view of a part of the shoulder land portion of the tire shown in FIG. 1.

[0021] FIG. 9 is a developed partial view of a tread portion of a comparative example tire.

DETAILED DESCRIPTION OF THE INVENTION

[0022] Hereinafter, an embodiment of the present disclosure will be described in detail in conjunction with accompanying drawings.

[0023] Incidentally, in order to facilitate understanding of the present disclosure, the drawings may include exaggerations and dimensional proportions which differ from reality.

[0024] The present disclosure can be suitably applied to pneumatic tires although it can be applied to non-pneumatic tires. Taking a pneumatic tire as example the present disclosure will be described.

[0025] FIG. 1 shows a tread portion 2 of a pneumatic tire 1 as an embodiment of the present disclosure.

[0026] In the present embodiment, the tire 1 is designed as a winter tire for passenger cars.

[0027] As shown in FIG. 1, the tread portion 2 is provided, between its tread edges Te, with a plurality of circumferential grooves 3 extending continuously in the tire circumferential direction, and a plurality of land portions 4 axially divided by the circumferential grooves 3.

[0028] The tread edges Te are the axial outermost edges of the ground contacting patch of the tire which occurs when the tire under a standard state is placed on a flat horizontal plane at a camber angle of 0 degrees and loaded with 70% of a standard load.

[0029] In the case that, as in the present embodiment, the tire 1 is a type of pneumatic tire for which various standards have been established, the standard state is a state of the tire which is mounted on a standard wheel rim and inflated to a standard inner pressure but loaded with no tire load.

[0030] In the case that the tire 1 is a tire for which various standards are not yet established, the “standard state” means a standard usage state depending on the purpose of use of the tire and in a condition in which the tire is not attached to a vehicle and no tire load is applied.

[0031] In this application, dimensions and positions of each part or portion of the tire refer to those under the standard state unless otherwise noted.

[0032] The “standard wheel rim” is a wheel rim specified for the tire in a standard system including standards on which the tire is based, for example, the “Standard rim” in JATMA, “Design Rim” in TRA, “Measuring Rim” in ETRTO.

[0033] The “standard inner pressure” is the air pressure specified for the tire in a standard system including standards on which the tire is based, for example, the “maximum air pressure” in JATMA, “INFLATION PRESSURE” in ETRTO, and the maximum air pressure listed in the table “TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES” in TRA.

[0034] In the case that, the tire 1 is a type of pneumatic tire for which various standards have been established, the “standard load” is the load specified for the tire in a standard system including standards on which the tire is based, for example, the “maximum load capacity” in JATMA, “LOAD CAPACITY” in ETRTO, and the maximum tire load listed in the table “TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES” in TRA.

[0035] In the case that the tire 1 is a tire for which various standards are not yet established, the “standard load” refers to the maximum load which can be applied when the tire is used under the

standard usage state, for example, as specified by the tire manufacturer.

[0036] In the present embodiment, the circumferential grooves **3** include two crown circumferential grooves **5** and two shoulder circumferential grooves **6**.

[0037] The two shoulder circumferential grooves **6** are disposed one on each side of the tire equator C.

[0038] The two crown circumferential grooves **5** are disposed one on each side of the tire equator C, between the two shoulder circumferential grooves **6**.

[0039] The distance L1 in the tire axial direction from the groove center line of each crown circumferential groove **5** to the tire equator C is, for example, set in a range from 5% to 15% of the tread width TW.

[0040] The distance L2 in the tire axial direction from the groove center line of each shoulder circumferential groove **6** to the tire equator C is, for example, set in a range from 20% to 35% of the tread width TW.

[0041] Incidentally, the tread width TW is the distance in the tire axial direction between the two tread edges Te measured under the standard state.

[0042] In the present embodiment, the circumferential grooves **3** extend linearly in parallel to the tire circumferential direction.

[0043] The groove width W1 of each circumferential groove **3** in this example is 3.0 mm or more. It is preferable that the groove width W1 of each circumferential groove **3** in this example is set in a range from 3.0% to 6.0% of the tread width TW.

[0044] The depth (not shown) of each circumferential groove **3** in this example is 5.0 to 15.0 mm. When a numerical range of a parameter such as groove width, depth or the like is described in this specification, the numerical range may be applied to the average value of such parameter.

[0045] The land portions **4** include middle land portions **7**. The middle land portion **7** is defined between the axially adjacent crown circumferential groove **5** and shoulder circumferential groove **6**.

[0046] In the present embodiment, two middle land portions **7** are provided so as to locate one on each side of the tire equator C.

[0047] In the present embodiment, the land portions **4** further include two shoulder land portions **9** and one crown land portion **8**.

[0048] The shoulder land portions **9** are axially divided by the respective shoulder circumferential grooves **6** and located axially outside the respective shoulder circumferential grooves **6** so as to include the tread edges Te, respectively.

[0049] The crown land portion **8** is defined between the two crown circumferential grooves **5**. The crown land portion **8** is positioned on the tire equator C. The crown land portion **8** is adjacent to the middle land portions **7** on both sides thereof via the crown circumferential grooves **5**.

[0050] In the present embodiment, the tread portion **2** is provided with a tread pattern which is point symmetrical with respect to a point on the tire equator C. Therefore, the features described for one middle land portion **7** can also be applied to the other middle land portion **7**. The same applies to the two shoulder land portions **9**.

[0051] FIG. **2** shows a top view of a part of one of the middle land portions **7** shown in FIG. **1**.

[0052] As shown in FIG. **2**, the middle land portion **7** is provided with a plurality of communicating sipes **10**, a plurality of axially inner sipes **15**, and a plurality of axially outer sipes **20**.

[0053] In this application, unless otherwise noted, the term “sipe” means a cut having no substantial width or a very narrow groove whose two opposite walls come into contact with each other when ground pressure is applied to the surrounding portion of the sipe of a land portion and thereby can maintain apparent stiffens of the land portion.

[0054] In the present embodiment, the above-mentioned and after-mentioned sipes are those having substantially constant widths from their open tops to bottoms.

[0055] In the present disclosure, however, a sipe may be provided with a variable width as far as the sipe has a main portion in which the two opposite walls extend in the tire radial direction in substantially parallel to each other (for example, with the angle difference of less than 10 degrees), and the width between the two opposite sipe walls is 1.5 mm or less, preferably 0.4 to 1.2 mm, more preferably 0.4 to 1.0 mm.

[0056] In this case, the sipe may be provided with a chamfer to one of or each of the sipe edges and/or a widened part in the bottom portion of the sipe.

[0057] In this application, unless otherwise noted, the term “groove” means a groove in which the opposite groove walls do not come into contact with each other even when ground pressure is applied and which can maintain a substantial drainage path, and in that sense it refers to a groove having a width of 2.0 mm or more.

[0058] The communicating sipe **10** is a sipe extending from the crown circumferential groove **5** to the adjacent shoulder circumferential groove **6**.

[0059] The axially inner sipe **15** is a sipe which communicates with the crown circumferential groove **5** and extends in the tire axial direction, but does not communicate with the shoulder circumferential groove **6**.

[0060] The axially outer sipe **20** is a sipe which communicates with the shoulder circumferential groove **6** and extends in the tire axial direction, but does not communicate with the crown circumferential groove **5**.

[0061] Here, the expression “the sipe communicates with the circumferential groove” includes a case in which a space constituting another groove or recess is interposed between the end of the sipe and the circumferential groove. In this case, the length of the space in the tire axial direction is required to be 5 mm or less.

[0062] The communicating sipes **10** include a plurality of first communicating sipes **11**. FIG. 3 shows the first communicating sipe **11** and its surroundings.

[0063] As shown in FIGS. 2 and 3, each of the first communicating sipes **11** comprises [0064] a first linear portion **26** extending linearly from the crown circumferential groove **5**, and [0065] an axially outer portion **24** extending from the axially outer end of the first linear portion **26** to the shoulder circumferential groove **6**.

[0066] Further, the axially outer portion **24** comprises a first curved portion **27** which curves and extends from the axially outer end of the first linear portion **26** toward the shoulder circumferential groove **6**.

[0067] By adopting the above configurations, the tire **1** according to the present disclosure can exhibit excellent on-snow/ice performance while maintaining dry performance. The reason is as follows.

[0068] In the tire **1** according to the present disclosure, as shown in FIG. 2, the middle land portion **7** is provided with the communicating sipes **10**, the axially outer sipes **20** and the axially inner sipes **15**, as described above. These sipes can provide frictional forces on snowy and icy roads.

[0069] Further, the axially outer sipes **20** and axially inner sipes **15** can prevent the middle land portion **7** from excessive decreasing in rigidity, and help to maintain dry performance.

[0070] Further, in the present disclosure, as shown in FIG. 3, the first communicating sipe **11** comprises the first linear portion **26** and the first curved portion **27**.

[0071] The first linear portion **26** helps to improve the traction performance on snowy and icy roads.

[0072] The first curved portion **27** provides frictional forces in multiple directions. Therefore, steering response on snowy and icy roads is improved.

[0073] As a result, cornering performance on snowy and icy roads can be improved.

[0074] Due to such mechanism, the tire according to the present disclosure can exhibit excellent on-snow/ice performance while maintaining dry performance.

[0075] Hereinafter, more detail of the present embodiment will be described.

[0076] Described below are specific configurations of the present embodiment. Thus, even if the tire does not include the specific configurations described below, the present disclosure may exert the above-mentioned effects.

[0077] If any one of the configurations described below is applied independently to the tire of the present disclosure having the above-mentioned configurations, an improvement of the performance according to each additional configuration can be expected.

[0078] Further, when some of the configurations described below are applied in combination, improvements of respective performances based on the applied configurations can be expected.

[0079] The first linear portion **26** is, for example, inclined at an angle $\theta 1$ with respect to the tire axial direction.

[0080] The angle $\theta 1$ is, for example, 10 to 50 degrees, preferably 25 to 35 degrees.

[0081] The dimension **L3** of the first linear portion **26** in the tire axial direction is, for example, 25% to 40% of the width **W2** (shown in FIG. 2) in the tire axial direction of the ground contacting top surface of the middle land portion **7**.

[0082] Thereby, the traction performance on snowy and icy roads can be reliably improved.

[0083] The first curved portion **27** is a portion of which angle $\theta 2$ with respect to the tire axial direction continuously changes from its end on the first linear portion **26** side toward the shoulder circumferential groove **6**.

[0084] In the present embodiment, the first curved portion **27** has a shape of a circular arc with a single radius of curvature **r1**. But, the first curved portion **27** is not limited to such a shape. The radius of curvature **r1** is, for example, 30 to 50 mm, preferably 33 to 40 mm.

[0085] In the present embodiment, the first communicating sipe **11** is bent at an angle $\theta 3$ between the first linear portion **26** and the first curved portion **27**.

[0086] In the present embodiment, the first linear portion **26** is inclined to one side in the tire circumferential direction toward the outside in the tire axial direction (inclining upward to the left in FIG. 3), and [0087] the first curved portion **27** continued therefrom is curved convexly in an oblique direction (in the upper right direction in FIG. 3) which is toward both the inside in the tire axial direction and the above-said one side in the tire circumferential direction.

[0088] As a result, the angle $\theta 2$ of the first curved portion **27** with respect to the tire axial direction decreases from its end on the first linear portion **26** side toward the shoulder circumferential groove **6**.

[0089] The range of change of the angle $\theta 2$ is, for example, 25 to 75 degrees.

[0090] The angle $\theta 3$ between the first linear portion **26** and the first curved portion **27** is, for example, 90 to 160 degrees, preferably 130 to 140 degrees.

[0091] Such first communicating sipe **11**, when in a state where the two sipe walls are in contact with each other, can effectively suppress shear deformation of the middle land portion **7** and can reliably maintain dry performance.

[0092] It is preferable that the first curved portion **27** extends across the center in the tire axial direction of the ground contacting top surface of the middle land portion **7**. Thus, the first curved portion **27** is formed over a wide range of the middle land portion **7**, and thereby, the steering response on snowy and icy roads is further improved.

[0093] In the present embodiment, the axially outer portion **24** comprises a short linear portion **23** which extends linearly from the first curved portion **27** to the shoulder circumferential groove **6**.

[0094] In the present disclosure, however, the axially outer portion **24** is not limited to such configuration, and it may be composed of only the first curved portion **27** extending from the first linear portion **26** to the shoulder circumferential groove **6**.

[0095] In the present embodiment, as shown in FIG. 2, the communicating sipes **10** include a plurality of second communicating sipes **12**.

[0096] In the middle land portion **7** in the present embodiment, the first communicating sipes **11** and the second communicating sipes **12** are alternately arranged in the tire circumferential

direction.

[0097] FIG. 4 shows one of the second communicating sipes 12 and its surroundings in FIG. 2.

[0098] As shown in FIGS. 2 and 4, each of the second communicating sipes 12 comprises [0099] a second linear portion 28 extending linearly from the shoulder circumferential groove 6, and [0100] an axially inner portion 30 extending from an axially inner end of the second linear portion 28 to the crown circumferential groove 5.

[0101] The axially inner portion 30 includes a second curved portion 31 which curves and extends from the axially inner end of the second linear portion 28.

[0102] Such second communicating sipe 12 can improve on-snow/ice performance while maintaining dry performance, similarly to the first communicating sipe 11,

[0103] The second linear portion 28 has the same features as the first linear portion 26. Therefore, the features of the first linear portion 26 described above can be applied to the second linear portion 28. Thus, the description of the second linear portion 28 is omitted here.

[0104] The second curved portion 31 is a portion of which angle $\theta 4$ with respect to the tire axial direction continuously changes from its end on the second linear portion 28 side toward the crown circumferential groove 5.

[0105] In the present embodiment, the second curved portion 31 has a shape of a circular arc with a single radius of curvature $r2$. But, the second curved portion 31 is not limited to such a shape.

[0106] The radius of curvature $r2$ is, for example, set in a range from 10 to 30 mm, preferably 15 to 25 mm.

[0107] In the present embodiment, the second communicating sipe 12 is bent at an angle $\theta 5$ between the second linear portion 28 and the second curved portion 31.

[0108] In the present embodiment, the second linear portion 28 is inclined similarly to the first linear portion 26, namely, inclined to the above-said one side in the tire circumferential direction toward the outside in the tire axial direction (inclining upward to the left in FIG. 4), and the second curved portion 31 continued therefrom is curved convexly in an oblique direction which is opposite to that of the first curved portion 27.

[0109] As a result, the angle $\theta 4$ of the second curved portion 31 with respect to the tire axial direction decreases from its axially outer end on the second linear portion 28 side toward its end on the crown circumferential groove 5 side.

[0110] The range of change of the angle $\theta 4$ is, for example, set in a range from 25 to 75 degrees. The above-mentioned angle $\theta 5$ between the second linear portion 28 and the second curved portion 31 is, for example, set in a range from 90 to 160 degrees, preferably 130 to 140 degrees.

[0111] Such second communicating sipe 12 can reliably maintain dry performance.

[0112] It is preferable that the second curved portion 31 extends across the center in the tire axial direction of the ground contacting top surface of the middle land portion 7. This makes it easier for a large ground pressure to act on the second curved portion 31. As a result, the second curved portion 31 can easily provide frictional forces in multiple directions, and the steering response on snowy and icy roads can be further improved.

[0113] In the present embodiment, the second curved portion 31 does not extend to the crown circumferential groove 5 (shown in FIG. 2). This means that the axially inner portion 30 includes a third linear portion 32 linearly extending from an axially inner end of the second curved portion 31 to the crown circumferential groove 5.

[0114] The third linear portion 32 is, for example, inclined in the same direction as the second linear portion 28, and the angular difference between them is 10 degrees or less. Preferably, the second linear portion 28 is arranged in parallel with the third linear portion 32.

[0115] The third linear portion 32 is disposed on the shoulder circumferential groove 6 side of the center in the tire axial direction of the middle land portion 7 in its entirety.

[0116] The length of the third linear portion 32 is, for example, 30% to 45% of the entire length of the second communicating sipe 12.

[0117] Such third linear portion **32** helps to improve traction performance on snowy and icy roads.
[0118] As another example, the axially inner portion **30** may be composed of only the second curved portion **31** in its entirety.

[0119] It is preferable that, as shown in FIG. 2, the dimension **L5** in the tire circumferential direction of the axially inner portion **30** is smaller than [0120] the dimension **L4** in the tire circumferential direction of the axially outer portion **24**.

[0121] Specifically, the dimension **L4** of the axially outer portion **24** is set in a range from 50% to 100% of the distance **L6** in the tire circumferential direction from the first communicating sipe **11** to the second communicating sipe **12** measured at the circumferential edge of the middle land portion **7** adjacent to the crown circumferential groove **5**.

[0122] The dimension **L5** of the axially inner portion **30** is set in a range from 50% to 80% of the distance **L6**.

[0123] Thereby, traction performance and cornering performance on snowy and icy roads can be improved in a well-balanced manner.

[0124] Next, regarding the communication sipe **10**, the cross-sectional shape along the length direction will be described.

[0125] Taking the first communicating sipe **11** as an example, its shape will be described. Such description may be applied mutatis mutandis to the second communicating sipe **12**.

[0126] FIG. 5 shows a cross-section taken along line AA in FIG. 3.

[0127] As shown in FIG. 5, the first communicating sipe **11** extends at a constant depth **d2** except for an end portion on the shoulder circumferential groove **6** side.

[0128] The depth **d2** is, for example, set in a range from 80% to 95% of the maximum depth **d1** of the crown circumferential groove **5**.

[0129] In the first communicating sipe **11** in the present embodiment, the depth in the end portion on the shoulder circumferential groove **6** side becomes smaller toward the groove **6**. And the depth **d4** at the end is, for example, in a range from 20% to 35% of the maximum depth **d6** of the shoulder circumferential groove **6**.

[0130] This effectively maintains the rigidity of the middle land portion **7** and helps to improve dry performance.

[0131] As shown in FIG. 2, the axially inner sipes **15** include first inner sipes **16** and second inner sipes **17**.

[0132] The first and second inner sipes **16** and **17** have axially outer ends on the shoulder circumferential groove **6** side which are terminated within the middle land portion and closed.

[0133] The first inner sipes **16** are inclined in the same direction as the first linear portions **26** with respect to the tire axial direction, and [0134] the angular difference therebetween is preferably 10 degrees or less.

[0135] Preferably, the first inner sipes **16** are in parallel with the first linear portions **26**.

[0136] Therefore, the angle $\theta 7$ of the first inner sipes **16** with respect to the tire axial direction is, for example, 10 to 50 degrees, preferably 25 to 35 degrees.

[0137] The first inner sipes **16**, in cooperation with the first linear portions **26**, help to improve traction performance on snowy and icy roads.

[0138] As shown in FIG. 3, the dimension **L8** in the tire axial direction of the first inner sipe **16** is preferably larger than the dimension **L3** in the tire axial direction of the first linear portion **26** when measured in the ground contacting top surface **7s** of the middle land portion **7**.

[0139] More specifically, the dimension **L8** of the first inner sipe **16** is 35% to 50% of the width **W2** (shown in FIG. 2) in the tire axial direction of the ground contacting top surface **7s** of the middle land portion **7**.

[0140] Such first inner sipe **16** improves dry performance and on-snow/ice performance in a well-balanced manner.

[0141] As shown in FIG. 2, in the top view of the middle land portion **7**, the first inner sipe **16** at

least partially overlaps with a virtual region **25** (dotted in FIG. 2) which is formed by extending the axially outer portion **24** toward the crown circumferential groove **5** in parallel to the tire axial direction, in other words, defined by a zone having a circumferential extent same as the circumferential extent (or dimension **L4**) of the axially outer portion **24**.

[0142] It is preferable that the first inner sipe **16** is located within the virtual region **25** in its entirety.

[0143] As a result, the first inner sipe **16** and the first curved portion **27** work together to provide a large frictional force. Thereby, on-snow/ice performance can be further improved.

[0144] From the same point of view, it is preferable that the first inner sipe **16** and the axially outer portion **24** are arranged so that, in the top view of the middle land portion **7**, the entire first inner sipe **16** and an end part on the shoulder circumferential groove **6** side of the axially outer portion **24** are located within a virtual zone **29** (dotted in FIG. 2) which is defined as extending in parallel to the first inner sipe **16** with a constant width **W3** of less than 10 mm.

[0145] With regard to the inclination angle and direction with respect to the tire axial direction, the second inner sipe **17** has the same features as the first inner sipe **16**, therefore, the features of the first inner sipe **16** described above can be applied to the second inner sipe **17**.

[0146] The dimension **L9** in the tire axial direction (shown in FIG. 4) of the second inner sipe **17** is larger than the dimension **L3** in the tire axial direction (shown in FIG. 3) of the first linear portion **26**.

[0147] The dimension **L9** of the second inner sipe **17** is larger than the dimension **L8** (shown in FIG. 3) of the first inner sipe **16**.

[0148] More specifically, the dimension **L9** of the second inner sipe **17** is 60% to 75% of the width **W2** in the tire axial direction (shown in FIG. 2) of the ground contacting top surface **7s** of the middle land portion **7**.

[0149] Such second inner sipe **17** improves dry performance and on-snow/ice performance in a well-balanced manner.

[0150] As shown in FIG. 2, in the top view of the middle land portion **7**, the second inner sipe **17** at least partially overlaps with a virtual region **33** (dotted in FIG. 2) which is formed by extending the axially inner portion **30** of the second communicating sipe **12** toward the crown circumferential groove **5** in parallel to the tire axial direction. It is preferable that 10% to 50% of the total length of the second inner sipe **17** overlaps with the virtual region **33**.

[0151] As a result, the second inner sipe **17** and the axially inner portion **30** work together to provide a large frictional force, and on-snow/ice performance can be further improved.

[0152] The axially outer sipes **20** include first outer sipes **21** and second outer sipes **22**. The first outer sipe **21** has a closed end on the crown circumferential groove **5** side. The second outer sipe **22** has an end on the crown circumferential groove **5** side which communicates with the after-mentioned first middle lateral groove **36**.

[0153] With regard to the inclination angle and direction with respect to the tire axial direction, the first outer sipe **21** and the second outer sipe **22** each have the same features as the first inner sipe **16**, therefore, the features of the first inner sipe **16** described above can be applied to the first outer sipe **21** and the second outer sipe **22**.

[0154] When measured in the ground contacting top surface **7s** of the middle land portion **7**, the dimension **L10** in the tire axial direction (shown in FIG. 3) of the first outer sipe **21** is 35% to 50% of [0155] the maximum width **W2** in the tire axial direction (shown in FIG. 2) of the ground contacting top surface **7s** of the middle land portion **7**.

[0156] The first outer sipe **21** is however, not limited to such configuration.

[0157] In the top view of the middle land portion **7**, the first outer sipe **21** at least partially overlaps with a virtual region **34** (dotted in FIG. 3) which is formed by extending the axially outer portion **24** toward the shoulder circumferential groove **6** in parallel to the tire axial direction.

[0158] It is preferable that the first outer sipe **21** is located within the virtual region **34** in its

entirety.

[0159] As a result, the first outer sipe **21** and the axially outer portion **24** cooperate to provide a large frictional force.

[0160] The middle land portion **7** is provided with a plurality of middle lateral grooves **35**. The middle lateral grooves **35** include first middle lateral grooves **36** and second middle lateral grooves **37**.

[0161] The first middle lateral groove **36** communicates with the crown circumferential groove **5** and extends in the tire axial direction, but does not communicate with the shoulder circumferential groove **6**.

[0162] The second middle lateral groove **37** communicates with the shoulder circumferential groove **6** and extends in the tire axial direction, but does not communicate with the crown circumferential groove **5**.

[0163] In the middle land portion **7** in the present embodiment, the first middle lateral grooves **36** and the second middle lateral grooves **37** are alternately arranged in the tire circumferential direction.

[0164] With regard to the inclination angle and direction with respect to the tire axial direction, the first middle lateral groove **36** and the second middle lateral groove **37** have the same features as the first inner sipe **16**, therefore, the above-described features of the first inner sipe **16** can be applied to the first middle lateral groove **36** and the second middle lateral groove **37**.

[0165] Each of the first middle lateral grooves **36** extends across the center in the tire axial direction of the ground contacting top surface of the middle land portion **7**, and communicates with one of the second outer sipes **22**.

[0166] The dimension **L11** in the tire axial direction of the first middle lateral groove **36** is larger than the dimension **L3** in the tire axial direction (shown in FIG. **3**) of the first linear portion **26** of the first communicating sipe **11** and [0167] larger than the dimension **L8** in the tire axial direction (shown in FIG. **3**) of the first inner sipe **16**.

[0168] Such first middle lateral groove **36** helps to improve on-snow/ice performance while maintaining dry performance.

[0169] In the present embodiment, one of the edges of the first middle lateral groove **36** on the above-said one side in the tire circumferential direction (upper side in FIG. **2**) is made up of [0170] a major part extending substantially linearly along the longitudinal direction of the first middle lateral groove **36**, and [0171] a minor part extending linearly from the major part to the crown circumferential groove **5** at an obtuse angle with respect to the major part.

[0172] The minor part forms an upper side (edge) of a chamfer which is a triangle when viewed in the top view of the middle land portion **7**.

[0173] And the other of the edges of the first middle lateral groove **36** on the other side in the tire circumferential direction (lower side in FIG. **2**) is made up [0174] a major part extending substantially linearly along the longitudinal direction of the first middle lateral groove **36**, and [0175] a minor part extending from the major part to the crown circumferential groove **5** while curving toward the other side in the tire circumferential direction, and increasing the groove width.

[0176] As a result, the first middle lateral groove **36** comprises a constant width portion **36a** extending with a constant groove width, and a widened end portion **36b** extending while increasing the groove width toward the crown circumferential groove **5**.

[0177] Such first middle lateral groove **36** makes it easier to discharge ice and snow packed into the groove during running on snowy and icy roads, which makes it possible to continuously exhibit excellent on-snow/ice performance.

[0178] The second middle lateral groove **37** has a shape which is point symmetrical to the first middle lateral groove **36**. Therefore, the features of the first middle lateral groove **36** described above can be applied mutatis mutandis to the second middle lateral groove **37**.

[0179] In the present embodiment, the middle land portion **7** is provided with circular recesses **40**

which open in the ground contacting top surface **7s**.

[0180] The diameter of each circular recess **40** is, for example, 1.5 to 2.5 mm.

[0181] The depth of each circular recess **40** is, for example, 1.0 to 2.0 mm.

[0182] In this example, the circular recesses **40** include those respectively connected to the first curved portions **27** of the first communicating sipes **11**, and those respectively connected to the second curved portions **31** of the second communicating sipes **12**.

[0183] Such circular recesses **40** can provide multidirectional frictional forces and further enhance on-snow/ice performance.

[0184] FIG. **6** is a partial top of the crown land portion **8** of the tire shown in FIG. **1**. The crown land portion **8** has [0185] a ground contacting top surface **8s** defined between the two crown circumferential grooves **5**, [0186] a first side surface **8a** on one side in the tire axial direction, and [0187] a second side surface **8b** on the other side in the tire axial direction.

[0188] The crown land portion **8** is provided with a plurality of first recesses **41**, a plurality of second recesses **42**, and a plurality of crown communicating sipes **45**.

[0189] The first recess **41** is opened at the ground contacting top surface **8s** and the first side surface **8a**.

[0190] The second recess **42** is opened at the ground contacting top surface **8s** and the second side surface **8b**.

[0191] The crown communicating sipes **45** each extend in the ground contacting top surface **8s** from one of the first recesses **41** to one of the second recesses **42**.

[0192] Such first recesses **41**, second recesses **42** and crown communicating sipes **45** help to improve on-snow/ice performance.

[0193] Each of the crown communicating sipes **45** is arranged so that an imaginary straight line (not shown) drawn between both ends of the crown communicating sipe **45** inclines in the opposite direction to the axially inner sipe **15** (shown in FIG. **2**) (namely, inclines upward to the right in FIG. **6**).

[0194] The crown communicating sipe **45** comprises [0195] an S-shaped portion **47** in which two circular arc portions **46** convex in opposite directions are connected, [0196] a first linear portion extending linearly from one of the ends of the S-shaped portion **47** to the first recess **41**, and [0197] a second linear portion extending linearly from the other of the ends of the S-shaped portion **47** to the second recess **42**.

[0198] Such crown communicating sipe **45** can prevent shear deformation of the crown land portion **8** when the two sipe walls come into contact with each other, and can effectively maintain dry performance.

[0199] FIG. **7** shows a cross section taken along line B-B in FIG. **6**.

[0200] As shown in FIG. **7**, the crown communicating sipe **45** has a greater depth than those of the first and second recesses **41** and **42**.

[0201] The crown communicating sipe **45** has a constant depth **d7** over its entire length.

[0202] The depth **d7** is, for example, 65% to 80% of the maximum depth **d6** of the crown circumferential grooves **5**.

[0203] Such crown communicating sipes **45** help to improve the balance between dry performance and on-snow/ice performance.

[0204] As shown in FIG. **6**, the crown land portion **8** is provided with linearly-extending crown sipes which include a plurality of first crown sipes **51**, a plurality of second crown sipes **52**, and a plurality of third crown sipes **53**.

[0205] Each of the first crown sipes **51** extends from one of the crown circumferential grooves **5** to the other of the crown circumferential grooves **5**.

[0206] Each of the second crown sipes **52** extends from one of the crown circumferential grooves **5** and terminates to have a closed end within the ground contacting top surface **8s**.

[0207] Each of the third crown sipes **53** extends from the other of the crown circumferential

grooves 5 and terminates to have a closed end within the ground contacting top surface 8s.

[0208] The second crown sipes 52 and third crown sipes 53 extend at least to the center in the tire axial direction of the crown land portion 8.

[0209] Such sipe arrangement reliably improves on-snow/ice performance.

[0210] The first crown sipes 51, second crown sipes 52 and third crown sipes 53 are each inclined in the opposite direction to the axially inner sipe 15 (shown in FIG. 2) (namely, inclined upward to the right in FIG. 6).

[0211] The angles $\theta 8$ of the sipes 51, 52 and 53 with respect to the tire axial direction are, for example, set in a range from 20 to 30 degrees.

[0212] Such sipe arrangement improves traction performance and cornering performance on snowy and icy roads in a well-balanced manner.

[0213] FIG. 8 is a partial top view of the shoulder land portion 9 on the left side in FIG. 1. As the shoulder land portion 9 on the right side is point symmetrical, the following description can be applied mutatis mutandis thereto.

[0214] As shown in FIG. 8, the shoulder land portion 9 is provided with a plurality of communicating sipes 54, a plurality of shoulder lateral grooves 55, a plurality of first shoulder sipes 56, and a plurality of second shoulder sipes 57.

[0215] Each of the communicating sipes 54 extends from the shoulder circumferential groove 6 and is terminated to have an axially outer end within the shoulder land portion 9.

[0216] Each of the shoulder lateral grooves 55 extends from the axially outer end of the communicating sipe 54 to at least the tread edge Te.

[0217] Such communicating sipes 54 and shoulder lateral grooves 55 can improve wet performance while suppressing excessive decrease in rigidity of the shoulder land portion 9.

[0218] Each of the first shoulder sipes 56 extends obliquely from the shoulder circumferential groove 6 and is terminated to have an axially outer closed end within the shoulder land portion 9.

[0219] Each of the second shoulder sipes 57 extends from its axially inner closed end to at least the tread edge Te.

[0220] The axially inner closed ends of the second shoulder sipes 57 are respectively disposed axially outward of and adjacently to the axially outer closed ends of the first shoulder sipes 56, and the distances therebetween are 3 mm or less, for example.

[0221] Such sipe arrangement sipes helps to maintain the rigidity of the shoulder land portion 9.

[0222] As a modified example, one first shoulder sipe 56 and one second shoulder sipe 57 may be connected with each other to form one continuous sipe.

[0223] In the present embodiment, each of the first shoulder sipes 56 and the second shoulder sipes 57 extends zigzag in its longitudinal direction.

[0224] This allows the opposite two sipe walls of each sipe to come into contact and engage with each other, therefore, the rigidity of the shoulder land portion 9 is maintained reliably, and excellent dry performance can be exhibited.

[0225] The sipes 56 and 57 are however, not limited to such zigzag shapes. Both or one of the sipe 56 and sipe 57 may be configured as a straight sipe.

[0226] While detailed description has been made of a preferable embodiment of the present disclosure, the present disclosure can be embodied in various forms without being limited to the illustrated embodiment.

Comparison Tests

[0227] A pneumatic tire of size 215/55R17 having the tread pattern shown in FIG. 1 was experimentally manufactured as an example tire according to the present disclosure.

[0228] Further, as a comparative tire, a pneumatic tire of the same size having a tread pattern shown in FIG. 9 was experimentally manufactured, wherein middle land portions (a) were provided with linearly extending communicating sipes (b) as shown, instead of the first communicating sipes 11 and second communicating sipes 12, otherwise same as the example tire.

[0229] Each test tire was mounted on a wheel rim of size 17×7J and inflated to 250 kPa, and installed on all wheels of a 2500 cc front-wheel-drive test car.

[0230] Then, using the test car, the tires were tested for dry performance and on-snow/ice performance as follows.

<Dry Performance>

[0231] During driving the test car on a dry road surface of a tire test course, driving performance was evaluated by a test driver.

[0232] The results are indicated in Table 1 by an index based on the comparative example being 100, wherein the larger the value, the better the dry performance.

<On-Snow/Ice Performance>

[0233] During driving the test car on an icy and snowy road, driving performance was evaluated by a test driver.

[0234] The results are indicated in Table 1 by an index based on the comparative example being 100, wherein the larger the value, the better the on-snow/ice performance.

TABLE-US-00001 TABLE 1 Comparative Tire example Example Tread pattern FIG.9 FIG.1 Dry performance 100 105 On-snow/ice 100 105 Performance

[0235] From the test results, it was confirmed that the example tire was improved in dry performance and on-snow/ice performance as compared to the comparative example tire. This shows that the tire according to the present disclosure can exhibit excellent on-snow/ice performance while maintaining dry performance.

STATEMENT OF THE PRESENT DISCLOSURE

[0236] The present disclosure is as follows.

Present Disclosure 1

[0237] A tire (1) comprising: a tread portion (2) comprising a plurality of circumferential grooves (3) extending continuously in the tire circumferential direction, and a plurality of land portions (4) axially divided by the circumferential grooves (3), wherein [0238] the circumferential grooves (3) include a crown circumferential groove (5), and a shoulder circumferential groove (6) disposed axially outside the crown circumferential groove (5) adjacently thereto, [0239] the land portions (4) include a middle land portion (7) defined between the crown circumferential groove (5) and the shoulder circumferential groove (6), [0240] the middle land portion (7) is provided with [0241] a plurality of communicating sipes (10) extending from the crown circumferential groove (5) to the shoulder circumferential groove (6), [0242] a plurality of axially inner sipes (15) extending axially outwards from the crown circumferential groove (5) and terminated without reaching the shoulder circumferential groove (6), and [0243] a plurality of axially outer sipes (20) extending axially inwards from the shoulder circumferential groove (6) and terminated without reaching the crown circumferential groove (5), and [0244] the communicating sipes (10) include a plurality of first communicating sipes (11), each of the first communicating sipes (11) comprising [0245] a first linear portion (26) extending linearly axially outward from the crown circumferential groove (5), and [0246] a first curved portion (27) extending curvedly from an axially outer end of the first linear portion (26) toward the shoulder circumferential groove (6).

Present Disclosure 2

[0247] The tire according to Present Disclosure 1, wherein [0248] the communicating sipes (10) include a plurality of second communicating sipes (12), each of the second communicating sipes (12) comprises [0249] a second linear portion (28) extending linearly axially inward from the shoulder circumferential groove (6), and [0250] an axially inner portion (30) extending from an axially inner end of the second linear portion (28) to the crown circumferential groove (5), and the axially inner portion (30) includes [0251] a second curved portion (31) which curves and extends from the axially inner end of the second linear portion (28).

Present Disclosure 3

[0252] The tire according to Present Disclosure 2, wherein [0253] each of the first communicating

sipes (11) comprises an axially outer portion (24) extending from the axially outer end of the first linear portion (26) to the shoulder circumferential groove (6), [0254] the axially outer portion (24) includes the above-said first curved portion (27), and a dimension (L5) in the tire circumferential direction of the axially inner portion (30) is smaller than a dimension (L4) in the tire circumferential direction of the axially outer portion (24).

Present Disclosure 4

[0255] The tire according to Present Disclosure 2 or 3, wherein [0256] the dimension (L4) in the tire circumferential direction of the axially outer portion (24) is 50% to 100% of a distance (L6) in the tire circumferential direction from the first communicating sipe (11) to the second communicating sipe (12) when measured at a circumferential edge of the middle land portion (7) adjacent to the crown circumferential groove (5), and the dimension (L5) in the tire circumferential direction of the axially inner portion (30) is 10% to 50% of the above-said distance (L6) in the tire circumferential direction.

Present Disclosure 5

[0257] The tire according to any one of Present Disclosures 2 to 4, wherein [0258] the axially inner portion (30) includes a third linear portion (32) extending linearly from an axially inner end of the second curved portion (31) to the crown circumferential groove (5).

Present Disclosure 6

[0259] The tire according to any one of Present Disclosures 1 to 5, wherein [0260] the first communicating sipe (11) is bent at an angle $\theta 3$ between the first linear portion (26) and the first curved portion (27).

Present Disclosure 7

[0261] The tire according to any one of Present Disclosures 1 to 6, wherein [0262] the first curved portion (27) extends across the center in the tire axial direction of the ground contacting top surface (7s) of the middle land portion (7).

Present Disclosure 8

[0263] The tire according to any one of Present Disclosures 1 to 7, wherein [0264] the axially outer sipes (20) include first outer sipes (21) whose ends on the crown circumferential groove side are closed, and [0265] in a top view of the middle land portion (7), each first outer sipe (21) is disposed within a virtual region which is formed by extending one of the first curved portions (27) toward the shoulder circumferential groove (6) in parallel to the tire axial direction.

Present Disclosure 9

[0266] The tire according to any one of Present Disclosures 1 to 8, wherein [0267] the axially inner sipes (15) include first inner sipes (16) whose ends on the shoulder circumferential groove side are closed, and [0268] in a top view of the middle land portion (7), each first inner sipe (16) is disposed within a virtual region which is formed by extending one of the first curved portions (27) toward the crown circumferential groove (5) in parallel to the tire axial direction.

Present Disclosure 10

[0269] The tire according to Present Disclosure 9, wherein [0270] the axially inner sipes (15) include second inner sipes (17) whose ends on the shoulder circumferential groove side are closed, and [0271] a dimension (L9) in the tire axial direction of the second inner sipe (17) is greater than a dimension (L8) in the tire axial direction of the first inner sipe (16).

Present Disclosure 11

[0272] The tire according to any one of Present Disclosures 1 to 10, wherein [0273] the land portions (4) include a single crown land portion (8) defined between two crown circumferential grooves (5) which are disposed one on each side of the tire equator (C), the crown land portion (8) has a ground contacting top surface (8s) defined between the two crown circumferential grooves (5), a first side surface (8a) on one side in the tire axial direction, and a second side surface (8b) on the other side in the tire axial direction, the crown land portion (8) is provided with [0274] a plurality of first recesses (41) opening in the ground contacting top surface (8s) and the first side

surface (8a); [0275] a plurality of second recesses (42) opening in the ground contacting top surface (8s) and the second side surface (8b); and [0276] a plurality of crown communicating sipes (45) extending from the first recesses (41) to the second recesses (42).

Present Disclosure 12

[0277] The tire according to Present Disclosure 11, wherein [0278] each of the crown communicating sipes (45) comprises an S-shaped portion (47) in which two circular arc portions convex in opposite directions are connected.

DESCRIPTION OF THE REFERENCE SIGNS

[0279] **2** tread portion [0280] **3** circumferential groove [0281] **4** land portion [0282] **5** crown circumferential groove [0283] **6** shoulder circumferential groove [0284] **7** middle land portion [0285] **10** communicating sipe [0286] **11** first communicating sipe [0287] **15** axially inner sipe [0288] **20** axially outer sipe [0289] **26** first linear portion [0290] **27** first curved portion

Claims

1. A tire comprising: a tread portion comprising a plurality of circumferential grooves extending continuously in the tire circumferential direction, and a plurality of land portions axially divided by the circumferential grooves, wherein the circumferential grooves include a crown circumferential groove, and a shoulder circumferential groove disposed axially outside the crown circumferential groove adjacently thereto, the land portions include a middle land portion defined between the crown circumferential groove and the shoulder circumferential groove, the middle land portion is provided with a plurality of communicating sipes extending from the crown circumferential groove to the shoulder circumferential groove, a plurality of axially inner sipes extending axially outwards from the crown circumferential groove and terminated without reaching the shoulder circumferential groove, and a plurality of axially outer sipes extending axially inwards from the shoulder circumferential groove and terminated without reaching the crown circumferential groove, and the communicating sipes include a plurality of first communicating sipes, each of the first communicating sipes comprising a first linear portion extending linearly axially outward from the crown circumferential groove, and a first curved portion extending curvedly from an axially outer end of the first linear portion toward the shoulder circumferential groove.
2. The tire according to claim 1, wherein the communicating sipes include a plurality of second communicating sipes, each of the second communicating sipes comprises a second linear portion extending linearly axially inward from the shoulder circumferential groove, and an axially inner portion extending from an axially inner end of the second linear portion to the crown circumferential groove, and the axially inner portion includes a second curved portion which curves and extends from the axially inner end of the second linear portion.
3. The tire according to claim 2, wherein each of the first communicating sipes comprises an axially outer portion extending from the axially outer end of the first linear portion to the shoulder circumferential groove, the axially outer portion includes the above-said first curved portion, and a dimension (L5) in the tire circumferential direction of the axially inner portion is smaller than a dimension (L4) in the tire circumferential direction of the axially outer portion.
4. The tire according to claim 3, wherein in the middle land portion, the first communicating sipes and the second communicating sipes are alternately arranged in the tire circumferential direction, and the first curved portion of each first communicating sipe is convex toward an oblique direction with respect to the tire axial direction the second curved portion of each second communicating sipe is convex toward an oblique direction with respect to the tire axial direction which is opposite to that of the first curved portion.
5. The tire according to claim 3, wherein the dimension (L4) in the tire circumferential direction of the axially outer portion is 50% to 100% of a distance (L6) in the tire circumferential direction from the first communicating sipe to the second communicating sipe when measured at a

circumferential edge of the middle land portion adjacent to the crown circumferential groove, and the dimension (L5) in the tire circumferential direction of the axially inner portion is 10% to 50% of the above-said distance (L6) in the tire circumferential direction.

6. The tire according to claim 5, wherein in the middle land portion, the first communicating sipes and the second communicating sipes are alternately arranged in the tire circumferential direction, and the first curved portion of each first communicating sipe is convex toward an oblique direction with respect to the tire axial direction the second curved portion of each second communicating sipe is convex toward an oblique direction with respect to the tire axial direction which is opposite to that of the first curved portion.

7. The tire according to claim 5, wherein the axially inner portion includes a third linear portion extending linearly from an axially inner end of the second curved portion to the crown circumferential groove.

8. The tire according to claim 7, wherein in the middle land portion, the first communicating sipes and the second communicating sipes are alternately arranged in the tire circumferential direction, and the first curved portion of each first communicating sipe is convex toward an oblique direction with respect to the tire axial direction the second curved portion of each second communicating sipe is convex toward an oblique direction with respect to the tire axial direction which is opposite to that of the first curved portion.

9. The tire according to claim 7, wherein the first communicating sipe is bent at an angle $\theta 3$ between the first linear portion and the first curved portion.

10. The tire according to claim 1, wherein the first curved portion extends across the center in the tire axial direction of the ground contacting top surface of the middle land portion.

11. The tire according to claim 1, wherein the axially outer sipes include first outer sipes whose ends on the crown circumferential groove side are closed, and in a top view of the middle land portion, each first outer sipe is disposed within a virtual region which is formed by extending one of the first curved portions toward the shoulder circumferential groove in parallel to the tire axial direction.

12. The tire according to claim 1, wherein the axially inner sipes include first inner sipes whose ends on the shoulder circumferential groove side are closed, and in a top view of the middle land portion, each first inner sipe is disposed within a virtual region which is formed by extending one of the first curved portions toward the crown circumferential groove in parallel to the tire axial direction.

13. The tire according to claim 11, wherein the axially inner sipes include first inner sipes whose ends on the shoulder circumferential groove side are closed, and in a top view of the middle land portion, each first inner sipe is disposed within a virtual region which is formed by extending one of the first curved portions toward the crown circumferential groove in parallel to the tire axial direction.

14. The tire according to claim 12, wherein the axially inner sipes include second inner sipes whose ends on the shoulder circumferential groove side are closed, and a dimension (L9) in the tire axial direction of the second inner sipe is greater than a dimension (L8) in the tire axial direction of the first inner sipe.

15. The tire according to claim 13, wherein the axially inner sipes include second inner sipes whose ends on the shoulder circumferential groove side are closed, and a dimension (L9) in the tire axial direction of the second inner sipe is greater than a dimension (L8) in the tire axial direction of the first inner sipe.

16. The tire according to claim 1, wherein the land portions include a single crown land portion defined between two crown circumferential grooves which are disposed one on each side of the tire equator (C), the crown land portion has a ground contacting top surface defined between the two crown circumferential grooves, a first side surface on one side in the tire axial direction, and a second side surface on the other side in the tire axial direction, and the crown land portion is

provided with a plurality of first recesses opening in the ground contacting top surface and the first side surface; a plurality of second recesses opening in the ground contacting top surface and the second side surface; and a plurality of crown communicating sipes extending from the first recesses to the second recesses.

17. The tire according to claim 6, wherein the land portions include a single crown land portion defined between two crown circumferential grooves which are disposed one on each side of the tire equator (C), the crown land portion has a ground contacting top surface defined between the two crown circumferential grooves, a first side surface on one side in the tire axial direction, and a second side surface on the other side in the tire axial direction, and the crown land portion is provided with a plurality of first recesses opening in the ground contacting top surface and the first side surface; a plurality of second recesses opening in the ground contacting top surface and the second side surface; and a plurality of crown communicating sipes extending from the first recesses to the second recesses.

18. The tire according to claim 8, wherein the land portions include a single crown land portion defined between two crown circumferential grooves which are disposed one on each side of the tire equator (C), the crown land portion has a ground contacting top surface defined between the two crown circumferential grooves, a first side surface on one side in the tire axial direction, and a second side surface on the other side in the tire axial direction, and the crown land portion is provided with a plurality of first recesses opening in the ground contacting top surface and the first side surface; a plurality of second recesses opening in the ground contacting top surface and the second side surface; and a plurality of crown communicating sipes extending from the first recesses to the second recesses.

19. The tire according to claim 16, wherein each of the crown communicating sipes comprises an S-shaped portion in which two circular arc portions convex in opposite directions are connected.

20. The tire according to claim 18, wherein each of the crown communicating sipes comprises an S-shaped portion in which two circular arc portions convex in opposite directions are connected.
