

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276626

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

TAKEDA; Jun et al.

VEHICLE SEAT

Abstract

A vehicle seat includes a seatback that supports a back of a seated occupant from a seat rear side, a back frame that configures a framework of the seatback and that includes an insertion portion, and a lumbar support that is arranged at a position facing a lumbar region of the seated occupant in a seat front-rear direction within the seatback. The vehicle seat includes a wire that extends from the lumbar support toward an insertion portion side and that is anchored at the insertion portion in a state of being inserted into the insertion portion. A notch that is directly or indirectly anchored at an edge of the insertion portion when the lumbar support is pressed toward the seat rear side is formed at the wire.

Inventors: TAKEDA; Jun (Yokohama-shi, JP), ODA; Mitsuaki (Yokohama-shi, JP), FUKUSHIMA; Masato (Tokyo, JP)

Applicant: NHK SPRING CO., LTD. (Yokohama-shi, JP); SUBARU CORPORATION (Tokyo, JP)

Family ID: 96881766

Appl. No.: 19/058783

Filed: February 20, 2025

Foreign Application Priority Data

JP	2024-030578	Feb. 29, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: B60N2/66 (20060101); B60N2/42 (20060101); B60N2/427 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2024-030578 filed on Feb. 29, 2024, the disclosure of which is incorporated by reference herein.

BACKGROUND

Technical Field

[0002] The present disclosure relates to a vehicle seat.

Related Art

[0003] Japanese Patent Application Laid-Open (JP-A) No. 2011-136649 discloses a vehicle seat including a lumbar support (posture holding member) that supports a lumbar region of a seated occupant. Wires extending toward a back frame side are anchored at the lumbar support described in this document. Further, the lumbar support is supported by the back frame via the wires, due to the wires being inserted into holes (axial support portions) formed at the back frame.

[0004] During a rear-end collision of the vehicle, the lumbar support is pressed with strong force toward a seat rear side. Therefore, it is important to prevent the wires supporting the lumbar support from coming loose from the back frame, but the configuration described in Japanese Patent Application Laid-Open (JP-A) No. 2011-136649 has room for improvement in this respect.

SUMMARY

[0005] The present disclosure obtains a vehicle seat that is capable of preventing a wire supporting a lumbar support from coming loose from a back frame.

[0006] A vehicle seat of a first aspect includes: a seatback that supports a back of a seated occupant from a seat rear side; a back frame that configures a framework of the seatback and that includes an insertion portion; a lumbar support that is arranged at a position facing a lumbar region of the seated occupant in a seat front-rear direction within the seatback; and a wire that extends from the lumbar support toward an insertion portion side and that is anchored at the insertion portion in a state of being inserted into the insertion portion, a notch that is directly or indirectly anchored at an edge of the insertion portion when the lumbar support is pressed toward the seat rear side being formed at the wire.

[0007] In the vehicle seat of the first aspect, the back of the seated occupant is supported from the seat rear side by the seatback, and the lumbar region of the seated occupant is supported from the seat rear side by the lumbar support. The wire extends from the lumbar support, and is anchored at the insertion portion of the back frame in a state in which the wire is inserted into the insertion portion. Consequently, the lumbar support is supported by the back frame via the wire. When the lumbar support is pressed toward the seat rear side during a rear-end collision of the vehicle, the notch formed at the wire is directly or indirectly anchored at the edge of the insertion portion. Consequently, the wire that supports the lumbar support can be prevented from coming loose from the back frame.

[0008] A vehicle seat of a second aspect is the vehicle seat of the first aspect, wherein a bushing is attached to the edge of the insertion portion, and, when a force with which the lumbar support is pressed toward the seat rear side exceeds a predetermined load, the bushing is broken, and the notch is directly anchored at the edge of the insertion portion.

[0009] In the vehicle seat of the second aspect, the bushing is attached to the edge of the insertion portion. When a force with which the lumbar support is pressed toward the seat rear side exceeds

the predetermined load, the bushing is broken, and the notch is directly anchored at the edge of the insertion portion. Due to the notch being configured to be directly anchored at the edge of the insertion portion in this manner, the wire that supports the lumbar support can be more robustly prevented from coming loose from the back frame.

[0010] A vehicle seat of a third aspect is the vehicle seat of the first aspect, wherein a bushing that includes a portion formed in a shape that gradually narrows on progression toward a direction in which the wire is inserted into the insertion portion is attached to the edge of the insertion portion.

[0011] In the vehicle seat of the third aspect, the bushing is attached to the edge of the insertion portion. The bushing includes the portion formed in a shape that gradually narrows on progression toward the direction in which the wire is inserted into the insertion portion. Therefore, when the wire is inserted into the insertion portion, a leading end of the wire can be guided toward the insertion portion side along the aforementioned portion of the bushing. Consequently, workability when inserting the wire into the insertion portion can be improved.

[0012] The vehicle seat according to the present disclosure has an effect in that it is capable of preventing a wire supporting a lumbar support from coming loose from a back frame.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] An exemplary embodiment of the present disclosure will be described in detail based on the following figures, wherein:

[0014] FIG. 1 is a side view schematically illustrating a vehicle seat according to the present exemplary embodiments;

[0015] FIG. 2 is a front view illustrating a lumbar unit that is supported by a back frame;

[0016] FIG. 3 is an enlarged perspective view illustrating a vicinity of an upper side anchoring portion of a support wire in an enlarged manner;

[0017] FIG. 4 is a cross-sectional view illustrating the support wire, an intermediate frame portion, and a bushing at a portion corresponding to the upper side anchoring portion of the support wire in a cross-section taken along a front-rear direction and an up-down direction;

[0018] FIG. 5 is a cross-sectional view corresponding to FIG. 4 and illustrates a state at a time when a vehicle has undergone a rear-end collision.

DETAILED DESCRIPTION

[0019] A vehicle seat **10** according to an exemplary embodiment of the present disclosure will be explained, with reference to FIGS. 1 to 5. It should be noted that, in the drawings, arrow FR indicates a seat front side, arrow UP indicates a seat upper side, arrow LH indicates a seat width direction left side, and arrow RH indicates a seat width direction right side, respectively. Further, unless specifically stated otherwise, in the following explanation, reference to front-rear, up-down, and left-right directions refers to front and rear in a seat front-rear direction, up and down in a seat up-down direction, and left and right in a seat width direction.

[0020] As illustrated in FIG. 1, the vehicle seat **10** of the present exemplary embodiment includes a seat cushion **12** that supports buttocks of a seated occupant from a lower side, a seatback **14** that supports a back of the seated occupant from a rear side, and a lumbar support unit **16** that is provided within the seatback **14**.

[0021] As illustrated in FIGS. 1 and 2, the seatback **14** is configured to include a back frame **18** that configures a framework of the seatback **14**, and a back pad **20** that is attached to the back frame **18**.

[0022] The back frame **18** is provided with a left and right pair of side frame portions **22** that are arranged at an interval in the seat width direction and that extend in the up-down direction. Further, the back frame **18** includes an upper frame portion **24** that connects upper end portions of the left and right pair of side frame portions **22** in the seat width direction, and a lower frame portion **26**

that connects lower end portions of the left and right pair of side frame portions **22** in the seat width direction. Moreover, the back frame **18** includes an intermediate frame portion **28** that connects upper side portions of the left and right pair of side frame portions **22** in the seat width direction at a lower side of the upper frame portion **24**.

[0023] The intermediate frame portion **28** is formed, for example, by performing press working or the like on a steel plate material. The intermediate frame portion **28** includes a base plate portion **30** that extends in the left-right direction. Both left-right direction end portions **30A** of the base plate portion **30** are offset toward a front side with respect to a left-right direction intermediate portion **30B** of the base plate portion **30**. Both of the left-right direction end portions **30A** of the base plate portion **30** are joined to the left and right pair of side frame portions **22** by welding or the like. Further, the intermediate frame portion **28** is provided with a lower flange portion **32** that extends toward the front side from a lower end of the left-right direction intermediate portion **30B**.

[0024] As illustrated in FIG. 2, the lumbar support unit **16** is configured to include a lumbar support **34** that is arranged at a position facing a lumbar region of the seated occupant in the front-rear direction within the seatback **14**, and a support wire **36** serving as a wire for allowing the back frame **18** to support the lumbar support **34**.

[0025] The lumbar support **34** includes a lumbar plate **38** that is formed using, for example, a resin material. The lumbar plate **38** is formed in a rectangular shape in a seat front view, is formed in a plate shape with a thickness direction thereof being along the front-rear direction, and has a configuration in which weight-reduction punching is appropriately performed at both left and right end portions and a center portion. Further, the lumbar support **34** includes a first fixing member **40**, a second fixing member **42**, and a third fixing member **44** that extend in the left-right direction at a rear side of the lumbar plate **38** and that are arranged at intervals in the up-down direction. The first fixing member **40** is fixed to an upper end portion of the lumbar plate **38**. Furthermore, the second fixing member **42** is fixed to a center portion in the up-down direction of the lumbar plate **38**. Moreover, the third fixing member **44** is fixed to a lower end portion of the lumbar plate **38**. Further, the lumbar support **34** is provided with an actuator portion **46** that is provided at the rear side of the lumbar plate **38**. The actuator portion **46** is supported in a state in which it is spanned between the second fixing member **42** and the third fixing member **44**. Due to actuation of the actuator portion **46**, the interval in the up-down direction between the second fixing member **42** and the third fixing member **44** is changed, and the shape of the lumbar plate **38** is changed.

[0026] The support wire **36** is formed, for example, by performing bending work or the like on a rod-shaped steel material, and is bent into substantially a U-shape and a shape having left-right symmetry, with an upper side thereof being open in a seat front view. Respective portions of the support wire **36** are respectively anchored to the first fixing member **40**, the second fixing member **42**, and the third fixing member **44**. A length direction center portion **36A** of the support wire **36** is arranged at a lower side of the lumbar plate **38** in a seat front view. Further, the length direction center portion **36A** of the support wire **36** is fixed to the lower frame portion **26** via a bracket **48**. Furthermore, an end portion **36B** at one side of the support wire **36** extends toward an upper side with respect to an end portion at a left side of the first fixing member **40**. Moreover, an end portion **36B** at the other side of the support wire **36** extends toward the upper side with respect to an end portion at a right side of the first fixing member **40**.

[0027] As illustrated in FIGS. 2 and 3, the end portion **36B** at the one side of the support wire **36** and the end portion **36B** at the other side of the support wire **36** are respectively anchored to both seat width direction end portions of the lower flange portion **32** of the intermediate frame portion **28**. It should be noted that a configuration of an anchoring portion between the end portion **36B** at the one side of the support wire **36** and the end portion at the left side of the lower flange portion **32**, and a configuration of an anchoring portion between the end portion **36B** at the other side of the support wire **36** and the end portion at the right side of the lower flange portion **32**, are configurations that are the same as each other. Thus, in the following explanation, the configuration

of the anchoring portion between the end portion 36B at the one side of the support wire 36 and the end portion at the left side of the lower flange portion 32 will be explained, and explanation regarding the configuration of the anchoring portion between the end portion 36B at the other side of the support wire 36 and the end portion at the right side of the lower flange portion 32 will be omitted.

[0028] As illustrated in FIGS. 3 and 4, the lower flange portion 32 is inclined toward the lower side on progression toward the rear side. An insertion hole 32A, serving as an insertion portion into which the end portion 36B at the one side of the support wire 36 is inserted from the lower side, is formed at the end portion at the left side of the lower flange portion 32 so as to penetrate the lower flange portion 32. A shape of an edge of the insertion hole 32A as viewed from a thickness direction of the lower flange portion 32 is a circular shape. It should be noted that, in the following explanation, an insertion direction of the end portion 36B at the one end of the support wire 36 into the insertion hole 32A is simply referred to as an insertion direction A (arrow A direction) in some cases.

[0029] A bushing 50 is attached to a circumference of the insertion hole 32A in the lower flange portion 32. The bushing 50 is formed in a tube shape using, for example, a resin material. The bushing 50 includes a first tube-shaped portion 52 that is formed in a tube shape, and a second tube-shaped portion 54 that is formed in a tube shape and connected to the first tube-shaped portion 52 at a lower side of the first tube-shaped portion 52. The first tube-shaped portion 52 and the second tube-shaped portion 54 are coaxially arranged. An outer diameter of the first tube-shaped portion 52 is set to be smaller than an outer diameter of the second tube-shaped portion 54. Further, an inner face of the first tube-shaped portion 52 has a first tapered face 52A that gradually narrows on progression toward the second tube-shaped portion 54 side. Furthermore, an inner face of the second tube-shaped portion 54 has a second tapered face 54A that gradually narrows on progression toward the first tube-shaped portion 52 side. A connecting portion between the first tapered face 52A and the second tapered face 54A at an inner peripheral portion of the bushing 50 is configured as a corner portion 56 having a shape that is pointed toward a radial direction inner side of the bushing 50. The bushing 50 explained above is attached to the lower flange portion 32 due to the first tube-shaped portion 52 being inserted into the insertion hole 32A formed at the lower flange portion 32 from the lower side. It should be noted that attachment of the bushing 50 to the lower flange portion 32 is completed in a state in which the second tube-shaped portion 54 is in contact with a lower face of the lower flange portion 32. In a state in which attachment of the bushing 50 to the lower flange portion 32 has been completed, the corner portion 56 of the bushing 50 is arranged at a radial direction inner side of the edge of the insertion hole 32A.

[0030] As illustrated in FIG. 4, a notch 36C having a shape that is concave toward a center portion side of the support wire 36 is formed at a rear portion of the end portion 36B at the one side of the support wire 36. An amount of concavity of the notch 36C with respect to an outer peripheral face of the support wire 36 becomes gradually deeper on progression toward the insertion direction A side. The end portion 36B at the one side of the support wire 36 explained above is inserted from the lower side into the insertion hole 32A formed at the end portion at the left side of the lower flange portion 32 and into the bushing 50 attached to the lower flange portion 32. Consequently, anchoring of the end portion 36B at the one side of the support wire 36 to the lower flange portion 32 is completed. In a state in which anchoring of the end portion 36B at the one side of the support wire 36 to the lower flange portion 32 has been completed, a lower end portion of the notch 36C formed at the rear portion of the end portion 36B at the one side of the support wire 36 is arranged proximate to the corner portion 56 of the bushing 50 in the front-rear direction.

Operation and Advantageous Effects of Present Exemplary Embodiment

[0031] Next, operation and advantageous effects of the present exemplary embodiment will be explained.

[0032] As illustrated in FIGS. 1 and 2, in the vehicle seat 10 of the present exemplary embodiment,

the buttocks of the seated occupant are supported from the lower side by the seat cushion **12**, and the back of the seated occupant is supported from the rear side by the seatback **14**. Further, the lumbar region of the seated occupant is supported from the rear side by the lumbar support **34** via the back pad **20**. When the actuator portion **46** of the lumbar support **34** is actuated, the interval in the up-down direction between the second fixing member **42** and the third fixing member **44** is changed, and the shape of the lumbar plate **38** is changed. Consequently, a state of support of the lumbar region by the lumbar plate **38** can be adjusted according to a body type or preference of the seated occupant.

[0033] It should be noted that the lumbar support **34** is supported by the back frame **18** via the support wire **36**. As illustrated in FIGS. **3** and **4**, the end portion **36B** at the one end of the support wire **36** is inserted from the lower side into the insertion hole **32A** that is formed at the end portion at the left side of the lower flange portion **32** and into the bushing **50** that is attached to the end portion at the left side of the lower flange portion **32**. Although not illustrated in the drawings, the end portion **36B** at the other side of the support wire **36** is inserted from the lower side into the insertion hole **32A** that is formed at the end portion at the right side of the lower flange portion **32** and into the bushing **50** that is attached to the end portion at the right side of the lower flange portion **32**.

[0034] When the lumbar support **34** is pressed toward the rear side during a rear-end collision of the vehicle, the notch **36C** that is formed at the support wire **36** is anchored at the corner portion **56** of the bushing **50** as illustrated in FIG. **5**. That is to say, the notch **36C** formed at the support wire **36** is indirectly anchored at the edge of the insertion hole **32A** via the bushing **50**. Consequently, the support wire **36** supporting the lumbar support **34** can be prevented from coming loose from the back frame **18** (the insertion hole **32A**). Further, due to this configuration, it is unnecessary to increase an insertion amount of the support wire **36** into the insertion hole **32A** in order to prevent the support wire **36** from coming loose from the insertion hole **32A**. As a result, a protrusion amount of the support wire **36** toward the upper side with respect to the lower flange portion **32** can be reduced. As a result, a volume (capacity) occupied by the support wire **36** in a space within the seatback **14** can be reduced.

[0035] Further, in the present exemplary embodiment, when a force with which the lumbar support **34** is pressed toward the rear side exceeds a predetermined threshold value during a rear-end collision of the vehicle, the bushing **50** is broken (destroyed), and the notch **36C** that is formed at the support wire **36** is directly anchored at the edge of the insertion hole **32A**. Due to the notch **36C** being configured to be directly anchored at the edge of the insertion hole **32A** in this manner, the support wire **36** that supports the lumbar support **34** can be more robustly prevented from coming loose from the back frame **18** (the insertion hole **32A**).

[0036] Furthermore, in the present exemplary embodiment, as illustrated in FIGS. **3** and **4**, the inner face of the second tube-shaped portion **54** of the bushing **50** has the second tapered face **54A** that gradually narrows on progression toward the first tube-shaped portion **52** side (the insertion direction A side). Due to this configuration, when the support wire **36** is inserted into the insertion hole **32A**, a leading end **36D** of the support wire **36** can be guided toward the insertion hole **32A** side along the second tapered face **54A**. Consequently, workability when inserting the support wire **36** into the insertion hole **32A** can be improved.

[0037] It should be noted that, although an example in which the second tapered face **54A** that functions as described above is provided at the bushing **50** has been explained in the present exemplary embodiment, the present disclosure is not limited thereto. Whether or not the second tapered face **54A** that functions as described above is to be provided at the bushing **50** may be appropriately determined in consideration of an assembly process or the like of the vehicle seat **10**.

[0038] Further, although an example in which the bushing **50** is broken (destroyed) and the notch **36C** that is formed at the support wire **36** is directly anchored at the edge of the insertion hole **32A** when a force with which the lumbar support **34** is pressed toward the rear side exceeds a

predetermined threshold value has been explained in the present exemplary embodiment, the present disclosure is not limited thereto. For example, by increasing a strength of the bushing **50**, a configuration can be provided in which the bushing **50** does not break during a rear-end collision of the vehicle. Further, a configuration can also be provided in which the notch **36C** that is formed at the support wire **36** is directly anchored at the edge of the insertion hole **32A**, without providing the bushing **50**.

[0039] Although exemplary embodiments of the present disclosure have been explained above, the present disclosure is not limited to that which has been described above, and it is obvious that various modifications other than those described above can also be made to implement the present disclosure, within a range that does not depart from the spirit thereof.

Claims

1. A vehicle seat comprising: a seatback that supports a back of a seated occupant from a seat rear side; a back frame that configures a framework of the seatback and that includes an insertion portion; a lumbar support that is arranged at a position facing a lumbar region of the seated occupant in a seat front-rear direction within the seatback; and a wire that extends from the lumbar support toward an insertion portion side and that is anchored at the insertion portion in a state of being inserted into the insertion portion, a notch that is directly or indirectly anchored at an edge of the insertion portion when the lumbar support is pressed toward the seat rear side being formed at the wire.
 2. The vehicle seat according to claim 1, wherein: a bushing is attached to the edge of the insertion portion, and when a force with which the lumbar support is pressed toward the seat rear side exceeds a predetermined load, the bushing is broken, and the notch is directly anchored at the edge of the insertion portion.
 3. The vehicle seat according to claim 1, wherein a bushing that includes a portion formed in a shape that gradually narrows on progression toward a direction in which the wire is inserted into the insertion portion is attached to the edge of the insertion portion.
-