

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396466
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Henley; Jason et al.

Removal of insolubles from aqueous streams used in food processing

Abstract

A food processing system includes at least one receptacle containing a composition of water and insoluble solids, a centripetal force-based solid/liquid separator having an inlet, a solids outlet, and a liquid outlet, and a pump able to direct the composition from the receptacle to the inlet of the separator. The separator is configured to separate the composition into a solids stream including the insoluble solids and a liquid stream including water and to direct the solids stream through the solids outlet and the liquid stream through the liquid outlet.

Inventors: Henley; Jason (Searcy, AR), Huff; Steve (Sherwood, AR), Coleman; Todd (Batesville, AR)

Applicant: SAFE FOODS CORPORATION (North Little Rock, AR)

Family ID: 1000008778305

Assignee: Safe Foods Corporation (North Little Rock, AR)

Appl. No.: 18/405669

Filed: January 05, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240156114 A1	May. 16, 2024

Related U.S. Application Data

division parent-doc US 17759477 US 11918002 WO PCT/US2021/015649 20210129 child-doc US 18405669
us-provisional-application US 62967793 20200130

Publication Classification

Int. Cl.: A22B5/08 (20060101); A22C17/08 (20060101); A22C21/00 (20060101); A22C21/04 (20060101); B01D17/02 (20060101); B01D21/26 (20060101); C02F11/127 (20190101); C02F103/22 (20060101)

U.S. Cl.:

CPC A22C17/08 (20130101); A22B5/08 (20130101); A22C21/0061 (20130101); A22C21/04 (20130101); B01D17/0208 (20130101); B01D21/262 (20130101); C02F11/127 (20130101); C02F2103/22 (20130101)

Field of Classification Search

CPC: A22B (5/0082); A22B (5/08); A22C (17/08); A22C (21/0061); A22C (21/04); B01D (17/0208); B01D (21/262); C02F (11/127); C02F (2103/22)

USPC: 452/74; 452/123

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4852215	12/1988	Covell, III	N/A	N/A
5605503	12/1996	Martin	N/A	N/A
6142861	12/1999	Buhot	452/78	A22B 5/08
6395181	12/2001	Mullerheim	N/A	N/A
6802984	12/2003	Perkins et al.	N/A	N/A
6986910	12/2005	Howarth	N/A	N/A
7963828	12/2010	Roth et al.	N/A	N/A
2003/0205514	12/2002	Potter et al.	N/A	N/A
2007/0141973	12/2006	Howarth	N/A	N/A
2008/0076619	12/2007	Scott et al.	N/A	N/A
2010/0317271	12/2009	Roth et al.	N/A	N/A
2011/0027437	12/2010	Liimatta	N/A	N/A
2015/0313247	12/2014	Nicholson	N/A	N/A
2018/0370809	12/2017	Lee et al.	N/A	N/A
2019/0194081	12/2018	Bhalla et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101445296	12/2008	CN	N/A
101921044	12/2009	CN	N/A
105347443	12/2015	CN	N/A
107082528	12/2016	CN	N/A
108675519	12/2017	CN	N/A
208471704	12/2018	CN	N/A
110698030	12/2019	CN	N/A
NC2024/0005392	12/2023	CO	N/A
2509137	12/2013	GB	N/A

261837	12/2018	IL	N/A
WO 2017/112605	12/2016	WO	N/A
WO 2019/035999	12/2018	WO	N/A
WO 2020/058971	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of the International Searching Authority issued by the U.S. Patent and Trademark Office for International Application No. PCT/US2021/015649 dated Apr. 12, 2021. (8 pages). cited by applicant

First Examination Report for Saudi Arabian Patent Application No. 522433433, prepared by Saudi Authority for Intellectual Property, dated Jul. 25, 2023, (14 pgs.). cited by applicant

First Examiner's Requisition for Canadian Patent Application No. 3,166,154, prepared by the Canadian Patent Office, dated Oct. 5, 2023, (3 pgs.). cited by applicant

Office Action for Colombian Patent Application No. NC2022/0010385 prepared by the Colombian Patent and Trademark Office dated Jan. 9, 2025. (9 pgs.). cited by applicant

Second Examination Report for Saudi Arabian Patent Application No. 522433433 prepared by Saudi Authority for Intellectual Property dated Feb. 5, 2024. (10 pgs.). cited by applicant

Second Office Action for Colombian Patent Application No. NC2022/0010385 prepared by the Colombian Patent and Trademark Office dated May 19, 2025. (11 pgs.). cited by applicant

Primary Examiner: Parsley; David J

Attorney, Agent or Firm: Haynes and Boone, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. Nonprovisional patent application Ser. No. 17/759,477 filed Jul. 26, 2022, titled "REMOVAL OF INSOLUBLES FROM AQUEOUS STREAMS USED IN FOOD PROCESSING," which is a U.S. National Stage patent application of International Patent Application No. PCT/US2021/015649 filed Jan. 29, 2021, titled "REMOVAL OF INSOLUBLES FROM AQUEOUS STREAMS USED IN FOOD PROCESSING," which claims benefit of U.S. Provisional Patent Application No. 62/967,793 filed Jan. 30, 2020, titled "Removal of Insolubles from Aqueous Streams used in Poultry Processing," the disclosures of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(1) The present application relates to removal of insoluble materials from aqueous streams used in food processing. More particularly, the application relates to removal of insoluble materials from aqueous streams used in poultry processing using a centripetal force-based solid/liquid separator.

BACKGROUND OF THE DISCLOSURE

(2) Poultry processing establishments transform a live animal to a whole bird or individual parts for consumption by the general population. The process of this transformation requires multiple unit operations that involve large volumes of water. During the various processing steps, the water streams become contaminated with solids such as feathers, ingesta, and fecal matter as well as insoluble liquids such as lipids.

(3) In order to ensure a safer food supply for the general population, the United States Department of Agriculture (USDA) has established microbial performance standards for these establishments. Antimicrobial interventions are used at the various unit operations to aid in microbial reduction,

allowing the establishments to achieve the performance standards. However, the presence of solid and liquid contaminants from the process can also interact with the antimicrobials, especially oxidizers such as peracetic acid (PAA), rendering the antimicrobials less effective. In addition, the solids, such as feathers and fecal matter, contain bacteria that can increase the microbial load that will need to be treated downstream. Solids, such as ingesta, and liquids, such as insoluble fat, can serve as food sources for microbes. These issues can increase the difficulty for establishments to achieve the USDA microbial performance standards. A need remains for a unit operation to remove solids and insoluble liquids from the aqueous processing streams in order to diminish the challenge of reducing the microbial load.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a food processing system according to an embodiment of the present disclosure.
- (2) FIG. 2 is a schematic diagram of a food processing system according to an embodiment of the present disclosure.
- (3) FIG. 3 is a schematic diagram of a food processing system according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

(4) Embodiments of the present disclosure relate to removal of insoluble materials from aqueous streams used in food processing. While the present disclosure is described herein with reference to illustrative embodiments for particular applications, it should be understood that embodiments are not limited thereto. Other embodiments are possible, and modifications can be made to the embodiments within the spirit and scope of the teachings herein and additional fields in which the embodiments would be of significant utility.

(5) In a typical poultry processing plant, scalding systems are used to open the feather follicle pores of poultry workpieces prior to feather removal. A typical scalding system includes one or more scalding tanks filled with water that has been heated to a temperature of generally about 125 to about 135° F. During the scalding process, feed and fecal material become dislodged in the heated scalding water. As the feed and fecal matter is dense, the majority of the matter will sink to the bottom of the scalding tank and, in conventional processes, accumulate over the processing day which is typically a period of about sixteen hours. The feed and fecal matter may, and usually does, contain a microbial load. The temperature of the scalding system is also conducive to microbial growth of the contaminants that enter the system with the harvested birds. In conventional scalding processes, during the sixteen-hour processing day, solid contaminants build-up in volume and microbial growth takes place; the solids are eventually removed at the end of the processing day by draining the water and manually shoveling out the solids. In such processes, maintaining a low microbial load is difficult due to the presence of solids (such as feathers, fecal matter, and ingesta) and insoluble liquids (such as insoluble fats) in the aqueous processing streams.

(6) Referring to FIG. 1, a scalding system **100** according to an embodiment of the present disclosure is capable of removing solids from aqueous streams in order to avoid the unwanted effects detailed above. In operation of the scalding system **100**, recently harvested poultry workpieces, contaminated with feed and fecal matter, are placed on a shackle line (not shown) and travel in the direction of arrow B through the scalding system **100**. The poultry workpieces enter the first scalding tank **10a** and traverse through the second scalding tank **10b** and third scalding tank **10c** before exiting the scalding system. Water is added to the scalding system in a counter-current method, as indicated by arrow A. The water may be maintained at a temperature of, for example, 100 to 150° F., 110 to 140° F., or 125 to 135° F. The water enters the third scalding tank **10c** as shown by line **12** and

overflows into the second scalder tank **10b** as shown by line **14**. Scalder water in the second scalder tank **10b** overflows into the first scalder tank **10a** as shown by line **16**. Although three scalder tanks **10a**, **10b**, **10c** are shown in FIG. **1**, the scalder system **100** according to the present disclosure may have one or more scalder tanks.

(7) A pump **24a** directs scalder water from the first scalder tank **10a** to a centripetal force-based solid/liquid separator (“SL separator”) **20a** via line **18**. In one or more embodiments, a portion of the scalder water in the first scalder tank **10a** overflows and exits to a waste treatment system (not shown). The pump **24a** is appropriately sized to deliver a raw feed stream to a stationary conical-shaped housing of the SL separator **20a**. The raw feed stream is an aqueous stream containing insolubles (solids and/or liquids). The SL separator **20a** uses centripetal force to cause heavier-than-water solids within the raw feed stream to drop to the bottom of the conical-shaped housing while the liquid, free of heavier-than-water solids, (“solids-free water”) exits the top of the SL separator **20a** via line **22**. The solids-free water may be either 1) returned to one of the scalder tanks **10a**, **10b**, **10c** or 2) transferred to a liquid/liquid decanter, as described in more detail below. A small liquid stream containing solids is discharged from the bottom of the SL separator **20a** via line **26a** and directed to a waste collection site **28**.

(8) According to one or more embodiments, the SL separator **20a** has no moving parts, thereby reducing maintenance costs. In such embodiments, the pump **24a** supplies the proper velocity to obtain the centripetal force needed to separate the solids from the liquid.

(9) Specifications for the SL separator **20a** (such as height and width) and pump **24a** are designed based on the specific inputs (e.g., water usage, bird size of each plant, % solids, and % insoluble liquid) to produce a continuous operating system. For example, in an embodiment, the pump **24a** is a 5 HP centrifugal pump capable of pumping at 50-100 gallons/min (gpm), and the pump **24a** delivers liquid from the first scalder tank **10a** into the SL separator **20a** at a pressure of 25-50 psig through line **18**, which is 1-2” in diameter. In said embodiment, the SL separator **20a** has a 4-6” diameter conical body with a height of 12-25”, the discharge line **22** has a diameter of 1-2”, and the discharge line **26a** has a diameter of 0.5-1”.

(10) According to one or more embodiments, a volume of make-up water may also be added to the third scalder tank **10c** via line **12** in order to maintain a constant water volume in the scalder system **100**. In some embodiments, the ratio of the discharge streams from the SL separator **20a** through line **26a** and line **22** is 50:50, 30:70, 25:70, 20:80, or 5:95.

(11) The scalder system **100** according to FIG. **1** is capable of removing up to 90% of the dislodged solids from the first scalder tank **10a**, thereby reducing the probability of microbial growth and contamination in the first scalder tank **10a**. Removal of the solids also reduces the amount of labor required to shovel out solids at the end of a sixteen-hour processing day. Although FIG. **1** depicts the SL separator **20a** as being in communication with the first scalder tank **10a**, the system **100** is not so limited and the SL separator **20a** may be in communication with any scalder tank. However, in general, the first scalder tank **10a** contains the largest amount of insoluble solids and liquids. In any embodiment, a plurality of SL separators **20a** may be employed and each SL separator **20a** may include one or more pumps **24a**, as needed to provide appropriate hydraulic volume, flow, and pressure requirements.

(12) Turning to FIG. **2**, an alternative scalder system **200** is illustrated. In the scalder system **200**, a plurality of SL separator **20a**, **20b**, **20c** are employed, each of which being associated with a single scalder tank **10a**, **10b**, **10c**, respectively. A pump **24c** directs scalder water from the third scalder tank **10c** via line **32** to SL separator **20c**. A solids-containing stream exits SL separator **20c** via line **26c** and a solids-free stream exits via line **34c**. A pump **24b** directs scalder water from the second scalder tank **10b** via line **30** to SL separator **20b**. A solids-containing stream exits SL separator **20b** via line **26b** and a solids-free stream exits via line **34b**. As in system **100**, a pump **24a** directs scalder water from the first scalder tank **10a** via line **18** to SL separator **20a**. A solids-containing stream exits SL separator **20a** via line **26a** and a solids-free stream exits via line **34a**. Each of the

pumps **24a**, **24b**, **24c** may be the same or different. For example, in view of the generally decreasing amount of insolubles as the poultry workpieces move through the scalding system **200**, pump **24a** may be configured to pump a larger amount of liquid than pump **24b** and pump **24b** may be configured to pump a larger amount of liquid than pump **24c**. Each of the SL separators **20a**, **20b**, **20c** may be the same or different. For instance, the SL separator **20a** may be configured to process a larger volume than SL separator **20b** and SL separator **20b** may be configured to process a larger volume than SL separator **20c**.

(13) According to one or more embodiments, a volume of make-up water may also be added to the third scalding tank **10c** via line **12** in order to maintain a constant water volume in the scalding system **200**. In some embodiments, the ratio of the discharge streams from each SL separator **20a**, **20b**, **20c** through lines **26a**, **26b**, **26c** and lines **34a**, **34b**, **34c** is 50:50, 30:70, 25:70, 20:80, or 5:95.

(14) As shown in FIG. 2, solids-free water from SL separator **20a** may be directed through a common header **22** into any of the first, second, or third scalding tanks **10a**, **10b**, **10c** via lines **22a**, **22b**, **22c**, respectively. Similarly, solids-free water from SL separator **20b** may be directed through a common header **22** into either of the second or third scalding tanks **10b**, **10c** via lines **22b**, **22c**, respectively. In some embodiments, all of the solids-free water from SL separators **20a**, **20b**, **20c** is directed to the third scalding tank **10c**. In any embodiment, a volume of makeup water may be supplied to any of the scalding tanks **10a**, **10b**, **10c** to maintain a constant volume.

(15) Specifications for the SL separators **20a**, **20b**, **20c** (such as height and width) and pumps **24a**, **24b**, **24c** are designed based on the specific inputs (e.g., water usage, bird size of each plant, % solids, and % insoluble liquid) to produce a continuous operating system. For example, in an embodiment, each pump **24a**, **24b**, **24c** is a 5 HP centrifugal pump capable of pumping at 50-100 gpm, and each pump **24a**, **24b**, **24c** delivers liquid from the respective scalding tank **10a**, **10b**, **10c** into the respective SL separators **20a**, **20b**, **20c** at a pressure of 25-50 psig through line **18**, **30**, **32** having a 1-2" diameter. In this embodiment, each SL separator **20a**, **20b**, **20c** has a 4-6" diameter conical body with a height of 12-25", the discharge lines **34a**, **34b**, **34c** each have a diameter of 1-2", and the discharge lines **26a**, **26b**, **26c** each have a diameter of 0.5-1".

(16) In any embodiment, the scalding system **200** may include any number of scalding tanks (e.g., 1, 2, 3, 4, 5, or 6 or more) and each scalding tank may have 0, 1, 2, or 3 or more SL separators in fluid communication therewith, as needed to provide adequate removal of insolubles. In any embodiment, each SL separator may include one or more pumps, as needed to provide appropriate hydraulic volume, flow, and pressure requirements.

(17) The scalding system **200** according to FIG. 2 is capable of removing up to 90% of the dislodged solids from each scalding tank **10a**, **10b**, **10c** thereby reducing the probability of microbial growth and contamination in the scalding tanks **10a**, **10b**, **10c**. Removal of the solids also reduces the amount of labor required to shovel out solids at the end of a sixteen-hour processing day.

(18) In some embodiments, any of the SL separators **20a**, **20b**, **20c** can be used in conjunction with a liquid/liquid decanter ("LL decanter") **40**, an example of which is shown in FIG. 3, to remove lighter-than-water insoluble liquid and solids from the aqueous stream. The LL decanter **40** is a tank or widened pipe that collects and retains a feed stream containing two immiscible liquids. According to embodiments of the present disclosure, the feed stream may be scalding water from a scalding tank (**10a**, **10b**, **10c**) or the solids-free water from a SL separator (**20a**, **20b**, **20c**). The feed stream enters the LL decanter and is retained for a pre-determined period of time (i.e., a resonance time). During the resonance time, the insoluble liquids of the feed stream separate, with the less dense liquid rising to the top of the LL decanter while the denser liquid sinks to the bottom. The liquids are removed at their respective locations via piping for discharge to collection vessels or recycling back to the process. In particular, the lighter-than-water insoluble liquid (and lighter-than-water solids) rises to the top of the LL decanter **40** and is removed at a steady rate via line **52** to a collection center. The lower water exits the LL decanter **40** at the bottom and returns via line **48** to the application point (e.g., a scalding tank or chiller (described below)). In one or more

embodiments, the LL decanter **40** may include a manual discharge valve on line **48** that may be throttled to control the volume in LL decanter **40** and the location of the interface between the two liquid phases within the LL decanter **40**. According to one or more embodiments, a volume ratio of the streams through line **52** and line **48** may be 50:50, 30:70, 25:70, 20:80, or 5:95.

(19) The LL decanter **40** may be used in any embodiment disclosed herein. In some embodiments, a plurality of LL decanters **40** may be employed. For example, each SL separator **20a**, **20b**, **20c** may be paired with one or more LL decanter **40** or a single LL decanter **40** may be coupled to a plurality of SL separators **20a**, **20b**, **20c**.

(20) Turning again to FIG. 3, also described herein is a chiller system **300** used to cool processed poultry workpieces to below 40° F. The chiller system **300** includes a chiller unit **50** having up to three chiller tanks filled with cooled water, supplied at least in part by line **36**. In one or more embodiments, the chiller unit **50** includes three tanks, wherein the temperature of the water in the first tank is 55-60° F., the temperature of the water in the second tank is 40-55° F., and the temperature of the water in the third tank is less than 40° F. In another embodiment, the chiller unit **50** includes a single tank filled with water at a temperature of less than 40° F. or a single tank having a temperature gradient along its length such that one end has a water temperature of less than 40° F. The chiller unit **50** includes, in each tank, an agitation system well known to those of ordinary skill in the art, such as a rocking arm or a screw-shaft mechanism. In some embodiments, compressed air is also pumped into the bottom of the tanks of the chiller unit **50** as an agitation source.

(21) According to one or more embodiments, poultry workpieces enter the chiller unit **50** via a ramp **38**. The combination of the agitation systems transfers poultry workpieces, along with carry-over water, through each tank of the chiller unit **50**. The chilled poultry workpieces then exit at a discharge **44**. In embodiments where the chiller unit **50** includes three tanks, the residence time in each tank may be, for example, 60-90 minutes. In such embodiments, as the water level in the third tank increases, the water is transferred back to the second tank and/or the first tank. In any embodiment, as needed, make-up water may be added to the chiller unit in any of the tanks.

(22) As the processed poultry workpieces enter the chiller system **300**, certain material can become dislodged from the carcasses. The material may include viscera, entrails, skin, fats, and digesta. Most of the material is dislodged and accumulates near a front end of the chiller unit **50** (e.g., in the first tank). As the organic load in the chiller unit **50** increases from the dislodged material, operational issues can occur such as foaming and decreased antimicrobial efficacy.

(23) In order to avoid accumulation of the organic load in the chiller unit **50**, the chiller system **300** of the present disclosure employs SL separator **20a** and, optionally, LL decanter **40** to remove insolubles from the aqueous stream. The SL separator **20a** and LL decanter **40** are described in detail above. As shown in FIG. 3, pump **24a** directs liquid from the chiller unit **50** to the SL separator **20a** via line **42**. The pump **24a** is described in detail above. The SL separator **20a** uses centripetal force to cause heavier-than-water solids within the raw feed stream to drop to the bottom of the conical-shaped housing while the liquid, free of heavier-than-water solids, ("solids-free water") exits the top of the SL separator **20a** via line **46**. The solids-free water may be either 1) returned to the chiller unit **50** (not shown in FIG. 3) or 2) transferred to the LL decanter **40**. A small liquid stream containing solids is discharged from the bottom of the SL separator **20a** via line **26a** and directed to a waste collection site **28**.

(24) Although the above embodiments have been directed to processing poultry workpieces, the systems and methods described herein may be applied to other food products, such as beef, pork, fruits and vegetables. Additionally, the SL separator and, optionally, the LL decanter described herein may be used in any food processing operation wherein separation of insolubles from an aqueous stream is required.

(25) A system for processing food has been disclosed herein. The food processing system, comprises: at least one receptacle containing a composition comprising water and insoluble solids;

a centripetal force-based solid/liquid separator comprising an inlet, a solids outlet, and a liquid outlet; and a pump configured to direct the composition from the receptacle to the inlet of the separator; wherein the separator is configured to separate the composition into a solids stream comprising the insoluble solids and a liquid stream comprising water and to direct the solids stream through the solids outlet and the liquid stream through the liquid outlet.

(26) The system may include any of the following features: the insoluble solids comprise poultry feed, fecal matter, viscera, entrails, skin, fats, and/or digesta; the pump is a centrifugal pump configured to direct the composition into the inlet of the separator at sufficient pressure to induce centrifugal separation of the solid stream and the liquid stream; the receptacle is a scalding tank and the composition is at a temperature of 100 to 150° F.; a second scalding tank containing a second composition comprising water and insoluble solids; a second centripetal force-based solid/liquid separator comprising an inlet, a solids outlet, and a liquid outlet; and a second pump configured to direct the composition from the receptacle to the inlet of the second separator; wherein the second separator is configured to separate the composition into a solids stream comprising the insoluble solids and a liquid stream comprising water and to direct the solids stream through the solids outlet and the liquid stream through the liquid outlet; a liquid/liquid decanter coupled to the liquid outlet of the separator; wherein the composition further comprises insoluble liquids; and wherein the decanter is configured to separate the liquid stream from the separator into a water stream and an insoluble liquid stream; the decanter is in fluid communication with the scalding tank and configured to direct the water stream to the scalding tank; the liquid outlet of the separator is in fluid communication with the receptacle and configured to direct the liquid stream to the receptacle; the receptacle is a chiller tank and wherein the composition is at a temperature of less than 40° F.; a liquid/liquid decanter coupled to the liquid outlet of the separator; wherein the composition further comprises insoluble liquids; and wherein the decanter is configured to separate the liquid stream from the separator into a water stream and an insoluble liquid stream; and/or the liquid outlet of the separator is in fluid communication with the chiller tank and configured to direct the liquid stream to the chiller tank.

(27) A method of scalding poultry workpieces has been disclosed herein. The method includes: immersing the workpieces in a scalding tank containing water, wherein, during the immersing step, insoluble solids are dislodged from the workpieces and deposited in the scalding tank; using a pump to direct water and the insoluble solids from the scalding tank to a solid/liquid separator; using the separator to remove the insoluble solids from the water; and recycling the water from the separator.

(28) The method may include any of the following features: the pump is a centrifugal pump configured to direct the water and insoluble solids into the separator at sufficient pressure and speed to induce centrifugal separation of the insoluble solids and the water; wherein during the immersing step, insoluble liquids from the workpieces are deposited into the scalding tank; wherein the water leaving the separator contains the insoluble liquids; the method further comprising: directing the water from the separator to a liquid/liquid decanter; separating the insoluble liquids from the water; and returning the water from the decanter to the scalding tank; immersing the workpieces in a second scalding tank; and overfilling the second scalding tank with fresh water such that it overflows into the first scalding tank.

(29) A method of chilling poultry workpieces has been disclosed herein. The method comprises: immersing the workpieces in a chiller tank containing water at a temperature of less than 40° F., wherein immersing the workpieces dislodges insoluble solids that are deposited in the chiller tank; using a pump, directing the water and insoluble solids from the chiller tank to a separator; using the separator, separating the insoluble solids from the water; disposing of the insoluble solids; and recycling the water.

(30) The method may include any of the following features: wherein the pump is a centrifugal pump capable of pumping at 50-100 gallons/min; and wherein directing the water and insoluble solids comprises pumping the water and insoluble solids into the separator at a pressure of 25-50

psig; wherein the separator is a stationary conical-shaped housing; directing the water from the separator to a decanter, wherein the water comprises insoluble liquids; separating the water and the insoluble liquids; and returning the water to the chiller tank; supplying fresh water to the chiller tank to maintain a constant volume within the chiller tank.

(31) The above specific example embodiments are not intended to limit the scope of the claims. The example embodiments may be modified by including, excluding, or combining one or more features or functions described in the disclosure. The description of the present disclosure has been presented for purposes of illustration and description but is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the disclosure. The illustrative embodiments described herein are provided to explain the principles of the disclosure and the practical application thereof, and to enable others of ordinary skill in the art to understand that the disclosed embodiments may be modified as desired for a particular implementation or use. The scope of the claims is intended to broadly cover the disclosed embodiments and any such modification.

Claims

1. A method of scalding poultry workpieces, comprising immersing the workpieces in a first scalding tank containing water, wherein, during the immersing step, insoluble solids are dislodged from the workpieces and deposited in the scalding tank to create an aqueous composition comprising the water, the insoluble solids and insoluble liquids; using a centrifugal pump to direct the aqueous composition from the first scalding tank to an inlet of a centripetal force-based solid/liquid separator at a sufficient pressure and velocity to induce centrifugal separation of heavier-than-water insoluble solids from the aqueous composition in the separator; using the separator to separate the heavier-than-water insoluble solids from the aqueous composition to create a solids stream comprising the heavier-than-water insoluble solids and a liquid stream comprising the water, the insoluble liquids and lighter-than-water insoluble solids, wherein the solids stream is directed through a solids outlet of the separator and the liquid stream is directed through a liquid outlet of the separator to a liquid/liquid decanter; using the liquid/liquid decanter to separate the insoluble liquids and the lighter-than-water insoluble solids from the water; and returning the water from the liquid/liquid decanter to the first scalding tank.
 2. The method of claim 1, further comprising: immersing the workpieces in a second scalding tank; and overfilling the second scalding tank with fresh water such that it overflows into the first scalding tank.
 3. The method of claim 1, wherein the water in the scalding tank is heated to a temperature of from 100 to 150° F.
 4. The method of claim 1, wherein the water in the scalding tank is heated to a temperature of from 110 to 140° F.
 5. The method of claim 1, wherein the water in the scalding tank is heated to a temperature of from 125 to 135° F.
 6. The method of claim 1, wherein the centrifugal pump directs the water and insoluble solids from the scalding tank to the separator at a velocity of from 50 to 100 gallons per minute and at a pressure of from 25 to 50 psig.
-