

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396634
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kuroda; Yohei et al.

Medical observation device, observation device, observation method, and adapter

Abstract

There is provided a medical observation device that includes an imaging unit that can image an environment inside an abdominal cavity of a living body, and the imaging unit includes a plurality of first pixels that are aligned in a matrix, and an event detection unit that detects a luminance change amount of light incident on each of the plurality of first pixels exceeds a predetermined threshold.

Inventors:	Kuroda; Yohei (Tokyo, JP), Katsuki; Shinji (Tokyo, JP), Tomatsu; Kei (Tokyo, JP), Katsuki; Yugo (Tokyo, JP), Nagao; Daisuke (Tokyo, JP)
Applicant:	SONY GROUP CORPORATION (Tokyo, JP)
Family ID:	1000008778287
Assignee:	SONY GROUP CORPORATION (Tokyo, JP)
Appl. No.:	18/264385
Filed (or PCT Filed):	January 21, 2022
PCT No.:	PCT/JP2022/002276
PCT Pub. No.:	WO2022/172733
PCT Pub. Date:	August 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240090759 A1	Mar. 21, 2024

Foreign Application Priority Data

Publication Classification**Int. Cl.:** A61B1/313 (20060101); A61B1/00 (20060101); H04N25/47 (20230101)**U.S. Cl.:****CPC** A61B1/3132 (20130101); A61B1/00179 (20130101); H04N25/47 (20230101);**Field of Classification Search****CPC:** A61B (1/3132); A61B (1/00179); A61B (1/000095); A61B (1/042); A61B (1/045); H04N (25/47); H04N (23/555)**USPC:** 348/68

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0292258	12/2010	Adler	348/263	H10F 39/8053
2013/0038708	12/2012	Iwasaki	348/E7.085	A61B 1/00188
2016/0000307	12/2015	Akimoto	600/109	A61B 1/000094
2016/0094796	12/2015	Govil	348/295	H04N 25/707
2018/0295298	12/2017	Zamir	N/A	H04N 25/533
2018/0344284	12/2017	Freudenberger	N/A	G06N 3/045
2019/0043583	12/2018	Majumder	N/A	G11C 15/04
2019/0167377	12/2018	Hirose	N/A	G02B 21/0012
2020/0160813	12/2019	Aurongzeb	N/A	G09G 3/36
2020/0315432	12/2019	Tully	N/A	N/A
2020/0410272	12/2019	Seo	N/A	G06V 10/22
2021/0152757	12/2020	Wakabayashi	N/A	H04N 25/51
2022/0150424	12/2021	Numata	N/A	H04N 25/47
2022/0172375	12/2021	Seo	N/A	H04N 25/46
2023/0300282	12/2022	Seo	348/294	H04N 25/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3090680	12/2019	EP	N/A
2020-025263	12/2019	JP	N/A
2020-127186	12/2019	JP	N/A
2016/129160	12/2015	WO	N/A
2016/129162	12/2015	WO	N/A
WO-2020116185	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of PCT Application No. PCT/JP2022/002276, issued on Apr. 12, 2022, 09 pages of ISRWO. cited by applicant

Primary Examiner: Matt; Marnie A

Attorney, Agent or Firm: CHIP LAW GROUP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Phase of International Patent Application No. PCT/JP2022/002276 filed on Jan. 21, 2022, which claims priority benefit of Japanese Patent Application No. JP 2021-020822 filed in the Japan Patent Office on Feb. 12, 2021. Each of the above-referenced applications is hereby incorporated herein by reference in its entirety.

FIELD

(2) The present disclosure relates to a medical observation device, an observation device, an observation method, and an adapter.

BACKGROUND

(3) In recent years, in endoscopic surgery, surgery is performed while imaging an inside of an abdominal cavity of a patient using an endoscope, and displaying on a display the captured image imaged by the endoscope. For example, following Patent Literature 1 and following Patent Literature 2 disclose techniques of endoscopes.

CITATION LIST

Patent Literature

(4) Patent Literature 1: WO 2016/129162 A

(5) Patent Literature 2: WO 2016/129160 A

SUMMARY

Technical Problem

(6) However, the above-described conventional techniques have limits in robustly and highly accurately measuring and recognizing in real time a subject such as an environment inside an abdominal cavity having a restriction.

(7) Therefore, the present disclosure proposes a medical observation device, an observation device, an observation method, and an adapter that enable real-time, robust, and highly accurate measurement and recognition of a subject.

Solution to Problem

(8) According to the present disclosure, there is provided a medical observation device including an imaging unit that can image an environment inside an abdominal cavity of a living body. In the medical observation device, the imaging unit includes: a plurality of first pixels that are aligned in a matrix, and an event detection unit that detects that a luminance change amount of light incident on each of the plurality of first pixels exceeds a predetermined threshold.

(9) Furthermore, according to the present disclosure, there is provided an observation device including: an imaging unit; and an image detection unit. In the observation device, the imaging unit includes a plurality of first pixels that are aligned in a matrix, and an event detection unit that detects that a luminance change amount of light incident on each of the plurality of first pixels exceeds a predetermined threshold. The image detection unit includes a plurality of second pixels that are aligned in a matrix, and detects an image that is based on the light incident on each of the

plurality of second pixels.

(10) Furthermore, according to the present disclosure, there is provided an observation method includes: by a medical observation device that can image an environment inside an abdominal cavity of a living body, detecting luminance of light incident on each of a plurality of first pixels aligned in a matrix; calculating a change amount of the luminance; and determining whether or not the change amount exceeds a predetermined threshold.

(11) Furthermore, according to the present disclosure, there is provided an adapter includes: a plurality of second pixels aligned in a matrix, and is inserted between a camera head unit and an optical system, the camera head unit includes an image detection unit that detects an image that is based on light incident on each of the plurality of second pixels, and the optical system guides the light to the camera head unit. The adapter includes an imaging unit that can image an environment inside an abdominal cavity of a living body. In the adapter, the imaging unit includes: a plurality of first pixels that are aligned in a matrix, and an event detection unit that detects that a luminance change amount of light incident on each of the plurality of first pixels exceeds a predetermined threshold.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating an example of a schematic configuration of an endoscopic surgery system to which a technique according to the present disclosure is applicable.

(2) FIG. 2 is a view illustrating an example of an image of a laparoscopic environment.

(3) FIG. 3 is a block diagram illustrating an example of a configuration of an EVS **200** used in embodiments of the present disclosure.

(4) FIG. 4 is a block diagram illustrating an example of a configuration of a pixel **302** located in a pixel array unit **300** in the EVS **200** illustrated in FIG. 3.

(5) FIG. 5 is a diagram illustrating an example of a configuration of a medical observation system **10** according to a first embodiment of the present disclosure.

(6) FIG. 6 is an explanatory view for describing an example of a configuration of a camera head **100** and an optical system **400** illustrated in FIG. 5.

(7) FIG. 7 is an explanatory view for describing another example of the configuration of the camera head **100** according to the first embodiment of the present disclosure.

(8) FIG. 8 is a block diagram illustrating an example of a functional block configuration of the medical observation system **10** according to the first embodiment of the present disclosure.

(9) FIG. 9 is a flowchart of a control method according to the first embodiment of the present disclosure.

(10) FIG. 10 is an explanatory view for describing the control method according to the first embodiment of the present disclosure.

(11) FIG. 11 is an explanatory view for describing motion compensation of the control method according to the first embodiment of the present disclosure.

(12) FIG. 12 is a functional block diagram illustrating main components of a CCU **500** according to a first modified example according to the first embodiment of the present disclosure.

(13) FIG. 13 is an explanatory view for describing an example of a configuration of a camera head **100** according to a second embodiment of the present disclosure.

(14) FIG. 14 is an explanatory view for describing an example of a configuration of an adapter **150** according to a third embodiment of the present disclosure.

(15) FIG. 15 is a flowchart of an image recognition method according to a first example of a fourth embodiment of the present disclosure.

(16) FIG. 16 is an explanatory view for describing the first example of the fourth embodiment of

the present disclosure.

(17) FIG. **17** is a flowchart of an image recognition method according to a second example of the fourth embodiment of the present disclosure.

(18) FIG. **18** is an explanatory view for describing an image recognition method according to the second example of the fourth embodiment of the present disclosure.

(19) FIG. **19** is a flowchart of an image recognition method according to a fifth embodiment of the present disclosure.

(20) FIG. **20** is an explanatory view for describing the fifth embodiment of the present disclosure.

(21) FIG. **21** is a hardware configuration diagram illustrating an example of a computer that implements a CCU **500** according to the embodiments of the present disclosure.

DESCRIPTION OF EMBODIMENTS

(22) Hereinafter, preferred embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. Note that, in the description and the drawings, components employing substantially the same functional configurations will be assigned the same reference numerals, and redundant description will be omitted. Furthermore, in the description and the drawings, a plurality of components employing substantially the same or similar functional configurations are distinguished by assigning different alphabets to ends of the same reference numerals in some cases. In this regard, in a case where it is not particularly necessary to distinguish each of a plurality of components employing substantially the same or similar functional configurations, only the same reference numeral is assigned.

(23) Note that the description will be given in the following order. 1. Configuration Example of Endoscopic Surgery System **5000** 1.1 Schematic Configuration of Endoscopic Surgery System **5000** 1.2 Detailed Configuration Example of Support Arm Device **5027** 1.3 Detailed Configuration Example of Light Source Device 2. Background Leading to Creation of Embodiments of Present Disclosure 2.1 Background Leading to Creation of Embodiments of Present Disclosure 2.2 Outline of Embodiments of Present Disclosure 2.3 Regarding EVS 3. First Embodiment 3.1 Configuration Example of Medical Observation System **10** 3.2 Configuration Example of Camera Head **100** and Optical System **400** 3.3 Functional Block Configuration Example 3.4 Control Method 3.5 Modified Example 4. Second Embodiment 5. Third Embodiment 6. Fourth Embodiment 6.1 First Example 6.2 Second Example 7. Fifth Embodiment 8. Conclusion 9. Hardware Configuration 10.

Supplementary Note

1. Configuration Example of Endoscopic Surgery System **5000**

1.1 Schematic Configuration of Endoscopic Surgery System **5000**

(24) First, prior to description of details of embodiments of the present disclosure, a schematic configuration of the endoscopic surgery system **5000** to which a technique according to the present disclosure can be applied will be described with reference to FIG. **1**. FIG. **1** is a diagram illustrating an example of the schematic configuration of the endoscopic surgery system **5000** to which the technique according to the present disclosure can be applied. FIG. **1** illustrates a state where a surgeon **5067** is performing surgery on a patient **5071** on a patient bed **5069** using the endoscopic surgery system **5000**. As illustrated in FIG. **1**, the endoscopic surgery system **5000** includes an endoscope **5001**, other surgical instruments **5017**, the support arm device **5027** that supports the endoscope **5001**, and a cart **5037** on which various devices for endoscopic surgery are mounted. Hereinafter, details of the endoscopic surgery system **5000** will be sequentially described.

(25) (Surgical Instrument **5017**)

(26) According to endoscopic surgery, for example, a plurality of cylindrical specula that are called trocars **5025a** to **5025d** puncture an abdominal wall instead of cutting the abdominal wall and performing laparotomy. Furthermore, a lens barrel **5003** of the endoscope **5001** and the other surgical instrument **5017** are inserted from the trocars **5025a** to **5025d** into a body cavity of the patient **5071**. In the example illustrated in FIG. **1**, a pneumoperitoneum tube **5019**, an energy treatment tool **5021**, and forceps **5023** are inserted as the other surgical instruments **5017** into the

body cavity of the patient **5071**. Furthermore, the energy treatment tool **5021** is a treatment tool that, for example, incises and detaches tissues, and seals blood vessels by a high frequency current or ultrasonic vibration. In this regard, the surgical instrument **5017** illustrated in FIG. **1** is merely an example, and examples of the surgical instruments **5017** include various surgical instruments such as tweezers and retractors that are generally used for endoscopic surgery.

(27) (Support Arm Device **5027**)

(28) The support arm device **5027** includes an arm part **5031** that extends from a base part **5029**. In the example illustrated in FIG. **1**, the arm part **5031** includes joint parts **5033a**, **5033b**, and **5033c**, and links **5035a** and **5035b**, and is driven under control of an arm control device **5045**.

Furthermore, the endoscope **5001** is supported by the arm part **5031** to control a position and a posture of the endoscope **5001**. Consequently, it is possible to stably fix the position of the endoscope **5001**.

(29) (Endoscope **5001**)

(30) The endoscope **5001** includes the lens barrel **5003** whose area of a predetermined length from a distal end is inserted into the body cavity of the patient **5071**, and a camera head **5005** that is connected to a proximal end of the lens barrel **5003**. Although the example illustrated in FIG. **1** illustrates the endoscope **5001** configured as a so-called rigid endoscope including the rigid lens barrel **5003**, the endoscope **5001** may be configured as a so-called flexible endoscope having the flexible lens barrel **5003**, and is not particularly limited in the embodiments of the present disclosure.

(31) An opening part into which an objective lens is fitted is provided at the distal end of the lens barrel **5003**. The endoscope **5001** is connected with the light source device (medical light source device) **5043**, and light generated by the light source device **5043** is guided to the distal end of the lens barrel by a light guide extending to an inside of the lens barrel **5003**, and is radiated toward an observation target in the body cavity (e.g., an inside of the abdominal cavity) of the patient **5071** through the objective lens. Note that, in the embodiments of the present disclosure, the endoscope **5001** may be a forward viewing endoscope, or may be an oblique viewing endoscope, and is not particularly limited.

(32) An optical system and an imaging element are provided inside the camera head **5005**, and reflected light (observation light) from the observation target is condensed on the imaging element by the optical system. The observation light is photoelectrically converted by the imaging element to generate an electric signal corresponding to the observation light, that is, a pixel signal corresponding to an observation image. The pixel signal is transmitted as RAW data to a Camera Control Unit (CCU) **5039**. Note that a function of adjusting a magnification and a focal distance by appropriately driving this optical system is mounted on the camera head **5005**.

(33) Note that, for example, a plurality of imaging elements may be provided in the camera head **5005** to support stereoscopic vision (stereoscopic system) or the like. In this case, a plurality of relay optical systems are provided inside the lens barrel **5003** to guide the observation light to each of the plurality of imaging elements. Furthermore, different types of imaging elements can be provided in the embodiments of the present disclosure, which will be described later. Furthermore, details of the camera head **5005** and the lens barrel **5003** according to the embodiments of the present disclosure will also be described later.

(34) (Various Devices Mounted on Cart)

(35) First, under control of the CCU **5039**, a display device **5041** displays an image that is based on a pixel signal subjected to image processing by the CCU **5039**. In a case where the endoscope **5001** supports high resolution photographing such as 4K (3840 horizontal pixels×2160 vertical pixels) or 8K (7680 horizontal pixels×4320 vertical pixels), and/or supports 3D display, for example, a display device that can perform high resolution display corresponding to each of 4K and 8K and/or a display device that can perform 3D display is used as the display device **5041**. Furthermore, the plurality of display devices **5041** having different resolutions and sizes may be provided depending

on applications.

(36) Furthermore, an image of a surgical site inside the body cavity of the patient **5071** photographed by the endoscope **5001** is displayed on the display device **5041**. While viewing the image of the surgical site displayed on the display device **5041** in real time, the surgeon **5067** can perform treatment such as excision of an affected part using the energy treatment tool **5021** and the forceps **5023**. Note that, although not illustrated, the pneumoperitoneum tube **5019**, the energy treatment tool **5021**, and the forceps **5023** may be supported by the surgeon **5067**, an assistant, or the like during surgery.

(37) Furthermore, the CCU **5039** includes a Central Processing Unit (CPU), a Graphics Processing Unit (GPU), and the like, and can integrally control operations of the endoscope **5001** and the display device **5041**. More specifically, the CCU **5039** performs various image processing such as development processing (demosaic processing) for displaying an image that is based on the pixel signal, on the pixel signal accepted from the camera head **5005**. Furthermore, the CCU **5039** provides the pixel signal subjected to the image processing to the display device **5041**.

Furthermore, the CCU **5039** transmits a control signal to the camera head **5005**, and controls driving of the camera head **5005**. The control signal can include information that relates to imaging conditions such as a magnification and a focal distance. Note that details of the CCU **5039** according to the embodiments of the present disclosure will be described later.

(38) The light source device **5043** includes a light source such as a Light Emitting Diode (LED), and supplies irradiation light for photographing a surgical site to the endoscope **5001**. Note that details of the light source device **5049** according to the embodiments of the present disclosure will be described later.

(39) The arm control device **5045** includes, for example, a processor such as a CPU, and operates according to a predetermined program to control driving of the arm part **5031** of the support arm device **5027** according to a predetermined control scheme. Note that details of the arm control device **5045** according to the embodiments of the present disclosure will be described later.

(40) An input device **5047** is an input interface for the endoscopic surgery system **5000**. The surgeon **5067** can input various pieces of information and input instructions to the endoscopic surgery system **5000** via the input device **5047**. For example, the surgeon **5067** inputs various pieces of information related to surgery such as body information of a patient and information regarding a surgical procedure of the surgery via the input device **5047**. Furthermore, for example, the surgeon **5067** can input an instruction to drive the arm part **5031**, an instruction to change imaging conditions (a type of irradiation light, a magnification, a focal distance, and the like) of the endoscope **5001**, an instruction to drive the energy treatment tool **5021**, and the like via the input device **5047**. Note that the type of the input device **5047** is not limited, and the input device **5047** may be various known input devices. As the input device **5047**, for example, a mouse, a keyboard, a touch panel, a switch, a foot switch **5057**, a lever, and/or the like can be applied. In a case where, for example, the touch panel is used as the input device **5047**, the touch panel may be provided on a display surface of the display device **5041**.

(41) Alternatively, the input device **5047** may be a device such as an eyeglass-type wearable device or a Head Mounted Display (HMD) that is attached to part of the body of the surgeon **5067**. In this case, various inputs are performed according to gestures or lines of sight of the surgeon **5067** detected by these devices. Furthermore, the input device **5047** can include a camera that can detect motions of the surgeon **5067**, and may input various inputs according to gestures or lines of sight of the surgeon **5067** detected from images imaged by the camera. Furthermore, the input device **5047** can include a microphone that can collect voice of the surgeon **5067**, and may input various inputs with voice via the microphone. As described above, the input device **5047** is configured to be able to input various pieces of information in a non-contact manner, so that a user (e.g., the surgeon **5067**) belonging to a clean area in particular can operate equipment belonging to an unclean area in a non-contact manner. Furthermore, the surgeon **5067** can operate the equipment without releasing

a possessed surgical instrument from the hand, so that convenience of the surgeon **5067** improves. (42) A treatment tool control device **5049** controls driving of the energy treatment tool **5021** for cauterization and incision of tissues, sealing of blood vessels, or the like. A pneumoperitoneum device **5051** feeds gas into the body cavity of the patient **5071** through the pneumoperitoneum tube **5019** to inflate the body cavity for a purpose of securing a visual field of the endoscope **5001** and securing a working space of the surgeon **5067**. A recorder **5053** is a device that can record various pieces of information related to surgery. A printer **5055** is a device that can print various pieces of information related to surgery in various formats such as a text, an image, or a graph.

1.2 Detailed Configuration Example of Support Arm Device **5027**

(43) Furthermore, an example of a detailed configuration of the support arm device **5027** will be described. The support arm device **5027** includes the base part **5029** that is a base, and the arm part **5031** that extends from the base part **5029**. Although the arm part **5031** includes the plurality of joint parts **5033a**, **5033b**, and **5033c**, and the plurality of links **5035a** and **5035b** coupled by the joint part **5033b** in the example illustrated in FIG. 1, FIG. 1 illustrates a simplified configuration of the arm part **5031** for the sake of simplicity. More specifically, the shape, the number, and arrangement of the joint parts **5033a** to **5033c** and the links **5035a** and **5035b**, a direction of rotation axes of the joint parts **5033a** to **5033c**, and the like can be appropriately set such that the arm part **5031** has a desired degree of freedom. For example, the arm part **5031** can be suitably configured to have a degree of freedom equal to or more than six degrees of freedom.

Consequently, it is possible to freely move the endoscope **5001** within a movable range of the arm part **5031**, so that the lens barrel **5003** of the endoscope **5001** can be inserted into the body cavity of the patient **5071** from a desired direction.

(44) Actuators are provided to the joint parts **5033a** to **5033c**, and the joint parts **5033a** to **5033c** are configured to be able to rotate around a predetermined rotation axis by driving the actuators.

Driving of the actuators is controlled by the arm control device **5045** to control a rotation angle of each of the joint parts **5033a** to **5033c**, and control driving of the arm part **5031**. Consequently, it is possible to realize control of a position and a posture of the endoscope **5001**. At this time, the arm control device **5045** can control driving of the arm part **5031** by various known control schemes such as force control or position control.

(45) For example, the surgeon **5067** may appropriately input an operation via the input device **5047** (including the foot switch **5057**) to make the arm control device **5045** appropriately control driving of the arm part **5031**, and control the position and the posture of the endoscope **5001** according to the operation input. Note that the arm part **5031** may be operated by a so-called master-slave mode. In this case, the arm part **5031** (slave) can be remotely controlled by the surgeon **5067** via the input device **5047** (master console) installed at a place remote from an operation room or in the operating room.

(46) Here, doctors who are called scopists have generally supported the endoscope **5001** for endoscopic surgery. By contrast with this, according to the embodiments of the present disclosure, it is possible to reliably fix the position of the endoscope **5001** without someone else's hand by using the support arm device **5027**, so that it is possible to stably obtain an image of a surgical site, and smoothly perform surgery.

(47) Note that the arm control device **5045** may not necessarily be provided to the cart **5037**. Furthermore, the arm control device **5045** may not necessarily be one device. For example, the arm control device **5045** may be each provided to each of the joint parts **5033a** to **5033c** of the arm part **5031** of the support arm device **5027**, and the plurality of arm control devices **5045** may cooperate with each other to realize driving control of the arm part **5031**.

1.3 Detailed Configuration Example of Light Source Device **5043**

(48) Next, the example of the detailed configuration of the light source device **5043** will be described. The light source device **5043** supplies to the endoscope **5001** irradiation light for photographing a surgical site. The light source device **5043** includes, for example, white light

sources formed by LEDs, laser light sources, or a combination of these. At this time, in a case where the white light sources are formed by a combination of RGB laser light sources, it is possible to highly accurately control an output intensity and an output timing of each color (each wavelength), so that the light source device **5043** can adjust a white balance of a captured image. Furthermore, in this case, by irradiating an observation target with the laser light from each of the RGB laser light sources in a time division manner, and controlling driving of the imaging element of the camera head **5005** in synchronization with an irradiation timing of the laser light, it is also possible to image an image corresponding to each of RGB in the time division manner. According to this method, it is possible to obtain a color image without providing a color filter to the imaging element.

(49) Furthermore, driving of the light source device **5043** may be controlled to change an intensity of light to be output per predetermined time. By controlling driving of the imaging element of the camera head **5005** in synchronization with a timing to change the intensity of the light, acquiring images in the time division manner, and synthesizing the images, it is possible to generate an image of a high dynamic range without so-called blocked up shadows and over exposure.

(50) Furthermore, the light source device **5043** may be configured to be able to supply light of a predetermined wavelength band corresponding to special light imaging. Special light imaging performs so-called narrow band imaging for radiating light of a narrower band than that of irradiation light (i.e., white light) at a time of normal observation using wavelength dependency of light absorption in body tissues, and thereby photographing predetermined tissues such as blood vessels in a mucosal surface layer with high contrast. Alternatively, special light imaging may perform fluorescence imaging for obtaining an image using fluorescence generated by radiating excitation light. According to fluorescence imaging, body tissues may be irradiated with excitation light to observe fluorescence from the body tissues (autofluorescence imaging), or a reagent such as Indocyanine Green (ICG) may be locally injected into body tissues and the body tissues may be irradiated with excitation light corresponding to a fluorescence wavelength of the reagent to obtain a fluorescent image. The light source device **5043** can be configured to be able to supply narrow band light and/or excitation light that support such special light imaging.

2. Background Leading to Creation of Embodiments of Present Disclosure

2.1 Background Leading to Creation of Embodiments of Present Disclosure

(51) Meanwhile, in recent years, development for causing the support arm device **5027** to autonomously operate has been advanced for the above-described endoscopic surgery system **5000**. More specifically, the autonomous operation of the support arm device **5027** in the endoscopic surgery system **5000** can be classified into various levels. Examples of the levels include a level at which the surgeon (operator) **5067** is guided by the system, and a level at which the system autonomously executes part of operations (tasks) of surgery of, for example, suturing a surgical site by moving a position of the endoscope **5001** and causing the surgical instrument **5017** to autonomously operate. Furthermore, the examples of the levels can include, for example, a level at which the system automatically generates operation contents of the surgery, and the endoscopic surgery system **5000** performs an operation selected by a doctor from the automatically generated operation. Furthermore, a level at which the endoscopic surgery system **5000** executes all tasks of surgery under monitoring of the doctor or without monitoring of the doctor in the future may also be conceivable.

(52) Note that the embodiments of the present disclosure described below assume use in a case where the endoscopic surgery system **5000** autonomously executes a task (scope work) of moving the position of the endoscope **5001** in place of a scopist, and the surgeon **5067** performs surgery directly or surgery by a remote operation by referring to an image obtained by the moved endoscope **5001**. According to endoscopic surgery, for example, depending on a difference in skill of scope work of an assistant who operates an endoscope, an appropriate field of view cannot be obtained, a surgical result is affected, moreover, there are problems of difficulty of the skill of the

scope work itself and a shortage of medical workers due to aging, and therefore it is strongly demanded to make the scope work of the endoscopic surgery system **5000** autonomous.

(53) For this purpose, for example, it is required to robustly measure and recognize the environment inside an abdominal cavity in real time, and cause the endoscopic surgery system **5000** to autonomously operate based on a recognition result. However, although conventional techniques mainly use the endoscope **5001** that uses an RGB sensor that is a sensor that detects light of three primary colors of red (R), green (G), and blue (B), such an RGB sensor has had a limit in robustly and highly accurately measuring and recognizing a laparoscopic environment in real time.

(54) Referring to, for example, FIG. 2 illustrating an example of an image of an inside of an abdominal cavity, the RGB sensor is expected to acquire an image as illustrated on the left side of FIG. 2. However, the abdominal cavity is actually a closed environment, a light irradiation range of the endoscopic surgery system **5000** is also limited, and therefore the RGB sensor can only acquire a dark image as illustrated on the right side of FIG. 2 depending on conditions in some cases. Such a dark image makes it difficult to accurately recognize a tumor, a surgical site, or a surgical instrument inside an abdominal cavity from, for example, the image, and, for example, it is difficult to acquire an image of a desired site, recognize the surgical site, and avoid an interference with the surgical instrument. Furthermore, when an imaging target becomes dark, it is necessary to reduce a shutter speed, and, when a surgical site moves or deforms, motion blur remarkably occurs in an image, which may make recognition more difficult.

(55) Furthermore, a large difference between brightness and darkness is likely to occur in environment inside an abdominal cavity, and therefore it is difficult to recognize a subject (e.g., a tumor, a surgical site, a surgical instrument, or the like) captured at a dark part of an image. Furthermore, it is difficult to recognize organs having no characteristic texture or parts to which blood is attached even if these organs and parts are segmented, and a high frame rate is required to capture high speed deformation of the organ, and therefore a processing load is great, that is, the environment inside the abdominal cavity has many disadvantageous conditions for recognition processing that uses an RGB sensor.

(56) Furthermore, although it is conceivable to use not only an RGB sensor, but also a distance measurement device of, for example, a Time of Flight (ToF) scheme that performs distance measurement using a return time of reflection of pulsed light from a subject to measure and recognize the environment inside the abdominal cavity, there are many problems that, for example, water, a body fluid, a blood, or the like make it difficult to perform accurate distance measurement due to specular reflection on a liquid surface thereof unique to surgery environment in a case where the ToF is used, and, moreover, it is difficult to incorporate the distance measurement device into the endoscope **5001**.

2.2 Outline of Embodiments of Present Disclosure

(57) Furthermore, in the above-described situation, the inventors of the present disclosure have intensively studied means for robustly measuring and recognizing an environment inside an abdominal cavity in real time. During such study, the inventors of the present disclosure have reached an idea that it is possible to compensate for drawbacks of existing RGB sensors using an Event Vision Sensor (EVS).

(58) The EVS is an image sensor that sensitively detects a luminance change, and has higher sensitivity than that of general RGB sensors. Consequently, it is possible to easily obtain a shape (edge information) of a subject even in a dark place that is difficult for the RGB sensor to capture.

(59) Furthermore, the EVS has no concept of a frame rate, and can sparsely output time stamp information and pixel information when a luminance change exceeds a threshold. Consequently, the EVS can output the time stamp information and the pixel information at a high frame rate in response to frequent luminance changes. Furthermore, by integrating outputs of a certain period from the EVS, and converting the outputs as an image of a suitable frame rate, it is possible to

easily capture a motion and deformation of the subject. More specifically, the number of events to be integrated changes according to a frame length, and therefore the information included in the converted image also changes. Consequently, by performing processing of adjusting the frame length to capture a desired subject and deformation thereof using such features of the EVS, it is possible to more easily obtain the shape (edge information) of the subject, and improve recognition performance of the subject.

(60) Furthermore, the EVS does not output all pixel information every other certain frames, and therefore a data amount becomes smaller than that of a normal RGB sensor, so that it is possible to make a load of arithmetic processing lower.

(61) According to the embodiments of the present disclosure that are created by the inventors of the present disclosure and use the above-described EVS, it is possible to robustly measure and recognize an environment inside an abdominal cavity in real time. Furthermore, according to the embodiments of the present disclosure, it is possible to robustly and highly accurately measure and recognize the environment inside the abdominal cavity in real time, so that it is also easy to make scope work of the endoscopic surgery system **5000** autonomous. In addition, according to the embodiments of the present disclosure, advantages of conventional image recognition such as tracking of long term feature that the RGB camera is good at, and the EVS are combined, so that it is possible to more robustly measure and recognize the environment inside an abdominal cavity in more real time. Hereinafter, details of these embodiments of the present disclosure will be sequentially described.

2.3 Regarding EVS

(62) Here, the Event Vision Sensor (EVS) will be described with reference to FIGS. **3** and **4**. FIG. **3** is a block diagram illustrating an example of a configuration of an EVS **200** used in the embodiments of the present disclosure, and FIG. **4** is a block diagram illustrating an example of a configuration of a pixel **302** located in a pixel array unit **300** in the EVS **200** illustrated in FIG. **3**.

(63) As illustrated in FIG. **3**, the EVS **200** includes the pixel array unit **300** configured by aligning the plurality of pixels (first pixels) **302** (see FIG. **4**) in a matrix. Each pixel **302** can generate as a pixel signal a voltage corresponding to a photocurrent generated by photoelectric conversion. Furthermore, each pixel **302** can detect whether or not an event has occurred by comparing with a predetermined threshold a change in the photocurrent corresponding to a change in luminance of incident light. In other words, the pixel **302** can detect the event based on a fact that the luminance change has exceeded the predetermined threshold.

(64) Furthermore, as illustrated in FIG. **3**, the EVS **200** includes a drive circuit **211**, an arbiter unit (arbitration unit) **213**, a column processing unit **214**, and a signal processing unit **212** as peripheral circuit units of the pixel array unit **300**.

(65) When detecting an event, each pixel **302** can output, to the arbiter unit **213**, a request for requesting output of event data indicating occurrence of the event. Furthermore, when receiving from the arbiter unit **213** a response indicating permission to output the event data, each pixel **302** outputs the event data to the drive circuit **211** and the signal processing unit **212**. Furthermore, the pixel **302** that has detected the event outputs a pixel signal generated by photoelectric conversion to the column processing unit **214**.

(66) The drive circuit **211** can drive each pixel **302** of the pixel array unit **300**. For example, the drive circuit **211** detects an event, drives the pixel **302** that has output the event data, and outputs a pixel signal of the corresponding pixel **302** to the column processing unit **214**.

(67) The arbiter unit **213** arbitrates a request for requesting output of event data supplied from each of the respective pixels **302**, and can transmit a response that is based on a result of this arbitration (permission/non-permission of output of the event data), and a reset signal for resetting event detection to the pixel **302**.

(68) The column processing unit **214** can perform processing of converting analog pixel signals output from the pixels **302** of a corresponding column into digital signals per column of the pixel

array unit **300**. The column processing unit **214** can also perform Correlated Double Sampling (CDS) processing on the digitized pixel signal.

(69) The signal processing unit **212** can execute predetermined signal processing on the digitized pixel signals supplied from the column processing unit **214** and the event data output from the pixel array unit **300**, and output the event data (time stamp information and the like) and the pixel signal subjected to the signal processing.

(70) The change in the photocurrent generated in the pixel **302** can be regarded as a light quantity change (luminance change) of light incident on the pixel **302**. Therefore, the event can also be referred to as a luminance change of the pixel **302** that exceeds the predetermined threshold.

Furthermore, event data indicating occurrence of an event can include at least position information such as coordinates indicating the position of the pixel **302** at which the light quantity change that is the event has occurred.

(71) Furthermore, the pixel **302** will be described with reference to FIG. **4**. In the pixel array unit **300** configured by aligning the plurality of pixels **302** in a matrix, each pixel **302** includes a light reception unit **304**, a pixel signal generation unit **306**, and a detection unit (event detection unit) **308**.

(72) More specifically, the light reception unit **304** can photoelectrically convert incident light and generate a photocurrent. Furthermore, the light reception unit **304** can supply a signal of a voltage corresponding to the photocurrent to one of the pixel signal generation unit **306** and the detection unit **308** under control of the drive circuit **211**.

(73) The pixel signal generation unit **306** can generate a signal supplied from the light reception unit **304** as a pixel signal. Furthermore, the pixel signal generation unit **62** can supply the generated analog pixel signal to the column processing unit **214** via a vertical signal line VSL (not illustrated) corresponding to the column of the pixel array unit **300**.

(74) The detection unit **308** can detect whether or not an event has occurred based on whether or not a change amount of the photocurrent from the light reception unit **304** has exceeded a predetermined threshold. The event can include, for example, an on-event that indicates that the change amount of the photocurrent has exceeded an upper limit threshold, and an off-event that indicates that this change amount has fallen below a lower limit threshold. Note that the detection unit **308** may detect only the on-event.

(75) When an event occurs, the detection unit **308** can output to the arbiter unit **213** a request for requesting output of event data indicating the occurrence of the event. Furthermore, when receiving a response to the request from the arbiter unit **213**, the detection unit **308** can output the event data to the drive circuit **211** and the signal processing unit **212**.

(76) In the embodiments of the present disclosure, by applying this EVS **200** to the endoscopic surgery system **5000**, it is possible to make use of a high dynamic range, high robustness for detecting a subject that moves fast, and high time resolution that are the features of the EVS **200**, so that it is possible to improve recognition accuracy of the subject.

3. First Embodiment

3.1 Configuration Example of Medical Observation System **10**

(77) First, the configuration example of the medical observation system **10** according to the first embodiment of the present disclosure will be described with reference to FIG. **5**. FIG. **5** is a diagram illustrating an example of the configuration of the medical observation system **10** according to the present embodiment. The medical observation system **10** can be applied to an above-described endoscopic surgery system **5000**.

(78) As illustrated in FIG. **5**, the medical observation system **10** mainly includes a camera head **100** (corresponding to an above-described camera head **5005**), an optical system **400** (corresponding to an above-described lens barrel **5003**), a Camera Control Unit (CCU) (processing unit) **500** (that tracks an above-described CCU **5039**), a light source device **600** (corresponding to an above-described light source device **5043**), a robot control unit **700** (corresponding to an above-described

arm control device **5045**), a robot arm **800** (corresponding to an above-described support arm device **5027**), and a display device **900** (corresponding to an above-described display device **5041**). Hereinafter, each device included in the medical observation system **10** will be described.

(79) First, an outline of an operation of the medical observation system **10** will be described prior to description of details of the configuration of the medical observation system **10**. By controlling the robot arm **800** using the robot control unit **700**, the medical observation system **10** can fix positions of the camera head **100** and the optical system **400** supported by the robot arm **800** to suitable positions without someone else's hand. Consequently, the medical observation system **10** can stably obtain an image of a surgical site, so that a surgeon **5067** can smoothly perform surgery. Note that, in the following description, a person who moves or fixes a position of an endoscope **5001** is referred to as a scopist, and an operation of the endoscope **5001** (including movement, stop, change of a posture, zoom-in, zoom-out, and the like) is referred to as scope work regardless of control of someone else's hand or a machine.

(80) (Camera Head **100** and Optical System **400**)

(81) The camera head **100** and the optical system **400** are provided at a distal end of the robot arm **800** described later, and image images of various imaging targets (e.g., the environment inside an abdominal cavity). In other words, the robot arm **800** supports the camera head **100** and the optical system **400**. Note that the camera head **100** and the optical system **400** may be, for example, an oblique viewing endoscope, a forward viewing endoscope (not illustrated) with a wide angle/cutout function, an endoscope (not illustrated) with a distal end bending function, an endoscope (not illustrated) with an other direction simultaneous photographing function, an exoscope, or a microscope, and are not particularly limited.

(82) Furthermore, the camera head **100** and the optical system **400** can image, for example, a surgical field image including various surgical instruments, organs, and the like in an abdominal cavity of a patient. More specifically, the camera head **100** can function as a camera that can photograph a photographing target in a form of a movie or a still image. Furthermore, the camera head **100** can transmit an electric signal (pixel signal) corresponding to the captured image to the CCU **500** described later. Note that the robot arm **800** may support a surgical instrument such as forceps **5023**.

(83) Furthermore, in the embodiments of the present disclosure, the camera head **100** and the optical system **400** may be a stereoscopic endoscope that can perform distance measurement. Alternatively, a depth sensor (distance measurement device) (not illustrated) may be provided in the camera head **100** or separately from the camera head **100**. The depth sensor can be, for example, a sensor that performs distance measurement using a Time of Flight (ToF) scheme that performs distance measurement using a return time of reflection of pulsed light from a subject, or a structured light scheme that performs distance measurement based on a distorted pattern by radiating lattice pattern light.

(84) Note that details (more specifically, an RGB sensor and an EVS **200**) of the camera head **100** and the optical system **400** according to the present embodiment will be described later.

(85) (CCU **500**)

(86) As described above, the CCU **500** includes a CPU, a GPU, and the like, and can integrally control an operation of the camera head **100**. More specifically, the CCU **500** can subject a pixel signal accepted from the camera head **100** to various image processing for displaying an image. Furthermore, the CCU **500** provides the pixel signal subjected to the image processing to the display device **900** described later. Furthermore, the CCU **500** can transmit a control signal to the camera head **100** and control driving thereof. The control signal can include information that relates to imaging conditions such as a magnification and a focal distance. Note that details of the CCU **500** according to the present embodiment will be described later.

(87) (Light Source Device **600**)

(88) The light source device **600** irradiates an imaging target of the camera head **100** with light. The

light source device **600** can be realized by, for example, Light Emitting Diodes (LEDs) for a wide angle lens. For example, the light source device **600** may be configured by combining normal LEDs and a lens, and diffuse light. Furthermore, the light source device **600** may employ a configuration where, for example, a lens diffuses (widens an angle of) light transmitted through an optical fiber (light guide). Furthermore, the light source device **600** may expand an irradiation range by directing optical fibers themselves toward a plurality of directions and radiating light. Note that details of the light source device **600** according to the present embodiment will be described later.

(89) (Robot Control Unit **700**)

(90) The robot control unit **700** controls driving of the robot arm **800** described later. The robot control unit **700** is realized by, for example, causing a CPU, an MPU, and the like to execute a program (e.g., a program according to the embodiments of the present disclosure) stored in a storage unit described later using a Random Access Memory (RAM) or the like as a working area. Furthermore, the robot control unit **700** is a controller, and may be realized by, for example, an integrated circuit such as an Application Specific Integrated Circuit (ASIC) or a Field Programmable Gate Array (FPGA). Furthermore, the robot control unit **700** may be a device that is integrated with the above-described CCU **500**, or may be a separate device. Note that details of the robot control unit **700** according to the present embodiment will be described later.

(91) (Robot Arm **800**)

(92) As described above, the robot arm **800** includes an articulated arm (corresponding to an arm part **5031** illustrated in FIG. 1) that is a multilink structure including a plurality of joint parts and a plurality of links, and can control positions and postures of the camera head **100** and the optical system **400** provided at the distal end of the robot arm **800** by driving the robot arm **800** within a movable range. Furthermore, the robot arm **800** may include a motion sensor (not illustrated) including an acceleration sensor, a gyro sensor, a geomagnetic sensor, and the like to obtain data of the position and posture of the robot arm **800**.

(93) (Display Device **900**)

(94) The display device **900** displays various images. The display device **900** displays, for example, an image imaged by the camera head **100**. The display device **900** can be, for example, a display that includes a Liquid Crystal Display (LCD), an organic Electro-Luminescence (EL) display, or the like. Note that the display device **900** may be the above-described device that is integrated with the CCU **500** illustrated in FIG. 5, or may be the above-described separate device that is connected with the CCU **500** communicably by wire or wirelessly.

3.2 Configuration Example of Camera Head **100** and Optical System **400**

(95) Next, an example of a detailed configuration of the camera head (camera head unit) **100** and the optical system **400** according to the present embodiment will be described with reference to FIG. 6. FIG. 6 is an explanatory view for describing an example of the configuration of the camera head **100** and the optical system **400** illustrated in FIG. 5.

(96) (Camera Head **100**)

(97) More specifically, as illustrated in FIG. 6, the EVS **200** provided in the camera head **100** includes a substrate on which a pixel array unit **300** is mounted, and a substrate on which a peripheral circuit unit **310** of the pixel array unit **300** is mounted. As described above, the EVS **200** mainly includes a plurality of pixels (first pixels) **302** that are aligned in a matrix, and a detection unit **308** that detects that a luminance change amount of light incident on each of the plurality of pixels **302** has exceeded a predetermined threshold. Furthermore, event data and a pixel signal detected by the EVS **200** are transmitted to the CCU **500**. Note that the detailed configuration of the EVS **200** has been described above, and therefore description thereof will be omitted here.

(98) Note that, although the present embodiment has described that the camera head **100** provided with the EVS **200** is different from a camera head provided with an RGB sensor, the EVS **200** and the RGB sensor may be provided in the same camera head as described later. Furthermore, in a

case where the camera head **100** provided with the EVS **200** and the camera head provided with the RGB sensor are different, the camera head **100** and the camera head may be supported by the respectively different robot arms **800**.

(99) (Optical System **400**)

(100) The optical system **400** can guide light from the light source device **600** to a subject, and can guide the light reflected by the subject to the camera head **100**. The optical system **400** includes an imaging optical system **402** and a light source optical system **404**. More specifically, the light from the light source device **600** is guided to the subject by the light source optical system **404**, and the light reflected by the subject is further guided to the camera head **100** by the imaging optical system **402** and condensed on the pixel array unit **300** of the EVS **200**. Furthermore, the imaging optical system **402** and the light source optical system **404** are configured by combining a plurality of lenses including zoom lenses and focus lenses. Furthermore, the zoom lenses and the focus lenses may be configured such that positions on optical axes thereof are able to move to, for example, adjust a magnification and a focus of a captured image.

(101) Note that the components such as the camera head **100** and the optical system **400** have sealed structures having high airtightness and waterproofness in the present embodiment, so that the camera head **100** and the optical system **400** can have resistance to autoclave sterilization processing.

(102) Furthermore, in the present embodiment, not only the EVS **200** but also an RGB sensor (image detection unit) **250** that images an RGB image may be disposed in the camera head **100**. Such a configuration will be described with reference to FIG. 7. FIG. 7 is an explanatory view for describing another example of the configuration of the camera head **100** according to the present embodiment.

(103) The camera head **100** illustrated in FIG. 7 includes the RGB sensor **250** and a prism (dispersion unit) **260** in addition to the EVS **200**. More specifically, the RGB sensor **250** provided in the camera head **100** mainly includes a plurality of pixels (second pixels) (not illustrated) that are aligned in a matrix, and a peripheral circuit unit (not illustrated) that outputs as a pixel signal an image that is based on light incident on each of the plurality of pixels **302**. Furthermore, the pixel signal output from the RGB sensor **250** is transmitted to the CCU **500**. More specifically, the RGB sensor **250** is, for example, an image sensor that has a Bayer arrangement that makes it possible to detect blue light, green light, and red light, and can perform color photographing, and is preferably, for example, an image sensor that can support photographing of a high resolution image of 4K or more. It is possible to obtain an image of a surgical site with high resolution using such an image sensor, so that the surgeon **5067** can grasp a more detailed state of the surgical site and proceed with surgery more smoothly.

(104) Furthermore, the RGB sensor **250** may include a pair of image sensors for respectively acquiring right-eye and left-eye images that support 3D display (stereoscopic system). 3D display is performed, so that the surgeon **5067** can more accurately grasp the depth of living body tissues (organ) at the surgical site, and grasp a distance to the living body tissues.

(105) Furthermore, the prism **260** can guide the light reflected by the subject to both of the EVS **200** and the RGB sensor **250**.

(106) Furthermore, the prism (distribution ratio adjustment unit) **260** may have a function of adjusting between the EVS **200** and the RGB sensor **250** a distribution ratio of a light quantity of light incident on each of the EVS **200** and the RGB sensor **250**. It is possible to provide the above function by, for example, adjusting a transmittance of the prism **260**. More specifically, in a case where, for example, the optical axis of the incident light is the same between the EVS **200** and the RGB sensor **250**, it is preferable to adjust the transmittance of the prism **260** such that the light quantity of light incident on the RGB sensor **250** side becomes great.

(107) In the present embodiment, by combining the EVS **200** and the RGB sensor **250**, it is possible to make use of both features of a high dynamic range, high robustness for detecting a

subject that moves fast, and high time resolution that are features of the EVS **200**, and high tracking performance over a long time that is a feature of the RGB sensor **250**, so that it is possible to improve recognition accuracy of the subject.

(108) Note that, in the present embodiment, the camera head **100** may include an IR sensor (not illustrated) that detects infrared light.

(109) Note that the present embodiment is not limited to the configuration where the prism **260** guides light to both of the EVS **200** and the RGB sensor **250**, and, for example, a hybrid-type sensor may be used in which pixel arrays corresponding to the EVS **200** and the RGB sensor **250** are provided on the same substrate (light reception surface). In such a case, the above-described prism **260** is unnecessary, so that it is possible to simplify rigidity in the camera head **100**.

(110) Furthermore, in the embodiments of the present disclosure, the two EVSs **200** and RGB sensors **250** or the three or more EVSs **200** and RGB sensors **250** may be provided to enable the stereoscopic system that can perform distance measurement. Furthermore, in a case where the stereoscopic system is realized, two image circles may be projected on one pixel array by associating the two optical systems **400** with the one pixel array.

(111) Note that, in the present embodiment, the EVS **200** and the RGB sensor **250** may be provided in the distal end part of a flexible endoscope or a rigid endoscope to be inserted in an abdominal cavity.

3.3 Functional Block Configuration Example

(112) Next, a functional block configuration example of the medical observation system **10** according to the present embodiment will be described with reference to FIG. **8**. FIG. **8** is a block diagram illustrating an example of the functional block configuration of the medical observation system **10** according to the present embodiment. As described above, the medical observation system **10** according to the present embodiment mainly includes the camera head **100**, the optical system **400**, the CCU **500**, the light source device **600**, the robot control unit **700**, the robot arm **800**, and the display device **900**. Furthermore, the camera head **100**, the CCU **500**, the light source device **600**, and the robot control unit **700** can be bidirectionally communicably connected by a transmission cable (not illustrated).

(113) Alternatively, the camera head **100**, the CCU **500**, the light source device **600**, and the robot control unit **700** may be bidirectionally communicably connected wirelessly. As described above, in a case where communication is performed wirelessly, it is not necessary to lay the transmission cable in an operating room, so that it is possible to overcome a situation that movement of a medical staff (e.g., surgeon **5067**) in the operating room is hindered by the transmission cable. Hereinafter, each device included in the medical observation system **10** will be described.

(114) (Camera Head **100**)

(115) As illustrated in FIG. **8**, the camera head **100** mainly includes the pixel array unit **300** and the peripheral circuit unit **310** of the EVS (imaging unit) **200**, the RGB sensor **250**, a communication unit **102**, and a drive control unit **316**. More specifically, the pixel array unit **300** and the RGB sensor **250** of the EVS **200** receive light guided by an optical unit **410** including a plurality of lenses, generate a signal, and output the generated signal to the communication unit **102**.

(116) The communication unit **102** includes a communication device for transmitting and receiving various pieces of information to and from the CCU **500**, and can transmit signals from the pixel array unit **300** and the RGB sensor **250** to the CCU **500**, and receive from the CCU **500** a control signal for controlling driving of the camera head **100**. The control signal includes, for example, information related to imaging conditions such as information for designating a frame rate of imaging, information for designating an exposure value at a time of imaging, and/or information for designating a magnification and a focus of a captured image. Note that the imaging conditions such as the above frame rate, exposure value, magnification, and focus may be automatically set by an integration information processing/control unit **508** of the CCU **500** based on the acquired image or the like.

(117) The drive control unit **316** controls driving of the EVS **200** based on the control signal received from the CCU **500** via the communication unit **102**. For example, the drive control unit **316** adjusts a threshold or the like to be compared with the luminance change amount when detecting an event.

(118) (CCU **500**)

(119) As illustrated in FIG. **8**, the CCU **500** mainly includes communication units **502**, **522**, and **532**, an RGB signal/image processing unit **504**, an RGB recognition unit **506**, the integration information processing/control unit **508**, an event preprocessing unit **514**, an event information processing unit **516**, a synchronization control unit **520**, and a display information generation unit **530**.

(120) The communication units **502**, **522**, and **532** include communication devices for transmitting and receiving various pieces of information (detection signals, control signals, and the like) to and from each of the camera head **100**, the light source device **600**, and the robot control unit **700**. In the present embodiment, by providing these communication units **502**, **522**, and **532**, it is possible to enable cooperation between the camera head **100**, the light source device **600**, and the robot arm **800**.

(121) The RGB signal/image processing unit **504** can perform various image processing on a pixel signal that is RAW data acquired via the communication unit **502** and transmitted from the RGB sensor **250** of the camera head **100**, and output the pixel signal to the RGB recognition unit **506** described later. The image processing includes, for example, various known signal processing such as development processing, image quality improvement processing (band enhancement processing, super-resolution processing, Noise Reduction (NR) processing, camera shake correction processing, and/or the like), and/or enlargement processing (electronic zoom processing). More specifically, the RGB signal/image processing unit **504** includes a processor such as a CPU and a GPU, and the processor operates according to a predetermined program to perform the above-described image processing. Note that, in a case where the RGB signal/image processing unit **504** includes a plurality of GPUs, the RGB signal/image processing unit **504** may appropriately divide information related to the pixel signal, and the plurality of these GPUs may perform image processing on the information in parallel.

(122) The RGB recognition unit **506** can perform recognition processing on the image processed by the RGB signal/image processing unit **504** to obtain information for controlling the RGB sensor **250**, the light source device **600**, and the robot arm **800**. For example, the RGB recognition unit **506** can recognize a position, a shape, sharpness, a luminance, and the like of the subject from the image, and obtain information for controlling focus of the RGB sensor **250**, an intensity and a range of light radiated from the light source device **600**, driving of the robot arm **800**, and the like. The obtained information is output to the integration information processing/control unit **508** described later. Furthermore, the RGB recognition unit **506** can recognize a surgical instrument such as forceps, a specific living body site, bleeding, and the like by segmenting a subject included in each surgical site image using various image recognition techniques.

(123) The integration information processing/control unit (processing unit) **508** performs various processing related to control of the EVS **200** and the RGB sensor **250**, and image display that uses various pixel signals (first and second outputs) from the EVS **200** and the RGB sensor **250**. For example, the integration information processing/control unit **508** generates a control signal for controlling the EVS **200** and the RGB sensor **250**. At this time, in a case where imaging conditions are input by the surgeon **5067**, the integration information processing/control unit **508** may generate a control signal based on the input of the surgeon **5067**. Furthermore, the integration information processing/control unit **508** can integrate signals from the EVS **200** and the RGB sensor **250**, or arbitrate images from the EVS **200** and the RGB sensor **250** having different frame rates, and simultaneously handle the images.

(124) Furthermore, the integration information processing/control unit **508** may perform processing

such as image quality enhancement, three-dimensional shape measurement, optical flow estimation (for, for example, estimating an apparent speed of an object in an image, or estimating and tracking a moving object from the image), visual inertial odometry (for estimating and tracking a posture of a camera by combining an image with motion data), motion detection, segmentation, image recognition, and Simultaneous Localization And Mapping (SLAM).

(125) Thus, in the present embodiment, the integration information processing/control unit **508** can perform integration processing on output information from the EVS **200** and the RGB sensor **250**, so that it is possible to clearly capture an edge of the subject even in a dark area based on, for example, the output from the EVS **200**. Furthermore, the EVS **200** has high time resolution, and can consequently compensate for tracking of a subject of a low frame rate performed by the RGB sensor **250**, so that it is possible to improve tracking performance for a subject that moves at a high speed or deforms in the present embodiment. Furthermore, the output information of the EVS **200** is sparse information, so that it is possible to reduce a processing load according to the present embodiment.

(126) Note that, in the present embodiment, the integration information processing/control unit **508** is not limited to performing the integration processing on the output information from the EVS **200** and the RGB sensor **250**, and may individually process the output information.

(127) The event preprocessing unit **514** can perform various processing on the event data and the pixel signal that are RAW data acquired via the communication unit **502** and transmitted from the EVS **200** of the camera head **100**, and output the event data and the pixel signal to the event information processing unit **516** described later. The processing includes, for example, integration of pixel signals of a certain period (frame length) from the EVS **200**, and adjustment of the frame length. More specifically, the event preprocessing unit **514** includes processors such as a CPU and a GPU, and the processors operate according to a predetermined program to perform the above-described processing.

(128) The event information processing unit **516** can perform image processing based on the event data and the pixel signal processed by the event preprocessing unit **514**. Furthermore, by detecting a shape of the edge of the subject included in each surgical site image using various image recognition techniques, the event information processing unit **516** may recognize a surgical instrument such as forceps, a specific living body site, a shape, bleeding, or the like.

(129) The synchronization control unit **520** generates a synchronization control signal for synchronizing the camera head **100** and the light source device **600** based on the control signal of the integration information processing/control unit **508**, and controls the light source device **600** via the communication unit **522**. For example, by adjusting an intensity and a cycle of an intensity change of the light radiated from the light source device **600** based on the information of brightness of a screen that is based on the image from the RGB sensor **250**, the EVS **200** can more suitably perform imaging.

(130) The display information generation unit **530** causes the display device **900** to display the image of the surgical site based on the pixel signal processed by the integration information processing/control unit **508**. In the present embodiment, the display information generation unit **530** may cause the display device **900** to display not only the image of the surgical site, but also segmentation information that follows, for example, a size, a distance, deformation, and the like of an organ.

(131) (Light Source Device **600**)

(132) As illustrated in FIG. **8**, the light source device **600** mainly includes a communication unit **602**, a light source control unit **604**, and a light source unit **606**. The communication unit **602** includes a communication device for transmitting and receiving various pieces of information (a control signal and the like) to and from the CCU **500**. The light source control unit **604** controls driving of the light source unit **606** based on the control signal received from the CCU **500** via the communication unit **602**. The light source unit **606** includes a light source such as an LED, and

supplies irradiation light to a surgical site under control of the light source control unit **604**.

(133) (Robot Control Unit **700**)

(134) As illustrated in FIG. **8**, the robot control unit (control unit) **700** mainly includes a communication unit **702**, an arm trajectory generation unit **704**, and an arm control unit **706**. The communication unit **702** includes a communication device for transmitting and receiving various pieces of information (a control signal and the like) to and from the CCU **500**. The arm trajectory generation unit **704** can generate trajectory information as autonomous operation control information for causing the robot arm **800** to autonomously operate based on the control information from the CCU **500**. Furthermore, the arm control unit **706** controls driving of an arm actuator **802** of the robot arm **800** based on the generated trajectory information. In the present embodiment, a sudden motion of the surgical instrument that is the subject can also be detected in real time by the EVS **200** having high time resolution, so that the robot arm **800** can more instantaneously move the camera head **100** without interfering with the surgical instrument. Consequently, it is possible to safely perform surgery.

3.4 Control Method

(135) Next, an example of the control method according to the first embodiment of the present disclosure will be described with reference to FIGS. **9** to **11**. FIG. **9** is a flowchart of the control method according to the present embodiment. FIG. **10** is an explanatory view for describing the control method according to the present embodiment, and FIG. **11** is an explanatory view for describing motion compensation of the control method according to the present embodiment.

(136) By the way, during laparoscopic surgery, an erroneous operation of the surgical instrument or the like causes a surgical instrument and an endoscope (the camera head **100** and the optical system **400**) to contact. As a result, dirt adheres to the endoscope, and labor is required to take out the endoscope to an outside of the body and clean the endoscope, which is a cause that an operation time becomes long.

(137) For this reason, it is required to avoid contact (interference) with the surgical instrument using the robot arm **800** that supports the endoscope (the camera head **100** and the optical system **400**). However, the RGB sensor **250** used for the conventional techniques takes several 10 to 100 ms to perform image recognition on the surgical instrument, and then an avoidance operation of the robot arm **800** is started. Therefore, according to the autonomous operation of the robot arm **800** based on the image recognition that uses the RGB sensor **250**, it has not been possible to adapt to a sudden motion of the surgical instrument and a quick motion such as drop of a raised organ.

(138) On the other hand, in the present embodiment, by using image recognition of the EVS **200**, the robot arm **800** can avoid the sudden motion of the surgical instrument and the quick motion such as drop of the raised organ.

(139) More specifically, as illustrated in FIG. **9**, the control method according to the present embodiment can mainly include steps of step **S101** to step **S104**. Details of these respective steps according to the present embodiment will be described below.

(140) Hereinafter, a case where the optical system **400** and the camera head **100** moved by the robot arm **800** image a surgical instrument **910a** that does not move and a surgical instrument **910b** that moves as illustrated in FIG. **10** will be described as an example.

(141) First, the medical observation system **10** executes motion compensation processing of canceling motions of the optical system **400** and the camera head **100** using an image captured at a high frame rate by the EVS **200** (step **S101**). More specifically, for example, the medical observation system **10** detects a motion vector from an entire image (in an example on the left side of FIG. **11**, the optical system **400** and the camera head **100** are moving, and therefore that the surgical instruments **910a** and **910b** are moving is captured) before the motion compensation processing illustrated on the left side of FIG. **11**, and corrects the image using the detected motion vector, so that it is possible to obtain an image (in the example on the right side of FIG. **11**, the motions of the optical system **400** and the camera head **100** are canceled, and therefore the surgical

instrument **910a** stops and the surgical instrument **910b** is moving) after motion compensation illustrated on the right side of FIG. **11**. Furthermore, at this time, the image may be corrected using position/motion information of the camera/endoscope obtained from the robot in addition to the motion vector to obtain the image after motion compensation.

(142) Next, the medical observation system **10** detects a dynamic object (here, the moving surgical instrument **910b**) that is making a motion, from the image after motion compensation obtained in step **S101** (step **S102**).

(143) Next, by, for example, making use of time series data of the images or using stereoscopic distance measurement, or the like for the dynamic object (here, the moving surgical instrument **910b**) detected in step **S102**, the medical observation system **10** detects the distance to the dynamic object. Furthermore, the medical observation system **10** determines whether or not the dynamic object approaches the camera head **100** and the optical system **400** based on the detected distance (step **S103**). The medical observation system **10** proceeds to step **S104** in a case where the dynamic object approaches (step **S103**: Yes), and returns to above-described step **S101** in a case where the dynamic object does not approach (step **S103**: No).

(144) Furthermore, the medical observation system **10** causes the robot arm **800** to autonomously operate to avoid interference and collision with the dynamic object (here, the moving surgical instrument **910b**) using the distance detected in step **S103** or the like (step **S104**).

(145) As described above, the present embodiment provides high robustness for detecting a subject that moves fast, and high time resolution that are features of the EVS **200**, so that it is possible to quickly capture the surgical instrument by performing image recognition on an EVS image of the EVS **200**. Furthermore, in the present embodiment, such image recognition enables the robot arm **800** to avoid a sudden motion of the surgical instrument and a quick motion such as drop of a raised organ. That is, according to the present embodiment, it is possible to robustly and highly accurately measure and recognize an environment inside an abdominal cavity in real time, so that it is also possible to make scope work of the endoscopic surgery system **5000** autonomous.

3.5 Modified Example

First Modified Example

(146) Furthermore, in the first modified example of the present embodiment, frame rates of the EVS **200** and the RGB sensor **250** having different frame rates may be adjusted to improve accuracy of image recognition. Such a modified example will be described with reference to FIG. **12**. FIG. **12** is a functional block diagram illustrating main components of the CCU **500** according to the first modified example of the present embodiment.

(147) As illustrated in FIG. **12**, the CCU **500** according to the first modified example may include a frame rate adjustment unit **542** provided between the above-described RGB recognition unit **506** and integration information processing/control unit **508**, and an EVS frame adjustment unit **540** provided between the event preprocessing unit **514** (not illustrated in FIG. **12**) and the event information processing unit **516**.

(148) More specifically, the RGB recognition unit **506** acquires an image at a low frame rate of, for example, approximately 30 fps using the RGB sensor **250**, acquires luminance and contrast information from the image, and outputs the acquired information to the EVS frame adjustment unit **540**.

(149) Next, based on the acquired information, the EVS frame adjustment unit (adjustment unit) **540** determines a frame length that is a period for integrating the pixel signals from the EVS **200**, and a frequency for thinning out the pixel signals (images) from the EVS **200**. Note that the frame length or the like may be determined using a model obtained by machine learning in the present modified example. By so doing, it is possible to further improve recognition accuracy of a shape (edge information) of the subject of interest from the EVS image of the EVS **200**.

(150) Furthermore, the event information processing unit **516** generates a suitable EVS image by integrating or performing thinning processing on pixel signals from the EVS **200** based on the

determination of the EVS frame adjustment unit **540**. Furthermore, the event information processing unit **516** may perform subject recognition or the like based on the shape (edge information) of the subject in the generated EVS image.

(151) Furthermore, the frame rate adjustment unit **542** adjusts a frame rate of the image or the like such that that the integration information processing/control unit **508** can suitably perform the integration processing on the EVS image from which the edge information of the subject can be obtained, and the RGB image that is obtained from the RGB sensor **250** and from which segment information of the subject can be obtained. Furthermore, the integration information processing/control unit **508** can accurately recognize the subject by performing integration processing on the adjusted EVS image from which the edge information of the subject can be obtained, and RGB image from which the segment information of the subject can be obtained. Consequently, according to the present modified example, it is possible to robustly and accurately recognize a tumor or the like that is a surgical site even in, for example, a dark abdominal cavity.

Second Modified Example

(152) Furthermore, in the second modified example of the present embodiment, an angle of view indicating a range of a scene captured by the EVS **200** and an angle of view indicating a range of a scene captured by the RGB sensor **250** may be different. In a case where, for example, an image (e.g., an image of the entire inside of the abdominal cavity) for controlling the operation of the robot arm **800** is captured by the EVS **200**, the angle of view indicating the range of the scene captured by the EVS **200** may be made wider than the angle of view indicating the range of the scene captured by the RGB sensor **250** that captures the image (e.g., the image of the tumor that is the surgical site) required by a doctor who does surgery. That is, in present second modified example, the angles of view of the EVS **200** and the RGB sensor **250** may be suitably set according to a use method.

4. Second Embodiment

(153) By the way, an EVS **200** cannot detect an event unless a luminance changes a predetermined threshold or more. Therefore, the EVS **200** cannot capture a subject whose luminance does not change or changes little. Hence, in the second embodiment of the present disclosure, by providing a drive unit that forcibly moves the EVS **200** in a predetermined direction, and thereby forcibly causing luminance to change, the EVS **200** may be encouraged to detect an event.

(154) The second embodiment where an actuator (drive unit) **270** that moves the EVS **200** itself along the predetermined direction is provided will be described with reference to FIG. **13**. FIG. **13** is an explanatory view for describing an example of a configuration of a camera head **100** according to the present embodiment.

(155) As illustrated on the left side of FIG. **13**, when a subject does not make a motion, luminance does not change, an event does not occur, and therefore the EVS **200** cannot capture an image of the subject. Therefore, in the present embodiment, to cause the EVS **200** to forcibly capture the image of the subject, the actuator **270** that can finely move the EVS **200** in a left-right direction is provided as illustrated on the right side of FIG. **13**. In the present embodiment, by causing the actuator **270** to finely move the EVS **200** itself, the EVS **200** detects a luminance change, so that it is possible to capture an image of the subject that does not move. Note that the present embodiment is not limited to the actuator **270** that moves the EVS **200** in the left-right direction, and may be the actuator **270** that finely moves the EVS **200** in an upward-downward direction. Furthermore, the present embodiment is not limited to the actuator that moves the EVS **200**, and an actuator that drives an optical system **400** may be provided.

(156) Furthermore, in the present embodiment, when the EVS **200** cannot detect the subject, the EVS **200** and a light source device **600** may cooperate to change the intensity of light in a short period (i.e., may change a light irradiation cycle) such that a luminance change becomes great. Furthermore, in the present embodiment, when the EVS **200** cannot detect the subject, a threshold to be compared with a luminance change amount may be dynamically changed.

(157) As described above, according to the present embodiment, the EVS **200** can capture even a subject whose luminance does not change or changes little.

5. Third Embodiment

(158) Furthermore, in the third embodiment of the present disclosure described below, an adapter may be attached between a conventional camera head **100a** and an optical system **400** to enable use of an EVS **200**. This third embodiment of the present disclosure will be described with reference to FIG. **14**. FIG. **14** is an explanatory view for describing an example of a configuration of an adapter **150** according to the present embodiment.

(159) More specifically, as illustrated in FIG. **14**, the adapter **150** according to the present embodiment can be attached (inserted) between the conventional camera head **100a** including only an RGB sensor **250**, and the optical system **400**. The adapter **150** includes a prism **260** that disperses light guided from the optical system **400**, to the RGB sensor **250** of the camera head **100a** and the EVS **200** in the adapter **150**, and the EVS **200**.

(160) Furthermore, in the present embodiment, pixel signals from the EVS **200** and the like can be transmitted to a CCU **500** connected with the RGB sensor **250**, and pixel signals or images of two sensors may be subjected to integration processing in the CCU **500**. Alternatively, in the present embodiment, the EVS **200** and the RGB sensor **250** may be connected to separate CCUs, and the pixel signals from these sensors and the like may be processed separately, or may be processed separately, and then be subjected to the integration processing by another information processing device.

(161) As described above, by using the adapter **150** according to the present embodiment, it is possible to easily extend functions such that even an endoscope including the conventional camera head **100a** including only the RGB sensor **250** can use a function of the EVS **200**.

6. Fourth Embodiment

6.1 First Example

(162) By the way, as described above, to avoid a camera head **100** and an optical system **400** supported by a robot arm **800** and a surgical instrument from damaging other organs and tissues when a tumor is excised, the endoscopic surgery system **5000** is required to highly accurately recognize a tumor position at a high speed, and cause the robot arm **800** to autonomously operate according to a recognition result. However, image recognition that uses an RGB image of a conventional RGB sensor has a limit in increasing a frame rate. When a tumor moves at a high speed due to pulsation or the like, a tumor position is tracked while predicting a motion of the tumor using RGB images of previous and subsequent frames. In such a case, a time between frames is long, therefore it is not possible to accurately predict the motion of the tumor that moves at a high speed, the tumor deviates from a set Region Of Interest (ROI), and it is not possible to track the tumor.

(163) Furthermore, although it is also conceivable to set a wide ROI such that the tumor always enters the ROI at a time of tracking, if the ROI is widened, a processing time becomes long. Furthermore, although it is conceivable to attach a high speed camera as alternative means, an inside of an abdominal cavity is narrow, includes many shields, and is dark, and therefore the high speed camera interferes with other sensors, or it is difficult for the high speed camera to clearly capture a subject.

(164) Therefore, in the fourth embodiment of the present disclosure, an RGB sensor **250** and an EVS **200** are combined to make an EVS sensor highly accurately track the tumor position at a high speed, set an ROI on an RGB image based on tracked information, and perform image recognition on the subject. In the present embodiment, high robustness for detecting a subject that moves fast and high time resolution that are features of the EVS **200** make it possible to highly accurately track the tumor position at a high speed. Hereinafter, the present embodiment will be described with reference to FIGS. **15** and **16**. FIG. **15** is a flowchart of an image recognition method according to the first example of the present embodiment, and FIG. **16** is an explanatory view for

describing the first example of the present embodiment.

(165) As illustrated in FIG. 15, the image recognition method according to the present example can mainly include steps of step S201 to step S204. Details of these respective steps according to the present example will be described below.

(166) More specifically, as illustrated in an upper part of FIG. 16, a medical observation system 10 first recognizes the tumor position using an RGB image of the RGB sensor 250 (step S201).

Furthermore, as illustrated in the upper part of FIG. 16, the medical observation system 10 sets an ROI (illustrated by a bold frame in FIG. 16) based on the recognized tumor position (step S202).

(167) Next, as illustrated in the lower part of FIG. 16, the medical observation system 10 tracks the tumor that moves at a high speed using the EVS 200 based on the set ROI (step S203). Note that, although it is required to narrow the ROI as much as possible when tracking is performed using the RGB image, the EVS 200 operates upon detection of an event in response to a luminance change, so that it is not essential to set the narrow ROI, and it is possible to control accuracy of tracking by setting a threshold to be compared with the luminance change. For example, the threshold may be locally lowered, and detection sensitivity may be increased in the first example.

(168) Furthermore, as illustrated in the upper part of FIG. 16, the medical observation system 10 sets the ROI on the RGB image based on a tracking result of the EVS 200, and performs image recognition processing on the tumor using an image in the set ROI (step S204). In the first example, the EVS 200 performs highly accurate tracking, so that it possible to narrow the ROI set on the RGB image. Consequently, according to the first example, it is possible to reduce a load of the image recognition processing of the tumor in the RGB image.

6.2 Second Example

(169) Furthermore, shapes of soft objects such as organs often change, and therefore it is difficult to track these soft organs by image recognition. Therefore, an example of recognition and tracking where a shape change can be captured by combining the RGB sensor 250 and the EVS 200 will be described with reference to FIGS. 17 and 18. FIG. 17 is a flowchart of the image recognition method according to the second example of the present embodiment, and FIG. 18 is an explanatory view for describing the image recognition method according to the second example of the present embodiment.

(170) As illustrated in FIG. 17, the image recognition method according to the present example can mainly include steps of step S301 to step S307. Details of these respective steps according to the present example will be described below.

(171) First, the medical observation system 10 recognizes a target tumor in the RGB image (step S301). Furthermore, the medical observation system 10 acquires the shape of the target tumor in the RGB image (step S302). For example, the acquired shape is an object shape 920a illustrated on the right side of FIG. 18.

(172) Next, the medical observation system 10 acquires, from an EVS image, shape information (edge information) of a shape similar to the shape acquired in step S302 (step S303). For example, the shape acquired from the EVS image is an object shape 930a illustrated on the left side of FIG. 18.

(173) Furthermore, the medical observation system 10 compares the detected shape information (edge information) with the shape information (edge information) of a previous frame, and determines whether or not the shape of the tumor has changed (step S304). More specifically, the object shape 920a in FIG. 18 and the object shape 930a are compared. The medical observation system 10 proceeds to step S305 in a case where the shape has changed (step S304: Yes), and proceeds to step S306 in a case where the shape has not changed (step S304: No).

(174) Next, the medical observation system 10 updates the shape of the tumor (step S305). Here, in a case where the shape has changed from the edge information obtained from the EVS image, processing of updating the shape of the tumor is performed as needed. By repeating this processing, it is possible to track the tumor while capturing the shape change. More specifically, as illustrated

in FIG. 18, for example, an object shape **920b** that is based on the RGB image and an object shape **930b** that is newly acquired from the EVS image one frame after the RGB image are compared to update as an object shape **920c** the object shape that is based on the RGB image in the case where the shape has changed.

(175) Furthermore, the medical observation system **10** determines whether or not an RGB image has been newly imported (step **S306**). The medical observation system **10** proceeds to step **S307** in a case where the RGB image has been newly imported (step **S306**: Yes), and returns to above-described step **S303** in a case where the RGB image has not been imported (step **S306**: No).

(176) Furthermore, the medical observation system **10** performs tumor image recognition on the newly imported RGB image using a tracking result of the EVS **200** (step **S307**).

(177) In the present second example, even when the shape changes, high robustness for detecting a subject that moves fast and high time resolution that are features of the EVS **200** make it possible to track the tumor position highly accurately at a high speed. Note that, in the present second example, the shape of the tumor changes, and therefore a shape of an ROI may also be deformed according to the shape of the tumor.

7. Fifth Embodiment

(178) By the way, although a method for averaging or synthesizing images in a time direction is conceived to suppress a noise amount of the images, if a position of a subject is not correctly adjusted, image quality deteriorates. Although, in a case where a conventional RGB image is used, a motion amount of a tumor is obtained using RGB images of preceding and subsequent frames, and the position of the subject is adjusted based on a motion amount of the subject, there is a limit in increasing a frame rate, and therefore when the subject moves at a high speed, it is difficult to accurately obtain the motion amount of the subject, and accurately adjust the position of the subject in some cases.

(179) Hence, in the fifth embodiment of the present disclosure, it is possible to accurately obtain the motion amount of the subject by combining an RGB sensor **250** and an EVS **200**. As a result, in the present embodiment, it is possible to accurately adjust the position of the subject based on the motion amount of the subject, and consequently achieve a highly accurate noise suppression effect. Hereinafter, the present embodiment will be described with reference to FIGS. 19 and 20. FIG. 19 is a flowchart of an image recognition method according to the present embodiment, and FIG. 20 is an explanatory view for describing the present embodiment.

(180) As illustrated in FIG. 19, the image recognition method according to the present embodiment can mainly include steps of step **S401** to step **S404**. Details of these respective steps according to the present embodiment will be described below.

(181) First, as illustrated on the left side of the upper part of FIG. 20, a medical observation system **10** acquires an RGB image (frame 0) of the RGB sensor **250**, and recognizes a subject (step **S401**). Furthermore, as illustrated in the lower part of FIG. 20, the medical observation system **10** obtains a motion amount of the subject using continuously acquired EVS images based on the recognized subject (step **S402**).

(182) Next, as illustrated on the right side of the upper part of FIG. 20, the medical observation system **10** obtains the motion amount of the subject using the already acquired RGB image (frame 0) and an RGB image (frame 1) newly acquired by the RGB sensor **250** (step **S403**). Furthermore, the medical observation system **10** can obtain the accurate motion amount of the subject by integrating and processing the motion amount from the RGB image and the motion amount from the EVS image (step **S404**).

(183) Note that, in the present embodiment, when the image is dark or when the motion of the subject is fast, the motion amount from the EVS image may be weighted highly compared to the motion amount from the RGB image to calculate a final motion amount of the subject.

Furthermore, in the present embodiment, when the image is bright or when the motion of the subject is slow, the motion amount from the RGB image may be weighted highly compared to the

motion amount from the EVS image to calculate the final motion amount of the subject.

8. Conclusion

(184) As described above, according to each embodiment of the present disclosure, it is possible to robustly and highly accurately measure and recognize a subject in real time.

(185) Note that, in the above-described embodiments of the present disclosure, an imaging target is not limited to an inside of an abdominal cavity, may be living body tissues, a fine mechanical structure, or the like, and is not particularly limited. Furthermore, the above-described embodiments of the present disclosure are not limited to application to medical use, research use, or the like, and can be applied to an observation device that performs, for example, highly accurate analysis using an image. Consequently, the above-described medical observation system **10** can be used as an observation system (observation device).

(186) Furthermore, the above-described medical observation system **10** can be used as a rigid endoscope, a flexible endoscope, an exoscope, a microscope, or the like, and may not include a robot arm **800** or may include only the EVS **200**, and a configuration thereof is not particularly limited, either.

9. Hardware Configuration

(187) An information processing device such as a CCU **500** according to each of the above-described embodiments is realized by, for example, a computer **1000** employing a configuration illustrated in FIG. **21**. Hereinafter, the CCU **500** according to the embodiments of the present disclosure will be described as an example. FIG. **21** is a hardware configuration diagram illustrating an example of a computer that implements the CCU **500** according to the embodiments of the present disclosure. The computer **1000** includes a CPU **1100**, a RAM **1200**, a Read Only Memory (ROM) **1300**, a Hard Disk Drive (HDD) **1400**, a communication interface **1500**, and an input/output interface **1600**. Each unit of the computer **1000** is connected by a bus **1050**.

(188) The CPU **1100** operates based on a program stored in the ROM **1300** or the HDD **1400**, and controls each unit. For example, the CPU **1100** develops in the RAM **1200** a program stored in the ROM **1300** or the HDD **1400**, and executes processing corresponding to various programs.

(189) The ROM **1300** stores a boot program such as a Basic Input Output System (BIOS) executed by the CPU **1100** when the computer **1000** is activated, a program that depends on hardware of the computer **1000**, and the like.

(190) The HDD **1400** is a computer-readable recording medium that non-transiently records a program executed by the CPU **1100**, data used by this program, and the like. More specifically, the HDD **1400** is a recording medium that records a program for the medical observation system **10** according to the present disclosure that is an example of program data **1450**.

(191) The communication interface **1500** is an interface for the computer **1000** to connect to an external network **1550** (e.g., the Internet). For example, the CPU **1100** receives data from another equipment, and transmits data generated by the CPU **1100** to the another equipment via the communication interface **1500**.

(192) The input/output interface **1600** is an interface for connecting an input/output device **1650** and the computer **1000**. For example, the CPU **1100** receives data from an input device such as a keyboard and a mouse via the input/output interface **1600**. Furthermore, the CPU **1100** transmits data to an output device such as a display, a speaker, or a printer via the input/output interface **1600**. Furthermore, the input/output interface **1600** may function as a media interface that reads a program or the like recorded on computer-readable predetermined recording media (media). The media are, for example, optical recording media such as a Digital Versatile Disc (DVD) and a Phase change rewritable Disk (PD), magneto-optical recording media such as a Magneto-Optical disk (MO), tape media, magnetic recording media, semiconductor memories, or the like.

(193) For example, in a case where the computer **1000** functions as the CCU **500** according to the embodiments of the present disclosure, the CPU **1100** of the computer **1000** realizes a function of controlling the medical observation system **10** by executing a program loaded on the RAM **1200**.

Furthermore, the HDD **1400** may store the program for controlling the medical observation system **10** according to the embodiments of the present disclosure. Note that, although the CPU **1100** reads the program data **1450** from the HDD **1400** to execute, the information processing program may be acquired from another device via the external network **1550** in another example.

(194) Furthermore, the CCU **500** according to the present embodiment may be applied to a system including a plurality of devices that assumes connection to a network (or communication between respective devices) such as cloud computing.

(195) An example of the hardware configuration of the CCU **500** has been described above. Each of the above-described components may be configured using a general-purpose part, or may be configured by hardware specialized in the function of each component. Such a configuration can be appropriately changed according to technical levels at times of implementation.

10. Supplementary Note

(196) Note that the embodiments of the present disclosure described above can include, for example, an information processing method executed by the above-described medical observation system **10**, a program for causing the medical observation system **10** to function, and a non-transitory tangible medium in which the program is recorded. Furthermore, the program may be distributed via a communication line (including wireless communication) such as the Internet.

(197) Furthermore, each step of the information processing method according to the above-described embodiments of the present disclosure may not necessarily be processed in the described order. For example, the order of each step may be appropriately changed to perform processing. Furthermore, each step may be processed partially in parallel or individually instead of being processed in chronological order. Furthermore, the processing of each step does not necessarily need to be performed according to the described method, and may be performed by, for example, another method by another functional unit.

(198) It is possible to manually perform all or part of processing described as the processing that is automatically performed among each processing described in each of the above embodiments, or automatically perform by a known method all or part of processing described as the processing that is manually performed. Furthermore, the processing procedures, the specific names, and information including the items of various data and parameters illustrated in the above description and drawings can be arbitrarily changed unless otherwise specified. For example, the various pieces of information illustrated in each drawing are not limited to the illustrated information.

(199) Furthermore, each component of each device illustrated in the drawings is functionally conceptual, and does not necessarily need to be physically configured as illustrated in the drawings. That is, the specific modes of distribution and integration of each device are not limited to the illustrated modes, and all or part thereof can be functionally or physically distributed and integrated in an arbitrary unit according to various loads, usage conditions, and the like.

(200) Although the preferred embodiments of the present disclosure have been described in detail with reference to the accompanying drawings, the technical scope of the present disclosure is not limited to these embodiments. It is obvious that a person having common knowledge in the technical field of the present disclosure can arrive at various modified examples or altered examples within the scope of the technical idea recited in the claims, and it is naturally understood that these modified examples or altered examples also belong to the technical scope of the present disclosure.

(201) Furthermore, the effects described in the description are merely illustrative or exemplary, and are not restrictive. That is, the technique according to the present disclosure can exhibit other effects that are obvious to those skilled in the art from the disclosure of the description together with the above effects or instead of the above effects.

(202) Note that the technique of the present disclosure can also employ the following configurations.

(203) (1) A medical observation device comprising an imaging unit that can image an environment

inside an abdominal cavity of a living body, wherein the imaging unit includes a plurality of first pixels that are aligned in a matrix, and an event detection unit that detects that a luminance change amount of light incident on each of the plurality of first pixels exceeds a predetermined threshold.

(204) (2) The medical observation device according to (1), further comprising a medical light source that irradiates the inside of the abdominal cavity with the light.

(205) (3) The medical observation device according to (1) or (2), wherein the environment inside the abdominal cavity is at least one of a tumor, a surgical site, and a surgical instrument.

(206) (4) The medical observation device according to (2), further comprising an image detection unit that includes a plurality of second pixels that are aligned in a matrix, and detects an image that is based on the light incident on each of the plurality of second pixels.

(207) (5) The medical observation device according to (4), wherein the imaging unit is provided in a distal end part inserted in the inside of the abdominal cavity.

(208) (6) The medical observation device according to (4), further comprising a dispersion unit that guides the light to the imaging unit and the image detection unit.

(209) (7) The medical observation device according to (4), wherein the plurality of first pixels or the plurality of second pixels are disposed on a same light reception surface.

(210) (8) The medical observation device according to (4), further comprising an adjustment unit that adjusts a frame rate of an image obtained by the imaging unit.

(211) (9) The medical observation device according to (4), further comprising a distribution ratio adjustment unit that adjusts a distribution ratio of a light quantity of the incident light between the imaging unit and the image detection unit.

(212) (10) The medical observation device according to any one of (4) to (9), wherein an angle of view of a scene captured by the imaging unit is different from an angle of view of a scene captured by the image detection unit.

(213) (11) The medical observation device according to any one of (1) to (10), further comprising a drive unit that moves the plurality of first pixels along a predetermined direction.

(214) (12) The medical observation device according to (1), further comprising: an optical system that takes in light into the imaging unit; and a drive unit that moves the optical system along a predetermined direction.

(215) (13) The medical observation device according to (4), further comprising a processing unit that processes a first output from the imaging unit, and a second output from the image detection unit.

(216) (14) The medical observation device according to (13), wherein the processing unit recognizes a subject based on the first and second outputs.

(217) (15) The medical observation device according to (13), wherein the processing unit specifies a subject based on the second output; and tracks the subject based on the first output.

(218) (16) The medical observation device according to (13), wherein the processing unit calculates a motion of a subject based on the first and second outputs.

(219) (17) The medical observation device according to (13), wherein the imaging unit is provided in a camera head unit, and the medical observation device further comprises a robot arm that supports the camera head unit.

(220) (18) The medical observation device according to (17), further comprising another robot arm that supports a surgical instrument.

(221) (19) The medical observation device according to (17), further comprising a control unit that performs control to cause the robot arm to autonomously operate based on a processing result of the processing unit.

(222) (20) The medical observation device according to any one of (1) to (19), wherein medical observation device is one of an endoscope, an exoscope, and a microscope.

(223) (21) An observation device comprising: an imaging unit; and an image detection unit, wherein the imaging unit includes a plurality of first pixels that are aligned in a matrix, and an

event detection unit that detects that a luminance change amount of light incident on each of the plurality of first pixels exceeds a predetermined threshold, and the image detection unit includes a plurality of second pixels that are aligned in a matrix, and detects an image that is based on the light incident on each of the plurality of second pixels.

(224) (22) The observation device according to (21), wherein an angle of view of a scene captured by the imaging unit is different from an angle of view of a scene captured by the image detection unit.

(225) (23) The observation device according to (21) or (22), further comprising an adjustment unit that adjusts a frame rate of an image obtained by the imaging unit.

(226) (24) An observation method comprising: by a medical observation device that can image an environment inside an abdominal cavity of a living body: detecting luminance of light incident on each of a plurality of first pixels aligned in a matrix; calculating a change amount of the luminance; and determining whether or not the change amount exceeds a predetermined threshold.

(227) (25) An adapter that comprises a plurality of second pixels aligned in a matrix, and is inserted between a camera head unit and an optical system, the camera head unit including an image detection unit that detects an image that is based on light incident on each of the plurality of second pixels, and the optical system guiding the light to the camera head unit, the adapter comprising an imaging unit that can image an environment inside an abdominal cavity of a living body, wherein the imaging unit includes a plurality of first pixels that are aligned in a matrix, and an event detection unit that detects that a luminance change amount of light incident on each of the plurality of first pixels exceeds a predetermined threshold.

REFERENCE SIGNS LIST

(228) **10** MEDICAL OBSERVATION SYSTEM **100**, **100a** CAMERA HEAD **102**, **502**, **522**, **532**, **602**, **702** COMMUNICATION UNIT **150** ADAPTER **200** EVS **211** DRIVE CIRCUIT **212** SIGNAL PROCESSING UNIT **213** ARBITER UNIT **214** COLUMN PROCESSING UNIT **250** RGB SENSOR **260** PRISM **270** ACTUATOR **300** PIXEL ARRAY UNIT **302** PIXEL **304** LIGHT RECEPTION UNIT **306** PIXEL SIGNAL GENERATION UNIT **308** DETECTION UNIT **310** PERIPHERAL CIRCUIT UNIT **316** DRIVE CONTROL UNIT **400** OPTICAL SYSTEM **410** OPTICAL UNIT **500** CCU **504** RGB SIGNAL/IMAGE PROCESSING UNIT **506** RGB RECOGNITION UNIT **508** INTEGRATION INFORMATION PROCESSING/CONTROL UNIT **514** EVENT PREPROCESSING UNIT **516** EVENT INFORMATION PROCESSING UNIT **520** SYNCHRONIZATION CONTROL UNIT **530** DISPLAY INFORMATION GENERATION UNIT **540** EVS FRAME ADJUSTMENT UNIT **542** FRAME RATE ADJUSTMENT UNIT **600** LIGHT SOURCE DEVICE **604** LIGHT SOURCE CONTROL UNIT **606** LIGHT SOURCE UNIT **700** ROBOT CONTROL UNIT **704** ARM TRAJECTORY GENERATION UNIT **706** ARM CONTROL UNIT **800** ROBOT ARM **802** ARM ACTUATOR **900** DISPLAY DEVICE **910a**, **910b** SURGICAL INSTRUMENT **920a**, **920b**, **920c**, **930a**, **930b** OBJECT SHAPE

Claims

1. A medical observation device, comprising: a first image sensor that includes a plurality of first pixels in a first matrix; a second image sensor that includes a plurality of second pixels in a second matrix; a medical light source configured to irradiate inside of an abdominal cavity of a living body with light; each of the first image sensor and the second image sensor is configured to receive the light from the abdominal cavity; and a prism configured to adjust a distribution ratio between a light quantity of the light received by the first image sensor and a light quantity of the light received by the second image sensor, wherein the first image sensor is further configured to: detect, based on the adjustment of the distribution ratio, a change in luminance of the light received by each pixel of the plurality of first pixels, wherein the change in the luminance is greater than a threshold; and capture, based on the detected change, an image of an environment of the inside of

the abdominal cavity, and the second image sensor is further configured to capture, based on the light received by each pixel of the plurality of second pixels, an image of a surgical site of the living body.

2. The medical observation device according to claim 1, wherein the first image sensor is in a distal end part of the medical observation device, and the distal end part is insertable in the inside of the abdominal cavity.

3. The medical observation device according to claim 1, wherein the prism is further configured to: receive the light from the abdominal cavity; and guide the light received from the abdominal cavity to the first image sensor and the second image sensor.

4. The medical observation device according to claim 1, further comprising a central processing unit (CPU) configured to adjust a frame rate of the image captured by the first image sensor.

5. The medical observation device according to claim 1, wherein the first image sensor is further configured to capture a first scene at a first angle of view, the second image sensor is further configured to capture a second scene at a second angle of view, the second angle of view is different from the first angle of view, and the first scene corresponds to the environment of the inside of the abdominal cavity and the second scene corresponds to the surgical site of the living body.

6. The medical observation device according to claim 1, further comprising a central processing unit (CPU) configured to: process a first output of the image of the environment of the inside of the abdominal cavity; and process a second output of the image of the surgical site of the living body.

7. The medical observation device according to claim 6, wherein the CPU is further configured to recognize a subject based on the first output and the second output.

8. The medical observation device according to claim 6, wherein the CPU is further configured to: recognize a subject based on the first output; and track the subject based on the second output.

9. The medical observation device according to claim 6, wherein the CPU is further configured to calculate a motion of a subject based on the first output and the second output.

10. The medical observation device according to claim 6, further comprising a first robot arm configured to support the first image sensor.

11. The medical observation device according to claim 10, further comprising a second robot arm configured to support a surgical instrument.

12. The medical observation device according to claim 10, wherein the CPU is further configured to control, based on the first output and the second output, an autonomous operation of the first robot arm.

13. The medical observation device according to claim 1, wherein the environment is at least one of a tumor, the surgical site, or a surgical instrument.

14. The medical observation device according to claim 1, further comprising an actuator configured to move the plurality of first pixels along a specific direction.

15. The medical observation device according to claim 1, further comprising: an optical system configured to: receive the light from the abdominal cavity; and guide the light received from the abdominal cavity into the first image sensor; and an actuator configured to move the optical system along a specific direction.

16. The medical observation device according to claim 1, wherein the medical observation device is one of an endoscope, an exoscope, or a microscope.

17. An observation device, comprising: a first image sensor that includes a plurality of first pixels in a first matrix, wherein the first image sensor is configured to: receive light by each pixel of the plurality of first pixels; detect a change in luminance of the light received by each pixel of the plurality of first pixels, wherein the change in the luminance is greater than threshold; and capture, based on the detected change, a first scene at a first angle of view; and a second image sensor that includes a plurality of second pixels in a second matrix, wherein the second image sensor is configured to: receive the light by each pixel of the plurality of second pixels; and capture, based

on the light received by each pixel of the plurality of second pixels, a second scene at a second angle of view, and the second angle of view is different from the first angle of view.

18. The observation device according to claim 17, further comprising a central processing unit (CPU) configured to adjust a frame rate of the first scene captured by the first image sensor.

19. An observation method, comprising: in a medical observation device that includes a first image sensor, a second image sensor, a medical light source, a prism, and a central processing unit (CPU): irradiating, by the medical light source, inside of an abdominal cavity of a living body with light; receiving, by each of the first image sensor and the second image sensor, the light from the abdominal cavity; adjusting, by the prism, a distribution ratio between a light quantity of the light received by the first image sensor and a light quantity of the light received by the second image sensor; detecting, by the first image sensor, luminance of the light received by each pixel of a plurality of first pixels, wherein the luminance is detected based on the adjustment of the distribution ratio, and the first image sensor includes the plurality of first pixels in a first matrix; calculating, by the first image sensor, a change in the detected luminance; determining, by the first image sensor, the change in the luminance is greater than a threshold; capturing, by the first image sensor, based on the determination that the change in the luminance is greater than the threshold, an image of an environment of the inside of the abdominal cavity; and capturing, by the second image sensor, based on the light received by each pixel of a plurality of second pixels, an image of a surgical site of the living body, wherein the second image sensor includes the plurality of second pixels in a second matrix.
