

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397240
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Milton; Robert et al.

Crutch mountable toy assembly

Abstract

A crutch mountable toy assembly for personalizing or decorating a crutch includes a three-dimensional body shape formed by an outer casing with a top end and a bottom end. The three-dimensional body shape defines a torso. A fastener capable of repeatedly opening and closing is attached to the torso. A resiliently compressible material is enclosed within the outer casing, defining a filling that expands the outer casing outwardly into the three-dimensional body shape. The three-dimensional body shape also has a channel therein extending into the top end and outwardly through the bottom end. The channel can encircle the crutch within the three-dimensional body shape. The outer casing also has a slit therein extending into the channel and outwardly through the outer casing. The channel is accessible through the slit. The fastener may be positioned adjacent to the slit, capable of overlaying and extending across the slit when the fastener is closed.

Inventors:	Milton; Robert (Birmingham, AL), Milton; Kelsie (Birmingham, AL)
Applicant:	Milton; Robert (Birmingham, AL); Milton; Kelsie (Birmingham, AL)
Family ID:	1000008778208
Appl. No.:	18/221248
Filed:	July 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250017807 A1	Jan. 16, 2025

Publication Classification

Int. Cl.: **A63H3/00** (20060101); **A45B3/00** (20060101); **A61H3/02** (20060101); **A63H3/02** (20060101); **A63H3/50** (20060101)

U.S. Cl.:

CPC **A63H3/003** (20130101); **A45B3/00** (20130101); **A61H3/02** (20130101); **A63H3/02** (20130101); **A63H3/50** (20130101);

Field of Classification Search

CPC: A61H (3/02); A63H (3/003); A63H (3/02); A63H (3/50); A45B (3/00)

USPC: 446/71; 446/72; 446/369; 446/371; 446/372; 135/66; 135/120.1

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
847066	12/1906	Hall	472/137	A45B 3/00
1488890	12/1923	Muller	446/338	A63H 3/18
1641057	12/1926	Sweet	446/314	A63H 11/04
2347405	12/1943	Ford	446/369	A63H 3/02
D323363	12/1991	Ely	N/A	N/A
5078640	12/1991	Berman	446/72	A63H 3/003
5114185	12/1991	Reedom	280/801.1	B60R 22/00
D378551	12/1996	Shelnutt	N/A	N/A
5978962	12/1998	Hamowy	2/24	A41D 13/0568
6824112	12/2003	Lange	248/105	A61J 9/0607
7921860	12/2010	McQueen	135/66	A45B 3/10
2003/0214162	12/2002	Romano	N/A	N/A
2006/0011786	12/2005	Finney	248/118	A63H 3/02
2009/0056778	12/2008	Dean	N/A	N/A
2009/0104837	12/2008	Manwaring	N/A	N/A
2012/0227776	12/2011	Neitzel	135/73	A61H 3/02
2017/0216732	12/2016	Frazier	N/A	A63G 17/00
2019/0191941	12/2018	Brunelle	N/A	A63H 3/005
2019/0192980	12/2018	Vogel	N/A	A45C 13/42
2019/0374864	12/2018	Cragle	N/A	A63H 3/003
2021/0196060	12/2020	Lawson	N/A	A63H 3/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO03088866	12/2002	WO	N/A

Primary Examiner: Canfield; Robert

Background/Summary**CROSS-REFERENCE TO RELATED APPLICATIONS**

(1) Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(2) Not Applicable

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

(3) Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

(4) Not Applicable

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT INVENTOR

(5) Not Applicable

BACKGROUND OF THE INVENTION

(1) Field of the Invention

(6) The disclosure relates to embellishments and more particularly pertains to a new embellishment for personalizing or decorating a crutch, cane, walker, or other mobility assisting device.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

(7) The prior art relates to embellishments and crutch mountable toy assemblies. Many prior art references relate to cushioning devices configured to increase the under-arm padding of a crutch. Other references relate to ornamental designs for crutch tips, such as fake shoes. However, there is a need in the field for a soft, plushie decorative embellishment designed to wrap around a shaft of a crutch, cane, walker, or other mobility assisting device, making the mobility assisting device more whimsical.

BRIEF SUMMARY OF THE INVENTION

(8) An embodiment of the disclosure meets the needs presented above by generally comprising an embellishment configured for placement on a crutch. More specifically, the present disclosure contemplates a body that is configured to be removably positioned on a crutch. The body generally comprises an outer casing having a top end and a bottom end, the outer casing being formed into a three-dimensional body shape defining a torso. A fastener is positioned on and attached to the torso. The fastener is configured to repeatedly transition between an open position and a closed position. A resiliently compressible material is enclosed within the outer casing, defining a filling configured to expand the outer casing outwardly into the three-dimensional body shape. The three-dimensional body shape has a channel therein extending into the top end and outwardly through the bottom end. The channel is configured to encircle the crutch within the three-dimensional body shape. The outer casing is configured to exclude the filling from the channel. The outer casing also has a slit therein extending into the channel and outwardly through the outer casing. The outer casing is configured to exclude the filling from the slit so that the channel is accessible through the slit. The fastener may be positioned adjacent to the slit, the slit being configured to receive the crutch to position the three-dimensional body shape on the crutch when the fastener is in the open position, and the fastener overlaying and extending across the slit when the fastener is in the closed position.

(9) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(10) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

- (1) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:
- (2) FIG. 1 is a top isometric view of a crutch mountable toy assembly according to an embodiment of the disclosure.
- (3) FIG. 2 is a rear isometric view of an embodiment of the disclosure.
- (4) FIG. 3 is a top view of an embodiment of the disclosure.
- (5) FIG. 4 is a bottom view of an embodiment of the disclosure.
- (6) FIG. 5 is a front view of an embodiment of the disclosure.
- (7) FIG. 6 is a cross-sectional view of an embodiment of the disclosure.
- (8) FIG. 7 is an exploded in-use view of an embodiment of the disclosure.
- (9) FIG. 8 is an in-use view of an embodiment of the disclosure.
- (10) FIG. 9 is an in-use view of an alternative embodiment of the disclosure.

DETAILED DESCRIPTION OF THE INVENTION

- (11) With reference now to the drawings, and in particular to FIGS. 1 through 9 thereof, a new embellishment embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral 10 will be described.
- (12) As best illustrated in FIGS. 1 through 6, the crutch mountable toy assembly 10 generally comprises a body 12 that is configured to be removably positioned on a crutch, cane, walker, or other mobility assisting device 50. For brevity's sake, the crutch, cane, walker, or other mobility assisting device 50 will be referred to herein as a crutch 50. However, that is merely intended as a convenient shorthand and is not intended to limit the use of the disclosed embellishment for use in a crutch or to exclude the embellishment's use on other objects or devices. For example, the disclosed crutch mountable toy assembly 10 could be used to embellish nearly any vertically oriented column, rod, shaft, leg, or object.
- (13) The body 12 generally comprises an outer casing 14 having a top end 16 and a bottom end 18. The outer casing 14 may be formed into a three-dimensional body shape 20 defining a torso 22 and a head 24 that is attached to and extends outwardly from the torso 22. In exemplary embodiments, the head 24 may be proximate to the top end 16. Certain embodiments may also include a limb 26 that is attached to and extends outwardly from the torso 22. For example, the limb 26 may be positioned proximate to the bottom end 18. Some embodiments, such as the embodiment depicted in FIGS. 1-8, may include a plurality of limbs 26 arranged around the torso 22 as appendages including arms, legs, tails, or some combination thereof. Other embodiments, such as the one depicted in FIG. 9, may only include a torso 22.
- (14) In certain embodiments, a plurality of decorative pieces 28 may be affixed to the head 24. An example of such an embodiment is depicted in FIGS. 1-8. In other embodiments, such as the one depicted in FIG. 9, the plurality of decorative pieces 28 may be affixed on the torso 22. The plurality of decorative pieces 28 may be formed of any suitable material, including a rubber or plastic composite or by stitching. In some embodiments, the plurality of decorative pieces 28 are permanently affixed to the outer casing 14. In other embodiments, the plurality of decorative pieces 28 may be movably or temporarily attached to the outer casing 14, for example by a hook-and-loop adhesive, snaps, magnets, or another suitable fastening device. In such embodiments, the user can adjust the arrangement of the plurality of decorative pieces 28 for further embellishment, personalization, or whimsy.
- (15) Embodiments of the present disclosure also include a fastener 30 that is positioned on and attached to the torso 22. The fastener 30 is configured to repeatedly transition between an open position, for example as depicted in FIG. 7, and a closed position, for example as depicted in FIG. 2. The fastener 30 may be formed of any suitable means, including a hook and loop adhesive

material, an assembly of magnets, a snapping mechanism, a zipper, or some combination thereof. (16) As shown in FIG. 6, a resiliently compressible material **32** is enclosed within the outer casing **14**. The resiliently compressible material **32** defines a filling **32** configured to expand the outer casing **14** outwardly into the three-dimensional body shape **20**. The resiliently compressible material **32** may be formed of any soft and cushiony material, including cotton, linen, bamboo, hemp, polyester, rayon, or some combination thereof.

(17) Embodiments of the three-dimensional body shape **20** have a channel **34** therein extending into the top end **16** and outwardly through the bottom end **18**. The channel **34** is generally configured to encircle the crutch **50** within the three-dimensional body shape **20**. The outer casing **14** is generally configured to exclude the filling **32** from the channel **34**.

(18) The outer casing **14** also includes a slit **36** therein extending into the channel **34** and outwardly through the outer casing **14**. The outer casing **14** may generally be configured to exclude the filling **32** from the slit **36**. In preferred embodiments, the channel **34** is accessible through the slit **36**. The fastener **30** may be adjacent to the slit **36**. The slit **36** is generally configured to receive the crutch **50**, allowing the user to position the three-dimensional body shape **20** on the crutch **50** when the fastener **30** is in the open position, an example of which is shown in FIG. 7. The fastener **30** may be configured to overlay and extend across the slit **36** when the fastener **30** is in the closed position, an example of which is depicted in FIG. 2.

(19) In use, the user may position the crutch mountable toy assembly **10** over a portion of a crutch **50**. As shown in FIG. 7, the user can adjust the fastener **30** to the open position, then slide the crutch **50** through the slit **36**, following the trajectory of the dashed line in FIG. 7. FIG. 8 provides an in-use view of the embodiment depicted by FIG. 7. FIG. 9 provides an in-use view of an alternative embodiment of the present disclosure. As shown in FIGS. 8 and 9, the crutch mountable toy assembly **10** can be placed near the bottom of the crutch **50**. The channel **34** fits snugly around the crutch **50**, so that when the fastener **30** is in the closed position, the crutch mountable toy assembly **10** will remain attached to the crutch **50** and capable of maintaining its general position on the crutch **50**.

(20) With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(21) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A body being configured to be removably positioned on a crutch comprising: an outer casing having a top end and a bottom end, the outer casing being formed into a three-dimensional body shape defining a torso; a fastener being positioned on and attached to the torso, the fastener being configured to repeatedly transition between an open position and a closed position; a resiliently compressible material being enclosed within the outer casing and defining a filling configured to

expand the outer casing outwardly into the three-dimensional body shape; the three-dimensional body shape having a channel therein extending into the top end and outwardly through the bottom end, the channel being configured to encircle the crutch within the three-dimensional body shape, the outer casing being configured to exclude the filling from the channel; and the outer casing having a slit therein extending into the channel and outwardly through the outer casing, the outer casing being configured to exclude the filling from the slit, the channel being accessible through the slit, the fastener being adjacent to the slit, the slit being configured to receive the crutch to position the three-dimensional body shape on the crutch when the fastener is in the open position, the fastener overlaying and extending across the slit when the fastener is in the closed position.

2. The body of claim 1, the three-dimensional body shape further defining a head attached to and extending outwardly from the torso.
3. The body of claim 2, the head further comprising a plurality of decorative pieces being affixed to the head, the plurality of decorative pieces being formed of a plastic composite or being formed by stitching.
4. The body of claim 3, wherein the plurality of decorative pieces is arranged to resemble a face.
5. The body of claim 2, wherein the head is proximate to the top end.
6. The body of claim 1, the three-dimensional body shape further defining a limb attached to and extending outwardly from the torso.
7. The body of claim 6, wherein the limb is proximate to the bottom end.
8. The body of claim 6, the limb further comprising a plurality of limbs arranged around the torso in a configuration depicting an arm, a leg, a tail, or some combination thereof.
9. The body of claim 1, wherein the fastener is formed of a hook and loop adhesive material, an assembly of magnets, a snap mechanism, a zipper mechanism, or some combination thereof.
10. The body of claim 1, wherein the resiliently compressible material is formed of a soft and cushiony material selected from the group consisting of cotton, linen, bamboo, hemp, polyester, rayon, or some combination thereof.
11. A body being configured to be removably positioned on a crutch comprising: an outer casing having a top end and a bottom end, the outer casing being formed into a three-dimensional body shape defining a torso; a fastener being positioned on and attached to the torso, the fastener being configured to repeatedly transition between an open position and a closed position; a resiliently compressible material being enclosed within the outer casing and defining a filling configured to expand the outer casing outwardly into the three-dimensional body shape, the resiliently compressible material being formed of a soft and cushiony material, the soft and cushiony material being cotton; the three-dimensional body shape having a channel therein extending into the top end and outwardly through the bottom end, the channel being configured to encircle the crutch within the three-dimensional body shape, the outer casing being configured to exclude the filling from the channel; and the outer casing having a slit therein extending into the channel and outwardly through the outer casing, the outer casing being configured to exclude the filling from the slit, the channel being accessible through the slit, the fastener being adjacent to the slit, the slit being configured to receive the crutch to position the three-dimensional body shape on the crutch when the fastener is in the open position, the fastener overlaying and extending across the slit when the fastener is in the closed position.
12. The body of claim 11, the three-dimensional body shape further defining a head attached to and extending outwardly from the torso.
13. The body of claim 12, the head further comprising a plurality of decorative pieces being affixed to the head, the plurality of decorative pieces being formed of a plastic composite or being formed by stitching.
14. The body of claim 11, the torso further comprising a plurality of decorative features being affixed to the torso, the plurality of decorative pieces being arranged to resemble a face.
15. The body of claim 11, the three-dimensional body shape further defining a limb attached to and

extending outwardly from the torso.

16. The body of claim 15, wherein the limb is proximate to the bottom end.

17. The body of claim 15, the limb further comprising a plurality of limbs arranged around the head and the torso in a configuration depicting an arm, a leg, a tail, an ear, or some combination thereof.

18. The body of claim 11, wherein the fastener is formed of a hook and loop adhesive material, an assembly of magnets, a snap mechanism, a zipper mechanism, or some combination thereof.

19. The body of claim 11, wherein the resiliently compressible material is formed of a soft and cushiony material such as cotton, linen, bamboo, hemp, polyester, rayon, or some combination thereof.

20. A body being configured to be removably positioned on a crutch comprising: an outer casing having a top end and a bottom end, the outer casing being formed into a three-dimensional body shape defining a torso, a head being attached to and extending outwardly from the torso, the head being proximate the top end, a limb being attached to and extending outwardly from the torso, the limb being proximate the bottom end; a plurality of decorative pieces being permanently affixed to the head, the plurality of decorative features being formed of a plastic composite or being formed by stitching; a fastener being positioned on and attached to the torso, the fastener being configured to repeatedly transition between an open position and a closed position, the fastener being formed of a hook and loop adhesive material; a resiliently compressible material being enclosed within the outer casing and defining a filling configured to expand the outer casing outwardly into the three-dimensional body shape, the resiliently compressible material being formed of a soft and cushiony material, the soft and cushiony material being cotton; the three-dimensional body shape having a channel therein extending into the top end and outwardly through the bottom end, the channel being configured to encircle the crutch within the three-dimensional body shape, the outer casing being configured to exclude the filling from the channel; and the outer casing having a slit therein extending into the channel and outwardly through the outer casing, the outer casing being configured to exclude the filling from the slit, the channel being accessible through the slit, the fastener being adjacent to the slit, the slit being configured to receive the crutch to position the three-dimensional body shape on the crutch when the fastener is in the open position, the fastener overlaying and extending across the slit when the fastener is in the closed position.
