

# US Patent & Trademark Office

## Patent Public Search | Text View

|                      |                           |
|----------------------|---------------------------|
| United States Patent | 12398535                  |
| Kind Code            | B2                        |
| Date of Patent       | August 26, 2025           |
| Inventor(s)          | Iwashita; Hidekazu et al. |

### Turning unit of construction machine

#### Abstract

Formed inside a housing of a slewing unit are: an upper outer space located outside a piston in the radial direction, and at least one supply passage that guides, inward in the radial direction, a lubricant that has passed through a lower space, an outer passage, and an upper outer space in this order, to the lubricant to a plurality of brake members located below the piston. The plurality of brake members are disposed above a speed reducer and receive pressing force from the piston to brake the rotation of a rotation shaft before the rotation is decelerated by the speed reducer.

|                              |                                                                                                                                                                   |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inventors:</b>            | Iwashita; Hidekazu (Hyogo, JP), Terauchi; Kenichi (Hiroshima, JP), Hamasaki; Masatsugu (Hiroshima, JP), Abe; Takamasa (Hiroshima, JP), Kamon; Yoshiki (Hyogo, JP) |
| <b>Applicant:</b>            | KOBELCO CONSTRUCTION MACHINERY CO., LTD. (Hiroshima, JP)                                                                                                          |
| <b>Family ID:</b>            | 1000008778242                                                                                                                                                     |
| <b>Assignee:</b>             | KOBELCO CONSTRUCTION MACHINERY CO., LTD. (Hiroshima, JP)                                                                                                          |
| <b>Appl. No.:</b>            | 18/259424                                                                                                                                                         |
| <b>Filed (or PCT Filed):</b> | December 16, 2021                                                                                                                                                 |
| <b>PCT No.:</b>              | PCT/JP2021/046465                                                                                                                                                 |
| <b>PCT Pub. No.:</b>         | WO2022/149429                                                                                                                                                     |
| <b>PCT Pub. Date:</b>        | July 14, 2022                                                                                                                                                     |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240318406 A1          | Sep. 26, 2024           |

## Foreign Application Priority Data

JP 2021-000855 Jan. 06, 2021

---

## Publication Classification

**Int. Cl.:** B66C23/00 (20060101); B66C23/84 (20060101); E02F9/12 (20060101); F16D55/40 (20060101); F16D121/04 (20120101)

**U.S. Cl.:**

CPC E02F9/128 (20130101); B66C23/84 (20130101); E02F9/126 (20130101); F16D55/40 (20130101); F16D2121/04 (20130101)

## Field of Classification Search

**CPC:** B66C (23/84); B66C (23/86); B66C (23/163); B66C (2700/0342); B66C (2700/0371)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name     | U.S. Cl. | CPC            |
|--------------|-------------|-------------------|----------|----------------|
| 3539053      | 12/1969     | Hefferin          | 192/225  | F16D<br>55/228 |
| 2008/0029354 | 12/2007     | Yoshimatsu et al. | N/A      | N/A            |
| 2015/0099604 | 12/2014     | Hamasaki et al.   | N/A      | N/A            |
| 2015/0126319 | 12/2014     | Hamasaki et al.   | N/A      | N/A            |

### FOREIGN PATENT DOCUMENTS

| Patent No.      | Application Date | Country | CPC        |
|-----------------|------------------|---------|------------|
| 103080589       | 12/2012          | CN      | B66C 23/84 |
| 103097759       | 12/2012          | CN      | B60T 1/062 |
| 10025693        | 12/2000          | DE      | B66C 23/86 |
| 202012009167    | 12/2013          | DE      | B66C 23/02 |
| 2 540 916       | 12/2012          | EP      | N/A        |
| 2843264         | 12/2014          | EP      | B60T 1/062 |
| 2140086         | 12/1983          | GB      | B60T 13/22 |
| 2006-25580      | 12/2005          | JP      | N/A        |
| 4608384         | 12/2010          | JP      | N/A        |
| 2011-21 4586    | 12/2010          | JP      | N/A        |
| 2013-227798     | 12/2012          | JP      | N/A        |
| 2013-228055     | 12/2012          | JP      | N/A        |
| 6276782         | 12/2017          | JP      | B66C 23/84 |
| 10-2004-0055954 | 12/2003          | KR      | N/A        |

### OTHER PUBLICATIONS

*Primary Examiner:* Marcelo; Emmanuel M

*Attorney, Agent or Firm:* Oblon, McClelland, Maier & Neustadt, L.L.P.

---

## **Background/Summary**

### **TECHNICAL FIELD**

(1) The present disclosure relates to a slewing unit of a construction machine.

### **BACKGROUND ART**

(2) A construction machine, such as a crane, includes a slewing unit for slewing an upper slewing body mounted on a machine body with respect to the machine body. This slewing unit includes a speed reducer that decelerates the rotation of a slewing motor, and a brake mechanism. The speed reducer decelerates the rotation of the slewing motor to increase driving torque, and transmits the rotational force to a pinion (output shaft).

(3) For example, the speed reducer of the slewing unit in Patent Literatures 1 to 3 is a three-stage planetary speed reducer, and includes a first deceleration portion connected to a slewing motor, a second deceleration portion connected to the first deceleration portion, and a third deceleration portion connected to the second deceleration portion. The brake mechanism includes a plurality of brake members (plurality of brake plates) located between the first deceleration portion and the second deceleration portion, and brakes the rotation after being decelerated by the first deceleration portion. These first deceleration portion, the plurality of brake plates, the second deceleration portion, and the third deceleration portion are accommodated in a cylindrical housing in this order. A lubricant is stored in the housing.

(4) Normally, the lubricant is stored up to the height of the first deceleration portion, or the height of the top deceleration portion in the housing. With this configuration, lubrication of all the deceleration portions and lubrication of the plurality of brake plates located between the first deceleration portion and the second deceleration portion are performed.

(5) In that connection, there is a case where a breather having functions such as intake, exhaust, and air filter is attached at the upper portion of the housing of the slewing unit. In this case, to prevent the lubricant in the housing from leaking out of the breather, it is necessary to secure a certain degree of air volume in the housing. As a means for securing the air volume, for example, increasing the size of the housing can be considered. However, since the slewing unit is required to have a size that does not interfere with various parts arranged around the slewing unit, it is undesirable to increase the size of the housing.

### **CITATION LIST**

Patent Literatures

(6) Patent Literature 1: Japanese Patent No. 4608384 Patent Literature 2: JP 2013-227798 A Patent Literature 3: JP 2011-214586 A

### **SUMMARY OF INVENTION**

(7) The present disclosure has been made in view of the above-described problem, and an object of the present disclosure is to provide a slewing unit of a construction machine that can secure an appropriate air volume in a housing and appropriately lubricate a speed reducer and brake members

while suppressing an increase in the size of the housing.

(8) The provided slewing unit of a construction machine includes: a rotation shaft to which rotational force of a slewing motor is transmitted, the rotation shaft extending in an up-and-down direction; a speed reducer to decelerate rotation of the rotation shaft; a piston located to surround the rotation shaft with a spacing to the rotation shaft outside the rotation shaft in a radial direction, the piston being displaceable in the up-and-down direction; a housing that accommodates the rotation shaft, the speed reducer, and the piston, the housing including a guide portion that is located to surround the piston to guide the piston in the up-and-down direction; and a plurality of brake members that includes: a rotation side brake member that is located to surround the rotation shaft and rotates as the rotation shaft rotates; and a housing side brake member supported by the housing to face the rotation side brake member in the up-and-down direction, the plurality of brake members being located below the piston, in which an upper central space in which at least part of the rotation shaft is disposed, the upper central space being a space surrounded by an inner circumferential surface of the piston; a lower space in which the speed reducer is disposed, the lower space being located below the upper central space; an upper outer space located outside the piston in the radial direction and above the lower space; an outer passage that connects the lower space to the upper outer space; and at least one supply passage that guides, inward in the radial direction, a lubricant that has passed through the lower space, the outer passage, and the upper outer space in this order to supply the lubricant to the plurality of brake members located below the piston are formed in the housing, and the plurality of brake members is disposed above the speed reducer and is configured to brake, by receiving pressing force from the piston, the rotation of the rotation shaft before being decelerated by the speed reducer.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a side view showing a construction machine including a slewing unit according to an embodiment.
- (2) FIG. 2 is a schematic diagram showing a slewing drive device including the slewing unit.
- (3) FIG. 3 is a side view showing part of the slewing drive device, and depicts a cross section of part of the slewing unit.
- (4) FIG. 4 is a cross-sectional view of the slewing unit, and is a view showing a cross section parallel to a rotation shaft of the slewing unit.
- (5) FIG. 5 is a cross-sectional view taken along the line V-V of FIG. 4, and is a view showing a cross section perpendicular to the rotation shaft of the slewing unit.
- (6) FIG. 6 is a perspective view of the slewing unit cut at the same position as in FIG. 5.
- (7) FIG. 7 is a cross-sectional view taken along the line VII-VII of FIG. 4, and is a view showing a cross section perpendicular to the rotation shaft of the slewing unit.
- (8) FIG. 8 is a perspective view of the slewing unit cut at the same position as in FIG. 7.
- (9) FIG. 9 is a cross-sectional view taken along the line IX-IX of FIG. 4, and is a view showing a cross section perpendicular to the rotation shaft of the slewing unit.
- (10) FIG. 10 is a perspective view of the slewing unit cut at the same position as in FIG. 9.
- (11) FIG. 11 is a cross-sectional view taken along the line XI-XI of FIG. 4, and is a view showing a cross section perpendicular to the rotation shaft of the slewing unit.
- (12) FIG. 12 is a perspective view of the slewing unit cut at the same position as in FIG. 11.
- (13) FIG. 13 is a cross-sectional view showing part of the slewing unit according to a first modification of the embodiment.
- (14) FIG. 14 is a cross-sectional view showing part of the slewing unit according to a second modification of the embodiment.

## DESCRIPTION OF EMBODIMENT

(15) An embodiment of the present disclosure will be described below with reference to the drawings.

(16) [Construction Machine]

(17) FIG. 1 is a side view showing a crane **100** including a slewing unit according to the embodiment. The crane **100** is one example of a construction machine. As shown in FIG. 1, the crane **100** includes a self-travelling lower travelling body **101** and an upper slewing body **102** slewably supported on the lower travelling body **101**.

(18) The upper slewing body **102** includes a slewing frame **103** mounted on the lower travelling body **101** so as to be slewable about a vertical axis, an attachment **104** attached to the front of the slewing frame **103** so as to be hoisted and lowered, a hook **105** suspended from the tip of the attachment **104** via a rope R (wire rope), a winch device **107**, and a slewing drive device **1**.

(19) The attachment **104** may include a boom as shown in FIG. 1 and may further include a jib pivotably attached to the distal end of the boom. A hoist load **106** is suspended from the hook **105**. The winch device **107** winds up or pays out the rope R connected to the hook **105**, thereby causing the hook **105** to perform an up-and-down operation for hoisting work.

(20) [Slewing Drive Device]

(21) FIG. 2 is a schematic diagram showing the slewing drive device **1** including a slewing unit **3** according to the present embodiment. The slewing drive device **1** is a device for slewing the upper slewing body **102** with respect to the lower travelling body **101**. The slewing drive device **1** includes a slewing motor **2**, the slewing unit **3**, and an output shaft **4**.

(22) The slewing motor **2** includes, for example, a motor such as a hydraulic motor or an electric motor. The slewing unit **3** includes a brake mechanism **10** and a speed reducer **30**. The speed reducer **30** increases driving torque while decelerating the rotation of the slewing motor **2**, and transmits the rotational force to the output shaft **4**. The output shaft **4** includes, for example, a pinion, and is disposed to mesh with a slewing ring gear (slewing circle) (not shown). The rotational force of the output shaft **4** is transmitted to the upper slewing body **102** via the slewing ring gear. This allows the upper slewing body **102** to slew about the vertical axis with respect to the lower travelling body **101**.

(23) [Slewing Unit]

(24) The slewing unit **3** according to the present embodiment will be specifically described below. FIG. 3 is a side view showing part of the slewing drive device **1**, and depicts a cross section of part of the slewing unit **3**.

(25) The slewing unit **3** includes a rotation shaft **71** to which the rotational force of the slewing motor **2** is transmitted, a rotation member **72**, the speed reducer **30**, a spider **20**, a plurality of brake members **13** and **15**, a piston **11**, a spring **17**, a housing **60**, and a breather **97**. The piston **11** and the plurality of brake members **13** and **15** constitute the brake mechanism **10** described above. The spring **17** is one example of a biasing member, and the spider **20** is one example of a supporting member.

(26) The rotation shaft **71** is a cylindrical member extending downward from the slewing motor **2**, and is connected to the slewing motor **2** such that the rotational force of the slewing motor **2** is transmitted.

(27) The rotation member **72** is a member having a shape surrounding the rotation shaft **71**, and is fixed to the rotation shaft **71** to rotate together with the rotation shaft **71**. The rotation member **72** includes a spider attachment portion to which the spider **20** is attached and a lower portion **31** located below the spider attachment portion. This lower portion **31** functions as a sun gear **31** to be described later in the speed reducer **30**.

(28) The speed reducer **30** includes at least one deceleration portion for decelerating the rotation of the rotation shaft **71**. In the present embodiment, the speed reducer **30** includes a plurality of deceleration portions arranged in the up-and-down direction. FIG. 3 shows only the top first

deceleration portion. The first deceleration portion includes the sun gear **31**, a plurality of planetary gears **32** located around the sun gear **31**, and a ring gear **33**. In the first deceleration portion, the plurality of planetary gears **32** revolves while rotating, thereby deaccelerating the rotation of the rotation shaft **71**. The second deceleration portion located below the first deceleration portion includes a sun gear (not shown) and a plurality of planetary gears (not shown). The rotation decelerated by the first deceleration portion may be further decelerated by the second deceleration portion, and the rotational force may be transmitted to the output shaft **4**. In addition, the third deceleration portion may be further located below the second deceleration portion. In this case, the rotation decelerated by the second deceleration portion is further decelerated by the third deceleration portion, and the rotational force is transmitted to the output shaft **4**.

(29) FIG. **4** is a view showing a cross section parallel to the rotation shaft **71** of the slewing unit **3**, and is a cross-sectional view when the slewing unit **3** is cut at a position different from FIG. **3**. FIG. **5** is a cross-sectional view taken along the line V-V of FIG. **4**. FIG. **6** is a perspective view of the slewing unit **3** when the slewing unit **3** is cut at the same position as in FIG. **5**. FIG. **7** is a cross-sectional view taken along the line VII-VII of FIG. **4**. FIG. **8** is a perspective view of the slewing unit **3** when the slewing unit **3** is cut at the same position as in FIG. **7**. FIG. **9** is a cross-sectional view taken along the line IX-IX of FIG. **4**. FIG. **10** is a perspective view of the slewing unit **3** when the slewing unit **3** is cut at the same position as in FIG. **9**. FIG. **11** is a cross-sectional view taken along the line XI-XI of FIG. **4**. FIG. **12** is a perspective view of the slewing unit **3** when the slewing unit **3** is cut at the same position as in FIG. **11**.

(30) The spider **20** is a member that supports the rotation side brake members **13** such that the rotation side brake members **13** rotate as the rotation shaft **71** rotates. The spider **20** has a shape that surrounds the rotation shaft **71**. Specifically, the spider **20** has an annular shape in plan view, and the outer diameter of the upper portion of the spider **20** is greater than the outer diameter of the lower portion of the spider **20**. The plurality of rotation side brake members **13** to be described later is attached to the outer circumferential surface of the upper portion of the spider **20**. The spider **20** is disposed between the plurality of rotation side brake members **13** and the rotation shaft **71**. The spider **20** is disposed above the sun gear **31**. Specifically, the spider **20** is supported by the rotation shaft **71** by being attached to the spider attachment portion of the rotation member **72**. More specifically, the spider **20** is supported by the spider attachment portion of the rotation member **72** by, for example, spline coupling.

(31) As shown in FIGS. **3** and **4**, the plurality of brake members **13** and **15** is disposed below the piston **11** and above the speed reducer **30**, specifically, the plurality of brake members **13** and **15** is disposed above the first deceleration portion at the top of the speed reducer **30**. The plurality of brake members **13** and **15** includes a plurality of brake plates **13** and a plurality of separators **15**. Each of the plurality of brake plates **13** is one example of the rotation side brake member, and each of the plurality of separators **15** is one example of the housing side brake member. The brake plates **13** and the separators **15** are alternately arranged vertically.

(32) As shown in FIGS. **3**, **4**, **11**, and **12**, each of the plurality of brake plates **13** has an annular shape surrounding the rotation shaft **71** and is supported by the spider **20**. When the rotational force of the slewing motor **2** is transmitted and the rotation shaft **71** rotates, the plurality of brake plates **13** rotates together with the rotation member **72** and the spider **20**.

(33) As shown in FIG. **4**, each of the plurality of separators **15** is supported by the housing **60** to face the brake plate **13** in the up-and-down direction. Each of the plurality of separators **15** has, for example, an annular shape surrounding the rotation shaft **71**, but the shape of the separator **15** is not limited to the annular shape, and may be any shape as long as the shape can brake the rotation of the rotation shaft **71** by friction with the adjacent brake plate **13**.

(34) As shown in FIG. **4**, the piston **11** is disposed above the plurality of brake members **13** and **15**, and is supported by the housing **60** to be displaceable in the up-and-down direction. As shown in FIGS. **4** to **8**, the piston **11** is disposed around the rotation shaft **71** with a spacing to the rotation

shaft **71** outside the rotation shaft **71** in the radial direction.

(35) In the present embodiment, the piston **11** has a cylindrical shape surrounding the rotation shaft **71**. The piston **11** includes an inner circumferential surface **11A**, an outer circumferential surface **11B**, a pilot pressure receiving surface **11C**, a biasing force receiving surface **11D**, an upper surface **11E**, and a pressing surface **11F**. The inner circumferential surface **11A** is located with a spacing outside the outer circumferential surface of the rotation shaft **71** in the radial direction. The outer circumferential surface **11B** includes an upper outer circumferential surface and a lower outer circumferential surface located at a position below the upper outer circumferential surface and shifted from the upper outer circumferential surface in the radial direction. The pilot pressure receiving surface **11C** is an upward surface that connects the upper outer circumferential surface to the lower outer circumferential surface. The pilot pressure receiving surface **11C** displaces the piston **11** downward against upward biasing force of the spring **17** by receiving the pilot pressure to be described later. The biasing force receiving surface **11D** receives the upward biasing force from the spring **17**. The upper surface **11E** is located at a position facing a top plate portion **67** of an upper cover **62** to be described later in the up-and-down direction in the housing **60**. The pressing surface **11F** gives downward pressing force to the plurality of brake members **13** and **15**.

(36) The plurality of brake members **13** and **15** is configured to brake the rotation of the rotation shaft **71** before being decelerated by the speed reducer **30** by receiving the downward pressing force from the pressing surface **11F** of the piston **11**. In other words, the plurality of brake members **13** and **15** is configured to brake the rotation of the rotation shaft **71** before the driving torque is increased by the speed reducer **30** by receiving the pressing force from the piston **11**.

(37) The spring **17** biases the piston **11** upward. The spring **17** includes an upper end that exerts the biasing force on the receiving surface **11D** of the piston **11** and a lower end whose downward displacement is restricted by an intervention member **63** of the housing **60** to be described later. The spring **17** is disposed between the biasing force receiving surface **11D** of the piston **11** and the intervention member **63** of the housing **60** to be able to expand and contract in the up-and-down direction. The upper end of the spring **17** is located below a plurality of piston passages **85** to be described later.

(38) The housing **60** includes a rotation shaft support portion **61**, the upper cover **62**, the intervention member **63**, and a speed reducer cover **64**, which are disposed in this order from the top. The rotation shaft support portion **61** supports the slewing motor **2** and rotatably supports the rotation shaft **71** extending downward from the slewing motor **2**.

(39) The upper cover **62** is disposed below the rotation shaft support portion **61** and is fixed to the rotation shaft support portion **61** by, for example, bolts. The upper cover **62** has a substantially cylindrical shape that can surround the rotation shaft **71** and the piston **11**, and can accommodate inside the rotation shaft **71** extending downward from the slewing motor **2**.

(40) Specifically, in the present embodiment, the upper cover **62** includes an inner cylindrical portion **65**, an outer cylindrical portion **66**, the top plate portion **67**, and a plurality of bridges **68**. The inner cylindrical portion **65** has a cylindrical shape surrounding the rotation shaft **71** and the piston **11**. The outer cylindrical portion **66** has a cylindrical shape surrounding the inner cylindrical portion **65**, and is located with a spacing outside the inner cylindrical portion **65** in the radial direction. The top plate portion **67** has an annular shape surrounding the rotation shaft **71** and extending in the radial direction from the upper end of the inner cylindrical portion **65** to the upper end of the outer cylindrical portion **66**. The top plate portion **67** blocks an upper opening between the inner cylindrical portion **65** and the outer cylindrical portion **66**. The plurality of bridges **68** is located at intervals in the circumferential direction and each connects the upper portion of the inner cylindrical portion **65** to the upper portion of the outer cylindrical portion **66**. The circumferential direction is the circumferential direction of the inner cylindrical portion **65**. In the present embodiment, the circumferential direction of the inner cylindrical portion **65** is the same direction as the circumferential direction of the rotation shaft **71**. A pilot oil passage **99** is formed in at least

one of the plurality of bridges **68**. Note that the inner cylindrical portion **65** may include a member different from the outer cylindrical portion **66** and the top plate portion **67**. In the present embodiment, the upper cover **62** includes the plurality of bridges **68**, but the number of bridges **68** may be one.

(41) The opening formed in the center of the upper cover **62**, that is, the central opening of the top plate portion **67** is blocked by the rotation shaft support portion **61**. Note that the rotation shaft support portion **61** and the upper cover **62** may include a single member. The rotation shaft support portion **61** may be a member that constitutes part of the slewing motor **2**.

(42) The inner cylindrical portion **65** is located to surround the piston **11** and guides the piston **11** in the up-and-down direction. The inner cylindrical portion **65** is one example of a guide portion. An inner circumferential surface **65A** of the inner cylindrical portion **65** is a surface parallel to the outer circumferential surface **11B** of the piston **11**, and faces the outer circumferential surface **11B** of the piston **11** with a slight gap in the radial direction. The inner circumferential surface **65A** of the inner cylindrical portion **65** includes an upper inner circumferential surface and a lower inner circumferential surface located at a position below the upper inner circumferential surface and shifted from the upper inner circumferential surface in the radial direction. A connection surface that connects the upper inner circumferential surface to the lower inner circumferential surface is a downward surface facing the pilot pressure receiving surface **11C** of the piston **11** in the up-and-down direction with a spacing in the up-and-down direction. The upper outer circumferential surface and the pilot pressure receiving surface **11C** of the piston **11**, and the lower inner circumferential surface and the connection surface of the inner cylindrical portion **65** define a space to which a pilot oil to be described later is supplied.

(43) At least one O-ring **98** is disposed between the outer circumferential surface **11B** of the piston **11** and the inner circumferential surface **65A** of the inner cylindrical portion **65**. Specifically, the O-ring is disposed between the upper outer circumferential surface of the outer circumferential surface **11B** of the piston **11** and the upper inner circumferential surface of the inner circumferential surface **65A** of the inner cylindrical portion **65**. Another O-ring is disposed between the lower outer circumferential surface of the outer circumferential surface **11B** of the piston **11** and the lower inner circumferential surface of the inner circumferential surface **65A** of the inner cylindrical portion **65**. The O-ring **98** is one example of a seal member.

(44) The top plate portion **67** includes an inner projecting portion projecting inside the upper end of the inner cylindrical portion **65** in the radial direction. The inner projecting portion includes a lower surface **67A** facing the upper surface **11E** of the piston **11** in the up-and-down direction. When the upper surface **11E** of the piston **11** touches the lower surface **67A** of the top plate portion **67**, the lower surface **67A** restricts further upward displacement of the piston **11** from this position. That is, the lower surface **67A** of the top plate portion **67** determines the upper limit position of the piston **11**.

(45) As shown in FIG. **4**, the intervention member **63** is interposed between the piston **11** and the speed reducer **30**. The intervention member **63** is fixed to the upper cover **62** below the upper cover **62**. The intervention member **63** has a shape surrounding the rotation shaft **71**, the rotation member **72**, the spider **20**, and the plurality of brake plates **13**. Specifically, in the present embodiment, the intervention member **63** has a disk shape. The intervention member **63** includes an inner circumferential surface **63A**, a spring placement surface **63B**, a pressing force receiving surface **63C**, and an upper surface **63D**. The inner circumferential surface **63A** supports the plurality of separators **15**. The lower end of the spring **17** is disposed on the spring placement surface **63B**. The pressing force receiving surface **63C** receives the pressing force of the piston **11** via the plurality of brake members **13** and **15**. The upper surface **63D** will be described later.

(46) Each of the plurality of brake plates **13** is disposed to extend outward in the radial direction from the outer circumferential surface of the spider **20**, and each of the plurality of separators **15** is disposed to extend inward in the radial direction from the inner circumferential surface **63A** of the



intervention member **63**. The brake members **13** and **15** are disposed to be sandwiched between the pressing surface **11F** of the piston **11** and the pressing force receiving surface **63C** of the intervention member **63**.

(47) The speed reducer cover **64** is fixed to the intervention member **63** below the intervention member **63**. The speed reducer cover **64** has a shape that can accommodate the speed reducer **30**. The speed reducer cover **64** includes, for example, a barrel portion having a shape (for example, cylindrical shape) that surrounds the speed reducer **30**, and a bottom portion (not shown) covering the lower portion of the speed reducer **30**. The output shaft **4** is disposed below the bottom portion. The rotational force output from the deceleration portion at the bottom of the speed reducer **30** (second deceleration portion or third deceleration portion in the present embodiment) is transmitted to the output shaft **4**. Note that the bottom portion may include a member different from the speed reducer cover **64**.

(48) The breather **97** is fixed to the upper portion of the housing **60**, specifically to the upper portion of the upper cover **62** for the purpose of suction and discharge of gas in the housing **60**, air filtering, and the like. The breather **97** is disposed at a position corresponding to a through hole formed in the upper portion of the upper cover **62** and has a shape extending upward from the upper cover **62**.

(49) The housing **60** has an internal space that accommodates the rotation shaft **71**, the rotation member **72**, the spider **20**, the plurality of brake members **13** and **15**, the piston **11**, the spring **17**, the speed reducer **30**, and the like. This internal space includes a lower space **81**, a plurality of outer passages **82**, an upper outer space **83**, a plurality of guide portion passages **84**, the plurality of piston passages **85**, an upper central space **86**, a plurality of inner passages **87**, a plurality of seal member lubrication passages **88**, a guide portion lower passage **89**, and a piston lower passage **90**. The guide portion passages **84** and the piston passages **85** are one example of a supply passage, and the guide portion lower passage **89** and the piston lower passage **90** are another example of the supply passage.

(50) The lower space **81** is a space in which the speed reducer **30** is disposed, and is a space surrounded by the inner circumferential surface of the speed reducer cover **64**. Specifically, in the present embodiment, the lower space **81** is defined primarily by the inner surface of the speed reducer cover **64** and the lower surface of the intervention member **63**. The lower space **81** is formed below the outer passage **82**, the upper outer space **83**, the guide portion passages **84**, the piston passages **85**, the upper central space **86**, the inner passages **87**, the seal member lubrication passages **88**, the guide portion lower passage **89**, and the piston lower passage **90**.

(51) The upper central space **86** is a space in which part or all of the rotation shaft **71**, the piston **11**, and the upper portion of the rotation member **72** are disposed, and is a space surrounded by the inner circumferential surface of the upper cover **62**. Specifically, in the present embodiment, the upper central space **86** is primarily defined by the lower surface of the rotation shaft support portion **61**, the inner circumferential surface of the upper cover **62**, the upper surface of the spider **20**, and the upper surface of the intervention member **63**.

(52) The upper outer space **83** is a space formed outside the upper central space **86** in the radial direction and above the lower space **81**. The upper outer space **83** is a space between the inner cylindrical portion **65** of the upper cover **62** and the outer cylindrical portion **66** of the upper cover **62**. Specifically, the upper outer space **83** is defined by the outer circumferential surface of the inner cylindrical portion **65**, the inner circumferential surface of the outer cylindrical portion **66**, the lower surface of the top plate portion **67**, and the upper surface of the intervention member **63**.

(53) The upper outer space **83** is intermittently or continuously formed in the circumferential direction along the outer circumferential surface of the inner cylindrical portion **65** of the upper cover **62**. The upper outer space **83** includes a single space outside the inner cylindrical portion **65** in the radial direction, and is formed over the entire circumference along the outer circumferential surface of the inner cylindrical portion **65**. The upper outer space **83** is formed such that the size of

the upper outer space **83** in the circumferential direction is larger than the size of the upper outer space **83** in the up-and-down direction, and that the size of the upper outer space **83** in the circumferential direction is larger than the size of the upper outer space **83** in the radial direction. (54) Note that the upper outer space **83** may include a plurality of spaces partitioned by partitions (not shown) arranged in the circumferential direction outside the inner cylindrical portion **65** in the radial direction. In this case as well, each of the plurality of spaces that constitute the upper outer space **83** is preferably formed such that the size in the circumferential direction is larger than the size in the up-and-down direction, and that the size in the circumferential direction is larger than the size in the radial direction.

(55) The plurality of outer passages **82** is formed in the intervention member **63**. Each of the plurality of outer passages **82** includes a through-hole penetrating the intervention member **63** in the up-and-down direction, and causes the lower space **81** to communicate with the upper outer space **83**. The plurality of outer passages **82** is formed in the intervention member **63** to be arranged along the circumferential direction at intervals in the circumferential direction. In the present embodiment, each of the plurality of outer passages **82** has an opening shape in which the dimension in the circumferential direction is larger than the dimension in the radial direction. However, the shape of the outer passage **82** is not limited to such a shape. The number of outer passages **82** may be one.

(56) The plurality of guide portion passages **84** is passages formed in the inner cylindrical portion **65** (one example of guide portion), leading to the upper outer space **83**. In the present embodiment, the plurality of guide portion passages **84** is formed in the upper portion of the inner cylindrical portion **65** as shown in FIGS. **3** and **4**, and is formed in the inner cylindrical portion **65** to be arranged along the circumferential direction at intervals in the circumferential direction as shown in FIGS. **5** and **6**. However, at least one of the plurality of guide portion passages **84** may be formed in an intermediate area between the upper end and the lower end of the inner cylindrical portion **65**. The number of guide portion passages **84** may be one.

(57) The plurality of piston passages **85** is passages formed in the piston **11**, leading to the upper central space **86**. In the present embodiment, the plurality of piston passages **85** is formed in the upper portion of the piston **11** as shown in FIG. **3**, and is formed in the piston **11** to be arranged along the circumferential direction at intervals in the circumferential direction as shown in FIGS. **5** and **6**. However, at least one of the plurality of piston passages **85** may be formed in an intermediate area between the upper end and the lower end of the piston **11**. The number of piston passages **85** may be one.

(58) Specifically, in the present embodiment, six guide portion passages **84** are formed in the inner cylindrical portion **65**, and six piston passages **85** are formed in the piston **11**. Three guide portion passages **84** out of the six guide portion passages **84** are located at positions corresponding to three piston passages **85**, that is, at positions arranged with the three piston passages **85** in the radial direction. On the other hand, the remaining three guide portion passages **84** are not located at positions corresponding to the piston passages **85**. Note that in terms of supplying the lubricant as evenly as possible to the plurality of brake members **13** and **15** all around, the plurality of piston passages **85** is preferably arranged at regular intervals in the circumferential direction. For the similar reason, the plurality of guide portion passages **84** is preferably arranged at regular intervals in the circumferential direction.

(59) The set of the guide portion passage **84** and the piston passage **85** that is continuous inside the guide portion passage **84** in the radial direction constitutes a first supply passage. The first supply passage is a passage that causes the upper outer space **83** to communicate with the upper central space **86**, and is one example of the supply passage. The first supply passage is a passage formed at a position where the lubricant that has moved in the lower space **81**, the outer passages **82**, and the upper outer space **83** in this order can be supplied to the plurality of brake members **13** and **15**.

(60) The plurality of inner passages **87** is formed in the spider **20** (one example of supporting

member). Each of the plurality of inner passages **87** includes a through-hole penetrating the spider **20** in the up-and-down direction, and causes the upper central space **86** to communicate with the lower space **81**. The plurality of inner passages **87** is formed in the spider **20** to be arranged along the circumferential direction at intervals in the circumferential direction. In the present embodiment, each of the plurality of inner passages **87** has a circular shape in plan view. However, the shape of the inner passage **87** is not limited to such a shape. The number of inner passages **87** may be one.

(61) As shown in FIG. **4**, the plurality of seal member lubrication passages **88** is formed in the intervention member **63**. Each of the plurality of seal member lubrication passages **88** includes a through-hole penetrating the intervention member **63** in the up-and-down direction, and causes a space **91** located directly below the lower edge of the outer circumferential surface **11B** of the piston **11** to communicate with the lower space **81**. As shown in FIGS. **9** to **12**, the plurality of seal member lubrication passages **88** is formed in the intervention member **63** to be arranged along the circumferential direction at intervals in the circumferential direction. In the present embodiment, each of the plurality of seal member lubrication passages **88** has a circular shape in plan view. However, the shape of the inner passage **87** is not limited to such a shape. The number of inner passages **87** may be one.

(62) As shown in FIG. **4**, the upper surface **63D** of the intervention member **63** includes: an outer upper surface portion **63D1**, which is a portion that defines the lower portion of the upper outer space **83**; an intermediate upper surface portion **63D2**, which is a portion facing the inner cylindrical portion **65** (one example of guide portion) in the up-and-down direction; and an inner upper surface portion **63D3**, which is a portion facing the piston **11** in the up-and-down direction.

(63) The guide portion lower passage **89** is a passage between the intermediate upper surface portion **6312** of the intervention member **63** and the inner cylindrical portion **65**, leading to the upper outer space **83**. The piston lower passage **90** is a passage between the inner upper surface portion **63D3** of the intervention member **63** and the piston **11**, and causes the guide portion lower passage **89** to communicate with the upper central space **86**.

(64) The set of the guide portion lower passage **89** and the piston lower passage **90** that is continuous inside the guide portion lower passage **89** in the radial direction constitutes a second supply passage. The second supply passage is a passage that causes the upper outer space **83** to communicate with the upper central space **86**, and is one example of the supply passage. The second supply passage is a passage formed at a position where the lubricant that has moved in the lower space **81**, the outer passages **82**, and the upper outer space **83** in this order can be supplied to the plurality of brake members **13** and **15**.

(65) As shown in FIGS. **4** and **10**, the upper surface **63D** of the intervention member **63** includes an intermediate portion **63M** between an annular portion outward in the radial direction and an annular portion inward in the radial direction. The intermediate portion **63M** has an annular shape that is continuous along the circumferential direction in plan view. The plurality of outer passages **82** and the plurality of seal member lubrication passages **88** are formed in the intermediate portion **63M**. The intermediate portion **63M** is located below the outer annular portion and the inner annular portion in the radial direction via a step. When the plurality of outer passages **82** and the plurality of seal member lubrication passages **88** are formed in the intermediate portion **63M** located below the outer portion and the inner portion in this way, for example, if the slewing motor **2** stops, the lubricant that is located above the upper surface **63D** of the intervention member **63** is likely to fall from the place and gather in the intermediate portion **63M**, making it more likely to be collected into the lower space **81** through the plurality of outer passages **82** and the plurality of seal member lubrication passages **88**.

(66) The lubricant is stored in advance in the internal space of the housing **60**.

(67) Meanwhile, to prevent the lubricant from leaking out of the breather **97**, a predetermined air volume is secured in the housing **60**. For example, the amount of the lubricant stored in the housing

**60** may be adjusted such that the liquid surface of the lubricant is below the piston **11** and above the speed reducer **30** in a state where the slewing motor **2** is stopped. Specifically, in the present embodiment, as shown in FIG. **3**, the amount of the lubricant stored in the housing **60** is adjusted such that the liquid surface **L1** of the lubricant is located between the brake member at the highest position and the brake member at the lowest position among the plurality of brake members **13** and **15** in a state where the slewing motor **2** is stopped. Note that the amount of the lubricant stored in the housing **60** is preferably adjusted such that the plurality of brake members **13** and **15** are entirely immersed in the lubricant in a state where the slewing motor **2** is stopped.

(68) Meanwhile, in a state where the slewing motor **2** is operating, the rotation shaft **71** is rotating, and the speed reducer **30** is being driven, the lubricant within the lower space **81** is agitated by the speed reducer **30**, thereby causing the liquid surface **L2** of the lubricant to have a mortar shape as shown in FIG. **3**. The liquid surface **L2** at this time is located below the plurality of brake members **13** and **15**.

(69) The lubricant within the lower space **81** is agitated by the speed reducer **30** (in particular, plurality of planetary gears **32** of the first deceleration portion). Part of the agitated lubricant flows from the lower space **81** through the outer passages **82** into the upper outer space **83**. Then, part of the lubricant that has flowed into the upper outer space **83** is guided by the guide portion passages **84** and the piston passages **85** and flows into the upper central space **86**, falls in the upper central space **86**, and is supplied to the plurality of brake members **13** and **15**, the rotation member **72** including the sun gear **31**, and the like. Note that the outer passages **82** are not depicted in the cross section shown in FIG. **3**, but the plurality of outer passages **82** exists in places shifted from the cross section in the circumferential direction, and the lubricant flows into the upper outer space **83** through the outer passages **82**.

(70) Part of the lubricant that has flowed from the lower space **81** through the outer passages **82** into the upper outer space **83** is guided to the guide portion lower passage **89** and the piston lower passage **90**, and is supplied to the plurality of brake members **13** and **15**, the rotation member **72** including the sun gear **31**, and the like, as shown in FIG. **4**.

(71) As shown in FIG. **4**, part of the lubricant agitated in the lower space **81** flows from the lower space **81** through the seal member lubrication passages **88** into the space **91** located directly below the lower edge of the outer circumferential surface **11B** of the piston **11**, and is supplied to the area between the inner cylindrical portion **65** (one example of guide portion) and the piston **11**, and the seal member located in this area.

(72) As described above, in the slewing unit **3** according to the present embodiment, the plurality of brake members **13** and **15** is disposed above the speed reducer **30** and receives the pressing force from the piston **11**, thereby braking the rotation of the rotation shaft **71** before being decelerated by the speed reducer **30**, that is, the rotation of the rotation shaft **71** before the torque is increased by the speed reducer **30**. This allows compactification of the plurality of brake members **13** and **15** and the piston **11** giving the pressing force to the brake members **13** and **15** in the radial direction more than in a conventional case of braking the rotation after being decelerated by the speed reducer and the torque has increased. This compactification makes it possible to form an appropriately sized space within the housing **60** for securing the air volume in an area outside the piston **11** in the radial direction and above the speed reducer **30** while suppressing an increase in the size of the housing **60**. Moreover, the upper outer space **83** formed in the area is not only used to secure the air volume, but also used as part of the passage for supplying the lubricant stored in the lower space **81** located below the upper outer space **83** to the brake members **13** and **15**. Therefore, the amount of the lubricant stored in advance in the housing **60** may be a level that allows the lubricant stored in the lower space **81** where the speed reducer **30** is disposed to move in the lower space **81**, the outer passages **82**, and the upper outer space **83** in this order, to be guided inward in the radial direction by at least one of the first supply passage and the second supply passage, and to be supplied to the plurality of brake members **13** and **15**. That is, the amount of the lubricant stored in advance in the

housing **60** is required at least to be a level that allows the lubricant stored in the lower space **81** to be supplied to the plurality of brake members **13** and **15**, and the liquid surface **L2** of the lubricant does not need to be higher than the plurality of brake members **13** and **15** when the speed reducer **30** is driven by the rotational force of the slewing motor **2**. This allows a decrease in the amount of the lubricant stored in advance in the housing **60** and a further increase in the air volume accordingly. Therefore, the slewing unit **3** can secure the appropriate air volume in the housing **60** and appropriately lubricate the speed reducer **30** and the brake members **13** and **15** while suppressing an increase in the size of the housing **60**.

#### MODIFICATIONS

(73) The construction machine according to the embodiment of the present disclosure has been described above, but the present disclosure is not limited to these modes, and includes the following modifications, for example.

(74) FIG. **13** is a cross-sectional view showing part of a slewing unit **3** according to a first modification of the embodiment. In this first modification, the bottom surface of a guide portion passage **84** is inclined with respect to the horizontal plane such that the bottom surface is located downward as the bottom surface approaches a rotation shaft **71**. In this first modification, the lubricant that has reached a first supply passage is likely to flow toward an upper central space **86** along the bottom surface of the guide portion passage **84** that is inclined with respect to the horizontal plane, thereby making it possible to suppress the lubricant from flowing backward in the first supply passage. This allows the lubricant to be efficiently supplied to the plurality of brake members **13** and **15**.

(75) Note that the bottom surface of the piston passage **85** may be inclined with respect to the horizontal plane such that the bottom surface is located downward as the bottom surface approaches the rotation shaft **71**. In this case as well, the lubricant that has reached the first supply passage is likely to flow toward the upper central space **86** along the bottom surface of the piston passage **85** that is inclined with respect to the horizontal plane, thereby allowing the lubricant to be more efficiently supplied to the plurality of brake members **13** and **15**.

(76) In the first modification, the upper surface of the intervention member **63**, specifically the outer upper surface portion, the intermediate upper surface portion, and the inner upper surface portion of the intervention member **63** are inclined with respect to the horizontal plane to be located downward as the upper surface approaches the rotation shaft **71**. In this first modification, the lubricant that has reached the second supply passage is likely to flow toward the upper central space **86** along the upper surface of the intervention member **63** that is inclined with respect to the horizontal plane, thereby making it possible to suppress the lubricant from flowing backward in the second supply passage. This allows the lubricant to be efficiently supplied to the plurality of brake members. Note that at least one of the outer upper surface portion, the intermediate upper surface portion, and the inner upper surface portion of the intervention member **63** may be inclined with respect to the horizontal plane, and other upper surface portions may be horizontal.

(77) Although illustration is omitted, the piston passage **85** may be located at a position lower than the guide portion passage **84** via a step, for example. In this case as well, the backflow of the lubricant that has reached the piston passage **85** via the guide portion passage **84** and returning to the guide portion passage **84** is suppressed, thereby allowing the lubricant to be more efficiently supplied to the plurality of brake members **13** and **15**.

(78) FIG. **14** is a cross-sectional view showing part of a slewing unit **3** according to a second modification of the embodiment. In this second modification, an intervention member **63** includes a backflow prevention wall **631** located inside an opening at the upper end of an outer passage **82** in the radial direction and outside an inner cylindrical portion **65** (one example of guide portion) in the radial direction. The backflow prevention wall **631** stands upward from an outer upper surface portion of the intervention member **63**. The second modification suppresses the lubricant that has moved inside the backflow prevention wall **631** in the radial direction from returning outside the

backflow prevention wall **631** in the radial direction, thereby allowing the lubricant to be more efficiently supplied to a plurality of brake members **13** and **15**.

(79) The supply passage leading to an upper outer space **83** is required at least to allow the lubricant that has passed through a lower space **81**, outer passages **82**, and the upper outer space **83** in this order to be guided inward in the radial direction and supplied to the plurality of brake members **13** and **15**. Therefore, the supply passage may be formed, for example, in the top plate portion of an upper cover **62**.

(80) In the above-described embodiment, the inner cylindrical portion **65** (one example of guide portion) has a cylindrical shape formed to continuously surround a rotation shaft **71** and a piston **11** over the entire circumference of the circumferential direction, but the shape of the guide portion is not limited to the above-described embodiment. The guide portion may be configured, for example, to intermittently surround the rotation shaft **71** and the piston **11** to guide the piston **11** in the up-and-down direction. The guide portion may have a tubular shape other than the cylindrical shape.

(81) The construction machine has been a crane, but may be another construction machine such as a hydraulic excavator. The machine body slewably supporting the upper slewing body does not need to be self-travelling like the lower travelling body.

(82) The present disclosure provides the slewing unit of a construction machine that can secure the appropriate air volume in the housing and appropriately lubricate the speed reducer and the brake members while suppressing an increase in the size of the housing.

(83) The provided slewing unit of a construction machine includes: a rotation shaft to which rotational force of a slewing motor is transmitted, the rotation shaft extending in an up-and-down direction; a speed reducer to decelerate rotation of the rotation shaft; a piston located to surround the rotation shaft with a spacing to the rotation shaft outside the rotation shaft in a radial direction, the piston being displaceable in the up-and-down direction; a housing that accommodates the rotation shaft, the speed reducer, and the piston, the housing including a guide portion that is located to surround the piston to guide the piston in the up-and-down direction; and a plurality of brake members that includes: a rotation side brake member that is located to surround the rotation shaft and rotates as the rotation shaft rotates; and a housing side brake member supported by the housing to face the rotation side brake member in the up-and-down direction, the plurality of brake members being located below the piston, in which an upper central space in which at least part of the rotation shaft is disposed, the upper central space being a space surrounded by an inner circumferential surface of the piston; a lower space in which the speed reducer is disposed, the lower space being located below the upper central space; an upper outer space located outside the piston in the radial direction and above the lower space; an outer passage that connects the lower space to the upper outer space; and at least one supply passage that guides, inward in the radial direction, a lubricant that has passed through the lower space, the outer passage, and the upper outer space in this order to supply the lubricant to the plurality of brake members located below the piston are formed in the housing, and the plurality of brake members is disposed above the speed reducer and is configured to brake, by receiving pressing force from the piston, the rotation of the rotation shaft before being decelerated by the speed reducer.

(84) In this slewing unit, since the plurality of brake members disposed above the speed reducer brakes the rotation of the rotation shaft before being decelerated by the speed reducer, compactification of the plurality of brake members and the piston is possible, and since it is possible to form the upper outer space, which is an appropriately sized space for securing the air volume and a space used as part of a passage for supplying the lubricant to the plurality of brake members in the area outside the piston in the radial direction newly available because of the compactification, it is possible to secure an appropriate air volume in the housing while suppressing the size of the housing from increasing, and to appropriately lubricate the speed reducer and the brake members. Specifically, this will be described as follows.

(85) In this slewing unit, the plurality of brake members is disposed above the speed reducer and

receives the pressing force from the piston, thereby braking the rotation of the rotation shaft before being decelerated by the speed reducer, that is, the rotation of the rotation shaft before the torque is increased by the speed reducer. This allows compactification of the plurality of brake members and the piston giving the pressing force to the brake members in the radial direction more than in a conventional case of braking the rotation after being decelerated by the speed reducer and the torque has increased. This compactification makes it possible to form an appropriately sized space within the housing for securing the air volume in an area outside the piston in the radial direction and above the speed reducer while suppressing an increase in the size of the housing. Moreover, the upper outer space formed in the area is not only used to secure the air volume, but also used as part of the passage for supplying the lubricant stored in the lower space located below the upper outer space to the brake members. Therefore, the amount of the lubricant stored in advance in the housing may be a level that allows the lubricant stored in the lower space where the speed reducer is disposed to move in the lower space, the outer passage, and the upper outer space in this order, to be guided to the supply passage, and to be supplied to the plurality of brake members. That is, the amount of the lubricant stored in advance in the housing is required at least to be a level that allows the lubricant stored in the lower space to be supplied to the plurality of brake members, and the liquid surface of the lubricant does not need to be higher than the plurality of brake members when the speed reducer is driven by the rotational force of the slewing motor. This allows a decrease in the amount of the lubricant stored in advance in the housing and a further increase in the air volume accordingly. Therefore, the slewing unit can secure the appropriate air volume in the housing and appropriately lubricate the speed reducer and the brake members while suppressing an increase in the size of the housing.

(86) In the slewing unit, the upper outer space is preferably formed such that a size of the upper outer space in a circumferential direction is larger than a size of the upper outer space in the up-and-down direction. With this configuration, the upper outer space is not an elongated space in the up-and-down direction, but a space extending in the circumferential direction in the housing. Therefore, a larger air volume can be secured in the housing.

(87) In the slewing unit, preferably, the guide portion has a cylindrical shape surrounding the piston, the housing further includes an outer cylindrical portion located to surround the guide portion with a spacing to the guide portion outside the guide portion in the radial direction, and the upper outer space is a space defined by an outer circumferential surface of the guide portion and an inner circumferential surface of the outer cylindrical portion. With this configuration, the circumferentially expanding upper outer space can be formed along the circumferential direction between the cylindrical guide portion and the outer cylindrical portion.

(88) In the slewing unit, preferably, the at least one supply passage includes a first supply passage including: a guide portion passage that is a passage formed in the guide portion and leading to the upper outer space; and a piston passage that is a passage formed in the piston and connecting the guide portion passage to the upper central space. With this configuration, the first supply passage including the guide portion passage and the piston passage can guide the lubricant that has passed through the lower space, the outer passage, and the upper outer space in this order to the upper central space that is a space surrounded by the inner circumferential surface of the piston, and supply the lubricant to the plurality of brake members located below the piston. With this configuration, since the supply passage is formed in the guide portion and the piston, it is possible to suppress an increase in size of the housing in the height direction.

(89) The slewing unit preferably further includes a supporting member disposed between the rotation side brake member and the rotation shaft, the supporting member being located to surround the rotation shaft, the supporting member supporting the rotation side brake member such that the rotation side brake member rotates as the rotation shaft rotates, in which an inner passage penetrating the supporting member in the up-and-down direction to connect the upper central space to the lower space is further formed in the housing. With this configuration, the lubricant that has

passed through the lower space, the outer passage, the upper outer space, and the first supply passage in this order and has flowed into the upper central space can be efficiently returned to the lower space through the inner passage formed in the supporting member.

(90) In the slewing unit, preferably, at least one of the guide portion passage and the piston passage includes a portion that is inclined with respect to a horizontal plane to be located downward as the portion approaches the rotation shaft. With this configuration, the lubricant that has reached the first supply passage is likely to flow toward the upper central space along the portion inclined with respect to the horizontal plane, thereby making it possible to suppress the lubricant from flowing backward in the first supply passage. This allows the lubricant to be efficiently supplied to the plurality of brake members.

(91) The slewing unit preferably further includes a biasing member that biases the piston upward, in which a pilot oil passage that enables a pilot oil for moving the piston downward against upward biasing force exerted by the biasing member to be supplied toward the piston is formed in the housing, and the biasing member includes an upper end that transmits the upward biasing force to the piston, and the upper end is located below the piston passage. With this configuration, since the biasing member is located below the piston passage, the biasing member does not interfere with the flow of lubricant in the piston passage.

(92) In the slewing unit, preferably, the housing includes: an intervention member in which the outer passage is formed, the intervention member being interposed between the piston and the speed reducer, the intervention member being located to surround the rotation shaft and the rotation side brake member, the intervention member supporting the housing side brake member; and an upper cover including the guide portion, the upper cover being disposed above the intervention member and connected to the intervention member. With this configuration, since the upper cover and the intervention member are formed as separate members, machining of parts constituting the slewing unit is facilitated, and assembly of the slewing unit is facilitated.

(93) In the slewing unit, the intervention member may include an upper surface, the upper surface may include an outer upper surface portion that is a portion defining a lower portion of the upper outer space, an intermediate upper surface portion that is a portion facing the guide portion in the up-and-down direction, and an inner upper surface portion that is a portion facing the piston in the up-and-down direction, and the at least one supply passage may include a second supply passage including: a guide portion lower passage that is a passage between the intermediate upper surface portion of the intervention member and the guide portion, leading to the upper outer space; and a piston lower passage that is a passage between the inner upper surface portion of the intervention member and the piston, the piston lower passage guiding, inward in the radial direction, the lubricant that has passed through the lower space, the outer passage, the upper outer space, and the guide portion lower passage in this order to supply the lubricant to the plurality of brake members located below the piston. With this configuration, the second supply passage including the guide portion lower passage and the piston lower passage can supply the lubricant that has passed through the lower space, the outer passage, and the upper outer space in this order to the plurality of brake members located below the piston. With this configuration, since the guide portion lower passage and the piston lower passage are located lower than the guide portion passage and the piston passage, the lubricant is supplied to the plurality of brake members easily.

(94) In this case, preferably, at least one of the outer upper surface portion, the intermediate upper surface portion, and the inner upper surface portion of the intervention member includes a portion that is inclined with respect to the horizontal plane to be located downward as the portion approaches the rotation shaft. With this configuration, the lubricant that has reached the supply passage is likely to flow toward the upper central space along the portion inclined with respect to the horizontal plane, thereby making it possible to suppress the lubricant from flowing backward in the supply passage. This allows the lubricant to be efficiently supplied to the plurality of brake members.



(95) The intervention member preferably includes a backflow prevention wall that is a wall located inside an opening of an upper end of the outer passage in the radial direction and outside the guide portion in the radial direction, the backflow prevention wall standing upward from the outer upper surface portion of the intervention member. This configuration suppresses the lubricant that has moved inside the backflow prevention wall in the radial direction from returning outside the backflow prevention wall in the radial direction, thereby allowing the lubricant to be more efficiently supplied to the plurality of brake members.

(96) In the slewing unit, the intervention member preferably includes a receiving surface that receives the plurality of brake members that receives the pressing force by the piston. With this configuration, stable braking characteristics can be obtained.

(97) The slewing unit preferably further includes a seal member disposed between the guide portion and an outer circumferential surface of the piston, in which a seal member lubrication passage connecting a space located directly below a lower edge of the outer circumferential surface of the piston to the lower space is preferably further formed in the housing. This configuration, which can supply the lubricant to the sealing member between the guide portion and the piston, can improve the life of the seal member and smoothly displace the piston in the up-and-down direction.

## Claims

1. A slewing unit of a construction machine, the slewing unit comprising: a rotation shaft to which rotational force of a slewing motor is transmitted, the rotation shaft extending in an up-and-down direction; a speed reducer to decelerate rotation of the rotation shaft; a piston located to surround the rotation shaft with a spacing to the rotation shaft outside the rotation shaft in a radial direction, the piston being displaceable in the up-and-down direction; a housing that accommodates the rotation shaft, the speed reducer, and the piston, the housing including a guide portion that is located to surround the piston to guide the piston in the up-and-down direction; and a plurality of brake members that includes: a rotation side brake member that is located to surround the rotation shaft and rotates as the rotation shaft rotates; and a housing side brake member supported by the housing to face the rotation side brake member in the up-and-down direction, the plurality of brake members being located below the piston, wherein an upper central space in which at least part of the rotation shaft is disposed, the upper central space being a space surrounded by an inner circumferential surface of the piston; a lower space in which the speed reducer is disposed, the lower space being located below the upper central space; an upper outer space located outside the piston in the radial direction and above the lower space; an outer passage that connects the lower space to the upper outer space; and at least one supply passage that guides, inward in the radial direction, a lubricant that has passed through the lower space, the outer passage, and the upper outer space in this order to supply the lubricant to the plurality of brake members located below the piston are formed in the housing, and the plurality of brake members is disposed above the speed reducer and is configured to brake, by receiving pressing force from the piston, the rotation of the rotation shaft before being decelerated by the speed reducer.

2. The slewing unit of a construction machine according to claim 1, wherein the upper outer space is formed such that a size of the upper outer space in a circumferential direction is larger than a size of the upper outer space in the up-and-down direction.

3. The slewing unit of a construction machine according to claim 1, wherein the guide portion has a cylindrical shape surrounding the piston, the housing further includes an outer cylindrical portion located to surround the guide portion with a spacing to the guide portion outside the guide portion in the radial direction, and the upper outer space is a space defined by an outer circumferential surface of the guide portion and an inner circumferential surface of the outer cylindrical portion.

4. The slewing unit of a construction machine according to claim 1, wherein the at least one supply passage includes a first supply passage including: a guide portion passage that is a passage formed

in the guide portion and leading to the upper outer space; and a piston passage that is a passage formed in the piston and connecting the guide portion passage to the upper central space.

5. The slewing unit of a construction machine according to claim 4, further comprising a supporting member disposed between the rotation side brake member and the rotation shaft, the supporting member being located to surround the rotation shaft, the supporting member supporting the rotation side brake member such that the rotation side brake member rotates as the rotation shaft rotates, wherein an inner passage penetrating the supporting member in the up-and-down direction to connect the upper central space to the lower space is further formed in the housing.

6. The slewing unit of a construction machine according to claim 4, wherein at least one of the guide portion passage and the piston passage includes a portion that is inclined with respect to a horizontal plane to be located downward as the portion approaches the rotation shaft.

7. The slewing unit of a construction machine according to claim 4, further comprising a biasing member that biases the piston upward, wherein a pilot oil passage that enables a pilot oil for moving the piston downward against upward biasing force exerted by the biasing member to be supplied toward the piston is formed in the housing, and the biasing member includes an upper end that transmits the upward biasing force to the piston, and the upper end is located below the piston passage.

8. The slewing unit of a construction machine according to claim 1, wherein the housing includes: an intervention member in which the outer passage is formed, the intervention member being interposed between the piston and the speed reducer, the intervention member being located to surround the rotation shaft and the rotation side brake member, the intervention member supporting the housing side brake member; and an upper cover including the guide portion, the upper cover being disposed above the intervention member and connected to the intervention member.

9. The slewing unit of a construction machine according to claim 8, wherein the intervention member includes an upper surface, the upper surface includes an outer upper surface portion that is a portion defining a lower portion of the upper outer space, an intermediate upper surface portion that is a portion facing the guide portion in the up-and-down direction, and an inner upper surface portion that is a portion facing the piston in the up-and-down direction, and the at least one supply passage includes a second supply passage including: a guide portion lower passage that is a passage between the intermediate upper surface portion of the intervention member and the guide portion, leading to the upper outer space; and a piston lower passage that is a passage between the inner upper surface portion of the intervention member and the piston, the piston lower passage guiding, inward in the radial direction, the lubricant that has passed through the lower space, the outer passage, the upper outer space, and the guide portion lower passage in this order to supply the lubricant to the plurality of brake members located below the piston.

10. The slewing unit of a construction machine according to claim 9, wherein at least one of the outer upper surface portion, the intermediate upper surface portion, and the inner upper surface portion of the intervention member includes a portion that is inclined with respect to the horizontal plane to be located downward as the portion approaches the rotation shaft.

11. The slewing unit of a construction machine according to claim 9, wherein the intervention member includes a backflow prevention wall that is a wall located inside an opening of an upper end of the outer passage in the radial direction and outside the guide portion in the radial direction, the backflow prevention wall standing upward from the outer upper surface portion of the intervention member.

12. The slewing unit of a construction machine according to claim 9, wherein the intervention member includes a receiving surface that receives the plurality of brake members that receives the pressing force by the piston.

13. The slewing unit of a construction machine according to claim 1, further comprising a seal member disposed between the guide portion and an outer circumferential surface of the piston, wherein a seal member lubrication passage connecting a space located directly below a lower edge

of the outer circumferential surface of the piston to the lower space is further formed in the housing.

---