

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400184
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kim; Seon Ki et al.

Systems and methods for optimization of pick walks

Abstract

A system including one or more processors and one or more non-transitory computer-readable media storing computing instructions that, when executed on the one or more processors, cause the one or more processors to perform: determining that a respective number of totes for a respective order of one or more orders can be reduced; reducing, using an infeasible totes loop, the respective number of the totes for the respective order to a respective reduced number of the totes; executing, as part of the infeasible totes loop, an item search; running the item search until a predefined number of iterations is reached; generating directions for a route of a pick walk based on a map of a retail facility; and facilitating displaying, on an electronic device, the route of the pick walk on the map of the retail facility. Other embodiments are disclosed herein.

Inventors: Kim; Seon Ki (Dublin, CA), Arcot Srinivasan; Aditya (Sunnyvale, CA), Fu; Mingang (Palo Alto, CA)

Applicant: WALMART APOLLO, LLC (Bentonville, AR)

Family ID: 1000008778257

Assignee: WALMART APOLLO, LLC (N/A, N/A)

Appl. No.: 18/407169

Filed: January 08, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240144179 A1	May. 02, 2024

Related U.S. Application Data

continuation parent-doc US 16778393 20200131 US 11868958 child-doc US 18407169

Publication Classification

Int. Cl.: G06F7/00 (20060101); G06F16/901 (20190101); G06F16/9035 (20190101); G06F16/9038 (20190101); G06G7/48 (20060101); G06Q10/047 (20230101); G06Q10/087 (20230101); G06Q30/00 (20230101)

U.S. Cl.:

CPC G06Q10/087 (20130101); G06F16/901 (20190101); G06F16/9035 (20190101); G06F16/9038 (20190101); G06Q10/047 (20130101);

Field of Classification Search

CPC: G06Q (10/087); G06Q (10/047); G06F (16/901); G06F (16/9038); G06F (16/9035)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5909023	12/1998	Ono	N/A	N/A
6123259	12/1999	Ogasawara	N/A	N/A
6246998	12/2000	Matsumori	N/A	N/A
6266649	12/2000	Linden	N/A	N/A
6317722	12/2000	Jacobi et al.	N/A	N/A
6484161	12/2001	Chipalkatti	N/A	N/A
6876958	12/2004	Chowdhury	703/2	G06Q 10/04
7046685	12/2005	Matsuoka	N/A	N/A
7147154	12/2005	Myers et al.	N/A	N/A
7295990	12/2006	Braumoeller et al.	N/A	N/A
7747543	12/2009	Braumoeller et al.	N/A	N/A
7932831	12/2010	Malik	N/A	N/A
7949686	12/2010	Chang et al.	N/A	N/A
8005761	12/2010	Braumoeller et al.	N/A	N/A
8121876	12/2011	Braumoeller et al.	N/A	N/A
8201737	12/2011	Palacios Durazo et al.	N/A	N/A
8401914	12/2012	Kim	N/A	N/A
8428988	12/2012	Braumoeller et al.	N/A	N/A
8452797	12/2012	Paleja et al.	N/A	N/A
8560461	12/2012	Tian	705/332	G06Q 10/087
8571702	12/2012	Haake	705/26.1	G06Q 10/047
8688598	12/2013	Shakes et al.	N/A	N/A
8732028	12/2013	Napper	N/A	N/A
8818836	12/2013	Braumoeller et al.	N/A	N/A
9015069	12/2014	Brantley	N/A	N/A
9147208	12/2014	Argue et al.	N/A	N/A
9309056	12/2015	Lafontaine	N/A	B65G 47/54
9466045	12/2015	Kumar	N/A	N/A
9470532	12/2015	Pellow et al.	N/A	N/A
9569745	12/2016	Ananthanarayanan	N/A	N/A

9626709	12/2016	Koch et al.	N/A	N/A
9710767	12/2016	Dietrich	N/A	N/A
9773097	12/2016	Mu et al.	N/A	N/A
10099864	12/2017	Gopalakrishnan	N/A	B07C 5/00
10127514	12/2017	Napoli	N/A	N/A
10336540	12/2018	Gravelle	N/A	N/A
10373226	12/2018	Russell et al.	N/A	N/A
10445807	12/2018	Commons et al.	N/A	N/A
10460332	12/2018	Kujat et al.	N/A	N/A
10572932	12/2019	Kumar	N/A	N/A
10657580	12/2019	Kumar	N/A	N/A
10699328	12/2019	Rajkhowa et al.	N/A	N/A
10740862	12/2019	Cui	N/A	G06F 30/20
10943356	12/2020	Armstrong et al.	N/A	N/A
2002/0143655	12/2001	Elston	N/A	N/A
2002/0161664	12/2001	Shaya et al.	N/A	N/A
2002/0174038	12/2001	Chien	N/A	N/A
2002/0198756	12/2001	Ghaisas et al.	N/A	N/A
2003/0033177	12/2002	MacGonigle et al.	N/A	N/A
2003/0046169	12/2002	Fraser et al.	N/A	N/A
2003/0177072	12/2002	Bared	N/A	N/A
2003/0200148	12/2002	Razumov	N/A	N/A
2003/0204431	12/2002	Ingman	N/A	N/A
2004/0010437	12/2003	Kiran et al.	N/A	N/A
2004/0068443	12/2003	Hopson et al.	N/A	N/A
2004/0210621	12/2003	Antonellis	709/200	G06Q 10/087
2004/0249497	12/2003	Saigh	N/A	N/A
2005/0278062	12/2004	Janert et al.	N/A	N/A
2006/0020366	12/2005	Bloom	N/A	N/A
2007/0005377	12/2006	Cherry	N/A	N/A
2007/0043468	12/2006	Schaefer et al.	N/A	N/A
2007/0094067	12/2006	Kumar	N/A	N/A
2007/0150375	12/2006	Yang	N/A	N/A
2007/0174144	12/2006	Borders et al.	N/A	N/A
2007/0244758	12/2006	Xie	N/A	N/A
2007/0250355	12/2006	Leet et al.	N/A	N/A
2009/0048878	12/2008	Metcalf	N/A	N/A
2009/0106124	12/2008	Yang	N/A	N/A
2009/0157472	12/2008	Burazin et al.	N/A	N/A
2009/0254398	12/2008	Smith	705/28	G06Q 10/087
2009/0257081	12/2008	Bouchard	N/A	N/A
2009/0281921	12/2008	Foster et al.	N/A	N/A
2009/0307096	12/2008	Antonellis	N/A	N/A
2010/0010902	12/2009	Casey	N/A	N/A
2010/0194560	12/2009	Hojecki et al.	N/A	N/A
2010/0287025	12/2009	Fletcher et al.	N/A	N/A
2011/0213651	12/2010	Milana	N/A	N/A
2012/0023034	12/2011	Lynch et al.	N/A	N/A
2012/0030133	12/2011	Rademaker	N/A	N/A
2012/0078747	12/2011	Chakrabarti	N/A	N/A

2012/0123674	12/2011	Perks et al.	N/A	N/A
2012/0150340	12/2011	Suess et al.	N/A	N/A
2012/0173449	12/2011	Waddington	N/A	N/A
2012/0278672	12/2011	Sinanoglu	N/A	N/A
2012/0330458	12/2011	Weiss	N/A	N/A
2013/0030955	12/2012	David	N/A	N/A
2013/0035978	12/2012	Richardson et al.	N/A	N/A
2013/0185198	12/2012	Lorch	N/A	N/A
2013/0231990	12/2012	Munjal et al.	N/A	N/A
2013/0332273	12/2012	Gu et al.	N/A	N/A
2013/0339966	12/2012	Meng et al.	N/A	N/A
2013/0346204	12/2012	Wissner-Gross et al.	N/A	N/A
2014/0003727	12/2013	Lortz et al.	N/A	N/A
2014/0040075	12/2013	Perry et al.	N/A	N/A
2014/0046733	12/2013	Grichnik et al.	N/A	N/A
2014/0095350	12/2013	Carr	N/A	N/A
2014/0136255	12/2013	Grabovski et al.	N/A	N/A
2014/0156553	12/2013	Leach et al.	N/A	N/A
2014/0207615	12/2013	Li et al.	N/A	N/A
2014/0222623	12/2013	Napper	N/A	N/A
2014/0266616	12/2013	Jones et al.	N/A	N/A
2014/0278627	12/2013	Grabovski et al.	N/A	N/A
2014/0278635	12/2013	Fulton et al.	N/A	N/A
2014/0279294	12/2013	Field-Darragh	705/28	H04B 5/77
2014/0288696	12/2013	Lert	700/216	B65G 1/065
2014/0324491	12/2013	Banks	705/7.12	G06Q 10/087
2014/0336814	12/2013	Moore	700/216	G06Q 10/08
2014/0351101	12/2013	Danelski	705/28	G06Q 30/06
2014/0379529	12/2013	Agasti et al.	N/A	N/A
2014/0379829	12/2013	Mahdi	N/A	N/A
2015/0051994	12/2014	Ward et al.	N/A	N/A
2015/0081088	12/2014	Lyon et al.	N/A	N/A
2015/0120514	12/2014	Deshpande et al.	N/A	N/A
2015/0149320	12/2014	Smirin	N/A	N/A
2015/0170256	12/2014	Pettyjohn	N/A	N/A
2015/0186803	12/2014	Stong	N/A	N/A
2015/0187027	12/2014	Lowe	N/A	N/A
2015/0206093	12/2014	Trew et al.	N/A	N/A
2015/0227890	12/2014	Bednarek	N/A	N/A
2015/0242918	12/2014	McCarthy	N/A	N/A
2015/0278759	12/2014	Harris et al.	N/A	N/A
2015/0307278	12/2014	Wickham et al.	N/A	N/A
2015/0310447	12/2014	Shaw	N/A	N/A
2015/0363843	12/2014	Loppatto et al.	N/A	N/A
2015/0370251	12/2014	Siegel et al.	N/A	N/A
2016/0012391	12/2015	Burnett	N/A	N/A
2016/0055222	12/2015	Sarferaz	N/A	N/A
2016/0055452	12/2015	Qin	N/A	N/A
2016/0063604	12/2015	Shaffer et al.	N/A	N/A
2016/0071056	12/2015	Ellison et al.	N/A	N/A

2016/0092969	12/2015	Gopalsamy et al.	N/A	N/A
2016/0148300	12/2015	Carr et al.	N/A	N/A
2016/0155088	12/2015	Pylappan	N/A	N/A
2016/0171592	12/2015	Pugh et al.	N/A	N/A
2016/0203543	12/2015	Snow	N/A	N/A
2016/0217513	12/2015	Moghaddam et al.	N/A	N/A
2016/0223339	12/2015	Pellow et al.	N/A	N/A
2016/0247113	12/2015	Rademaker	N/A	N/A
2016/0253740	12/2015	Goulart	N/A	N/A
2016/0258762	12/2015	Taylor et al.	N/A	N/A
2016/0260158	12/2015	High et al.	N/A	N/A
2016/0299782	12/2015	Jones et al.	N/A	N/A
2016/0314335	12/2015	Al-Kofahi	N/A	G06T 7/187
2016/0314429	12/2015	Gillen et al.	N/A	N/A
2016/0321605	12/2015	Maifeld et al.	N/A	N/A
2016/0328781	12/2015	Patel-Zellinger et al.	N/A	N/A
2016/0350837	12/2015	Williams et al.	N/A	N/A
2017/0011338	12/2016	Stenneth	N/A	N/A
2017/0011449	12/2016	Mueller et al.	N/A	N/A
2017/0018041	12/2016	Fox	N/A	N/A
2017/0024789	12/2016	Frehn et al.	N/A	N/A
2017/0024805	12/2016	Tepfenhart	N/A	N/A
2017/0069013	12/2016	Castillo	N/A	N/A
2017/0124378	12/2016	High et al.	N/A	N/A
2017/0124511	12/2016	Mueller et al.	N/A	N/A
2017/0200108	12/2016	Au et al.	N/A	N/A
2017/0213186	12/2016	Grifoni	N/A	G06Q 10/087
2017/0228701	12/2016	Wosk et al.	N/A	N/A
2017/0278047	12/2016	Welty et al.	N/A	N/A
2017/0278176	12/2016	Valkov	N/A	B65B 57/00
2017/0285648	12/2016	Welty et al.	N/A	N/A
2017/0337523	12/2016	Roach	N/A	N/A
2017/0344010	12/2016	Rander et al.	N/A	N/A
2017/0353833	12/2016	de Barros Chapiewski	N/A	N/A
2017/0369245	12/2016	Suemitsu	N/A	B65G 1/1373
2017/0372226	12/2016	Costa	N/A	N/A
2018/0012151	12/2017	Wang	N/A	N/A
2018/0075404	12/2017	Hendrickson	N/A	N/A
2018/0096295	12/2017	Wang et al.	N/A	N/A
2018/0121992	12/2017	Agarwal et al.	N/A	N/A
2018/0137452	12/2017	Khartravath et al.	N/A	N/A
2018/0137455	12/2017	Mack et al.	N/A	N/A
2018/0182054	12/2017	Yao et al.	N/A	N/A
2018/0218311	12/2017	Kumar	N/A	N/A
2018/0218440	12/2017	Kumar	N/A	G06Q 30/0635
2018/0247257	12/2017	Lert, Jr.	N/A	G06Q 10/087
2018/0253805	12/2017	Kelly et al.	N/A	N/A
2018/0260744	12/2017	Fukuda et al.	N/A	N/A
2018/0275525	12/2017	Bow et al.	N/A	N/A

2018/0300800	12/2017	Rajkhowa et al.	N/A	N/A
2018/0307998	12/2017	Strachan	N/A	N/A
2018/0314991	12/2017	Grundberg	N/A	N/A
2018/0342031	12/2017	Tada	N/A	H04N 9/3194
2018/0349861	12/2017	Goja	N/A	N/A
2018/0374046	12/2017	Powers	N/A	G06Q 10/08345
2019/0019240	12/2018	Smith	N/A	N/A
2019/0057347	12/2018	Vitek et al.	N/A	N/A
2019/0130323	12/2018	Sundel	N/A	N/A
2019/0197195	12/2018	Krishnamurthy et al.	N/A	N/A
2019/0313489	12/2018	Guatta	N/A	N/A
2019/0325377	12/2018	Rajkhowa	N/A	G06Q 10/087
2019/0340561	12/2018	Rajkhowa et al.	N/A	N/A
2020/0311644	12/2019	Willard, III	N/A	G06Q 30/0601
2021/0061566	12/2020	Cacioppo	N/A	B25J 9/162
2021/0269244	12/2020	Ahmann	N/A	B65G 1/0492

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101778045	12/2009	CN	N/A
101964799	12/2010	CN	N/A
102137100	12/2010	CN	N/A
102377629	12/2011	CN	N/A
102012100354	12/2012	DE	N/A
2309792	12/2007	ES	N/A
2524952	12/2014	GB	N/A
20160068403	12/2015	KR	N/A
2015120506	12/2014	WO	N/A
2016119747	12/2015	WO	N/A
2016119749	12/2015	WO	N/A

OTHER PUBLICATIONS

ISR for corresponding Int'l Application No. PCT/CN2016/072791, dated Apr. 28, 2016 Apr. 4, 2016. cited by applicant

Ertekin, S., & Pelton, L.E. (2015). Navigating the Retail Environment: An Exploratory Investigation of In-Store Mapping Applications. Academy of Marketing Studies Journal, 19(2), 37-48. Retrieved from <https://search.proquest.com/docview/1750421168?accountid=14753> 2015. cited by applicant

Sharma et al., A Proposed Hybrid Storage Assignment Framework: A Case Study, International Journal of Productivity and Performance Management 65.6:870-892. Emerald Group Publishing Limited. Dialog #2115757331 20 pgs. (Year: 2015) 2015. cited by applicant

Matusiak, Marek et al., "Data-Driven warehouse optimization: deploying skills of order pickers", Finnish Centre of Excellence in Generic Intelligent Machines Research Jun. 29, 2015. cited by applicant

Fulton, Rick, Estimating Delivery Times: A Case Study in Practical Machine Learning, Postmates Blog, Oct. 23, 2015 Oct. 23, 2015. cited by applicant

Pingulkar et al., "Picking productivity estimation in distribution warehouses," Feb. 25, 2015 Feb.

25, 2015. cited by applicant

Mao et al., "Small boxes big data—deep learning approach to optimize variable sized bin packing," IEEE 3rd Conf Big Data Service, pp. 80-89, <https://eeexplore.ieee.org/abstract/document/7944923> (Year: 2017) Apr. 6, 2017. cited by applicant

Elmahi, I., et al. "A genetic algorithm approach for the batches delivery optimization in a supply chain." IEEE International Conference on Networking, Sensing and Control, 2004. vol. 1. IEEE, 2004. (Year: 2004). cited by applicant

A. Ulbrich, S. Galka, and W.A. Gunther, "Secure Planning of Order Picking Systems with the Aid of Simulation," 2010 43rd Hawaii International Conference on System Sciences, Honolulu, HI, 2010, pp. 1-7, doi: 10.1109/HICSS.2010.326. (Year: 2010) 2010. cited by applicant

Y. Wang, Z. Wang, and S. Mi, "An Order Batching Clustering Algorithm of Fixed Maximum Order Number Based on Order Picking System," 2017 4th International Conference on Industrial Economics System and Industrial Security Engineering (IEIS), Kyoto, 2017, pp. 106, doi: 10.1109/IEIS.2017.8078640. (Year: 2017) 2017. cited by applicant

J.P. Gagliani, J. Renaud, and A. Ruiz, "A Simulation Model to Improve Warehouse Operations," 2007 Winter Simulation Conference, Washington, DC, 2007, pp. 2012-2018, doi: 10.1109/WSC.2007.4419831. (Year: 2007) 2007. cited by applicant

G. Pedrielli, A. Vinsensius, E.P. Chew, L.H. Lee, A. Duri, and Haobin Li, "Hybrid order picking strategies for fashion E-commerce warehouse systems," 2016 Winter Simulation Conference (WSC), Washington, DC, 2016, pp. 2250-2261, doi: 10.1109/WSC.2016.7822266. (Year: 2016) 2016. cited by applicant

J. Shiau and H. Ma, "An order picking heuristic algorithm for economical packing," Proceedings of the 11th IEEE International Conference on Networking, Sensing and Control, Miami, FL, 2014, pp. 423-437, doi: 10.1109/CNSC.2014.6819665 (Year: 2014) 2014. cited by applicant

M. Bustillo, B. Menendez, E.G. Pardo, and A. Duarte, "An algorithm for batching, sequencing and picking operations in a warehouse," 2015 International Conference on Industrial Engineering and Systems Management (IESM), Seville, 2015, pp. 842-849, doi: 10.1109/IESM.2015.7380254. (Year: 2015) 2015. cited by applicant

Grosse, et al., "The effect of worker learning on manual order picking processes," (2015) (vol. 170, Part C, Dec. 2015, pp. 882-890) 2015. cited by applicant

Primary Examiner: Crawley; Talia F

Attorney, Agent or Firm: FOLEY & LARDNER LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a Continuation Application of U.S. patent application Ser. No. 16/778,393, filed on Jan. 31, 2020, to be issued as U.S. Pat. No. 11,868,958. U.S. patent application Ser. No. 16/778,393 is herewith incorporated by reference in its entirety.

TECHNICAL FIELD

(1) This disclosure relates generally to pick walk generating systems, and more particularly to optimization of pick walk systems for improved speed of pick walk generation.

BACKGROUND

(2) In general, pick walk generating systems focus on minimizing a time spent and distance traveled by a picker on a pick walk. While numerous methods for generating a pick walk are known in the art, optimization and further refinement of already generated pick walks have proven

cumbersome and slow. For example, a commonly used technique for pick walk optimization known as ant colony optimization produces satisfactory solutions, but is known to be time and processing power intensive due to the need to calculate savings among all possible combinations for a pick walk. As users continue to migrate to eCommerce and in-store pick-up for goods, the number of pick walk optimizations needed continues to rise. This problem is compounded by a recent leveling off in advancements in computer processing power due to an oncoming death of Moore's Law. Therefore, there is a need for a pick path optimization system that avoids the problems of prior pick path optimization systems, thereby leading to faster processing times and fewer burdens on processing circuits.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) To facilitate further description of the embodiments, the following drawings are provided in which:
- (2) FIG. 1 illustrates a front elevational view of a computer system that is suitable for implementing various embodiments of the systems disclosed in FIGS. 3 and 5;
- (3) FIG. 2 illustrates a representative block diagram of an example of the elements included in the circuit boards inside a chassis of the computer system of FIG. 1;
- (4) FIG. 3 illustrates a representative block diagram of a system, according to an embodiment;
- (5) FIG. 4 illustrates a flowchart for a method, according to certain embodiments;
- (6) FIG. 5 illustrates a flowchart for a method, according to certain embodiments;
- (7) FIG. 6 illustrates representative pseudocode instructions, according to a representative embodiment;
- (8) FIG. 7 illustrates a flowchart for a method, according to certain embodiments;
- (9) FIG. 8 illustrates representative pseudocode instructions, according to a representative embodiment;
- (10) FIG. 9 illustrates representative pseudocode instructions, according to a representative embodiment;
- (11) FIG. 10 illustrates representative pseudocode instructions, according to a representative embodiment;
- (12) FIG. 11 illustrates representative pseudocode instructions, according to a representative embodiment;
- (13) FIG. 12 illustrates a representative block diagram of a system, according to an additional embodiment;
- (14) FIG. 13 illustrates a representative block diagram of a system, according to an additional embodiment; and
- (15) FIG. 14 illustrates a representative block diagram of a system, according to an additional embodiment.
- (16) For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the present disclosure. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure. The same reference numerals in different figures denote the same elements.
- (17) The terms “first,” “second,” “third,” “fourth,” and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are

interchangeable under appropriate circumstances such that the embodiments described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms “include,” and “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, system, article, device, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, system, article, device, or apparatus.

(18) The terms “left,” “right,” “front,” “back,” “top,” “bottom,” “over,” “under,” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the apparatus, methods, and/or articles of manufacture described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein.

(19) The terms “couple,” “coupled,” “couples,” “coupling,” and the like should be broadly understood and refer to connecting two or more elements mechanically and/or otherwise. Two or more electrical elements may be electrically coupled together, but not be mechanically or otherwise coupled together. Coupling may be for any length of time, e.g., permanent or semi-permanent or only for an instant. “Electrical coupling” and the like should be broadly understood and include electrical coupling of all types. The absence of the word “removably,” “removable,” and the like near the word “coupled,” and the like does not mean that the coupling, etc. in question is or is not removable.

(20) As defined herein, two or more elements are “integral” if they are comprised of the same piece of material. As defined herein, two or more elements are “non-integral” if each is comprised of a different piece of material.

(21) As defined herein, “real-time” can, in some embodiments, be defined with respect to operations carried out as soon as practically possible upon occurrence of a triggering event. A triggering event can include receipt of data necessary to execute a task or to otherwise process information. Because of delays inherent in transmission and/or in computing speeds, the term “real time” encompasses operations that occur in “near” real time or somewhat delayed from a triggering event. In a number of embodiments, “real time” can mean real time less a time delay for processing (e.g., determining) and/or transmitting data. The particular time delay can vary depending on the type and/or amount of the data, the processing speeds of the hardware, the transmission capability of the communication hardware, the transmission distance, etc. However, in many embodiments, the time delay can be less than approximately one second, two seconds, five seconds, or ten seconds.

(22) As defined herein, “approximately” can, in some embodiments, mean within plus or minus ten percent of the stated value. In other embodiments, “approximately” can mean within plus or minus five percent of the stated value. In further embodiments, “approximately” can mean within plus or minus three percent of the stated value. In yet other embodiments, “approximately” can mean within plus or minus one percent of the stated value.

DESCRIPTION OF EXAMPLES OF EMBODIMENTS

(23) A number of embodiments can include a system. The system can include one or more processors and one or more non-transitory computer-readable storage devices storing computing instructions. The computing instructions can be configured to run on the one or more processors and perform: receiving a respective number of totes for each respective order of one or more orders; determining, using a first set of rules, when the respective number of totes for a respective order of the one or more orders can be reduced; when the respective number of totes is determined to be able to be reduced, reducing, using a second set of rules, the respective number of totes for the respective order to a respective reduced number of totes for the respective order of the one or more orders; comparing the respective number of totes for the respective order to the respective

reduced number of totes for the respective order; and when the respective number of totes for the respective order is compared to be equal to the respective reduced number of totes for the respective order, facilitating displaying, on an electronic device to a picker, the respective number of totes for the respective order.

(24) Various embodiments include a method. The method can be implemented via execution of computing instructions configured to run at one or more processors and configured to be stored at non-transitory computer-readable media. The method can comprise receiving a respective number of totes for each respective order of one or more orders; determining, using a first set of rules, when the respective number of totes for a respective order of the one or more orders can be reduced; when the respective number of totes is determined to be able to be reduced, reducing, using a second set of rules, the respective number of totes for the respective order to a respective reduced number of totes for the respective order of the one or more orders; comparing the respective number of totes for the respective order to the respective reduced number of totes for the respective order; and when the respective number of totes for the respective order is compared to be equal to the respective reduced number of totes for the respective order, facilitating displaying, on an electronic device to a picker, the respective number of totes for the respective order.

(25) A number of embodiments can include a system. The system can include one or more processors and one or more non-transitory computer-readable storage devices storing computing instructions. The computing instructions can be configured to run on the one or more processors and perform: executing a greedy incremental batcher loop, which can comprise: selecting a first picklist of one or more picklists; and merging the first picklist with one or more picklists in a first remainder of the one or more picklists when the merging would decrease a cost of the first picklist, wherein the first remainder of the one or more picklists comprises the one or picklists excluding the first picklist; executing a randomized tote local search loop, which can comprise: selecting two random picklists of the one or more picklists, as merged; and swapping totes of the two random picklists of the one or more picklists, as merged, when the swapping would decrease a cost of at least one picklist of the two random picklists; executing an update min trolley loop, which can comprise: selecting a shortest picklist of the one or more picklists, as merged and swapped; and combining the shortest picklist with at least one picklist of the one or more picklists, as merged and swapped, wherein a combination picklist of the shortest picklist and the at least one picklist results in a savings of cost; and facilitating displaying the combination picklist and the one or more picklists, as merged and swapped, to a picker.

(26) Various embodiments include a method. The method can be implemented via execution of computing instructions configured to run at one or more processors and configured to be stored at non-transitory computer-readable media. The method can comprise executing a greedy incremental batcher loop, which can comprise: selecting a first picklist of one or more picklists; and merging the first picklist with one or more picklists in a first remainder of the one or more picklists when the merging would decrease a cost of the first picklist, wherein the first remainder of the one or more picklists comprises the one or picklists excluding the first picklist; executing a randomized tote local search loop, which can comprise: selecting two random picklists of the one or more picklists, as merged; and swapping totes of the two random picklists of the one or more picklists, as merged, when the swapping would decrease a cost of at least one picklist of the two random picklists; executing an update min trolley loop, which can comprise: selecting a shortest picklist of the one or more picklists, as merged and swapped; and combining the shortest picklist with at least one picklist of the one or more picklists, as merged and swapped, wherein a combination picklist of the shortest picklist and the at least one picklist results in a savings of cost; and facilitating displaying the combination picklist and the one or more picklists, as merged and swapped, to a picker.

(27) A number of embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions that, then executed on the

one or more processors, cause the one or more processors to perform certain acts. The acts can include determining that a respective number of totes for a respective order of one or more orders can be reduced. The acts also can include reducing, using an infeasible totes loop, the respective number of the totes for the respective order to a respective reduced number of the totes for the respective order of the one or more orders. The acts further can include executing, as part of the infeasible totes loop, an item search that determines combinations of items swapped between the respective number of the totes for the respective order. The acts additionally can include running the item search until a predefined number of iterations is reached. The acts also can include generating directions for a route of a pick walk based on a map of a retail facility. The pick walk can include a picklist comprising the respective number of the totes for the respective order. The acts further can include facilitating displaying, on an electronic device, the route of the pick walk on the map of the retail facility.

(28) Various embodiments include a method being implemented via execution of computing instructions configured to run on one or more processors stored on one or more non-transitory computer-readable media. The method can include determining that a respective number of totes for a respective order of one or more orders can be reduced. The method also can include reducing, using an infeasible totes loop, the respective number of the totes for the respective order to a respective reduced number of the totes for the respective order of the one or more orders. The method further can include executing, as part of the infeasible totes loop, an item search that determines combinations of items swapped between the respective number of the totes for the respective order. The method additionally can include running the item search until a predefined number of iterations is reached. The method also can include generating directions for a route of a pick walk based on a map of a retail facility. The pick walk can include a picklist comprising the respective number of the totes for the respective order. The method further can include facilitating displaying, on an electronic device, the route of the pick walk on the map of the retail facility.

(29) Turning to the drawings, FIG. 1 illustrates an exemplary embodiment of a computer system **100**, all of which or a portion of which can be suitable for (i) implementing part or all of one or more embodiments of the techniques, methods, and systems and/or (ii) implementing and/or operating part or all of one or more embodiments of the memory storage modules described herein. As an example, a different or separate one of a chassis **102** (and its internal components) can be suitable for implementing part or all of one or more embodiments of the techniques, methods, and/or systems described herein. Furthermore, one or more elements of computer system **100** (e.g., a monitor **106**, a keyboard **104**, and/or a mouse **110**, etc.) also can be appropriate for implementing part or all of one or more embodiments of the techniques, methods, and/or systems described herein. Computer system **100** can comprise chassis **102** containing one or more circuit boards (not shown), a Universal Serial Bus (USB) port **112**, a Compact Disc Read-Only Memory (CD-ROM) and/or Digital Video Disc (DVD) drive **116**, and a hard drive **114**. A representative block diagram of the elements included on the circuit boards inside chassis **102** is shown in FIG. 2. A central processing unit (CPU) **210** in FIG. 2 is coupled to a system bus **214** in FIG. 2. In various embodiments, the architecture of CPU **210** can be compliant with any of a variety of commercially distributed architecture families.

(30) Continuing with FIG. 2, system bus **214** also is coupled to a memory storage unit **208**, where memory storage unit **208** can comprise (i) non-volatile memory, such as, for example, read only memory (ROM) and/or (ii) volatile memory, such as, for example, random access memory (RAM). The non-volatile memory can be removable and/or non-removable non-volatile memory. Meanwhile, RAM can include dynamic RAM (DRAM), static RAM (SRAM), etc. Further, ROM can include mask-programmed ROM, programmable ROM (PROM), one-time programmable ROM (OTP), erasable programmable read-only memory (EPROM), electrically erasable programmable ROM (EEPROM) (e.g., electrically alterable ROM (EAROM) and/or flash memory), etc. In these or other embodiments, memory storage unit **208** can comprise (i) non-

transitory memory and/or (ii) transitory memory.

(31) In many embodiments, all or a portion of memory storage unit **208** can be referred to as memory storage module(s) and/or memory storage device(s). In various examples, portions of the memory storage module(s) of the various embodiments disclosed herein (e.g., portions of the non-volatile memory storage module(s)) can be encoded with a boot code sequence suitable for restoring computer system **100** (FIG. **1**) to a functional state after a system reset. In addition, portions of the memory storage module(s) of the various embodiments disclosed herein (e.g., portions of the non-volatile memory storage module(s)) can comprise microcode such as a Basic Input-Output System (BIOS) operable with computer system **100** (FIG. **1**). In the same or different examples, portions of the memory storage module(s) of the various embodiments disclosed herein (e.g., portions of the non-volatile memory storage module(s)) can comprise an operating system, which can be a software program that manages the hardware and software resources of a computer and/or a computer network. The BIOS can initialize and test components of computer system **100** (FIG. **1**) and load the operating system. Meanwhile, the operating system can perform basic tasks such as, for example, controlling and allocating memory, prioritizing the processing of instructions, controlling input and output devices, facilitating networking, and managing files. Exemplary operating systems can comprise one of the following: (i) Microsoft® Windows® operating system (OS) by Microsoft Corp. of Redmond, Washington, United States of America, (ii) Mac® OS X by Apple Inc. of Cupertino, California, United States of America, (iii) UNIX® OS, and (iv) Linux® OS. Further exemplary operating systems can comprise one of the following: (i) the iOS® operating system by Apple Inc. of Cupertino, California, United States of America, (ii) the Blackberry® operating system by Research In Motion (RIM) of Waterloo, Ontario, Canada, (iii) the WebOS operating system by LG Electronics of Seoul, South Korea, (iv) the Android™ operating system developed by Google, of Mountain View, California, United States of America, (v) the Windows Mobile™ operating system by Microsoft Corp. of Redmond, Washington, United States of America, or (vi) the Symbian™ operating system by Accenture PLC of Dublin, Ireland.

(32) As used herein, “processor” and/or “processing module” means any type of computational circuit, such as but not limited to a microprocessor, a microcontroller, a controller, a complex instruction set computing (CISC) microprocessor, a reduced instruction set computing (RISC) microprocessor, a very long instruction word (VLIW) microprocessor, a graphics processor, a digital signal processor, or any other type of processor or processing circuit capable of performing the desired functions. In some examples, the one or more processing modules of the various embodiments disclosed herein can comprise CPU **210**.

(33) Alternatively, or in addition to, the systems and procedures described herein can be implemented in hardware, or a combination of hardware, software, and/or firmware. For example, one or more application specific integrated circuits (ASICs) can be programmed to carry out one or more of the systems and procedures described herein. For example, one or more of the programs and/or executable program components described herein can be implemented in one or more ASICs. In many embodiments, an application specific integrated circuit (ASIC) can comprise one or more processors or microprocessors and/or memory blocks or memory storage.

(34) In the depicted embodiment of FIG. **2**, various I/O devices such as a disk controller **204**, a graphics adapter **224**, a video controller **202**, a keyboard adapter **226**, a mouse adapter **206**, a network adapter **220**, and other I/O devices **222** can be coupled to system bus **214**. Keyboard adapter **226** and mouse adapter **206** are coupled to keyboard **104** (FIGS. **1-2**) and mouse **110** (FIGS. **1-2**), respectively, of computer system **100** (FIG. **1**). While graphics adapter **224** and video controller **202** are indicated as distinct units in FIG. **2**, video controller **202** can be integrated into graphics adapter **224**, or vice versa in other embodiments. Video controller **202** is suitable for monitor **106** (FIGS. **1-2**) to display images on a screen **108** (FIG. **1**) of computer system **100** (FIG. **1**). Disk controller **204** can control hard drive **114** (FIGS. **1-2**), USB port **112** (FIGS. **1-2**), and CD-ROM drive **116** (FIGS. **1-2**). In other embodiments, distinct units can be used to control each of

these devices separately.

(35) Network adapter **220** can be suitable to connect computer system **100** (FIG. **1**) to a computer network by wired communication (e.g., a wired network adapter) and/or wireless communication (e.g., a wireless network adapter). In some embodiments, network adapter **220** can be plugged or coupled to an expansion port (not shown) in computer system **100** (FIG. **1**). In other embodiments, network adapter **220** can be built into computer system **100** (FIG. **1**). For example, network adapter **220** can be built into computer system **100** (FIG. **1**) by being integrated into the motherboard chipset (not shown), or implemented via one or more dedicated communication chips (not shown), connected through a PCI (peripheral component interconnector) or a PCI express bus of computer system **100** (FIG. **1**) or USB port **112** (FIG. **1**).

(36) Returning now to FIG. **1**, although many other components of computer system **100** are not shown, such components and their interconnection are well known to those of ordinary skill in the art. Accordingly, further details concerning the construction and composition of computer system **100** and the circuit boards inside chassis **102** are not discussed herein.

(37) Meanwhile, when computer system **100** is running, program instructions (e.g., computer instructions) stored on one or more of the memory storage module(s) of the various embodiments disclosed herein can be executed by CPU **210** (FIG. **2**). At least a portion of the program instructions, stored on these devices, can be suitable for carrying out at least part of the techniques and methods described herein.

(38) Further, although computer system **100** is illustrated as a desktop computer in FIG. **1**, there can be examples where computer system **100** may take a different form factor while still having functional elements similar to those described for computer system **100**. In some embodiments, computer system **100** may comprise a single computer, a single server, or a cluster or collection of computers or servers, or a cloud of computers or servers. Typically, a cluster or collection of servers can be used when the demand on computer system **100** exceeds the reasonable capability of a single server or computer. In certain embodiments, computer system **100** may comprise a portable computer, such as a laptop computer. In certain other embodiments, computer system **100** may comprise a mobile electronic device, such as a smartphone. In certain additional embodiments, computer system **100** may comprise an embedded system.

(39) Turning ahead in the drawings, FIG. **3** illustrates a block diagram of a system **300** that can be employed for optimization of pick walks, as described in greater detail below. System **300** is merely exemplary and embodiments of the system are not limited to the embodiments presented herein. System **300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements or modules of system **300** can perform various procedures, processes, and/or activities. In these or other embodiments, the procedures, processes, and/or activities can be performed by other suitable elements or modules of system **300**.

(40) Generally, therefore, system **300** can be implemented with hardware and/or software, as described herein. In some embodiments, part or all of the hardware and/or software can be conventional, while in these or other embodiments, part or all of the hardware and/or software can be customized (e.g., optimized) for implementing part or all of the functionality of system **300** described herein.

(41) In some embodiments, system **300** can include a web server **310** and/or a store computer **360**. Web server **310** and/or store computer **360** can each be a computer system, such as computer system **100** (FIG. **1**), as described above, and can each be a single computer, a single server, or a cluster or collection of computers or servers, or a cloud of computers or servers. In another embodiment, a single computer system can host each of two or more of web server **310** and/or store computer **360**. In these or other embodiments, web server **310** and/or store computer **360** can comprise a second system **400**, which is described in further detail below. Additional details regarding web server **310** and/or store computer **360** are described herein.

(42) In many embodiments, system 300 also can comprise user computers 330, 331. In other embodiments, user computers 330, 331 are external to system 300. User computers 330, 331 can comprise any of the elements described in relation to computer system 100. In some embodiments, user computers 330, 331 can be mobile devices. A mobile electronic device can refer to a portable electronic device (e.g., an electronic device easily conveyable by hand by a person of average size) with the capability to present audio and/or visual data (e.g., text, images, videos, music, etc.). For example, a mobile electronic device can comprise at least one of a digital media player, a cellular telephone (e.g., a smartphone), a personal digital assistant, a handheld digital computer device (e.g., a tablet personal computer device), a laptop computer device (e.g., a notebook computer device, a netbook computer device), a wearable user computer device, or another portable computer device with the capability to present audio and/or visual data (e.g., images, videos, music, etc.). Thus, in many examples, a mobile electronic device can comprise a volume and/or weight sufficiently small as to permit the mobile electronic device to be easily conveyable by hand. For examples, in some embodiments, a mobile electronic device can occupy a volume of less than or equal to approximately 1790 cubic centimeters, 2434 cubic centimeters, 2876 cubic centimeters, 4056 cubic centimeters, and/or 5752 cubic centimeters. Further, in these embodiments, a mobile electronic device can weigh less than or equal to 15.6 Newtons, 17.8 Newtons, 22.3 Newtons, 31.2 Newtons, and/or 44.5 Newtons.

(43) Exemplary mobile electronic devices can comprise (i) an iPod®, iPhone®, iTouch®, iPad®, MacBook® or similar product by Apple Inc. of Cupertino, California, United States of America, (ii) a Blackberry® or similar product by Research in Motion (RIM) of Waterloo, Ontario, Canada, (iii) a Lumia® or similar product by the Nokia Corporation of Keilaniemi, Espoo, Finland, and/or (iv) a Galaxy™ or similar product by the Samsung Group of Samsung Town, Seoul, South Korea. Further, in the same or different embodiments, a mobile electronic device can comprise an electronic device configured to implement one or more of (i) the iPhone® operating system by Apple Inc. of Cupertino, California, United States of America, (ii) the Blackberry® operating system by Research In Motion (RIM) of Waterloo, Ontario, Canada, (iii) the Palm® operating system by Palm, Inc. of Sunnyvale, California, United States, (iv) the Android™ operating system developed by the Open Handset Alliance, (v) the Windows Mobile™ operating system by Microsoft Corp. of Redmond, Washington, United States of America, or (vi) the Symbian™ operating system by Nokia Corp. of Keilaniemi, Espoo, Finland.

(44) Further still, the term “wearable user computer device” as used herein can refer to an electronic device with the capability to present audio and/or visual data (e.g., text, images, videos, music, etc.) that is configured to be worn by a user and/or mountable (e.g., fixed) on the user of the wearable user computer device (e.g., sometimes under or over clothing; and/or sometimes integrated with and/or as clothing and/or another accessory, such as, for example, a hat, eyeglasses, a wrist watch, shoes, etc.). In many examples, a wearable user computer device can comprise a mobile electronic device, and vice versa. However, a wearable user computer device does not necessarily comprise a mobile electronic device, and vice versa.

(45) In specific examples, a wearable user computer device can comprise a head mountable wearable user computer device (e.g., one or more head mountable displays, one or more eyeglasses, one or more contact lenses, one or more retinal displays, etc.) or a limb mountable wearable user computer device (e.g., a smart watch). In these examples, a head mountable wearable user computer device can be mountable in close proximity to one or both eyes of a user of the head mountable wearable user computer device and/or vectored in alignment with a field of view of the user.

(46) In more specific examples, a head mountable wearable user computer device can comprise (i) Google Glass™ product or a similar product by Google Inc. of Menlo Park, California, United States of America; (ii) the Eye Tap™ product, the Laser Eye Tap™ product, or a similar product by ePI Lab of Toronto, Ontario, Canada, and/or (iii) the Raptyr™ product, the STAR 1200™ product,

the Vuzix Smart Glasses M100™ product, or a similar product by Vuzix Corporation of Rochester, New York, United States of America. In other specific examples, a head mountable wearable user computer device can comprise the Virtual Retinal Display™ product, or similar product by the University of Washington of Seattle, Washington, United States of America. Meanwhile, in further specific examples, a limb mountable wearable user computer device can comprise the iWatch™ product, or similar product by Apple Inc. of Cupertino, California, United States of America, the Galaxy Gear or similar product of Samsung Group of Samsung Town, Seoul, South Korea, the Moto **360** product or similar product of Motorola of Schaumburg, Illinois, United States of America, and/or the Zip™ product, One™ product, Flex™ product, Charge™ product, Surge™ product, or similar product by Fitbit Inc. of San Francisco, California, United States of America.

(47) In many embodiments, system **300** can comprise graphical user interface (“GUI”) **350-353**. In the same or different embodiments, GUI **350-353** can be part of and/or displayed by user computers **330, 331**, which also can be part of system **300**. In some embodiments, GUI **350-353** can comprise text and/or graphics (image) based user interfaces. In the same or different embodiments, GUI **350-353** can comprise a heads up display (“HUD”). When GUI **350-353** comprises a HUD, GUI **350-353** can be projected onto glass or plastic, displayed in midair as a hologram, or displayed on monitor **106** (FIG. 1). In various embodiments, GUI **350-353** can be color or black and white. In many embodiments, GUI **350-353** can comprise an application running on a computer system, such as computer system **100**, user computers **330, 331**, server computer **310**, and/or store computer **360**. In the same or different embodiments, GUI **350-353** can comprise a website accessed through internet **320**. In some embodiments, GUI **350-353** can comprise an eCommerce website. In the same or different embodiments, GUI **350-353** can be displayed as or on a virtual reality (VR) and/or augmented reality (AR) system or display. In some embodiments, an interaction with a GUI can comprise a click, a look, a selection, a grab, a view, a purchase, a bid, a swipe, a pinch, etc.

(48) In some embodiments, web server **320** can be in data communication through Internet **320** with user computers (e.g., **350-353**). In certain embodiments, user computers **350-351** can be desktop computers, laptop computers, smart phones, tablet devices, and/or other endpoint devices. Web server **310** and/or store computer **360** can host one or more websites. For example, web server **310** and/or store computer **360** can host an eCommerce web site that allows users to browse and/or search for products, to add products to an electronic shopping cart, and/or to purchase products, in addition to other suitable activities.

(49) In many embodiments, web server **310** and/or store computer **360** can each comprise one or more input devices (e.g., one or more keyboards, one or more keypads, one or more pointing devices such as a computer mouse or computer mice, one or more touchscreen displays, a microphone, etc.), and/or can each comprise one or more display devices (e.g., one or more monitors, one or more touch screen displays, projectors, etc.). In these or other embodiments, one or more of the input device(s) can be similar or identical to keyboard **104** (FIG. 1) and/or a mouse **110** (FIG. 1). Further, one or more of the display device(s) can be similar or identical to monitor **106** (FIG. 1) and/or screen **108** (FIG. 1). The input device(s) and the display device(s) can be coupled to the processing module(s) and/or the memory storage module(s) web server **310** and/or store computer **360** in a wired manner and/or a wireless manner, and the coupling can be direct and/or indirect, as well as locally and/or remotely. As an example of an indirect manner (which may or may not also be a remote manner), a keyboard-video-mouse (KVM) switch can be used to couple the input device(s) and the display device(s) to the processing module(s) and/or the memory storage module(s). In some embodiments, the KVM switch also can be part of web server **310** and/or store computer **360**. In a similar manner, the processing module(s) and the memory storage module(s) can be local and/or remote to each other.

(50) In many embodiments, web server **310** and/or store computer **360** can be configured to communicate with one or more user computers **330** and **331**. In some embodiments, user

computers **330** and **331** also can be referred to as customer computers and/or picker computers. In some embodiments, web server **310** and/or store computer **360** can communicate or interface (e.g., interact) with one or more user computers **330** and **331** through a network or internet **330**. Internet **330** can be an intranet that is not open to the public. Accordingly, in many embodiments, web server **310** and/or store computer **360** (and/or the software used by such systems) can refer to a back end of system **300** operated by an operator and/or administrator of system **300**, and user computers **350-353** (and/or the software used by such systems) can refer to a front end of system **300** used by one or more users **340**, **341**, respectively. In some embodiments, users **340**, **341** can also be referred to as customers, in which case, user computers **330**, **331** can be referred to as customer computers. In other embodiments, users **340**, **341** can be referred to as pickers, in which case, user computers **330**, **331** can be referred to as picker computers. In these or other embodiments, the operator and/or administrator of system **300** can manage system **300**, the processing module(s) of system **300**, and/or the memory storage module(s) of system **300** using the input device(s) and/or display device(s) of system **300**.

(51) Meanwhile, in many embodiments, web server **310** and/or store computer **360** also can be configured to communicate with one or more databases. The one or more databases can comprise a product database that contains information about products, items, or SKUs (stock keeping units) sold by a retailer. The one or more databases can be stored on one or more memory storage modules (e.g., non-transitory memory storage module(s)), which can be similar or identical to the one or more memory storage module(s) (e.g., non-transitory memory storage module(s)) described above with respect to computer system **100** (FIG. 1). Also, in some embodiments, for any particular database of the one or more databases, that particular database can be stored on a single memory storage module of the memory storage module(s), and/or the non-transitory memory storage module(s) storing the one or more databases or the contents of that particular database can be spread across multiple ones of the memory storage module(s) and/or non-transitory memory storage module(s) storing the one or more databases, depending on the size of the particular database and/or the storage capacity of the memory storage module(s) and/or non-transitory memory storage module(s).

(52) The one or more databases can each comprise a structured (e.g., indexed) collection of data and can be managed by any suitable database management systems configured to define, create, query, organize, update, and manage database(s). Exemplary database management systems can include MySQL (Structured Query Language) Database, PostgreSQL Database, Microsoft SQL Server Database, Oracle Database, SAP (Systems, Applications, & Products) Database, IBM DB2 Database, and/or NoSQL Database.

(53) Meanwhile, communication between web server **310** and/or store computer **360**, and/or the one or more databases can be implemented using any suitable manner of wired and/or wireless communication. Accordingly, system **300** can comprise any software and/or hardware components configured to implement the wired and/or wireless communication. Further, the wired and/or wireless communication can be implemented using any one or any combination of wired and/or wireless communication network topologies (e.g., ring, line, tree, bus, mesh, star, daisy chain, hybrid, etc.) and/or protocols (e.g., personal area network (PAN) protocol(s), local area network (LAN) protocol(s), wide area network (WAN) protocol(s), cellular network protocol(s), powerline network protocol(s), etc.). Exemplary PAN protocol(s) can comprise Bluetooth, Zigbee, Wireless Universal Serial Bus (USB), Z-Wave, etc.; exemplary LAN and/or WAN protocol(s) can comprise Institute of Electrical and Electronic Engineers (IEEE) 802.3 (also known as Ethernet), IEEE 802.11 (also known as WiFi), etc.; and exemplary wireless cellular network protocol(s) can comprise Global System for Mobile Communications (GSM), General Packet Radio Service (GPRS), Code Division Multiple Access (CDMA), Evolution-Data Optimized (EV-DO), Enhanced Data Rates for GSM Evolution (EDGE), Universal Mobile Telecommunications System (UMTS), Digital Enhanced Cordless Telecommunications (DECT), Digital AMPS (IS-136/Time Division

Multiple Access (TDMA)), Integrated Digital Enhanced Network (iDEN), Evolved High-Speed Packet Access (HSPA+), Long-Term Evolution (LTE), WiMAX, etc. The specific communication software and/or hardware implemented can depend on the network topologies and/or protocols implemented, and vice versa. In many embodiments, exemplary communication hardware can comprise wired communication hardware including, for example, one or more data buses, such as, for example, universal serial bus(es), one or more networking cables, such as, for example, coaxial cable(s), optical fiber cable(s), and/or twisted pair cable(s), any other suitable data cable, etc. Further exemplary communication hardware can comprise wireless communication hardware including, for example, one or more radio transceivers, one or more infrared transceivers, etc. Additional exemplary communication hardware can comprise one or more networking components (e.g., modulator-demodulator components, gateway components, etc.).

(54) In many embodiments, the techniques described herein can provide a practical application and several technological improvements. In some embodiments, the techniques described herein can provide for improved processing times for pick path optimization. These techniques described herein can provide a significant improvement over conventional approaches of pick path optimization, such as ant colony optimization. In many embodiments, the techniques described herein can beneficially make determinations based on dynamic order information that is continually fed into the system and efficiently optimized in real time.

(55) In a number of embodiments, the techniques described herein can solve a technical problem that arises only within the realm of computer networks, as pick path optimization system do not exist outside the realm of computer networks.

(56) Turning ahead in the drawings, FIG. 4 illustrates a flow chart for a method **400**, according to an embodiment. Method **400** is merely exemplary and is not limited to the embodiments presented herein. Method **400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the activities of method **400** can be performed in the order presented. In other embodiments, the activities of method **400** can be performed in any suitable order. In still other embodiments, one or more of the activities of method **400** can be combined or skipped. In many embodiments, system **300** (FIG. 3) can be suitable to perform method **400** and/or one or more of the activities of method **400**. In these or other embodiments, one or more of the activities of method **400** can be implemented as one or more computer instructions configured to run at one or more processing modules and configured to be stored at one or more non-transitory memory storage modules. Such non-transitory memory storage modules can be part of a computer system such as web server **310** and/or store computer **360** (FIG. 3). The processing module(s) can be similar or identical to the processing module(s) described above with respect to computer system **100** (FIG. 1).

(57) In many embodiments, method **400** can comprise an activity **401** of receiving one or more orders. In some embodiments, one or more orders can be placed via user computers **330-331** (FIG. 3) and/or store computer **360** (FIG. 3). In these or other embodiments, one or more orders can be entered into user computers **330-331** (FIG. 3) and/or store computer **360** (FIG. 3) via GUIs **350-351** (FIG. 3) and/or GUI **353** (FIG. 3). In various embodiments, orders can be placed via an ecommerce website displayed on user computers **330-331** (FIG. 3) and/or store computer **353** (FIG. 3). In many embodiments, an order can comprise one or more items. In various embodiments, the one or more items can be store in a brick and mortar store and/or a warehouse. In the embodiment of FIG. 4, there are three orders.

(58) In many embodiments, method **400** can comprise an activity **402** of splitting an order into one or more totes. In some embodiments, a tote can comprise a container configured to hold one or more items. In these or other embodiments, one or more totes can be configured to be loaded onto a cart. In this way, one or more totes can travel around a brick and mortar store and/or a warehouse with a picker during a pick walk. Each picker can bring pull one or more carts with such picker during the pick walk of the picker. In various embodiments, each of the totes used in method **400**

are identical to each other in size, shape, volume, carrying capacity, etc., and in other embodiments, different totes can have different sizes, shapes, volumes, carrying capacities, etc. Similarly, in various embodiments, each of the carts used in method **400** are identical to each other in size, shape, volume, carrying capacity, etc., and in other embodiments, different totes can have different sizes, shapes, volumes, carrying capacities, etc. As used herein, a “pick walk” refers to a path taken by a picker to collect item(s) of an order. In many embodiments, activity **402** can comprise method **500** (FIG. 5). In other embodiments, activity **402** can comprise one or more of and/or portions of one or more activities of method **500** (FIG. 5). In various embodiments, activity **402** can be performed without any part of method **500** (FIG. 5). In the embodiment of FIG. 4, the three orders from activity **401** are split into different numbers of totes—the first order has three totes; the second order has two totes; and the third order has a single tote.

(59) In many embodiments, method **400** can comprise an activity **403** of batching one or more totes. In some embodiments, activity **403** can comprise method **600** (FIG. 6). In other embodiments, activity **403** can comprise one or more and/or portions of one or more activities of method **600** (FIG. 6). In various embodiments, activity **403** can be performed without any part of method **600** (FIG. 6). In various embodiments, batching can comprise assigning one or more totes to one or more pickers for a pick walk, such that one or more pickers can be assigned to pick the respective items for any single order. In the embodiment of FIG. 4, the single tote of the third order is batched into a first picklist; two totes from the first order are batched into a second picklist; and a third tote from the first order and the two totes from the second order are batched into a third picklist.

(60) In many embodiments, method **400** can comprise an activity **404** facilitating displaying a picklist on an electronic device or store computer **360** (FIG. 3). In various embodiments, a picklist can comprise one or more totes for one or more orders. In some embodiments, a store computer can be carried by a picker during a pick walk. In these or other embodiments, a map of a store and/or a warehouse can be displayed, and the map can comprise directions for the pick walk. In various embodiments, directions for a pick walk can comprise turn by turn directions and/or a route overlaid or displayed on the map.

(61) In one embodiment, as illustrated in FIG. 4, a first pick list can be shown on a first store computer or electronic device for a first picker, and the first pick list can comprise the single tote for the third order. In this same embodiment of FIG. 4, a second pick list can be shown on a second store computer or electronic device for a second picker, and the second pick list can comprise two totes for the first order. Also in this same embodiment of FIG. 4, a third pick list can be shown on a third store computer or electronic device for a third picker, and the third pick list can comprise three totes—the third tote for the first order and the two totes for the second order. In this embodiment, a single picker is assigned to pick all of the items in the third order, and a different single picker is assigned to pick all of the items in the second order, and a third picker and the different single picker are assigned to pick the items in the first order.

(62) In a different embodiment, as also can be illustrated by FIG. 4, the three aforementioned pick lists can be transmitted to a single electronic device for a single picker, who is assigned to pick the first pick list first, and then the second pick list, and the third pick list. This different embodiment can be useful, for example, when there are time constraints for the third order to be picked before the first and second orders. In another embodiment, as also can be illustrated by FIG. 4, if the time constraints for the three orders do not impact the picking order for the pick lists, then the three aforementioned pick lists can be transmitted to a single electronic device for a single picker, who can pick the three pick lists in any order, as long as the single picker completely picks all of the items in one pick list before beginning to pick any items for the next pick list. Other embodiments also are possible.

(63) In many embodiments, after the items are picked for an order, activity **404** can further comprise displaying packing instructions on a store computer **360**. In these or other embodiments,

packing instructions can comprise directions on packing items of an order into one or more containers for receipt by a user, particularly when one or more of the items should be kept at one temperature (i.e., cold) while other items can be kept at a different temperature (i.e., room temperature). In various embodiments, an order and/or a portion of an order can be picked up by a user at a brick and mortar store. In these or other embodiments, an order and/or a portion of an order can be delivered to a user at one or more addresses.

(64) Turning ahead in the drawings, FIG. 5 illustrates a flow chart for a method **500**, according to an embodiment. Method **500** is merely exemplary and is not limited to the embodiments presented herein. Method **500** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the activities of method **500** can be performed in the order presented. In other embodiments, the activities of method **500** can be performed in any suitable order. In still other embodiments, one or more of the activities of method **500** can be combined or skipped. In many embodiments, system **300** (FIG. 3) can be suitable to perform method **500** and/or one or more of the activities of method **500**. In these or other embodiments, one or more of the activities of method **500** can be implemented as one or more computer instructions configured to run at one or more processing modules and configured to be stored at one or more non-transitory memory storage modules. Such non-transitory memory storage modules can be part of a computer system such as web server **310** and/or store computer **360** (FIG. 3). The processing module(s) can be similar or identical to the processing module(s) described above with respect to computer system **100** (FIG. 1).

(65) In many embodiments, method **500** can comprise an activity **501** of receiving a number of totes. In various embodiments, a number of totes can be determined using an order received in activity **401** (FIG. 4). In some embodiments, items in an order can be ordered by sequence ID, and totes comprising the items can be created using the sequence ID for each respective item. In some embodiments, a sequence ID can correspond with an items location in a warehouse and/or brick a mortar store. In many embodiments, items can be sorted, filtered, and/or ordered using a sequence ID. In these or other embodiments, items can be placed into totes using a sequence ID. In many embodiments, an a list of items can be placed sequentially into a tote using a sequence ID as forted, filtered, and/or ordered. In some embodiments, items can be place into a tote until a maximum weight capacity of a tote and/or a maximum volume capacity of a tote is reached and/or exceeded. In these or other embodiments, a new tote can be added to an order when a maximum weight capacity of a tote and/or a maximum volume capacity of a tote is reached and/or exceeded. In various embodiments, a number of totes can be determined by summing a number of totes added to an order. In some embodiments, a number of totes for an order can be received with an order in activity **501**. In these embodiments, a number of totes can be determined by an exogenous system. In various embodiments, a number of totes can be determined before or during activity **501**. In some embodiments, a number of totes can be determined in parallel with activity **501**.

(66) In many embodiments, method **500** can comprise an activity **502** of determining when a number of totes can be reduced. In some embodiments, a first set of rules can be used to determine when a number of totes can be reduced. In many embodiments, method **500** can optionally comprise an activity **503** of determining a theoretical minimum number of totes. In some embodiments, activity **503** can be performed after and/or as a part of activity **502**. In various embodiments, activity **503** can be performed entirely separate from activity **502**. In these or other embodiments, a first set of rules can comprise calculating a theoretical minimum number of totes for an order. In many embodiments, calculating a theoretical minimum number of totes can comprise calculating a total weight for an order using a weight of each item in the order. In these embodiments, a total weight for an order can then be divided by a maximum weight capacity of a tote to determine a theoretical minimum number of totes. In these or other embodiments, calculating a theoretical minimum number of totes can comprise calculating a total volume for an order using a volume of each item in the order. In these embodiments, a total volume for an order

can then be divided by a maximum volume capacity of a tote to determine a theoretical minimum number of totes. In some embodiments, a maximum weight capacity of a tote and/or a maximum volume capacity of a tote can comprise a Boolean value that indicates when a maximum weight capacity of a tote and/or a maximum volume capacity of a tote can be applied to an order and/or a tote within the order.

(67) In many embodiments, method **500** can further optionally comprise an activity **504** of comparing a theoretical minimum number of totes to the number of totes received in activity **501**. In some embodiments, activity **504** can be performed after and/or as a part of activity **502**. In various embodiments, activity **504** can be performed entirely separate from activity **502**. Activity **504** can be performed before or after activity **503**.

(68) In some embodiments, when a theoretical minimum number of totes is equal to the number of totes received, method **500** can terminate. In some embodiments, when method **500** has terminated, activity **404** (FIG. 4) can be then be performed by displaying the number of totes on a store computer **360** (FIG. 3) as part of a picklist, where the number of totes is as received in activity **501**, as returned after activity **507** (described below), or as returned from a previous iteration of an infeasible totes algorithm of activity **506** (described below). In many embodiments, when method **500** has terminated, all or a part of method **700** (FIG. 7) can be performed. In various embodiments, when a theoretical minimum number of totes is not equal to a number of totes, method **500** can continue, as explained in the following paragraphs.

(69) In many embodiments, method **500** can comprise an activity **505** of reducing a number of totes. In these or other embodiments, the number of totes can be received as described in activity **501**, and/or returned after activity **507**, as described below. In various embodiments, reducing a number of totes can comprise creating a reduced number of totes.

(70) In some embodiments, reducing a number of totes can comprise executing a greedy tote reduction algorithm using a maximum volume capacity of each tote of one or more totes. In various embodiments, a greedy algorithm can be configured to make a locally optimal choice at certain steps of an algorithm. In this way, a greedy algorithm can approximate and/or find a global optimum. In some embodiments, a greedy algorithm can approximate and/or find a globally optimal solution in a reasonable amount of time using a shorter (e.g. faster and/or with fewer burdens on a processor) and/or less data intensive process than traditional optimization algorithms. In many embodiments, a tote reduction algorithm can be greedy when the algorithm is configured to choose a locally optimal choice based on a weight of an item and/or a volume of an item. In many embodiments, a locally optimal choice can comprise choosing items of highest volume and/or weight first. In this way, a greedy tote reduction algorithm can approximate and/or find a globally optimal arrangement of items within totes. In these or other embodiments, a maximum volume capacity can be the same for each tote of the one or more totes. In some embodiments, the maximum volume capacity can be different, in which case a different greedy tote reduction algorithm can be used. In many embodiments, reducing a number of totes can comprise executing a greedy tote reduction algorithm using a maximum weight capacity of each tote of one or more totes. In these or other embodiments, a maximum weight capacity can be the same for each tote of the one or more totes. In some embodiments, the maximum weight capacity can be different, in which case a different greedy tote reduction algorithm can be used. In various embodiments, a greedy tote reduction algorithm can comprise an infeasible tote loop, as described in further detail below. In some embodiments, a reduced number of totes can be determined when an infeasible totes loop and/or a portion of an infeasible totes loop terminates. In these embodiments, a reduced number of totes, as determined via executing the greedy tote reduction algorithm and ending the infeasible totes loop, can be set as the number of totes for the order.

(71) Accordingly, in many embodiments, method **500** can optionally comprise an activity **506** of executing (i.e. running) an infeasible totes loop. In various embodiments, activity **506** can be performed as a part of and/or after activity **505**. In many embodiments, activity **506** can be

performed completely separate from activity **505**. In various embodiments, a second set of rules can comprise an infeasible totes loop. In various embodiments, an infeasible totes loop can be used to determine a reduced number of totes. In many embodiments, an infeasible tote loop can comprise all or a part of a set of instructions embodied in pseudocode shown in FIG. **6**. In some embodiments, an infeasible totes loop can comprise determining a theoretical number of totes, as described in activity **503**. In various embodiments, a theoretical minimum number of totes can be compared to the number of totes received or determined, as described above and below. For example, in these embodiments, the number of totes can be a number of totes received, as described in **501**. As another example, in other embodiments, the number of totes can be the number of totes as returned from a previous iteration of an infeasible totes algorithm or portions of an infeasible totes algorithm. As a further example, in these embodiments, the number of totes can be a number of totes, as returned after activity **507** (described below).

(72) In some embodiments, when a theoretical minimum number of totes is equal to a number of totes, an infeasible totes algorithm can terminate. In some embodiments, when the infeasible totes algorithm has terminated, activity **404** (FIG. **4**) can be then be performed by displaying the number of totes, as received or determined, as described above and below, on a store computer **360** (FIG. **3**) as part of a picklist. In many embodiments, when an infeasible totes algorithm has terminated, all or a part of method **700** (FIG. **7**) can be performed. In various embodiments, when a theoretical minimum number of totes is not equal to the number of totes, then the number of totes can be determined to be reducible.

(73) In many embodiments, an infeasible totes loop can proceed when a theoretical minimum number of totes is less than or equal to a number of totes, as received or determined. In these or other embodiments, an infeasible tote loop can comprise creating one or more infeasible totes using items in totes comprising the number of totes. In some embodiments, an infeasible tote can comprise a tote that cannot exist because it violates a maximum weight and/or maximum volume restriction (i.e. capacity) of the tote. In many embodiments, an infeasible tote can be created by adding items into a theoretical minimum number of totes. In these or other embodiments, an item (or an item of items remaining in an order) with a largest volume and/or a largest weight can be added first. In various embodiments, remaining items can be added to each tote of the theoretical minimum number of totes having a largest remaining volume capacity and/or a largest remaining weight capacity. In these or other embodiments, items can be added to a tote of the theoretical minimum number of totes until a last item added to the tote violates a maximum weight and/or maximum volume restriction of the tote. In these or other embodiments, an infeasible tote ratio can be determined for each tote created. In many embodiments, an infeasible tote ratio can comprise a sum of an unused ratio in weight, an overused ratio in weight, an unused ratio in volume, and/or an overused ratio in volume. In many embodiments, an unused and/or overused ratio in weight can be a ratio between a total weight of item(s) in the tote to a maximum weight of the tote. In these or other embodiments, an unused and/or overused ratio in volume can be a ratio between a total volume of item(s) in the tote to a maximum volume of the tote.

(74) In various embodiments, an infeasible tote loop can proceed by adding a heaviest item of an order to a tote having a smallest infeasible tote ratio. After doing so, if the items in the tote violate the maximum weight and/or maximum volume of the tote, then the infeasible loop can repeat by adding remaining heaviest items, one at a time, of the order to the tote until the tote is full (i.e., the maximum weight and/or maximum volume is reached) and/or until there are no more remaining items of the order to add to the tote. Then, a remaining tote having the second smallest infeasible tote ratio is filled by adding a remaining heaviest item of the order to the remaining tote. After doing so, if the items in the remaining tote violate the maximum weight and/or maximum volume of the remaining tote, then the infeasible loop can repeat again by adding remaining heaviest items, one at a time, of the order to the remaining tote until the remaining tote is full (i.e., the maximum weight and/or maximum volume is reached) and/or until there are no more remaining items of the

order to add to the remaining tote. This process is repeated until there are no more remaining items to add to a remaining tote.

(75) In many embodiments, an infeasible totes loop can comprise executing a large scale neighborhood search using infeasible tote ratios. In various embodiments, a neighborhood search can be configured to identify near-optimal and/or optimal solutions to an optimization problem by repeatedly transforming a current solution into a different solution in a neighborhood of a current solution. In some embodiments a neighborhood of a solution can comprise a set of similar solutions obtained by making modifications to an original solution. In many embodiments, a neighborhood search can be performed on a larger, and in some embodiments, exponentially sized neighborhood. In these embodiments, a large scale neighborhood search can outperform a neighborhood search because local improvements are larger, and therefore allows a neighborhood search to escape from a local minima to find a more optimal solution. In these or other embodiments, a large scale neighborhood search can comprise an item exhaustive large scale neighborhood search. In these or other embodiments, an item exhaustive search can determine most or all possible combinations of items that can be swapped between totes, thereby searching for a best swap. In many embodiments, an item exhaustive large scale neighborhood search can continue until no savings can be found and/or it reaches a maximum number of iterations.

(76) In many embodiments, a third set of rules can comprise an item exhaustive large scale neighborhood search. In some embodiments, an item exhaustive large scale neighborhood search can be referred to as a large scale neighborhood search. In these or other embodiments, a large scale neighborhood search can comprise determining when items can be swapped between two totes. In these or other embodiments, determining when items can be swapped can comprise selecting two items from two different totes. In various embodiments, all possible swaps for an order can be determined. In many embodiments, four infeasible tote ratios can be determined using the two items from two different totes. In various embodiments, the four infeasible tote ratios can be computed for the original two totes and modified two totes created by swapping the two items between the original two totes, where each of the four totes has a different one of the four infeasible tote ratios. In some embodiments, a savings of a swap can be determined using the four infeasible tote ratios. In these or other embodiments, a savings of a swap can be determined by subtracting a sum of the infeasible tote ratios of two totes created by swapping from a sum of the infeasible tote ratios of the two totes. In many embodiments, all possible swaps for an order can be determined. In some embodiments, swaps that create a negative savings can be discarded and/or filtered out. In embodiments where all swaps create a negative savings, an infeasible loop can be terminated. In some embodiments, when an infeasible totes algorithm has terminated, activity **404** (FIG. 4) can be then be performed by displaying the number of totes, as received or determined, as described herein, on a store computer **360** (FIG. 3) as part of a picklist. In various embodiments, when an infeasible totes algorithm has terminated, all or a part of method **700** (FIG. 7) can be performed.

(77) In many embodiments, swaps that create a positive savings (or a list of all swaps when discarding/filtering is not performed) can be sorted from most savings to least savings. In these or other embodiments, a swap with a highest savings can be made. In some embodiments, each tote in a large scale neighborhood search can have only one swap performed using it. In various embodiments, a large scale neighborhood search can proceed by determining when a tote in the large scale neighborhood search violates a maximum weight and/or maximum volume restriction of a tote. In many embodiments, when no totes in a large scale neighborhood search violate a maximum weight and/or maximum volume restriction of a tote, an infeasible totes algorithm can terminate. In some embodiments, when an infeasible totes algorithm has terminated, activity **404** (FIG. 4) can be then be performed by displaying, an electronic device to the picker, the number of totes, as received or determined, as described herein. In various embodiments, when an infeasible totes algorithm has terminated, all or a part of method **700** (FIG. 7) can be performed. In

embodiments where one or more totes in a large scale neighborhood search violate a maximum weight and/or maximum volume restriction of a tote (e.g., when a swap cannot be made), a number of totes used in all or a portion of an infeasible totes loop can be increased, and the infeasible totes loop can be repeated until all totes adhere to the maximum weight and maximum volume restriction of the tote.

(78) Returning now to FIG. 5, in many embodiments, method **500** can comprise an activity **507** of comparing a number of totes to a reduced number of totes. In some embodiments, when a reduced number of totes is equal to the number of totes for an order, method **500** can be completed, and activity **404** (FIG. 4) can be performed by displaying, on an electronic device to a picker, the number of totes of the order or as returned or determined, as described herein. In many embodiments, all or a part of method **700** (FIG. 7) can be performed when a reduced number of totes is equal to a number of totes for an order. In embodiments where a reduced number of totes for the order is not equal to (or is less than) the previously calculated number of totes for the order, then, totes of the reduced number of totes can be set to be the number of totes of the order, and all or portions (i.e., at least activities **505** and **507**) of method **500** can be performed again to further reduce the number of totes for the order.

(79) Turning ahead in the drawings, FIG. 7 illustrates a flow chart for a method **700**, according to an embodiment. Method **700** is merely exemplary and is not limited to the embodiments presented herein. Method **700** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the activities of method **700** can be performed in the order presented. In other embodiments, the activities of method **700** can be performed in any suitable order. In still other embodiments, one or more of the activities of method **700** can be combined or skipped. In many embodiments, system **300** (FIG. 3) can be suitable to perform method **700** and/or one or more of the activities of method **700**. In these or other embodiments, one or more of the activities of method **700** can be implemented as one or more computer instructions configured to run at one or more processing modules and configured to be stored at one or more non-transitory memory storage modules. Such non-transitory memory storage modules can be part of a computer system such as web server **310** and/or store computer **360** (FIG. 3). The processing module(s) can be similar or identical to the processing module(s) described above with respect to computer system **100** (FIG. 1). In some embodiments, all or a portion of method **700** can be performed after method **500** (FIG. 5). In various embodiments, all or portions of method **700** can be performed independently of method **500** (FIG. 5).

(80) In many embodiments, method **700** can comprise an activity **701** of executing a randomized greedy incremental batcher loop. In some embodiments, a randomized greedy incremental batcher loop can be configured to identify and/or perform a merge when the merge results in a maximum savings (thereby selecting a locally optimal solution). In these or other embodiments, executing a randomized greedy incremental batcher loop can comprise performing activities **702-703**. In various embodiments, activities **702-703** can be performed without executing a randomized greedy incremental batcher loop. In many embodiments, a randomized greedy incremental batcher loop can comprise all or a part of a set of instructions embodied in pseudocode shown in FIG. 8.

(81) Returning now to FIG. 7, in many embodiments, method **700** can comprise an activity **702** of selecting a first picklist. In some embodiments, a first picklist can be received with one or more picklists. In these or other embodiments, one or more picklists can have been generated using all or a part of activity **401** (FIG. 4), all or a part of activity **402** (FIG. 4), and/or all or a part of method **500** (FIG. 5). In many embodiments, selecting a first picklist can comprise receiving one or more totes. In these or other embodiments, each tote can be assigned to one or more picklists. In various embodiments, only one tote can be assigned to each of one or more picklists. In many embodiments, each picklist can have its own cost calculated for it. In various embodiments, a cost can function as a proxy for an approximate amount of time it will take a picker to pick a picklist. In these or other embodiments, a cost can be calculated by summing a total walk time of a pick, a total

turn time of a pick, a total line time of a pick, a total processing time of a pick, and/or a total setup time of a pick. In some embodiments, a total walk time of a pick can comprise an amount of time a picker performing the pick is predicted to be walking. In many embodiments, a total turn time of a pick can comprise an amount of time a picker performing the pick is predicted to be turning while walking to pick the next item. In these or other embodiments, a total line time of a pick can comprise an amount of time a picker performing the pick is predicted to be standing in line waiting at the deli counter, the meat counter, the seafood counter, the bakery, the checkout line, etc. If the picking is performed in a retail store (and not in a warehouse), the total line time can vary depending on the time of day and how busy the store is during that time of day. In various embodiments, a total processing time of a pick can comprise an amount of time a picker performing the pick is predicted to be scanning and packing items of the pick. In the same or different embodiments a total setup time of a pick can comprise an amount of time a picker performing the pick is predicted to be setting up, labeling, and/or packing one or more totes of the pick.

(82) In many embodiments, one or more picklists can be sorted by cost. In these or other embodiments, a picklist with a lowest cost can be selected, and a remainder of one or more picklists can be retained. In various embodiments, one or more potential mergers between a picklist with a lowest cost and a remainder of one or more picklists can be determined in an activity **703** of method **700**. In the same or different embodiments, a cost can be calculated for each of one or more potential mergers as described above. In many embodiments, a savings for each of one or more potential mergers can be calculated using a cost for each of one or more potential mergers and a cost of a picklist with a lowest cost. In these or other embodiments, a savings can be calculated by subtracting a cost of a picklist with a lowest cost from a cost of each of one or more potential mergers. In some embodiments, a negative savings can be a proxy for an inefficient merge, and/or a positive savings can be a proxy for an efficient merge. In many embodiments, a merger of one or more potential merger having a highest savings can be selected. In various embodiments, a merger having a highest savings can be set to be and/or used as a picklist with a lowest cost, and the aforementioned merging algorithm can be performed again using the merger having the highest savings and a remainder of one or more picklists having not been merged.

(83) In embodiments where savings for all mergers are negative, the most recent round of potential mergers can be unmerged or deleted, thereby leaving a picklist with a lowest cost and a remainder of one or more picklists. In some embodiments, the picklist with a lowest cost can comprise a merged picklist. In these or other embodiments, a picklist with the lowest cost can then be retained, and a greedy incremental batcher loop can be repeated using the remainder of one or more picklists. In many embodiments, a greedy incremental batcher loop can terminate when only one picklist remains in a remainder of one or more picklists.

(84) In many embodiments, method **700** can comprise an activity **704** of executing a randomized tote local search loop. In some embodiments, a randomized tote local search loop can be configured to move from solution to solution in a space of candidate solutions (e.g., the search space) by applying local changes, until a solution deemed optimal is found or a time bound (e.g., a maximum number of iterations) has elapsed. In these or other embodiments, executing a randomized tote local search loop can comprise performing activities **705-706**. In various embodiments, activities **705-706** can be performed without executing a randomized tote local search loop. In many embodiments, a randomized tote local search loop can comprise all or a part of a set of instructions embodied in pseudocode shown in FIG. **9**.

(85) Returning now to FIG. **7**, in many embodiments, method **700** can comprise an activity **705** of selecting two random picklists of one or more picklists. In some embodiments, two random picklists can comprise one or more merged picklists, as created by at least a portion of a randomized greedy incremental batcher loop. In these or other embodiments, a first random picklist can be randomly selected using a weighted technique. In the same or different embodiments, a

weighted technique can be configured to weight a randomness of a selection of a first random picklist towards selecting a most expensive picklist of one or more picklists. In these or other embodiments, a randomness of a selection of a first random picklist can be determined using a roulette wheel selection algorithm. In many embodiments, a roulette wheel selection algorithm can be weighted by an average tote cost per picklist of one or more picklists. In many embodiments, an average tote cost per picklist can be determined by summing a cost of each tote, and then dividing by a number of totes in a picklist. In some embodiments, a second random picklist can be randomly selected using a heuristic that approximates true randomness. In these or other embodiments, a randomness of a selection of a second random picklist can be unweighted. In various embodiments, a picklist can comprise one or more totes. In these or other embodiments, totes in a first random picklist can be assigned an index number having a maximum value comprising a maximum number of totes. In various embodiments, a maximum number of totes can be determined via a carrying capacity of a cart.

(86) In many embodiments, method **700** can comprise an activity **706** of swapping totes of two random picklists when the swapping would save a cost. In some embodiments, swapping totes of two random picklists can comprise randomly picking an index number for a first random tote and picking an index number for a second random tote. In many embodiments, a randomly picked index number can have a maximum value of a maximum number of totes. In various embodiments, an index number for a first random tote and an index number for a second random tote are both assigned to totes in a random picklist. In these embodiments, a two-way swap can be performed. In the same or different embodiments, a two-way swap can comprise swapping a first random tote and a second random tote between their respective random picklists. In many embodiments, only one index number of the index numbers for the first random tote and the second random tote are assigned to a tote in a random picklist. In these embodiments, a one-way swap can be performed. In various embodiments, a one-way swap can comprise moving the tote from the random picklist to the other random picklist. In many embodiments, a cost savings can be determined between a random picklist having been swapped and a first random picklist, as selected above. In various embodiments, a cost savings can comprise a cost of a picklist after a swap minus a cost of a picklist prior to a swap. In embodiments where the cost savings is positive (e.g., when swapping would decrease a cost of at least one random picklist of two random picklists), the resulting picklists after the swap can be re-incorporated into the one or more picklists, and all or a portion of a randomized tote local search loop can be repeated. In embodiments wherein the cost savings is negative (e.g., when swapping would increase a cost of at least one random picklist of two random picklists), swaps can be undone and/or swapped picklists can be deleted, and at least a portion of a randomized tote local search loop can be repeated. In some embodiments where a cost savings is positive, resulting picklists the swap can be checked for one or more business conditions. In various embodiments, one or more business conditions can comprise a maximum volume capacity of a tote, a maximum weight capacity of a tote, and/or a maximum tote capacity of a trolley. In embodiments where a business condition is violated, swaps can be undone and/or swapped picklists can be deleted, and at least a portion of a randomized tote local search loop can be repeated. In these or other embodiments, a randomized tote local search loop can be repeated a predetermined number of iterations before terminating. In some embodiments, a predetermined number of iterations can be set by an administrator of system **300** (FIG. 3).

(87) In many embodiments, method **700** can comprise an activity **707** of executing an update min trolley loop. In these or other embodiments, executing an update min trolley loop can comprise performing activities **708-709**. In various embodiments, activities **708-709** can be performed without executing an update min trolley loop. In many embodiments, an update min trolley loop can comprise all or a part of a set of instructions embodied in pseudocode shown in FIG. 10.

(88) Returning now to FIG. 7, in many embodiments, method **700** can comprise an activity **708** of selecting a shortest picklist of one or more picklists. In some embodiments, one or more picklists

can comprise at least one picklist as swapped by at least a portion of a randomized tote local search loop. In various embodiments, a randomized tote local search loop can comprise a greedy algorithm. In these or other embodiments, a shortest picklist can comprise a last picklist leftover after performing a one-way swap as described in activity **706**. In many embodiments, a number of totes in a shortest picklist can be compared to a maximum number of totes. In embodiments where a number of totes in a shortest picklist is equal to a maximum number of totes, an update min trolley loop can be terminated. In some embodiments, activity **404** (FIG. **4**) can be performed after an update min trolley loop is terminated by displaying a number of totes of a shortest picklist and a remainder of one or more picklists on a store computer **360** (FIG. **3**) as part of a picklist. In embodiments where a number of totes in a shortest picklist is less than a maximum number of totes, one or more best totes of one or more remaining totes can be determined. In some embodiments, one or more best totes can be determined by executing an add totes to min trolley loop. In some embodiments, an add totes to min trolley loop can comprise executing a local search. In these or other embodiments, executing a randomized tote local search loop can comprise performing activity **709**. In various embodiments, activity **709** can be performed without executing an add totes to min trolley loop. In many embodiments, an add totes to min trolley loop can comprise all or a part of a set of instructions embodied in pseudocode shown in FIG. **11**

(89) Returning now to FIG. **7**, in many embodiments, method **700** can comprise an activity **709** of combining a shortest picklist with at least one picklist when the combining would save a cost. In some embodiments, a cost savings can be determined by subtracting a cost of picklists pre-merger (a sum of a cost of all totes in a picklist) with cost of picklists post-merger. In many embodiments, a tote with a highest savings can be selected, and the tote with the highest savings can be removed from its picklist and added to a shortest picklist to create a combination picklist. In various embodiments, an add totes to min trolley loop can be repeated until no more savings can be found and/or the combination picklist reaches a maximum number of totes.

(90) In many embodiments, method **700** can comprise an activity **710** of facilitating displaying a combination picklist to a picker. In many embodiments, a combination picklist can be displayed with one or more other picklists created and/or used in method **700**. In some embodiments, activity **710** can be performed as a part of and/or in addition to activity **404** (FIG. **4**). In these or other embodiments, activity **710** can be performed without activity **404** (FIG. **4**). In many embodiments, facilitating displaying a combination picklist to a picker can comprise displaying a number of totes on a store computer **360** (FIG. **3**) as part of a picklist.

(91) Turning ahead in the drawings, FIG. **12** illustrates a block diagram of a system **1200** that can be employed for behavior based messaging. System **1200** is merely exemplary and embodiments of the system are not limited to the embodiments presented herein. System **1200** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements or modules of system **1200** can perform various procedures, processes, and/or activities. In these or other embodiments, the procedures, processes, and/or activities can be performed by other suitable elements or modules of system **1200**.

(92) Generally, therefore, system **1200** can be implemented with hardware and/or software, as described herein. In some embodiments, part or all of the hardware and/or software can be conventional, while in these or other embodiments, part or all of the hardware and/or software can be customized (e.g., optimized) for implementing part or all of the functionality of system **1200** described herein.

(93) In many embodiments, system **1200** can comprise non-transitory memory storage module **1201**. Memory storage module **1201** can be referred to as number of totes receiving module **1201**. In many embodiments, number of totes receiving module **1201** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **500** (FIG. **5**) (e.g., activity **501** (FIG. **5**)).

(94) In many embodiments, system **1200** can comprise non-transitory memory storage module

1202. Memory storage module **1202** can be referred to as reduction determining module **1202**. In many embodiments, reduction determining module **1202** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **500** (FIG. 5) (e.g., activity **502** (FIG. 5)).

(95) In many embodiments, system **1200** can comprise non-transitory memory storage module **1203**. Memory storage module **1203** can be referred to as minimum number of totes determining module **1203**. In many embodiments, minimum number of totes determining module **1203** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **500** (FIG. 5) (e.g., activity **503** (FIG. 5)).

(96) In many embodiments, system **1200** can comprise non-transitory memory storage module **1204**. Memory storage module **1204** can be referred to as theoretical minimum comparing module **1204**. In many embodiments, theoretical minimum comparing module **1204** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **500** (FIG. 5) (e.g., activity **505** (FIG. 5)).

(97) In many embodiments, system **1200** can comprise non-transitory memory storage module **1205**. Memory storage module **1205** can be referred to as tote reducing module **1205**. In many embodiments, tote reducing module **1205** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **500** (FIG. 5) (e.g., activity **505** (FIG. 5)).

(98) In many embodiments, system **1200** can comprise non-transitory memory storage module **1206**. Memory storage module **1206** can be referred to as infeasible totes loop executing module **1206**. In many embodiments, infeasible totes loop executing module **1206** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **500** (FIG. 5) (e.g., activity **506** (FIG. 5)).

(99) In many embodiments, system **1200** can comprise non-transitory memory storage module **1207**. Memory storage module **1207** can be referred to as number of totes comparing module **1207**. In many embodiments, number of totes comparing module **1207** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **500** (FIG. 5) (e.g., activity **507** (FIG. 5)).

(100) Turning ahead in the drawings, FIG. **13** illustrates a block diagram of a system **1300** that can be employed for behavior based messaging. System **1300** is merely exemplary and embodiments of the system are not limited to the embodiments presented herein. System **1300** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements or modules of system **1300** can perform various procedures, processes, and/or activities. In these or other embodiments, the procedures, processes, and/or activities can be performed by other suitable elements or modules of system **1300**.

(101) Generally, therefore, system **1300** can be implemented with hardware and/or software, as described herein. In some embodiments, part or all of the hardware and/or software can be conventional, while in these or other embodiments, part or all of the hardware and/or software can be customized (e.g., optimized) for implementing part or all of the functionality of system **1300** described herein.

(102) In many embodiments, system **1300** can comprise non-transitory memory storage module **1301**. Memory storage module **1301** can be referred to as randomized greedy incremental batcher module **1301**. In many embodiments, randomized greedy incremental batcher module **1301** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **701** (FIG. 7)).

(103) In many embodiments, system **1300** can comprise non-transitory memory storage module **1302**. Memory storage module **1302** can be referred to as picklist selecting module **1302**. In many embodiments, picklist selecting module **1302** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g.,

activity **702** (FIG. 7)).

(104) In many embodiments, system **1300** can comprise non-transitory memory storage module **1303**. Memory storage module **1303** can be referred to as picklist merging module **1303**. In many embodiments, picklist merging module **1303** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **703** (FIG. 7)).

(105) In many embodiments, system **1300** can comprise non-transitory memory storage module **1304**. Memory storage module **1304** can be referred to as randomized tote local search executing module **1304**. In many embodiments, randomized tote local search executing module **1304** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **704** (FIG. 7)).

(106) In many embodiments, system **1300** can comprise non-transitory memory storage module **1305**. Memory storage module **1305** can be referred to as random picklist selecting module **1305**. In many embodiments, random picklist selecting module **1305** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **705** (FIG. 7)).

(107) In many embodiments, system **1300** can comprise non-transitory memory storage module **1306**. Memory storage module **1306** can be referred to as tote swapping module **1306**. In many embodiments, tote swapping module **1306** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **706** (FIG. 7)).

(108) In many embodiments, system **1300** can comprise non-transitory memory storage module **1307**. Memory storage module **1307** can be referred to as update min trolley loop executing module **1307**. In many embodiments, update min trolley loop executing module **1307** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **707** (FIG. 7)).

(109) In many embodiments, system **1300** can comprise non-transitory memory storage module **1308**. Memory storage module **1308** can be referred to as shortest picklist selection module **1308**. In many embodiments, shortest picklist selection module **1308** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **708** (FIG. 7)).

(110) In many embodiments, system **1300** can comprise non-transitory memory storage module **1309**. Memory storage module **1309** can be referred to as shortest picklist combining module **1309**. In many embodiments, shortest picklist combining module **1309** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **709** (FIG. 7)).

(111) In many embodiments, system **1300** can comprise non-transitory memory storage module **1310**. Memory storage module **1310** can be referred to as display facilitating module **1310**. In many embodiments, display facilitating module **1310** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **700** (FIG. 7) (e.g., activity **710** (FIG. 7)).

(112) Turning ahead in the drawings, FIG. **14** illustrates a block diagram of a system **1400** that can be employed for behavior based messaging. System **1400** is merely exemplary and embodiments of the system are not limited to the embodiments presented herein. System **1400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements or modules of system **1400** can perform various procedures, processes, and/or activities. In these or other embodiments, the procedures, processes, and/or activities can be performed by other suitable elements or modules of system **1400**.

(113) Generally, therefore, system **1400** can be implemented with hardware and/or software, as described herein. In some embodiments, part or all of the hardware and/or software can be

conventional, while in these or other embodiments, part or all of the hardware and/or software can be customized (e.g., optimized) for implementing part or all of the functionality of system **1400** described herein.

(114) In many embodiments, system **1400** can comprise non-transitory memory storage module **1401**. Memory storage module **1401** can be referred to as order receiving module **1401**. In many embodiments, order receiving module **1401** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **400** (FIG. **4**) (e.g., activity **401** (FIG. **4**)).

(115) In many embodiments, system **1400** can comprise non-transitory memory storage module **1402**. Memory storage module **1402** can be referred to as order splitting module **1402**. In many embodiments, order splitting module **1402** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **400** (FIG. **4**) (e.g., activity **402** (FIG. **4**)).

(116) In many embodiments, system **1400** can comprise non-transitory memory storage module **1403**. Memory storage module **1403** can be referred to as tote batching module **1403**. In many embodiments, tote batching module **1403** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **400** (FIG. **4**) (e.g., activity **403** (FIG. **4**)).

(117) In many embodiments, system **1400** can comprise non-transitory memory storage module **1404**. Memory storage module **1404** can be referred to as display of picklist facilitating module **1404**. In many embodiments, display of picklist facilitating module **1404** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **400** (FIG. **4**) (e.g., activity **404** (FIG. **4**)).

(118) Although systems and methods for optimization of pick walks have been described with reference to specific embodiments, it will be understood by those skilled in the art that various changes may be made without departing from the spirit or scope of the disclosure. Accordingly, the disclosure of embodiments is intended to be illustrative of the scope of the disclosure and is not intended to be limiting. It is intended that the scope of the disclosure shall be limited only to the extent required by the appended claims. For example, to one of ordinary skill in the art, it will be readily apparent that any element of FIGS. **1-12** may be modified, and that the foregoing discussion of certain of these embodiments does not necessarily represent a complete description of all possible embodiments. For example, one or more of the procedures, processes, or activities of FIGS. **4, 5**, and/or **7** may include different procedures, processes, and/or activities and be performed by many different modules, in many different orders.

(119) All elements claimed in any particular claim are essential to the embodiment claimed in that particular claim. Consequently, replacement of one or more claimed elements constitutes reconstruction and not repair. Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be construed as critical, required, or essential features or elements of any or all of the claims, unless such benefits, advantages, solutions, or elements are stated in such claim.

(120) Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

Claims

1. A system comprising: one or more processors; and one or more non-transitory computer-readable media storing computing instructions that, when executed on the one or more processors, cause the one or more processors to perform operations comprising: determining that a respective number of totes for a respective order of one or more orders can be reduced; reducing the respective number of totes for the respective order by using an infeasible totes loop that executes a large scale neighborhood search comprising: performing an item exhaustive search to determine combinations of items swapped between the respective number of totes for the respective order to find a more optimal allocation of totes; calculating savings for potential swaps based on constraints including maximum weight and volume; and iteratively executing swaps of the potential swaps that provide positive savings to adjust the respective number of totes based on the constraints until no further positive savings are found or a predefined number of iterations is reached, resulting in an optimized number of totes; when the optimized number of totes is determined, displaying, on an electronic device of a picker, the optimized number of totes; generating directions for a route of a pick walk based on a map of a retail facility, wherein the pick walk comprises a picklist comprising the respective number of totes for the respective order; and facilitating displaying, on the electronic device, the route of the pick walk on the map of the retail facility, wherein the display includes turn-by-turn directions for the pick walk.
2. The system of claim 1, wherein determining that the respective number of totes for the respective order of the one or more orders can be reduced comprises: determining a theoretical minimum number of totes for the respective order; comparing the theoretical minimum number of totes for the respective order with the respective number of totes; and when the theoretical minimum number of totes for the respective order is less than the respective number of totes, determining that the respective number of totes can be reduced.
3. The system of claim 2, wherein determining the theoretical minimum number of totes for the respective order comprises: calculating a respective total volume for items in the respective order; and dividing the respective total volume for the items in the respective order by a maximum volume capacity for each tote.
4. The system of claim 2, wherein determining the theoretical minimum number of totes for the respective order comprises: calculating a respective total weight for items in the respective order; and dividing the respective total weight for the items in the respective order by a maximum weight capacity for each tote.
5. The system of claim 1, wherein the computing instructions, when executed on the one or more processors, further cause the one or more processors to perform the operations comprising: creating one or more infeasible totes using items in the respective number of totes for the respective order; determining a respective infeasible tote ratio for each of the one or more infeasible totes; and when a first respective item in a first respective tote for the respective order cannot be swapped with a second respective item in a second respective tote for the respective order, increasing a minimum number of totes for the respective order by one tote.
6. The system of claim 5, wherein the computing instructions, when executed on the one or more processors, further cause the one or more processors to perform functions comprising: repeating: (1) determining whether the first respective item in the first respective tote for the respective order cannot be swapped with the second respective item in the second respective tote for the respective order and (2) increasing the minimum number of totes for the respective order by one tote; until the first respective item in the first respective tote for the respective order can be swapped with the second respective item in the second respective tote for the respective order; and setting the optimized number of totes for the respective order as a current number of totes for the respective order when the first respective item in the first respective tote for the respective order can be swapped with the second respective item in the second respective tote for the respective order.
7. The system of claim 5, wherein the computing instructions, when executed on the one or more

processors, further cause the one or more processors to perform functions comprising: determining, using two or more infeasible tote ratios, a savings metric for each swap of items between the respective number of totes; and terminating the infeasible totes loop when all swaps of the items provide no further positive savings.

8. The system of claim 1, wherein the computing instructions, when executed on the one or more processors, further cause the one or more processors to perform the operations comprising at least one of: executing a greedy tote reduction algorithm using a maximum volume capacity of each tote of totes for the respective order; or executing a greedy tote reduction algorithm using a maximum weight capacity of each tote of totes for the respective order.

9. The system of claim 1, wherein the computing instructions, when executed on the one or more processors, further cause the one or more processors to perform functions comprising: when the optimized number of totes is unequal to further optimized number of totes: reducing the optimized number of totes to a respective further optimized number of totes for the respective order; comparing the optimized number of totes to further optimized number of totes for the respective order; and when the optimized number of totes for the respective order is equal to further optimized number of totes for the respective order: displaying, on the electronic device, the optimized number of totes for the respective order.

10. The system of claim 1, wherein the electronic device is carried by the picker who travels the route of the pick walk to select items in the picklist.

11. A method being implemented via execution of computing instructions configured to run on one or more processors stored on one or more non-transitory computer-readable media, the method comprising: determining that a respective number of totes for a respective order of one or more orders can be reduced; reducing the respective number of totes for the respective order by using an infeasible totes loop that executes a large scale neighborhood search, comprising: performing an item exhaustive search to determine combinations of items swapped between the respective number of totes for the respective order to find a more optimal allocation of totes; calculating savings for potential swaps based on constraints including maximum weight and volume; and iteratively executing swaps of the potential swaps that provide positive savings to adjust the respective number of totes based on the constraints until no further positive savings are found or a predefined number of iterations is reached, resulting in an optimized number of totes; when the optimized number of the totes is determined, displaying, on an electronic device of a picker, the optimized number of totes; generating directions for a route of a pick walk based on a map of a retail facility, wherein the pick walk comprises a picklist comprising the respective number of totes for the respective order; and facilitating displaying, on the electronic device, the route of the pick walk on the map of the retail facility, wherein the display includes turn-by-turn directions for the pick walk.

12. The method of claim 11, wherein determining that the respective number of totes for the respective order of the one or more orders can be reduced comprises: determining a theoretical minimum number of totes for the respective order; comparing the theoretical minimum number of totes for the respective order with the respective number of totes; and when the theoretical minimum number of totes for the respective order is less than the respective number of totes, determining that the respective number of totes can be reduced.

13. The method of claim 12, wherein determining the theoretical minimum number of totes for the respective order comprises: calculating a respective total volume for items in the respective order; and dividing the respective total volume for the items in the respective order by a maximum volume capacity for each tote.

14. The method of claim 12, wherein determining the theoretical minimum number of totes for the respective order comprises: calculating a respective total weight for items in the respective order; and dividing the respective total weight for the items in the respective order by a maximum weight capacity for each tote.

15. The method of claim 11 further comprising: creating one or more infeasible totes using items in

the respective number of totes for the respective order; determining a respective infeasible tote ratio for each of the one or more infeasible totes; and when a first respective item in a first respective tote for the respective order cannot be swapped with a second respective item in a second respective tote for the respective order, increasing a minimum number of totes for the respective order by one tote.

16. The method of claim 15 further comprising: repeating: (1) determining whether the first respective item in the first respective tote for the respective order cannot be swapped with the second respective item in the second respective tote for the respective order and (2) increasing the minimum number of totes for the respective order by one tote; until the first respective item in the first respective tote for the respective order can be swapped with the second respective item in the second respective tote for the respective order; and setting the optimized number of totes for the respective order as a current number of totes for the respective order when the first respective item in the first respective tote for the respective order can be swapped with the second respective item in the second respective tote for the respective order.

17. The method of claim 15 further comprising: determining, using two or more infeasible tote ratios, a savings metric for each swap of the items between the respective number of totes; and terminating the infeasible totes loop when all swaps of the items provide no further positive savings.

18. The method of claim 11 further comprising at least one of: executing a greedy tote reduction algorithm using a maximum volume capacity of each tote of totes for the respective order; or executing a greedy tote reduction algorithm using a maximum weight capacity of each tote of totes for the respective order.

19. The method of claim 11 further comprising: when the respective number of totes for the respective order is unequal to the optimized number of totes for the respective order: reducing the optimized number of totes for the respective order to a respective further reduced number of totes for the respective order of the one or more orders; comparing the optimized number of totes for the respective order to the respective further reduced number of totes for the respective order; and when the optimized number of totes for the respective order is equal to the respective further reduced number of totes for the respective order: displaying, on the electronic device, the optimized number of totes for the respective order.

20. A non-transitory computer-readable medium storing instructions, wherein the instructions, upon execution by a processor, cause the processor to perform operations comprising: determining that a respective number of totes for a respective order of one or more orders can be reduced; reducing the respective number of totes for the respective order by using an infeasible totes loop that executes a large scale neighborhood search comprising: performing an item exhaustive search to determine combinations of items swapped between the respective number of totes for the respective order to find a more optimal allocation of totes; calculating savings for potential swaps based on constraints including maximum weight and volume; and iteratively executing swaps of the potential swaps that provide positive savings to adjust the respective number of totes based on the constraints until no further positive savings are found or a predefined number of iterations is reached, resulting in an optimized number of totes; when the optimized number of totes is determined, displaying, on an electronic device of a picker, the optimized number of totes; generating directions for a route of a pick walk based on a map of a retail facility, wherein the pick walk comprises a picklist comprising the respective number of totes for the respective order; and facilitating displaying, on the electronic device, the route of the pick walk on the map of the retail facility, wherein the display includes turn-by-turn directions for the pick walk.
