

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12400345
B2
August 26, 2025
Jung; Hong et al.

Method and device for matching three-dimensional oral scan data via deep-learning based 3D feature detection

Abstract

Disclosed is a three-dimensional oral scan data matching device including a matching unit, a deep-learning unit, a scanned frame feature determination unit, and a scan data re-matching unit. The matching unit matches a plurality of scanned frames to generate a full mouth image. The deep-learning unit performs deep-learning to detect a feature of the full mouth image. The scanned frame feature determination unit determines a feature of the plurality of scanned frames by utilizing the feature of the full mouth image. The scan data re-matching unit re-matches the plurality of scanned frames on the basis of the feature of the plurality of scanned frames, to reconstruct a three-dimensional oral model.

Inventors:	Jung; Hong (Seoul, KR), Lee; Sung Min (Bucheon-si, KR), Song; Bo Hyun (Seoul, KR)
Applicant:	HDX WILL CORP. (Seoul, KR)
Family ID:	1000008778276
Assignee:	HDX WILL CORP. (Seoul, KR)
Appl. No.:	18/261433
Filed (or PCT Filed):	January 13, 2022
PCT No.:	PCT/KR2022/000653
PCT Pub. No.:	WO2022/154523
PCT Pub. Date:	July 21, 2022

Prior Publication Data

Document Identifier

US 20240070882 A1

Publication Date

Feb. 29, 2024

Foreign Application Priority Data

KR

10-2021-0006549

Jan. 18, 2021

Publication Classification

Int. Cl.: **G06T7/33** (20170101); **A61C9/00** (20060101); **G06T7/593** (20170101); **G06T11/00** (20060101)

U.S. Cl.:

CPC **G06T7/33** (20170101); **A61C9/0046** (20130101); **G06T7/593** (20170101); **G06T11/00** (20130101); G06T2200/04 (20130101); G06T2207/10012 (20130101); G06T2207/20081 (20130101); G06T2207/30036 (20130101)

Field of Classification Search

CPC: G06T (7/33); G06T (7/593); G06T (11/00); G06T (2200/04); G06T (2207/10012); G06T (2207/20081); G06T (2207/30036); G06T (17/00); A61C (9/0046); A61C (9/0053); A61B (5/0088); A61B (5/7264)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2005/0089213	12/2004	Geng	N/A	N/A
2006/0263739	12/2005	Sporbert	433/213	A61C 9/0053
2018/0028065	12/2017	Elbaz	N/A	H04N 13/221
2018/0028294	12/2017	Azernikov	N/A	G06F 18/24143
2020/0005552	12/2019	Furst	N/A	G06T 7/344
2020/0085546	12/2019	Li	N/A	A61C 7/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019162426	12/2018	JP	N/A
101911327	12/2017	KR	N/A
102056480	12/2019	KR	N/A
20200100448	12/2019	KR	N/A
20210000942	12/2020	KR	N/A
102310662	12/2020	KR	N/A

OTHER PUBLICATIONS

International Search Report issued in International application No. PCT/KR2022/000653 dated May 4, 2022 (3 pages). cited by applicant

Primary Examiner: McDowell, Jr.; Maurice L.

Attorney, Agent or Firm: Osha Bergman Watanabe & Burton LLP

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a method and device for matching three-dimensional (3D) intraoral scan data through deep learning-based 3D feature point detection.

BACKGROUND ART

(2) In order to generate three-dimensional (3D) intraoral scan data from an intraoral scanner, a process of scanning an oral cavity of a patient with a scanner and matching (registration) point clouds generated for each frame into one frame in three dimensions is required. There is an iterative closest point (ICP) algorithm that is widely used for matching of point clouds. In the existing method, even when a matching error between frames of one frame pair is small, geometric distortion occurs in a finally reconstructed 3D oral cavity model due to accumulated errors.

RELATED ART DOCUMENT

Patent Document

(3) (Patent Document 1) Korean Patent Registration No. 10-1911327

DISCLOSURE

Technical Problem

(4) The present invention is directed to providing a method and device for matching three-dimensional (3D) intraoral scan data that can reduce geometric distortion.

Technical Solution

(5) One aspect of the present invention provides a method of matching three-dimensional (3D) intraoral scan data, which includes matching a plurality of scanned frames and generating a full mouth image; detecting feature points of the full mouth image by performing deep learning; determining feature points of the plurality of scanned frames using the feature points of the full mouth image; and re-matching the plurality of scanned frames on the basis of the feature points of the plurality of scanned frames and reconstructing a 3D oral cavity model.

(6) The determining of the feature points of the plurality of scanned frames using the feature points of the full mouth image may include generating a virtual frame from the full mouth image, projecting the feature points of the full mouth image onto the virtual frame and determining feature points of the virtual frame, and determining the feature points of the plurality of scanned frames using the feature points of the virtual frame.

(7) The determining of the feature points of the plurality of scanned frames using the feature points of the virtual frame may include generating a first patch image having a predetermined size around a feature point of the virtual frame, selecting a second patch image within a scanned frame corresponding to the virtual frame on the basis of the first patch image, and determining a center point of the second patch image as a feature point of the scanned frame corresponding to the virtual frame.

(8) A similarity between the first patch image and the second patch image may be greater than a threshold value.

- (9) The virtual frame may be generated from the full mouth image on the basis of an orientation and size of the scanned frame.
- (10) The reconstructing of the 3D oral cavity model may include matching the feature points of the plurality of scanned frames and determining a matching pair, and re-matching the plurality of scanned frames on the basis of the matching pair and reconstructing the 3D oral cavity model.
- (11) The plurality of scan frames may be matched using an iterative closest point (ICP) algorithm.
- (12) The detecting of the feature points of the full mouth image may include generating a rendered two-dimensional (2D) image by rendering the full mouth image, and detecting the feature points of the full mouth image by applying deep learning to the rendered 2D image.
- (13) The detecting of the feature points of the full mouth image by applying the deep learning to the rendered 2D image may include generating a heatmap for points where teeth meet by applying deep learning to the rendered 2D image, and detecting the feature points of the full mouth image from the heatmap.
- (14) The detecting of the feature points of the full mouth image by applying the deep learning to the rendered 2D image may further include when a first tooth meets a second tooth at a first feature point and the second tooth meets a third tooth at a second feature point, determining a center point between the first feature point and the second feature point, determining three straight lines passing through the first point, the second point, and the center point while being perpendicular to a straight line passing through the first feature point and the second feature point, and determining additional feature points, other than the first point and the second point, on the three straight lines.
- (15) Another aspect of the present invention provides a device for matching 3D intraoral scan data, which includes a matching unit configured to match a plurality of scanned frames to generate a full mouth image; a deep learning unit configured to detect feature points of the full mouth image by performing deep learning; a scanned frame feature point determination unit configured to determine feature points of the plurality of scanned frames using the feature points of the full mouth image; and a scan data re-matching unit configured to re-match the plurality of scanned frames on the basis of the feature points of the plurality of scanned frames to reconstruct a 3D oral cavity model.
- (16) The device for matching the 3D intraoral scan data may further include a virtual frame generation unit configured to generate a virtual frame from the full mouth image; and a virtual frame feature point determination unit configured to project the feature points of the full mouth image onto the virtual frame to determine feature points of the virtual frame, wherein the scanned frame feature point determination unit may determine the feature points of the plurality of scanned frames using the feature points of the virtual frame.
- (17) The device for matching the 3D intraoral scan data may further include a feature point matching unit configured to match the feature points of the plurality of scanned frames to determine a matching pair, wherein the scan data re-matching unit may re-match the plurality of scanned frames on the basis of the matching pair to reconstruct the 3D oral cavity model.

Advantageous Effects

- (18) According to the embodiment of the present invention, by obtaining a matching pair between frame models using deep learning and re-matching scanned frames on the basis of the matching pair, it is possible to reduce an overall matching error of a reconstructed scan model.

Description

DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a block diagram of a device for matching three-dimensional (3D) intraoral scan data according to an embodiment of the present invention.
- (2) FIG. 2 schematically shows an operating method of a device for matching 3D intraoral scan

data according to an embodiment of the present invention.

(3) FIG. 3 is a flowchart illustrating an operating method of a device for matching 3D intraoral scan data according to an embodiment of the present invention.

(4) FIG. 4 shows an oral cavity scan and scan image matching process according to an embodiment of the present invention.

(5) FIG. 5 shows a process of generating a heatmap according to an embodiment of the present invention.

(6) FIG. 6 shows a process of determining 3D feature points of a full mouth image according to an embodiment of the present invention.

(7) FIG. 7 shows a process of additionally determining 3D feature points of a full mouth image according to an embodiment of the present invention.

(8) FIG. 8 shows a process of determining feature points of a virtual frame according to an embodiment of the present invention.

(9) FIG. 9 shows a process of determining feature points of a plurality of scanned frames according to an embodiment of the present invention.

(10) FIG. 10 shows a process of reconstructing a 3D oral cavity model according to an embodiment of the present invention.

(11) FIG. 11 shows a process of reconstructing a 3D oral cavity model according to another embodiment of the present invention.

MODES OF THE INVENTION

(12) Hereinafter, embodiments of the present invention that can be easily performed by those skilled in the art will be described in detail with reference to the accompanying drawings. In addition, parts irrelevant to description are omitted in the drawings in order to clearly explain the present invention.

(13) FIG. 1 is a block diagram of a device for matching three-dimensional (3D) intraoral scan data according to an embodiment of the present invention.

(14) As shown in FIG. 1, a device **100** for matching 3D intraoral scan data according to the embodiment of the present invention includes a scanning unit **110**, a matching unit **120**, a deep learning unit **130**, a virtual frame generation unit **140**, a virtual frame feature point determination unit **150**, a scanned frame feature point determination unit **160**, a feature point matching unit **170**, and a scan data re-matching unit **180**. The operation of each component of the device **100** for matching 3D intraoral scan data will be described below.

(15) FIG. 2 schematically shows an operating method of the device for matching the 3D intraoral scan data according to the embodiment of the present invention.

(16) In particular, FIG. 2 shows a 3D oral cavity model reconstruction process for reducing matching errors accumulated during a process of reconstructing intraoral scan data.

(17) As shown in FIG. 2, the scanning unit **110** scans an oral cavity to generate a plurality of scanned frames (S21).

(18) The matching unit **120** generates a full mouth image by matching the plurality of scanned frames using an iterative closest point (ICP) algorithm, and the deep learning unit **130** determines 3D feature points in the full mouth image by performing deep learning (S22).

(19) The virtual frame generation unit **140** generates a virtual frame from the full mouth image on the basis of an orientation and size of the scanned frames, and the virtual frame feature point determination unit **150** projects the feature points of the full mouth image onto the virtual frame to determine feature points of the virtual frame (S23).

(20) The scanned frame feature point determination unit **160** determines feature points of the plurality of scanned frames using the feature points of the virtual frame (S24).

(21) The feature point matching unit **170** matches the feature points of the plurality of scanned frames to determine a matching pair, and the scan data re-matching unit **180** re-matches the plurality of scanned frames on the basis of the matching pair to reconstruct the 3D oral cavity

model (S25).

(22) FIG. 3 is a flowchart illustrating an operating method of a device for matching 3D intraoral scan data according to an embodiment of the present invention.

(23) The scanning unit **110** scans an oral cavity to generate a plurality of scanned frames (S101).

(24) The matching unit **120** matches the plurality of scanned frames using, for example, an ICP algorithm to generate a full mouth image (S103). The matching method includes any method of obtaining rigid-body transformations through iterative surface matching, such as ICP.

(25) Next, an oral cavity scan and scan image matching process will be described with reference to FIG. 4.

(26) FIG. 4 shows an oral cavity scan and scan image matching process according to an embodiment of the present invention.

(27) As shown in FIG. 4, the scanning unit **110** may scan an oral cavity **401** to generate a plurality of scanned frames **403**, and the matching unit **120** may match the plurality of scanned frames to generate a full mouth image **405**.

(28) Again, FIG. 3 will be described.

(29) The deep learning unit **130** detects 3D feature points in the full mouth image by performing deep learning (S105). Since handling 3D mesh data directly in the deep learning process may have a problem of high computational cost, the deep learning unit **130** may generate a rendered two-dimensional (2D) image by rendering the full mouth image instead of 3D scan data, and apply deep learning to the 2D image.

(30) For data learning, the deep learning unit **130** may use a 2D image rendered in a z-direction of the full mouth image, which is full mouth scan data, as an input of deep learning and use adjacent 2D points between teeth as an output of deep learning. In consideration of the fact that patients have different numbers of teeth, the deep learning unit **130** does not use a coordinate vector of a constant number of feature points as an output of deep learning, but may generate a heatmap image that displays the positions of feature points and use the heatmap image as an output of deep learning to train a deep learning network. The heatmap is a data visualization technique that shows the intensity of a phenomenon as color in two dimensions. Therefore, the deep learning unit **130** may perform deep learning and output a heatmap that shows the intensity of feature points as color. In order to obtain 3D feature points from a 2D heatmap, the deep learning unit **130** may retrieve 2D coordinates of points having the maximum intensity in the heatmap and project the points onto a 3D full mouth image to obtain 3D feature points of the 3D full mouth image.

(31) Next, a process of obtaining feature points of a 3D full mouth image will be described with reference to FIGS. 5 and 6.

(32) FIG. 5 shows a process of generating a heatmap according to an embodiment of the present invention.

(33) As shown in FIG. 5, the deep learning unit **130** generates a 2D rendered image **503** by rendering a 3D full mouth image **501**. The deep learning unit **130** may determine a point where teeth meet in the 2D rendered image **503** (**505**), and generate a heatmap **507** by performing Gaussian mapping on the determined point.

(34) FIG. 6 shows a process of determining 3D feature points of a full mouth image according to an embodiment of the present invention.

(35) As shown in FIG. 6, the deep learning unit **130** generates a 2D rendered image **603** by rendering a 3D full mouth image **601**. The deep learning unit **130** performs deep learning **605** using the 2D rendered image **603** as an input to generate a heatmap **607** for a point where teeth meet. The deep learning unit **130** may determine 3D feature points **609** of a full mouth image on the basis of the heatmap **607**.

(36) Since at least three feature points are required for each frame to match a plurality of scanned frames, more points are additionally required in addition to adjacent points between teeth. A process of obtaining additional feature points in addition to adjacent points between teeth will be

described with reference to FIG. 7.

(37) FIG. 7 shows a process of additionally determining 3D feature points of a full mouth image according to an embodiment of the present invention.

(38) The deep learning unit **130** may determine 3D feature points **703** of a full mouth image on the basis of a heatmap **701**.

(39) When it is assumed that a first tooth meets a second tooth at a first point and the second tooth meets a third tooth at a second point, the deep learning unit **130** determines a center point between the first point and the second point, and the deep learning unit **130** determines three straight lines passing through the first point, the second point, and the center point while being perpendicular to a straight line passing through the first point and the second point (**705**). The deep learning unit **130** may determine additional feature points, other than the first point and the second point, on the three straight lines (**707**).

(40) By applying the above process to all the teeth, the deep learning unit **130** may determine at least three times as many feature points as the number of teeth for the entirety of the full mouth image (**709**).

(41) Again, FIG. 3 will be described.

(42) The virtual frame generation unit **140** generates a virtual frame from the full mouth image on the basis of an orientation and size of the scanned frames (**S107**). The virtual frame generation unit **140** may generate the virtual frame by rendering the full mouth image in the same orientation and the same size as the scanned frames. The virtual frame may represent a rendered image, a depth map, or both the rendered image and the depth map.

(43) The virtual frame feature point determination unit **150** projects the feature points of the full mouth image onto the virtual frame to determine feature points of the virtual frame (**S109**).

(44) FIG. 8 shows a process of determining feature points of a virtual frame according to an embodiment of the present invention.

(45) As shown in FIG. 8, the virtual frame feature point determination unit **150** may project feature points of a full mouth image **801** onto a virtual frame **803** to determine feature points of the virtual frame **803**.

(46) The scanned frame feature point determination unit **160** determines feature points of a plurality of scanned frames using the feature points of the virtual frame (**S111**). Specifically, the scanned frame feature point determination unit **160** may generate a patch image having a predetermined size around a feature point of the virtual frame. The scanned frame feature point determination unit **160** may select a patch image having a similarity with the patch image greater than a threshold value from the scanned frame. The scanned frame feature point determination unit **160** may determine a center point of the patch image selected from the scanned frame as a feature point of the scanned frame.

(47) FIG. 9 shows a process of determining feature points of a plurality of scanned frames according to an embodiment of the present invention.

(48) The scanned frame feature point determination unit **160** may generate a patch image **903** having a predetermined size around a feature point of a virtual frame **901**. The scanned frame feature point determination unit **160** may select a patch image **905** having a similarity with the patch image **903** greater than a threshold value from a scanned frame **907**. However, when searching for a patch image similar to the patch image **903** in the entire scanned frame **907**, two or more patch images **905** may be selected as shown in FIG. 9, or unwanted patch images **905** having a large error may be selected.

(49) In order to solve the above problem, first, the scanned frame feature point determination unit **160** may generate a patch image **913** having a predetermined size around a feature point of a virtual frame **911**. The scanned frame feature point determination unit **160** may select a patch image **915** having a similarity with the patch image **913** greater than a threshold value from an area of a scanned frame **917** corresponding to the vicinity of a feature point of the virtual frame **911**.

Thereafter, the scanned frame feature point determination unit **160** may determine a center point of the patch image selected from the scanned frame as a feature point of the scanned frame, thereby reducing the amount of calculation and error.

(50) Again, FIG. **3** will be described.

(51) The feature point matching unit **170** determines a matching pair by matching the feature points of the plurality of scanned frames (**S113**).

(52) The scan data re-matching unit **180** reconstructs a 3D oral cavity model by re-matching the plurality of scanned frames on the basis of the matching pair (**S115**). A process of reconstructing the 3D oral cavity model will be described with reference to FIGS. **10** and **11**.

(53) FIG. **10** shows a process of reconstructing a 3D oral cavity model according to an embodiment of the present invention.

(54) As shown in FIG. **10**, since there are differences between virtual frames and scanned frames due to errors generated in the matching process of the matching unit **120**, when a first virtual frame **1001** and a second virtual frame **1003** are matched based on a feature point pair between the first virtual frame **1001** and the second virtual frame **1003**, spatial distortion may occur in a matched image **1005**.

(55) However, when feature points of the first virtual frame **1001** and second virtual frame **1003** are transferred to a first scanned frame **1011** and a second scanned frame **1013**, and the first scanned frame **1011** and the second scanned frame **1013** are matched based on a feature point pair between the first scanned frame **1011** and the second scanned frame **1013**, a matched image **1015** may have reduced spatial distortion.

(56) FIG. **11** shows a process of reconstructing a 3D oral cavity model according to another embodiment of the present invention.

(57) As shown in FIG. **11**, an oral cavity image **1101** generated by the matching unit **120** has spatial distortion. It can be seen that, since the scan data re-matching unit **180** generates a matched image **1107** by re-matching a plurality of scanned frames **1103** and **1105** on the basis of a feature point matching pair, spatial distortion is reduced. As a result, a 3D oral cavity model **1109** generated from the image **1107** with little spatial distortion also has little spatial distortion.

(58) While the present invention has been described with reference to the embodiment illustrated in the accompanying drawings, the embodiment should be considered in a descriptive sense only, and it should be understood by those skilled in the art that various alterations and equivalent other embodiments may be made. Therefore, the scope of the present invention should be defined by only the following claims.

Claims

1. A method of matching three-dimensional (3D) intraoral scan data, comprising: matching a plurality of scanned frames and generating a full mouth image; detecting feature points of the full mouth image by performing deep learning; determining feature points of the plurality of scanned frames using the feature points of the full mouth image; and re-matching the plurality of scanned frames on the basis of the feature points of the plurality of scanned frames and reconstructing a 3D oral cavity model.
2. The method of claim 1, wherein the determining of the feature points of the plurality of scanned frames using the feature points of the full mouth image includes: generating a virtual frame from the full mouth image; projecting the feature points of the full mouth image onto the virtual frame and determining feature points of the virtual frame; and determining the feature points of the plurality of scanned frames using the feature points of the virtual frame.
3. The method of claim 2, wherein the determining of the feature points of the plurality of scanned frames using the feature points of the virtual frame includes: generating a first patch image having a predetermined size around a feature point of the virtual frame; selecting a second patch image

within a scanned frame corresponding to the virtual frame on the basis of the first patch image; and determining a center point of the second patch image as a feature point of the scanned frame corresponding to the virtual frame.

4. The method of claim 3, wherein a similarity between the first patch image and the second patch image is greater than a threshold value.

5. The method of claim 2, wherein the virtual frame is generated from the full mouth image on the basis of an orientation and size of the scanned frame.

6. The method of claim 1, wherein the reconstructing of the 3D oral cavity model includes: matching the feature points of the plurality of scanned frames and determining a matching pair; and re-matching the plurality of scanned frames on the basis of the matching pair and reconstructing the 3D oral cavity model.

7. The method of claim 1, wherein the plurality of scanned frames are matched using an iterative closest point (ICP) algorithm.

8. The method of claim 1, wherein the detecting of the feature points of the full mouth image includes: generating a rendered two-dimensional (2D) image by rendering the full mouth image; and detecting the feature points of the full mouth image by applying deep learning to the rendered 2D image.

9. The method of claim 8, wherein the detecting of the feature points of the full mouth image by applying the deep learning to the rendered 2D image includes: generating a heatmap for points where teeth meet by applying deep learning to the rendered 2D image; and detecting the feature points of the full mouth image from the heatmap.

10. The method of claim 8, wherein the detecting of the feature points of the full mouth image by applying the deep learning to the rendered 2D image further includes: when a first tooth meets a second tooth at a first feature point and the second tooth meets a third tooth at a second feature point, determining a center point between the first feature point and the second feature point; determining three straight lines passing through the first point, the second point, and the center point while being perpendicular to a straight line passing through the first feature point and the second feature point; and determining additional feature points, other than the first point and the second point, on the three straight lines.

11. A device for matching three-dimensional (3D) intraoral scan data, comprising: a matching unit configured to match a plurality of scanned frames to generate a full mouth image; a deep learning unit configured to detect feature points of the full mouth image by performing deep learning; a scanned frame feature point determination unit configured to determine feature points of the plurality of scanned frames using the feature points of the full mouth image; and a scan data re-matching unit configured to re-match the plurality of scanned frames on the basis of the feature points of the plurality of scanned frames to reconstruct a 3D oral cavity model.

12. The device of claim 11, further comprising: a virtual frame generation unit configured to generate a virtual frame from the full mouth image; and a virtual frame feature point determination unit configured to project the feature points of the full mouth image onto the virtual frame to determine feature points of the virtual frame, wherein the scanned frame feature point determination unit determines the feature points of the plurality of scanned frames using the feature points of the virtual frame.

13. The device of claim 11, further comprising a feature point matching unit configured to match the feature points of the plurality of scanned frames to determine a matching pair, wherein the scan data re-matching unit re-matches the plurality of scanned frames on the basis of the matching pair to reconstruct the 3D oral cavity model.
