

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12400559

Kind Code

B2

Date of Patent

August 26, 2025

Inventor(s)

Becker; William Joshua et al.

Weld modules for weld training systems

Abstract

Systems are disclosed relating to a weld module for weld training systems. In some examples, a weld module is configured for attachment to (and/or detachment from) a plug of a welding tool (e.g., welding torch, gun, stinger, foot pedal, etc.). The weld module may be configured to detect tool events based one or more signals received from the plug of the welding tool. The weld module may communicate the tool events to the weld training system for use during a weld simulation, for example.

Inventors: Becker; William Joshua (Neenah, WI), Marquinez Torrecilla; Pedro Gerardo (Annapolis, MD), Pérez; Jesús Calvo (Huelva, ES), de la Rosa; David Barroso (Huelva, ES), Márquez; Victor López (Huelva, ES), Escobar Garrido; Jose Miguel (Huelva, ES)

Applicant: ILLINOIS TOOL WORKS INC. (Glenview, IL); SEABERY NORTH AMERICA INC. (Annapolis, MD)

Family ID: 1000008778294

Assignee: ILLINOIS TOOL WORKS INC. (Glenview, IL); SEABERY NORTH AMERICA INC. (Annapolis, MD)

Appl. No.: 18/378246

Filed: October 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240046816 A1	Feb. 08, 2024

Related U.S. Application Data

continuation parent-doc US 16793768 20200218 US 11817006 child-doc US 18378246
us-provisional-application US 62807664 20190219

Publication Classification

Int. Cl.: G09B19/24 (20060101); G06F3/01 (20060101); G09B25/02 (20060101)

U.S. Cl.:

CPC G09B19/24 (20130101); G06F3/016 (20130101); G09B25/02 (20130101);

Field of Classification Search

CPC: G09B (19/24); G09B (19/00); B23K (9/09); B23K (9/095); B23K (9/0953)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2043331	12/1935	Notvest	N/A	N/A
2175891	12/1938	Graham	N/A	N/A
2526597	12/1949	Winslow	N/A	N/A
2617913	12/1951	Oestreicher	N/A	N/A
2642515	12/1952	Bagg	N/A	N/A
3567902	12/1970	Stearns	N/A	N/A
3992565	12/1975	Gatfield	N/A	N/A
4051344	12/1976	Robbins	N/A	N/A
4079231	12/1977	Toth	N/A	N/A
4147919	12/1978	Matasovic	N/A	N/A
4216367	12/1979	Risberg	N/A	N/A
4216368	12/1979	Delay	N/A	N/A
4227066	12/1979	Bulwidas	N/A	N/A
4247752	12/1980	Stringer	N/A	N/A
4266114	12/1980	Hansen	N/A	N/A
4410789	12/1982	Story	N/A	N/A
4450340	12/1983	Corrigall	N/A	N/A
4467174	12/1983	Gilliland	N/A	N/A
4508954	12/1984	Kroll	N/A	N/A
4521672	12/1984	Fronius	N/A	N/A
4531045	12/1984	Kemp	N/A	N/A
4561059	12/1984	Davis	N/A	N/A
4641292	12/1986	Tunnell	N/A	N/A
4767908	12/1987	Dallavalle	N/A	N/A
4931018	12/1989	Herbst et al.	N/A	N/A
5039835	12/1990	Schwiete	N/A	N/A
5043557	12/1990	Tabata	N/A	N/A
5276305	12/1993	Hsien	N/A	N/A
5406050	12/1994	MacOmber	N/A	N/A
5708523	12/1997	Kubo	N/A	N/A
6040555	12/1999	Tiller	N/A	N/A
6103994	12/1999	Decoster et al.	N/A	N/A
6156999	12/1999	Ignatchenko	N/A	N/A
6423936	12/2001	Reed	N/A	N/A
6512199	12/2002	Blazina	N/A	N/A
6531673	12/2002	Fedorcak	N/A	N/A
6570132	12/2002	Brunner	N/A	N/A
6624388	12/2002	Blankenship et al.	N/A	N/A
6781095	12/2003	Hayes	N/A	N/A
6841752	12/2004	Ward	N/A	N/A
6906285	12/2004	Zucker	N/A	N/A
6909285	12/2004	Jordan	N/A	N/A
7045742	12/2005	Feichtinger	N/A	N/A
7205503	12/2006	Reynolds	N/A	N/A
7245875	12/2006	Clark	N/A	N/A
7336259	12/2007	Li	N/A	N/A
7381922	12/2007	Ulrich	N/A	N/A
8487216	12/2012	Reynolds	N/A	N/A
8658940	12/2013	Reynolds	N/A	N/A

8785817	12/2013	Luck	N/A	N/A
9180544	12/2014	Luck	N/A	N/A
9672757	12/2016	Becker et al.	N/A	N/A
9718141	12/2016	Denis	N/A	N/A
9724778	12/2016	Denis	N/A	N/A
9943924	12/2017	Denis	N/A	N/A
9993890	12/2017	Denis et al.	N/A	N/A
10144085	12/2017	Reynolds	N/A	N/A
10369652	12/2018	Denis	N/A	N/A
10464156	12/2018	Denis et al.	N/A	N/A
11423800	12/2021	Batzler	N/A	N/A
2003/0184515	12/2002	Tsai	N/A	N/A
2004/0026392	12/2003	Feichtinger	N/A	N/A
2005/0155068	12/2004	Chang	N/A	N/A
2005/0199605	12/2004	Furman	N/A	N/A
2006/0163227	12/2005	Hillen	N/A	N/A
2008/0083121	12/2007	Cziraky	N/A	N/A
2013/0040270	12/2012	Albrecht	N/A	N/A
2014/0144898	12/2013	Upton	219/132	B23K 9/1087
2014/0168443	12/2013	Aguilar	N/A	N/A
2014/0263224	12/2013	Becker	N/A	N/A
2014/0332515	12/2013	Luck	N/A	N/A
2015/0194073	12/2014	Becker	N/A	N/A
2016/0039035	12/2015	Luck	N/A	N/A
2016/0193682	12/2015	Vogel	219/132	B23K 9/32
2017/0046975	12/2016	Becker et al.	N/A	N/A
2017/0046976	12/2016	Becker et al.	N/A	N/A
2018/0229324	12/2017	Denis	N/A	N/A
2019/0105725	12/2018	Reynolds	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1538306	12/2003	CN	N/A
1746833	12/2005	CN	N/A
0575082	12/1992	EP	N/A
1112800	12/2000	EP	N/A
1500456	12/2004	EP	N/A
1683599	12/2013	EP	N/A
61137675	12/1985	JP	N/A
04162964	12/1991	JP	N/A
04162966	12/1991	JP	N/A
2003088957	12/2002	JP	N/A
2003154455	12/2002	JP	N/A
2003191075	12/2002	JP	N/A
2003236663	12/2002	JP	N/A
0134337	12/2000	WO	N/A
02085566	12/2001	WO	N/A
2009146359	12/2008	WO	N/A

OTHER PUBLICATIONS

“Miller PC-300 Owner's Manual”, Aug. 1989 (Aug. 1989), http://igor.chudov.com/manuals/Miller/Miller-PC-300-Pulse-Control_Manual.pdf. cited by applicant

Avocent, “LongView Wireless User Guide”, 2005, <http://site.i-techcompany.com/DataSheet/Avocent/lv5800UG.pdf>. cited by applicant

American Welding Society, “Welding Journal, Special Emphasis: Computer Technology in Welding,” vol. 79, No. 1, https://app.aws.org/wj/2000/01/WJ_2000_01.pdf, Jan. 2000. cited by applicant

Scientific Atlanta, “WebSTAR Model DPW941 Wireless Ethernet Adapter,”

<http://www.cisco.com/web/consumer/support/userguides2/738183.pdf>, Apr. 2005. cited by applicant

D-Link, “D-Link AirPlus G DWL-G730AP,”

http://www.dlink.com/-/media/Consumer_Products/DWL/DWL%20G730AP/Manual/DWLG730AP_Manual_EN_UK.pdf
Aug. 10, 2004. cited by applicant
Echelon, "PL 3120 / PL 3150 Power Line Smart Transceiver Data Book," Version 2, 005-0154-01, 255 pgs. cited by applicant
Intellon, "CEBus Power Line Encoding and Signaling," White Paper #0027, Mar. 1997, Version 0.1, pp. 1-6. cited by applicant
Wireless Universal Serial Bus Specification, Revision 1.0, May 12, 2005. cited by applicant
Hackl et al., "Digitally Controlled GMA Power Sources," Fronius,
www.fronius.com/worldwide/usa/products/paper_digitally_controlld_power_sources_gb.pdf, pp. 1-7, publication date not provided. cited by applicant
International Search Report and Written Opinion, International Patent Application No. PCT/US2020/018836, mailed May 19, 2020, 15 pages. cited by applicant
European Patent Office, Office Action, Application No. 20715513.6, mailed Oct. 10, 2022, 8 pages. cited by applicant
Canada Patent Office, Office Action, Application No. 3,130,588 dated Sep. 5, 2023, 4 pages. cited by applicant

Primary Examiner: Utama; Robert J

Attorney, Agent or Firm: McAndrews, Held & Malloy, Ltd.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application claims priority to, and is a continuation of, U.S. Non-Provisional patent application Ser. No. 16/793,768, filed Feb. 18, 2020, entitled "WELD MODULES FOR WELD TRAINING SYSTEMS," which claims the benefit of U.S. Provisional Patent Application Ser. No. 62/807,664, filed Feb. 19, 2019, entitled "WELD MODULES FOR WELD TRAINING SYSTEMS," the entire contents of all of which are expressly incorporated herein by reference.

TECHNICAL FIELD

(1) This disclosure relates to weld modules and, more particularly, to weld modules for weld training systems.

BACKGROUND

(2) The welding industry has a shortage of experienced and skilled operators. Additionally, it is difficult and expensive to train new operators using live welding equipment. Further, even experienced welders often have difficulty maintaining important welding techniques throughout welding processes. Thus, there is a demand for affordable training tools and equipment that help operators develop, maintain, and/or refine welding skills.

(3) Weld training simulations make it possible for both experienced and inexperienced weld operators to practice producing high quality welds prior to actually using the real welding equipment. However, conventional weld training simulation systems require substantial investments in specialized equipment (e.g., processors, displays, practice workpieces, practice welding tool(s), sensor(s), etc).

SUMMARY

(4) Weld modules for weld training systems are disclosed, substantially as illustrated by and described in connection with at least one of the figures, as set forth more completely in the claims.

(5) These and other advantages, aspects, and/or novel features of the present disclosure, as well as details of an illustrated example thereof, will be more fully understood from the following description and drawings.

Description

DRAWINGS

(1) Features, aspects, and/or advantages of the present disclosure will become better understood when the following detailed description is read with reference to the accompanying drawings in which like characters represent like parts throughout the drawings, wherein:

(2) FIG. 1 illustrates a conventional welding-type system, in accordance with aspects of this disclosure.

(3) FIG. 2 illustrates an example weld training system, in accordance with aspects of this disclosure.

(4) FIG. 3 illustrates an example weld module, several example welding tools, and the weld training system of FIG. 2, in accordance with aspects of this disclosure.

(5) FIG. 4A is a block diagram illustrating components of the example weld module of FIG. 3, in accordance with aspects of this disclosure.

(6) FIG. 4B is a circuit diagram illustrating an example portion of control circuitry of the example weld module of

FIG. 4A, in accordance with aspects of this disclosure.

(7) FIG. 5A is an exploded perspective view of an example implementation of the weld module of FIG. 3, in accordance with aspects of this disclosure.

(8) FIG. 5B is another exploded view of the example weld module of FIG. 5A, in accordance with aspects of this disclosure.

(9) FIG. 6A shows a perspective view of an example mock welding tool having an alternative example weld module.

(10) FIG. 6B shows an exploded perspective view of the example mock welding tool of FIG. 6A.

(11) FIG. 7 shows an underside of a panel connecting an alternative example weld module to the example mock welding tool of FIG. 6A.

(12) FIG. 8A is a perspective view of a first side of the example weld module of FIG. 6A.

(13) FIG. 8B is a perspective view of a second side of the example weld module of FIG. 6A.

(14) FIG. 9 is a flow diagram illustrating an example control process of a weld module.

(15) The figures are not necessarily to scale. Where appropriate, similar or identical reference numbers are used to refer to similar or identical components. For example, reference numerals utilizing lettering (e.g., prong 330a, prong 330b) refer to instances of the same reference numeral that does not have the lettering (e.g., prongs 330).

DETAILED DESCRIPTION

(16) Some weld training systems use specialized equipment. For example, some weld training systems may use specialized power supplies, wire feeders, and/or welding torches. However, such specialized equipment tends to be complicated and expensive. It may be more efficient and/or cost effective to instead adapt conventional equipment for training. Additionally, adapting conventional equipment may help to add to the realism and/or applicability of the training.

(17) The present disclosure therefore contemplates using a weld module to connect with conventional equipment (e.g., conventional weld torches, wire feeders, and/or power supplies), so as to integrate the conventional equipment into a weld training system. In some examples, the weld module may be configured for attachment to (and/or detachment from) a conventional plug of a welding tool (e.g., welding torch, gun, stinger, foot pedal, etc.). The weld module may be configured to detect tool events based on one or more signals received from the plug of the welding tool. The weld module may communicate the tool events to the weld training system for use during a weld simulation, for example. The weld module may additionally be configured for secure attachment to a fixture (so as to secure otherwise loose and/or dangling cords) and/or a conventional socket of a welding-type power supply and/or wire feeder.

(18) The present disclosure also contemplates an alternative weld module that may be used with a specialized mock welding tool. While there may be some additional cost to providing the specialized mock welding tool, the cost may be substantially less than the cost of an actual live welding tool. Further, using a mock welding tool for weld training ensures that no live welding tool is made unavailable for live welding.

(19) Some examples of the present disclosure relate to a mock welding tool, comprising a handle having a trigger, and a communication module comprising: wireless communication circuitry configured to wirelessly send one or more signals to a computing system in response to activation of the trigger, and a module housing enclosing the communication circuitry, the module housing being coupled to the handle.

(20) In some examples, a trigger signal is generated when the trigger is activated and the wireless communication circuitry is configured to receive the trigger signal. In some examples, the mock welding tool further comprises a trigger circuit configured to generate the trigger signal when the trigger is activated. In some examples, the mock welding tool further comprises a panel securing the communication module to the handle. In some examples, the handle comprises a recessed portion that retains the panel and an end portion coupled to the module housing.

(21) In some examples, the module housing further comprises an identifier that assists in communicatively pairing the mock welding tool with the computing system. In some examples, the module housing comprises a base that retains the wireless communication circuitry and a cover configured to attach to the base. In some examples, the mock welding tool further comprises an illuminator configured to provide illumination when the wireless communication circuitry is powered, paired, transmitting, or receiving. In some examples, the mock welding tool further comprises a vibrator configured to vibrate in response to a vibration signal. In some examples, the mock welding tool further comprises a sensor configured to measure a position, orientation, or motion of the communication module, wherein the wireless communication circuitry is configured to transmit a signal indicative of the position, orientation, or motion.

(22) Some examples of the present disclosure relate to a detachable communication module for a welding tool, comprising: a housing configured for attachment to a connector of a welding cable, and circuitry retained by the housing such that the circuitry is in electrical communication with the connector when the housing attaches to the plug, the circuitry configured to detect a tool event via the connector, and transmit a signal to a weld training system that is separate from the detachable communication module in response to the tool event.

(23) In some examples, the signal is indicative of a type of tool event, the circuitry being configured to determine the type of tool event via the connector, the type of tool event comprising an activation event, a deactivation event, a pressure increase event, or a pressure decrease event. In some examples, the circuitry is configured to detect the tool event and/or determine a type of tool event based on a change in voltage across the connector. In some examples, the circuitry is configured to be communicatively paired with complementary communication circuitry via a wireless communication protocol.

(24) In some examples, the housing comprises: receptacles configured to receive the connector, and a chamber configured to house the circuitry, the receptacles leading to the chamber. In some examples, the detachable communication module further comprises an input mechanism in electrical communication with the circuitry, the input mechanism configured to trigger a signal transmission by the circuitry, and an output mechanism in electrical communication with the circuitry, the output mechanism configured to indicate status or identification information. In some examples, the housing is further configured for attachment to a clamp, clip, weight, or fixture. In some examples, the detachable communication module further comprises a vibrator in electrical communication with the circuitry, the vibrator configured to activate in response to detecting a tool event or in response to receipt of one or more welding parameters by the circuitry. In some examples, the detachable communication module further comprises a port receptacle configured to provide power to the circuitry. In some examples, the connector comprises a first connector, and the detachable communication module further comprises a second connector configured for electrical communication with the first connector, wherein the housing is further configured for attachment to a socket configured to receive the second connector.

(25) FIG. 1 shows an example of a conventional welding-type system **100**, such as may be used to conduct conventional welding-type operations, for example. In some examples, the example welding-type system **100** shown in FIG. 1 may be used to conduct gas metal arc welding (GMAW) processes. In some examples, the welding-type system **100** may also be used with other arc welding processes (e.g., flux-cored arc welding (FCAW), gas shielded flux-cored arc welding (FCAW-G), gas tungsten arc welding (GTAW), submerged arc welding (SAW), shielded metal arc welding (SMAW), or similar arc welding processes). In some examples, the welding-type system **100** may be used with metal fabrication systems, such as plasma cutting systems, induction heating systems, and so forth.

(26) In the example of FIG. 1, the welding-type system **100** includes a welding-type power supply **102** (i.e., a welding-type power source), a welding wire feeder **104**, a gas supply **106**, and a welding torch **108**. In some examples, the welding-type power supply **102** generally supplies welding-type power for the various welding-type components and/or accessories of the welding-type system **100** (e.g., the welding wire feeder **104** and/or welding torch **108**) through plug and socket connections **110**. In the example of FIG. 1, the welding-type power supply **102** is coupled to the welding wire feeder **104** and workpiece **112** through the plug and socket connections **110**. One plug and socket connection **110b** is coupled to one or more lead cables **114** that lead to the workpiece **112** through the work clamp **116**, while another plug and socket connection **110a** is connected to one or more weld cables **118** which lead to the wire feeder **104**. In the example of FIG. 1, the gas supply **106** is coupled to the welding torch **108** through the wire feeder **104** via a gas conduit **120**.

(27) In the example of FIG. 1, the wire feeder **104** includes sockets **122** connected to a power plug **124** and trigger plug **125** of the welding torch **108**. In some examples, welding-type power may be supplied to the welding torch **108** via connection of the power plug **124** and the socket **122**. In some examples, filler material (e.g., wire) and/or gas from the gas supply **106** may also be supplied to the welding torch **108** via connection of the power plug **124** and the socket **122**. In some examples, signals from activation/deactivation of the trigger **126** of the welding torch **108** may be communicated to the wire feeder **104** and/or power supply **102** through connection of the trigger plug **125** and socket **122**. In some examples, the welding-type power supply **102** may instead directly couple to the power plug **124** and/or trigger plug **125** of the welding torch **108**, such that power, filler material, gas, and/or trigger signals may be directly transmitted therethrough (e.g., via plug and socket connection **110b**). In operation, an operator may engage a trigger **126** of the torch **108** to initiate an arc (and/or other welding-type operation) between the torch **108** and the workpiece **112**.

(28) However, as previously discussed, there are several issues with using conventional welding systems (e.g., as shown in FIG. 1) for weld training. Thus, separate weld training systems are sometimes used instead. Some of these weld training systems simulate welding operations rather than actually performing welding operations.

(29) FIG. 2 illustrates an example weld training system **200**. As shown, the weld training system **200** includes a sensor **202** (e.g., a camera, an optical sensor, a sound sensor, etc.), a computing device **204**, a mock workpiece **212**, a welding tool **208** (e.g., welding torch), and a welding helmet **210**. In some examples, the welding helmet **210** may comprise a pair of goggles, a headgear combining goggles and some sort of helmet, a mobile device mount attached to a headgear, and/or some other face and/or head mounted wearable assembly. In the example of FIG. 2, the sensor **202** is positioned on or within (or otherwise retained by) the welding helmet **210** (and/or associated helmet assembly). While only one sensor **202** is shown in the example of FIG. 2, in some examples, the weld training

system **200** may include more than one sensor **202**. As shown, the sensor **202** is configured to sense (e.g., view, see, hear, and/or otherwise detect) a mock workpiece **212** and/or a welding tool **208** of the weld training system **200**.

(30) In the example of FIG. 2, the weld training system **200** further includes a computing device **204**. In some examples, the computing device **204** may be a smartphone, tablet, personal digital assistant, electronic book reader, ipod, laptop, desktop computer, mainframe computer, server computer, and/or other appropriate computational apparatus. As shown, the computing device **204** is also positioned in (and/or retained by) the welding helmet **210** (and/or associated helmet assembly). In some examples, the computing device **204** may instead be located remote from the welding helmet **210**.

(31) In the example of FIG. 2, the computing device **204** is in communication with the sensor **202**. Such communication may be through a wired and/or wireless connection. In operation, the sensor **202** may detect certain characteristics of the surrounding environment (e.g., the mock workpiece **212** and/or welding tool **208**) and the computing device **204** may analyze those characteristics to generate a (e.g., augmented, mixed, and/or virtual reality) weld training simulation. For example, the sensor **202** may capture images of the environment, and the computing system may analyze those images (e.g., using computer vision techniques) as well as other information to simulate a welding operation (e.g., with a simulated arc, weld pool, debris, etc.).

(32) In the example of FIG. 2, the mock workpiece **212** and welding torch **20** include markers **250** to assist with recognition by the sensor **202** and/or computing device **204**. As shown, the markers **250** are pattern markers. In some examples, each marker **250** may be a unique pattern. In some examples, no markers **250** may be used on the welding tool **208** and/or mock workpiece **212**.

(33) While, in the example of FIG. 2, the weld training system **200** uses a mock workpiece **212**, in some examples, a real workpiece may be used instead. However, there is little advantage (and several drawbacks) to using real workpieces. Though specialized weld training equipment can be expensive to buy and/or make, mock workpieces **212** are a relatively inexpensive exception.

(34) Welding tools (e.g., torches) are a different matter. Specialized weld tools can indeed be expensive to buy and/or make. Nevertheless, some weld training systems must use specialized welding tools out of necessity. This is because the weld training systems must know when a trigger (and/or foot pedal) is activated in order to operate.

(35) As discussed above, conventional welding tools (e.g., torches and/or foot pedals) activate welding operations when a user pulls a trigger (or presses a pedal). The activation of the trigger or pedal causes a signal indicative of the activation to be transmitted to the wire feeder **104** and/or welding-type power supply **102** (e.g., through connection trigger plug **125**). In order for the weld training system **200** to effectively simulate welding operations, the weld training system **200** also requires some sort of indication of trigger activation and/or deactivation.

(36) However, most computing devices **204** are not configured to receive a trigger plug **125**. Thus, in order for the computing device **204** to obtain an indication of trigger activation, some sort of adaptation is necessary. One solution is to try and adapt the computing device **204** to receive and/or interpret signals from the conventional trigger plug **125**. Another solution is to customize a conventional wire feeder **104** and/or power supply **102** to somehow transmit a trigger signal to the computing device **204**. Another solution is to create a customized welding torch that can connect to the computing device **204** (e.g., via universal serial bus (USB)). Unfortunately, all these solutions may require significant investments of time and/or money.

(37) The present disclosure contemplates a different solution. In particular, the present disclosure contemplates a weld module attachable to (and/or detachable from) conventional trigger plugs **126** (and/or other appropriate plugs). Control circuitry within the weld module may be configured to interpret trigger signals received through the trigger plug **125**, and communication circuitry may be configured to communicate this information to the weld training system **200**. Such a weld module may be relatively inexpensive to produce, easy to use, and allow for incorporation with conventional welding equipment, which may help to add to the cost efficiency, realism, and/or applicability of the training.

(38) FIGS. 3 and 4A show examples of a weld module **400**. As shown, the weld module **400** includes a housing **402** having a socket connector **404** configured for attachment to a plug **304** of a welding tool **308**. Using information transmitted via prongs of the plug **304**, the weld module **400** may detect one or more tool events. As shown, the weld module **400** may communicate tool event information to communication circuitry **222** of the computing device **204**. While this communication is indicated as being wireless in the example of FIG. 3, in some examples, the communication may be over a wired link. The computing device **204** may then use this tool event information to conduct a weld training simulation.

(39) In the example of FIG. 3, several welding tools **308** with several different plugs **304** are shown. As shown, the welding tool **308a** and welding tool **308d** are welding torches or guns, such as a torch or gun configured for gas metal arc welding (GMAW). In some examples, the welding tool **308a** and/or welding tool **308d** may be guns configured for flux-cored arc welding (FCAW). In the example of FIG. 3, the welding tool **308b** and welding tool **308c** are foot pedals (having pedals **310**) such as may be used with a torch and/or filler rod configured for gas tungsten arc welding (GTAW). As shown, the welding tool **308b** has a plug **304b** that is wired to the foot pedal,

while the welding tool **308c** is a wireless foot pedal configured to wirelessly communicate with a receiver **312** that is wired to plug **304c**.

(40) In the example of FIG. 3, the plug **304b** and plug **304c** are shown with two prongs for ease of understanding. In some examples, these prongs may be used to communicate signals indicative of activation/deactivation of a pedal **310**. In some examples, the plug **304b** and/or plug **304c** may be differently configured, with more, less, and/or different prongs (and/or other connectors). In the example of FIG. 3, the welding tool **308a** has a European (and/or Chinese) style plug **304a** with several prongs (and/or connectors) for transmission of gas, wire, power, and trigger signals through the plug **304c**. The welding tool **308d**, in contrast, has a U.S. style plug **304d** that includes only two prongs for transmission of trigger signals, while a separate power plug **306** handles transmission of power, gas, and/or wire. In some examples, the weld module **400** may have a socket connector **404** detachable from the housing **402**, such that the socket connector **404** may be swapped for a different socket connector **404** configured for the applicable type of plug **304**.

(41) In the examples of FIGS. 3 and 4A, the weld module **400** further includes a port **406** configured to couple the weld module **400** to an external power source and/or external device. In some examples, the port **406** may comprise, for example, an Ethernet port, a USB port, an HDMI port, a fiber-optic communications port, and/or any other suitable port for interfacing with a wired cable. In some examples, the port **406** may be a multi-purpose port which can be used for send and/or receiving both power and data.

(42) As shown, the weld module **400** further includes its own plug connector **408**. In some examples, the plug connector **408** may be detachable and/or swappable, so that a plug connector **408** that shares the same configuration as the plug **304** may be used. Using the plug connector **408**, the weld module **400** may be able to connect to the same socket of conventional welding equipment (e.g., power supply **102** and/or wire feeder **104**) to which the plug **304** of the welding tool **308** would normally connect. In some examples, the weld module **400** may also route transmissions through the weld module (e.g., to/from the socket connector **404** and/or plug connector **408**), so as to allow the same information, power, gas, and/or filler material to pass through the weld module **400** to and/or from the welding equipment and/or welding tool **308**.

(43) In the examples of FIGS. 3 and 4A, the weld module **400** further includes a fixture connector **410**. As shown, the weld module **400** is connected to a clamp **320** through the fixture connector **410**. The clamp **320** is, in turn, secured to a table **322**. By securing the weld module **400** to the table **322** via the clamp **320**, the weld module **400** may prevent cables connecting the welding tool **308** to the plug **304** from dangling loose and/or unsecured in examples where the weld module **400** does not connect to conventional welding equipment.

(44) In some examples, the fixture connector **410** may include connecting features (e.g., screw threads, screws, bolts, screw holes, bolt holes, hook and loop connectors, magnetic features, etc.) to enable connection with the clamp **320**. In some examples, the clamp **320** may include complementary connecting features, and/or include a specialized attachment mechanisms having the complementary connecting features, so as to facilitate connection to the weld module **400**. In some examples, the clamp **320** may instead be a clip, weight, and/or some other securing fixture. In some examples, the clamp **320** may be integrated with the weld module **400**.

(45) FIG. 4A illustrates electrical components of the weld module **400**. As shown, the weld module **400** includes one or more illuminators **412**, one or more sensors **414**, one or more vibrators **416**, a user interface (UI) **418**, a power source **420**, communication circuitry **422**, and control circuitry **424** in electrical communication with one another. In the example of FIG. 4A, the control circuitry **424** includes memory **426** and one or more processors **428**. As shown, the control circuitry **424** is in electrical communication with the illuminator(s) **412**, sensor(s) **414**, vibrator(s) **416**, UI **418**, and communication circuitry **422**. In some examples, the components of the weld module **400** may reside on one or more printed circuit boards (PCBs) and/or flex circuits. In some examples, the power source **420**, the port **406**, the illuminator(s), the UI **418**, the sensor(s) **414**, and/or the vibrator(s), may be realized as subsystems (e.g., implemented on separate PCBs and/or attached to primary PCB of the weld module **400**).

(46) Though not shown for the sake of simplicity, the power source **420** may be in electrical communication with the illuminator(s) **412**, sensor(s) **414**, vibrator(s) **416**, UI **418**, control circuitry **424**, and/or communication circuitry **422** through separate electrical connections, to provide power. The power source **420** may comprise, for example, a battery (e.g., a lithium ion or sodium ion or lithium polymer or dual carbon battery), circuitry for charging the battery from an AC and/or DC power source, and/or circuitry for conditioning/delivering energy from the battery to the other circuitry of the weld module **400**. In some examples, the power source **420** may receive and/or provide power from/to external devices through the port **406**.

(47) In some examples, the illuminator(s) **412** may be one or more light emitting diodes (LEDs). In some examples, the illuminator(s) **412** may be configured and/or controlled (e.g., via control circuitry **424**) to light up and/or blink when the communication circuitry **422** is successfully paired and/or actively communicating (e.g., with communication circuitry **222**). In some examples, the illuminator(s) **412** may be configured and/or controlled (e.g., via control circuitry **424**) to light up and/or blink when the welding tool **308** is activated (e.g., via activation of trigger **326** or pedal **310**), so as to visually indicate that the activation has taken place. In some examples, the

illuminator(s) **412** may be configured and/or controlled (e.g., via control circuitry **424**) to light up and/or blink when the weld module **400** is powered on. In some examples, the illuminator(s) **412** may be a separate device configured to attach to and/or detach from the weld module **400** (e.g., via port **406**).

(48) In some examples, the UI **418** may include, for example, one or more display screens, touchscreen elements, microphones, speakers, physical buttons (and/or switches, knobs, dials, keys, etc.), gesture controls, biometric sensors, and/or other types of input and/or output devices. For example, the UI **418** may include capacitive, acoustic, inductive, and/or resistive touchscreen sensors that enable a user to interact with graphics displayed on the UI **418**. In some examples, outputs mechanisms (e.g., display screen, speakers, etc.) of the UI **418** may be configured to output status information (e.g., connection/communication/pairing status, power status, simulation settings, etc.) of the weld module **400**.

(49) In some examples, the UI **418** may include an on/off input mechanism operable to activate and/or deactivate power to the weld module **400**. In some examples, the UI **418** may include an input mechanism operable to activate a pairing process between the communication circuitry **422** of the weld module **400** and some other communication circuitry (e.g., communication circuitry **222** of computing device **204**). In some examples, the pairing may comprise a process for establishing wireless communication (via an appropriate wireless communication protocol) between the communication circuitry **422** of the weld module **400** and some other communication circuitry (e.g., communication circuitry of the computing device **204**). In some examples, the weld module **400** may be marked with an identification number (e.g., serial number) and/or identification pattern (e.g., barcode, QR code, etc.) to assist with the pairing. In some examples, the identification number and/or identification pattern may be stored in memory **426** and/or displayed to the user via a display of the UI **418**. In some examples, the sensor(s) **414** may assist with the pairing.

(50) In some examples, the sensor(s) **414** may include infrared and/or ultrasonic sensors, accelerometers, gyroscopes, inertial measurement units (IMUs), near field communication (NFC) sensors, radio frequency identification (RFID) sensors, Bluetooth sensors, and/or the like. The sensor(s) **414** may include one or more inertial measurement units (IMUs) such as multi-axis gyroscopes, multi-axis accelerometers, and/or multi-axis magnetometers to detect, encode, and/or measure movement of the weld module **400**. In some examples, the sensor(s) **414** may be a separate device configured to attach to and/or detach from the weld module **400** (e.g., via port **406**).

(51) In some examples, the vibrator(s) **416** may be configured to provide vibration and/or haptic feedback to an operator of the welding tool **308** during weld training. For example, the vibrator(s) **416** may be used to simulate vibrations that would be felt during actual welding due to the arc and/or filler material (e.g., wire) feeding process. In some examples, the control circuitry **424** may control the vibrator(s) **416** to activate and/or deactivate in response to detection of one or more tool events. In some examples, the vibrator(s) **416** may be a separate device configured to attach to and/or detach from the weld module **400** (e.g., via port **406**).

(52) In some examples, the communication circuitry **422** is configured to communicate with one or more external devices, such as, for example, communication circuitry **222** of the computing device **204**, and/or other communication circuitry in third party devices, remote servers, and/or conventional welding equipment. In some examples, the communication circuitry **422** may include an antenna configured to facilitate this communication. In some examples, the communication circuitry **422** may facilitate communication through a wired connection (e.g., through port **406**). In some examples, the communication circuitry **422** may facilitate communication through one or more wireless communication protocols. Wireless protocols may include, for example, cellular protocols (e.g., GSM, IS-95, UMTS, CDMA, LTE, etc.), IEEE 802.15.4 based protocols in the 2.4 GHz industrial, scientific, and medical (ISM) radio band (commonly known as Zigbee), low frequency magnetic signal protocols being transmitted at a frequency of approximately 131-134 kHz in conformance with IEEE 1902.1 standard (commonly known as Rubee), short wavelength ultra high frequency radio communication protocols in the 2.400 to 2.485 GHz ISM band in conformance with IEEE 802.15.1 standard (commonly known as Bluetooth), communication protocols in conformance with the IEEE 802.11 standard (commonly known as Wifi), and/or other appropriate communication protocols.

(53) In some examples, the control circuitry **424** is configured to process data from, and/or send data (e.g., control signals) to, the components of the weld module **400**. In the example of FIG. 4A, the control circuitry **424** is in electrical communication with electrical contacts **430** positioned at the end of receptacles **432** formed in the socket connector **404** of the weld module **400**. In operation, the electrical contacts **430** may come into contact with prongs **330** of a plug **304** connected to the weld module **400** (see, e.g., FIG. 4B). Thus, electrical signals from the welding tool **308** may be communicated to the control circuitry **424** of the weld module **400** via the electrical pathway of the prongs **330** and contacts **430**. In some examples, the control circuitry **424** may include one or more current and/or voltage sensors configured to measure the current through, and/or voltage across, the contacts **430**.

(54) In the example of FIG. 4A, the electrical contacts **430** are also in electrical communication with tines **434** of the plug connector **408** of the weld module **400**. Thus, in operation, electrical signals from the welding tool **308**

may be communicated to the plug connector **408** of the weld module **400** via the electrical pathway of the prongs **330** and contacts **430**. In this way, data from the welding tool **308** may be communicated both to the weld module **400** and through the weld module **400** (e.g., to conventional welding equipment). In some examples, the plug connector **408** and/or socket connector **404** of the weld module **400** may include additional tines **434** and/or receptacles **432**, so as to route additional inputs/outputs of welding equipment and/or the welding tool **308** (e.g., welding-type power, gas, filler material, signals, etc.) through the weld module **400**.

(55) In operation, the control circuitry **424** may determine whether a tool event has occurred based on one or more signals received from the prongs **330** and/or contacts **430**. In some examples, a tool event may comprise a change in a state of the welding tool **308**. For example, a tool event may include one or more of a pull of a trigger **326**, a release of a trigger **326**, a press of a pedal **310**, a release of a pedal **310**, and/or a change (e.g., increase and/or decrease) in pressure on a trigger **326** and/or pedal **310**. In some examples, a tool event may be communicated from the welding tool **308** by a change in voltage across the prongs **330** of the plug **304** of the welding tool **308**.

(56) FIG. **4B** is an example of a logic circuit **450** that may be used to determine whether a tool event has occurred, and/or determine a type of tool event. In some examples, the logic circuit **450** may be part of the control circuitry **424**. In some examples, the logic circuit **450** may be implemented in digital and/or analog circuitry, discrete and/or integrated circuitry, microprocessors, DSPs, software, hardware and/or firmware.

(57) In the example of FIG. **4B**, the logic circuit **450** includes a voltage source V_s in electrical communication with a first contact **430a** and a first input **452a** of a comparator **454**. As shown, the logic circuit **450** further includes a second contact **430b** in electrical communication with a second input **452b** of the comparator **454**. As shown, the second contact **430b** is also in electrical communication with ground **456** (through resistor **458**). As shown, first contact **430a** and second contact **430b** are positioned (at least partially) within receptacles **432**, such that first contact **430a** and second contact **430b** will be electrically connected with first prong **330a** and second prong **330b** of the plug **304** when the plug **304** is coupled to the socket connector **404**.

(58) In the example of FIG. **4B**, the first prong **330a** and second prong **330b** of the welding tool **308** may be electrically connected or electrically disconnected by a switch **460** in communication with a trigger **326** or pedal **310**. In some examples, the switch **460** may be closed when the trigger **326** or pedal **310** is activated, and/or opened when the trigger **326** or pedal **310** is deactivated (or vice versa). When the switch **460** is closed, the voltage across the first contact **430a** and second contact **430b** (and/or first input **452a** and second input **452b**) may be approximately zero (and/or less than some minimum threshold). When the switch **460** is open, the voltage across the first contact **430a** and second contact **430b** (and/or first input **452a** and second input **452b**) may be non-zero (and/or greater than some minimum threshold). In some examples, the comparator **454** may detect the voltage across the first input **452** and second input **452** and send a signal indicative of the voltage to the output **462**, which may be received and/or further processed by the control circuitry **424** (e.g., to control communication circuitry **422** to send a similarly indicative signal).

(59) In some examples, the welding tool **308** may have a more complicated configuration (e.g., several switches in parallel with different resistors for each switch) to generate a range of voltages in response to a range of pressures on the trigger **326** and/or pedal **310**. In some examples, there may be more than two receptacles **432**, prongs **330**, and/or inputs **452**, and/or an entirely different implementation.

(60) FIGS. **5A** and **5B** show examples of another example weld module **500**. While, in the examples of FIGS. **5A** and **5B**, the weld module **500** does not include the plug connector **408** or fixture connector **410** of the weld module **400**, the weld module **500** does share similarities with weld module **400**. For example, the weld module **500** includes a housing **402**, similar to the weld module **400**. As shown, the housing **402** of the weld module **500** includes a generally cylindrical base **502** configured for connection to a cap **504**. The cap **504** includes an aperture **506** through which an on/off switch **530** (e.g., of the UI **418**) may extend. In some examples, the aperture **506** may instead be used for another input/output of the UI **418**, and/or for the port **406**. In the example of FIG. a hollow chamber **508** configured to retain a circuit board **510** of the weld module **500** is formed between the cap **504** and base **502**. As shown, the circuit board **510** includes a terminal **524** configured to receive a battery (not shown) that may act as a power source **420** to power electrical elements of the circuit board **510**. In some examples, the circuit board **510** may include and/or implement the electrical elements of the weld module **500**. In some examples, the electrical elements of the weld module **500** may include some or all of the previously described electrical elements of the weld module **400** (e.g., UI **418**, vibrator(s) **416**, sensor(s) **414**, power source **420**, illuminator(s) **412**, communication circuitry **422**, control circuitry **424**, and/or logic circuit **450**).

(61) In the examples of FIGS. **5A** and **5B**, the circuit board **510** is generally circular, and includes protrusions **512** formed on opposite sides of the circuit board **510**. Complementary slots **514** configured to receive the protrusions **512** are formed in the base **502**. The slots **514** terminate at a shelf **516**. The shelf **516** narrows the diameter of the chamber **508** to less than that of the circuit board **510**, so as to retain the circuit board **510** within the chamber **508**. Stanchions **518** of the cap **504** are positioned to fit within the slots **514** of the base **502** as well, so as to secure the circuit board **510** against movement. Holes **520** on the cap **504** and base **502** align to fit fasteners (not shown) that

securely couple the cap **504** to the base **502**.

(62) In the examples of FIGS. 5A and 5B, the base **502** is further formed with the socket connector **404**. As shown, the diameter of the socket connector **404** is less than that of the base **502** and cap **504**. As shown, the socket connector **404** is configured to accept a European style plug **304a**. Thus, the socket connector **404** has four receptacles **432** in conformance with the configuration of the plug **304a**. In the examples of FIGS. 5A and 5B, the socket connector **404** is formed with connection features **522** (i.e., screw threads) configured to engage with complementary features of the plug **304a**.

(63) FIGS. 6A-8B show examples of an alternative example weld module **800**. In some examples, the weld module **800** may be configured to provide any of the functions, and/or include any of the features, discussed above with reference to the weld modules **400** and **500**. In some examples, the weld module **800** may be configured for use with a mock welding tool **600**, rather than a live welding tool **308** like the weld modules **400** and **500**. In some examples, specialized mock welding tools may be a better option than live welding tools. For instance, where conventional live welding tools are needed for live welding, it may be more efficient to use a mock welding tool rather than a live welding tool for weld training. However, the computing device **204** of the weld training system **200** may still need to know when a trigger of the welding tool is activated and/or deactivated in order to conduct a weld training simulation, regardless of whether a live or mock welding tool is used. Thus, in some examples, the weld module **800** is configured to communicate tool event information (e.g., trigger activation/deactivation) to communication circuitry **222** of the computing device **204** when a mock welding tool is used.

(64) In the example of FIG. 6A, the mock welding tool **600** is a mock welding torch configured for mock gas metal arc welding (GMAW). In some examples, the mock welding tool **600** may instead be a mock torch configured for mock gas tungsten arc welding (GTAW) or a mock gun configured for mock flux-cored arc welding (FCAW). As shown, the mock welding tool **600** has a nozzle **602** with markers **250** disposed on the nozzle **602**. The nozzle **602** is attached to a neck **604** that leads to a handle **606**. In some examples, the handle **606** and/or nozzle **602** may be weighted to add heft to the mock welding tool **600**, making the mock welding tool **600** feel heavier and/or more realistic. As shown, a trigger **626** is movably attached to the handle **606**. In some examples, activation (e.g., squeezing, moving, actuation, etc.) of the trigger **626** may close one or more switches (e.g., switch **460**), while deactivation of the trigger **626** may open the switch(es).

(65) In the example of FIG. 6A, the alternative weld module **800** is attached to the mock welding tool **600** at an end **608** of the handle **606**, opposite the neck **604**. In live welding tools (e.g., the welding tool **308a** and/or **308d**), this end **608** is where a cord might extend out of the welding tool, leading to a plug **304**. One of the benefits of using a mock welding tool **600**, as opposed to a live welding tool, is that there is no need for an inconvenient cord that can get tangled or a cumbersome plug **304**. Because there is no cord or plug **304** for the mock welding tool **600**, the weld module **800** may be conveniently attached to the end of the handle **606** of the welding tool **600**.

(66) Despite the lack of a cord or plug **304**, the weld module **800** may still be in electrical communication with a switch **460** activated by the trigger **626**. For example, the mock welding torch **600** may include an internal plug similar to plug **304** that is configured to connect to a socket connector **804** of the weld module **800** (see, e.g., FIG. 8A). In some examples, the mock welding torch **600** may include internal wiring directly connecting a switch **460** activated by the trigger **626** to the weld module **800** (e.g., via socket connector **804** and/or some other part of the weld module **800**). Thus, an electrical connection between the switch **460** and the weld module **800** may still be made, even in the absence of an external cord and plug **304**.

(67) FIGS. 6B-8A show how the weld module **800** may be integrally coupled to the end of the welding tool **600**. In some examples, the weld module **800** may be integrally molded with an end of the handle **606** of the welding tool **600**. In some examples, the weld module **800** and handle **606** of the mock welding tool **600** may have complementary connecting and/or locking features that facilitate connection and/or interlocking of the weld module **800** and handle **606**. In some examples, a separate panel **700** additionally secures the weld module **800** to the handle **606**.

(68) FIG. 8A shows the connecting and/or locking features of the weld module **800**. In particular, FIG. 8A shows several protuberances **808** protruding from an interior surface of a connecting portion **806** of a housing **802** of the weld module **800**. As shown, the protuberances **808** are spaced approximately ninety degrees apart. While only two protuberances **808** are shown in the example of FIG. 8A due to the view, in some examples, there may be more protuberances **808**, such as, for example, four protuberances **808** equally spaced around the interior of the connecting portion **806**. In some examples, the protuberances **808** of the weld module **800** may be used as connecting and/or locking mechanisms configured to connect and/or interlock with complementary connecting and/or locking mechanisms of the handle **606**.

(69) In the example of FIG. 6A, the handle **606** of the mock welding tool **600** has a connecting end **608** that is generally cylindrical. As shown, the connecting end **608** includes several channels **610** formed in the outer surface of the connecting end **608**. Each channel **610** has a first portion and second portion formed at right angles to one another, providing an L shape. As shown, the channels **610** are spaced approximately ninety degrees apart. While

only two channels **610** are shown in the example of FIG. **6B** due to the view, in some examples, there may be more channels **610**, such as, for example, four channels equally spaced around the exterior surface of the connecting end **608**. In some examples, the channels **610** of the connecting end **608** may be complementary to the protuberances **808** of the weld module **800**.

(70) In some examples, the weld module **800** may be attached to the handle **606** by aligning the protuberances **808** with the channels **610**, pushing the weld module **800** and handle **606** together, and then rotating the weld module **800** with respect to the handle **606**. When the channels **610** and protuberances **808** are aligned and the weld module **800** and handle **606** are moved together, the protuberances **808** may move along the first portion of the channels **610**. Subsequently twisting or rotating the weld module **800** relative to the handle **606** may move the protuberances **808** along the second portion of the channel **610**. While in the second portion of the channels **610**, the frictional fit of the protuberances **808** within the channels **610** may prevent the weld module **800** from uncoupling from the handle **606**.

(71) In the examples of FIG. **6A-6B**, the mock welding tool **600** also includes a panel **700** to secure the weld module **800** in place against accidental rotation and/or removal from the handle **606**. As shown, the panel **700** is a solid, generally elongated, and curved piece. In some examples, the panel **700** may be a piece of plastic. As shown, the curvature of the panel **700** at an elongated first portion **702** is generally complementary to the curvature of the handle **606**. The curvature of the panel **700** at a hemispherical second portion **704** is generally complementary to the curvature of the connecting portion **806** of the weld module **800**. In some examples, the second portion **704** of the panel **700** is configured to fit over and/or frictionally retain in place the connecting portion **806** of the weld module **800** when the weld module **800** is connected to the handle **606**.

(72) In the example of FIG. **6B**, a recessed portion **612** is formed on a rear of the handle **606**, proximate the connecting end **608**. The recessed portion **612** is shaped complementary to the panel **700**, and is configured to receive the panel **700**. As shown, the recessed portion **612** includes a pattern of indents **614** and holes **616** arranged symmetrically about a groove **618** that runs lengthwise down the recessed portion **612** of the handle **606**. In some examples, the groove **618**, indents **614**, and/or holes **616** of the recessed portion **612** may comprise coupling features configured to interface with complementary coupling features of the panel **700**, so as to secure the panel **700** to the handle **606**.

(73) FIG. **7** shows a view of an underside of the panel **700**. As shown, the underside of the panel **700** includes a spine **706** extending along a length of the panel **700** through an approximate center. Ribs **708** are arranged along the spine **706**, with each rib **708** extending perpendicular to the spine **706** such that approximately equal portions of each rib **708** extend from opposite sides of the spine **706**. Proximate an inflection point of the panel **700**, where the elongated first portion **702** begins to flare out to the hemispherical shape of the second portion **704**, there are formed several pairs of tabs **710** arranged along opposite edges of the underside of the panel **700**. In some examples, the spine **706**, ribs **708**, and/or tabs **710** of the panel **700** formed on the underside of the panel **700** may comprise complementary coupling features configured to interface with coupling features of the handle **606**, so as to secure the panel **700** to the handle **606** (and secure the handle **606** to the weld module **800**).

(74) FIGS. **8A-8B** show the weld module **800** with a cover **810** removed from the housing **802**. As shown, the housing **802** of the weld module **800** is generally hollow and cylindrical. The housing **802** includes the connecting portion **806** and a base **812** that has a diameter that is larger than that of the connecting portion **806**. The base **812** includes receptacles **814** having apertures **815** configured to receive fasteners **816**. When the fasteners **816** are inserted through wings **818** of the cover **810** they may be used to connect the cover **810** to the housing **802** via the receptacles **814**. In the example of FIG. **8B**, the cover **810** is shown disconnected from the housing **802**, revealing a circuit board **820** fit into a hollow chamber in the base **812** of the housing **802**.

(75) In the example of FIGS. **8A-8B**, the circuit board **820** is similar to the circuit board **510** of the weld module **500**. For example, the circuit board **820** is also generally circular, with protrusions **813** formed on opposite sides of the circuit board **820**. Complementary slots **817** that receive the protrusions **815** are formed in the base **812**. In some examples, the base **812** may also have a similar shelf supporting the circuit board **820**. Stanchions **822** of the cover **810** are positioned to fit within the slots **817** of the base **812** as well, so as to secure the circuit board **820** against movement. In the example of FIG. **8B**, the circuit board **820** further includes a terminal **824** configured to receive a battery (not shown) that may act as a power source **420** to power electrical elements of the circuit board **820**. In some examples, the circuit board **820** may include and/or implement the electrical elements of the weld module **800**. In some examples, the electrical elements of the weld module **800** may include some or all of the electrical elements of the weld module **400** (e.g., UI **418**, vibrator(s) **416**, sensor(s) **414**, power source **420**, illuminator(s) **412**, communication circuitry **422**, control circuitry **424**, and/or logic circuit **450**).

(76) In the example of FIG. **8B**, the circuit board **820** also includes an illuminator **826** which may be similar or identical to the illuminator **412** of the weld module **400**. The circuit board **820** further includes a switch **830** that may be used as an input mechanism of the UI **418**. As shown, the cover **810** includes a window **832** through which the switch **830** may extend, and a port **834** through which illumination of the illuminator **826** may be seen. The

cover **810** also includes an identifier **836** that may be used to assist with communicative pairing of the weld module **800** with the computing device **204**. As shown, the identifier **836** is a QR code, though, in some examples, the identifier **836** may instead be a bar code and/or serial number.

(77) FIG. **9** is a flowchart illustrating an example control process **900** that may be used with any of the weld modules **400**, **500**, **800**. In some examples, some or all of the control process **900** may be implemented in machine readable instructions stored in memory **426** and/or executed by the one or more processors **428**. In some examples, some or all of the control process **900** may be implemented in analog and/or discrete circuitry of the control circuitry **424**.

(78) At block **902**, the control process **900** receives one or more signals. In some examples, the signal(s) may be received from a welding tool **308** or **600**, such as, for example, via the connection of plug **304** and socket connector **404** or **804**. For example, the signal(s) may be indicative of a trigger **326**, trigger **626**, and/or pedal **310** activation, deactivation, and/or pressure. In some examples, the signal(s) may be received from the port **406**, the UI **418**, and/or the communication circuitry **422**. For example, the signal(s) may be indicative of a communication from communication circuitry **222** of the computing device **204**, communication from some device attached via port **406**, and/or an input from the user (e.g., to simulate a tool event).

(79) In the example of FIG. **9**, the control process **900** determines whether the signal(s) is indicative of a tool event at block **904**. If not, then the control process **900** returns to block **902**. If so, then the control process proceeds to block **906**, where the control process **900** determines the type of tool event. As shown, the control process **900** proceeds to block **908** after block **906**.

(80) In the example of FIG. **9**, the control process **900** emits one or more control signals based on the tool event (and/or type of tool event) at block **908**. In some examples, the control signal(s) may be to the communication circuitry **422**. For example, the control signal(s) may be indicative of the tool event (and/or type of tool event) so that the communication circuitry **422** can send an appropriate communication signal to the computing device **204** indicative of the tool event (and/or type of tool event). In some examples, the communication circuitry **422** may additionally (or alternatively) send sensor **414** information to the computing device **204**. In some examples, the illuminator(s) **412** may be controlled to light up and/or blink when the communication circuitry **422** is transmitting and/or receiving information, so as to provide a visual indication to the user. In some examples, the computing device **204** may use the tool event (and/or tool event type) information, and/or sensor information, to conduct the weld training simulation. For example, in response to one or more communication signals indicating a trigger **326**, trigger **826**, or pedal **310** activation or deactivation, the computing device **204** may render appropriate virtual objects (e.g., virtual arc, virtual weld bead, etc.) based on set welding parameters and/or a target training activity.

(81) In some examples, the control signal(s) emitted at block **908** may be to the UI **418** to display and/or otherwise output certain information (e.g., status information). In some examples, the control signal(s) may be to the vibrator(s) **416**, to initiate a vibration at a certain frequency and/or amplitude based on type of tool event and/or one or more simulation characteristics stored in memory, set via the UI **418**, and/or communicated from the computing device **204**. In some examples, simulation characteristics may include, for example, weld settings (e.g., current, voltage, wire feed speed, etc.), arc properties, workpiece properties, difficulty settings, and/or other appropriate settings of the simulation. In some examples, the control signal(s) may be to the illuminator(s) **412** to light up and/or blink to indicate the tool event (and/or type of tool event). As shown, the control process **900** returns to block **902** after block **908**.

(82) As discussed above, the weld module **400** and weld module **500** present efficient and/or cost effective ways to adapt conventional weld equipment for training. Adapting conventional equipment may help to add to the realism and/or applicability of the training, while also saving on time and/or money. Alternatively, where specialized mock welding equipment is instead called for, the weld module **800** presents an effective means for adapting the specialized welding equipment for training. Thus, the present disclosure contemplates using weld modules to connect with conventional or specialized welding equipment, so as to integrate the welding equipment into a weld training system.

(83) The present methods and systems may be realized in hardware, software, and/or a combination of hardware and software. A typical combination of hardware and software may include a general-purpose computing system with a program or other code that, when being loaded and executed, controls the computing system such that it carries out the methods described herein. Another typical implementation may comprise an application specific integrated circuit or chip. Some implementations may comprise a non-transitory machine-readable (e.g., computer readable) medium (e.g., FLASH drive, optical disk, magnetic storage disk, or the like) having stored thereon one or more lines of code executable by a machine, thereby causing the machine to perform processes as described herein. As used herein, the term “non-transitory machine-readable medium” is defined to include all types of machine readable storage media and to exclude propagating signals.

(84) As used herein, “and/or” means any one or more of the items in the list joined by “and/or”. As an example, “x and/or y” means any element of the three-element set {(x), (y), (x, y)}. In other words, “x and/or y” means “one or

both of x and y". As another example, "x, y, and/or z" means any element of the seven-element set {(x), (y), (z), (x, y), (x, z), (y, z), (x, y, z)}. In other words, "x, y and/or z" means "one or more of x, y and z".

(85) As used herein, the terms "approximate" and/or "approximately," when used to modify or describe a value (or range of values), position, shape, orientation, and/or action, mean reasonably close to that value, range of values, position, shape, orientation, and/or action. Thus, the examples described herein are not limited to only the recited values, ranges of values, positions, shapes, orientations, and/or actions but rather should include reasonably workable deviations.

(86) As utilized herein, the terms "e.g.," and "for example" set off lists of one or more non-limiting examples, instances, or illustrations.

(87) As used herein, the terms "couple," "coupled," "attach," "attached," "connect," and/or "connected" refer to a structural and/or electrical affixing, joining, fasten, linking, and/or other securing.

(88) As utilized herein the terms "circuits" and "circuitry" refer to physical electronic components (i.e. hardware) and/or any software and/or firmware ("code") which may configure the hardware, be executed by the hardware, and or otherwise be associated with the hardware. As used herein, for example, a particular processor and memory may comprise a first "circuit" when executing a first one or more lines of code and may comprise a second "circuit" when executing a second one or more lines of code.

(89) As utilized herein, circuitry is "configured" to perform a function whenever the circuitry comprises the necessary hardware and code (if any is necessary) to perform the function, regardless of whether performance of the function is disabled or not enabled (e.g., by a user-configurable setting, factory trim, etc.).

(90) As used herein, a control circuit may include digital and/or analog circuitry, discrete and/or integrated circuitry, microprocessors, DSPs, etc., software, hardware and/or firmware, located on one or more boards, that form part or all of a controller, and/or are used to control a welding process, and/or a device such as a power source or wire feeder.

(91) As used herein, the term "processor" means processing devices, apparatus, programs, circuits, components, systems, and subsystems, whether implemented in hardware, tangibly embodied software, or both, and whether or not it is programmable. The term "processor" as used herein includes, but is not limited to, one or more computing devices, hardwired circuits, signal-modifying devices and systems, devices and machines for controlling systems, central processing units, programmable devices and systems, field-programmable gate arrays, application-specific integrated circuits, systems on a chip, systems comprising discrete elements and/or circuits, state machines, virtual machines, data processors, processing facilities, and combinations of any of the foregoing. The processor may be, for example, any type of general purpose microprocessor or microcontroller, a digital signal processing (DSP) processor, an application-specific integrated circuit (ASIC). The processor may be coupled to, and/or integrated with a memory device.

(92) As used, herein, the term "memory" and/or "memory device" means computer hardware or circuitry to store information for use by a processor and/or other digital device. The memory and/or memory device can be any suitable type of computer memory or any other type of electronic storage medium, such as, for example, read-only memory (ROM), random access memory (RAM), cache memory, compact disc read-only memory (CDROM), electro-optical memory, magneto-optical memory, programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically-erasable programmable read-only memory (EEPROM), a computer-readable medium, or the like.

(93) The term "power" is used throughout this specification for convenience, but also includes related measures such as energy, current, voltage, and enthalpy. For example, controlling "power" may involve controlling voltage, current, energy, and/or enthalpy, and/or controlling based on "power" may involve controlling based on voltage, current, energy, and/or enthalpy.

(94) As used herein, welding-type power refers to power suitable for welding, cladding, brazing, plasma cutting, induction heating, CAC-A and/or hot wire welding/preheating (including laser welding and laser cladding), carbon arc cutting or gouging, and/or resistive preheating.

(95) As used herein, a welding-type power supply and/or power source refers to any device capable of, when power is applied thereto, supplying welding, cladding, brazing, plasma cutting, induction heating, laser (including laser welding, laser hybrid, and laser cladding), carbon arc cutting or gouging and/or resistive preheating, including but not limited to transformer-rectifiers, inverters, converters, resonant power supplies, quasi-resonant power supplies, switch-mode power supplies, etc., as well as control circuitry and other ancillary circuitry associated therewith.

(96) While the present method and/or system has been described with reference to certain implementations, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the present method and/or system. For example, blocks and/or components of disclosed examples may be combined, divided, re-arranged, and/or otherwise modified. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present disclosure without departing from its scope. Therefore, the present method and/or system are not limited to the particular

implementations disclosed. Instead, the present method and/or system will include all implementations falling within the scope of the appended claims, both literally and under the doctrine of equivalents.

Claims

1. A detachable communication module for a welding tool, the detachable communication module comprising: a housing configured for attachment to a cable connector of a welding tool cable; and module circuitry attached to, or positioned within, the housing such that the module circuitry is placed in electrical communication with the cable connector when the cable connector is attached to the housing, the module circuitry being configured to: detect a tool event via the cable connector, and transmit a tool event signal to a weld training system that is separate from the detachable communication module in response to the tool event.
2. The detachable communication module of claim 1, wherein the tool event signal is indicative of a tool event type, the module circuitry being configured to determine the tool event type via the cable connector, the tool event type comprising an activation event, a deactivation event, a pressure increase event, or a pressure decrease event.
3. The detachable communication module of claim 2, wherein the module circuitry is configured to detect the tool event or determine a tool event type based on a change in voltage across the cable connector.
4. The detachable communication module of claim 1, wherein the module circuitry is configured to be communicatively paired with complementary communication circuitry via a wireless communication protocol.
5. The detachable communication module of claim 1, wherein the housing comprises: one or more receptacles configured to receive the cable connector; and a chamber configured to house the module circuitry, the one or more receptacles leading to the chamber.
6. The detachable communication module of claim 1, further comprising: an input mechanism in electrical communication with the module circuitry, the input mechanism configured to trigger a signal transmission by the module circuitry; and an output mechanism in electrical communication with the module circuitry, the output mechanism configured to indicate status or identification information.
7. The detachable communication module of claim 1, wherein the housing further comprises a housing connector configured for attachment to a clamp, clip, weight, or fixture.
8. The detachable communication module of claim 1, further comprising a vibrator in electrical communication with the module circuitry, the vibrator configured to activate in response to the module circuitry detecting the tool event, or in response to receipt of one or more welding parameters by the module circuitry.
9. The detachable communication module of claim 1, further comprising a port receptacle configured to provide power to the module circuitry.
10. The detachable communication module of claim 1, wherein the cable connector is configured for electrical connection with a piece of welding equipment, the piece of welding equipment comprising a welding-type power supply or a welding wire feeder, the detachable communication module further comprising an equipment connector configured for electrical connection with the piece of welding equipment.
11. A welding system, comprising: a welding tool; a welding tool cable attached to the welding tool, the welding tool cable comprising a cable connector configured for electrical connection to a piece of welding equipment; and a detachable communication module comprising: a housing configured for connection to the cable connector of the welding tool cable, and module circuitry attached to, or positioned within, the housing such that the module circuitry is in electrical communication with the cable connector when the housing attaches to the cable connector, the module circuitry being configured to: detect a tool event via the cable connector, and transmit a tool event signal to a weld training system that is separate from the detachable communication module in response to the tool event.
12. The welding system of claim 11, wherein the tool event signal is indicative of a tool event type, the module circuitry being configured to determine the tool event type via the cable connector, the tool event type comprising an activation event, a deactivation event, a pressure increase event, or a pressure decrease event.
13. The welding system of claim 12, wherein the module circuitry is configured to detect the tool event or determine a tool event type based on a change in voltage across the cable connector.
14. The welding system of claim 11, further comprising the weld training system, the weld training system comprising complementary communication circuitry communicatively paired with the module circuitry via a wireless communication protocol.
15. The welding system of claim 11, wherein the housing comprises: one or more receptacles configured to receive the cable connector, and a chamber configured to house the module circuitry, the one or more receptacles leading to the chamber.
16. The welding system of claim 11, further comprising: an input mechanism in electrical communication with the module circuitry, the input mechanism configured to trigger a signal transmission by the module circuitry, and an output mechanism in electrical communication with the module circuitry, the output mechanism configured to indicate status or identification information.

17. The welding system of claim 11, wherein the housing further comprises a housing connector configured for attachment to a clamp, clip, weight, or fixture.

18. The welding system of claim 11, further comprising a vibrator in electrical communication with the module circuitry, the vibrator configured to activate in response to the module circuitry detecting the tool event, or in response to receipt of one or more welding parameters by the module circuitry.

19. The welding system of claim 11, wherein the detachable communication module further comprises a port receptacle configured to provide power to the module circuitry.

20. The welding system of claim 1, wherein the piece of welding equipment comprises a welding-type power supply or a welding wire feeder, the detachable communication module further comprising an equipment connector further configured for electrical connection with the piece of welding equipment.
