

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384542
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Okado; Michihito et al.

Moving object

Abstract

A moving object includes a passenger cabin. The passenger cabin is defined by a first side wall and a second side wall. The first side wall is formed with a doorway through which passengers can enter and exit the passenger cabin. The moving object further includes a first seat disposed between a center line LA and the second side wall so as to face forward, the center line extending in a region between the first side wall and the second side wall, and a second seat disposed between the center line and the second side wall and disposed rearward of the first seat so as to face rearward. At least a part of the first seat and at least a part of the second seat overlap the doorway in a side view.

Inventors: Okado; Michihito (Wako, JP), Alcahud Guim; Victor (Wako, JP), Kanki; Takao (Wako, JP)

Applicant: HONDA MOTOR CO., LTD. (Tokyo, JP)

Family ID: 89834318

Assignee: HONDA MOTOR CO., LTD. (Tokyo, JP)

Appl. No.: 18/424044

Filed: January 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240262507 A1	Aug. 08, 2024

Foreign Application Priority Data

JP	2023-014320	Feb. 02, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: B64D11/06 (20060101)

U.S. Cl.:

CPC **B64D11/0601** (20141201); **B64D11/0638** (20141201);

Field of Classification Search

CPC: B64D (11/0601); B64D (11/0638); B64D (11/0605); B64D (11/0606); B64D (11/06);
 B60N (2/01)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2710731	12/1954	Bright	244/118.6	B64D 11/0023
10919631	12/2020	Scoley	N/A	B64C 1/143
11136105	12/2020	Moore	N/A	B64C 1/1438
2009/0050740	12/2008	Saint-Jalmes et al.	N/A	N/A
2009/0173825	12/2008	Dehn	244/129.5	B64C 1/1438
2018/0312082	12/2017	Lalague	N/A	B60N 2/01
2019/0039712	12/2018	Moore	N/A	B64D 11/0601
2020/0130837	12/2019	Scoley	N/A	B64D 11/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108791502	12/2017	CN	N/A
3 378 770	12/2017	EP	N/A

OTHER PUBLICATIONS

Extended European Search Report dated Jul. 2, 2024 issued in corresponding European Application No. 24155158.9; 6 pages. cited by applicant

Primary Examiner: Benedik; Justin M

Attorney, Agent or Firm: Rankin, Hill & Clark LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is based upon and claims the benefit of priority from Japanese Patent Application No. 2023-014320 filed on Feb. 2, 2023, the contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

(2) The present disclosure relates to a moving object.

Description of the Related Art

(3) Moving objects such as an eVTOL (electronic Vertical Take-Off and Landing aircraft) that carries passengers are known. U.S. Pat. No. 11,136,105 B2 discloses an eVTOL interior.

SUMMARY OF THE INVENTION

(4) A more suitable moving object is desired.

(5) An object of the present invention is to solve the above-mentioned problem.

(6) A first aspect of the present invention is a moving object including a passenger cabin, wherein the passenger cabin is defined by a first side wall positioned on one side with respect to a center line of the moving object and a second side wall positioned on another side with respect to the center line, the center line extending in a front-rear direction, a doorway through which a passenger enters and exits the passenger cabin is formed in the first side wall, wherein the moving object further includes: a first seat positioned between the center line and the second side wall and disposed to face forward; and a second seat positioned between the center line and the second side wall, and rearward of the first seat, the second seat being disposed to face rearward, and wherein at least a part of the first seat and at least a part of the second seat overlap the doorway in a side view.

(7) According to the present invention, a more suitable moving object is provided.

(8) The above and other objects features and advantages of the present invention will become more apparent from the following description when taken in conjunction with the accompanying drawings in which a preferred embodiment of the present invention is shown by way of illustrative example.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a moving object according to an embodiment;

(2) FIG. 2 is a top view looking down on a passenger cabin and a cockpit;

(3) FIG. 3 is a view showing a shielding device provided in the passenger cabin; and

(4) FIG. 4 is a view showing a shielding device provided in the passenger cabin.

DETAILED DESCRIPTION OF THE INVENTION

(5) The eVTOL according to U.S. Pat. No. 11,136,105 B2 is provided with a plurality of passenger seats. The plurality of passenger seats are densely arranged. In this case, the passengers' eyes are likely to meet with each other. As a result, the passengers may feel some other passenger watching her/him, and may not be able to get relaxed sufficiently.

(6) With the above situation in mind, an embodiment is described below.

Embodiment

(7) FIG. 1 is a perspective view of a moving object **10** according to the present embodiment. Note that FIG. 1 shows a front-rear direction Z (Z1, Z2), a vertical direction Y (Y1, Y2), and a widthwise direction X. The front-rear direction Z, the vertical direction Y, and the widthwise direction X are orthogonal to each other. The downward direction Y2 indicates the gravity direction.

(8) The moving object **10** is a vehicle that carries passengers. In the present embodiment, a case where the moving object **10** is an eVTOL will be described, but the present invention is not limited thereto. Note that the eVTOL belongs to an aircraft.

(9) The moving object **10** includes a fuselage (body) **12**. The moving object **10**, which is an eVTOL, may further include a main wing **14**, which is a fixed wing, a front wing **16** disposed forward of the main wing **14**, and a plurality of electric rotary wings **18**, but detailed description thereof will be omitted.

(10) A doorway (entrance/exit) **20** is formed in the fuselage **12**. The doorway **20** is an opening formed such that passengers and crews can get on and off the moving object **10**. The number of the doorways **20** formed in the fuselage **12** is preferably one, but is not limited thereto. By minimizing the number of the doorways **20**, the weight of the moving object **10** can be suppressed.

(11) The doorway **20** is provided with a doorway door **22** so as to be openable and closable. When the doorway door **22** is in an open state, passengers are allowed to get on and off the moving object **10** via the doorway **20**. When the doorway door **22** is in a closed state, passengers are prohibited from getting on and off the moving object **10** via the doorway **20**. The doorway door **22** shown in FIG. **1** is in a closed state. The doorway door **22** is opened and closed by sliding in the front-rear direction **Z**, for example, but is not limited thereto. The doorway door **22** may be a single swing door or a double swing door.

(12) The fuselage **12** further includes a passenger cabin **28** and a cockpit **30**. The passenger cabin **28** and the cockpit **30** are formed inside the fuselage **12**.

(13) FIG. **2** is a top view looking down on the passenger cabin **28** and the cockpit **30**. FIG. **3** is a view showing a shielding device **50** provided in the passenger cabin **28**.

(14) The fuselage **12** has a first side wall **24** and a second side wall **26**. The first side wall **24** is a side wall positioned on one side with respect to the center line **LA** of the fuselage **12** (the moving object **10**). The second side wall **26** is a side wall located on the other side with respect to the center line **LA**. The first side wall **24** and the second side wall **26** define the passenger cabin **28** provided in the moving object **10**. Although not shown, one or more windows may be provided in the first side wall **24** and the second side wall **26** as appropriate. The center line **LA** is parallel to the front-rear direction **Z** (see also FIG. **1**).

(15) The doorway **20** described above is formed in the first side wall **24** of the fuselage **12**. Passengers can get on the moving object **10** through the doorway **20** to enter the passenger cabin **28**.

(16) The cockpit **30** is located in front of the passenger cabin **28**, but is not limited thereto. The cockpit **30** includes, for example, a pilot's seat **32** and an operation panel **34**. A crew who operates the moving object **10** sits on the pilot's seat **32**. The operation panel **34** is operated to operate the moving object **10**.

(17) The cockpit **30** and the passenger cabin **28** communicate with each other via a communication passage **36**. The crew can move between the cockpit **30** and the passenger cabin **28** through the communication passage **36**. With this configuration, it is not necessary to provide a doorway dedicated for the crew, separately from the above-described doorway **20**. A door may be provided for the communication passage **36**.

(18) The communication passage **36** is preferably located between a center aisle **46** described later and the first side wall **24** or between the center aisle **46** and the second side wall **26**. The reason for this will be described later. In the present embodiment, the communication passage **36** is located between the center aisle **46** and the second side wall **26**.

(19) The passenger cabin **28** is provided with a first seat **38**, a second seat **40**, a third seat **42**, and a fourth seat **44**. The first seat **38** is a seat on which a first passenger sits. The second seat **40** is a seat on which a second passenger sits. The third seat **42** is a seat on which a third passenger sits. The fourth seat **44** is a seat on which a fourth passenger sits. A power machine room (not shown) can be provided behind the passenger cabin **28**. The power machine room can include equipment for driving the moving object **10**. The equipment may include, for example, an engine, a motor for power generation, a battery, and the like.

(20) The passenger cabin **28** also has the center aisle **46**. The center aisle **46** extends along the center line **LA**. In the present embodiment, the center line of the center aisle **46** and the center line **LA** coincide with each other, but the present invention is not limited thereto.

(21) The crew can pass through the center aisle **46** to reach the communication passage **36** described above.

(22) When the communication passage **36** is located between the center aisle **46** and the first side wall **24** or between the center aisle **46** and the second side wall **26**, the position of the communication passage **36** in the widthwise direction **X** is different from the position of the center aisle **46** in the widthwise direction **X**. Accordingly, a part of the flow line **FL** of the crew moving

from the doorway **20** to the cockpit **30** deviates from the center aisle **46** (see also FIG. 2). With this configuration, the crew cannot reach the cockpit **30** by simply moving in the forward direction **Z1** along the center aisle **46**. As a result, the possibility that the passengers may stray into the cockpit **30** is reduced.

(23) As described above, in the present embodiment, the communication passage **36** is located between the center line LA and the second side wall **26**. A space **48** may be formed between the communication passage **36** and the first side wall **24**.

(24) The space **48** may be used as a machine room **481**. The machine room **481** is provided with, for example, a control computer for controlling the moving object **10**. The space **48** may be used as a storage space for storing luggage of passengers. A door **482** for the space **48** (machine room **481**) may be provided in the cockpit **30**, for example, but is not limited thereto.

(25) The first seat **38** and the second seat **40** are located between the center line LA and the second side wall **26**. More specifically, the first seat **38** and the second seat **40** are located between the center aisle **46** and the second side wall **26**. The first seat **38** is arranged to face forward. The second seat **40** is disposed rearwardly of the first seat **38** to face rearward.

(26) With this configuration, the first passenger seated on the first seat **38** and the second passenger seated on the second seat **40** do not face each other. Therefore, the first passenger's eyes and the second passenger's eyes are unlikely to meet. Note that an arrow A1 indicating the orientation of the first seat **38** and an arrow A2 indicating the orientation of the second seat **40** are shown in FIG. 2. The orientation of the first seat **38** can be specified by the orientation of a backrest **38b** of the first seat **38**. The orientation of the second seat **40** can be specified by the orientation of a backrest **40b** of the second seat **40**.

(27) At least a part of the first seat **38** overlaps the doorway **20** in a side view. At least a part of the second seat **40** also overlaps the doorway **20** in the side view.

(28) With this configuration, the first passenger and the second passenger can enter and exit the passenger cabin **28** via the doorway **20** without caring about each other's eyes. That is, the doorway **20** and the first seat **38** are separated from each other in the widthwise direction X and overlap each other in a side view. With this configuration, the doorway **20** is easily in the blind spot of the first passenger seated on the first seat **38**. Thus, when the first passenger is seated in the first seat **38**, the second passenger can enter and exit the passenger cabin **28** through the doorway **20** without caring about the first passenger's eyes. The doorway **20** and the second seat **40** are separated from each other in the widthwise direction X and overlap each other in a side view. With this configuration, the doorway **20** is easily in the blind spot of the second passenger seated on the second seat **40**. Thus, when the second passenger is seated in the second seat **40**, the first passenger can enter and exit the passenger cabin **28** through the doorway **20** without caring about the second passenger's eyes.

(29) The third seat **42** and the fourth seat **44** are located between the center line LA and the first side wall **24**. More specifically, the third seat **42** and the fourth seat **44** are located between the center aisle **46** and the first side wall **24**. The third seat **42** is positioned on the front side of the doorway **20**. On the other hand, the fourth seat **44** is positioned on the rear side of the doorway **20**.

(30) The orientation of the third seat **42** in the top view is obliquely rearward. On the other hand, the orientation of the fourth seat **44** in the top view is obliquely forward. Note that an arrow A3 indicating the orientation of the third seat **42** and an arrow A4 indicating the orientation of the fourth seat **44** are shown in FIG. 2. The orientation of the third seat **42** can be specified by the orientation of a backrest **42b** of the third seat **42**. The orientation of the fourth seat **44** can be specified by the orientation of a backrest **44b** of the fourth seat **44**. The position of the third seat **42** in the widthwise direction X is the same as the position of the fourth seat **44** in the widthwise direction X.

(31) With this configuration, the third passenger seated on the third seat **42** and the fourth passenger seated on the fourth seat **44** are unlikely to face each other. Therefore, the third

passenger's eyes and the fourth passenger's eyes are unlikely to meet.

(32) It is preferable that one of the third seat **42** and the fourth seat **44** is inclined toward the first side wall **24** in a top view, and the other of the third seat **42** and the fourth seat **44** is inclined toward the second side wall **26** in the top view.

(33) With this configuration, the legs of the third passenger seated on the third seat **42** and the legs of the fourth passenger seated on the fourth seat **44** are less likely to interfere with each other. FIG. 2 shows the third seat **42** inclined toward the first side wall **24** in a top view and the fourth seat **44** inclined toward the second side wall **26** in the top view.

(34) As mentioned above, the center aisle **46** is located between the first seat **38** and the third seat **42**. Therefore, the distance between the first seat **38** and the third seat **42** in the widthwise direction X is at least equal to or larger than the width W**46** of the center aisle **46**.

(35) Thus, the third passenger seated in the third seat **42** is less likely to be in the field of view of the first passenger seated in the first seat **38**. Similarly, the first passenger seated in the first seat **38** is less likely to be in the field of view of the third passenger seated in the third seat **42**. Therefore, the first passenger's eyes and the third passenger's eyes are less likely to meet.

(36) It is more preferable that at least a part of the first seat **38** and at least a part of the third seat **42** overlap each other in a side view. This makes it easier for the third passenger to be in the blind spot of the first passenger, and makes it easier for the first passenger to be in the blind spot of the third passenger. As a result, the possibility that the first passenger's eyes and the third passenger's eyes may meet is further reduced.

(37) As described above, the third seat **42** is positioned in front of the doorway **20** and faces obliquely rearward. Therefore, the third passenger who has entered the passenger cabin **28** through the doorway **20** can sit on the third seat **42** without going around to the front of the third seat **42**. In other words, the third passenger can sit in the third seat **42** without passing by the first seat **38**.

(38) In this way, the third passenger is less likely to be in the field of view of the first passenger seated in the first seat **38**.

(39) As mentioned above, the center aisle **46** is located between the second seat **40** and the fourth seat **44**. Therefore, the distance between the second seat **40** and the fourth seat **44** in the widthwise direction X is at least equal to or greater than the width of the center aisle **46**.

(40) In this way, the fourth passenger seated on the fourth seat **44** is less likely to be in the field of view of the second passenger seated on the second seat **40**. Similarly, the second passenger seated in the second seat **40** is less likely to be in the field of view of the fourth passenger seated in the fourth seat **44**. Therefore, the second passenger's eyes and the fourth passenger's eyes are less likely to meet.

(41) It is more preferable that at least a part of the second seat **40** and at least a part of the fourth seat **44** overlap each other in the side view. This makes it easier for the fourth passenger to be in the blind spot of the second passenger, and makes it easier for the second passenger to be in the blind spot of the fourth passenger. As a result, the possibility that the second passenger's eyes and the fourth passenger's eyes may meet is further reduced.

(42) As described above, the fourth seat **44** is positioned rearward of the doorway **20** and faces obliquely forward. Therefore, the fourth passenger who has entered the passenger cabin **28** through the doorway **20** can sit on the fourth seat **44** without going around to the rear of the fourth seat **44**. In other words, the fourth passenger can sit on the fourth seat **44** without passing by the second seat **40**.

(43) In this way, the fourth passenger is less likely to be in the field of view of the second passenger seated in the second seat **40**.

(44) Moreover, since the third passenger does not need to go around to the front of the third seat **42** when sitting on the third seat **42**, it is not necessary to add a passage between the third seat **42** and the first side wall **24**. Similarly, since the fourth passenger does not need to go around to the rear of the fourth seat **44** when sitting on the fourth seat **44**, it is not necessary to add a passage between

the fourth seat **44** and the first side wall **24**. As a result, it is possible to suppress an increase in the dimension of the fuselage **12** in the widthwise direction X due to the addition of the passage.

(45) FIG. **4** is a view showing a shielding device **50** provided in the passenger cabin **28**.

(46) The moving object **10** further includes a shielding device **50**. The shielding device **50** includes a first partition **52**, a second partition **54**, and a main body **56**. The first partition **52** is a partition for shielding between the first seat **38** and the third seat **42**. The second partition **54** is a partition for shielding between the second seat **40** and the fourth seat **44**. The first partition **52** and the second partition **54** can be retracted in the main body **56**. FIG. **4** shows the shielding device **50** with the first partition **52** and the second partition **54** retracted in the main body **56**.

(47) The main body **56** includes a housing capable of accommodating the first partition **52** and the second partition **54**, and an actuator (not shown). The actuator deploys (projects) the first partition **52**. That is, the first partition **52** accommodated in the main body **56** moves in the front direction **Z1** in response to the driving of the actuator.

(48) As a result, as shown in FIGS. **2** and **3**, the first partition **52** shields between the first seat **38** and the third seat **42**. As a result, the possibility that the first passenger's eyes and the third passenger's eyes may meet is further reduced. The first partition **52** positioned between the first seat **38** and the third seat **42** can be accommodated in the main body **56** again by moving in the rearward direction **Z2** in response to the driving of the actuator.

(49) The second partition **54** is also deployed (projected) by an actuator (not shown) provided in the main body **56**. That is, the second partition **54** accommodated in the main body **56** moves in the rearward direction **Z2** in response to the driving of the actuator.

(50) As a result, as shown in FIGS. **2** and **3**, the second partition **54** shields between the second seat **40** and the fourth seat **44**. As a result, the possibility that the second passenger's eyes and the fourth passenger's eyes may meet is further reduced. The second partition **54** positioned between the second seat **40** and the fourth seat **44** can be accommodated in the main body **56** again by moving in the front direction **Z1** in response to the driving of the actuator.

(51) The actuator provided in the main body **56** includes, for example, a motor, but is not limited thereto. The actuator can be controlled by a computer (not shown). The computer (not shown) may be provided in the moving object **10**. The actuator may be driven in response to operation of a switch appropriately disposed around the first seat **38** or the second seat **40**. A first actuator for moving the first partition **52** and a second actuator for moving the second partition **54** may be provided in the main body **56**. In addition, one of the first partition **52** and the second partition **54** may be omitted.

(52) As shown in FIG. **2**, the moving object **10** further includes a first table **58**, a second table **60**, a third table **62**, and a fourth table **64**. Each of the first table **58** and the second table **60** is, for example, a rectangular table, but is not limited thereto. Each of the third table **62** and the fourth table **64** is a circular table, but is not limited thereto. At least one of the first table **58**, the second table **60**, the third table **62**, or the fourth table **64** may be omitted.

(53) The first table **58** is a table used by the first passenger. The second table **60** is a table used by the second passenger. Each of the first table **58** and the second table **60** is, for example, a folding table that can be accommodated in the second side wall **26**.

(54) The second side wall **26** is provided with an accommodation portion (first accommodation portion) (not shown) capable of accommodating the first table **58**. The first accommodation portion is, for example, a concave portion capable of accommodating the folded first table **58**.

(55) The second side wall **26** is provided with an accommodation portion (second accommodation portion) (not shown) capable of accommodating the second table **60**. The second accommodation portion is, for example, a concave portion capable of accommodating the folded second table **60**.

(56) The third table **62** is a table used by the third passenger. The fourth table **64** is a table used by the fourth passenger. Each of the third table **62** and the fourth table **64** is, for example, a folding table that can be accommodated in the doorway door **22**.

(57) The doorway door **22** or the first side wall **24** is provided with an accommodation portion (third accommodation portion) (not shown) capable of accommodating the third table **62**. The third accommodation portion is, for example, a concave portion capable of accommodating the folded third table **62**.

(58) Further, the doorway door **22** or the first side wall **24** is provided with an accommodation portion (fourth accommodation portion) (not shown) capable of accommodating the fourth table **64**. The fourth accommodation portion is, for example, a concave portion capable of accommodating the folded fourth table **64**.

(59) The third table **62** and the fourth table **64** may be attached to the first side wall **24**.

APPENDIXES

(60) With respect to the above disclosure, the following appendixes are further disclosed.

Appendix 1

(61) The moving object (**10**) according to the present disclosure includes the passenger cabin (**28**). The passenger cabin is defined by the first side wall (**24**) positioned on one side with respect to the center line (LA) of the moving object and the second side wall (**26**) positioned on another side with respect to the center line, the center line extending in the front-rear direction (Z). The doorway (**20**) through which a passenger enters and exits the passenger cabin is formed in the first side wall. The moving object further includes: the first seat (**38**) located between the center line and the second side wall and disposed to face forward; and the second seat (**40**) positioned between the center line and the second side wall and disposed rearward of the first seat, the second seat being disposed to face rearward. At least a part of the first seat and at least a part of the second seat overlap the doorway in a side view. Thus, the first passenger seated on the first seat and the second passenger seated on the second seat do not face each other. Therefore, the first passenger's eyes and the second passenger's eyes are unlikely to meet.

Appendix 2

(62) The moving object according to Appendix 1 may further include the third seat (**42**) disposed between the center line and the first side wall, and on the front side of the doorway; and the fourth seat (**44**) disposed between the center line and the first side wall, and on the rear side of the doorway, wherein the third seat may face obliquely rearward in the top view, and the fourth seat may face obliquely forward in the top view. With this configuration, the third passenger is less likely to be in the field of view of the first passenger seated on the first seat, and the fourth passenger is less likely to be in the field of view of the second passenger seated on the second seat.

Appendix 3

(63) In the moving object according to Appendix 2, one of the third seat and the fourth seat may be inclined toward the first side wall in the top view, and another of the third seat and the fourth seat may be inclined toward the second side wall in the top view. With this configuration, the legs of the third passenger seated on the third seat and the legs of the fourth passenger seated on the fourth seat are less likely to interfere with each other.

Appendix 4

(64) The moving object according to any one of Appendixes 1 to 3 may further include the partition (**52, 54**) disposed at least one of between the first seat and the third seat or between the second seat and the fourth seat. This further reduces the possibility that the first passenger's eyes and the third passenger's eyes can meet, and further reduces the possibility that the second passenger's eyes and the fourth passenger's eyes can meet.

Appendix 5

(65) In the moving object according to any one of Appendixes 1 to 4, the passenger cabin may include the aisle extending along the center line, the moving object may further include the cockpit (**30**) disposed forward of the passenger cabin and communicating with the passenger cabin via the communication passage (**36**), and the position of the aisle in the widthwise direction (X) orthogonal to the front-rear direction may be different from the position of the communication passage in the

widthwise direction. Thus, the passenger doorway and the crew doorway are consolidated into one doorway, and the possibility that the passenger may get lost into the cockpit is reduced.

Appendix 6

(66) In the moving object according to any one of Appendixes 1 to 5, at least one of the first table (58) used by a passenger seated on the first seat or the second table (60) used by a passenger seated on the second seat may be attached to the second side wall. This can give facilities to passengers.

Appendix 7

(67) The moving object according to any one of Appendixes 1 to 6 may further include the doorway door (22) provided at the doorway, and at least one of the third table (62) used by a passenger seated on the third seat or the fourth table (64) used by a passenger seated on the fourth seat may be accommodated in the doorway door so as to be extractable. Thus, the third table and the fourth table do not hinder the passengers and the crew from getting on and off the moving object through the doorway.

Appendix 8

(68) In the moving object according to any one of Appendixes 1 to 7, the moving object may be an aircraft. The aircraft is, for example, an eVTOL, a small jet (airplane), a helicopter, or the like.

(69) Moreover, it should be noted that the present invention is not limited to the disclosure described above, but various configurations may be adopted therein without departing from the essence and gist of the present invention.

Claims

1. A moving object comprising a passenger cabin, wherein the passenger cabin is defined by a first side wall positioned on one side with respect to a center line of the moving object and a second side wall positioned on another side with respect to the center line, the center line extending in a front-rear direction, a doorway through which a passenger enters and exits the passenger cabin is formed in the first side wall, wherein the moving object further comprises: a first seat positioned between the center line and the second side wall and disposed to face forward; and a second seat positioned between the center line and the second side wall, and rearward of the first seat, the second seat being disposed to face rearward, and wherein at least a part of the first seat and at least a part of the second seat overlap the doorway in a side view so that the doorway is in a blind spot of a first passenger facing forward in the first seat and a second passenger facing rearward in the second seat.
2. The moving object according to claim 1, further comprising: a third seat disposed between the center line and the first side wall, and on a front side of the doorway; and a fourth seat disposed between the center line and the first side wall, and on a rear side of the doorway, wherein the third seat faces obliquely rearward in a top view, and the fourth seat faces obliquely forward in the top view.
3. The moving object according to claim 2, wherein one of the third seat and the fourth seat is inclined toward the first side wall in the top view, and another of the third seat and the fourth seat is inclined toward the second side wall in the top view.
4. The moving object according to claim 2, further comprising: a partition disposed at least one of between the first seat and the third seat or between the second seat and the fourth seat.
5. The moving object according to claim 2, further comprising: a doorway door provided at the doorway, wherein at least one of a third table used by a passenger seated on the third seat or a fourth table used by a passenger seated on the fourth seat is accommodated in the doorway door so as to be extractable.
6. The moving object according to claim 1, wherein at least one of a first table used by a passenger seated on the first seat or a second table used by a passenger seated on the second seat is attached to the second side wall.

7. The moving object according to claim 1, wherein the moving object is an aircraft.
 8. The moving object according to claim 1, wherein the passenger cabin includes an aisle extending along the center line, the moving object further comprises a cockpit disposed forward of the passenger cabin and communicating with the passenger cabin via a communication passage, and a position of the aisle in a widthwise direction orthogonal to the front-rear direction is different from a position of the communication passage in the widthwise direction.
 9. A moving object comprising a passenger cabin, wherein the passenger cabin is defined by a first side wall positioned on one side with respect to a center line of the moving object and a second side wall positioned on another side with respect to the center line, the center line extending in a front-rear direction, the passenger cabin includes an aisle extending along the center line, a doorway through which a passenger enters and exits the passenger cabin is formed in the first side wall, the moving object further comprises: a first seat positioned between the center line and the second side wall and disposed to face forward; a second seat positioned between the center line and the second side wall, and rearward of the first seat, the second seat being disposed to face rearward; and a cockpit disposed forward of the passenger cabin and communicating with the passenger cabin via a communication passage, at least a part of the first seat and at least a part of the second seat overlap the doorway in a side view, and a position of the aisle in a widthwise direction orthogonal to the front-rear direction is different from a position of the communication passage in the widthwise direction.
 10. The moving object according to claim 9, further comprising: a third seat disposed between the center line and the first side wall, and on a front side of the doorway; and a fourth seat disposed between the center line and the first side wall, and on a rear side of the doorway, wherein the third seat faces obliquely rearward in a top view, and the fourth seat faces obliquely forward in the top view.
 11. The moving object according to claim 10, wherein one of the third seat and the fourth seat is inclined toward the first side wall in the top view, and another of the third seat and the fourth seat is inclined toward the second side wall in the top view.
 12. The moving object according to claim 10, further comprising: a partition disposed at least one of between the first seat and the third seat or between the second seat and the fourth seat.
 13. The moving object according to claim 10, further comprising: a doorway door provided at the doorway, wherein at least one of a third table used by a passenger seated on the third seat or a fourth table used by a passenger seated on the fourth seat is accommodated in the doorway door so as to be extractable.
 14. The moving object according to claim 9, wherein at least one of a first table used by a passenger seated on the first seat or a second table used by a passenger seated on the second seat is attached to the second side wall.
 15. The moving object according to claim 9, wherein the moving object is an aircraft.
-