

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281007

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Fan; Zhilin et al.

TOWEL HEATING DEVICE

Abstract

A foldable towel heating device includes: a rigid shell; a flexible connection member, connected to the rigid shell, wherein, the flexible connection member and the rigid shell cooperatively encloses to form a receiving chamber, the rigid shell or the flexible connection member defines an opening communicating with the receiving chamber; and a heating assembly, configured to heat the receiving chamber, wherein, the heating assembly is disposed at least on the flexible connection member.

Inventors: Fan; Zhilin (Guangzhou, CN), Lin; Zhenji (Guangzhou, CN)

Applicant: Guangzhou Hansong Electric Technology Co., Limited (Guangzhou, CN)

Family ID: 1000007992036

Appl. No.: 18/763734

Filed: July 03, 2024

Foreign Application Priority Data

CN 202410260988.9

Mar. 07, 2024

CN 202420441375.0

Mar. 07, 2024

Publication Classification

Int. Cl.: A47K10/06 (20060101)

U.S. Cl.:

CPC A47K10/06 (20130101); A61L2/04 (20130101); A61L12/04 (20130101); A63B37/0003 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priorities of the Chinese patent application No. CN202410260988.9, filed on Mar. 7, 2024, and the Chinese patent application No. CN202420441375.0, filed on Mar. 7, 2024, and contents of which are incorporated herein by their entireties.

TECHNICAL FIELD

[0002] The present disclosure relates to the field of towel heating devices, and in particular to a towel heating device.

BACKGROUND

[0003] A towel heating device is substantially configured to receive a towel and to heat the towel. The towel heating device may quickly heat the towel to reach a proper temperature, enabling a user to feel a more comfortable temperature when taking a bath or washing the face.

[0004] A shell of the towel heating device in the art usually has a fixed structure. The shell of the towel heating device occupies a large space and cannot be deformed, such that the towel heating device may not be transported and stored easily.

SUMMARY OF THE DISCLOSURE

[0005] The present disclosure a foldable towel heating device including: a rigid shell; a flexible connection member, connected to the rigid shell, wherein, the flexible connection member and the rigid shell cooperatively encloses to form a receiving chamber, the rigid shell or the flexible connection member defines an opening communicating with the receiving chamber; and a heating assembly, configured to heat the receiving chamber, wherein, the heating assembly is disposed at least on the flexible connection member.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] In order to more clearly illustrate the technical solutions in the embodiments of the present disclosure or in the art, the accompanying drawings for describing the embodiments of the present disclosure or in the art will be briefly introduced in the following. Obviously, that the following accompanying drawings show only some of the embodiments of the present disclosure. Any ordinary skilled person in the art may obtain other accompanying drawings based on the following drawings without making any creative work.

[0007] FIG. 1 is a perspective view of a towel heating device according to an embodiment of the present disclosure, in which a foldable bracket is in an unfolding state, and the foldable bracket has a first slide slot, a second slide slot, a third slide slot, and a fourth slide slot.

[0008] FIG. 2 is an exploded view of the towel heating device according to an embodiment of the present disclosure.

[0009] FIG. 3 is a schematic view of a receiving chamber and an opening of the towel heating device according to an embodiment of the present disclosure.

[0010] FIG. 4 is a cross-sectional view of the towel heating device according to an embodiment of the present disclosure.

[0011] FIG. 5 is an enlarged view of a portion A shown in FIG. 4.

[0012] FIG. 6 is a schematic view of connection between a rigid shell and a heating plate according to an embodiment of the present disclosure.

[0013] FIG. 7 is a schematic view of connection between a shell body, a first fixation frame, a second fixation frame, and the heating plate according to an embodiment of the present disclosure.

[0014] FIG. **8** is an exploded view of the second fixation frame and the heating plate according to an embodiment of the present disclosure.

[0015] FIG. **9** is a cross-sectional view of the towel heating device according to an embodiment of the present disclosure, in which a bottom wall and another three side walls of the receiving chamber are shown.

[0016] FIG. **10** is an enlarged view of a portion B shown in FIG. **9**.

[0017] FIG. **11** is an exploded view of a first receiving bag, a first heat-insulation layer, and a flexible heating sheet according to an embodiment of the present disclosure.

[0018] FIG. **12** shows distribution of a first positioning post, a second positioning post, and a third positioning post in a cavity according to an embodiment of the present disclosure.

[0019] FIG. **13** is an enlarged view of a portion C shown in FIG. **12**.

[0020] FIG. **14** is another perspective view of the towel heating device according to an embodiment of the present disclosure, in which the foldable bracket is in the unfolding state and in the folding state, and the foldable bracket has the first slide slot and the third slide slot.

REFERENCE NUMERALS IN THE DRAWINGS

[0021] Rigid shell **1**, shell body **11**, cavity **111**, first fixation frame **12**, second fixation frame **13**, first positioning post **112**, second positioning post **113**, third positioning post **114**, first fixation rod **121**, second fixation rod **131**, first clamping protrusion **1311**, second clamping protrusion **1141**, wire through-slot **122**, limiting tab **132**, front shell **101**, rear shell **102**, first connection shaft **1011**, second connection shaft **1012**, third connection shaft **1021**, fourth connection shaft **1022**, left end of the rigid shell **1001**, right end of the rigid shell **1002**, bottom of the rigid shell **1003**, inner side of the first fixation frame **1201**; [0022] Flexible connection member **2**, first receiving bag **21**, first heat-insulation layer **22**, first fabric sheet **211**, first connection portion **201**, flexible bottom plate **202**, flexible side plate **203**, bottom of the flexible connection member **2001**, and side of the first heat-insulation layer facing the receiving chamber **2201**; [0023] Foldable bracket **3**, first support rod **31**, second support rod **32**, first end of the first support rod **311**, second end of the first support rod **312**, first end of the second support rod **321**, second end of the second support rod **322**, first slide slot **301**, second slide slot **302**, third slide slot **303**, fourth slide slot **304**; [0024] Heating assembly **4**, heating plate **41**, flexible heating sheet **42**, control board **43**, heat-conducting plate **411**, electric wire plate **412**, bottom heating sheet **421**, side heating sheet **422**, first conducting wire **401**, second conducting wire **402**, edge of the heating plate **4101**, side of the heating plate **4102**, side of the heat-conducting plate facing the cavity **4111**, side of the control board **431**; [0025] Top cover **5**, first end of the top cover **501**, second end of the top cover **502**, second connection portion **503**, second receiving bag **51**, second heat-insulation layer **52**, second fabric sheet **511**, edge of the second receiving bag **5101**; [0026] Receiving chamber **6**, bottom wall of the receiving chamber **61**, side wall of the receiving chamber **61**; [0027] Opening **7**; [0028] Bolt **8**.

DETAILED DESCRIPTION

[0029] Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by any ordinary skilled person in the art. Terms used herein in the specification of the present disclosure are used only for the purpose of describing specific embodiments and are not intended to limit the present disclosure. The terms “include”, “have” and any variations thereof in the specification, claims, and accompanying drawings of the present disclosure are intended to cover non-exclusive inclusion. The terms “first”, “second”, and so on in the specification, claims, and the accompanying drawings of the present disclosure are used to distinguish different objects and are not intended to describe a particular order.

[0030] Reference to “embodiment” herein implies that particular features, structures, or properties described in an embodiment may be included in at least one embodiment of the present disclosure. The presence of the term at various sections in the specification does not necessarily refer to a same embodiment, nor a separate or an alternative embodiment that is mutually exclusive of other embodiments. Any ordinary skilled person in the art shall understand, explicitly and implicitly, that

the embodiments described herein may be combined with other embodiments.

[0031] In order to enable any ordinary skilled person in the art to better understand the embodiments of the present disclosure, technical solutions in the embodiments of the present disclosure will be clearly and completely described below by referring to the accompanying drawings.

[0032] As shown in FIGS. **1** to **14**, the present disclosure provides a foldable towel heating device including two rigid shells **1**, a flexible connection member **2**, at least one foldable bracket **3**, and a heating assembly **4**. Folding or unfolding the foldable bracket **3** drives the two rigid shells **1** to move towards or away from each other and drives the flexible connection member **2** to be correspondingly folded or unfolded. Therefore, the towel heating device herein may be a foldable or folding towel heating device.

[0033] The two rigid shells **1** are arranged parallel to each other. Each rigid shell **1** includes a shell body **11**, a first fixation frame **12** and a second fixation frame **13**. The shell body **11** defines a cavity **111**. The second fixation frame **13** is disposed at an inner side **1201** of the first fixation frame **12**. The first fixation frame **12** and the second fixation frame **13** are both connected to the shell body **1** and are received in the cavity **111**. The inner side **1201** of the first fixation frame **12** refers to a space surrounded by the first fixation frame **12**. To be noted that, the two rigid shells **1** may cooperatively form any shape, such as cylindrical, squared, polygonal, and so on. For example, when the two rigid shells **1** form a cylindrical structure, the towel heating device in the present disclosure may be a foldable or folding towel warmer bucket.

[0034] Each of two sides of the flexible connection member **2** is arranged with a first connection portion **201**. The two first connection portions **201** are clamped by the two rigid shells **1**, respectively. Specifically, each first connection portion **201** firstly extends through a gap between the first fixation frame **12** and the second fixation frame **13**, and is then clamped between the first fixation frame **12** and the shell body **11**. The flexible connection member **2** is arranged to connect the two rigid shells **1** to each other, and the flexible connection member **2** and the two rigid shells **1** cooperatively enclose a receiving chamber **6**. The receiving chamber **6** has an opening **7**. The opening **7** may be defined in either one of the two rigid shells **1** or in the flexible connection member **2**. The opening **7** is configured to enable a user to place a towel into the receiving chamber **6**.

[0035] The at least one foldable bracket **3** enables the two rigid shells **1** to be connected to each other. Each foldable bracket **3** may be a scissor-type structure, a folding plate, and so on. As shown in FIGS. **1** and **14**, when the foldable bracket **3** is being folded, the two rigid shells **1** are driven to move to approach each other, and the flexible connection member **2** is folded correspondingly. As shown in FIG. **14**, when the foldable bracket **3** is being unfolded, the two rigid shells **1** are driven to move away from each other, and the flexible connection member **2** is unfolded correspondingly. In addition, in order to improve balance and stability of mutual movement between the two rigid shells **1**, in the present embodiment, two foldable brackets **3** are arranged, and each of the two foldable brackets **3** is in a scissor form. The two foldable brackets **3** are symmetrically disposed at a left end **1001** and a right end **1002** of the rigid shells **1**, such that the two rigid shells **1** are enabled to move towards each other more stably and reliably. Of course, in other embodiments, only one foldable bracket **3** is arranged to connect the two rigid shells **1** to each other, and the two rigid shells **1** can still be driven to move towards each other. The only difference is reflected in the stability of the movement between the two rigid shells **1**. This type of embodiment is not shown in the accompanying drawings.

[0036] The heating assembly **4** may be disposed on any of the rigid shells **1** and/or the flexible connection member **2**. When the heating assembly **4** is disposed on the rigid shell **1**, the second fixation frame **13** is configured to fix the heating assembly **4**. The user may place the towel into the receiving chamber **6** from the opening **7**, the heating assembly **4**, which is disposed in the towel heating device, is configured to heat the receiving chamber **6** and the towel received therein. In

addition, the user may take the foldable bracket **3** to drive the two rigid shells **1** to move to approach or away from each other. Since the flexible connection member **2** has a deforming capability, the approaching movement between the two rigid shells **1** may not be blocked by the flexible connection member **2**. Therefore, the towel heating device may be folded and unfolded, and can be stored and transported easily.

[0037] Connection between the flexible connection member **2** and the two rigid shells **1** is as follows.

[0038] As shown in FIGS. **4**, **5**, **12**, a plurality of first positioning posts **112** are arranged on the shell body **11**. Each first positioning post **112** extends through the respective first connection portion **201**. The first fixation frame **12** is fastened to the plurality of first positioning posts **112** by bolts **8**. Specifically, when one first connection portion **201** is connected with one rigid shell **1**, the first positioning posts **112** on the rigid shell **1** extend through the first connection portion **201**, and subsequently, the first fixation frame **12** is brought to approach the shell body **11**. The first positioning posts **112** are aligned to corresponding bolt holes defined in the first fixation frame **12**. At last, the bolts **8** are arranged to fasten the first fixation frame **12** to the first positioning posts **112**. In this way, the first connection portion **201** is clamped between the shell body **11** of the rigid shell **1** and the first fixation frame **12**. The connection between the flexible connection member **2** and the rigid shell **1** is more secure. Accordingly, two first connection portions **201** of the flexible connection member **2** are fastened successively by following the above method, such that the connection between the flexible connection member **2** and the two rigid shells **1** is achieved. In this process, the first positioning posts **112** are used to position the first connection portion **201** with respect to the first fixation frame **12**, and the bolts **8** are used to achieve the fastening and fixation between the first connection portion **201** and the first fixation frame **12**.

[0039] In addition, as shown in FIG. **2**, the flexible connection member **2** includes a flexible bottom plate **202** and two flexible side plates **203**. The flexible bottom plate **202** and the two flexible side plates **203** are integrally formed as a one-piece structure. The flexible bottom plate **202** and the two flexible side plates **203** cooperatively form a “U”-shaped structure, such that a bottom **61** and four sides **62** of the receiving chamber **6** are closed, and the only opening **7** is formed at a top of the U-shaped flexible connection member **2**. The first connection portion **201** is extended along and distributed at an edge of each of the two flexible side plates **203** and the flexible bottom plates **202**. That is, the first connection portion **201** extends along a length direction of the flexible connection member **2**. In order to facilitate the connecting process between the flexible connection member **2** and the rigid shell **1**, the first fixation frame **12** is formed by three first fixation rods **121** sequentially connected to each other from end to end. The three first fixation rods **121** are configured to fix two first connection portions **201** arranged on the two flexible side plates **203** and one first connection portion **201** arranged on the flexible bottom plate **202**, respectively.

[0040] Further, in an embodiment, the heating assembly **4** is disposed on only the two rigid shells **1**. In the present embodiment, the heating assembly **4** includes two heating plates **41** and a control board **43**. The two heating plates **41** are electrically connected to the control board **43**. The two heating plates **41** are mounted on two second fixation frames **13** of the two rigid shells **1**, respectively. The control board **43** is mounted on the shell body **11** of either one of the two rigid shells **1**. The control board **43** is a PCB board.

[0041] In another embodiment of the present disclosure, the heating assembly **4** is disposed on the two rigid shells **1** and the flexible connection member **2**. In the present embodiment, the heating assembly **4** includes two heating plates **41**, a flexible heating sheet **42**, and a control board **43**. The two heating plates **41** and the flexible heating sheet **42** are electrically connected to the control board **43**. The two heating plates **41** are mounted on the two second fixation frames **13** of the two rigid shells **1**, respectively. The flexible heating sheet **42** is mounted in the flexible connection member **2**. The control board **43** is mounted in the cavity **111** of either one of the two rigid shells **1**.

The control board **43** is the PCB board.

[0042] Mounting of the heating plate **41** on the second fixation frame **13** is as shown in FIGS. **6**, **7**, **8**, and **12**.

[0043] A plurality of second positioning posts **113** are arranged on each shell body **11**. The plurality of second positioning posts **113** are inserted into the second fixation frame **13**. Bolts **8** may further be arranged to fasten the second fixation frame **13** to the second positioning posts **113**. The heating plate **41** is mounted at a middle of the second fixation frame **13**. In this way, mounting of the flexible connection member **2** and mounting of the heating assembly **4** are performed separately from each other. Therefore, the mounting can be performed conveniently, and connection stability can be ensured. In this process, the second positioning posts **113** are configured to position the second fixation frame **13**, and the bolts **8** are configured to fasten and fix the first fixation frame **12**.

[0044] In addition, the heating plate **41** may be rectangular. The second fixation frame **13** is an enclosed structure formed by four second fixation rods **131** successively connected to each other from end to end. The four second fixation rods **131** cooperatively clamp one heating plate **41**. Each second fixation rod **131** is arranged with two first clamping protrusions **1311**. The two first clamping protrusions **1311** abut against two side surfaces **4102** of the heating plate **41**, respectively. The two first clamping protrusions **1311** cooperatively clamp one heating plate **41**. The four second fixation rods **131** are disposed at and clamp four edges **4101** of the heating plate **41**, respectively. In this way, the four edges **4101** of the heating plate **41** are completely wrapped in the second fixation frame **13**. Further, the second fixation frame **13** is mounted to the shell body **11**. In this way, the fixation of the heating plate **41** is more convenient and reliable. On the other hand, since the heating plate **41** generates heat and is at a high temperature when operating, in the present embodiment, the second fixation frame **13** is made of plastic material that is resistant to high temperatures and is flame retardant; and the shell body **11** is made of any ordinary plastic material at a lower cost.

[0045] Specific structure of the heating plate **41** is as shown in FIG. **8**.

[0046] The heating plate **41** includes a heat-conducting plate **411** and an electric wire plate **412**. The electric wire plate **412** is electrically connected to the control board **43**. The heat-conducting plate **411** is mounted in the middle of the second fixation frame **13**.

[0047] In addition, since the electric wire plate **412** generates heat to reach a high temperature when operating, the user may be burned if direct contacting the electric wire plate **412**. The electric wire plate **412** is adhered, by a double-sided adhesive, to a side **4111** of the heat-conducting plate **411** facing the cavity **111**. In this way, the electric wire plate **412** is prevented from being directly exposed to the receiving chamber **6**, and the service life of the electric wire plate **412** is extended. The heat-conducting plate **411** is a steel plate with a zinc layer plated on a surface thereof. The heat generated by the electric wire plate **412** is conducted into the receiving chamber **6** through the heat-conducting plate **411**. Moreover, the heat-conducting plate **411** has good corrosion resistance, and a service life of the heat-conducting plate **411** in a humid environment may be improved.

[0048] Each of the two heating plates **41** is electrically connected to the control board **43** by a first wire **401**. A bottom of each of the two first fixation frames **12** defines a wire through-slot **122** extending through the bottom. The wire through-slot **122** is defined to enable the first wire **401** to pass through. In addition, the first wire **401** may further arranged to extend through the flexible connection member **2** if desired.

[0049] Structures of the flexible heating sheet **42** is as shown in FIG. **11**.

[0050] The flexible heating sheet **42** includes a bottom heating sheet **421** and two side heating sheets **422**. The bottom heating sheet **421** is disposed in the flexible bottom plate **202**. The two side heating sheets **422** are disposed in the two flexible side plates **203** respectively. The two side heating sheets **422** are both electrically connected to the bottom heating sheet **421**. The bottom heating sheet **421** is electrically connected to the control board **43** via a second wire **402**. The second wire **402** also extends through the wire through-slot **122** to be further connected to the

control board **43**. In summary, the configuration of the flexible heating sheet **42** and the two heating plates **41** enables the bottom wall **61** and the four side walls **62** of the receiving chamber **6** to generate heat. Therefore, a heating efficiency of the towel heating device is improved.

[0051] To be noted that the control board **43** controlling the two heating plates **41** and the flexible heating sheet **42** may be achieved by any controlling technology available in the art. Of course, any ordinary skilled person in the art shall understand that, a built-in power supply may be arranged on the shell body **11**, or the control board **43** may be connected to an external power supply, such that power is provided for the heating plates **41** and the flexible heating sheet **42**.

[0052] In addition, a display screen may be arranged on a front shell **101**. The display screen is electrically connected to the control board **43**. The display screen may be configured to display information about an operating state of the heating assembly **4**. A plurality of control buttons for controlling the operating state of the heating assembly **4** may be arranged on the display screen. Alternatively, the operating state of the heating assembly **4** may be controlled remotely.

[0053] Mounting the control panel **43** to the rigid shell **1** is as shown in FIGS. **12** and **13**.

[0054] At least two third positioning posts **114** are further arranged in the shell body **11**. Each third positioning post **114** is arranged with two second clamping protrusions **1141**. The two second clamping protrusions **1141** abut against two sides **431** of the control plate **43**, respectively. The two second clamping protrusions **1141** cooperatively clamp the heating plate **41**. All of the third positioning posts **114** cooperatively clamp the control plate **43**, such that a balanced force is applied on the control plate **43**. Of course, the user may disengage the control plate **43** from the plurality of third positioning posts **114** by pulling the control plate **43**.

[0055] Further, in order to achieve heat preservation performance of the towel heating device, in the present embodiment, as shown in FIGS. **4** and **5**, the flexible connection member **2** includes a first receiving bag **21** and a first heat-insulation layer **22**. The flexible heating sheet **42** and the first heat-insulation layer **22** are arranged inside the first receiving bag **21**. The first receiving bag **21** is arranged with two first connection portions **201** at an edge of the first receiving bag **21**. To be noted that the first receiving bag **21** and the first heat-insulation layer **22** are layered structures of the flexible connection member **2**. Combination of the first receiving bag **21** and the first heat-insulation layer **22** cooperatively form the above-mentioned flexible bottom plate **202** and the two flexible side plates **203**.

[0056] The first heat-insulation layer **22** is made of heat-insulation cotton, and the first heat-insulation layer **22** is soft.

[0057] In the present embodiment, the first receiving bag **21** is formed by two first fabric sheets **211** sewn to each other. Both the flexible heating sheet **42** and the first heat-insulation layer **22** are sandwiched between the two first fabric sheets **211**. Each first fabric sheet **211** is made of fabric material. The flexible heating sheet **42** is disposed on a side **2201** of the first heat-insulation layer **22** facing the receiving chamber **6**. Therefore, the heat generated by the flexible heating sheet **42** passes through one of the two first fabric sheets **211** to be conducted to the receiving chamber **6**, obstruction during heat conduction is reduced. In addition, due to a blocking effect of the first heat-insulation layer **22**, the heat generated by the flexible heating sheet **42** cannot pass through the first heat-insulation layer **22** easily, and therefore, the heat is not easily conducted to an outside environment.

[0058] Specifically, the two first fabric sheets **211** are stitched together to each other at edges thereof. The first connection portion **201** is formed at a position where the two first fabric sheets **211** are stitched to each other. The first wire **401** and the second wire **402** both extend between the two first fabric sheets **211**. In addition, holes may be pre-defined in the first receiving bag **21** to allow the first wire **401** and the second wire **402** to extend through the first receiving bag **21**.

[0059] Further, in order to improve the heat preservation performance of the receiving chamber **6**, in the present embodiment, as shown in the FIGS. **1**, **2**, **9**, and **10**, the towel heating device further includes a top cover **5**. A first end of the top cover **5** is arranged with a second connection portion

503. The second connection portion **503** is clamped between the second fixation frame **13** and the shell body **11** of one of the two rigid shells **1**. Furthermore, the second positioning posts **113** extend through the second connection portion **503**, preventing the second connection portion **503** from being disengaged from the rigid shell **1**. A second end **502** of the top cover **5** can swing around the second connection portion **503** and may be lapped on the other one of the two rigid shells **1**, enabling the top cover **5** to cover the opening **7** and to improve sealing of the receiving chamber **6**. In addition, a limiting tab **132** is arranged on the second fixation frame **13**. The limiting tab **132** is extending towards the opening **7**. The second end **502** of the top cover **5** may be lapped on the limiting tab **132**.

[0060] In the present embodiment, the top cover **5** includes a second receiving bag **51** and a second heat-insulation layer **52**. The second heat-insulation layer **52** is arranged inside the second receiving bag **51**. The second receiving bag **51** extends at an edge **5101** to form a second connection portion **503**. The second receiving bag **51** and the second heat-insulation layer **52** are both layered structures of the top cover **5**. The second receiving bag **51** is formed by two second fabric sheets **511**. The second heat-insulation layer **52** is sandwiched between the two second fabric sheets **511**. The second heat-insulation layer **52** is made of heat-insulation cotton. When the top cover **5** covers the opening **7**, a rate at which the heat inside the receiving chamber **6** is dissipated from the opening **7** is reduced, i.e., the heat-insulation performance of the receiving chamber **6** is improved.

[0061] Further, in the present embodiment, the two rigid shells **1** are distributed in a front-rear direction. One of the two rigid shells **1** is named as a front shell **101**, and the other one of the two rigid shells **1** is named as a rear shell **102**. The opening **7** is defined at the top of the flexible connection member **2**. The two foldable brackets **3** are disposed at a left side and a right side of the towel heating device. This configuration is more conformity with usage habits of the user.

[0062] In an embodiment, as shown in FIG. **14**, the front shell **101** is arranged with a first connection shaft **1011** and a second connection shaft **1012**. The rear shell **102** is arranged with a third connection shaft **1021** and a fourth connection shaft **1022**. The foldable bracket **3** includes a first support rod **31** and a second support rod **32**. The first support rod **31** and the second support rod **32** are crossed to each other and are hinged to each other at a middle of the first support rod **31** and the second support rod **32**. A first end **311** of the first support rod **31** defines a first slide slot **301**, the first connection shaft **1011** slides in the first slide slot **301**. A second end **312** of the first support rod **31** is rotationally connected to the fourth connection shaft **1022**. A first end **321** of the second support rod **32** is rotationally connected to the second connection shaft **1012**. A second end **322** of the second support rod **32** defines a third slide slot **303**. The third connection shaft **1021** slides in the third slide slot **303**. In the present embodiment, the above configuration provides a feasible structural basis for the foldable bracket **3** to move.

[0063] In another embodiment, as shown in FIG. **1**, the front shell **101** is arranged with a first connection shaft **1011** and a second connection shaft **1012**. The rear shell **102** is arranged with a third connection shaft **1021** and a fourth connection shaft **1022**. The foldable bracket **3** includes a first support rod **31** and a second support rod **32**. The first support rod **31** and the second support rod **32** are crossed to each other and are hinged to each other at a middle of the first support rod **31** and the second support rod **32**. A first end **311** of the first support rod **31** defines a first slide slot **301**, a second end **312** of the first support rod **31** defines a fourth slide slot **304**. The first connection shaft **1011** slides in the first slide slot **301**, the fourth connection shaft **1022** slides in the fourth slide slot **304**. A first end **321** of the second support rod **32** defines a second slide slot **302**, a second end **322** of the second support rod **32** defines a third slide **303**. The second connection shaft **1012** slides in the second slide **302**, and the third connection shaft **1021** slides in the third slide **303**. In the present embodiment, the above configuration provides a feasible structural basis for the foldable bracket **3** to move. Compared to the above embodiment, the present embodiment enables a length of one slide slot to be shortened, effectively improving structural strength of the support rod.

[0064] Further, since the towel heating device usually needs to be placed in a bathroom, the floor is often wet or has moisture. Therefore, in the present embodiment, when the foldable bracket **3** is in the unfolded state, a lower end of the foldable bracket **3** is configured to be supported on the floor. That is, the first end **311** of the first support rod **31** and the second end **322** of the second support rod **32** contact the floor, enabling a bottom **1003** of the rigid shell **1** and a bottom **2001** of the flexible connection member **2** are both above the floor, preventing the rigid shell **1** and the flexible connection member **2** from becoming dirty due to contacting the floor.

[0065] It is understood that in other embodiments, the two rigid shells **1** may alternatively be distributed in an up-down direction, and the opening **7** is defined at the upper rigid shell **1**. In this case, the flexible connection member **2** is an enclosed structure, and the flexible connection member **2** completely wraps the space between the two rigid shells **1**. This embodiment is not shown in the accompanying drawings.

[0066] Obviously, the above-described embodiments show only some of, not all of, the embodiments of the present disclosure. All of the embodiments may be performed in combination with each other. The accompanying drawings show preferred embodiments of the present disclosure, but do not limit the scope of the present disclosure. The present disclosure may be achieved in various different forms. On the contrary, these embodiments are provided for the purpose for understanding the present disclosure more thoroughly and comprehensively. Although the present disclosure has been described in detail with reference to the foregoing embodiments, any ordinary skilled person in the art may still modify the technical solutions in the foregoing specific embodiments or make equivalent substitutions for some of the technical features therein. Any equivalent structure made based on the contents of the specification and the accompanying drawings of the present disclosure, applied directly or indirectly in other related technical fields, shall be equivalently included in scope of the present disclosure.

Claims

1. A foldable towel heating device, comprising: a rigid shell; a flexible connection member, connected to the rigid shell, wherein, the flexible connection member and the rigid shell cooperatively encloses to form a receiving chamber, the rigid shell or the flexible connection member defines an opening communicating with the receiving chamber; a heating assembly, configured to heat the receiving chamber, wherein, the heating assembly is disposed inside both the rigid shell and the flexible connection member; and a portion of the heating assembly disposed inside the flexible connection member is folded as the flexible connection member is folded.
2. The foldable towel heating device according to claim 1, wherein, the heating assembly further comprises a control board, the flexible heating sheet is electrically connected to the control board, the flexible heating sheet is mounted on the flexible connection member, the control board is mounted on the rigid shell or on the flexible connection member.
3. A foldable towel heating device, comprising: a rigid shell; a flexible connection member, connected to the rigid shell, wherein, the flexible connection member and the rigid shell cooperatively encloses to form a receiving chamber, the rigid shell or the flexible connection member defines an opening communicating with the receiving chamber; a heating assembly, configured to heat the receiving chamber, wherein, the heating assembly comprises a flexible heating plate that is disposed inside the flexible connection member; wherein the flexible connection member comprises a flexible bottom plate and two flexible side plates, the flexible bottom plate and the two flexible side plates are integrally formed into a one-piece structure, the flexible bottom plate and the two flexible side plates cooperatively form a U-shaped structure, the opening is located at a top of the U-shaped structure; the flexible heating plate is disposed in the flexible bottom plate and the two flexible side plates.
4. The foldable towel heating device according to claim 3, wherein, the flexible connection

member comprises a first receiving member and a first heat-insulation layer, the heating assembly comprises a flexible heating sheet, the first receiving member comprises two first fabric sheets stitched to each other, the flexible heating sheet and the first heat-insulation layer are sandwiched between the two first fabric sheets.

5. (canceled)

6. The foldable towel heating device according to claim 3, wherein, the rigid shell comprises two rigid sub-shells, the flexible connection member is connected to the two rigid sub-shells, the flexible connection member and the two rigid sub-shells cooperatively enclose to form the receiving chamber.

7. The foldable towel heating device according to claim 6, wherein, the flexible connection member is arranged with two first connection portions, the two first connection portions are connected to the two rigid sub-shells respectively, each rigid sub-shell comprises a shell body and a first fixation frame, the shell body defines a cavity, the first fixation frame is mounted in the cavity, each first connection portion is clamped between the respective first fixation frame and the respective shell body.

8. (canceled)

9. The foldable towel heating device according to claim 3, wherein, the flexible heating sheet comprises a bottom heating sheet and two side heating sheets, the bottom heating sheet is disposed in the flexible bottom plate, the two side heating sheets are disposed in the two flexible side plates, the two side heating sheets are electrically connected to the bottom heating sheet, and the bottom heating sheet is electrically connected to a control board.

10. The foldable towel heating device according to claim 7, wherein, the heating assembly further comprises two heating plates, the two heating plates are mounted in the two rigid sub-shells, and the two heating plates are electrically connected to a control board.

11. The foldable towel heating device according to claim 10, wherein, each rigid sub-shell further comprises a second fixation frame, a heating plate is mounted in the second fixation frame, the second fixation frame is mounted in the cavity, the second fixation frame is located at an inner side of the first fixation frame, the first connection portion extends through a gap between the first fixation frame and the second fixation frame.

12. The foldable towel heating device according to claim 11, wherein, the second fixation frame is ring shaped, the second fixation frame is formed by a plurality of second fixation rods successively connected to each other from end to end, the heating plate is rectangular, each of four edges of the heating plate is connected to at least one second fixation rod of the plurality of second fixation rods.

13. The foldable towel heating device according to claim 12, wherein, each of the plurality of second fixation rods is arranged with two first clamping protrusions, each of the two first clamping protrusions abuts against two sides of the heating plate, the two first clamping protrusions cooperatively clamp the heating plate.

14. The foldable towel heating device according to claim 11, wherein, the heating plate comprises a heat-conducting plate and an electric wire plate, the heat-conducting plate is mounted at a middle of the second fixation frame, the electric wire plate is attached to the heat-conducting plate, and the electric wire plate is electrically connected to the control board.

15. The foldable towel heating device according to claim 14, wherein, the electric wire plate is adhered to the side of the heat-conducting plate facing the cavity by double-sided adhesive.

16. The foldable towel heating device according to claim 14, wherein, the heat-conducting plate is a steel plate with a zinc layer plated on a surface thereof.

17. The foldable towel heating device according to claim 14, wherein, the shell body is made of plastic, and the second fixation frame is made of plastic material that is resistant to high temperatures and is flame retardant.

18. The foldable towel heating device according to claim 2, wherein, the rigid shell is further

arranged with at least two positioning posts, each of the plurality of positioning posts is arranged with two clamping protrusions, the two clamping protrusions abut against two sides of the control board, all of the at least two positioning posts are configured to cooperatively clamp the control board.

19. A foldable towel heating device according to claim 10, comprising: a rigid shell, comprising a first fixation frame; a flexible connection member, connected to the rigid shell, wherein, the flexible connection member and the rigid shell cooperatively encloses to form a receiving chamber, the rigid shell or the flexible connection member defines an opening communicating with the receiving chamber; a heating assembly, configured to heat the receiving chamber, wherein, the heating assembly is disposed inside both the rigid shell and the flexible connection member; the heating assembly further comprises two heating plates, the two heating plates are mounted in the rigid shell, and the two heating plates are electrically connected to a control board via a first wire, and the first fixation frame defines a wire through-slot at a bottom thereof, the wire through-slot extends through the bottom of the first fixation frame, the first wire extends through the wire through-slot.

20. The foldable towel heating device according to claim 6, further comprising a foldable bracket, wherein, the two rigid sub-shells are connected to each other via the foldable bracket; when the foldable bracket is being folded, the two rigid sub-shells are driven to move to approach each other, the flexible connection is folded correspondingly; and when the foldable bracket is being unfolded, the two rigid sub-shells are driven to move away from each other, the flexible connection is unfolded correspondingly.
