



US 20250284095A1

(19) **United States**

(12) **Patent Application Publication**
Sun et al.

(10) **Pub. No.: US 2025/0284095 A1**

(43) **Pub. Date: Sep. 11, 2025**

(54) **CAMERA OPTICAL LENS**

(71) Applicant: **AAC OPTICS (CHANGZHOU) CO., LTD.**, Changzhou (CN)

(72) Inventors: **Qun Sun**, Changzhou (CN); **Shunda Zhou**, Changzhou (CN)

(21) Appl. No.: **18/733,594**

(22) Filed: **Jun. 4, 2024**

Related U.S. Application Data

(63) Continuation of application No. PCT/CN2024/080155, filed on Mar. 5, 2024.

Publication Classification

(51) **Int. Cl.**
G02B 13/00 (2006.01)
G02B 1/04 (2006.01)
G02B 9/62 (2006.01)


(52) **U.S. Cl.**

CPC **G02B 13/0045** (2013.01); **G02B 1/041** (2013.01); **G02B 9/62** (2013.01); **G02B 13/0055** (2013.01); **G02B 13/008** (2013.01)

(57)

ABSTRACT

A camera optical lens is provided according to the present disclosure, which includes in sequence from an object side to an image side: a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens. The camera optical lens satisfies the following conditions: $nd1 \geq 1.70$, and $(FOV \cdot f)/IH \geq 120.00$. $nd1$ represents a refractive index of the first lens, FOV represents a field of view of the camera optical lens, f represents a focal length of the camera optical lens, and IH represents an image height of the camera optical lens. The camera optical lens according to the present disclosure has good optical performance, and can meet the design requirements of large aperture and miniaturization with good reception effect.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24

CAMERA OPTICAL LENS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation of PCT patent Application No. PCT/CN2024/080155, filed on Mar. 5, 2024, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] Embodiments of the present disclosure relate to the technical field of optics, and in particular to a camera optical lens.

BACKGROUND

[0003] With the development of intelligent driving, in-vehicle lens is also rapidly updated and iterated. An in-vehicle camera is favored by developers of autonomous driving technology because of its clear imaging effect. However, the in-vehicle camera is easily affected by environmental factors (such as strong light, rain and snow, etc.), which leads to poor shooting effect. Based on this, the use of an in-vehicle laser radar to supplement the information received by the in-vehicle lens is of great significance. The laser radar detects the target, obtains the target light wave signal from the reflected light, and processes the information together with the transmitted signal to obtain the distance, speed, azimuth and other information of the detected target. For the laser radar, the camera optical lens is an indispensable part of the laser radar. The camera optical lens can collimate the beam of the laser radar to improve the detection effect.

[0004] However, the existing camera optical lens of the laser radar still cannot meet the design requirements of large aperture and miniaturization, and the reception effect is poor, which is difficult to meet the application requirements of intelligent driving.

SUMMARY

[0005] Embodiments of the present disclosure provide a camera optical lens, which has good optical performance and can meet the design requirements of large aperture and miniaturization with good reception effect.

[0006] In order to solve the above technical problems, a camera optical lens is provided according to the present disclosure, which includes in sequence from an object side to an image side: a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens. The camera optical lens satisfies the following conditions: $nd1 \geq 1.70$, and $(FOV \cdot f)/IH \geq 120.00$. $nd1$ represents a refractive index of the first lens, FOV represents a field of view of the camera optical lens, f represents a focal length of the camera optical lens, and IH represents an image height of the camera optical lens.

[0007] As an improvement, the camera optical lens further satisfies the following condition: $-5.00 \leq R5/R6 \leq -1.20$. $R5$ represents a curvature radius of an object-side surface of the third lens, and $R6$ represents a curvature radius of an image-side surface of the third lens.

[0008] As an improvement, the camera optical lens further satisfies the following condition: $-4.00 \leq R7/R8 \leq -1.00$. $R7$ represents a curvature radius of an object-side surface of the fourth lens, and $R8$ represents a curvature radius of an image-side surface of the fourth lens.

[0009] As an improvement, the camera optical lens further satisfies the following condition: $1.40 \leq d9/d11 \leq 5.00$. $d9$ represents an on-axis thickness of the fifth lens, and $d11$ represents an on-axis thickness of the sixth lens.

[0010] As an improvement, the camera optical lens further satisfies the following condition: $-6.00 \leq f12/f \leq -1.20$. $f12$ represents a combined focal length of the first lens and the second lens.

[0011] As an improvement, the field of view FOV and the focal length f further satisfy the following condition: $(FOV \cdot f)/IH \leq 150.00$.

[0012] As an improvement, the first lens has a negative refractive power, and an image-side surface of the first lens is concave in a paraxial region. The camera optical lens further satisfies the following conditions: $0.33 \leq (R1+R2)/(R1-R2) \leq 1.97$, $-3.54 \leq f1/f \leq -0.54$, and $0.02 \leq d1/TTL \leq 0.22$. $R1$ represents a curvature radius of an object-side surface of the first lens, $R2$ represents a curvature radius of the image-side surface of the first lens, $f1$ represents a focal length of the first lens, $d1$ represents an on-axis thickness of the first lens, and TTL represents a total track length of the camera optical lens.

[0013] As an improvement, the second lens has a positive refractive power, an object-side surface of the second lens is concave in a paraxial region, and an image-side surface of the second lens is convex in the paraxial region. The camera optical lens further satisfies the following conditions: $0.54 \leq (R3+R4)/(R3-R4) \leq 1.71$, $1.66 \leq f2/f \leq 5.87$, and $0.02 \leq d3/TTL \leq 0.09$. $R3$ represents a curvature radius of the object-side surface of the second lens, $R4$ represents a curvature radius of the image-side surface of the second lens, $f2$ represents a focal length of the second lens, $d3$ represents an on-axis thickness of the second lens, and TTL represents a total track length of the camera optical lens.

[0014] As an improvement, the third lens has a negative refractive power, an object-side surface of the third lens is concave in a paraxial region, and an image-side surface of the third lens is concave in the paraxial region. The camera optical lens further satisfies the following conditions: $0.05 \leq (R5+R6)/(R5-R6) \leq 1.00$, $-7.30 \leq f3/f \leq -1.56$, and $0.02 \leq d5/TTL \leq 0.12$. $R5$ represents a curvature radius of the object-side surface of the third lens, $R6$ represents a curvature radius of the image-side surface of the third lens, $f3$ represents a focal length of the third lens, $d5$ represents an on-axis thickness of the third lens, and TTL represents a total track length of the camera optical lens.

[0015] As an improvement, the fourth lens has a positive refractive power, an object-side surface of the fourth lens is convex in a paraxial region, and an image-side surface of the fourth lens is convex in the paraxial region. The camera optical lens further satisfies the following conditions: $0.00 \leq (R7+R8)/(R7-R8) \leq 0.90$, $0.61 \leq f4/f \leq 2.69$, and $0.03 \leq d7/TTL \leq 0.27$. $R7$ represents a curvature radius of the object-side surface of the fourth lens, $R8$ represents a curvature radius of the image-side surface of the fourth lens, $f4$ represents a focal length of the fourth lens, $d7$ represents an on-axis thickness of the fourth lens, and TTL represents a total track length of the camera optical lens.

[0016] As an improvement, the fifth lens has a positive refractive power, an object-side surface of the fifth lens is convex in a paraxial region, and an image-side surface of the fifth lens is concave in the paraxial region. The camera optical lens further satisfies the following conditions: $-17.54 \leq (R9+R10)/(R9-R10) \leq -1.95$, $4.38 \leq f5/f \leq 45.60$, and $0.06 \leq d9/TTL \leq 0.36$. $R9$ represents a curvature radius of the object-side surface of the fifth lens, $R10$ represents a curvature radius of the image-side surface of the fifth lens, $f5$

represents a focal length of the fifth lens, d9 represents an on-axis thickness of the fifth lens, and TTL represents a total track length of the camera optical lens.

[0017] As an improvement, the sixth lens has a positive refractive power, an object-side surface of the sixth lens is convex in a paraxial region, and an image-side surface of the sixth lens is concave in the paraxial region. The camera optical lens further satisfies the following conditions: $-5.98 \leq (R11+R12)/(R11-R12) \leq -1.50$; $0.92 \leq f_6/f \leq 4.36$; and $0.02 \leq d11/TTL \leq 0.14$. R11 represents a curvature radius of the object-side surface of the sixth lens, R12 represents a curvature radius of the image-side surface of the sixth lens, f6 represents a focal length of the sixth lens, d11 represents an on-axis thickness of the sixth lens, and TTL represents a total track length of the camera optical lens.

[0018] As an improvement, the fourth lens is made of glass.

[0019] The beneficial effects of the present disclosure are that, by the configuration of the lens as described above, the camera optical lens according to the present disclosure has good optical performance, a large aperture, miniaturization, and good reception effect.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] One or more embodiments are exemplarily described with reference to the corresponding figures in the accompanying drawings, and the descriptions are not to be construed as limiting the embodiments. Elements in the accompanying drawings that have same reference numerals are represented as similar elements, and unless otherwise particularly stated, the figures in the accompanying drawings are not drawn to scale.

[0021] FIG. 1 is a schematic structural view of a camera optical lens according to a first embodiment of the present disclosure;

[0022] FIG. 2 is a schematic diagram of a field curvature and a distortion of the camera optical lens shown in FIG. 1;

[0023] FIG. 3 is a schematic diagram of a lateral color of the camera optical lens shown in FIG. 1;

[0024] FIG. 4 is a schematic diagram of a longitudinal aberration of the camera optical lens shown in FIG. 1;

[0025] FIG. 5 is a schematic structural diagram of a camera optical lens according to a second embodiment of the present disclosure;

[0026] FIG. 6 is a schematic diagram of a field curvature and a distortion of the camera optical lens shown in FIG. 5;

[0027] FIG. 7 is a schematic diagram of a lateral color of the camera optical lens shown in FIG. 5;

[0028] FIG. 8 is a schematic diagram of a longitudinal aberration of the camera optical lens shown in FIG. 5;

[0029] FIG. 9 is a schematic structural diagram of a camera optical lens according to a third embodiment of the present disclosure;

[0030] FIG. 10 is a schematic diagram of a field curvature and a distortion of the camera optical lens shown in FIG. 9;

[0031] FIG. 11 is a schematic diagram of a lateral color of the camera optical lens shown in FIG. 9;

[0032] FIG. 12 is a schematic diagram of a longitudinal aberration of the camera optical lens shown in FIG. 9;

[0033] FIG. 13 is a schematic structural diagram of a camera optical lens according to a fourth embodiment of the present disclosure;

[0034] FIG. 14 is a schematic diagram of a field curvature and a distortion of the camera optical lens shown in FIG. 13;

[0035] FIG. 15 is a schematic diagram of a lateral color of the camera optical lens shown in FIG. 13;

[0036] FIG. 16 is a schematic diagram of a longitudinal aberration of the camera optical lens shown in FIG. 13;

[0037] FIG. 17 is a schematic structural diagram of a camera optical lens according to a fifth embodiment of the present disclosure;

[0038] FIG. 18 is a schematic diagram of a field curvature and a distortion of the camera optical lens shown in FIG. 17;

[0039] FIG. 19 is a schematic diagram of a lateral color of the camera optical lens shown in FIG. 17;

[0040] FIG. 20 is a schematic diagram of a longitudinal aberration of the camera optical lens shown in FIG. 17;

[0041] FIG. 21 is a schematic diagram of the structure of a camera optical lens according to a comparative embodiment of the present disclosure;

[0042] FIG. 22 is a schematic diagram of a field curvature and a distortion of the camera optical lens shown in FIG. 21;

[0043] FIG. 23 is a schematic diagram of a lateral color of the camera optical lens shown in FIG. 21;

[0044] FIG. 24 is a schematic diagram of a longitudinal aberration of the camera optical lens shown in FIG. 21.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0045] To make the objects, technical solutions, and advantages of the present disclosure clearer, embodiments of the present disclosure are described in detail with reference to accompanying drawings in the following. A person of ordinary skill in the art can understand that, in the embodiments of the present disclosure, many technical details are provided to make readers better understand the present disclosure. However, even without these technical details and any changes and modifications based on the following embodiments, technical solutions required to be protected by the present disclosure can be implemented.

[0046] In the present disclosure embodiment, the terms “top”, “bottom”, “left”, “right”, “front”, “back”, “top”, “bottom”, “inside”, “outside”, “center”, “vertical”, “horizontal”, “transverse”, “longitudinal”, etc. indicate that the orientation or positional relationship is based on the orientation or positional relationship shown in the accompanying drawings. These terms are primarily intended to better describe the present disclosure and its embodiments, and are not intended to qualify that the indicated device, element, or component must have a particular orientation, or be constructed and operated in a particular orientation.

[0047] Moreover, some of the above terms may be used to indicate other meanings in addition to an orientation or positional relationship, for example, the term “on” may also be used to indicate a certain dependency or connection relationship in some cases. To a person of ordinary skill in the art, the specific meaning of these terms in the present disclosure may be understood according to the specific circumstances.

[0048] In addition, the terms “mount”, “set”, “provide”, “open”, “connect”, “inter-connect” should be understood in a broad sense. For example, it may be a fixed connection, a removable connection, or a monolithic construction; it may be a mechanical connection, or an electrical connection; it may be a direct connection, or an indirect connection through an intermediate medium, or an internal connection between two devices, elements, or components. To a person of ordinary skill in the art, the specific meanings of the above terms in the present disclosure may be understood according to the specific circumstances.

[0049] In addition, the terms “first”, “second”, etc. are mainly used to distinguish different devices, elements or components (the specific types and configurations may be

the same or different), and are not used to indicate or imply the relative importance and number of the indicated devices, elements or components. Unless otherwise indicated, “plurality” is used primarily to distinguish between different devices, elements or components (which may be of the same specific type and configuration). Unless otherwise indicated, “plurality” means two or more.

[0050] In the drawings, the thickness of layers and an area has been enlarged for better understanding and ease of description. When it is described that a part, such as a layer, film, area, or substrate, is “over” or “on” another part, the part may be “directly” on another part or a third part may be present between the two parts. In contrast, when it is described that a part is “directly on” another part, it means that a third part is not present between the two parts. Furthermore, when it is described that a part is “generally” formed on another part, it means the part is not formed on the entire surface (or front surface) of another part and is also not formed in part of the edge of the entire surface.

[0051] Referring to FIG. 1, a camera optical lens 10 is provided according to a first embodiment of the present disclosure, which includes in sequence from an object side to an image side: a first lens L1, a second lens L2, a third lens L3, a fourth lens L4, a fifth lens L5, and a sixth lens L6. $nd1$ represents a refractive index of the first lens L1, FOV represents a field of view of the camera optical lens 10, f represents a focal length of the camera optical lens 10, and IH represents an image height of the camera optical lens 10. The camera optical lens 10 satisfies the following conditions:

$$nd1 \geq 1.70 \quad (1)$$

$$(FOV * f) / IH \geq 120.00 \quad (2)$$

[0052] The condition (1) specifies that the refractive index $nd1$ of the first lens L1 is not less than 1.70, that is, the first lens L1 is preferably made of an optical material with a high refractive index, which is beneficial to controlling a front-end aperture of the camera optical lens 10 and improving the imaging quality.

[0053] Moreover, within the range specified in the condition (2), the camera optical lens 10 can simultaneously realize a large field of view angle and a long focal length, thereby realizing medium distance imaging and long distance imaging of the camera optical lens 10.

[0054] In this embodiment, a plurality of lenses (L1, L2, L3, L4, L5, L6) are provided, and the refractive index $nd1$ of the first lens L1 and the camera optical lens 10 are set in the ranges specified in the above conditions (1) and (2), so that the camera optical lens 10 has good optical performance, large aperture, miniaturization, and good reception effect.

[0055] Preferably, the refractive index $nd1$ of the first lens L1 further satisfies the following condition:

$$nd1 \leq 2.20 \quad (3)$$

[0056] preferably, the camera optical lens 10 further satisfies the following condition:

$$(FOV * f) / IH \leq 150.00 \quad (4)$$

[0057] Preferably, $f12$ represents a combined focal length of the first lens L1 and the second lens L2, f represents a focal length of the camera optical lens 10, and the following condition is satisfied:

$$-6.00 \leq f12/f \leq -1.20 \quad (5)$$

[0058] The condition (5) specifies a ratio of the combined focal length $f12$ of the first lens L1 and the second lens L2 to the focal length f of the camera optical lens 10. Within the range specified in condition (4), an amount of a field curvature of the system can be effectively balanced, so that an offset of the field curvature of the central field of view is less than 0.04 mm, thus the camera optical lens 10 has good imaging accuracy.

[0059] Preferably, $R5$ represents a curvature radius of an object-side surface of the third lens L3, $R6$ represents a curvature radius of an image-side surface of the third lens L3, and the following condition is satisfied:

$$-5.00 \leq R5/R6 \leq -1.20 \quad (6)$$

[0060] The condition (6) specifies a shape of the third lens L3, and specifies a ratio of the curvature radius $R5$ of the object-side surface to the curvature radius $R6$ of the image-side surface of the third lens L3 within the range specified in the condition (6), which can moderate a degree of deflection of the light passing through the third lens L3 and effectively reduce the lateral color LC to satisfy: $|LC| \leq 3.5$.

[0061] Preferably, $R7$ represents a curvature radius of an object-side surface of the fourth lens L4, $R8$ represents a curvature radius of an image-side surface of the fourth lens L4, and the following condition is satisfied:

$$-4.00 \leq R7/R8 \leq -1.00 \quad (7)$$

[0062] The condition (7) specifies a shape of the fourth lens L4, and specifies a ratio of the curvature radius $R7$ of the object-side surface to the curvature radius $R8$ of the image-side surface of the fourth lens L4 within the range specified in the condition (7), which is beneficial to moderating a degree of deflection of the light passing through the fourth lens L4, so that the camera optical lens 10 has good imaging quality and low sensitivity.

[0063] Preferably, $d9$ represents an on-axis thickness of the fifth lens L5, $d11$ represents an on-axis thickness of the sixth lens L6, and the following condition is satisfied:

$$1.4 \leq d9/d11 \leq 5.0 \quad (8)$$

[0064] The condition (8) specifies a ratio of the on-axis thickness $d9$ of the fifth lens L5 to the on-axis thickness $d11$

of the sixth lens L6, which, within the range specified in the condition (8), is beneficial to controlling thicknesses of the fifth lens L5 and the sixth lens L6, facilitates the injection molding of the fifth lens L5 and the sixth lens L6, and reduces the difficulty in manufacturing of the camera optical lens 10.

[0065] In this embodiment, the object-side surface of the first lens L1 is convex in a paraxial region, an image-side surface of the first lens L1 is concave in the paraxial region, and the first lens L1 has a negative refractive power. In other optional embodiments, the first lens L1 may have a positive refractive force, and the object-side surface and image-side surface of the first lens 1 may be configured in other concave and convex arrangements.

[0066] Preferably, R1 represents a curvature radius of an object-side surface of the first lens L1, R2 represents a curvature radius of the image-side surface of the first lens L1, f1 represents a focal length of the first lens, f represents a focal length of the camera optical length 10, d1 represents an on-axis thickness of the first lens L1, TTL represents a total track length of the camera optical lens 10, and the following conditions are satisfied:

$$0.33 \leq (R1 + R2)/(R1 - R2) \leq 1.97 \quad (9)$$

$$-3.54 \leq f1/f \leq -0.54 \quad (10)$$

$$0.02 \leq d1/TTL \leq 0.22 \quad (11)$$

[0067] The condition (9) specifies a shape of the first lens L1, which can moderate the degree of deflection of the light passing through the first lens L1 and effectively reduce the aberration with the range of the condition. More preferably, the following condition is satisfied: $0.53 \leq (R1+R2)/(R1-R2) \leq 1.57$. The condition (10) specifies a ratio of the focal length f1 of the first lens L1 to the focal length f of the camera optical lens 10, which is beneficial to improving the optical performance of the camera optical lens 10 within the range limited by the condition. More preferably, $-2.21 \leq f1/f \leq -0.68$. The condition (11) specifies a ratio of the on-axis thickness d1 of the first lens L1 to a thickness of the total track length TTL of the camera optical lens 10, which is beneficial to realizing an ultra-thin design of the camera optical lens 10 within the range. More preferably, $0.03 \leq d1/TTL \leq 0.17$.

[0068] In this embodiment, an object-side surface of the second lens L2 is concave in a paraxial region, an image-side surface of the second lens L2 is convex in the paraxial region, and the second lens L2 has a positive refractive power. In other optional embodiments, the object-side surface and the image-side surface of the second lens L2 may be arranged in other concave and convex arrangements, and the second lens L2 may have a negative refractive power.

[0069] Preferably, R3 represents a curvature radius of the object-side surface of the second lens L2, R4 represents a curvature radius of the image-side surface of the second lens L2, f2 represents a focal length of the second lens L2, f represents a focal length of the camera optical lens 10, d3 represents an on-axis thickness of the second lens L2, TTL represents a total track length of the camera optical lens 10, and the following conditions are satisfied:

$$0.54 \leq (R3 + R4)/(R3 - R4) \leq 1.71 \quad (12)$$

$$1.66 \leq f2/f \leq 5.87 \quad (13)$$

$$0.02 \leq d3/TTL \leq 0.09 \quad (14)$$

[0070] The condition (12) specifies a shape of the second lens L2, which can moderate the degree of deflection of the light passing through the second lens L2 and effectively reduce the aberration with the range limited by the condition. More preferably, the following condition is satisfied: $0.87 \leq (R3+R4)/(R3-R4) \leq 1.37$. The condition (13) specifies a ratio of the focal length f2 of the second lens L2 to the focal length f of the camera optical lens 10, which is beneficial to improving the optical performance of the camera optical lens 10 within the range. More preferably, $2.65 \leq f2/f \leq 4.70$. The condition (14) specifies a ratio of the on-axis thickness d3 of the second lens L2 to the total track length TTL of the camera optical lens 10, which is beneficial to compressing the total track length TTL of the camera optical lens 10 and realizing an ultra-thin design of the camera optical lens 10 within the range. More preferably, $0.03 \leq d3/TTL \leq 0.07$.

[0071] In this embodiment, an object-side surface of the third lens L3 is concave in a paraxial region, and an image-side surface of the third lens L3 is concave in the paraxial region, and the third lens has a negative refractive power. In other optional embodiments, the object-side surface and the image-side surface of the third lens L3 may be arranged in other concave and convex arrangements, and the third lens L3 may have a positive refractive power.

[0072] Preferably, R5 represents a curvature radius of the object-side surface of the third lens L3, R6 represents a curvature radius of the image-side surface of the third lens L3, f3 represents a focal length of the third lens L3, f represents a focal length of the camera optical lens 10, d5 represents an on-axis thickness of the third lens L3, TTL represents a total track length of the camera optical lens, and the following conditions are satisfied:

$$0.05 \leq (R5 + R6)/(R5 - R6) \leq 1.00 \quad (15)$$

$$-7.30 \leq f3/f \leq -1.56 \quad (16)$$

$$0.02 \leq d5/TTL \leq 0.12 \quad (17)$$

[0073] The condition (15) specifies a shape of the third lens L3, which can moderate the degree of deflection of the light passing through the third lens L3 and effectively reduce the lateral color to meet $|LC| \leq 3.5$. More preferably, the following condition is satisfied: $0.07 \leq (R5+R6)/(R5-R6) \leq 0.80$. The condition (16) specifies a ratio of the focal length f3 of the third lens L3 to the focal length f of the camera optical lens 10, which is beneficial to reducing the aberration of the camera optical lens 10 and realizing the ultra-thin and wide-angle design of the camera optical lens 10 within the range. More preferably, $-4.56 \leq f3/f \leq -1.950$. The condition (17) specifies a ratio of the on-axis thickness d5 of the third lens L3 to a thickness of the total track length TTL of the camera optical lens 10, which is beneficial to reasonably controlling the total track length TTL of the camera optical lens 10 within the range limited by the condition. More preferably, $0.03 \leq d5/TTL \leq 0.09$.

[0074] In this embodiment, an object-side surface of the fourth lens L4 is convex in a paraxial region, an image-side

surface of the fourth lens **L4** is convex in the paraxial region, and the fourth lens **L4** has a positive refractive power. In other optional embodiments, the object-side surface and the image-side surface of the fourth lens **L4** may be arranged in other concave and convex arrangements, and the fourth lens **L4** may have a negative refractive power.

[0075] Preferably, $R7$ represents a curvature radius of the object-side surface of the fourth lens **L4**, $R8$ represents a curvature radius of the image-side surface of the fourth lens **L4**, $f4$ represents a focal length of the fourth lens **L4**, f represents a focal length of the camera optical lens **10**, $d7$ represents an on-axis thickness of the fourth lens **L4**, TTL represents a total track length of the camera optical lens **10**, and the following conditions are satisfied:

$$0.00 \leq (R7 + R8)/(R7 - R8) \leq 0.90 \quad (18)$$

$$0.61 \leq f4/f \leq 2.69 \quad (19)$$

$$0.03 \leq d7/TTL \leq 0.27 \quad (20)$$

[0076] The condition (18) specifies a shape of the fourth lens **L4**, which can moderate the degree of deflection of the light passing through the fourth lens **L4** within the range, so that the camera optical lens **10** has good imaging quality and low sensitivity. More preferably, the following condition is satisfied: $0.00 \leq (R7+R8)/(R7-R8) \leq 0.72$. The condition (19) specifies a ratio of the focal length $f4$ of the fourth lens **L4** to the focal length f of the camera optical lens **10**, which reasonably allocates the focal length inside the camera optical lens **10**, so that the camera optical lens **10** has good imaging quality and low sensitivity. More preferably, $0.98 \leq f4/f \leq 2.15$. The condition (20) specifies a ratio of the on-axis thickness $d7$ of the fourth lens **L4** to the total track length TTL of the camera optical lens **10**, which can efficiently compress the total track length TTL of the camera optical lens **10** and realize the ultra-thin design of the camera optical lens **10** within the range of the condition. More preferably, $0.05 \leq d7/TTL \leq 0.21$.

[0077] In this embodiment, an object-side surface of the fifth lens **L5** is convex in a paraxial region, an image-side surface of the fifth lens **L5** is concave in the paraxial region, and the fifth lens **L5** has a positive refractive power. In other optional embodiments, the object-side surface and the image-side surface of the fifth lens **L5** may be arranged in other concave and convex arrangements, and the fifth lens **L5** may have a negative refractive power.

[0078] Preferably, $R9$ represents a curvature radius of the object-side surface of the fifth lens **L5**, $R10$ represents a curvature radius of the image-side surface of the fifth lens **L5**, $f5$ represents a focal length of the fifth lens **L5**, f represents a focal length of the camera optical lens **10**, $d9$ represents an on-axis thickness of the fifth lens **L5**, TTL represents a total track length of the camera optical lens **10**, and the following conditions are satisfied:

$$-17.54 \leq (R9 + R10)/(R9 - R10) \leq -1.95 \quad (21)$$

$$4.38 \leq f5/f \leq 45.60 \quad (22)$$

$$0.06 \leq d9/TTL \leq 0.36 \quad (23)$$

[0079] The condition (21) specifies a shape of the fifth lens **L5**, which is beneficial to improving the optical performance of the camera optical lens **10** within the limited range. More

preferably, the following condition is satisfied: $-10.96 \leq (R9+R10)/(R9-R10) \leq -2.44$. The condition (122) specifies a ratio of the focal length $f5$ of the fifth lens **L5** to the focal length f of the camera optical lens **10**, which is beneficial to improving the optical performance of the camera optical lens **10** within the range limited by the condition. More preferably, $7.01 \leq f5/f \leq 36.48$. The condition (23) specifies a ratio of the on-axis thickness $d9$ of the fifth lens **L5** to the total track length TTL of the camera optical lens **10**, which is beneficial to realizing the ultra-thin design of the camera optical lens **10**. More preferably, $0.10 \leq d9/TTL \leq 0.29$.

[0080] In this embodiment, an object-side surface of the sixth lens **L6** is convex in a paraxial region, an image-side surface of the sixth lens **L6** is concave in the paraxial region, and the sixth lens **L6** has a positive refractive power. In other optional embodiments, the object-side surface and the image-side surface of the sixth lens **L6** may be arranged in other concave and convex arrangements, and the sixth lens **L6** may have a negative refractive power.

[0081] Preferably, $R11$ represents a curvature radius of the object-side surface of the sixth lens **L6**, $R12$ represents a curvature radius of the image-side surface of the sixth lens **L6**, $f6$ represents a focal length of the sixth lens **L6**, f represents a focal length of the camera optical lens **10**, $d11$ represents an on-axis thickness of the sixth lens **L6**, TTL represents a total track length of the camera optical lens **10**, and the following conditions are satisfied:

$$-5.98 \leq (R11 + R12)/(R11 - R12) \leq -1.50 \quad (24)$$

$$0.92 \leq f6/f \leq 4.36 \quad (25)$$

$$0.02 \leq d11/TTL \leq 0.14 \quad (26)$$

[0082] The condition (24) specifies a shape of the sixth lens **L6**, which can moderate the off-axis aberration of the camera optical lens **10** generated during the ultra-thin and wide-angle design. More preferably, the following condition is satisfied: $3.74 \leq (R11+R12)/(R11-R12) \leq -1.87$. The condition (25) specifies a range of a ratio of the focal length $f6$ of the sixth lens **L6** to the focal length f of the camera optical lens **10**, which reasonably allocates the focal length inside the camera optical lens **10** within the range, so that the camera optical lens **10** has good imaging quality and low sensitivity. More preferably, $1.48 \leq f6/f \leq 3.49$. The condition (26) specifies a range of a ratio of the on-axis thickness $d6$ of the sixth lens **L6** to the total track length TTL of the camera optical lens **10**, which is beneficial to realizing the ultra-thin design of the camera optical lens **10**. More preferably, $0.03 \leq d11/TTL \leq 0.11$.

[0083] Preferably, FNO refers to F number of the camera optical lens **10**, which further satisfies the following condition:

$$FNO \leq 1.30 \quad (27)$$

[0084] The condition (27) specifies the F number of the aperture of the camera optical lens **10**, which, within the range limited by the condition (27), can realize a large amount of light intake while the camera optical lens **10** is miniaturized, thus improving the range of the camera optical lens **10** and improving the anti-ambient light ability of the camera optical lens **10**, and ensuring that the camera optical lens **10** has a good reception effect.

[0085] In this embodiment, the first lens L1 is made of glass, the second lens L2 is made of plastic, the third lens L3 is made of plastic, the fourth lens L4 is made of glass, the fifth lens L5 is made of plastic, and the sixth lens L6 is made of plastic. In other optional embodiments, the lenses may be made of other materials.

[0086] In this embodiment, an optical element such as an optical filter GF is provided between the sixth lens L6 and an image surface Si. The optical filter GF may be a glass cover plate or an optical filter (filter). As shown in FIG. 1, a first optical filter GF1 and a second optical filter GF2 are provided between the sixth lens L6 and the image surface Si. In other embodiments, the optical filter GF is made of glass. In other embodiments, the optical filter GF may be provided at other positions.

[0087] The camera optical lens 10 according to the present disclosure has good optical performance, a large aperture, miniaturization, and has good reception. According to the optical characteristics of the camera optical lens 10, the camera optical lens 10 is particularly suitable for use on a detection device such as an in-vehicle laser radar.

[0088] In the following, the camera optical lens 10 according to the present disclosure will be described with examples. The symbols recorded in each example are shown in table 1, and the units of the focal length, the on-axis distance, the curvature radius, the on-axis thickness, the inflexion points, and the arrest points are millimeters.

[0089] TTL refers to a total track length (an on-axis distance from the object-side surface of the first lens L1 to the image surface) in units of millimeters.

[0090] Preferably, an inflexion point and/or an arrest point may be provided on the object-side surface and/or the image-side surface of the lens, so as to meet high quality imaging requirements. The specific implementations can make reference to the following description.

[0091] FIG. 1 is a schematic structural diagram of the camera optical lens 10 according to a first embodiment. The following shows design data of the camera optical lens 10 according to a first embodiment of the present disclosure.

[0092] Table 1 lists the curvature radius R, the on-axis thickness of each lens, the on-axis distance d between the lenses, the refractive index nd and the Abbe number vd of the object-side surface and the image-side surface of the first lens L1 to the sixth lens L6 constituting the camera optical lens 10 according to the first embodiment of the present disclosure. Table 2 illustrates a conic coefficient k and aspheric surface coefficients of the camera optical lens 10. It is noted that in this implementation, the units of the distance, the radius and the thickness are millimeters (mm).

TABLE 1

	R	d	nd	vd
S1	∞	d0=	-5.313	
R1	22.867	d1=	1.000	nd1 25.44
R2	3.076	d2=	1.185	
R3	-155.669	d3=	1.000	nd2 23.35
R4	-6.249	d4=	0.473	
R5	-13.695	d5=	1.310	nd3 56.22
R6	5.437	d6=	0.475	
R7	13.494	d7=	2.197	nd4 25.44
R8	-6.495	d8=	1.412	
R9	11.686	d9=	2.749	nd5 56.22
R10	16.540	d10=	0.301	
R11	2.948	d11=	1.000	nd6 23.35
R12	6.650	d12=	1.071	
R13	∞	d13=	0.300	ndg1 54.52
R14	∞	d14=	1.946	

TABLE 1-continued

	R	d	nd	vd
R15	∞	d15=	1.500	ndg2 54.52
R16	∞	d16=	0.115	

The meanings of the symbols in the above table are listed as follows.

R: curvature radius of the optical surface, or central curvature radius in the case of a lens;
S1: aperture;

R1: curvature radius of the object-side surface of the first lens L1;

R2: curvature radius of the image-side surface of the first lens L1;

R3: curvature radius of the object-side surface of the second lens L2;

R4: curvature radius of the image-side surface of the second lens L2;

R5: curvature radius of the object-side surface of the third lens L3;

R6: curvature radius of the image-side surface of the third lens L3;

R7: curvature radius of the object-side surface of the fourth lens L4;

R8: curvature radius of the image-side surface of the fourth lens L4;

R9: curvature radius of the object-side surface of the fifth lens L5;

R10: curvature radius of the image-side surface of the fifth lens L5;

R11: curvature radius of the object-side surface of the sixth lens L6;

R12: curvature radius of the image-side surface of the sixth lens L6;

R15: curvature radius of the object-side surface of the first optical filter GF1;

R16: curvature radius of the image-side surface of the first optical filter GF1;

R17: curvature radius of the object-side surface of the second optical filter GF2;

R18: curvature radius of the image-side surface of the second optical filter GF2;

d: on-axis thickness of the lens or on-axis distance between adjacent lenses;

d0: on-axis distance from the aperture S1 to the object-side surface of the first lens L1;

d1: on-axis thickness of the first lens L1;

d2: on-axis distance from the image-side surface of the first lens L1 to the object-side surface of the second lens L2;

d3: on-axis thickness of the second lens L2;

d4: on-axis distance from the image-side surface of the second lens L2 to the object-side surface of the third lens L3;

d5: on-axis thickness of the third lens L3;

d6: on-axis distance from the image-side surface of the third lens L3 to the object-side surface of the fourth lens L4;

d7: on-axis thickness of the fourth lens L4;

d8: on-axis distance from the image-side surface of the fourth lens L4 to the object-side surface of the fifth lens L5;

d9: on-axis thickness of the fifth lens L5;

d10: on-axis distance from the image-side surface of the fifth lens L5 to the object-side surface of the sixth lens L6;

d11: on-axis thickness of the sixth lens L6;

d12: on-axis distance from the image-side surface of the sixth lens L6 to the object-side surface of the first optical filter GF1;

d13: on-axis thickness of the first optical filter GF1;

d14: on-axis distance from the image-side surface of the first optical filter GF1 to the object-side surface of the second optical filter GF2;

d15: on-axis thickness of the second optical filter GF2;

d16: on-axis distance from the image-side surface of the second optical filter GF2 to the image surface Si;

nd: refractive index of d-line (the d-line is green light with a wavelength of 550 nm);

nd1: refractive index of the first lens L1;

nd2: refractive index of the second lens L2;

nd3: refractive index of the third lens L3;

nd4: refractive index of the fourth lens L4;

nd5: refractive index of the fifth lens L5;

nd6: refractive index of the sixth lens L6;

ndg1: refractive index of the first optical filter GF1;

ndg2: refractive index of the second optical filter GF2;

vd: Abbe number;

vd1: Abbe number of the first lens L1;

vd2: Abbe number of the second lens L2;

vd3: Abbe number of the third lens L3;

vd4: Abbe number of the fourth lens L4;

vd5: Abbe number of the fifth lens L5;

vd6: Abbe number of the sixth lens L6;

vg1: Abbe number of the first optical filter GF1;

vg2: Abbe number of the second optical filter GF2.

TABLE 2

	Conic coefficient	Aspheric surface coefficients				
	k	A4	A6	A8	A10	A12
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	-9.95000E+01	1.10220E-02	1.67540E-03	-1.23620E-03	5.34150E-04	-1.35540E-04
R4	3.98699E+00	2.77220E-02	-1.21440E-03	-8.17420E-04	6.36050E-04	-2.00260E-04
R5	2.57042E+01	1.38870E-02	-5.69370E-03	7.96450E-04	2.21080E-04	-1.44640E-04
R6	3.26335E+00	-9.42560E-03	-9.78890E-04	4.32470E-04	-1.14210E-04	1.56670E-05
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	4.73653E+00	-1.90320E-03	-8.96340E-06	-8.11080E-05	1.93540E-05	-3.49910E-06
R10	-2.55203E+01	-4.41890E-02	1.09320E-02	-2.16650E-03	3.17760E-04	-3.31930E-05
R11	-9.17298E+00	7.40320E-03	-1.01970E-02	3.87960E-03	-1.06450E-03	2.05440E-04
R12	1.71778E+00	4.58350E-03	-6.06640E-03	1.35840E-03	-1.97850E-04	1.86720E-05

	Conic coefficient	Aspheric surface coefficients				
	k	A14	A16	A18	A20	/
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	-9.95000E+01	1.99670E-05	-1.55100E-06	4.74150E-08	0.00000E+00	/
R4	3.98699E+00	3.44460E-05	-3.02680E-06	1.00760E-07	0.00000E+00	/
R5	2.57042E+01	3.42510E-05	-4.18840E-06	2.59760E-07	-6.43500E-09	/
R6	3.26335E+00	-1.05640E-06	0.00000E+00	0.00000E+00	0.00000E+00	/
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	4.73653E+00	3.31800E-07	-1.42450E-08	0.00000E+00	0.00000E+00	/
R10	-2.55203E+01	2.28520E-06	-9.19120E-08	1.61420E-09	0.00000E+00	/
R11	-9.17298E+00	-2.68300E-05	2.23650E-06	-1.06660E-07	2.19640E-09	/
R12	1.71778E+00	-1.08710E-06	3.45920E-08	-4.57720E-10	0.00000E+00	/

[0093] It should be noted that an aspheric surface of each lens surface in this embodiment uses the aspheric surfaces shown in the above condition (27). However, the specific form of the condition (27) below is only an example, and the present disclosure is not limited to the aspherical polynomials form shown in the condition (27).

$$y = (c^2/r) / [1 + \{1 - (k+1)(c^2/r^2)\}^{1/2}] + A4r^4 + A6r^6 + A8r^8 + A10r^{10} + A12r^{12} + A14r^{14} + A16r^{16} + A18r^{18} + A20r^{20} \quad (27)$$

[0094] k is a conic coefficient, and A4, A6, A8, A10, A12, A14, A16, A18 and A20 are aspheric surface coefficients. c is a curvature at the center of the optical surface, r is a vertical distance between the point on an aspheric curve and the optical axis, and z is an aspheric depth (a vertical distance between the point on the aspheric surface having a distance of r from the optical axis, and a tangent plane tangent to a vertex on the optical axis of an aspheric surface).

[0095] Table 3 and Table 4 show design data of inflexion points and arrest points of each lens of the camera optical lens 10 according to the first embodiment of the present disclosure. Herein, PIR1 and PIR2 represent the object-side surface and the image-side surface of the first lens L1, P2R1 and P2R2 represent the object-side surface and the image-side surface of the second lens L2, P3R1 and P3R2 represent the object-side surface and the image-side surface of the third lens L3, P4R1 and P4R2 represent the object-side surface and the image-side surface of the fourth lens L4, P5R1 and P5R2 represent the object-side surface and the image-side surface of the fifth lens L5, and P6R1 and P6R2 represent the object-side surface and the image-side surface of the sixth lens L6. The data in the column named “inflexion point position” refers to vertical distances from inflexion

points arranged on each lens surface to the optical axis of the camera optical lens 10. The data in the column named “arrest point position” refers to vertical distances from arrest points arranged on each lens surface to the optical axis of the camera optical lens 10.

TABLE 3

	Number(s) of inflexion points	Inflexion point position 1	Inflexion point position 2
PIR1	/	/	/
PIR2	/	/	/
P2R1	2	0.225	2.555
P2R2	1	0.775	/
P3R1	/	/	/
P3R2	1	1.885	/
P4R1	/	/	/
P4R2	/	/	/
P5R1	1	1.625	/
P5R2	1	0.355	/
P6R1	1	1.115	/
P6R2	1	1.315	/

TABLE 4

	Number(s) of arrest points	Arrest point position
PIR1	/	/
PIR2	/	/
P2R1	1	0.375
P2R2	1	1.385
P3R1	/	/
P3R2	/	/
P4R1	/	/
P4R2	/	/
P5R1	1	2.385

TABLE 4-continued

	Number(s) of arrest points	Arrest point position
P5R2	1	0.625
P6R1	1	2.055
P6R2	1	2.165

[0096] In addition, in the following table 25, the values corresponding to the various parameters in the first embodiment and the parameters specified in the condition are listed.

[0097] FIG. 2 shows a field curvature and a distortion after light with a wavelength of 850 nm passes through the camera optical lens 10 in the first embodiment. FIG. 3 shows a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens 10 in the first embodiment. FIG. 4 is a schematic diagram of a longitudinal aberration after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens 10 in the first embodiment.

[0098] As shown in Table 25, the first embodiment satisfies the various conditions.

[0099] In this embodiment, an entrance pupil diameter (ENPD) of the camera optical lens 10 is 2.237 mm, an image height (IH) of 1.0H is 3.300 mm, and a field of view (FOV) in a diagonal direction is 148.20°. Thus, the camera optical lens 10 meets the design requirement for large aperture, and miniaturization, the on-axis and off-axis aberrations are sufficiently corrected, thereby achieving excellent optical performance.

Second Embodiment

[0100] FIG. 5 is a schematic structural diagram of the camera optical lens 20 according to the second embodiment. The second embodiment is substantially the same as the first embodiment, and the meanings of the symbols in the second embodiment are the same as the meanings of the symbols in the first embodiment. In the following, only differences are described.

[0101] Table 5 and Table 6 show design data of the camera optical lens 20 in the second embodiment of the present disclosure.

TABLE 5

	R	d	nd	vd
S1	∞	d0=	-6.452	
R1	34.983	d1=	2.289	nd1 2.0007 vd1 25.44
R2	2.990	d2=	1.761	
R3	-123.315	d3=	0.550	nd2 1.6393 vd2 23.35
R4	-6.330	d4=	0.396	
R5	-11.344	d5=	0.924	nd3 1.5131 vd3 56.22
R6	9.407	d6=	0.387	
R7	9.177	d7=	1.690	nd4 2.0007 vd4 25.44
R8	-9.101	d8=	0.500	
R9	9.033	d9=	2.021	nd5 1.5131 vd5 56.22
R10	13.998	d10=	0.271	
R11	2.942	d11=	1.444	nd6 1.6393 vd6 23.35
R12	5.899	d12=	0.828	
R13	∞	d13=	0.300	ndg1 1.5233 vg1 54.52
R14	∞	d14=	1.764	
R15	∞	d15=	0.500	ndg2 1.5233 vg2 54.52
R16	∞	d16=	0.115	

TABLE 6

	Conic coefficient	Aspheric surface coefficients				
	k	A4	A6	A8	A10	A12
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	2.48119E+03	8.52470E-03	1.69910E-03	-1.19230E-03	5.34480E-04	-1.36390E-04
R4	4.28946E+00	2.59980E-02	-1.00370E-03	-7.96910E-04	6.34640E-04	-2.00770E-04
R5	2.19967E+01	1.48400E-02	-6.20670E-03	8.00990E-04	2.27920E-04	-1.43860E-04
R6	4.68935E+00	-7.86660E-03	-9.24500E-04	4.20010E-04	-1.14140E-04	1.64000E-05
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	1.60540E+00	-2.31260E-03	-1.41080E-04	-1.00970E-04	1.76340E-05	-3.58130E-06
R10	-6.95224E+01	-4.45160E-02	1.08570E-02	-2.17540E-03	3.17430E-04	-3.31770E-05
R11	-1.09234E+01	6.01550E-03	-1.04230E-02	3.86660E-03	-1.06330E-03	2.05730E-04
R12	2.14541E+00	5.54730E-03	-6.03770E-03	1.35890E-03	-1.98220E-04	1.86280E-05

	Conic coefficient	Aspheric surface coefficients				
	k	A14	A16	A18	A20	/
R1	/	/	/	/	/	/
R2	/	/	1	/	/	/
R3	2.48119E+03	1.97790E-05	-1.57770E-06	4.47250E-08	-1.26490E-10	/
R4	4.28946E+00	3.43220E-05	-3.04960E-06	9.70320E-08	-1.10650E-09	/
R5	2.19967E+01	3.42610E-05	-4.20080E-06	2.59160E-07	-5.44220E-09	/
R6	4.68935E+00	-8.89240E-07	1.87960E-08	1.13870E-10	-5.32650E-10	/
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	1.60540E+00	3.33960E-07	-1.32560E-08	1.25530E-10	-7.53450E-13	/
R10	-6.95224E+01	2.28850E-06	-9.16100E-08	1.61730E-09	-3.36030E-12	/
R11	-1.09234E+01	-2.68070E-05	2.23630E-06	-1.06970E-07	2.18520E-09	/
R12	2.14541E+00	-1.08730E-06	3.50650E-08	-4.22720E-10	-1.00660E-11	/

[0102] Table 7 and table 8 show design data of inflexion points and arrest points of each lens of the camera optical lens **20** in the second embodiment of the present disclosure.

TABLE 7

	Number(s) of inflexion points	Inflexion point position 1	Inflexion point position 2
P1R1	/	/	/
P1R2	/	/	/
P2R1	2	0.285	2.095
P2R2	2	0.795	2.095
P3R1	/	/	/
P3R2	1	1.055	/
P4R1	/	/	/
P4R2	/	/	/
P5R1	1	1.495	/
P5R2	1	0.375	/
P6R1	1	1.025	/
P6R2	1	1.505	/

TABLE 8

	Number(s) of arrest points	Arrest point position
P1R1	/	/
P1R2	/	/
P2R1	1	0.475
P2R2	1	1.425
P3R1	/	/
P3R2	1	1.845
P4R1	/	/
P4R2	/	/
P5R1	1	2.175
P5R2	1	0.665
P6R1	1	1.865
P6R2	1	2.695

[0103] In addition, in the following table **25**, the values corresponding to the various parameters in the second embodiment and the parameters specified in the condition are listed.

[0104] FIG. 6 shows a field curvature and a distortion after light with a wavelength of 850 nm passes through the camera optical lens **20** in the second embodiment. FIG. 7 shows a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **20** in the second embodiment. FIG. 8 is a schematic diagram of a longitudinal aberration and a lateral color after light with

wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **20** in the second embodiment.

[0105] As shown in Table 25, the second embodiment satisfies the various conditions.

[0106] In this Embodiment, an entrance pupil diameter (ENPD) of the camera optical lens **20** is 2.112 mm, an image height (IH) of 1.0H is 3.300 mm, and a field of view (FOV) in a diagonal direction is 156.40°. Thus, the camera optical lens **20** meets the design requirement for large aperture, and miniaturization, the on-axis and off-axis aberrations are sufficiently corrected, thereby achieving excellent optical performance.

Third Embodiment

[0107] FIG. 9 is a schematic structural diagram of the camera optical lens **30** according to the third embodiment. The third embodiment is substantially the same as the first embodiment, and the meanings of the symbols in the third embodiment are the same as the meanings of the symbols in the first embodiment. In the following, only differences are described.

[0108] The object-side surface of the first lens **L1** is concave in the paraxial region.

[0109] Table 9 and Table 10 show design data of the camera optical lens **30** in the third embodiment of the present disclosure.

TABLE 9

	R	d	nd	vd
S1	∞	d0=	-2.982	
R1	-18.174	d1=	0.500	nd1 2.1042 vd1 17.02
R2	3.752	d2=	0.514	
R3	-114.648	d3=	0.644	nd2 1.6393 vd2 23.35
R4	-6.922	d4=	0.458	
R5	-17.754	d5=	0.501	nd3 1.5131 vd3 56.22
R6	5.606	d6=	0.181	
R7	12.019	d7=	1.056	nd4 2.0007 vd4 25.44
R8	-6.310	d8=	1.781	
R9	9.142	d9=	3.733	nd5 1.5131 vd5 56.22
R10	18.622	d10=	0.415	
R11	2.725	d11=	0.915	nd6 1.6393 vd6 23.35
R12	7.105	d12=	1.604	
R13	∞	d13=	0.300	ndg1 1.5233 vg1 54.52
R14	∞	d14=	2.479	
R15	∞	d15=	0.500	ndg2 1.5233 vg2 54.52
R16	∞	d16=	0.115	

TABLE 10

	Conic coefficient		Aspheric surface coefficients				
	k	A4	A6	A8	A10	A12	
R1	/	/	/	/	/	/	
R2	/	/	/	/	/	/	
R3	2.08210E+03	1.29170E-02	1.60770E-03	-1.21860E-03	5.37440E-04	-1.35350E-04	
R4	3.98957E+00	2.74370E-02	-1.01320E-03	-8.36240E-04	6.31050E-04	-2.00440E-04	
R5	1.74098E+01	1.35630E-02	-5.78920E-03	8.16990E-04	2.23510E-04	-1.44650E-04	
R6	3.16262E+00	-1.00460E-02	-1.00150E-03	4.35360E-04	-1.13040E-04	1.58950E-05	
R7	/	/	/	/	/	/	
R8	/	/	/	/	/	/	
R9	5.88518E+00	-1.36230E-03	-6.57390E-06	-8.24010E-05	1.92220E-05	-3.51220E-06	
R10	-2.75681E+01	-4.40320E-02	1.09510E-02	-2.16550E-03	3.17810E-04	-3.31910E-05	
R11	-7.43833E+00	7.90160E-03	-1.02400E-02	3.87310E-03	-1.06450E-03	2.05530E-04	
R12	1.94814E+00	4.30810E-03	-5.98700E-03	1.36410E-03	-1.97550E-04	1.86880E-05	

TABLE 10-continued

	Conic coefficient	Aspheric surface coefficients				
	k	A14	A16	A18	A20	/
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	2.08210E+03	1.99530E-05	-1.55370E-06	4.76930E-08	2.45490E-10	/
R4	3.98957E+00	3.45420E-05	-3.00320E-06	1.04690E-07	5.19130E-10	/
R5	1.74098E+01	3.42040E-05	-4.19110E-06	2.61700E-07	-5.52920E-09	/
R6	3.16262E+00	-1.02240E-06	3.86990E-09	2.23940E-10	-5.15370E-11	/
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	5.88518E+00	3.30390E-07	-1.43430E-08	-3.73730E-12	2.49640E-12	/
R10	-2.75681E+01	2.28570E-06	-9.18510E-08	1.61820E-09	-2.58030E-13	/
R11	-7.43833E+00	-2.68190E-05	2.23730E-06	-1.06640E-07	2.19580E-09	/
R12	1.94814E+00	-1.08550E-06	3.47950E-08	-4.35410E-10	1.58170E-12	/

[0110] Table 11 and Table 12 show design data of inflexion points and arrest points of each lens of the camera optical lens **30** in the third embodiment of the present disclosure.

TABLE 11

	Number(s) of inflexion points	Inflexion point position 1	Inflexion point position 2
P1R1	/	/	/
P1R2	/	/	/
P2R1	1	0.245	/
P2R2	1	0.715	/
P3R1	1	1.985	/
P3R2	2	1.475	2.455
P4R1	/	/	/
P4R2	/	/	/
P5R1	1	1.985	/
P5R2	2	0.335	3.605
P6R1	2	1.155	2.905
P6R2	2	1.285	2.845

TABLE 12

	Number(s) of arrest points	Arrest point position 1	Arrest point position 2
P1R1	/	/	/
P1R2	/	/	/
P2R1	1	0.405	/
P2R2	1	1.275	/
P3R1	1	2.255	/
P3R2	/	/	/
P4R1	/	/	/
P4R2	/	/	/
P5R1	1	2.685	/
P5R2	1	0.585	/
P6R1	2	2.135	3.235
P6R2	2	2.155	3.165

[0111] In addition, in the following table **25**, the values corresponding to the various parameters in the third embodiment and the parameters specified in the condition are listed.

[0112] FIG. **10** shows a field curvature and a distortion after light with a wavelength of 850 nm passes through the camera optical lens **30** in the third embodiment. FIG. **11** shows a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **30** in the third embodiment. FIG. **12** is a schematic diagram of a longitudinal aberration and a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **30** in the third embodiment.

[0113] As shown in Table 25, the third embodiment satisfies the various conditions.

[0114] In this embodiment, an entrance pupil diameter (ENPD) of the camera optical lens **30** is 2.750 mm, an image height (IH) of 1.0H is 3.300 mm, and a field of view (FOV) in a diagonal direction is 115.88°. Thus, the camera optical lens **30** meets the design requirement for large aperture, and miniaturization, the on-axis and off-axis aberrations are sufficiently corrected, thereby achieving excellent optical performance.

Fourth Embodiment

[0115] FIG. **13** is a schematic structural diagram of the camera optical lens **40** according to the fourth embodiment. The fourth embodiment is substantially the same as the first embodiment, and the meanings of the symbols in the fourth embodiment are the same as the meanings of the symbols in the first embodiment. In the following, only differences are described.

[0116] Table 13 and Table 14 show design data of the camera optical lens **40** in the fourth embodiment of the present disclosure.

TABLE 13

	R	d	nd	vd
S1	∞	d0=	-6.505	
R1	24.046	d1=	1.591 nd1	1.7130 vd1 53.87
R2	2.961	d2=	1.613	
R3	-88.810	d3=	1.089 nd2	1.6393 vd2 23.35
R4	-5.920	d4=	0.448	
R5	-13.331	d5=	1.244 nd3	1.5131 vd3 56.22
R6	5.149	d6=	0.598	
R7	14.872	d7=	3.280 nd4	2.0007 vd4 25.44
R8	-6.437	d8=	0.500	
R9	12.291	d9=	3.693 nd5	1.5131 vd5 56.22
R10	15.455	d10=	0.307	
R11	2.880	d11=	0.741 nd6	1.6393 vd6 23.35
R12	6.663	d12=	0.808	
R13	∞	d13=	0.300 ndg1	1.5233 vg1 54.52
R14	∞	d14=	1.663	
R15	∞	d15=	0.500 ndg2	1.5233 vg2 54.52
R16	∞	d16=	0.115	

TABLE 14

	Conic coefficient	Aspheric surface coefficients				
	k	A4	A6	A8	A10	A12
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	1.03093E+03	9.66490E-03	1.67020E-03	-1.23320E-03	5.35410E-04	-1.35390E-04
R4	4.08506E+00	2.68380E-02	-1.23620E-03	-8.27870E-04	6.39020E-04	-2.00300E-04
R5	2.35605E+01	1.49380E-02	-5.67760E-03	7.89940E-04	2.18240E-04	-1.44860E-04
R6	3.20604E+00	-9.77940E-03	-1.02740E-03	4.23600E-04	-1.16810E-04	1.49510E-05
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	6.25691E+00	-2.00420E-03	8.72700E-06	-7.74630E-05	1.93350E-05	-3.48300E-06
R10	-2.54785E+01	-4.40940E-02	1.09360E-02	-2.16260E-03	3.17680E-04	-3.32010E-05
R11	-9.15452E+00	7.28460E-03	-1.02470E-02	3.87960E-03	-1.06430E-03	2.05480E-04
R12	1.33668E+00	4.50780E-03	-6.06890E-03	1.35990E-03	-1.97910E-04	1.86910E-05

	Conic coefficient	Aspheric surface coefficients				
	k	A14	A16	A18	A20	/
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	1.03093E+03	1.99940E-05	-1.54700E-06	4.77430E-08	2.40140E-11	/
R4	4.08506E+00	3.44720E-05	-3.01420E-06	1.01060E-07	-2.68210E-10	/
R5	2.35605E+01	3.42150E-05	-4.19750E-06	2.59800E-07	-6.40180E-09	/
R6	3.20604E+00	-1.23990E-06	1.89450E-08	2.06660E-09	1.27100E-09	/
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	6.25691E+00	3.28780E-07	-1.43590E-08	2.09920E-11	1.53230E-11	/
R10	-2.54785E+01	2.28620E-06	-9.17750E-08	1.62690E-09	-7.27470E-13	/
R11	-9.15452E+00	-2.68300E-05	2.23750E-06	-1.06650E-07	2.19760E-09	/
R12	1.33668E+00	-1.08570E-06	3.48250E-08	-4.46680E-10	-7.35760E-13	/

[0117] Table 15 and Table 16 show design data of inflexion points and arrest points of each lens of the camera optical lens **40** in the fourth embodiment of the present disclosure.

TABLE 15

	Number(s) of inflexion points	Inflexion point position 1	Inflexion point position 2
P1R1	/	/	/
P1R2	/	/	/
P2R1	1	0.315	/
P2R2	2	0.835	2.315
P3R1	/	/	/
P3R2	/	/	/
P4R1	/	/	/
P4R2	/	/	/
P5R1	1	1.635	/
P5R2	1	0.365	/
P6R1	1	1.105	/
P6R2	2	1.295	3.355

TABLE 16

	Number(s) of arrest points	Arrest point position 1
P1R1	/	/
P1R2	/	/
P2R1	1	0.535
P2R2	1	1.515
P3R1	/	/
P3R2	/	/
P4R1	/	/
P4R2	/	/
P5R1	1	2.425
P5R2	1	0.645

TABLE 16-continued

	Number(s) of arrest points	Arrest point position 1
P6R1	1	2.035
P6R2	1	2.135

[0118] In addition, in the following table **25**, the values corresponding to the various parameters in the fourth embodiment and the parameters specified in the condition are listed.

[0119] FIG. **14** shows a field curvature and a distortion after light with a wavelength of 850 nm passes through the camera optical lens **40** in the fourth embodiment. FIG. **15** shows a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **40** in the fourth embodiment. FIG. **16** is a schematic diagram of a longitudinal aberration and a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **40** in the fourth embodiment.

[0120] As shown in Table 25, the fourth embodiment satisfies the various conditions.

[0121] In this embodiment, an entrance pupil diameter (ENPD) of the camera optical lens **40** is 2.157 mm, an image height (IH) of 1.0H is 3.300 mm, and a field of view (FOV) in a diagonal direction is 143.88°. Thus, the camera optical lens **40** meets the design requirement for large aperture, and miniaturization, the on-axis and off-axis aberrations are sufficiently corrected, thereby achieving excellent optical performance.

Fifth Embodiment

[0122] FIG. **17** is a schematic structural diagram of the camera optical lens **50** according to the fifth embodiment. The fifth embodiment is substantially the same as the first

embodiment, and the meanings of the symbols in the fifth embodiment are the same as the meanings of the symbols in the first embodiment. In the following, only differences are described.

[0123] Table 17 and Table 18 show design data of the camera optical lens **50** in the fifth embodiment of the present disclosure.

TABLE 17

	R	d	nd	vd
S1	∞	d0=	-5.321	
R1	24.301	d1=	1.090	nd1 2.0007 vd1 25.44
R2	3.087	d2=	1.305	
R3	-139.723	d3=	0.788	nd2 1.6393 vd2 23.35
R4	-6.393	d4=	0.372	
R5	-25.991	d5=	1.228	nd3 1.5131 vd3 56.22
R6	5.205	d6=	0.455	
R7	23.063	d7=	2.080	nd4 2.0007 vd4 25.44
R8	-5.793	d8=	0.745	
R9	10.100	d9=	2.654	nd5 1.5131 vd5 56.22
R10	15.404	d10=	0.353	
R11	2.893	d11=	1.173	nd6 1.6393 vd6 23.35
R12	5.902	d12=	0.978	
R3	∞	d13=	0.300	ndg1 1.5233 vg1 54.52
R14	∞	d14=	1.852	
R15	∞	d15=	0.500	ndg2 1.5233 vg2 54.52
R16	∞	d16=	0.115	

TABLE 18

	Conic coefficient	Aspheric surface coefficients				
	k	A4	A6	A8	A10	A12
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	2.50961E+03	9.75380E-03	1.66600E-03	-1.23470E-03	5.32920E-04	-1.35850E-04
R4	3.94698E+00	2.77420E-02	-1.17020E-03	-8.15820E-04	6.36860E-04	-2.00020E-04
R5	2.47770E+01	1.37840E-02	-5.79180E-03	7.95070E-04	2.22890E-04	-1.43940E-04
R6	3.20052E+00	-9.38660E-03	-9.72320E-04	4.27200E-04	-1.15080E-04	1.55250E-05
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	6.56163E+00	-1.37860E-03	4.25250E-05	-8.08960E-05	1.89510E-05	-3.55710E-06
R10	-4.85108E+01	-4.43690E-02	1.09270E-02	-2.16770E-03	3.17650E-04	-3.32010E-05
R11	-9.17432E+00	7.06060E-03	-1.02900E-02	3.87370E-03	-1.06400E-03	2.05580E-04
R12	1.65805E+00	4.37170E-03	-6.02210E-03	1.36130E-03	-1.97830E-04	1.86660E-05

	Conic coefficient	Aspheric surface coefficients				
	k	A14	A16	A18	A20	/
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	2.50961E+03	1.99240E-05	-1.55580E-06	4.68280E-08	-3.40720E-11	/
R4	3.94698E+00	3.44950E-05	-3.02340E-06	1.00520E-07	-4.90190E-10	/
R5	2.47770E+01	3.43470E-05	-4.19030E-06	2.57310E-07	-6.37350E-09	/
R6	3.20052E+00	-1.07210E-06	-3.26240E-09	-1.22110E-09	-3.54090E-10	/
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	6.56163E+00	3.24330E-07	-1.47840E-08	-2.14090E-11	3.40650E-12	/
R10	-4.85108E+01	2.28460E-06	-9.19560E-08	1.61110E-09	-9.08430E-14	/
R11	-9.17432E+00	-2.68170E-05	2.23660E-06	-1.06750E-07	2.20480E-09	/
R12	1.65805E+00	-1.08550E-06	3.52680E-08	-4.07850E-10	-1.49920E-11	/

[0124] Table 19 and Table 20 show design data of inflexion points and arrest points of each lens of the camera optical lens **50** in the fifth embodiment of the present disclosure.

TABLE 19

	Number(s) of inflexion points	Inflexion point position 1	Inflexion point position 2	Inflexion point position 3
P1R1	/	/	/	/
P1R2	/	/	/	/
P2R1	2	0.255	2.285	/
P2R2	1	0.755	/	/
P3R1	3	0.605	1.025	1.985
P3R2	1	2.035	/	/
P4R1	/	/	/	/
P4R2	/	/	/	/
P5R1	1	1.925	/	/
P5R2	1	0.365	/	/
P6R1	2	1.095	3.015	/
P6R2	1	1.395	/	/

TABLE 20

	Number(s) of arrest points	Arrest point position 1	Arrest point position 1
P1R1	/	/	/
P1R2	/	/	/
P2R1	2	0.425	2.585
P2R2	1	1.355	/
P3R1	1	2.305	/
P3R2	/	/	/
P4R1	/	/	/

TABLE 20-continued

	Number(s) of arrest points	Arrest point position 1	Arrest point position 1
P4R2	/	/	/
P5R1	1	2.565	/
P5R2	1	0.635	/
P6R1	1	2.005	/
P6R2	1	2.435	/

[0125] In addition, in the following table 25, the values corresponding to the various parameters in the fifth embodiment and the parameters specified in the condition are listed.

[0126] FIG. 18 shows a field curvature and a distortion after light with a wavelength of 850 nm passes through the camera optical lens 50 in the fifth embodiment. FIG. 19 shows a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens 50 in the fifth embodiment. FIG. 20 is a schematic diagram of a longitudinal aberration and a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens 50 in the fifth embodiment.

[0127] As shown in Table 25, the fifth embodiment satisfies the various conditions.

[0128] In this embodiment, an entrance pupil diameter (ENPD) of the camera optical lens 50 is 2.187 mm, an image height (IH) of 1.0H is 3.300 mm, and a field of view in a diagonal direction is 155.20°. Thus, the camera optical lens 50 meets the design requirement for large aperture, and miniaturization, the on-axis and off-axis aberrations are sufficiently corrected, thereby achieving excellent optical performance.

COMPARATIVE EMBODIMENT

[0129] FIG. 21 is a schematic structural diagram of the camera optical lens 60 according to the comparative embodiment. The meanings of the symbols in the comparative embodiment are the same as the meanings of the symbols in the first embodiment. In the following, only differences are described.

[0130] Table 21 and Table 22 show design data of the camera optical lens 60 in the comparative embodiment of the present disclosure.

TABLE 21

	R	d	nd	vd
S1	∞	d0=	-4.567	
R1	68.535	d1=	0.500	nd1 1.6610 vd1 20.53
R2	2.949	d2=	1.189	
R3	-103.242	d3=	0.840	nd2 1.6393 vd2 23.35
R4	-6.413	d4=	0.427	
R5	-13.354	d5=	1.241	nd3 1.5131 vd3 56.22
R6	5.415	d6=	0.250	
R7	14.763	d7=	2.656	nd4 2.0007 vd4 25.44
R8	-6.394	d8=	1.297	
R9	11.721	d9=	2.719	nd5 1.5131 vd5 56.22
R10	16.046	d10=	0.294	
R11	2.925	d11=	0.978	nd6 1.6393 vd6 23.35
R12	6.785	d12=	0.999	
R13	∞	d13=	0.300	ndg1 1.5233 vg1 54.52
R14	∞	d14=	1.874	
R15	∞	d15=	0.500	ndg2 1.5233 vg2 54.52
R16	∞	d16=	0.115	

TABLE 22

	Conic coefficient k	Aspheric surface coefficients				
		A4	A6	A8	A10	A12
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	1.55047E+03	1.08850E-02	1.70150E-03	-1.23540E-03	5.33960E-04	-1.35550E-04
R4	4.04171E+00	2.79300E-02	-1.25690E-03	-8.28860E-04	6.34870E-04	-2.00580E-04
R5	2.53038E+01	1.42390E-02	-5.64660E-03	7.92760E-04	2.21070E-04	-1.44870E-04
R6	3.24051E+00	-9.24150E-03	-1.05060E-03	4.28480E-04	-1.14290E-04	1.57080E-05
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	6.93611E+00	-1.63650E-03	1.46460E-05	-7.83760E-05	1.94570E-05	-3.51100E-06
R10	-2.46794E+01	-4.41220E-02	1.09420E-02	-2.16620E-03	3.17750E-04	-3.31930E-05
R11	-9.62981E+00	7.43760E-03	-1.01980E-02	3.87920E-03	-1.06450E-03	2.05460E-04
R12	1.67481E+00	4.47090E-03	-6.06030E-03	1.35920E-03	-1.97840E-04	1.86680E-05

	Conic coefficient k	Aspheric surface coefficients				
		A14	A16	A18	A20	/
R1	/	/	/	/	/	/
R2	/	/	/	/	/	/
R3	1.55047E+03	1.99580E-05	-1.55360E-06	4.76520E-08	4.38170E-11	/
R4	4.04171E+00	3.44290E-05	-3.02670E-06	1.01050E-07	5.07750E-11	/
R5	2.53038E+01	3.42160E-05	-4.19350E-06	2.60470E-07	-6.16530E-09	/
R6	3.24051E+00	-1.04510E-06	1.67700E-09	6.15610E-11	-6.91470E-11	/
R7	/	/	/	/	/	/
R8	/	/	/	/	/	/
R9	6.93611E+00	3.29030E-07	-1.45670E-08	-3.40410E-11	2.01640E-11	/
R10	-2.46794E+01	2.28530E-06	-9.18920E-08	1.61690E-09	1.93690E-13	/
R11	-9.62981E+00	-2.68300E-05	2.23640E-06	-1.06660E-07	2.20070E-09	/
R12	1.67481E+00	-1.08670E-06	3.47100E-08	-4.51110E-10	-7.52790E-13	/

[0131] Table 23 and Table 24 show design data of inflexion points and arrest points of each lens of the camera optical lens **60** in the comparative embodiment.

TABLE 23

	Number(s) of inflexion points	Inflexion point position 1	Inflexion point position 2
P1R1	/	/	/
P1R2	/	/	/
P2R1	2	0.275	2.515
P2R2	1	0.755	/
P3R1	/	/	/
P3R2	1	1.715	/
P4R1	/	/	/
P4R2	/	/	/
P5R1	1	1.765	/
P5R2	1	0.355	/
P6R1	2	1.105	3.265
P6R2	1	1.295	/

[0132] FIG. 22 shows a field curvature and a distortion after light with a wavelength of 850 nm passes through the camera optical lens **60** in the comparative embodiment. FIG. 23 shows a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **60** in the comparative embodiment. FIG. 24 is a schematic diagram of a longitudinal aberration and a lateral color after light with wavelengths of 830 nm, 850 nm and 870 nm pass through the camera optical lens **60** in the comparative embodiment.

[0133] Table 25 lists the values of each of the conditions in the comparative embodiments according to the above conditions. Apparently, the camera optical lens **60** in the comparison embodiment does not satisfy the above condition: $nd1 \geq 1.70$.

[0134] In the comparative embodiment, an entrance pupil diameter (ENPD) of the camera optical lens **60** is 2.463 mm, an image height (IH) of 1.0H is 3.300 mm, and a field of view (FOV) in a diagonal direction is 133.90°. Thus, the camera optical lens **60** does not have excellent optical, and the on-axis and off-axis aberrations are not sufficiently corrected.

TABLE 25

Parameters and conditional equations	First embodiment	Second embodiment	Third embodiment	Fourth embodiment	Fifth embodiment	Comparative embodiment
nd1	2.001	2.001	2.104	1.713	2.001	1.661
(FOV*f)/IH	130.455	130.106	125.472	121.629	134.078	130
R5/R6	-2.519	-1.206	-3.167	-2.589	-4.993	-2.466
R7/R8	-2.078	-1.008	-1.905	-2.311	-3.982	-2.309
d9/d11	2.749	1.400	4.081	4.986	2.262	2.779
f12/f	-2.717	-2.601	-1.208	-5.967	-2.663	-3.753
f	2.908	2.745	3.575	2.804	2.844	3.202
f1	-3.757	-3.489	-2.904	-4.966	-3.735	-4.841
f2	10.491	10.747	11.859	10.183	10.786	10.996
f3	-7.523	-10.013	-8.36	-7.179	-8.458	-7.448
f4	4.778	4.928	4.384	5.004	4.941	4.896
f5	66.159	44.273	31.344	85.238	49.623	70.948
f6	7.754	7.981	6.605	7.614	7.969	7.562
f12	-7.900	-7.139	-4.317	-16.731	-7.573	-12.017
FNO	1.30	1.30	1.30	1.30	1.30	1.30

TABLE 24

	Number(s) of arrest points	Arrest point position 1
P1R1	/	/
P1R2	/	/
P2R1	1	0.465
P2R2	1	1.365
P3R1	/	/
P3R2	/	/
P4R1	/	/
P4R2	/	/
P5R1	1	2.525
P5R2	1	0.635
P6R1	1	2.045
P6R2	1	2.135

[0135] It will be understood by those skilled in the art that the embodiments described above are specific embodiments realizing the present disclosure. In practice, various changes may be made to these embodiments in form and in detail without departing from the spirit and scope of the disclosure.

What is claimed is:

1. A camera optical lens, comprising in sequence from an object side to an image side: a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens;

wherein the camera optical lens satisfies the following conditions:

$$nd1 \geq 1.70; \text{ and}$$

$$(FOV * f) / IH \geq 120.00;$$

wherein $nd1$ represents a refractive index of the first lens; FOV represents a field of view of the camera optical lens; f represents a focal length of the camera optical lens; and IH represents an image height of the camera optical lens.

2. The camera optical lens of claim 1, wherein the camera optical lens further satisfies the following condition:

$$-5.00 \leq R5/R6 \leq -1.20;$$

wherein $R5$ represents a curvature radius of an object-side surface of the third lens; and

$R6$ represents a curvature radius of an image-side surface of the third lens.

3. The camera optical lens of claim 1, wherein the camera optical lens further satisfies the following condition:

$$-4.00 \leq R7/R8 \leq -1.00;$$

wherein $R7$ represents a curvature radius of an object-side surface of the fourth lens; and

$R8$ represents a curvature radius of an image-side surface of the fourth lens.

4. The camera optical lens of claim 1, wherein the camera optical lens further satisfies the following condition:

$$1.40 \leq d9/d11 \leq 5.00;$$

wherein $d9$ represents an on-axis thickness of the fifth lens, and

$d11$ represents an on-axis thickness of the sixth lens.

5. The camera optical lens of claim 1, wherein the camera optical lens further satisfies the following condition:

$$-6.00 \leq f12/f \leq -1.20;$$

wherein $f12$ represents a combined focal length of the first lens and the second lens.

6. The camera optical lens of claim 1, wherein the field of view FOV and the focal length f further satisfy the following condition:

$$(FOV * f)/IH \leq 150.00.$$

7. The camera optical lens of claim 1, wherein the first lens has a negative refractive power, and an image-side surface of the first lens is concave in a paraxial region,

wherein the camera optical lens further satisfies the following conditions:

$$0.33 \leq (R1 + R2)/(R1 - R2) \leq 1.97;$$

$$-3.54 \leq f1/f \leq -0.54; \text{ and}$$

$$0.02 \leq d1/TTL \leq 0.22;$$

wherein $R1$ represents a curvature radius of an object-side surface of the first lens;

$R2$ represents a curvature radius of the image-side surface of the first lens;

$f1$ represents a focal length of the first lens;

$d1$ represents an on-axis thickness of the first lens; and

TTL represents a total track length of the camera optical lens.

8. The camera optical lens of claim 1, wherein the second lens has a positive refractive power, an object-side surface of the second lens is concave in a paraxial region, and an image-side surface of the second lens is convex in the paraxial region;

wherein the camera optical lens further satisfies the following conditions:

$$0.54 \leq (R3 + R4)/(R3 - R4) \leq 1.71;$$

$$1.66 \leq f2/f \leq 5.87; \text{ and}$$

$$0.02 \leq d3/TTL \leq 0.09;$$

wherein $R3$ represents a curvature radius of the object-side surface of the second lens;

$R4$ represents a curvature radius of the image-side surface of the second lens;

$f2$ represents a focal length of the second lens;

$d3$ represents an on-axis thickness of the second lens; and

TTL represents a total track length of the camera optical lens.

9. The camera optical lens of claim 1, wherein the third lens has a negative refractive power, an object-side surface of the third lens is concave in a paraxial region, and an image-side surface of the third lens is concave in the paraxial region;

wherein the camera optical lens further satisfies the following conditions:

$$0.05 \leq (R5 + R6)/(R5 - R6) \leq 1.00;$$

$$-7.30 \leq f3/f \leq -1.56; \text{ AND}$$

$$0.02 \leq d5/TTL \leq 0.12;$$

wherein $R5$ represents a curvature radius of the object-side surface of the third lens;

$R6$ represents a curvature radius of the image-side surface of the third lens;

$f3$ represents a focal length of the third lens;

$d5$ represents an on-axis thickness of the third lens; and

TTL represents a total track length of the camera optical lens.

10. The camera optical lens of claim 1, wherein the fourth lens has a positive refractive power, an object-side surface of the fourth lens is convex in a paraxial region, and an image-side surface of the fourth lens is convex in the paraxial region;

wherein the camera optical lens further satisfies the following conditions:

$$0.00 \leq (R7 + R8)/(R7 - R8) \leq 0.90;$$

$$0.61 \leq f4/f \leq 2.69; \text{ and}$$

$$0.03 \leq d7/TTL \leq 0.27;$$

wherein $R7$ represents a curvature radius of the object-side surface of the fourth lens;

$R8$ represents a curvature radius of the image-side surface of the fourth lens;

$f4$ represents a focal length of the fourth lens;

$d7$ represents an on-axis thickness of the fourth lens; and

TTL represents a total track length of the camera optical lens.

11. The camera optical lens of claim **1**, wherein the fifth lens has a positive refractive power, an object-side surface of the fifth lens is convex in a paraxial region, and an image-side surface of the fifth lens is concave in the paraxial region;

wherein the camera optical lens further satisfies the following conditions:

$$-17.54 \leq (R9 + R10) / (R9 - R10) \leq -1.95;$$

$$4.38 \leq f5 / f \leq 45.60; \text{ and}$$

$$0.06 \leq d9 / TTL \leq 0.36;$$

wherein R9 represents a curvature radius of the object-side surface of the fifth lens;

R10 represents a curvature radius of the image-side surface of the fifth lens;

f5 represents a focal length of the fifth lens;

d9 represents an on-axis thickness of the fifth lens; and

TTL represents a total track length of the camera optical lens.

12. The camera optical lens of claim **1**, wherein the sixth lens has a positive refractive power, an object-side surface of

the sixth lens is convex in a paraxial region, and an image-side surface of the sixth lens is concave in the paraxial region;

wherein the camera optical lens further satisfies the following conditions:

$$-5.98 \leq (R11 + R12) / (R11 - R12) \leq -1.50;$$

$$0.92 \leq f6 / f \leq 4.36; \text{ and}$$

$$0.02 \leq d11 / TTL \leq 0.14;$$

wherein R11 represents a curvature radius of the object-side surface of the sixth lens;

R12 represents a curvature radius of the image-side surface of the sixth lens;

f6 represents a focal length of the sixth lens;

d11 represents an on-axis thickness of the fifth lens; and

TTL represents a total track length of the camera optical lens.

13. The camera optical lens of claim **1**, wherein the fourth lens is made of glass.

* * * * *