

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282079

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

DATEMA; BRYAN S.

AXLE PRESSURE SETTING SYSTEMS AND METHODS

Abstract

A vehicle includes a mixing drum rotatably coupled to a chassis, a fill level sensor configured to provide a signal indicative of a fill level of a material within the mixing drum, an axle assembly including a first tractive element, a suspension actuator coupled to the axle assembly and configured to apply a biasing force that forces the first tractive element into engagement with a ground surface, a lift axle including a second tractive element, a lift actuator coupled to the lift axle, and a controller. The controller is configured to calculate a target weight to be supported by at least one of the first tractive element or the second tractive element based on the fill level of the material within the mixing drum and control the suspension actuator to vary the biasing force based on the target weight.

Inventors: DATEMA; BRYAN S. (Rochester, MN)

Applicant: Oshkosh Corporation (Oshkosh, WI)

Family ID: 1000008619665

Assignee: Oshkosh Corporation (Oshkosh, WI)

Appl. No.: 19/216112

Filed: May 22, 2025

Related U.S. Application Data

parent US continuation 18384548 20231027 parent-grant-document US 12330338 child US 19216112

parent US continuation 17184100 20210224 parent-grant-document US 11833713 child US 18384548

us-provisional-application US 62986463 20200306

Publication Classification

Int. Cl.: B28C5/42 (20060101); **B60C23/00** (20060101); **B60P3/16** (20060101); **B60R16/023** (20060101); **B62D61/12** (20060101); **G01F23/22** (20060101); **G01L17/00** (20060101); **G01P3/00** (20060101); **G01S19/52** (20100101)

U.S. Cl.:

CPC B28C5/4217 (20130101); **B28C5/422** (20130101); **B28C5/4272** (20130101); **B60P3/16** (20130101); **B60R16/023** (20130101); **B62D61/12** (20130101); **G01F23/22** (20130101); **G01L17/00** (20130101); **G01P3/00** (20130101); **G01S19/52** (20130101); B60C23/001 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATION [0001] This application is a continuation of U.S. patent application Ser. No. 18/384,548, filed Oct. 27, 2023, which is a continuation of U.S. Patent Application No. 17/184, 100, filed Feb. 24, 2021, now U.S. Pat. No. 11,833,713, which claims the benefit of U.S. Provisional Patent Application No. 62/986,463, filed Mar. 6, 2020, all of which are incorporated herein by reference in their entireties.

BACKGROUND

[0002] The present disclosure relates generally to vehicle control systems. More specifically, the present disclosure relates to a control system for controlling one or more axles of a vehicle.

[0003] Certain vehicles, such as concrete mixers and dump trucks, carry heavy payloads (e.g., concrete) to various locations (e.g., job sites). To minimize the wear of the gross weight of the vehicle and the payload on the road and the vehicle, additional axles may be added to the vehicle to distribute the gross weight over a larger area (e.g., such that the total contact area between the tires of the vehicle and the ground increases). Once the vehicle arrives at a job site, payload may be unloaded, reducing the weight of the vehicle. The unloaded vehicle may then be driven to another location (e.g., a location where another payload is then loaded onto the vehicle). In the unloaded state, the additional axles may not be necessary. To effectively accommodate both situations, vehicles include lift axles that can be selectively engaged with the ground to distribute the load of the vehicle and reduce the weight supported by each individual axle. Conventionally, operation (e.g., raising or lowering) of these axles is controlled manually by an operator.

SUMMARY

[0004] At least one embodiment relates to a concrete mixing truck includes a chassis, a front axle and a rear axle coupled to the chassis, a lift axle coupled to the chassis and including a tractive element, a lift actuator coupled to the lift axle, a mixing drum rotatably coupled to the chassis, a fill level sensor coupled to the mixing drum and configured to provide a signal indicative of a fill level of a material within the mixing drum, and a controller. The lift axle is selectively repositionable between a lowered position in which the tractive element engages a support surface and a raised position in which the tractive element is lifted out of engagement with the support surface. The controller is operatively coupled to the lift actuator and the fill level sensor and configured to control the lift actuator to reposition the lift axle into the lowered position in response to the fill level exceeding a threshold fill level.

[0005] At least one embodiment relates to a control system including a controller configured to receive a signal from a variety of input devices. The input devices include a fill level sensor including a fill level, a global positioning system (GPS), a speed sensor, and a tire pressure sensor. The controller provides a signal to a variety of output devices. The variety of output devices include an axle lift controller. The axle lift controller is configured to reposition a lift axle in an

upper position and a lower position. The lift axle is positioned in a lowered position in response to the fill level exceeding a fill level threshold.

[0006] At least one embodiment relates to a method of controlling a concrete mixing truck including providing a chassis including a front axle and a rear axle, coupling a lift axle including a tractive element to the chassis, coupling a lift actuator to the lift axle, coupling a mixing drum to the lift actuator, coupling a fill level sensor to the mixing drum, and coupling a controller to the signal wherein the controller controls the position of the lift axle based on the signal response. The lift axle can be selectively positioned in a lowered position where the tractive element engages a ground support and a raised position where the tractive element disengages from the ground support. The sensor is configured to provide a signal response.

[0007] This summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0008] FIG. 1 is a top, left perspective view of a concrete mixer truck, according to an exemplary embodiment.

[0009] FIG. 2 is a left side view of the concrete mixer truck of FIG. 1.

[0010] FIG. 3 is a right side view of a concrete mixer truck, according to another exemplary embodiment.

[0011] FIG. 4 is a top, left perspective view of the concrete mixer truck of FIG. 1.

[0012] FIG. 5 is a schematic of a drivetrain of a concrete mixer truck, according to an exemplary embodiment.

[0013] FIG. 6 is a block diagram of a front axle of the drivetrain of FIG. 5.

[0014] FIG. 7 is a block diagram of a front tandem axle of the drivetrain of FIG. 5.

[0015] FIG. 8 is a block diagram of a pusher axle of the drivetrain of FIG. 5.

[0016] FIG. 9 is a right side view of a tag axle of the drivetrain of FIG. 5 in a raised configuration and a lowered configuration.

[0017] FIG. 10 is a block diagram of a control system of a concrete mixer truck.

[0018] FIGS. 11-16 are front section views of a concrete mixer drum of the concrete mixer truck of FIG. 1 in various rotational positions and at various fill levels.

[0019] FIG. 17 is a top view of a map including a variety of geofences, according to an exemplary embodiment.

DETAILED DESCRIPTION

[0020] Before turning to the figures, which illustrate certain exemplary embodiments in detail, it should be understood that the present disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology used herein is for the purpose of description only and should not be regarded as limiting.

Overall Vehicle

[0021] Referring to FIGS. 1-3, a vehicle, shown as concrete mixer truck 10, includes a chassis, shown as frame 12, and a cab, body, cabin, or personnel compartment, shown as cab 14, coupled to the frame 12 (e.g., at a front end thereof with respect to the main direction of travel). The frame 12 extends longitudinally along a length of the concrete mixer truck 10 (e.g., from a front end to a rear end, along a longitudinal axis that extends in a direction of travel, etc.). The frame 12 may include one or more frame rails. The cab 14 is configured to hold one or more occupants (e.g., a driver or

operator and/or one or more passengers, etc.). The cab **14** may include various components to facilitate operation of the concrete mixer truck **10** by an operator (e.g., a seat, a steering wheel, hydraulic controls, a user interface, switches, buttons, dials, etc.).

[0022] As shown in FIGS. **1-3**, the concrete mixer truck **10** includes a prime mover, shown as engine **16**. The engine **16** is configured to supply mechanical energy (e.g., rotational mechanical energy) to power one or more functions of the concrete mixer truck **10** (e.g., propelling the concrete mixer truck **10**, driving the mixing drum **102**, etc.). In the embodiment of FIG. **1**, the engine **16** is coupled to the frame **12** adjacent the cab **14** (e.g., at a front end of the cab **14**, at a front end of the concrete mixer truck **10**). In the embodiment shown in FIG. **3**, the engine **16** is coupled to the frame **12** at a rear end of the concrete mixer truck **10**. The engine **16** may be configured to utilize one or more of a variety of fuels (e.g., gasoline, diesel, bio-diesel, ethanol, natural gas, etc.), according to various exemplary embodiments. Additionally or alternatively, the prime mover may include one or more electric motors and/or generators, which may be coupled to the frame **12** (e.g., as a hybrid vehicle, an electric vehicle, etc.). The electric motors may consume electrical power from an on-board storage device (e.g., batteries, ultra-capacitors, etc.), from an on-board generator (e.g., an internal combustion engine, a genset, etc.), and/or from an external power source (e.g., overhead power lines, etc.) and provide power (e.g., rotational mechanical energy) to systems of the concrete mixer truck **10**.

Drum Assembly

[0023] As shown in FIGS. **1-3**, the concrete mixer truck **10** includes a payload container, a mixing assembly, a mixing drum assembly, or equipment, shown as drum assembly **100**. The drum assembly **100** is configured to receive and mix dry ingredients (e.g., cementitious material, aggregate, sand, etc.) and water and to form a wet concrete mixture, which can be transported to a job site. The drum assembly **100** then dispenses the concrete at the job site (e.g., for use in forming one or more structures, such as buildings, roads, or foundations). The drum assembly **100** includes a mixing drum, shown as mixing drum **102**. The mixing drum **102** is coupled to the frame **12** and disposed behind the cab **14** (e.g., at a rear and/or middle of the frame **12**, etc.). The mixing drum **102** defines an inlet/outlet, shown as mixing drum aperture **104**, through which material enters and exits the mixing drum **102**. In the embodiment shown in FIGS. **1** and **2**, the mixing drum aperture **104** is positioned at a rear end of the frame **12** (i.e., the concrete mixer truck **10** is a rear discharge concrete mixer truck). In the embodiment shown in FIG. **3**, the mixing drum **102** extends over the cab **14**, and the mixing drum aperture **104** is positioned at the front end of the frame **12** (i.e., the concrete mixer truck **10** is a front discharge concrete mixer truck).

[0024] As shown in FIGS. **1-4**, the concrete mixer truck **10** includes a first support, shown as front pedestal **106**, and a second support, shown as rear pedestal **108**. According to an exemplary embodiment, the front pedestal **106** and the rear pedestal **108** rotatably couple the mixing drum **102** to the frame **12**. By way of example, one or both of the pedestals may include one or more bearings that engage an outer surface of the mixing drum **102**. The mixing drum **102** is configured to rotate relative to the frame about a central, longitudinal axis of rotation, shown as axis **110**. In some embodiments, the axis **110** is oriented generally upward as the mixing drum **102** extends toward the mixing drum aperture **104** to facilitate retaining the mixture within the mixing drum **102**. As shown in FIGS. **1-3**, the axis **110** is angled relative to the frame **12** such that the axis **110** intersects a horizontal plane extending along a top of the frame **12**. According to an exemplary embodiment, the axis **110** is elevated from the frame **12** at an angle in the range of five degrees to twenty degrees. In other embodiments, the axis **110** is elevated by less than five degrees (e.g., four degrees, three degrees, etc.) or greater than twenty degrees (e.g., twenty-five degrees, thirty degrees, etc.). In an alternative embodiment, the concrete mixer truck **10** includes an actuator positioned to facilitate selectively adjusting the axis **110** to a desired or target angle (e.g., manually in response to an operator input/command, automatically according to a control scheme, etc.).

[0025] According to an exemplary embodiment, drum assembly **100** includes a rotational actuator

(e.g., an electric motor, a hydraulic motor, etc.), shown as drum motor **120**. The drum motor **120** is configured to drive rotation of the mixing drum **102** about the axis **110**. In some embodiments, the drum motor **120** is powered by the engine **16**. By way of example, the engine **16** may drive a pump that provides a flow of pressurized hydraulic fluid to the drum motor **120**. In other embodiments, the drum motor **120** is an electric motor that consumes electrical energy (e.g., from an energy storage device, such as a battery, from a generator coupled to the engine **16**, etc.). The drum motor **120** may rotatably couple the mixing drum **102** to the front pedestal **106** (e.g., as shown in FIG. **1**) or to the rear pedestal **108** (e.g., as shown in FIG. **3**).

[0026] As shown in FIGS. **2** and **3**, the drum assembly **100** includes at least one internal protrusion (e.g., a ridge, a fin, a plate, etc.), shown as mixing element **122**. The mixing element **122** extends inward from an internal surface of the mixing drum **102** such that the mixing element **122** agitates the mixture within the mixing drum **102** when the mixing drum **102** is rotated (e.g., by the drum motor **120**). The mixing element **122** extends longitudinally along a length of the mixing drum **102**. In some embodiments, the mixing element **122** is shaped (e.g., helical or spiral-shaped) such that the mixing element **122** (a) drives the mixture toward the mixing drum aperture **104** when driven in a first rotational direction (e.g., clockwise) and (b) drives the mixture away from the mixing drum aperture **104**, agitating the mixture, when driven in a second rotational direction opposite the first rotational direction (e.g., counterclockwise). Accordingly, the drum motor **120** is configured to control whether the mixture is agitated or dispensed by controlling the direction of rotation of the mixing drum **102**. In some embodiments, the drum assembly **100** includes a container or vessel, shown as water tank **124**, that contains a volume of water. The water tank **124** may selectively (e.g., as controlled by a pump and/or valve) supply water to the mixing drum **102** to control a characteristic (e.g., consistency, slump, etc.) of the mixture within the mixing drum **102**.

[0027] As shown in FIGS. **1-3**, the drum assembly **100** includes an inlet assembly, shown as hopper **130**, coupled to the frame **12**. The hopper **130** is positioned at the mixing drum aperture **104** and configured to direct material (e.g., dry ingredients, water, etc.) into the mixing drum **102** through the mixing drum aperture **104**. The drum assembly **100** further includes an outlet assembly, shown as chute **132**, coupled to the frame **12**. The chute **132** is positioned at the mixing drum aperture **104** such that the chute **132** receives material (e.g., the concrete mixture) discharged from the mixing drum **102**. The chute **132** may be selectively repositioned by an operator to control the trajectory of the material. In some embodiments, the drum assembly **100** further includes a funnel, shown as collector **134**, that is positioned between the mixing drum aperture **104**. The collector **134** may be positioned and sized to receive the material discharged from the mixing drum aperture **104** and direct the material to the chute **132**.

Drivetrain

[0028] Referring to FIGS. **1-3** and **5**, the concrete mixer truck **10** includes a drivetrain, powertrain, drive system, or ground engagement system, shown as drivetrain **200**. The drivetrain **200** is coupled to the frame **12** and configured to engage a support surface (e.g., the ground) to support the concrete mixer truck **10**. Specifically, the drivetrain **200** includes a series of tractive elements (e.g., wheel and tire assemblies), shown as wheels **202**, configured to engage the support surface. The wheels **202** are coupled to the frame **12** by a series of axle assemblies extending laterally across the frame **12**. The axle assemblies are offset longitudinally from one another along the length of the concrete mixer truck **10**. The drivetrain **200** includes a first axle assembly (e.g., a steering axle, a drive axle), shown as front axle **210**; a second axle assembly (e.g., a non-steering or fixed axle, a drive axle), shown as front tandem axle **220**; and a third axle assembly (e.g., a non-steering or fixed axle, a drive axle), shown as rear tandem axle **230**; a fourth axle assembly (e.g., a non-powered axle, a lift axle), shown as pusher axle **240**; and a fifth axle assembly (e.g., a non-powered axle, a lift axle), shown as tag axle **250**. In other embodiments, the drivetrain **200** includes more or fewer axle assemblies. By way of example, the tandem axles may be replaced with a single driven axle. By way of example, the drivetrain **200** may include multiple pusher axles **240** and/or tag axles **250**.

[0029] As shown, the front axle **210** is the frontmost axle assembly and is positioned at the front end of the frame **12**. In some embodiments, the front axle **210** is positioned directly below the cab **14**. The front tandem axle **220** and the rear tandem axle **230** are positioned rearward of the front axle **210** in a tandem (i.e., side-by-side) configuration. The front tandem axle **220** is positioned forward of the rear tandem axle **230**. In some embodiments, the front tandem axle **220** and the rear tandem axle **230** are positioned directly below the drum assembly **100**. The pusher axle **240** is positioned between the front axle **210** and the front tandem axle **220**. In some embodiments, the pusher axle **240** is positioned directly below the drum assembly **100**. The tag axle **250** is positioned rearward of the rear tandem axle **230**.

[0030] As shown in FIG. 5, the drivetrain **200** includes components that couple the engine **16** to certain axles to permit the axles to drive the wheels **202** to propel the concrete mixer truck **10**. The concrete mixer truck **10** includes a power transfer device (e.g., a gearbox, a power transmission, a torque control device, or a variable ratio transmission), shown as transmission **260**. The transmission **260** is coupled (e.g., directly coupled, coupled by one or more intermediate shafts, etc.) to the engine **16** such that the transmission **260** is configured to receive rotational mechanical energy from the engine **16**. The transmission **260** may include one or more gears, brakes, clutches, or other power transmission devices configured to control (e.g., automatically, manually in response to an input from a user, etc.) an output speed of the transmission **260**.

[0031] Referring still to FIG. 5, the transmission **260** is coupled to a torque transfer device or torque distribution device, shown as transfer case **262**. As shown, the transfer case **262** is coupled to the transmission **260** by a shaft, shown as driveshaft **264**. In other embodiments, the transfer case **262** is otherwise coupled (e.g., directly coupled) to the transmission **260**. The transmission **260** and the transfer case **262** may be coupled to the frame **12**. The transmission **260** transfers rotational mechanical energy from the engine **16** to the transfer case (e.g., through the driveshaft **264**). The transfer case **262** then divides and transfers this rotational mechanical energy to the front axle **210** and the tandem axles.

[0032] The front axle **210** includes a power transmission device, shown as differential **266**, that is coupled to the transfer case **262** by a shaft, shown as driveshaft **268**. The differential **266** transfers rotational mechanical energy from the transfer case **262** to each wheel **202** of the front axle **210**. The front tandem axle **220** includes a power transmission device, shown as differential **270**, and the rear tandem axle **230** includes a power transmission device, shown as differential **272**. The differential **270** is coupled to the transfer case **262** by a driveshaft **274**, and the differential **272** is coupled to the differential **270** by a driveshaft **276**. The differential **270** transfers rotational mechanical energy from the transfer case **262** to the wheels **202** of the front tandem axle **220** and to the differential **272** (e.g., through the driveshaft **276**). The differential **272** transfers rotational mechanical energy from the driveshaft **276** to the wheels **202** of the rear tandem axle **230**.

Accordingly, the using this mechanical energy, the wheels **202** of the front axle **210**, the front tandem axle **220**, and the rear tandem axle **230** propel the concrete mixer truck **10**. In other embodiments, one or more of the front axle **210**, the front tandem axle **220**, and the rear tandem axle **230** are not driven. In such an embodiment, the transfer case **262** may be omitted, and one or more differentials (e.g., the differential **270**) may be directly coupled to the transmission **260**.

[0033] In some embodiments, the pusher axle **240** and the tag axle **250** are non-powered (e.g., non-driven, free-spinning, etc.) such that the wheels **202** of the pusher axle **240** and the tag axle **250** rotate freely (e.g., as concrete mixer truck **10** travels). Accordingly, the pusher axle **240** and the tag axle **250** may be decoupled from the engine **16** such that they pusher axle **240** and the tag axle **250** do not receive rotational mechanical energy from the engine **16** to propel the vehicle. The pusher axle **240** and/or the tag axle **250** may be configured to selectively engage the support surface (e.g., may be selectively raised or lowered to engage the ground) to support the gross weight of the concrete mixer truck **10** (i.e., the weight of the concrete mixer truck **10** and any payload, such as concrete, that is supported by the concrete mixer truck **10**). By way of example, when the gross

weight of the concrete mixer truck **10** is relatively high (e.g., the concrete mixer truck **10** is loaded with concrete), the pusher axle **240** and/or the tag axle **250** may be lowered to engage the ground. This puts a greater number of wheels **202** in contact with the ground, decreasing the weight supported by each wheel **202** and thus the pressure exerted on the ground. This may reduce wear on roads, and may be required by certain regulatory bodies in certain situations (e.g., a maximum weight per axle may be specified). When the gross weight of the concrete mixer truck **10** is relatively low (e.g., the mixing drum **102** is empty), the pusher axle **240** and/or the tag axle **250** may be lifted out of contact with the ground. This may reduce wear on the axle assemblies (e.g., bearing wear, tire wear, etc.) and may improve fuel efficiency.

[0034] FIGS. **6-8** illustrate the various systems that control each axle. Each axle includes a series of actuators that permit the user or a controller (e.g., the controller **402**) to control one or more aspects of the operation of each axle. In FIGS. **6-9**, dashed lines are used to illustrate the communication of signals (e.g., electrical signals, pressurized fluids, movement of a mechanical linkage, etc.) between different components. This communication may include one-way or two-way communication. As shown and described with respect to FIGS. **6-8**, each axle includes two wheels **202**, one positioned at each end of the axle. In other embodiments, each axle includes multiple wheels **202** at each end. Although specific arrangements of each axle are shown, in other embodiments, the components of each axle are otherwise positioned.

[0035] Referring to FIG. **6**, the front axle **210** is shown according to an exemplary embodiment. The front axle **210** includes an assembly, shown as axle main body **300**. The axle main body **300** may include a housing and/or one or more axle shafts that transfer rotational mechanical energy to the wheels **202**. The axle main body **300** may additionally include one or more housing members rotatably coupled (e.g., by one or more bearings) to the axle shafts that facilitate connection to the frame **12** and other components of the front axle **210**. The axle main body **300** further includes the differential **266**. The axle main body **300** may configure the front axle **210** as a dependent suspension (i.e., such that both wheels **202** move together) or an independent suspension (i.e., such that the wheels **202** can move independently of one another).

[0036] The axle main body **300** is movably coupled to the frame **12** by a pair of suspension assemblies (e.g., a spring assembly, a damper assembly, a combination spring/damper assembly, etc.), shown as suspension actuators **302**. The suspension actuators **302** are coupled to the frame **12** and the axle main body **300** and are offset laterally from one another along the length of the axle main body **300**. As shown, the suspension actuators **302** are configured to provide a biasing force to hold the frame **12** upward, away from the axle main body **300**. When the axle main body **300** experiences a vertical excitement force (e.g., from the wheels **202** encountering a bump during normal travel of the concrete mixer truck **10**), the suspension actuators **302** are configured to control the vertical movement of the axle main body **300** (and thus the wheels **202**) relative to the frame **12**. The suspension actuators **302** may provide a damping force based on a speed of the axle main body **300** relative to the frame **12**. Additionally or alternatively, the suspension actuators **302** may provide a spring force based on the position of the axle main body **300** relative to the frame **12**.

[0037] The suspension actuators **302** may include a spring element (e.g., a biasing element) that provides a spring force and/or a dampening element that provides a dampening force. In some embodiments, the spring element is a gas spring (e.g., an air bag) that contains a compressible gas. The compressible gas may exert a biasing spring force that biases the frame **12** upward. In other embodiments, the suspension actuators **302** include coil springs, leaf springs, or yet other types of biasing elements. In some embodiments, the dampening elements include one or more dampeners that produce a dampening force by forcing a fluid through an orifice. The spring elements and/or dampening elements may be coupled to the axle main body **300** and the frame **12** by one or more linkages, brackets, mounts, or other coupling arrangements.

[0038] In some embodiments, the suspension actuators **302** are actively controlled to vary the ride

height and/or the suspension response characteristics of each suspension actuator **302**. By way of example, a fluid (e.g., compressed gas, hydraulic oil, etc.) can be selectively added or removed from each suspension actuator **302** to vary the length of the suspension actuator **302**. If this is performed by multiple suspension actuators **302** (e.g., the suspension actuators of the front axle **210**, the front tandem axle **220**, and the rear tandem axle **230**), the ride height of the concrete mixer truck **10** may be varied. By way of another example, a fluid may be selectively added or removed from each suspension actuator **302** to vary the force applied by each suspension actuator **302**. By adding fluid (e.g., gas) to one suspension actuator **302**, the pressure within the suspension actuator **302** increases, increasing the force imparted by the suspension actuator **302**. This increases the portion of the gross weight of the concrete mixer truck **10** supported by the suspension actuator **302** (and thus the closest wheel **202** and the front axle **210** as a whole). Accordingly, fluid may be added to the suspension actuator **302** to control the force that the corresponding wheel **202** exerts on the ground.

[0039] As shown in FIG. **6**, each suspension actuator **302** is coupled (e.g., operatively, fluidly, etc.) to a suspension control device, suspension controller, valve, or actuator, shown as suspension controller **304**. The suspension controller **304** is configured to control at least one of (a) the position of the corresponding wheel **202** (e.g., by varying the length of the suspension actuator **302**) or (b) the suspension response characteristics of the suspension actuator **302**. In some embodiments, the suspension controller **304** includes one or more valves that control the flow of fluid into or out of the suspension actuator **302**. Accordingly, the suspension controller **304** may control both the position of the corresponding wheel **202** and the force exerted by the corresponding wheel **202**. By including a suspension controller **304** for each suspension actuator **302**, the suspension of each wheel **202** can be independently controlled. In other embodiments, one of the suspension actuators **302** is omitted, and one suspension controller **304** controls both suspension actuators **302**. In such an embodiment, the suspension controller **304** may provide similar control outputs (e.g., fluid at the same pressure or flow rate) to each suspension actuator **302**.

[0040] In other embodiments, the suspension actuators **302** are passively controlled. By way of example, each suspension actuators **302** may include coil spring and a sealed damper such that the position of the corresponding wheel **202** and the suspension response characteristics are fixed. In embodiments where the suspension actuators **302** are passively controlled, the concrete mixer truck **10** may have a predetermined or predefined ride height. Additionally or alternatively, the concrete mixer truck **10** may have predetermined or predefined suspension response characteristics.

[0041] As shown in FIG. **6**, the front axle **210** includes two suspension actuators **302**, each at a different lateral position along of the axle main body **300** and each corresponding to a different wheel **202**. The deflection (e.g., compression) of each suspension actuator **302** controls the vertical position of the axle main body **300** where the suspension actuator **302** is coupled to the axle main body **300**. Because the suspension actuator **302** is closer to one wheel **202** than the other wheel **202**, deflection of that suspension actuator **302** also primarily affects the vertical position of that wheel **202** (although this deflection may also affect the vertical position of the other wheel **202** to a lesser degree). Accordingly, when the length of one suspension actuator **302** changes at a different rate than the length of the other suspension actuator **302** of the front axle **210**, the front axle **210** rotates (e.g., about a longitudinal axis). This articulation of the axle may facilitate moving over obstacles that only engage one wheel **202** of the front axle **210**, permitting the other wheel **202** to stay in engagement with the ground.

[0042] Referring again to FIG. **6**, in some embodiments, the front axle **210** includes axle articulation controllers (e.g., articulation brakes, articulation locks, etc.), shown as locks **306**. In some embodiments, the locks **306** are coupled to at least one of (a) the frame **12**, (b) a suspension actuator **302**, or (c) the axle main body **300**. The locks **306** are configured to selectively limit (e.g., prevent) movement of the axle main body **300** relative to the frame **12**. Accordingly, the locks **306**

are configured to selectively prevent vertical movement of the wheels **202**. The locks **306** may limit movement of the axle main body **300** directly. By way of example, the locks **306** may be directly coupled to the axle main body **300** and the frame **12** and may maintain a fixed length when engaged. Alternatively, the locks **306** may limit movement of the axle main body **300** indirectly by limiting movement of the suspension actuator **302**. By way of example, the locks **306** may prevent fluid flow into or out of the suspension actuator **302**. In embodiments where the front axle **210** has a dependent suspension, the locks **306** may control the positions of both wheels **202** simultaneously. In embodiments where the front axle **210** has an independent suspension, the locks **306** may control the positions of each wheel **202** independently. In other embodiments, the front axle **210** includes only one lock **306**. In yet other embodiments, the locks **306** are omitted from the front axle **210**.

[0043] Referring still to FIG. **6**, the front axle **210** includes a pair of brake assemblies, shown as brakes **310**. Each brake **310** is coupled to one of the wheels **202** (e.g., to a hub of one of the wheels **202**). The brakes **310** are configured to resist rotation of the wheels **202** to arrest and/or prevent further motion of the concrete mixer truck **10**. The brakes **310** may include disc brakes, drum brakes, or other brake arrangements. The brakes **310** are coupled (e.g., operatively, fluidly, etc.) to a brake control device, brake controller, valve, or actuator, shown as brake controller **312**. The brake controller **312** is configured to control actuation of the brakes **310**. By way of example, the brake controller **312** may include a pump, compressor, or valve that initiates a flow of pressurized fluid (e.g., brake fluid, air, etc.) to the brakes **310** that engages the brakes, limiting movement of the wheels **202**. The brake controller **312** may be coupled to an electronic controller (e.g., the controller **402**) or may be initiated mechanically or electromechanically (e.g., in response to an operator pressing a brake pedal, in response to a user engaging a parking brake, etc.).

[0044] Referring still to FIG. **6**, the front axle **210** includes a heading control assembly, shown as steering assembly **320**. The steering assembly **320** is configured to initiate rotation of the wheels **202** about respective vertical or substantially vertical axes, thereby changing the trajectory of the concrete mixer truck **10** (e.g., causing the concrete mixer truck **10** to turn). The steering assembly **320** includes a linkage, shown as tie rod **322**, that is coupled to both of the wheels **202** of the front axle **210**. The tie rod **322** controls the rotation of both wheels **202** such that the wheels **202** rotate at similar rates and in similar directions. An actuator assembly (e.g., a motor, a linkage, etc.), shown as steering actuator **324**, is coupled to the tie rod **322**. The steering actuator **324** is configured to steer the concrete mixer truck **10**. Specifically, the steering actuator **324** is configured to move the tie rod **322** laterally to cause a corresponding rotation of the wheels **202**. The steering actuator **324** may include various motors, linkages, shafts, gears, pins, or other components to facilitate this motion. The steering actuator **324** may be controlled by an operator (e.g., through a user interface device, such as a steering wheel). Such an interface device may directly control the steering actuator **324**, or an electronic controller (e.g., the controller **402**) may receive an input from the user interface and provide a corresponding output to the steering actuator **324**. The steering assembly **320** further includes a dampener and/or biaser (e.g., a spring), shown as steering dampener **326**, coupled to the tie rod **322** and the axle main body **300**. The steering assembly **320** is configured to apply a dampening force the tie rod **322** to resist motion of steering assembly **320**. This may attenuate undesirable movement (e.g., vibration, oscillation, etc.) of the steering assembly **320**. Additionally or alternatively, the steering dampener **326** may be configured to apply a biasing force to bias the steering assembly **320** toward a central position (e.g., corresponding to travel in a straight direction).

[0045] Referring to FIGS. **6** and **9**, the concrete mixer truck **10** includes a tire pressure control system or central tire inflation (CTI) system, shown as CTI system **330**. The CTI system **330** is configured to manage (e.g., control, increase, decrease, maintain at a desired setpoint) the tire pressure of each wheel **202**. The CTI system **330** includes a compressed gas source, shown as compressor **332**, configured to provide a supply of pressurized gas (e.g., air). The compressor **332**

may be driven by the engine **16** or powered by electrical energy (e.g., from one or more energy storage devices or generators). The compressor **332** may communicate with one or more storage tanks for storage of the pressurized gas. In other embodiments, the compressed gas source is a prefilled tank of pressurized gas. The compressor **332** is fluidly coupled to each of the wheels **202** through one or more lines (e.g., conduits, hoses, pipe, etc.) and one or more tire pressure controllers, CTI system outputs, or valves, shown as tire pressure valves **334**. The tire pressure valves **334** are configured to selectively permit pressurized gas to enter a corresponding wheel **202** to increase tire pressure. The tire pressure valves **334** are configured to selectively permit pressurized gas to exit a corresponding wheel **202** (e.g., into the atmosphere) to reduce tire pressure. In other embodiments, the CTI system **330** is omitted from the concrete mixer truck **10**. [0046] Referring to FIG. 7, the front tandem axle **220** is shown according to an exemplary embodiment. Except as otherwise specified, the front tandem axle **220** may be substantially similar to the front axle **210**. Additionally, the front tandem axle **220** may be substantially similar to the rear tandem axle **230** except as otherwise specified. The axle main body **300** of the front tandem axle **220** includes the differential **270**. The axle main body **300** of the rear tandem axle **230** includes the differential **272**. In some embodiments, some or all of the axles of the concrete mixer truck **10** share the same brake controller **312** such that all of the brakes **310** activate simultaneously when a brake command is received.

[0047] The front tandem axle **220** omits the steering actuator **324** such that the steering of the front tandem axle **220** is not actively controlled. Instead, the steering dampener **326** and the dynamics of the wheels **202** and the steering assembly generally keep the wheels **202** centered and prevent oscillations. When concrete mixer truck **10** turns (e.g., as controlled by the front axle **210**), the steering assembly **320** of the front tandem axle **220** permits the wheels **202** to passively turn. In other embodiments, the steering assembly **320** is omitted from the front tandem axle **220**, and the wheels **202** maintain a constant (e.g., perpendicular) orientation relative to the axle main body **300**.

[0048] Referring to FIG. 8, the pusher axle **240** is shown according to an exemplary embodiment. Except as otherwise specified, the pusher axle **240** may be substantially similar to the front tandem axle **220**. In some embodiments, the pusher axle **240** is non-powered. Accordingly, the axle main body **300** omits the differential, and the wheels **202** may be permitted to spin freely relative to one another. As shown, the steering actuator **324** is omitted from the steering assembly **320**. In other embodiments, the steering assembly **320** is omitted from the pusher axle **240**, and the wheels **202** maintain a constant (e.g., perpendicular) orientation relative to the axle main body **300**.

[0049] The pusher axle **240** further includes one or more (e.g., shown as two) actuators (e.g., axle lift actuators) or biasing members, shown as axle lifters **350**. As shown, the axle lifters **350** are coupled to the frame **12** and the axle main body **300**. The axle lifters **350** are configured to lift the axle main body **300** relative to the frame **12** (e.g., such that the wheels **202** are brought out of engagement with the ground). Each axle lifter **350** may include one or more hydraulic cylinders, pneumatic cylinders, air bags, electric motors, or other types of actuators. Each axle lifter **350** may include one or more biasing members or biasing elements (e.g., coil springs, leaf springs, gas springs, etc.). Each axle lifter **350** may include linkages, brackets, mounts, or coupling arrangements that facilitate coupling the axle lifter **350** to the frame **12** and/or the axle main body **300**. As shown, the two axle lifters **350** are offset laterally along the length of the axle main body **300**. Accordingly, each axle lifter **350** acts to primarily lift one of the wheels **202** (e.g., the wheel **202** closest to the axle lifter **350**).

[0050] In some embodiments, the axle lifters **350** are actively controlled to selectively lift the wheels **202** out of contact with the ground. By way of example, a fluid (e.g., compressed gas, hydraulic oil, etc.) can be selectively added or removed from each axle lifter **350** to vary the displacement (e.g., length) of the axle lifter **350**. The axle lifters **350** are coupled to the frame **12** and the axle main body **300** such that the displacement of each axle lifter **350** has a corresponding vertical position of the corresponding wheel **202**. In some embodiments, the axle lifters **350** are

generally selectively reconfigurable (e.g., selectively repositionable) between a lowered configuration in which the wheels **202** contact the ground and a raised configuration in which the wheels **202** are lifted out of contact with the ground.

[0051] As shown in FIG. **8**, each axle lifter **350** is coupled (e.g., operatively, fluidly, etc.) to a lift control device, lift actuator controller, valve, or actuator, shown as axle lift controller **352**. The axle lift controllers **352** are configured to control the position of the corresponding wheel **202** (e.g., between a raised or lifted position and a lowered or operation position) by varying the configuration (e.g., displacement) of the axle lifter **350**. In some embodiments, the axle lift controller **352** includes one or more valves that control the flow of fluid into or out of the axle lifter **350**. By including an axle lift controller **352** for each axle lifter **350**, each wheel **202** can be independently lifted. In other embodiments, one of the axle lift controller **352** is omitted, and one axle lift controller **352** controls both axle lifters **350**. In other embodiments, the pusher axle **240** includes only one axle lifter **350** and thus only one axle lift actuator controller.

[0052] In other embodiments, the axle lifter **350** includes a passive biasing member (e.g., a spring) that is configured to impart an upward biasing force on the axle main body **300**. In such embodiments, the wheels **202** (e.g., and thus the pusher axle **240**) may default to the raised configuration when the concrete mixer truck **10** is in an unpowered state. The wheels **202** may be forced downward to the lowered configuration by the suspension actuators **302**. By way of example, the axle lifters **350** may include compression springs that apply a biasing force to the axle main body **300** to bias the axle main body **300** and the wheels **202** toward the raised position. The suspension actuators **302** may include air bags that, when supplied with pressurized air, overcome the biasing forces of the springs.

[0053] Referring to FIGS. **1**, **2**, and **9**, the tag axle **250** is shown according to an exemplary embodiment. The tag axle **250** is shown in the lowered configuration in solid lines and in the raised configuration in dashed lines. In this embodiment, the tag axle **250** includes an axle lifter **350** that includes a frame assembly, shown as tag axle subframe **360**, and an actuator, shown as hydraulic cylinder **362**. The axle main body **300** is fixedly coupled to the tag axle subframe **360**, and the suspension actuators **302** and the locks **306** are omitted. In other embodiments, the axle main body **300** is coupled to the tag axle subframe **360** by one or more suspension actuators. The tag axle subframe **360** is pivotally coupled to the frame **12** such that the tag axle subframe **360** is rotatable relative to the frame **12** about a lateral axis A1. Accordingly, the tag axle subframe **360** is rotated about the lateral axis A1 to raise or lower the wheels **202**. A first end of the hydraulic cylinder **362** is pivotally coupled to the tag axle subframe **360**, and an opposing second end of the hydraulic cylinder **362** is pivotally coupled to the frame **12**. The hydraulic cylinder **362** is rotatable relative to the frame **12** about a lateral axis A2. To lower the wheels **202**, the hydraulic cylinder **362** is extended, and to raise the wheels **202**, the hydraulic cylinder **362** is retracted. The hydraulic cylinder **362** may be controlled by an axle lift controller **352** (e.g., a valve that selectively supplies pressurized hydraulic fluid from a pump to the hydraulic cylinder **362** to extend or retract the hydraulic cylinder **362**).

Control System

[0054] Referring to FIG. **10**, the concrete mixer truck **10** includes a control system **400**. The control system **400** includes a controller (e.g., an electronic controller) or processing circuit, shown as controller **402**. The controller **402** includes a processor **404** and a memory device, shown as memory **406**. The controller **402** may be configured to monitor and/or control various aspects of the concrete mixer truck **10**. Specifically, the controller **402** may receive inputs from a variety of input devices, and provide commands to a variety of output devices. As shown in FIGS. **6-9**, the controller **402** provides outputs to one or more of: the engine **16**; the drum motor **120**; a user interface **410**; the suspension controllers **304**; the locks **306**; the axle lift controllers **352**; the brake controller **312**; the steering actuator **324**; the compressor **332**; the tire pressure valves **334**; or other output devices. The controller **402** receives inputs from one or more of: the engine **16**; the user

interface **410**; a fill level sensor **420**; wheel force sensors **308**; wheel position sensors **309**; tire pressure sensors **336**; a global positioning system (GPS) **430**; a speed sensor **432**; or other input devices. In one embodiment, the controller **402** is onboard the concrete mixer truck **10**. In other embodiments, at least a portion of the control system **400** (e.g., controller **402** a second controller **402**, another processing circuit, etc.) is disposed in a location that is remote from the concrete mixer truck **10**.

Wheel Force Sensors

[0055] Referring to FIG. **10**, the control system includes input devices, pressure sensors, or force sensors, shown as wheel force sensors **308**, operatively coupled to the controller **402**. Each wheel force sensor **308** is associated with one of the wheels **202** and/or one of the axle assemblies. Specifically, each wheel force sensor **308** is configured to provide a signal indicative of the weight supported by each wheel **202** and/or the total weight supported by one of the axle assemblies. Additionally or alternatively, the signal may indicate the force separating each wheel **202** and/or one of the axle assemblies from the frame **12**. In some embodiments, the wheel force sensor **308** includes a pressure sensor that measures a pressure within the suspension actuator **302** or the axle lifter **350** associated with a wheel **202** and/or an axle. The relationship between this pressure and the weight supported by the corresponding wheel **202** and/or axle may be predetermined and stored in the memory **406**. In some embodiments, the wheel force sensor **308** includes a load cell or other force transducer that measures a force on a component of the axle (e.g., a force applied by the suspension actuator **302** and/or the axle lifter **350**, a force on the axle main body **300**). The relationship between this force and the weight supported by the corresponding wheel **202** and may be predetermined and stored in the memory **406**. In some embodiments, the wheel force sensor **308** includes a strain gauge configured to measure a strain experienced by a component of the axle assembly. The relationship between this strain and the weight supported by the corresponding wheel **202** and/or axle may be predetermined and stored in the memory **406**. The controller **402** (onboard the concrete mixer truck **10** and/or a processing circuit disposed in a location that is remote from the concrete mixer truck **10**, in which case the signals from one or more of the sensors may be transmitted to the remote processing circuit, processed by the remote processing circuit, and command signals may thereafter be provided from the remote processing circuit to the concrete mixer truck to actuate one or more components) may use the wheel force sensors **308** to provide closed loop control of the suspension actuators **302** (e.g., using the suspension controllers **304**) and/or the axle lifters **350** (e.g., using the axle lift controllers **352**) to achieve a target weight supported by each wheel **202** or axle.

Wheel Position Sensors

[0056] Referring still to FIG. **10**, the control system **400** includes input devices, position sensors, length sensors, or displacement sensors, shown as wheel position sensors **309**, operatively coupled to the controller **402**. The wheel position sensors **309** are configured to provide a signal indicative of a position of each wheel **202** and/or axle relative to the frame **12**. The wheel position sensors **309** may include one or more position or length sensors (e.g., linear variable differential transformers (LVDTs), potentiometers, ultrasonic distance sensors, etc.) that measure at least one of (a) the displacement of a component or (b) the relative position of two components. The relationship between this measured value and the position of a corresponding wheel **202** and/or axle may be predetermined and stored in the memory **406**. The controller **402** may use the wheel position sensors **309** to provide closed loop control of the suspension actuators **302** and/or the axle lifters **305** to achieve a target axle or wheel **202** position. By performing this across multiple axles, the controller **402** may achieve a target ride height.

Tire Pressure Sensors

[0057] The control system **400** further includes a series of pressure sensors, shown as tire pressure sensors **336**, operatively coupled to the controller **402**. The tire pressure sensors **336** are configured to provide a signal indicative of the pressure within the tire of a corresponding wheel **202**. The

controller **402** may use the tire pressure sensors **336** in conjunction with the compressor **332** and/or the tire pressure valves **334** to provide closed loop control of the tire pressure of each wheel **202** (e.g., individually). By way of example, the controller **402** may open a tire pressure valve **334** and activate the compressor **332** to increase the pressure within a tire of a corresponding wheel **202** until the corresponding tire pressure sensor **336** indicates that a target tire pressure has been reached.

User Interface

[0058] Referring to FIG. **10**, the control system **400** includes an input device, output device, input/output device, or user interface, shown as user interface **410**. The user interface **410** is configured to facilitate interaction between a user (e.g., the driver) and the control system **400**. The user interface **410** may provide information to a user. By way of example, the user interface **410** may include lights, speakers, gauges, displays (e.g., LCD displays, LED displays, etc.), haptic feedback devices, or other devices capable of conveying information to a user. The user interface **410** may additionally or alternatively receive information (e.g., commands) from a user and provide the information to the controller **402**. By way of example, the user interface **410** may include switches, buttons, pedals, knobs, wheels, touch screens, touch pads, microphones, or other devices. The user interface **410** may include user devices (e.g., smartphones, laptop computers, tablets, etc.) in communication with the controller **402** (e.g., through a wireless communication protocol, such as Bluetooth).

Fill Level Sensor

[0059] Referring to FIG. **10**, the control system **400** includes a sensor or sensing system (e.g., a drum fill level sensor, a weight sensor, a volume sensor, etc.), shown as fill level sensor **420**, operatively coupled to the controller **402**. The fill level sensor **420** is configured to provide one or more signals indicative of an amount of material in the mixing drum **102** (i.e., a fill level of the mixing drum **102**). By way of example, the fill level sensor **420** may provide a signal indicative of the weight of the material in the mixing drum **102**. By way of another example, the fill level sensor **420** may provide a signal indicative of a volume of the material within the mixing drum **102** (i.e., an occupied volume of the mixing drum **102**). By way of another example, the fill level sensor **420** may provide a signal indicative of a height of the material within the mixing drum **102**.

[0060] One embodiment of the fill level sensor **420** is shown in FIGS. **4** and **11-16**. In this embodiment, the fill level sensor **420** includes a sensor assembly (e.g., a probe) that extends radially into the mixing drum **102**. As the mixing drum **102** rotates, the fill level sensor **420** is configured to move around the circumference of the internal volume of the mixing drum **102**. When material M is present in the mixing drum **102**, the fill level sensor **420** moves into and out of contact with (e.g., periodically becomes immersed in) the material M. The point at which the fill level sensor **420** becomes immersed in the material M varies based on a fill level of the mixing drum **102**. As shown in FIGS. **11-16**, as a volume $V_{\text{sub.material}}$ of the material M in the mixing drum **102** increases, the height of a top surface S increases, and the sensor assembly is in contact with the material M for a greater portion of each revolution.

[0061] The fill level sensor **420** is configured to provide a signal indicative of the whether or not the sensor is contacting (e.g., immersed in) material M within the mixing drum **102**. As the mixing drum **102** rotates, the controller **402** monitors an angle θ of the mixing drum **102**. This angle measurement may be provided by the fill level sensor **420**. Alternatively, a separate rotational position sensor may be used to monitor a rotational position of the mixing drum **102**. When the fill level sensor **420** first indicates contact with the material M, the fill level sensor **420** is at a top surface S of the material M, and the controller **402** records an angle $\theta_{\text{sub.1}}$ of the fill level sensor **420**. When the fill level sensor **420** stops indicating contact with the material M, the fill level sensor **420** is again at the top surface S of the material M, and the controller records an angle $\theta_{\text{sub.2}}$ of the fill level sensor **420**.

[0062] In some embodiments, the controller **402** uses the angle $\theta_{\text{sub.1}}$ and/or the angle $\theta_{\text{sub.2}}$ to

determine the fill level of the mixing drum **102**. By way of example, a relationship between the angle $\theta_{\text{sub.1}}$ and/or the angle $\theta_{\text{sub.2}}$ and the fill level of the mixing drum **102** may be predetermined and stored in the memory **406**. In some embodiments, this relationship is approximated using a function such as:

$$V_{\text{sub.material}} = f_{\text{sub.volume}}(\theta_{\text{sub.1}}, \theta_{\text{sub.2}}, R_{\text{sub.drum}}, V_{\text{sub.drum}})$$

where $V_{\text{sub.material}}$ is a volume of the material **M** present in the mixing drum **102**, $R_{\text{sub.drum}}$ is a radius of the mixing drum **102**, and $V_{\text{sub.drum}}$ is a volume of the mixing drum **102**. In some embodiments, function $f_{\text{sub.volume}}$ is determined using empirical data. In some embodiments, function $f_{\text{sub.volume}}$ is determined based on geometric relationships of mixing drum **102**.

[0063] Once the volume $V_{\text{sub.material}}$ has been determined, the volume $V_{\text{sub.material}}$ may be multiplied by a density $\rho_{\text{sub.material}}$ of the material **M** to determine a weight $W_{\text{sub.material}}$ of the material **M**. In some embodiments, the density $\rho_{\text{sub.material}}$ is predetermined (e.g., assumed) and stored in the memory **406**. In other embodiments, the controller **402** is operatively coupled to a sensor that provides a signal indicative of the density $\rho_{\text{sub.material}}$. Once the weight $W_{\text{sub.material}}$ has been determined, the controller **402** may combine the weight $W_{\text{sub.material}}$ of the material **M** with a weight of the concrete mixer truck **10** to determine a gross weight of the concrete mixer truck **10**. The weight of the concrete mixer truck **10** may be predetermined and stored in the memory **406**.

[0064] In the embodiment shown in FIGS. **4** and **11-16**, the fill level sensor **420** includes a first accelerometer, shown as internal accelerometer **422**, and a second accelerometer, shown as external accelerometer **424**. As shown, the internal accelerometer **422** and the external accelerometer **424** are radially offset from one another relative to the axis **110** of the mixing drum **102**. The external accelerometer **424** is positioned such that it measures a baseline acceleration signal. For example, the external accelerometer **424** may be positioned outside of the mixing drum **102**, inside the mixing drum **102** in an enclosure, etc. The internal accelerometer **422** is positioned such that it passes through the material **M** present in the mixing drum **102**. Specifically, the internal accelerometer **422** is positioned at the end of a cantilevered protrusion, shown as probe **426**, that extends radially inward from a wall of the mixing drum **102**. The internal accelerometer **422** measures acceleration signals which are disturbed (e.g., experience noise or vibrations) as the probe **426** passes through the material **M**. The internal accelerometer **422** and the external accelerometer **424** may be three-axis accelerometers, configured to measure radial, tangential, and lateral acceleration.

[0065] As the mixing drum **102** rotates, the measured radial and tangential acceleration changes according to a sinusoidal shape due to the changing amounts of gravitational acceleration measured in the radial and tangential directions. As the mixing drum **102** rotates and the internal accelerometer **422** passes through the material **M**, the internal accelerometer **422** produces disturbed/noisy acceleration signals. Since the external accelerometer **424** is outside of the mixing drum **102** or positioned such that it does not pass through the material **M**, the external accelerometer **424** produces undisturbed/baseline acceleration signals. The controller **402** analyzes (e.g., compares) the disturbed acceleration signals and the undisturbed acceleration signals, and based on the analysis of the disturbed/undisturbed acceleration signals can determine whether or not the fill level sensor **420** is contacting the material **M**. Additionally, the controller **402** may analyze the acceleration of the external accelerometer **424** to determine the direction of gravitation acceleration relative to the fill level sensor **420**, and based on this direction determine the angle θ of the fill level sensor **420** (e.g., because gravitational acceleration has a constant downward direction).

[0066] In other embodiments, the fill level sensor **420** includes a different type of sensor configured to determine the fill level of the mixing drum **102**. By way of example, the fill level sensor **420** may include a weight sensor or force sensor (e.g., a load cell) configured to measure a

weight of the mixing drum **102** and the material contained within the mixing drum **102**. Such as sensor may be coupled to one of the pedestals.

Global Positioning System (GPS)

[0067] In some embodiments, the control system includes an input device, vehicle position sensor, or location sensor, shown as global positioning system (GPS) **430**, operatively coupled to the controller **402**. The GPS **430** is configured to provide a location of the concrete mixer truck **10** in a frame of reference. In some embodiments, the GPS **430** provides the location of the concrete mixer truck **10** relative to the surface of the Earth. The GPS **430** may communicate with one or more satellites cellular network towers, or other devices to determine this location. In some embodiments, the controller **402** utilizes the location provided by the GPS **430** to determine the heading (e.g., direction of travel) and speed (e.g., rate of travel) of the concrete mixer truck **10**.

Speed Sensor

[0068] In some embodiments, the control system **400** includes a rate of travel sensor, shown as speed sensor **432**. The speed sensor **432** is configured to provide a signal indicative of a current speed of travel of the concrete mixer truck **10**. The speed sensor **432** may also provide a direction of travel of the concrete mixer truck **10** (e.g., forward, reverse, etc.). In some embodiments, the speed sensor **432** includes an accelerometer configured to measure an acceleration of the concrete mixer truck **10**. The controller **402** may then use the acceleration to determine the speed of the concrete mixer truck **10** (e.g., by integration over time). The accelerometer may be coupled to the frame **12**, the cab **14**, or to another part of the concrete mixer truck **10**. In some embodiments, the speed sensor **432** includes a rotation sensor (e.g., an encoder, a Hall-effect sensor, etc.) configured to measure rotation (e.g., a rotation position, a rotational speed, etc.) of a component of the drivetrain **200**. By way of example, the rotation sensor may be coupled to an output of the transmission **260**, to one of the driveshafts, to one of the wheels **202**, or to another rotating component. A ratio between the rotation of that component and the distance traveled may be predetermined (e.g., based on a circumference of the corresponding wheel **202** and any intervening gear ratios) and stored in the memory **406**. The controller **402** may then use the ratio to determine the speed of the concrete mixer truck **10**. In other embodiments, the GPS **430** provides the speed of the concrete mixer truck **10**, and the speed sensor **432** is omitted.

Control Logic

Determination of Operational Requirements

[0069] In some embodiments, the memory **406** includes a database or module that stores the locations of various road features that may be encountered by the concrete mixer truck **10**. These road features may include roads (e.g., unpaved roads, paved roads, highways, etc.), intersections, buildings, parking lots, bridges, train tracks, lakes, rivers, hills, mountains, gates, tollbooths, or other features. FIG. **17** illustrates a map **1000** of an area with such features. Specifically, the map **1000** includes paved roads PR, a highway H having an on ramp ONR and an off ramp OFR, a series of paved roads PR, an unpaved dirt road DR, and a bridge B spanning a river R. The memory **406** may also store one or more locations of relevance to the concrete mixer truck **10**. By way of example, the memory **406** may store the locations of one or more staging areas where the mixing drum **102** is filled with material (e.g., from a concrete batch plant located at the staging area). By way of another example, the memory **406** may store the locations of one or more job sites where the concrete mixer truck **10** is intended to deliver or dispense concrete. The map **1000** illustrates a job site **1002** and a staging area **1004**.

[0070] In some embodiments, the memory **406** includes a database or module that stores one or more operational requirements associated with a particular area or road feature. These operational requirements may specify how the vehicle is permitted to operate. By way of example, the operational requirements may include a maximum weight supported by each axle, a maximum weight supported by each wheel **202**, a maximum gross weight of the concrete mixer truck **10**, a requirement for the lift axles to be raised or lowered, or other requirements. These requirements

may be governed by a regulatory body, such as a government (e.g., a state, local, or national government), or may be specified by a user (e.g., for a job site). By way of example, the memory **406** may store operational requirements (e.g., a maximum weight supported by each axle) for a given jurisdiction (e.g., country, state, city, township, or other area). By way of another example, the memory **406** may store operational requirements for a user-defined area (e.g., the job site **1002**, the staging area **1004**, etc.). In one such example, the memory **406** may indicate that the maximum weight per axle is permitted to be higher than on the surrounding paved roads, such that the lift axles can be raised when entering the job site **1002** or the staging area **1004**.

[0071] In some embodiments, the controller **402** defines boundaries or geofences around certain areas or features. By using the location of the concrete mixer truck **10** (e.g., as provided by the GPS **430**), the controller **402** may determine if the concrete mixer truck **10** has passed through a geofence into a particular area. Based on this determination, the controller **402** may then utilize the operational requirement data stored in the memory **406** to determine what operational requirements apply to the concrete mixer truck **10** at the current location. The geofences may be defined along the boundary of a country, state, city, country, township, or other area subject to the governance of a particular regulatory body. The geofences may be defined around an object. By way of example, a geofence may be defined around a bridge, along a road, or around another type of road feature. A geofence may conform to the shape of the feature, or may have a predefined shape (e.g., a circle having a predetermined radius around a center point). A geofence may be defined by a user (e.g., surrounding a job site or a staging area).

[0072] In FIG. **17**, the map **1000** includes a series of geofences illustrated as dashed lines. A first geofence, shown as job site geofence **1010**, surrounds the job site **1002**. Accordingly, when the concrete mixer truck **10** is determined to be within the area defined by the job site geofence **1010**, the controller **402** may determine that the operational requirements associated with the job site **1002** apply. A second geofence, shown as staging area geofence **1012**, surrounds the staging area **1004**. Accordingly, when the concrete mixer truck **10** is determined to be within the area defined by the staging area geofence **1012**, the controller **402** may determine that the operational requirements associated with the staging area **1004** apply. A third geofence, shown as bridge geofence **1014**, surrounds the bridge B. Accordingly, when the concrete mixer truck **10** is determined to be within the area defined by the bridge geofence **1014**, the controller **402** may determine that the operational requirements associated with the bridge B apply.

[0073] An additional set pair of geofences are included in FIG. **17** to represent the boundaries between two areas under different governmental control. Specifically, a first state boundary, shown as state geofence **1020**, represents a first state (e.g., Wisconsin), and a second state boundary, shown as state geofence **1022**, represents a second state (e.g., Illinois). When the concrete mixer truck **10** is determined to be within the area defined by the state geofence **1020**, the controller **402** may determine that the operational requirements associated with the first state apply. When the concrete mixer truck **10** is determined to be within the area defined by the state geofence **1022**, the controller **402** may determine that the operational requirements associated with the second state apply.

[0074] In certain situations, multiple sets of operational requirements may apply simultaneously. By way of example, the concrete mixer truck **10** may be positioned within the bridge geofence **1014**, which is contained within the state geofence **1020**. In some embodiments, the controller **402** compares each of the applicable requirements and selects (e.g., utilizes) the most stringent requirements that apply to the current location. By way of example, the operational requirements for passing over the bridge B may be more stringent than the operational requirements that apply generically to all of the roads within the first state. Accordingly, the controller **402** may select the operational requirements for the bridge B when positioned within the bridge geofence **1014**. In some embodiments, the controller **402** identifies certain areas as being overriding areas. By way of example, the job site **1002** and the staging area **1004** may be considered overriding areas. When in

an overriding area, the controller **402** may select the operational requirements associated with that area, regardless of what other operational requirements may apply. By way of example, when on the job site **1002**, the operational requirements may be less stringent than those associated with the first state. However, because the job site **1002** is privately owned and does not include any state roads, the concrete mixer truck **10** may not be required to comply with the operational requirements associated with the first state when within the job site geofence **1010**.

Lift Axle Position

[0075] In some embodiments, the controller **402** is configured to control operation of the suspension actuators **302** and/or the axle lifter **350** (e.g., through the suspension controller **304** and/or the axle lift controller **352**) to move the lift axles (e.g., the pusher axle **240** and/or the tag axle **250**) between the raised configuration (e.g., the raised position) and the lowered configuration (e.g., the lowered position). The controller **402** may control each axle individually, or the controller **402** may control all of the lift axles simultaneously.

[0076] In some embodiments, the controller **402** controls the positions of the lift axles based on a user input through the user interface **410**. By way of example, the user interface **410** may include individual controls (e.g., buttons, switches, touch screen buttons, etc.) that, when interacted with by an operator, move one or more of the lift axles to the raised position or the lowered position. The user interface **410** may be configured to receive commands to control each lift axle individually (e.g., include two buttons with the text “raise/lower pusher axle” and “raise/lower tag axle,” respectively, etc.). Additionally or alternatively, the user interface **410** may be configured to receive commands to control the lift axles simultaneously (e.g., include two buttons with the text “raise all lift axles” and “lower all lift axles,” respectively, etc.).

[0077] In some embodiments, the controller **402** controls the positions of the lift axles based on the fill level of the mixing drum **102**. The fill level may be determined based on information from the fill level sensor **420**. Accordingly, the controller **402** may control the positions of the lift axles based on information from the fill level sensor **420**. When the fill level is below a certain point (e.g., the mixing drum **102** is empty, the mixing drum **102** is only partially filled, etc.), the weight of the material in the mixing drum **102** may not be sufficient to necessitate the use of the lift axles. Accordingly, the lift axles may be held in the raised position, reducing wear on the lift axles and improving fuel economy. As the fill level increases, the weight of the material increases, increasing the weight supported by each axle. To reduce the weight supported by each axle, one or more of the lift axles may be lowered to distribute the gross weight of the concrete mixer truck **10** and the material in the mixing drum **102** across a greater number of axles.

[0078] In some embodiments, the controller **402** defines a series of threshold fill levels (e.g., each corresponding to a threshold material volume and a threshold material weight). When the controller **402** determines that the fill level exceeds a first threshold fill level, the controller **402** may control one or more of the lift axles to move to the lowered position. In some embodiments, the controller **402** lowers all of the lift axles (e.g., a pusher axle **240** and a tag axle **250**, multiple pusher axles **240**, multiple tag axles **250**, multiple pusher axles **240** and multiple tag axles **250**, etc.) in response to the fill level exceeding the first threshold fill level. In other embodiments, the controller **402** defines additional threshold fill levels greater than the first threshold fill level (e.g., a second threshold fill level, a third threshold fill level, etc.). By way of example, the first fill level threshold may be when the mixing drum **102** is 50% full, and the second fill level threshold may be when the mixing drum **102** is 80% full. When the fill level exceeds each subsequent threshold fill level, the controller **402** may control additional lift axles to move to the lowered positions. Similarly, the controller **402** may raise the lift axles when the fill level decreases below a threshold fill level. This process may occur automatically (e.g., without requiring input from an operator). Accordingly, the controller **402** can automatically control the axles to redistribute the load as required to support the gross weight of the concrete mixer truck **10** as material is added or removed from the mixing drum **102**.

[0079] In some embodiments, the controller **402** controls the positions of the lift axles based on a location of the concrete mixer truck **10**. This location may be determined based on information from the GPS **430**. Accordingly, the controller **402** may control the positions of the lift axles based on information from the GPS **430**. In some embodiments, the controller **402** determines one or more operational requirements relating to the axle position based on the location (e.g., using one or more geofences). By way of example, the operational requirements may require that the lift axles be in the raised position or in the lowered position regardless of the gross weight of the vehicle. By way of another example, the operational requirements may require a certain maximum weight be supported by each axle. In such an embodiment, the controller **402** may utilize the fill level sensor **420** to determine a gross weight of the concrete mixer truck **10**. By way of example, the controller **402** may utilize the fill level sensor to determine the weight of the material of the mixing drum **102** and calculate the gross weight of the concrete mixer truck **10** as a sum of the weight of the material and a predetermined weight of the concrete mixer truck **10**. Based on this gross weight, the controller **402** may determine the weight supported by each axle. If the weight supported by any axle is greater than what is allowed by the operational requirements, the controller **402** may lower one or more of the lift axles distribute the weight across a greater number of axles. Alternatively, a relationship between the fill level and the weight supported by each axle may be predetermined, and the controller **402** may modify the threshold fill levels based on the operational requirements of the current location.

[0080] In some embodiments, the controller **402** controls the positions of the lift axles based on a speed of the concrete mixer truck **10**. The speed of the concrete mixer truck **10** may be provided by the GPS **430** and/or the speed sensor **432**. Accordingly, the controller **402** may control the positions of the lift axles based on an input from the GPS and/or the speed sensor **432**. Specifically, the controller **402** may be configured to automatically lower one or more lift axles to the lowered position when the concrete mixer truck **10** exceeds a threshold speed. Exceeding this threshold speed may indicate that the concrete mixer truck **10** is now traveling down a road or a highway and is no longer present at a job site. In some embodiments, this speed-based control of the lift axle position may be used to override a location-based control of the lift axle position. By way of example, the controller **402** may determine that the GPS **430** is errantly indicating that the concrete mixer truck **10** is present at a job site when the speed exceeds the threshold speed. In some embodiments, this speed-based control of the lift axle position is only used when the fill level of the mixing drum **102** requires the use of one or more lift axles. By way of example, if the mixing drum **102** is determined to be below a minimum threshold fill level, the controller **402** may not lower the lift axles when the concrete mixer truck exceeds the threshold speed.

[0081] Additionally or alternatively, the controller **402** may be configured to limit a speed of the concrete mixer truck **10** when one or more of the lift axles are in the raised position. By way of example, the controller **402** may be configured to limit the speed of the concrete mixer truck **10** to less than a maximum threshold speed when one or more lift axles are in the raised position. This speed may be measured by the speed sensor **432**.

Wheel Force

[0082] In some embodiments, the controller **402** is configured to control operation of the suspension actuators **302** and/or the axle lifters **350** to vary the weight supported by each wheel **202** and/or axle based on the fill level of the mixing drum **102** (e.g., as provided by the fill level sensor **420**). Specifically, in some embodiments, the fill level sensor **420** continuously or periodically measures the fill level of the mixing drum **102**, and the controller **402** continuously or periodically adjusts the suspension actuators **302** and/or the axle lifters **350** to compensate for changes in suspension. As the amount of material in the mixing drum **102** increases, the gross weight of the concrete mixer truck **10** increases, and thus the weight supported by each axle also increases. Similarly, as the amount of material in the mixing drum **102** decreases (e.g., concrete is dispensed), the gross weight of the concrete mixer truck **10** decreases, and thus the weight

supported by each axle also decreases. If these changes in gross weight are not accounted for by the controller **402** (e.g., by adjusting the suspension actuators **302** and/or the axle lifters **350**), the concrete mixer truck may experience a variety of undesirable effects, such as an uneven distribution of weight across the axles and/or an unintended change in ride height or body posture (e.g., pitch, roll, etc.).

[0083] In some embodiments, the controller **402** is configured to control the suspension actuators **302** and/or the axle lifters **350** to maintain an approximately even distribution of weight across each of the axles. As the suspension actuators **302** and/or the axle lifters **350** are adjusted to increase the weight supported by one axle, the weight supported by the other axles decreases. As the fill level of the mixing drum **102** increases, the weight supported by each axle generally increases. Due to the varying distances between the mixing drum **102** and the axles, a change in the fill level of the mixing drum **102** affects the weight supported by each axle differently (e.g., a change in weight of the material in the mixing drum **102** may affect axles closer to the mixing drum (e.g., the tandem axles) more severely than the axles that are positioned farther from the mixing drum **102** (e.g., the front axle **210**)). Accordingly, the controller **402** may be configured to adjust the suspension actuators **302** and/or the axle lifters **350** as the fill level of the mixing drum **102** changes in order to maintain an approximately even distribution of weight across the axles.

[0084] In some embodiments, a relationship between the fill level of the mixing drum **102** and a weight supported by each axle and/or wheel **202** when the weight is evenly distributed across the axles is predetermined and stored in the memory **406**. By way of example, a mathematical force balance and/or moment balance may be performed to develop an equation that relates the fill level of the mixing drum **102** to the weight supported by each wheel **202** and/or axle. As the concrete mixer truck **10**, the mixing drum **102** may continuously rotate, and the fill level sensor **420** may continuously or periodically determine the fill level of the mixing drum. Based on the fill level and the predetermined relationship, the controller **402** may determine a target weight for each axle and/or wheel **202** to support. The controller **402** may control the suspension actuators **302** and/or the axle lifters **350** to reach this target weight for each axle. In some embodiments, the wheel force sensors **308** may be used to provide feedback for closed loop control.

[0085] Throughout operation, the lift axles may be moved between the raised positions and the lowered positions, varying the weight supported by each axle. When this occurs, the controller **402** may be configured to control the suspension actuators **302** and/or the axle lifters **350** to provide a relatively even weight distribution across each axle. The predetermined relationship between the fill level of the drum **102** and the weight supported by each axle may differ based on which lift axles are in the lowered positions. By way of example, the controller **402** may utilize a different predetermined relationship for each lift axle configuration of the concrete mixer truck (e.g., only the pusher axle **240** lowered, only the tag axle **250** lowered, both the pusher axle **240** and the tag axle **250** lowered, neither lift axle lowered, etc.).

[0086] While the axle forces are adjusted, the position of one or more of the wheels **202** may vary relative to the frame **12**. This may undesirably change the ride height of the concrete mixer truck **10** and/or the posture of the frame **12**. To reduce these effects, the controller **402** may control the suspension actuators **302** and/or the axle lifters **350** based on inputs from the wheel position sensors **309** to maintain a target height range of each wheel **202**. In some embodiments, the controller **402** is configured to mitigate long term changes in wheel position while minimally affecting short term changes in wheel position (e.g., caused by encountering a bump).

Tire Pressure

[0087] In some embodiments, the controller **402** is configured to control the CTI system **330** to vary the tire pressure of the wheels **202** based on the fill level of the mixing drum **102** (e.g., as provided by the fill level sensor **420**). In some embodiments, the controller **402** increases the tire pressure as the fill level increases. In some embodiments, the controller **402** decreases the tire pressure as the fill level increases. In some embodiments, the controller **402** maintains a target tire

pressure as the fill level is varied.

Axle Articulation

[0088] In some embodiments, the controller **402** is configured to control the locks **306** to selectively prevent articulation of one or more axles based on the fill level of the mixing drum **102** (e.g., as provided by the fill level sensor **420**). In some embodiments, the controller **402** is configured to selectively engage one or more of the locks **306** to prevent articulation based on the fill level of the mixing drum being above or below a threshold fill level. By way of example, when the mixing drum **102** is filled, the center of gravity of the gross weight of the concrete mixer truck **10** may be elevated, decreasing the stability of the concrete mixer truck when turning. In such a situation, it may be advantageous to limit (e.g., prevent) articulation of the axles to limit body roll when turning, thereby reducing the likelihood that the center of gravity would move laterally beyond the wheels **202**, causing the concrete mixer truck **10** to tip. Accordingly, in some embodiments, the controller **402** is configured to engage one or more of the locks **306** to limit articulation of one or more axles when the fill level is above a threshold fill level. The controller **402** may constantly engage the locks **306**, or the controller **402** may engage the locks **306** only when the concrete mixer truck **10** is turning.

[0089] As utilized herein, the terms “approximately,” “about,” “substantially,” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the disclosure as recited in the appended claims.

[0090] It should be noted that the term “exemplary” and variations thereof, as used herein to describe various embodiments, are intended to indicate that such embodiments are possible examples, representations, or illustrations of possible embodiments (and such terms are not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

[0091] The term “coupled” and variations thereof, as used herein, means the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent or fixed) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members coupled directly to each other, with the two members coupled to each other using a separate intervening member and any additional intermediate members coupled with one another, or with the two members coupled to each other using an intervening member that is integrally formed as a single unitary body with one of the two members. If “coupled” or variations thereof are modified by an additional term (e.g., directly coupled), the generic definition of “coupled” provided above is modified by the plain language meaning of the additional term (e.g., “directly coupled” means the joining of two members without any separate intervening member), resulting in a narrower definition than the generic definition of “coupled” provided above. Such coupling may be mechanical, electrical, or fluidic.

[0092] References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below”) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

[0093] The hardware and data processing components used to implement the various processes, operations, illustrative logics, logical blocks, modules and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose single-or multi-chip processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), or other programmable logic device, discrete

gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, or, any conventional processor, controller, microcontroller, or state machine. A processor also may be implemented as a combination of computing devices, such as a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. In some embodiments, particular processes and methods may be performed by circuitry that is specific to a given function. The memory (e.g., memory, memory unit, storage device) may include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present disclosure. The memory may be or include volatile memory or non-volatile memory, and may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. According to an exemplary embodiment, the memory is communicably connected to the processor via a processing circuit and includes computer code for executing (e.g., by the processing circuit or the processor) the one or more processes described herein.

[0094] The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

[0095] Although the figures and description may illustrate a specific order of method steps, the order of such steps may differ from what is depicted and described, unless specified differently above. Also, two or more steps may be performed concurrently or with partial concurrence, unless specified differently above. Such variation may depend, for example, on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations of the described methods could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps.

[0096] It is important to note that the construction and arrangement of the concrete mixer truck **10** as shown in the various exemplary embodiments is illustrative only. Additionally, any element disclosed in one embodiment may be incorporated or utilized with any other embodiment disclosed herein. For example, the tag axle **250** of the exemplary embodiment shown in at least FIG. **1** may be incorporated in the concrete mixer truck **10** of the exemplary embodiment shown in at least FIG. **3**. Although only one example of an element from one embodiment that can be incorporated or utilized in another embodiment has been described above, it should be appreciated that other elements of the various embodiments may be incorporated or utilized with any of the other embodiments disclosed herein.

Claims

1. A vehicle, comprising: a chassis; a mixing drum rotatably coupled to the chassis; a fill level sensor configured to provide a signal indicative of a fill level of a material within the mixing drum; an axle assembly including a first tractive element; a suspension actuator coupled to the axle assembly and configured to apply a biasing force that forces the first tractive element into engagement with a ground surface; a lift axle including a second tractive element; a lift actuator coupled to the lift axle; and a controller configured to: calculate a target weight to be supported by at least one of the first tractive element or the second tractive element based on the fill level of the material within the mixing drum; and control the suspension actuator to vary the biasing force based on the target weight.
2. The vehicle of claim 1, wherein the controller is configured to calculate the target weight to be supported by the first tractive element based on the fill level of the material within the mixing drum.
3. The vehicle of claim 1, wherein the controller is configured to calculate the target weight to be supported by the second tractive element based on the fill level of the material within the mixing drum.
4. The vehicle of claim 1, wherein the controller is configured to determine the fill level based on an angular orientation of the mixing drum when the fill level sensor comes into contact with the material.
5. The vehicle of claim 1, wherein the controller is configured to control the lift actuator to reposition the lift axle into a lowered position in response to the fill level exceeding a threshold fill level.
6. The Vehicle of claim 1, wherein the controller is configured to control a central tire inflation (CTI) system to vary a tire pressure of the first tractive element based on the fill level.
7. The vehicle of claim 1, wherein the suspension actuator includes an air bag coupled to the axle assembly and the chassis and containing a compressed gas.
8. The vehicle of claim 7, wherein the suspension actuator is configured to vary the biasing force by introducing additional gas into the air bag.
9. The vehicle of claim 1, wherein the axle assembly is a rear axle assembly, further comprising a front axle assembly coupled to the chassis and positioned forward of the rear axle assembly.
10. The vehicle of claim 1, wherein the axle assembly is a front axle assembly, further comprising a rear axle assembly coupled to the chassis and positioned rearward of the front axle assembly.
11. The vehicle of claim 1, wherein the controller is configured to control the suspension actuator to increase the biasing force from a first magnitude to a second magnitude in response to a first increase in the fill level of the material within the mixing drum, and wherein the controller is configured to increase the biasing force from the second magnitude to a third magnitude in response to a second increase in the fill level of the material within the mixing drum.
12. The vehicle of claim 1, further comprising a wheel force sensor configured to provide a signal indicative of a weight supported by the first tractive element, and wherein the controller is configured to control the suspension actuator to vary the biasing force based on the target weight and the signal from the wheel force sensor.
13. The vehicle of claim 12, wherein the wheel force sensor is configured to measure a pressure of a fluid within the suspension actuator.
14. A vehicle, comprising: a chassis; a mixing drum rotatably coupled to the chassis; a fill level sensor configured to provide a signal indicative of a fill level of a material within the mixing drum; an axle assembly including a first tractive element; a lift axle including a second tractive element; a lift actuator coupled to the lift axle and configured to apply a biasing force that forces the second tractive element into engagement with a ground surface; and a controller configured to: calculate a

target weight to be supported by at least one of the first tractive element or the second tractive element based on the fill level of the material within the mixing drum; and control the lift actuator to vary the biasing force based on the target weight.

15. The vehicle of claim 14, wherein the controller is configured to calculate the target weight to be supported by the first tractive element based on the fill level of the material within the mixing drum.

16. The vehicle of claim 14, wherein the controller is configured to calculate the target weight to be supported by the second tractive element based on the fill level of the material within the mixing drum.

17. A vehicle, comprising: a chassis; a mixing drum rotatably coupled to the chassis; a first axle and including a first tractive element; a force sensor configured to provide a signal indicative of a weight supported by the first axle assembly; a second axle assembly including a second tractive element; and a controller configured to: calculate a target weight to be supported by the first axle assembly; and determine, based on the target weight and the signal from the force sensor, that the vehicle has an uneven distribution of weight across the first axle assembly and the second axle assembly.

18. The vehicle of claim 17, wherein the force sensor is a first force sensor, the signal is a first signal, and the target weight is a first target weight, further comprising a second force sensor configured to provide a second signal indicative of a weight supported by the second axle assembly, and wherein the controller is configured to: calculate a second target weight to be supported by the second axle assembly; and determine, based on the first target weight, the second target weight, the first signal from the first force sensor, and the second signal from the second force sensor, that the vehicle has the uneven distribution of weight across the first axle assembly and the second axle assembly.

19. The vehicle of claim 17, further comprising a fill level sensor configured to provide a signal indicative of a fill level of a material within the mixing drum, wherein the controller is configured to determine the target weight based on the fill level of the material within the mixing drum,

20. The vehicle of claim 17, wherein the first axle assembly is a lift axle, further comprising a lift actuator coupled to the lift axle.
