

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285306

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Umemura; Naoki

INFORMATION PROCESSING APPARATUS, INFORMATION PROCESSING METHOD, AND STORAGE MEDIUM

Abstract

The information processing apparatus generates three-dimensional shape data representing a three-dimensional shape of a first object by using a plurality of images obtained by a plurality of imaging apparatuses capturing the first object. The information processing apparatus estimates a size of the first object by using the three-dimensional shape data. The information processing apparatus specifies a position of a second object that is captured by the plurality of imaging apparatuses based on results of a comparison between the estimated size of the first object and a predetermined reference value.

Inventors: Umemura; Naoki (Chiba, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 1000008619612

Appl. No.: 19/215569

Filed: May 22, 2025

Foreign Application Priority Data

JP	2021-064865	Apr. 06, 2021
----	-------------	---------------

Related U.S. Application Data

parent US continuation 17709826 20220331 parent-grant-document US 12333749 child US 19215569

Publication Classification

Int. Cl.: G06T7/55 (20170101); A63B71/06 (20060101); G06T7/60 (20170101); G06T7/73 (20170101); G06T17/00 (20060101); G06V20/64 (20220101)

U.S. Cl.:

CPC G06T7/55 (20170101); A63B71/0605 (20130101); G06T7/60 (20130101); G06T7/75 (20170101); G06T17/00 (20130101); G06V20/64 (20220101); A63B2220/05 (20130101); A63B2220/62 (20130101); A63B2220/806 (20130101); A63B2243/0025 (20130101); A63B2243/0033 (20130101); A63B2243/0037 (20130101); G06T2207/30224 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/709,826, filed on Mar. 31, 2022, which claims the benefit of and priority to Japanese Patent Application No. 2021-064865, filed Apr. 6, 2021, each of which is hereby incorporated by reference herein in their entirety.

FIELD

[0002] The present disclosure relates to an information processing apparatus, an information processing method, and a storage medium.

DESCRIPTION OF THE RELATED ART

[0003] In recent years, in order to check whether the determination of a referee is correct or not in a sports game, a referee assistance system has been introduced, which displays an image including a target play on a display device among images obtained by image capturing by a plurality of imaging apparatuses installed around a sports stadium. Japanese Patent Laid-Open No. 2013-232181 has described a technique to determine whether or not image capturing-target objects, such as a player and a ball, have contacted each other based on results of calculation to calculate a moving speed and acceleration of each image capturing-target object from two-dimensional images obtained by image capturing by a plurality of imaging apparatuses in a game of soccer.

SUMMARY

[0004] For example, in basketball, there is a rule called a so-called 24-second rule. This requires that one of teams need to take a shot within 24 seconds after the team gets the ball. This determination is based on whether the ball has separated from a player at the point in time at which 24 seconds have elapsed, and therefore, an image in which the instant the ball has separated from the hand of the player is captured is necessary. For example, in a case where occlusion occurs due to the position relationship between players, it is difficult to specify the instant the ball has separated from the hand of the player even by adopting the technique of Japanese Patent Laid-Open No. 2013-232181.

[0005] The present disclosure has been made in view of the above-described problem and provides a technique to obtain information capable of assisting a referee in performing determination, for example, in a sports game.

[0006] An information processing apparatus according to one embodiment of the present disclosure generates three-dimensional shape data representing a three-dimensional shape of a first object by using a plurality of images obtained by a plurality of imaging apparatuses capturing the first object, estimates a size of the first object by using the three-dimensional shape data, and specifies a position of a second object that is captured by the plurality of imaging apparatuses based on results of a comparison between the size of the first object estimated in the estimating and a predetermined reference value.

[0007] Further features of the present disclosure will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a block diagram showing a configuration example of a virtual viewpoint image generation system;
[0009] FIG. 2 is a schematic diagram showing an arrangement example of imaging units;
[0010] FIG. 3 is a block diagram showing a function configuration example of a server;
[0011] FIG. 4A and FIG. 4B are each a schematic diagram showing an image capturing-target object example;
[0012] FIG. 5A and FIG. 5B are each a diagram explaining generation of a 3D model of a basketball court;
[0013] FIG. 6A to FIG. 6C are each a diagram explaining generation of a 3D model of a basketball;
[0014] FIG. 7A to FIG. 7F are each a diagram explaining generation of a 3D model at the time of shot by a basketball player;
[0015] FIG. 8 is a diagram explaining generation of a 3D model;
[0016] FIG. 9A and FIG. 9B are each a diagram explaining the presence/absence of a voxel at the time of modeling an image capturing-target object;
[0017] FIG. 10 is a flowchart showing a flow of processing to estimate a size of an object;
[0018] FIG. 11 is a flowchart showing a flow of processing to determine a violation in basketball;
[0019] FIG. 12 is a table showing examples of fouls/violations of each game; and
[0020] FIG. 13 is a diagram showing a hardware configuration example of a server.

DESCRIPTION OF THE EMBODIMENTS

[0021] In the following, embodiments of the present disclosure are explained with reference to the drawings. The following embodiments are not intended to limit the present disclosure according to the claims and all combinations of features explained in the present embodiments are not necessarily indispensable to the solution of the present disclosure. The same reference number is attached to the same component and its explanation is omitted.

First Embodiment

[0022] A virtual viewpoint image generation system according to the present embodiment is explained using a diagram. FIG. 1 is a diagram showing a hardware configuration example of the virtual viewpoint image generation system according to the present embodiment. The virtual viewpoint image generation system of the present embodiment has camera systems **110a-110j**, a switching hub **120**, a server **130**, a database **140**, a control device **150**, an operation device **160**, a display device **170**, and a timer device **180**.

[0023] Within each of the camera systems **110a-110j**, each of imaging units **111a-111j** including a lens, an imaging sensor and the like and each of camera adaptors **112a-112j** that perform control of the imaging unit and predetermined image processing in accordance with instructions of the control device **150** are provided, respectively. Each of the imaging units **111a-111j** is, for example, an imaging apparatus, such as a camera. Each of the camera adaptors **112a-112j** comprises a central processing unit (CPU or ASIC) and memories (RAM and ROM) necessary for control and image processing. Further, the adjacent camera systems of the camera systems **110a-110j** are connected by each of network cables **113a-113i** by the daisy chain method. Image data captured by each of the camera systems **110a-110j** is transferred via each of the network cables **113a-113i**. The switching hub (in the following, described as “HUB”) **120** performs routing of data transfer on the network. The HUB **120** and the camera system **110a** are connected by a network cable **114a** and the HUB **120** and the camera system **110j** are connected by a network cable **114b**.

[0024] The server **130** processes image data with a plurality of viewpoints (frame with a plurality of viewpoints) transmitted from the camera systems **110a-110j**, generates a three-dimensional model (in the following, described as “3D model”) by shape estimation from the image data with a plurality of viewpoints, and so on. Further, the server **130** generates a time synchronization signal and performs synchronization control of the entire system. That is, it can be said that the server **130** is an information processing apparatus because the server **130** processes information. The HUB **120** and the server **130** are connected by a network cable **114c**.

[0025] The database (in the following, described as “DB”) **140** accumulates image data and model information sent from the server **130** and provides the accumulated image data and model information to the server **130** as needed. The server **130** and the DB **140** are connected by a network cable **114d**.

[0026] The control device **150** comprehensively controls each of the camera systems **110a-110j** and the server **130**. Then, the control device **150** performs control for generating a virtual viewpoint video. The operation device **160** provides a user with a user interface unit (in the following, referred to as UI unit) through which the user operating the present camera system performs control for the control device **150**. The HUB **120** and the control device **150** are connected by a network cable **114e**.

[0027] The display device **170** is a device that displays an image, for example, such as a liquid crystal display, and displays an image that is sent from the control device **150**. The control device **150** and the display device **170** are connected by a video cable **114f**.

[0028] The timer device **180** is a timer that generates time information at the time of determining a game rule that is used in a game. That is, the timer device **180** times a predetermined time determined in advance. In the present embodiment, time information at the time of determining the 24-second rule or the like that is used in a game of basketball is generated. The predetermined time is set to the timer device **180** by a referee assistant, not shown schematically, or set automatically. The timer device **180** automatically performs a countdown and outputs the value as a count value (time information). That is, the timer device **180** times a time and outputs the timed time. The server **130** and the timer device **180** are connected by a network cable **114h**.

[0029] In the virtual viewpoint image generation system shown in FIG. 1, although the plurality of the camera systems is connected by the daisy chain method, the connection may be the star connection in which the HUB **120** and each of the camera systems **110a-110j** are connected directly. Further, in the virtual viewpoint image generation system, the number of camera systems is not limited to ten and the number may be smaller or larger than ten.

[0030] Here, the operation of the virtual viewpoint image generation system is explained. The image obtained by image capturing by the imaging unit **111a** is transferred to the camera adaptor **112b** of the camera system **110b** through the network cable **113a** after image processing, such as processing to separate the image into the image capturing-target object and the background, has been performed for the image by the camera adaptor **112a**. The image capturing-target object is one of the objects as an image capture target. The image of the image capturing-target object from which the background is separated is particularly called a silhouette image and for example, in the silhouette image, the foreground is a white image and the background is a black image. The camera adaptor **112** generates the silhouette image, the image of the foreground, and the image of the background and transfers them. For example, it is possible to generate a silhouette image by a general method, such as the background difference method in which a difference between the captured image obtained by capturing the image capturing-target object and the background image obtained by performing image capturing in advance in a case where the image capturing-target object does not exist, such as before the start of the game, is calculated and the portion whose difference is larger than or equal to a threshold value is taken as a silhouette (foreground area). Of course, the method of generating a silhouette image is not limited to this. For example, it may also be possible to generate a silhouette image by using a method of recognizing the human body and

the like. Similarly, the camera system **110b** combines the image obtained by image capturing by the imaging unit **111b** with the image obtained from the camera system **110a** and transfers the combined image to the camera system **110c**. By continuing the operation described previously, the images obtained by the imaging units in the camera systems **110a-110j** are transferred from the camera system **110j** to the HUB **120** via the network cable **114b** and after that, the images are transferred to the server **130**.

[0031] Next, the configuration and operation of the server **130** are explained. The server **130** performs processing of the data obtained from the camera system **110j**. The server **130** has a time server function and transmits a time and a synchronization signal to each camera system **110** and the timer device **180**. Each camera system **110** having received the time and the synchronization signal performs image capturing for each frame in synchronization with the same time by the ten imaging units **111a-111j**. The timer device **180** synchronizes the value of a 24-second timer, which is displayed on the display device of the timer device **180** itself, with the signal received from the server **130**. Further details will be described later by using a diagram.

Arrangement of Imaging Units

[0032] The arrangement of the imaging units of the camera system is explained by using a diagram. FIG. 2 is a diagram showing an arrangement example of the imaging units of the camera system. FIG. 2 shows the state where a basketball court (in the following, described as “court”) **201** is viewed from directly above. As shown in FIG. 2, the imaging units **111a-111j** of the camera systems **110a-110j** are arranged around the court **201** and so as to be capable of capturing a desired position of the court **201**. It is assumed that each of the imaging units **111a-111j** is arranged at a certain height from the ground. The imaging units **111a-111j** are arranged so as to be capable of capturing the entire area (three-dimensional area including height) in which an image capturing-target object on the court **201** moves.

Configuration of Server

[0033] The configuration of the server **130** is explained by using a diagram. FIG. 3 is a diagram showing a configuration example of the server **130**. As shown in FIG. 3, the server **130** has a time server **301**, a camera information obtaining unit **302**, a 3D model generation unit **303**, a shape estimation unit **304**, a ball detection unit **305**, and a violation determination unit **306**.

[0034] The time server **301** obtains time information for time synchronization for synchronizing the images (videos) obtained by the ten camera systems **110** shown in FIG. 1 performing image capturing. The time server **301** receives the world standard time by a GPS antenna, not shown schematically. Alternatively, the time server **301** internally generates its own time and transmits the time to each camera system **110**. Further, in the present embodiment, the time server **301** receives the counter value from the timer device **180** used for the basketball game, combines the value with the time for time synchronization, and sends the combination to the camera information obtaining unit **302**.

[0035] The camera information obtaining unit **302** obtains camera parameter information relating to image capturing, such as the current zoom value, focus value, and aperture value, of each of the imaging units **111a-111j** and image data obtained by image capturing by each imaging unit from the ten imaging units **111a-111j**. Here, the image obtained by image capturing by each of the imaging units **111a-111j** is the image obtained by time-synchronized image capturing of the imaging unit based on the time for time synchronization transmitted from the time server **301**.

[0036] The 3D model generation unit **303** generates a 3D model (three-dimensional shape data) of an image capturing-target object by using the camera parameter information obtained by the camera information obtaining unit **302** and the captured image with a plurality of viewpoints. That is, the 3D model generation unit **303** generates a 3D model corresponding to each of a plurality of objects in a frame with a plurality of viewpoints by using the frame. In the generation of a 3D model, the 3D model is generated by using, for example, a silhouette image of the image capturing-target object generated by the camera adaptor **112**. By using the silhouette image generated from

the image obtained by image capturing of all the imaging units and the camera parameter information, the 3D model of the image capturing-target object is generated. For the 3D model generation, it is possible to use, for example, the Visual Hull method. As a result of this processing, 3D data (set of points having three-dimensional coordinates) representing the 3D model of the image capturing-target object is obtained.

[0037] The shape estimation unit **304** estimates the size of the 3D model by using the camera parameter information obtained by the camera information obtaining unit **302** and the 3D model of the image capturing-target object generated by the 3D model generation unit **303**.

[0038] The ball detection unit **305** determines whether or not the 3D model is a basketball by using the size of the 3D model estimated by the shape estimation unit **304** and information relating to the size of the detection-target basketball, which is set in advance. Details of the determination method will be described later.

[0039] Here, by taking the game of basketball as an image capturing target, the positions of a player of interest and a ball handled by the player of interest, and the 24-second rule, which is one of violation targets, are explained by using diagrams. FIG. 4A and FIG. 4B are each a schematic diagram at the time of a certain player taking a shot in the game of basketball. FIG. 4A shows the state immediately before the shot and where the ball has not separated yet from the hand of the player of interest and FIG. 4B shows the state immediately after the shot and where the ball has separated from the hand of the player of interest. The game rules of basketball include, for example, the 24-second rule as a violation target. According to the 24-second rule, in a case where the player of interest controls a live ball on the court, on a condition that the following condition is not met, a violation is determined and the opponent team gets the control of the ball. That is, in a case where the condition that the team of the player of interest takes a shot within 24 seconds and the ball contacts with the ring or falls into the basket is not met, the opponent team gets the control of the ball. Here, what is important is whether the ball has separated from the hand of the player before the timer device that times 24 seconds counts the time “0”. Consequently, as shown in FIG. 4A, in a case where a hand **412** of a player of interest **411** is still in contact with a ball **413**, on a condition that the count of the timer device **180** reaches “0”, the 24-second rule is violated and the opponent team gets the control of the ball. On the other hand, in a situation of the state as shown in FIG. 4B, in a case where the count of the timer device **180** reaches “0” at the instant a ball **423** has separated from a hand **422** of a player of interest **421**, on a condition that the state is as follows, the 24-second rule is not violated. That is, in a case where the ball **423** contacts with a ring **424** or in a case where the ball falls in a basket **425** and the shot has succeeded, the 24-second rule is not violated. As described above, the count value of the timer device **180** and the position relationship between the player of interest and the ball handled by the player of interest are important.

[0040] Here, the generation of a 3D model of a court is explained by using diagrams. FIG. 5A and FIG. 5B are each a diagram for explaining the generation of a 3D model of a court. As shown in FIG. 5A, in a case where the floor surface of a court is represented by X and Y coordinates and the position in the height direction is represented by a Z coordinate of three-dimensional coordinates, a cuboid consisting of the court surface on X-and Y-axes and a height Z1 is a processing-target space **510** in which an image capturing-target object is modeled. In FIG. 5A, the plurality of cameras arranged around the court is omitted. FIG. 5B is a schematic diagram representing a voxel **520**. By the image data obtained by image capturing of the plurality of camera systems, the state is brought about where the place at which the image capturing-target object exists in the processing-target space **510** is filled with the voxel and the place at which the image capturing-target object does not exist, there is no voxel. The voxel **520** is the minimum unit at the time of modeling the image capturing-target object and as shown in FIG. 5B, the voxel represents the unit volume by a regular hexahedron and in the present embodiment, the voxel is taken as the minimum unit representing the model of the image capturing-target object.

[0041] Here, the generation of a 3D model of a basketball is explained by using diagrams. FIG. 6A

to FIG. 6C are each a diagram explaining the generation of a 3D model of a basketball. FIG. 6A shows an outline of a basketball, FIG. 6B shows a 3D model **620** of the basketball on the XY plane, and FIG. 6C shows a 3D model (voxel set) **630** of the basketball in the XYZ space. FIG. 6B and FIG. 6C are each a schematic diagram showing the basketball on three-dimensional coordinates at the time of modeling the image capturing-target object on three-dimensional coordinates and the basketball is viewed by changing the viewpoint in FIG. 6B and FIG. 6C, respectively. FIG. 6B and FIG. 6C show the basketball on the same coordinates.

[0042] As shown in FIG. 6A, it is assumed that a basketball **610** is the size whose diameter is M. As shown in FIG. 6B, the basketball is represented by voxels and the size of the 3D model **620** on the XY plane is taken as L. Here, it is assumed that the size M of the basketball **610** and the size L of the 3D model **620** on the XY plane satisfy a relationship of $L \gg M$. The size L of the 3D model **620** on the XY plane of the basketball is the size including errors at the time of representing the basketball by voxels whose size is M of the actual basketball **610** and it is assumed that the size L is sufficiently large compared to the size M of the basketball **610**.

[0043] FIG. 7A to FIG. 7F are each a schematic diagram at the time of a certain player taking a shot in the game of basketball. FIG. 7A, FIG. 7B, and FIG. 7C are diagrams corresponding to FIG. 4A and FIG. 7D, FIG. 7E, and FIG. 7F are diagrams corresponding to FIG. 4B. FIG. 7A shows a case where a silhouette image **710** in FIG. 4A is mapped onto three-dimensional coordinates. FIG. 7B shows a case where an image **720** corresponding to FIG. 7A, which is obtained by extracting the portions of the hand of the player and the ball, is mapped onto three-dimensional coordinates. FIG. 7C shows a case where a 3D model (voxel set) **730** of the image **720** in FIG. 7B is mapped onto three-dimensional coordinates.

[0044] Similarly, FIG. 7D shows a case where a silhouette image **740** in FIG. 4B is mapped onto three-dimensional coordinates. FIG. 7E shows a case where an image **750** corresponding to FIG. 7D, which is obtained by extracting the portions of the hand of the player and the ball, is mapped onto three-dimensional coordinates. FIG. 7F shows a case where a 3D model (voxel set) **760** of the image **750** in FIG. 7E is mapped onto three-dimensional coordinates. The voxel size shown in FIG. 6A to FIG. 6C and FIG. 7A to FIG. 7F is represented as one whose size is larger than the actual size in order to make explanation easier-to-understand.

[0045] Here, the three-dimensional coordinate position of a voxel at the time of mapping the voxel onto three-dimensional coordinates is explained by using a diagram. FIG. 8 is a schematic diagram in which a voxel is mapped onto three-dimensional coordinates as in the case of FIG. 5B. Each of a voxel **V1**, a voxel **V2**, and a voxel **V3** consists of a regular hexahedron whose length of each side is "1" and it is assumed that the position of the voxel is represented by three-dimensional coordinates of the vertex the closest to an origin 0 among the eight vertexes of the regular hexahedron.

According to this rule, it is possible to represent three-dimensional coordinates (x, y, z) of each of the voxel **V1**, the voxel **V2**, and the voxel **V3** as (0, 0, 0), (2, 0, 0), and (2, 0, 1), respectively.

Presence/Absence of Voxel at the Time of Modeling Image Capturing-Target Object

[0046] The presence/absence of a voxel at the time of modeling an image capturing-target object is explained by using diagrams. FIG. 9A and FIG. 9B are each a diagram for explaining the presence/absence of a voxel at the time of modeling an image capturing-target object. FIG. 9A shows a table that puts together information corresponding to one frame and relating to a voxel for each three-dimensional coordinates of a voxel explained in FIG. 8 and FIG. 9B shows a relationship between a voxel of interest and peripheral voxels.

[0047] As shown in FIG. 9A, a table **910** includes Voxel Presence/absence **912**, Peripheral Voxel Presence/absence **913**, and Image Capturing-target Object Group **914** for all three-dimensional coordinates **911** in the processing-target space. Voxel Presence/absence **912** indicates whether or not there is a voxel at target coordinates and in a case where there is a voxel at the target coordinates, "1" is stored and in a case where there is no voxel, "0" is stored. Peripheral Voxel Presence/absence **913** indicates whether or not there is a voxel at each coordinates of 26 places

(SV1 to SV26) around the target coordinates. In Peripheral Voxel Presence/absence **913**, in a case where there is a voxel at each coordinates of the 26 places around the target coordinates, “1” is stored and in a case where there is no voxel, “0” is stored. Image Capturing-target Object Group **914** indicates a group to which a voxel belongs in a case where the voxel exists at the target coordinates. The table **910** includes data generated by the shape estimation unit **304** with reference to point cloud data generated by the 3D model generation unit **303** and is stored in the DB **140**. The table **910** (information relating to voxels) stored in the DB **140** is read by the ball detection unit **305** and used at the time of performing processing to detect a ball. For each voxel, adjacent voxel positions exist at 26 places in three-dimensional directions around the self-voxel (voxel of interest). The table **910** shows a relationship between the self-voxel and each of the peripheral voxels (also referred to as adjacent voxels) at SV1 to SV25 in order of relative coordinates $(-1, -1, -1)$, $(0, -1, -1)$, $(1, -1, -1)$, $(-1, 0, -1)$, $(0, 0, -1)$, $(1, 0, -1)$, $(-1, 1, -1)$, $(0, 1, -1)$, $(1, 1, 0)$, $(-1, -1, 0)$, $(0, -1, 0)$, $(1, -1, 0)$, $(-1, 0, 0)$, $(1, 0, 0)$, $(-1, 1, 0)$, $(0, 1, 0)$, $(1, 1, 0)$, $(-1, 1, 0)$, $(0, 1, 0)$, $(1, 1, 0)$, $(-1, -1, 1)$, $(0, -1, 1)$, $(1, -1, 1)$, $(-1, 0, 1)$, $(0, 0, 1)$, $(1, 0, 1)$, $(-1, 1, 1)$, $(0, 1, 1)$, $(1, 1, 1)$ in a case where the coordinates of the self-voxel are taken to be $(0, 0, 0)$. Note that the endpoint of the three-dimensional coordinates is excluded. FIG. **9B** shows this. In FIG. **9B**, voxels are represented with a predetermined distance apart from one another for easier explanation and the self-voxel (voxel of interest) is represented in gray and 26 peripheral pixels are represented in white. For example, in FIG. **8**, although there are only seven voxel positions around the self-voxel because the voxel V1 is at the endpoint of three-dimensional coordinates, in a case of having a think along the example shown in FIG. **8** actually, there is no peripheral voxel, and therefore, in the table in FIG. **9A**, in all the fields of “Peripheral Voxel Presence/absence”, “0” is stored. Similarly, the voxel V2 is located at the endpoint of three-dimensional coordinates, and therefore, the number of peripheral voxels is 11 and among them, the voxel existing as the peripheral voxel is only the voxel **3** and “1” is stored only in the corresponding field and in the other fields, “0” is stored. Although not explained here, each of the coordinates of the 26 peripheral voxels for each voxel in the table is such that the values of x-, y-, and z-coordinates are a combination of +1 for the self-voxel. The voxel V3 is also the same. Here, it is assumed that in a case where each voxel exists as the peripheral voxel, the voxel is regarded as part of the same image capturing-target object and the image capturing-target object group is represented by the same symbol. Here, the voxel V1 belongs to a group A and the voxel V2 and the voxel V3 belong to a group B.

Estimation of Size of Object

[0048] Processing to estimate a size of an object, which is performed by the shape estimation unit **304**, is explained by using diagrams. FIG. **10** is the flowchart showing a flow of processing to estimate a size of an object. The series of processing shown in the flowchart in FIG. **10** is performed by the CPU loading a program code stored in the ROM onto the RAM and executing the program code. Further, it may also be possible to implement part or all of the functions at the steps in FIG. **10** by hardware, such as an ASIC and an electronic circuit. Symbol “S” in explanation of each piece of processing means that the step is a step in the flowchart and this also applies to subsequent flowcharts.

[0049] First, image capturing by a plurality of cameras is started and in a case where the operation by the camera information obtaining unit **302** and the 3D model generation unit **303** is completed, the shape estimation unit **304** starts the operation (S1001). That is, the shape estimation unit **304** obtains the camera parameter information obtained by the camera information obtaining unit **302** and the 3D model of the image capturing-target object generated by the 3D model generation unit **303**. It may also be possible to obtain the camera parameter information and the 3D model of the image capturing-target object from each function unit or obtain from the DB **140**.

[0050] At S1002, the shape estimation unit **304** determines whether or not there is an unprocessed voxel within the processing-target space for each voxel. In the example in FIG. **5A**, the processing-target space is the portion of the volume of the cuboid consisting of the court surface on the X-and

Y-axes and “Z1” as the value in the +z-direction, which is the height direction thereof. The voxel unit is, for example, the voxel shown in FIG. 5B. Based on the table in FIG. 9A, whether or not there is a voxel at each position is determined. The search of the presence/absence of a voxel is performed, for example, in the order indicated below. First, the search is performed in the X-axis direction from an origin (0, 0, 0). Then, in a case where the search of (Y, Z)=(0, 0) is completed, the search is performed in the X-axis direction from (Y, Z)=(1, 0). Then, in a case where the search is completed at the end of the Y-axis in the order such as this, the search is performed in the X-axis direction from (Y, Z)=(0, 1). Then, in a case where the search of (Y, Z)=(0, 1) is completed, the search is performed in the X-axis direction from (Y, Z)=(1, 1). In a case where the search is completed at the end of the Y-axis in the order such as this, the search is performed from the coordinates to which 1 is added in the Z-axis coordinate. In the order such as this, the search for the entire processing-target space is performed. The order of searching the presence/absence of a voxel is not limited to this. In a case where determination results that there is a voxel are obtained (YES at S1002), the processing is moved to S1003. On the other hand, in a case where determination results that there is no voxel are obtained (NO at S1002), the processing is moved to S1013 and the flow shown in FIG. 10 is terminated.

[0051] At S1003, the shape estimation unit 304 specifies a voxel of interest that is a processing target.

[0052] At S1004, the shape estimation unit 304 determines whether or not there is a voxel (peripheral voxel) at 26 positions surrounding the voxel of interest specified at S1003. Note that there is a case where the number of positions is less than 26 depending on the position of the voxel of interest. Here, in a case where determination results that there is no voxel at each of the 26 positions surrounding the voxel of interest are obtained (NO at S1004), the processing is moved to S1006. In a case where determination results that there is a voxel at one or more of the 26 positions surrounding the voxel of interest are obtained (YES at S1004), the processing is moved to S1005.

[0053] At S1005, the shape estimation unit 304 sets the peripheral voxel (adjacent voxel) located at the position at which it is determined that there is a voxel at S1004 to the same group as that of the voxel of interest.

[0054] At S1006, the shape estimation unit 304 determines whether or not the presence/absence of a peripheral voxel is checked for all the voxels detected from the processing-target space. In a case where determination results that the presence/absence of a peripheral voxel is checked for all the voxels are obtained (YES at S1006), the processing is moved to S1007. On the other hand, in a case where determination results that the presence/absence of a peripheral voxel is not checked for all the voxels are obtained (NO at S1006), the processing is returned to S1003. Then, the voxel of interest is specified from among unprocessed voxels at S1003 and the series of processing from S1004 to S1006 is performed.

[0055] At S1007, the shape estimation unit 304 derives the size of the voxel set for each group. In the voxel set, which is the cluster of the voxels set to the same group at S1005, the maximum value of the length of each axis is found from the coordinate points of the three-dimensional coordinates located at the endmost positions in the $\pm X$ -direction, $\pm Y$ -direction, and $\pm Z$ -direction, respectively. Here, this is explained by taking the X-axis direction as an example. In a certain group, in a case where the coordinate point whose values of (x, y, z) are (3, 0, 1) has the smallest value as the value of x and the coordinate point whose values of (x, y, z) are (10, 4, 3) has the largest value as the value of x, the length in the x-direction is $10-3=7$ and the length is “7”. By calculating the lengths in the y-axis direction and the z-axis direction similarly, it is possible to derive the size of the group as a cuboid.

[0056] At S1008, the shape estimation unit 304 specifies a group of interest that is a processing target.

[0057] At S1009, the shape estimation unit 304 determines whether or not the size of the group of interest is small compared to the size L of the object obtained in advance. In a case where

determination results that the size of the group of interest is small compared to the size L of the object (object of interest) are obtained (YES at **S1009**), the processing is moved to **S1010**. On the other hand, in a case where determination results that the size of the group of interest is not small compared to the size L of the object (object of interest) are obtained (NO at **S1009**), the processing is moved to **S1012**. Specifically, whether the size of the voxel set corresponding to the group of interest is smaller than the size “L” of the basketball represented by voxels in FIG. 6B is checked. Here, in order to check the size of the basketball, in the group of the cluster of voxels set to the same group at **S1005**, the maximum value of the length of each axis is found from the coordinate points of the three-dimensional coordinates located at the endmost positions in the $\pm X$ -direction, $\pm Y$ -direction, and $\pm Z$ -direction, respectively. In a case where there is an image capturing-target object smaller than “L”, that is, being smaller than L means being small in each of the x-, y-, and z-directions.

[0058] At **S1010**, the shape estimation unit **304** estimates the shape of the group of interest as the shape of the object.

[0059] At **S1011**, the shape estimation unit **304** stores position information indicating the position of the group of interest estimated as the object (in the present embodiment, basketball) at **S1010**. Further, the shape estimation unit **304** stores time information associated with the processing-target frame and including the time generated by the server **130** and the count value counted by the timer device **180** in the DB **140** and the like. That is, the position information on the object of interest, the count value, and the time of the image capturing-target game are stored in the DB **140** and the like in association with one another. Although the position information may be, for example, coordinate information on any voxel in the voxel set corresponding to the group of interest, it is assumed that the coordinate information is that on the vertex the closest to the origin among the vertexes of the voxel the closest to the origin of the three-dimensional coordinates as explained in FIG. 8. This is not limited and the position of the object may be, for example, the centroid of the position of each voxel.

[0060] At **S1012**, the shape estimation unit **304** determines whether or not the size of the object is checked for all the groups. In a case where determination results that the size of the object is not checked for all the groups are obtained (NO at **S1012**), the processing is returned to **S1008**. Then, the group of interest is specified from unprocessed groups at **S1008** and the series of processing from **S1009** to **S1012** is performed. On the other hand, in a case where determination results that the size of the object is checked for all the groups are obtained (YES at **S1012**), the processing is moved to **S1013** and the flow shown in FIG. 10 is terminated.

[0061] By performing the flow shown in FIG. 10 described above for each frame and comparing the size of the group (voxel set) and the size of the object obtained in advance, the position of the basketball at each time and whether or not the basketball is held by a player are known. Due to this, it can be said that it is possible for the shape estimation unit **304** to specify that a specific object and another object are in contact with each other. That is, it is possible to specify the position of the basketball in a frame. In other words, based on the results of the comparison between the size of the object estimated by the shape estimation unit **304** and a predetermined reference value, it is possible to specify the position of a specific object captured by the plurality of imaging apparatuses.

[0062] Explanation is returned to FIG. 3. The violation determination unit **306** determines whether or not there is a foul by using the position relationship between the player and the basketball and the count value of the timer device **180** and sends the determination results to the display device **170** via the HUB **120** and the control device **150**. The display device **170** displays the sent determination results. A case where the foul target is taken to be the 24-second rule is explained by using a diagram.

Processing Performed by Server

[0063] Processing performed by the server **130** is explained by using a diagram. FIG. 11 is a

flowchart showing a flow of processing performed by the server **130**. Here, a case is explained where the **24**-second rule of basketball is applied as a violation target.

[0064] First, at the point in time at which an attack of one of teams begins in a processing-target basketball game, the flow shown in FIG. **11** is started (**S1101**).

[0065] At **S1102**, at the point in time at which an attack of one of teams begins in the basketball game, the counter value of the timer device **180** is set to 24 seconds. The timer of 24 seconds to the timer device **180** is set manually by, for example, a referee assistant. In a case where the counter value is set in this manner, the timer device **180** starts count.

[0066] At **S1103**, the camera information obtaining unit **302** obtains a silhouette image from the camera system **110j**.

[0067] At **S1104**, the 3D model generation unit **303** estimates the shape of an image capturing-target object. Specifically, the 3D model generation unit **303** generates a 3D model of an image capturing-target object by using the silhouette image obtained by the camera information obtaining unit **302**.

[0068] At **S1105**, the shape estimation unit **304** estimates the size of the image capturing-target object. Specifically, the shape estimation unit **304** determines the size from the 3D model (voxel set) of the image capturing-target object generated at **S1104**. The determination method is as follows. First, the presence/absence of a voxel at all the coordinate positions of the cuboid shown in FIG. **5A** and the presence/absence of a voxel on the periphery thereof are checked. The checking method is performed by checking the presence/absence of a white voxel at the 26 points on the periphery at the time of focusing attention on the gray voxel in FIG. **9B**. The table **910** in FIG. **9A** shows this. Then, the group is specified for each voxel and the size of the voxel set (image capturing-target object) is determined for each group. The detailed processing at this **S1105** is the same as that at **S1007** described in the flowchart in FIG. **10** described previously.

[0069] At **S1106**, the shape estimation unit **304** checks whether there is an image capturing-target object whose size is smaller than the size “L” of the basketball represented by voxels shown in FIG. **6B**. The detailed processing at this **S1106** is the same as that at **S1009** and **S1010** described in the flowchart in FIG. **10** described previously.

[0070] At **S1107**, whether or not the basketball is detected is determined. Specifically, in a case where there is an image capturing-target object smaller than “L” (YES at **S1107**), the ball detection unit **305** determines that the image capturing-target object is the basketball and moves the processing to **S1110**. Being “smaller than L” means being small in each of the x-, y-, and z-directions. On the other hand, in a case where there is no image capturing-target object smaller than “L” (NO at **S1107**), the processing is moved to **S1108**. That is, processing is performed in order for the successive frames, and therefore, that the basketball is detected represents that the basketball has separated from the player.

[0071] At **S1108**, the violation determination unit **306** obtains the counter value of the timer device **180**.

[0072] At **S1109**, the violation determination unit **306** determines whether or not the counter value obtained at **S1108** is “0”. That is, the violation determination unit **306** determines whether or not a predetermined time has elapsed. In a case where determination results that the counter value obtained at **S1108** is not “0” are obtained (YES at **S1109**), the processing is returned to **S1103** and the series of processing at **S1103** and subsequent steps is performed for the next frame. On the other hand, in a case where determination results that the counter value obtained at **S1108** is “0” are obtained (NO at **S1109**), the processing is moved to **S1115**.

[0073] At **S1110**, the violation determination unit **306** determines whether or not the present point in time is the time immediately after the basketball and the player of the attacking side have separated, for example, such as the time immediately after the player of the attacking side has taken a shot from the times before and after the 3D model generation. Specifically, based on the processing results of the ball detection processing for the data corresponding to the processing-

target frame (frame of interest) and the data corresponding to the preceding frame, whether or not the present point in time is the time immediately after the basketball and the player have separated. In a case where in the processing for the data of the preceding frame, no ball is detected and in the processing for the data of the frame of interest, the ball is detected and determination results that the present point in time is the time immediately after the basketball and the player have separated are obtained (YES at **S1110**), the processing is moved to **S1112**. Then, at **S1112**, the violation determination unit **306** obtains the counter value of the timer device **180** and records it in the DB **140**. On the other hand, in a case where the basketball is detected both in the processing for the data of the preceding frame and in the processing for the data of the frame of interest and determination results that the present point in time is not the time immediately after the basketball and the player have separated are obtained (NO at **S1110**), the processing is moved to **S1111**.

[0074] At **S1111**, the violation determination unit **306** determines whether the basketball thrown by the player has contacted with the goal ring or whether the shot has succeeded. It is possible to determine the presence/absence of the contact between the basketball and the goal ring by determining whether or not there is a contact between each piece of position information and the 3D model. The coordinates of the goal are those already known on the x-, y-, and z-coordinates, and therefore, it is possible to easily determine whether the voxels the size of the basketball have contacted with the goal or whether they have fallen into the basket because the position coordinates of the ball are known, for example, from the table **910** shown in FIG. **9A**. Specifically, the position information on the basketball at the time of determination at **S1106** and the position information on the goal ring stored in advance in the DB **117** are used and in a case where both pieces of position information include position information indicating an adjacent position relationship, it is determined that the basketball and the goal ring have come into contact with each other. Further, in a case where there is a portion at which the area surrounded by the position information on the goal ring intersects with the area surrounded by the position information on the basketball, it is determined that the basketball has fallen into the basket. In a case where none of these conditions is met, it is determined that the basketball has not contacted with the goal ring and the basketball has not fallen into the basket.

[0075] At **S1113**, the violation determination unit **306** determines whether or not the basketball and the goal ring have contacted with each other. In a case where determination results that the basketball and the goal ring have contacted with each other are obtained (YES at **S1113**), the processing is moved to **S1114**. On the other hand, in a case where determination results that the basketball and the goal ring have not contacted with each other are obtained (NO at **S1113**), the processing is moved to **S1108**. By this processing, whether or not a player throws the basketball (takes a shot or makes a pass) and the basketball contacts with the goal ring within a certain time is determined.

[0076] At **S1114**, the violation determination unit **306** determines whether or not the counter value of the timer device **180** at the point in time at which the basketball has contacted with the goal ring is “0”. In a case where determination results that the counter value of the timer device **180** is “0” are obtained (YES at **S1114**), the processing is moved to **S1115**. On the other hand, in a case where determination results that the counter value of the timer device **180** is not “0” are obtained (NO at **S1114**), the processing is moved to **S1116**.

[0077] At **S1115**, the violation determination unit **306** keeps a record to the effect that a violation has occurred and notifies the referee of the violation. The method of giving a notification to the referee may be a method of giving a notification using a device capable of displaying an image, such as a user interface image, or a message, or a method of giving a notification using an alert device (not shown schematically) that issues an alert. After the notification is completed, the processing is moved to **S1117**.

[0078] At **S1116**, the violation determination unit **306** resets the counter value. That is, by the violation determination unit **306**, it is determined that no violation has occurred against the 24-

second rule in the series of play.

[0079] At **S1117**, the violation determination unit **306** terminates the flow shown in FIG. **11**.

[0080] Further, at **S1111**, although it is assumed that it is possible for the violation determination unit **306** to determine at which place on the x-, y-, and z-coordinates the basketball is located from FIG. **9A**, this is not limited. For example, it may also be possible to find the position of an image capturing-target object having a unique size, not limited to the basketball, by specifying the image capturing-target object from the size of the image capturing-target object of the cluster of voxels (voxel set) using information, such as a voxel set.

[0081] As explained above, according to the system that generates a virtual viewpoint image using a plurality of cameras arranged around an image capturing-target object, it is possible to obtain the following effects. That is, in the process (stage) before generating a virtual viewpoint image, by correlating the size of a model at the point in time of generating a 3D model of an image capturing-target object with the game time, it is possible to obtain an image capable of appropriately assisting a referee in performing determination. Due to this, it is possible to determine a violation against the rules of the basketball game.

[0082] Further, according to the present embodiment, by successively measuring the size of the model of each image capturing-target object, which is generated at the time of generating a virtual viewpoint image from image data of the image capturing-target object captured by a plurality of imaging units, it is possible to utilize the measurement results for a referee assistance device that performs referee assistance of the game.

[0083] The application target of the system of the present embodiment is not limited to the 24-second rule of basketball. It is also possible to apply the system of the present embodiment to, for example, the 3-second overtime, which is another violation target of the basketball game. Further, it is also possible to apply the system of the present embodiment to, for example, determination processing of offside in soccer, which is a game other than the basketball game. Furthermore, it is also possible to track the locus of a ball in a time series.

[0084] Fouls/violations for each game to which the system of the present embodiment can be applied are explained by using a diagram. FIG. **12** is a table in which fouls/violations for each game are enumerated. As shown in FIG. **12**, a table **1200** includes information relating to Game **1201**, which is the image capturing target, and Foul/Violation **1202**, which is the target. In the table **1200**, as regards Game **1201**, games, such as basketball, soccer, and handball, are stored.

[0085] As regards Foul/Violation **1202**, for basketball, information, such as “24-second rule”, “8-second rule”, “5-second rule”, “3-second rule”, “Traveling”, and “Double dribble” is stored. That is, information indicating a violation against the game rule of basketball is stored, which is determined in a case where the ball detected by the ball detection unit **305** does not exist in a predetermined area on the court at the point in time of timing that eight seconds have elapsed from the start of the attack by one of teams by the timer device **180**. Information indicating a violation against the game rule of basketball is stored, which is determined in a case where the ball detected by the ball detection unit **305** is in contact with a player at the point in time of timing that five seconds have elapsed from the delivery of the ball from the referee to the player by the timer device **180**.

[0086] Further, for soccer, information, such as “Offside” and “Hands”, is stored.

[0087] Furthermore, for handball, information, such as “7-meter throw”, “Overtime”, “Overstep”, and “Double dribble”, is stored. Information indicating a violation against the game rule of handball is stored, which is determined in a case where, at the point in time of timing that three seconds have elapsed from the time at which the ball detected by the ball detection unit **305** contacts with a player of handball by the timer device **180**, the ball and the player are in contact with each other.

[0088] By specifying in advance a flow that is fit to each rule and storing the flow, for example, in the DB **140** of the present system, it is also made possible to efficiently perform referee assistance

in accordance with each game. That is, as shown in FIG. 12, as regards each game, such as basketball and handball, it may also be possible to store in advance data that is associated with a predetermined rule that utilizes position information and time information for determination of a referee in the DB **140** in the format of a table or the like.

[0089] In the present embodiment, although the case is explained where the event that has occurred in the game of basketball is interpreted in more detail, the case is not limited to this. It may also be possible to apply the present embodiment to a case where an event that has occurred in another ball game, such as soccer and tennis, is interpreted in more detail. Further, it may also be possible to apply the present embodiment to a case where an event that has occurred in a game in which no ball is used, such as archery and Japanese archery, is interpreted in more detail. In a case where the present embodiment is applied to the interpretation of an event that has occurred in a game in which no ball is used, it is possible to implement detection of a target by determining the size of the target and the long and narrow shape of the target by the ball detection unit **305**.

[0090] Further, the determination is not limited to the determination of whether a limit time is exceeded. For example, in a case where it is possible to determine that a violation of hands or the like has occurred in which a soccer ball contacts with hands, it may also be possible to present this to a referee by displaying information indicating that the ball has contacted with hands on the display device **170** and the like. Furthermore, it may also be possible to generate a virtual viewpoint image by the control device **150** based on the frame corresponding thereto and present the generated virtual viewpoint image to a referee by displaying it on the display device **170** and the like. Due to this, it is possible to assist the referee in performing determination. Furthermore, in a case of assisting the referee in performing determination, it is also possible to make the determination-target place easier-to-see for the referee by setting the target spatial position at which it is deemed that the contact has occurred at the center in the image.

[0091] Further, it is also possible to apply the present embodiment to the output of information relating to the speed at the time of dribble of a player in a game, such as soccer, basketball, and handball. It is also possible to output information indicating the speed at the time of dribble of a player in a case where the ball is detected in the position relationship with the same player by the ball detection unit **305** during a predetermined period of time from the time timed by the timer device **180**. That is, during a certain period, it is also possible to output the speed at the time of dribble of a player, which is derived by using information generated based on two frames immediately after the ball and the player have contacted with each other and the frame interval between which is a predetermined value or more.

[0092] Further, in the above, although the contact between a person (player) and an item (ball and the like) is explained mainly, the contact is not limited to this. For example, it may also be possible to specify a contact between persons (foul and the like).

Other Embodiments

[0093] It is also possible to implement the present disclosure by processing to supply a program that implements one or more functions of the above-described embodiments to a system or an apparatus via a network or a storage medium and to cause one or more processors in a computer of the system or the apparatus to read and execute the program. Further, it is also possible to implement the present disclosure by a circuit (for example, ASIC) that implements one or more functions.

[0094] As above, although the embodiments of the present disclosure are described in detail, the present disclosure is not limited to the above-described embodiments and it is possible to make various variations and alterations within the scope of the gist of the present disclosure described in the claims. FIG. 13 is a block diagram showing a configuration example of hardware of a computer that can be applied to an apparatus, such as the server **130** of the system of the above-described embodiments.

[0095] A CPU **1301** performs each piece of processing described above on the assumption that an

apparatus, such as the server **130** of the system of the above-described embodiments performs, as well as performing control of the entire computer using computer programs and data stored in a RAM **1302** and a ROM **1302**. That is, the CPU **1301** functions as each processing unit shown in FIG. 3.

[0096] The RAM **1302** has an area for temporarily storing computer programs and data, which are loaded from an external storage device **1306**, data obtained from the outside via an I/F (interface) **1307**, and the like. Further, the RAM **1302** has a work area used by the CPU **1301** at the time of performing various kinds of processing. That is, for example, it is possible to allocate the RAM **1302** as a frame memory and appropriately provide other various areas.

[0097] In the ROM **1303**, setting data of the present computer, boot programs and the like are stored. An operation unit **1304** has a keyboard, a mouse and the like and it is possible for a user of the present computer to input various instructions to the CPU **1301** by operating the operation unit **1304**. An output unit **1305** has, for example, a liquid crystal display and displays the results of processing by the CPU **1301**. The operation unit **1304** and the output unit **1305** are not necessarily required and it may also be possible to input and output data to and from a connected external device via the I/F **1307**.

[0098] The external storage device **1306** is a large-capacity information storage device, such as a hard disk drive device. In the external storage device **1306**, an OS (Operating System) and computer programs for causing the CPU **1301** to implement the function of each processing unit shown in FIG. 3 are stored. Further, it may also be possible to store each piece of image data as the processing target in the external storage device **1306**.

[0099] The computer programs and data stored in the external storage device **1306** are loaded onto the RAM **1302** appropriately in accordance with the control by the CPU **1301** and taken as the processing target by the CPU **1301**. It is possible to connect a network, such as a LAN and the internet, and another device, such as a projection device and a display device, to the I/F **1307** and it is possible for the present computer to obtain and send various kinds of information via this I/F **1307**. A bus **1308** connects each portion of a device, such as the server **130**, and transmits information.

[0100] With the configuration described above, the operations described in the above embodiments are controlled mainly by the CPU **1301**.

[0101] It is also possible to achieve the object of the present disclosure by supplying a storage medium storing codes of computer programs implementing the functions described previously to the system and by the system reading and executing the codes of the computer programs. In this case, the codes of the computer programs themselves read from the storage medium implement the functions of the embodiments described previously and the storage medium storing the codes of the computer programs constitutes the present disclosure. Further, the present disclosure also includes a case where the operating system (OS) or the like running on the computer performs part or all of the actual processing based on instructions of the codes of the computer programs and by the processing, the functions described previously are implemented.

[0102] Further, it may also be possible to implement the present disclosure by the following aspect. That is, the present disclosure also includes a case where computer program codes read from a storage medium are written to a memory comprised by a function extension card inserted into a computer or a function extension unit connected to the computer and then based on instructions of the computer program codes, a CPU or the like comprised by the function extension card or the function extension unit performs part or all of the actual processing and thereby the functions described previously are implemented.

[0103] In a case where the present disclosure is applied to the above-described storage medium, in the storage medium, codes of computer programs corresponding to the processing explained previously are stored.

[0104] Embodiment(s) of the present disclosure can also be realized by a computer of a system or

apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a ‘non-transitory computer-readable storage medium’) to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

[0105] While the present disclosure has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0106] According to the present embodiment, it is possible to obtain information capable of appropriately assisting a referee in performing determination.

[0107] This application claims the benefit of Japanese Patent Application No. 2021-064865, filed Apr. 6, 2021, which is hereby incorporated by reference wherein in its entirety.

Claims

1. An information processing apparatus comprising: one or more memories storing instructions; and one or more processors executing the instructions to: obtain three-dimensional shape data captured objects generated by using a plurality of images obtained by a plurality of imaging apparatuses capturing the objects; estimate a size of groups representing the captured objects based on the three-dimensional shape data; and specify that the particular object is separate from another.
2. The information processing apparatus according to claim 1, wherein the one or more processors execute the instructions to: specify that the particular object is separated from the another object in a case where the three-dimensional shape data of a particular included in the captured objects whose estimated size is smaller than a reference value as the three-dimensional shape of the predetermined object.
3. The information processing apparatus according to claim 1, wherein the one or more processors execute the instructions to: specify that the particular object is not separated from the another object in a case where the each size of the captured object is not smaller than a predetermined reference value.
4. The information processing apparatus according to claim 1, wherein the one or more processors execute the instructions to: output information for notifying the separation of the particular object and the another object.
5. The information processing apparatus according to claim 1, wherein The particular object and the another object are objects in a game that is captured by the plurality of imaging apparatuses.
6. (canceled)
7. (canceled)
8. The information processing apparatus according to claim 1, wherein The predetermined object is

- a basketball, and the one or more processors execute the instructions to: detect the basketball, and output information relating to a game of basketball based on the specified separation.
- 9.** The information processing apparatus according to claim 8, wherein the information indicates that violation rule of basketball.
- 10.** The information processing apparatus according to claim 1, wherein the predetermined object is a soccer ball, and the one or more processors execute the instructions to: detect the soccer ball, and output information relating to a game of soccer based on the specified separation.
- 11.** The information processing apparatus according to claim 10, wherein the information indicates that violation rule of soccer.
- 12.** The information processing apparatus according to claim 1, wherein the second object is a handball, and the one or more processors execute the instructions to: detect the handball, and output information relating to a game of handball based on the specified separation.
- 13.** The information processing apparatus according to claim 12, wherein the information indicates that violation rule of handball.
- 14.** (canceled)
- 15.** (canceled)
- 16.** The information processing apparatus according to claim 1, wherein the three-dimensional shape data is data represented by voxels and the one or more processors execute the instructions to: estimate each size of the groups based on a number of voxels on three-dimensional coordinates.
- 17.** An information processing method comprising: generating three-dimensional shape data representing each three-dimensional shape of objects by using a plurality of images obtained by a plurality of imaging apparatuses capturing the objects, wherein the three-dimensional shape data is data represented by voxels and peripheral voxels are regarded as being part of one object; estimating each size of the objects based on the three-dimensional shape data based on positions of the voxels; comparing each estimated size of particular objects included in the objects obtained by the estimating with a reference value based on a predetermined size of a predetermined object; specifying the three-dimensional shape of the particular object whose estimated size is smaller than the reference value as the three-dimensional shape of the predetermined object; specifying a position of the specified three-dimensional shape of the predetermined object included in particular objects among the objects that is captured by the plurality of imaging apparatuses; and specifying a contact between the particular object and the predetermined object based on the specified position of the predetermined object.
- 18.** A non-transitory computer readable storage medium storing a program for causing a computer to perform an information processing method comprising: generating three-dimensional shape data representing a three-dimensional shape of objects by using a plurality of images obtained by a plurality of imaging apparatuses capturing the objects, wherein the three-dimensional shape data is data represented by voxels and peripheral voxels are regarded as being part of one object; estimating each size of the objects based on the three-dimensional shape data based on positions of the voxels; comparing each estimated size of particular objects included in the objects obtained by the estimating with a reference value based on a predetermined size of a predetermined object; specifying the three-dimensional shape of the particular object whose estimated size is smaller than the reference value as the three-dimensional shape of the predetermined object; specifying a position of the specified three-dimensional shape of the predetermined object included in particular objects among the objects that is captured by the plurality of imaging apparatuses; and specifying a contact between the particular object and the predetermined object based on the specified position of the predetermined object.
-