

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285897

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

TSAI; Tzu-Chung et al.

SEMICONDUCTOR DIE CARRIER STRUCTURE

Abstract

An apparatus having a first portion including a first front wall, a first rear wall, and a bottom wall integrally coupled to the first front wall and the first rear wall, and pivotal pin structures integrally coupled to and extending from the first rear wall. The apparatus includes a second portion having a second front wall, a second rear wall, and a top wall integrally coupled to the second front wall and the second rear wall, and pin holders integrally coupled to and extending from the second rear wall and at an offset angle with reference to the top wall. The pivotal pin structure includes a base support connected to the first rear wall and a shaft connected to the base support, and the pin holder defines an opening sized and shaped to accept the shaft. The first and second portions are sized and shaped to be pivotally movable between open and closed configurations.

Inventors: TSAI; Tzu-Chung (Hsinchu, TW), KO; Ping-Cheng (Hsinchu, TW), LIU; Fang-yu (Hsinchu, TW), YANG; Jhih-Yuan (Hsinchu, TW)

Applicant: Taiwan Semiconductor Manufacturing Co., Ltd. (Hsinchu, TW)

Family ID: 1000008619705

Assignee: Taiwan Semiconductor Manufacturing Co., Ltd. (Hsinchu, TW)

Appl. No.: 19/214983

Filed: May 21, 2025

Related U.S. Application Data

parent US continuation 18514268 20231120 parent-grant-document US 12322623 child US 19214983

parent US division 17216247 20210329 parent-grant-document US 11881421 child US 18514268

parent US division 16448467 20190621 parent-grant-document US 10964569 child US 17216247

us-provisional-application US 62692357 20180629

Publication Classification

Int. Cl.: **H01L21/673** (20060101); **B29C35/16** (20060101); **B29C45/72** (20060101); **B29C45/73** (20060101); **B29C45/74** (20060101); **B29C45/78** (20060101); **B29K69/00** (20060101); **B29L31/00** (20060101)

U.S. Cl.:

CPC **H01L21/67386** (20130101); **B29C45/7207** (20130101); **B29C45/73** (20130101); **B29C45/74** (20130101); **B29C45/78** (20130101); **H01L21/67356** (20130101); **H01L21/67366** (20130101); **H01L21/67369** (20130101); **H01L21/67373** (20130101); **H01L21/67379** (20130101); **H01L21/67396** (20130101); B29C2035/1616 (20130101); B29C2945/76531 (20130101); B29C2945/76668 (20130101); B29C2945/76688 (20130101); B29C2945/76765 (20130101); B29K2069/00 (20130101); B29L2031/712 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of U.S. patent application Ser. No. 18/514,268, titled “Semiconductor Die Carrier Structure,” filed on Nov. 20, 2023, which is a divisional application of U.S. patent application Ser. No. 17/216,247, titled “Semiconductor Die Carrier Structure,” filed on Mar. 29, 2021, which is a divisional application of U.S. patent application Ser. No. 16/448,467, titled “Semiconductor Die Carrier Structure,” filed on Jun. 21, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/692,357, titled “Semiconductor Die Carrier Structure,” filed on Jun. 29, 2018, all of which are incorporated herein by reference in their entireties.

BACKGROUND

[0002] Semiconductor samples undergo numerous processing operations during fabrication process in an integrated circuit (IC) fabrication facility. Such semiconductor samples are generally packed in a container for storing, transporting, and/or shipping. Containers whose interior offers a clean room climate are therefore necessary for storing the semiconductor wafers and for transporting the semiconductor samples to various processing locations.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with common practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

[0004] FIGS. 1A-1D are various views of an apparatus in a closed container configuration, according to some embodiments.

[0005] FIGS. 2A-2B are various views of an apparatus respectively in an open and a closed container configuration, according to some embodiments.

[0006] FIG. 3 is a side view of an apparatus in an open container configuration, according to some embodiments.

[0007] FIGS. 4A-4C are various views of an apparatus in a closed container configuration,

according to some embodiments.

[0008] FIGS. 5A-5D are various views of an apparatus, according to some embodiments.

[0009] FIGS. 6A-6B and 7A-7B are various views of pivot structures of an apparatus, according to some embodiments.

[0010] FIGS. 8A-8B are various views of a storage medium for one or more wireless communication devices in an apparatus in an open container configuration, according to some embodiments.

[0011] FIGS. 9A-9C are various views of padding structures of an apparatus, according to some embodiments.

[0012] FIG. 10 is a bottom view of an apparatus in a closed container configuration, according to some embodiments.

[0013] FIG. 11 is a mold injection apparatus for forming an apparatus, according to some embodiments.

[0014] FIG. 12 is a cooling system for cooling an apparatus, according to some embodiments.

[0015] FIG. 13 is a flow chart of forming an apparatus for transporting semiconductor elements, according to some embodiments.

DETAILED DESCRIPTION

[0016] The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed that are between the first and second features, such that the first and second features are not in direct contact.

[0017] Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper,” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

[0018] The term “nominal” as used herein refers to a desired, or target, value of a characteristic or parameter for a component or a process operation, set during the design phase of a product or a process, together with a range of values above and/or below the desired value. The range of values is typically due to slight variations in manufacturing processes or tolerances.

[0019] The term “substantially” as used herein indicates the value of a given quantity that can vary based on a particular technology node associated with the subject semiconductor device. In some embodiments, based on the particular technology node, the term “substantially” can indicate a value of a given quantity that varies within, for example, $\pm 5\%$ of a target (or intended) value.

[0020] The term “about” as used herein indicates the value of a given quantity that can vary based on a particular technology node associated with the subject semiconductor device. In some embodiments, based on the particular technology node, the term “about” can indicate a value of a given quantity that varies within, for example, 5-30% of the value (e.g., $\pm 5\%$, $\pm 10\%$, $\pm 20\%$, or $\pm 30\%$ of the value).

[0021] Semiconductor samples undergo numerous processing operations during a fabrication process in an integrated circuit (IC) fabrication facility. Such semiconductor samples are generally packed in a container for storing, transporting, and/or shipping. The container should tightly encapsulate one or more semiconductor samples and prevent the samples from physical damage or external contamination from, for example, gases, liquids, particles, and/or electrostatic charges. In

addition, the interior of the container should not release any contaminating chemical substances. Therefore, there is a need of containers for sensitive semiconductor elements that provide a clean room climate for storing and transporting sensitive semiconductor elements.

[0022] Various embodiments of the present disclosure are directed to an apparatus for storing and transporting semiconductor elements and a method of making the same. References to “apparatus” made below may be understood to encompass a container, a delivery unit, an assembly, a system thereof, and the like. References to “semiconductor elements” made below may be understood to encompass any semiconductor-based samples or products, including but not limited to wafers, portions of wafers, and semiconductor devices. In some embodiments, the apparatus is a semiconductor die carrier that includes a locking mechanism, such as a latch positioned between two adjacent bumpers protruding from a front surface of a closed semiconductor die carrier. The latch can include a catch structure positioned on a top portion (e.g., a cover) of the semiconductor die carrier and a beveled trapezoidal-shaped edge positioned on a bottom portion (e.g., a base) of the semiconductor die carrier. In some embodiments, the semiconductor die carrier can include a pair of partially-recessed pivotal pin structures positioned at a rear wall of the semiconductor die carrier opposing the latch. In some embodiments, the semiconductor die carrier can include one or more storage medium, such as slots within the enclosed space formed by the top and bottom portions of the semiconductor die carrier. The storage medium can include one or more grooves configured to securely hold one or more wireless communication devices. In some embodiments, the semiconductor die carrier can include silicone pad and sponges positioned in the bottom portion of the semiconductor die carrier for holding semiconductor dies having various sizes. In some embodiments, the semiconductor die carrier can include openings, such as drain holes at the bottom portion, for draining liquids and to facilitate cleaning of the semiconductor die carrier. In some embodiments, the top and bottom portions of the semiconductor die carrier can be formed using suitable polycarbonate composites that reduce the release of chemical contamination into the enclosed space and provides improved electrical and mechanical properties of the semiconductor die carrier. In some embodiments, the top and bottom portions of the semiconductor die carrier is manufactured by an injection molding apparatus. The manufacturing process provides a heating process where different portions of the mold injection barrel are heated to different temperatures. The manufacturing process also provides a cooling process where the mold-inject formed top or bottom portion is cooled down gradually in a controlled manner. Such heating and cooling process can provide improved electrical and mechanical properties by eliminating imperfections (e.g., particles, voids, or air bubbles) in the top and bottom portions. In some embodiments, the semiconductor die carrier can also include imprinted barcodes (e.g., two-dimensional matrix barcodes) on its exterior to identify information related to the semiconductor elements stored within the semiconductor die carrier.

[0023] In accordance with various embodiments of this disclosure, the apparatus described in the present disclosure provides, among other things, benefits such as (i) improved physical damage prevention due to protected latch and partially-recessed pivotal pin structures; (ii) improved protection for enclosed wireless communication devices due to an enclosed and grooved storage slots positioned between top and bottom portions of the semiconductor; (iii) reduced manufacturing cost due to silicone and sponge pads that allow semiconductor dies with various sizes to be securely placed inside the semiconductor die carrier; (iv) improved protection from electrostatic charges and physical damage due to improved polycarbonate material that forms the semiconductor die carrier; and (v) convenient information read due to imprinted barcodes located on the exterior surface of the semiconductor die carrier.

[0024] FIGS. 1A-1D are various views of an apparatus **100** in a closed container configuration, according to some embodiments. In some embodiments, a closed container configuration can be a position of apparatus **100** where a top portion and a bottom portion of apparatus **100** are engaged in a releasably locked configuration through a latch. FIG. 1A is a perspective view of apparatus **100**.

FIG. 1B is a side view of apparatus **100**. FIG. 1C is a bottom view of apparatus **100**. FIG. 1D is a plan view of apparatus **100**. Apparatus **100** can be a semiconductor die carrier structure that includes two body portions. For example, apparatus **100** can include a top portion **120** and a bottom portion **110** that have matching edges to form an interlocking structure in the closed container configuration as shown in FIGS. 1A-1D. Apparatus **100** includes a latch **114** positioned on a front wall of apparatus **100** and a pair of pivots **116** positioned on a rear wall of apparatus **100** opposing the front wall. As illustrated in FIG. 1C, apparatus **100** also includes a plurality of openings **140** located on a bottom surface of bottom portion **110**. The plurality of openings **140** can be used as drainage holes for draining liquids.

[0025] FIG. 2A is a perspective view of an apparatus **100** in an open container configuration, according to some embodiments. In some embodiments, an open container configuration can be a position of apparatus **100** where its latch is disengaged and a top surface of the top portion and a bottom surface of the bottom portion of apparatus **100** are substantially in the same geometrical plane, such as the configuration illustrated in FIG. 2A. The storage compartment can be accessed (e.g., by a user) within apparatus **100** to place or retrieve semiconductor samples in the open container configuration. In some embodiments, apparatus **100** can be in other container configurations between the closed and open container configuration. For example, apparatus **100** can be in a partially open container configuration that is between the open and closed container configurations where the stored semiconductor samples are accessible (e.g., to a user). FIG. 2B is a front view of apparatus **100** in a closed container configuration, according to some embodiments. Structures illustrated in FIGS. 2A-2B that are similar to those illustrated in FIGS. 1A-1D may use the same numerals for ease of explanation; however, this repetition does not in itself dictate a relationship between the various embodiments and/or configurations discussed. Apparatus **100** illustrated in FIGS. 2A-2B further includes a projection **114-1** of latch **114** integrally connected to a first front wall **112-1** of bottom portion **110**. Projection **114-1** can be a structure protruding from first front wall **112-1** and formed using any suitable shapes. In some embodiments, projection **114-1** can be formed using a beveled trapezoidal-shaped edge. A base of the trapezoidal-shaped edge can have a length between about 3 mm and about 60 mm and a width between about 4.5 mm and about 80 mm. A height of the beveled trapezoidal-shaped edge protruding from first front wall **112-1** can be between about 6 mm and 102 mm. Exemplary ratios of length, width, and height combinations of the trapezoidal-shaped edge can be about (i) 4/5/7, (ii) 7/8/10, (iii) 13/20/26, (iv) 20/26/40; or (v) 51/78/105. In some embodiments, exemplary ranges of length, width, and height combinations of the trapezoidal-shaped edge can be (i) about 0.1 to about 4/about 0.1 to about 5/about 0.1 to about 7, (ii) about 0.1 to about 7/about 0.1 to about 8/about 0.1 to about 10, (iii) about 0.1 to about 13/about 0.1 to about 20/about 0.1 to about 26, (iv) about 0.1 to about 20/about 0.1 to about 26/about 0.1 to about 40; or (v) about 0.1 to about 51/about 0.1 to about 78/about 0.1 to about 105, all in millimeters. For example, exemplary length, width, and height combinations of the trapezoidal-shaped edge can be about (i) 3.05/4.83/6.35, (ii) 6.35/7.87/9.40, (iii) 12.70/19.05/25.40, (iv) 19.05/25.40/38.10, and (v) 50.80/76.20/101.60, all in millimeters. Other suitable length, width, and height combinations can also be used. A pair of bumpers **114-2** are also integrally connected to first front wall **112-1** of bottom portion **110** and adjacent to projection **114-1**. In some embodiments, bumpers **114-2** protrude further from first front wall **112-1** than projection **114-1**. In some embodiments, projection **114-1** protrudes further from first front wall **112-1** than bumpers **114-2**. Nonetheless, as projection **114-1** and bumpers **114-2** protrude from first front wall **112-1**, bumpers **114-2** can be used to protect projection **114-1** from accidental physical contact with external objects during transportation of apparatus **100**—which in turn reduces the probability of apparatus **100** being accidentally opened.

[0026] Top portion **120** and bottom portion **110** are sized and shaped to be rotatably and pivotally movable between a closed container configuration (e.g., shown in FIG. 1A) and an open container configuration (e.g., shown in FIG. 2A). Top portion **120** includes a catch structure **124** integrally

connected to a second front wall **122-1**. Recess **125** is formed in catch structure **124**, and when apparatus **100** is in the closed container configuration, at least a portion of projection **114-1** is releasably secured inside recess **125** (as shown in FIG. 2B). In some embodiments, catch structure **124** can include a tip **124-1** that, in a closed container configuration of apparatus **100**, is configured to be pulled away in a direction away from first front walls **112-1** (e.g., by a user) such as to release projection **114-1** from catch structure **124**. Top portion **120** can then be rotatably moved away from bottom portion **110** so as to form a fully open configuration (FIG. 2A). Similarly, top portion **120** can be rotatably moved towards bottom portion **110**, and projection **114-1** can be releasably secured inside recess **125** by pushing top portion **120** down towards bottom portion **110**. The beveled-shaped edge of projection **114-1** and tip **124-1** that is formed using flexible material can provide the benefits of opening easily and better adhesion

[0027] Each wall of top portion **120** and bottom portion **110** can be in a square or rectangular shape as illustrated in the drawings of the present disclosure. However, these drawings are for illustration only. Each wall of top portion **120** and bottom portion **110** can be in any other suitable shape. Two additional side walls **112-3**, **112-4**, **122-3**, and **122-4** for respective top and bottom portions **120** and **110** can be provided and formed using any suitable geometrical shapes. For example, first and second front walls **112-1** and **122-1**, and rear walls **112-2** and **122-2**, can be curved and directly connected together in some embodiments. When each wall of top portion **120** and bottom portion **110** is in a square, rectangular or curved shape, each corner of apparatus **100** can have a smooth curvature. In some embodiments, a bottom wall **112-B** is integrally coupled to first front wall **112-1** and first rear wall **112-2**. In some embodiments, a top wall **122-T** of top portion **120** is integrally coupled to second front wall **122-1** and second rear wall **122-2**.

[0028] FIG. 3 is a side view of an apparatus **300** in an open container configuration, according to some embodiments. Apparatus **300** includes machine-readable identifying codes **310** and **320** formed on suitable exterior surfaces of the apparatus. For example, machine-readable identifying codes **310** and **320** can be formed on side walls **112-4** and **122-4** of bottom and top portions **110** and **120** respectively. Machine-readable identifying codes **310** and **320** can include data regions that include high-intensity features and low-intensity features. In some embodiments, the high-intensity features and low-intensity features represent binary data that can correspond to an identification of the semiconductor sample (e.g., serial number, sample name, sample type, sample attribute, or other suitable identifier) and/or other characteristics of the semiconductor sample, such as a suitable process characteristic or a performance metric. The machine-readable identifying codes **310** and **320** can also include a reference mark such as a position, alignment, or timing mark. In some embodiments, machine-readable identifying codes **310** and **320** comply with a linear code standard (e.g., a one-dimensional barcode) or matrix code standard (e.g., a two-dimensional barcode) such as United Parcel Code (“UPC”), QR Code® (a trademark of Denso Wave Inc.), Data Matrix, and/or Portable Data File 417 (“PDF417”).

[0029] FIGS. 4A-4C are various views of an apparatus **400** in a closed container configuration, according to some embodiments. FIG. 4A is a perspective view of apparatus **400**. FIG. 4B is a rear view of apparatus **400**. FIG. 4C is a side view of apparatus **400**. Apparatus **400** can be a semiconductor die carrier structure similar to apparatus **100** described above and includes two body portions (e.g., top and bottom portions). Structures illustrated in FIGS. 4A-4C that are similar to those illustrated in FIGS. 1A-1D may use the same numerals for ease of explanation; however, this repetition does not in itself dictate a relationship between the various embodiments and/or configurations discussed. Apparatus **400** illustrated in FIGS. 4A-4C further includes a pair of pivots **116** having integrally connected to a first rear wall **112-2** and a second rear wall **122-2** of bottom portion **110** and top portion **120** respectively. Each pivot **116** includes a pivotal pin structure **118** of bottom portion **110** releasably secured in a pin holder **117** of top portion **120**. Each pivot **116** and its pin holder **117** and pivotal pin structure **118** are further described in detail with references to FIGS. 5A-7B below.

[0030] FIGS. 5A, 5C, and 5D are various views of a top portion (e.g., a cover) of an apparatus, according to some embodiments. FIG. 5B is a side view of an apparatus in a closed container configuration. FIG. 5A is a perspective view of top portion **120**. FIGS. 5C and 5D are close up views of pin holder **117** as illustrated in FIGS. 5A-5B and also in FIGS. 4A-4C. Structures illustrated in FIGS. 5A-5D that are similar to those illustrated in FIGS. 4A-4C may use the same numerals for ease of explanation; however, this repetition does not in itself dictate a relationship between the various embodiments and/or configurations discussed. Top wall **122-T** is integrally coupled to second front wall **122-1** and second rear wall **122-2**. Pin holder **117** can be integrally coupled to and extend from second rear wall **122-2**. For example, a pin holder **117** can protrude from the intersection of sidewall **122-4** and second rear wall **122-2**, and an offset angle θ between second rear wall **122-2** and top wall **122-T** (as indicated by the dashed lines in FIG. 5A) can be in a range between about -20° and about 210° . In some embodiments, offset angle θ can be between about 0° and about 273° . Similarly, bottom portion **110** can have a first rear wall **112-2** that is at an angle $\pi-\theta$ degrees (in correlation with offset angle θ) with reference to bottom wall **112-B**. Therefore, first and second rear walls are aligned substantially in parallel with each other in open and closed container configurations. Such pivot configuration forms a pair of pivots **116** that are partially recessed without significantly protruding from the rear of the apparatus. Such configuration can provide the benefit of reducing the likelihood of damages to the pivot structure as pivots protruding from the rear of the apparatus are more likely to collide with other objects during transportation and suffer physical damage. Such configuration also provides the benefit of maintaining a substantially flat position for an open container configuration that enables easy access to contents stored within the container. For example, as illustrated in FIG. 2A and FIG. 3, top wall **122-T** and bottom wall **112-B** are substantially in the same geometrical plane (e.g., dashed line **330** in FIG. 3) when the apparatus is in a fully open container configuration. In addition, pin holder **117** defines an opening **117-1** sized and shaped to accept pivot **118** at an aligned position between bottom portion **110** and top portion **120**. Pin holder **117** also includes an entry surface **117-2** for guiding pivot **118** into opening **117-1**, as further described below with reference to FIGS. 6A-6B.

[0031] FIGS. 6A-6B are various views of top portion and bottom portion of an apparatus, according to some embodiments. FIGS. 7A-7B are various views of pivot **116** that releasably connects a top portion **120** to a bottom portion **110** of an apparatus, according to some embodiments. Structures illustrated in FIGS. 6A-7B that are similar to those illustrated in FIGS. 4A-4C may use the same numerals for ease of explanation; however, this repetition does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

[0032] FIG. 6A illustrates a shaft and a pin holder of pivot **118** prior to engagement and FIG. 6B illustrates the shaft being rotatably disposed inside the pin holder. For example, pivot **118** includes a shaft **118-2** protruding from a side surface of base support **118-1**. Base support **118-1** can be a supporting arm connected to first rear surface **112-2** of bottom portion **110**. Shaft **118-2** protrudes from a side wall of base support **118-1** and is configured to be releasably situated in opening **117-1** of pin holder **117**. FIG. 6A illustrates base support **118-1** and shaft **118-2** of bottom portion **110** in close proximity to entry surface **117-2** and opening **117-1** of pin holder **117** of top portion **120**. To releasably dispose shaft **118-2** into opening **117-1**, a force can be exerted (e.g., by a user) by pushing shaft **118-2** towards and form physical contact with entry surface **117-2**. The elasticity of base support **118-1** can be configured such that it allows shaft **118-2** to be further pushed (e.g., by a user) into opening **117-1**. Shaft **118-2** can then be disposed into opening **117-1** and secured by the surrounding interior walls of opening **117-1**. In some embodiments, a greater elasticity can also reduce the force needed for pushing shaft **118-2** into opening **117-1**.

[0033] As illustrated in FIGS. 7A-7B, pivot **116** includes pivot **118** and pin holder **117**. Entry surface **117-2** of pin holder **117** is configured to guide shaft **118-2** into opening **117-1**. For example, entry surface **117-2** can be at a non-perpendicular angle ϕ with reference to second rear wall **122-2**.

In some embodiments, non-perpendicular angle ϕ can be in a range from about 95° to about 170°. For example, non-perpendicular angle ϕ can be from about 95° to about 140° or from about 140° to about 170°. A greater non-perpendicular angle ϕ can reduce the force needed for pushing shaft **118-2** into opening **117-1**. Shaft **118-2** protrudes from a base support **118-1**. In some embodiments, shaft **118-2** can have a length **L1** measured along a y-axis and in a range between about 1.5 mm and 1.9 mm. For example, length **L1** can be between about 1.5 mm and about 1.6 mm, between about 1.6 mm and about 1.7 mm, between about 1.7 mm and about 1.8 mm, or between about 1.8 mm and 1.9 mm. In some embodiments, **L1** can be about 1.7 mm. In some embodiments, shaft **118-2** can have a width **L2** measured along an x-axis and in a range between about 1.35 mm and about 1.65 mm. For example, length **L2** can be between about 1.35 mm and about 1.55 mm or between 1.55 mm and 1.65 mm. In some embodiments, length **L2** can be about 1.5 mm. In some embodiments, a ratio of **L1** over **L2** can be between about 0.9 and about 1.4. For example, the ratio can be between about 0.9 and about 1.1, between about 1.1 and about 1.2, and between about 1.2 and about 1.4. In some embodiments, the ratio can be about 1.3. A lower ratio of **L1** to **L2** can provide a more secure fit of shaft **118** within opening **117-1**. In some embodiments, shaft **118-2** can have any suitable non-rectangular shapes such that it can be easily inserted into opening **117-1**. For example, shaft **118-2** can have a cross-sectional shape that includes two or more surfaces that are non-perpendicular to sidewall surfaces of base support **118-1**. For example, first surface **118-2A** of shaft **118-2** can be at a non-perpendicular angle α with reference to sidewall **118-1A** of base support **118-1**. In some embodiments, non-perpendicular angle α can be in a range between about 95° and about 170°. For example, non-perpendicular angle α can be between about 95° and about 140° or between about 140° and about 170°. Similar to non-perpendicular angle ϕ described above, a greater non-perpendicular angle α can reduce the force needed for pushing shaft **118-2** into opening **117-1**. First surface **118-2A** can have a length **L3** measured along the x-axis that is in a range of about 1.1 mm to about 1.3 mm. For example, length **L3** can be about 1.24 mm. In some embodiments, shaft **118-2** can further include a second surface **118-2B** connected to first surface **118-2A**, and an angle β between first and second surfaces **118-2A** and **118-2B** can be in a range from about 0° to about 225°. A length **L4** of second surface **118-2B** measured along the y-axis can be in a range between about 0.3 mm and about 0.4 mm. For example, length **L4** can be about 0.4 mm. A third surface **118-2C** is connected to second surface **118-2B** and can be substantially in parallel with sidewall **118-1A** of base support **118-1**. A length **L5** of third surface **118-2C** measured along the y-axis can be in a range between about 0.6 mm and about 1.0 mm. For example, length **L5** can be about 0.8 mm. In some embodiments, fourth surface **118-2D** is between third surface **118-2C** and sidewall **118-1A**. In some embodiments, fourth surface **118-2D** can be substantially perpendicular to sidewall **118-1A** of base support **118-1**.

[0034] FIG. **8A-8B** are various views of an apparatus that includes a storage medium for wireless communication devices, according to some embodiments. Structures illustrated in FIGS. **8A-8B** that are similar to those illustrated in FIGS. **4A-4C** may use the same numerals for ease of explanation; however, this repetition does not in itself dictate a relationship between the various embodiments and/or configurations discussed. FIG. **8A** illustrates an apparatus **800** that includes a storage medium **802** for storing wireless communication devices **810** such as, for example, a radio-frequency identification (RFID) device. In some embodiments, storage medium **802** can be positioned near or at a rear end of apparatus **800**, as illustrated in FIG. **8A**. In some embodiments, storage medium **802** can be positioned at any suitable location within apparatus **800**, such as walls **112-1**, **112-2**, **112-3**, and **112-4** of apparatus **100** illustrated in FIG. **2A** above. Storage medium **802** can be used to store wireless communication device **810** that can include quick response (QR) code for storing information, such as identification of samples inside apparatus **800**. In some embodiments, wireless communication device **810** can include electrically stored information of the one or more semiconductor samples stored in apparatus **800** such as their quantity, weight, fabrication process, history record, and any other suitable information. In some embodiments,

wireless communication device **810** can be an RFID device that uses electromagnetic fields to automatically identify and track tags or devices attached to apparatus **800**. In some embodiments, wireless communication device **810** can include passive tags or devices that collect energy from a nearby RFID reader's interrogating radio waves. In some embodiments, wireless communication device **810** can be active tags that includes a local power source, such as a battery, and can operate at hundreds of meters (for example) from the RFID reader. A receiver, such as a computer or reading device, can be used to record and track the information transmitted from the wireless communication device **810**. FIG. **8B** is a perspective view that illustrates a cross section of apparatus **800**. As illustrated in FIG. **8B**, apparatus **800** also includes a groove **804** and one or more clips **822** that can be configured to contour the shape of wireless communication device **810** such that wireless communication device **810** can be securely and releasably positioned in storage medium **802**.

[0035] FIGS. **9A-9C** are various views of padding used in apparatus to securely hold one or more semiconductor samples having various sizes, according to some embodiments. As illustrated in FIGS. **9A-9C**, padding **900** includes a base **902** and various trenches **904** formed therein. Trenches **904** can have a depth d into base **902** that can be configured based on thicknesses of semiconductor samples. In some embodiments, depth d can be in a range from about 0.1 mm to about 100 mm. In some embodiments, trenches **904** can have a width $w_{sub.T}$ that is between about 1 mm to about 100 mm and a length $L_{sub.T}$ that is between about 1 mm and 100 mm. In some embodiments, base **902** can be formed using any suitable material such as, for example, silicone material, sponge material, and combinations thereof. Silicone and sponge material can provide, among other things, benefits of (i) not leaving any glue residue on rear side of semiconductor devices after the semiconductor devices are removed from base **902**; (ii) free of volatile organic compounds (VOCs); (iii) high recyclability (e.g., used multiple times); and (iv) compliant with Restriction of Hazardous Substances Directive (RoHS). In some embodiments, silicone material and sponge material can reduce any external vibrations experienced by the apparatus such that the semiconductor samples stored within the apparatus can experience reduced vibration which in turn protects the stored samples.

[0036] FIG. **10** is a bottom view of an apparatus that includes openings formed in its bottom portion, according to some embodiments. As shown in FIG. **10**, a plurality of openings **1002** can be formed at the bottom surface of bottom portion **1010** of apparatus **1000**. Apparatus **1000** and bottom portion **1010** can be respectively similar to apparatus **100** and bottom portion **110** illustrated in FIGS. **1A-1D**, and would not be described in detail here for simplicity. In some embodiments, openings **1002** can be used as drainage holes to facilitate removal of cleaning solution during cleaning processes performed on apparatus **1000**. In some embodiments, openings **1002** can be used as means for releasing chemicals in the event of chemical contamination within apparatus **1000**. In some embodiments, openings **1002** can be formed at any suitable locations on bottom portion **1010**. In some embodiments, openings **1002** can have a width $W_{sub.D}$ that is in a range between about 3 mm and about 7 mm, and a length $L_{sub.D}$ that is in a range between about 3 mm and about 15 mm. In some embodiments, at least one or more openings **1002** are formed in bottom wall **1010** and under the storage medium for wireless communication devices, thus exposing a portion of the storage medium. Therefore, the at least one or more openings **1002** can also be used as a view port to determine (e.g., by a user) whether a wireless communication device is stored in the storage medium without having to open apparatus **1000**.

[0037] FIG. **11** illustrates an exemplary mold injection apparatus, according to some embodiments. Mold injection apparatus **1100** illustrated in FIG. **11** includes motor **1102**, controller **1104**, hopper **1106**, reciprocating screw **1110**, barrel **1112**, front heaters **1114A**, middle heaters **1114B**, rear heaters **1114C**, nozzle **1116**, and mold **1118**. Other structures can also be included in FIG. **11** but are not illustrated for simplicity. Reciprocating screw **1110** extends along the longitudinal axis of barrel **1112** and is driven by motor **1102**. Controller **1104** is configured to control the motions of motor

1102. For example, controller **1104** can start, stop, and adjust the power of motor **1102** which in turn determines the start, stop, and rotational speed of reciprocating screw **1110**. Front heaters **1114A** are configured to heat up a front portion of barrel **1112** to a nominal temperature for a nominal period of time. Similarly, middle heaters **1114B** are configured to heat up a middle portion of barrel **1112** and rear heaters **1114C** are configured to heat up a rear portion of barrel **1112**, both heaters providing heating capability at a nominal temperature for a nominal period of time. Pellets **1108** can be pre-heated to a nominal temperature and provided to barrel **1112** through hopper **1108**. In some embodiments, pellets **1108** can be polycarbonate resin in the molten state. In some embodiments, pellets **1108** can be polycarbonate resin in the solid state, and converts into molten state in barrel **1112**. Reciprocating screw **1110** pushes pellets **1108** through barrel **1112** including the front, middle, and rear portions of barrel **1112**. As pellets **1108** move through barrel **1112**, they are heated by front, middle, and rear heaters **1114A-C** respectively and eventually pushed through nozzle **1116** into mold **1118**. Mold **1118** compresses heated pellets **1108** such that the heated pellets **1108** coagulates and forms product **1120**. In some embodiments, product **1120** can be structures of upper and lower portions of a semiconductor carrier. Product **1120** can be transferred to other fabrication facility such as a cooling tank via belt **1122**.

[0038] FIG. **12** illustrates an exemplary cooling system, according to some embodiments. The cooling system includes a cooling tank **1202** and a temperature controller **1220** coupled to cooling tank **1202** through tubes. In some embodiments, cooling tank **1202** can include tubes **1204**, hoses **1206** connected to ends of tubes **1204**, waterway baffle **1208**, and branch tubes **1210**. Other components of the cooling system may be included and are not illustrated for simplicity. Cooling tank **1202** can be filled with water and a liquid coolant can be circulated in cooling tank **1202** through tubes **1204** and hoses **1206**, and the temperature of the liquid coolant can be regulated by temperature controller **1220**. For example, liquid coolant having a nominal temperature can exit temperature controller **1220** and enter one or more branch tubes **1210** which can connect to one or more tubes **1204**. The liquid coolant circulates through cooling tank **1202** and returns to temperature controller **1220** through another one of branch tubes **1210**. Waterway baffle **1208** can be controlled by temperature controller **1220** to adjust the flow rate of coolant in cooling tank **1202**. Such configuration allows accurate control of the coolant temperature. For example, the coolant temperature can be adjusted to and hold at temperatures between about 5° C. and about 90° C. which is also the temperature of water within cooling tank **1202**. Devices **1230** such as an upper or lower portion of a semiconductor carrier can be placed in cooling tank **1202** such that the temperature of the device can be gradually cooled down to a nominal temperature. For example, device **1230** having initial temperature of about 130° C. can be placed into cooling tank **1202** having initial coolant temperature of about 70° C. Temperature controller **1220** can adjust coolant temperature to reduce gradually until room temperature over a period of time, such as about 15 min. Therefore, the temperature of device **1230** can be reduced gradually to room temperature through heat exchange with the coolant.

[0039] FIG. **13** is a flow chart of method **1300**, which describes a method for forming top and bottom portions of an apparatus (e.g., semiconductor die carrier apparatus), according to some embodiments. In some embodiments, method **1300** describes forming top and bottom portions by mold injection of polycarbonate and any suitable plastics. Polycarbonate can be a colorless and transparent amorphous thermoplastic material.

[0040] Top and bottom portions of the apparatus formed using method **1300** can exhibit exceptional electrical and physical properties. For example, top and bottom portions can exhibit electrostatic charge resistibility due to high electrical resistance. In some embodiments, high electrical resistance can be determined by applying an electrical voltage on various portions of the top and bottom portions of the apparatus and measuring the generated electrical current. For example, voltages ranging from about 10V to about 300V applied to the apparatus (e.g., about 10V to 300V and ground—or 0V—applied to areas on the top or bottom portion using electrical

resistance probing systems) can generate electrical current of about 5 μ A, which is negligible for a semiconductor element carrier.

[0041] In some embodiments, top and bottom portions also exhibit high chemical resistance due to low reaction rate to various acids and alkalis. In addition, top and bottom portions also maintains high structural integrity under various temperatures (e.g., from about 15° C. to about 35° C.) and various humidity levels (e.g., relative humidity from 25% to about 75%). In some embodiments, top and bottom portions formed using poly carbonate can provide the benefits of, among other things, heat resistant (e.g., up to 120° C.), impact resistant, flame retardant without additives, shock proof, and high refractive index.

[0042] This disclosure is not limited to this operational description of method **1300**. Rather, other operations are within the spirit and scope of the present disclosure. It is to be appreciated that additional operations may be performed. Moreover, not all operations may be needed to perform the disclosure provided herein. Further, some of the operations may be performed simultaneously, or in a different order than shown in FIG. **13**. In some implementations, one or more other operations may be performed in addition to or in place of the presently described operations. For illustrative purposes, method **1300** is described to form top and bottom portions illustrated in FIGS. **1A-8B**, however, method **1300** is not limited to these embodiments.

[0043] Method **1300** begins with operation **1310**, where a mold for forming top and bottom portions is heated, according to some embodiments. In some embodiments, a mold can be a hollow container containing a cavity configured to provide a shape to molten or hot resin material when it cools and hardens. In some embodiments, the cavity can be configured to contour a nominal shape of a top portion or a bottom portion of a semiconductor die carrier apparatus. Examples of top and bottom portions can be top and bottom portions **120** and **110** described above in FIGS. **1A-8A**. The heating process of the mold can be performed using any suitable heating method, such as plasma heating, infra-red heating, lamp heating, rapid annealing, traditional baking, other suitable annealing methods, and/or combinations thereof. In some embodiments, the mold is heated to a low temperature between about 50° C. and about 90° C. For example, the mold can be heated to a temperature between about 50° C. and about 70° C. In some embodiments, the mold can be heated to a lower temperature between about 30° C. and about 70° C. In some embodiments, the heating process can be performed for a time period between about 10 min and about 30 min. In some embodiments, the heating process can be performed using multiple heating steps performed at various temperatures. For example, the mold can be heated at a first temperature of about 50° C. for about 10 min, gradually increasing the temperature to about 70° C. for about 10 min, and gradually increasing the temperature to about 90° C. for about 10 min. In some embodiments, the mold can be heated at a first temperature of about 50° C. for about 5 min, gradually increasing the heating temperature to about 60° C. for about 10 min, and gradually increasing the temperature to about 75° C. for about 25 min. In some embodiments, the heating process can be a single-step heating process. For example, the mold can be heated at about 70° C. for about 20 min. The low heating temperature and short heating time can provide the benefit of reducing particle and stable fluidity.

[0044] In operation **1320** of method **1300**, a resin is heated into a molten state, according to some embodiments. In some embodiments, a polycarbonate resin can be used to form top or bottom portions of the apparatus. Polycarbonate resin can be a colorless and transparent amorphous thermoplastic material in a solid state at room temperature. In some embodiments, polycarbonate resin can include any suitable primary material, such as bisphenol A-phosgenepolymer 2, 2-bis (4-Hydroxyphenyl) propane, polycarbonate lexan, poly isopropylidene diphenyl carbonate, poly oxycarbonyloxy-1, 4-phenylene(1-methylethylidene)-1,4-phenylene) Poly oxycarbonyloxy-1, 4-phenylene(1-methylethylidene)-1,4-phenylene, Poly-4, 4'-isopropylidenediphenylcarbonate), polycarbonate pc, and any other suitable polycarbonate composites. Polycarbonate material can be added as additives to the primary material according to a nominal proportion. Specifically, the resin

can include a nominal volume ratio of the primary material and the polycarbonate additive. For example, the primary material can make up about 99% of the resin while the polycarbonate additive is about 1% of the resin. In some embodiments, the primary material can make up greater or equal to about 55% of the resin material. For example, the primary material can make up about 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, and 99% of the resin material, and the polycarbonate additives can form the remaining proportions of the resin, respectively. The heating temperature for converting resin from a solid state to a molten state can be in a range of about 110° C. to about 170° C. In some embodiments, depending on the composition of the resin, the heating temperature can be between about 110° C. and about 135° C. A heating process is used to provide sufficient thermal energy to induce a thermal transition of resin from a solid state to a molten state and can use any suitable heating method, such as plasma heating, infra-red heating, lamp heating, rapid annealing, traditional baking, other suitable heating methods, and/or combinations thereof. In some embodiments, the heating process can be a single-step heating process. In some embodiments, the heating process can be performed for a time period between about 2 hours and about 4.5 hours. In some embodiments, the temperature for a single-step heating process can be performed at about 150° C. for about 4.5 hours. In some embodiments, the heating process can be performed at about 170° C. for about 2 hours. In some embodiments, the temperature can be any other suitable temperature, such as 110° C., 130° C., 150° C., 170° C., or any other suitable temperature. The heating process can include multiple heating steps at various temperatures, in accordance with some embodiments. For example, the multiple heating steps can include heating steps performed at temperatures of about 130° C., 140° C., 150° C., 160° C., 170° C., or any other suitable temperature. For example, the resin can be heated at a first temperature of about 110° C. for about 30 min, gradually increasing the heating temperature to about 120° C. for about 60 min, and gradually increasing the temperature to about 135° C. for about 120 min. The heating time and temperature can be determined by the temperature and humidity of the environment. For example, processing temperature can vary from about 22° C. to about 37° C., and humidity level can vary from 30% relative humidity (“RH”) to about 85% RH. In some embodiments, a greater processing temperature and/or a greater humidity level may call for a greater heating temperature and/or heating time. However, heating temperatures above 170° C. and heating times greater than 4.5 hours under normal circumstances (e.g., at room temperature and 50% relative humidity level) may cause material degradation and reduce electrical and mechanical properties of the top or bottom portions. In some embodiments, the heating time can be adjusted based on ambient environment. For example, when the temperature and humidity levels are elevated, the heating time can be adjusted to between about 4.5 hours and about 12 hours to avoid hue changes and rubble particle formation in the resin. In some embodiments, a heating time greater than 12 hours may cause irreversible damage to the polycarbonate material and cause it to lose desirable electrical and mechanical properties, such as high electrical and heat resistivity. In some embodiments, the heating process can also include pre-heating steps, stable heating steps, cooling steps, other suitable steps, and/or combinations thereof. The resin in molten state can undergo further heating processes in the mold injection apparatus prior to being dispensed by a nozzle.

[0045] In operation **1330** of method **1300**, a front section of a barrel of the injection apparatus is heated, according to some embodiments. For example, resin can be heated to a temperature between about 170° C. and about 260° C. in a front section of the barrel. In some embodiments, the temperature of the front section can be heated to between about 155° C. and about 285° C. In some embodiments, resin can be heated to temperatures such as, for example, 170° C., 180° C., 190° C., 200° C., 210° C., 220° C., 230° C., 240° C., 250° C., 260° C., or any other suitable temperature. The heating process can include multiple heating steps at various temperatures, in accordance with some embodiments. For example, the multiple heating steps can include heating steps performed at increasing temperatures of about 180° C., 200° C., 240° C., and 260° C. As a further example, the resin can be heated at a first temperature of about 180° C. for about 2 min, gradually increasing the

heating temperature to about 220° C. for about 2 min, and gradually increasing the temperature to about 240° C. for about 1 min. In some embodiments, the resin can be heated in the front section for about 1 min and 5 min. The heating time and temperature can be determined by the temperature and humidity of the environment. Examples of a front section of a barrel can be the portion of barrel **1114** heated by one or more heaters **1114A** illustrated in FIG. **11**.

[0046] In operation **1340** of method **1300**, a middle section of a barrel of the injection apparatus is heated, according to some embodiments. For example, resin can be heated to a temperature between about 210° C. and about 280° C. in a middle section of the barrel. In some embodiments, the temperature of the middle section can be heated to between about 205° C. and about 290° C. In some embodiments, resin can be heated to temperatures such as, for example, 210° C., 220° C., 230° C., 240° C., 250° C., 260° C., 270° C., 280° C., or any other suitable temperature. The heating process can include multiple heating steps at various temperatures, in accordance with some embodiments. For example, the multiple heating steps can include heating steps performed at increasing temperatures of about 220° C., 250° C., and 270° C. As a further example, the resin can be heated at a first temperature of about 210° C. for about 1 min, gradually increasing the heating temperature to about 240° C. for about 2 min, and gradually increasing the temperature to about 260° C. for about 0.5 min. In some embodiments, the resin can be heated in the middle section for about 1 min and 5 min. The heating time and temperature can be determined by the temperature and humidity of the environment. Examples of a middle section of a barrel can be the portion of barrel **1114** heated by one or more heaters **1114B** illustrated in FIG. **11**.

[0047] In operation **1350** of method **1300**, a rear section of a barrel of the injection apparatus is heated, according to some embodiments. For example, resin can be heated to a temperature between about 220° C. and about 280° C. in a rear section of the barrel. In some embodiments, the temperature of the rear section can be heated to between about 220° C. and about 320° C. In some embodiments, resin can be heated to temperatures such as, for example, 220° C., 230° C., 240° C., 250° C., 260° C., 270° C., 280° C., or any other suitable temperature. The heating process can include multiple heating steps at various temperatures, in accordance with some embodiments. For example, the multiple heating steps can include heating steps performed at increasing temperatures of about 230° C., 250° C., and 270° C. As a further example, the resin can be heated at a first temperature of about 230° C. for about 1 min, gradually increasing the heating temperature to about 250° C. for about 1 min, and gradually increasing the temperature to about 270° C. for about 2 min. In some embodiments, the resin can be heated in the rear section for about 1 min and 5 min. The heating time and temperature can be determined by the temperature and humidity of the environment. Examples of a rear section of a barrel can be the portion of barrel **1114** heated by one or more heaters **1114C** illustrated in FIG. **11**.

[0048] In operation **1360** of method **1300**, a nozzle of a mold injection apparatus is heated, according to some embodiments. The heating process of the nozzle can be performed using any suitable heating method, such as plasma heating, infra-red heating, lamp heating, rapid annealing, traditional baking, other suitable annealing methods, and/or combinations thereof. In some embodiments, the nozzle is heated to a temperature between about 170° C. and about 280° C. In some embodiments, the heating process can be performed for a time period between about 1 min and about 5 min. In some embodiments, the heating process can be performed using multiple heating steps performed at various temperatures. For example, the mold can be heated at a first temperature of about 170° C. for about 1 min, gradually increasing the heating temperature to about 230° C. for about 2 min, and gradually increasing the temperature to about 280° C. for about 2 min. In some embodiments, the heating process can be a single-step heating process. For example, the nozzle can be heated at about 200° C. for about 3 min. Examples of a nozzle can be nozzle **1118** illustrated in FIG. **11**.

[0049] In operation **1370** of method **1300**, the heated resin in the molten state is pushed through a nozzle and into a mold, according to some embodiments. Heated resin produced by moving the

resin through various portions of a barrel of a mold injection apparatus is dispensed through the nozzle of the mold injection apparatus and into and fills the cavity of the pre-heated mold. The mold then applies pressure to the injected resin by compressing the heated resin. After a pre-determined period of time (e.g., 5-10 min), the heated resin coagulates from a molten state into a solid state that has a tangible shape contouring the interior shape of the mold cavity. The solid structure can be an upper or lower portion of the semiconductor carrier structure. The mold then releases the upper or lower portion of the semiconductor carrier structure. Examples of the mold and portions of the semiconductor carrier structure can respectively be mold **1116** and product **1120** illustrated in FIG. **11**.

[0050] In operation **1380** of method **1300**, the upper or lower portion of the semiconductor carrier structure is moved from the mold injection apparatus and gradually cooled down in a cooling tank, according to some embodiments. The cooling tank can include hoses, waterway, tubes, and controlling mechanisms such as temperature sensors and controllers. The cooling tank can circulate thermal liquid coolants such as water and include any other suitable structures for providing a gradual cooling effect. In some embodiments, upper or lower portion of the semiconductor carrier structure is cooled from about 150° C. to about room temperature (e.g., 23° C.) in about 2-5 min in the cooling tank. An example of the cooling tank can be cooling tank **1202** described above in FIG. **12**.

[0051] The present disclosure describes an apparatus for storing and transporting semiconductor elements and a method for forming the same. In some embodiments, the apparatus is a semiconductor die carrier that includes a locking mechanism, such as a latch positioned between two adjacent bumpers protruding from a front surface of the closed semiconductor die carrier. In some embodiments, the semiconductor die carrier can include a pair of partially-recessed pivotal structures positioned at a rear surface of the semiconductor die carrier opposing the latch. In some embodiments, the semiconductor die carrier can include one or more slots within the enclosed space formed by the top and bottom portions of the apparatus. The slots can include two or more grooves configured to securely hold one or more wireless communication devices. In some embodiments, the semiconductor die carrier can include silicone pad and sponges positioned in the bottom portion of the semiconductor die carrier for holding semiconductor dies having various sizes. In some embodiments, the semiconductor die carrier can include openings such as drain holes at the bottom portion to facilitate easy cleaning of the semiconductor die carrier. In some embodiments, the top and bottom portions of the semiconductor die carrier can be formed using polycarbonate that reduces the release of chemical contamination into the enclosed space and provides improved electrical and mechanical properties of the semiconductor die carrier. In some embodiments, the semiconductor carrier structure can also include imprinted barcodes (e.g., two-dimensional matrix barcodes) on the exterior to enable easy read of the information. In some embodiments, the top and bottom portions of the semiconductor die carrier is formed by polycarbonate composites using injection molding. The semiconductor die carrier formed using polycarbonate can exhibit exceptional electrical and physical properties. In some embodiments, top and bottom portions also exhibit high chemical resistance due to low reaction rate to various acids and alkalis. In addition, top and bottom portions also maintains high structure integrity under various temperatures and humidity levels. In some embodiments, top and bottom portions formed using poly carbonate can provide the benefits of, among other things, heat resistant (e.g., up to 120° C.), impact resistant, flame retardant without additives, shock proof, and high refractive index.

[0052] In some embodiments, an apparatus includes a first portion including a first front wall, a first rear wall, a bottom wall integrally coupled to the first front wall and the first rear wall, and at least one pivotal pin structure integrally coupled to and extending from the first rear wall. The apparatus also includes a second portion having a second front wall, a second rear wall, a top wall integrally coupled to the second front wall and the second rear wall, and at least one pin holder integrally coupled to and extending from the second rear wall and at an offset angle with reference

to the top wall. The at least one pivotal pin structure includes a base support connected to the first rear wall and a shaft connected to the base support, and the at least one pin holder defines an opening sized and shaped to accept the shaft. The first portion and the second portion are sized and shaped to be pivotally movable between an open configuration and a closed configuration.

[0053] In some embodiments, an apparatus for transporting semiconductor elements includes a first portion having comprising a first front wall, a first rear wall, a bottom wall integrally coupled to the first front wall and the first rear wall, and at least one pivotal pin structure integrally coupled to and extending from the first rear side wall. The first rear wall is at an offset angle with reference to the top wall. The apparatus also includes a second portion having a second front wall, a second rear wall, a top wall integrally coupled to the second front wall and the second rear wall, and at least one pin holder integrally coupled to and extending from the second rear side wall. The at least one pivotal pin structure includes a base support connected to the first rear wall and a shaft connected to the base support. The at least one pin holder defines an opening sized and shaped to accept the shaft of the at least one pivotal pin structure. The first and second rear walls are in parallel with each other in an open configuration and a closed configuration.

[0054] In some embodiments, a method for forming an apparatus for transporting semiconductor elements includes providing a mold, wherein the mold includes a cavity contouring a shape of a top portion or a bottom portion of the apparatus. The method includes heating the mold to a temperature between about 50° C. and about 90° C. The method further includes providing a polycarbonate resin in a solid state and heating the polycarbonate resin to a temperature between about 110° C. and about 135° C. such that the polycarbonate resin converts from the solid state into a molten state. The method also includes flowing the polycarbonate resin through a barrel of a mold injection apparatus, wherein the barrel is heated to a temperature between about 155° C. and about 320° C. The method further includes heating a nozzle of the mold injection apparatus to a temperature between about 190° C. and about 300° C. The method also includes injecting the polycarbonate resin into the mold through the nozzle and gradually cooling the polycarbonate resin to form the top or bottom portions of the apparatus.

[0055] It is to be appreciated that the Detailed Description section, and not the Abstract of the Disclosure section, is intended to be used to interpret the claims. The Abstract of the Disclosure section may set forth one or more but not all possible embodiments of the present disclosure as contemplated by the inventor(s), and thus, are not intended to limit the subjoined claims in any way.

[0056] The foregoing disclosure outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art will appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art will also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. An apparatus, comprising: a first portion comprising a pin holder; and a second portion comprising: a front wall; a rear wall; a bottom wall between the front wall and the rear wall; and a pivotal pin structure extending from the rear wall and configured to couple with the pin holder, wherein the pivotal pin structure comprises a base support and a shaft protruding from the base support, and wherein top surfaces of the base support and the shaft are coplanar and parallel to the bottom wall.
2. The apparatus of claim 1, further comprising a padding on the bottom wall, wherein the padding

comprises a trench configured to secure a semiconductor device.

3. The apparatus of claim 2, wherein a depth of the trench is substantially the same as a thickness of the semiconductor device.

4. The apparatus of claim 2, wherein the padding comprises silicone, sponge, or a combination thereof.

5. The apparatus of claim 1, further comprising a storage medium configured to secure a wireless communication device, wherein the wireless communication device is configured to store information about a semiconductor device to be stored in the apparatus.

6. The apparatus of claim 5, wherein the wireless communication device comprises a radio-frequency identification (RFID) device.

7. The apparatus of claim 1, wherein the bottom wall comprises an opening configured to drain a cleaning solution during a cleaning process performed on the apparatus.

8. An apparatus, comprising: a bottom portion comprising a bottom wall and a side wall coupled to the bottom wall, wherein the side wall comprises a pivotal pin structure extending from the side wall, wherein the pivotal pin structure comprises: a base support connected to the rear wall and comprising a sidewall; and a shaft protruding from the base support and comprising first, second, third, and fourth side surfaces, wherein the first and fourth side surfaces are connected to the sidewall, and wherein the second side surface is connected to the first side surface; and a top portion comprising a pin holder configured to receive the pivotal pin structure.

9. The apparatus of claim 8, wherein the pin holder is further configured to couple the shaft and to join the top and bottom portions.

10. The apparatus of claim 9, further comprising a front wall coupled to the bottom wall, wherein: the bottom portion further comprises a projection protruding from an outer side surface of the front wall; and the top portion further comprises a catch structure configured to couple the projection.

11. The apparatus of claim 10, wherein the bottom portion further comprises bumpers protruding from the outer side surface of the front wall and adjacent to the catch structure.

12. The apparatus of claim 8, further comprising a storage medium on the bottom wall, wherein the storage medium comprises a radio-frequency identification (RFID) device.

13. The apparatus of claim 12, wherein the RFID device is configured to store information of a quantity, a weight, a fabrication process, and a history record of semiconductor samples stored in the apparatus.

14. The apparatus of claim 12, wherein the RFID device is configured to collect an energy from interrogating radio waves provided by an RFID reader.

15. The apparatus of claim 12, wherein the RFID device comprises a local power source.

16. An apparatus, comprising: a front wall; a rear wall; a bottom wall coupled to the front wall and the rear wall; and a pivotal pin structure extending from the rear wall and comprising: a base support connected to the rear wall and comprising a sidewall; and a shaft protruding from the base support and comprising first, second, third, and fourth side surfaces, wherein: the first and fourth side surfaces are connected to the sidewall; the second side surface is connected to the first side surface; and the third side surface is connected to the fourth side surface.

17. The apparatus of claim 16, further comprising a storage medium on the bottom portion and adjacent to the rear wall, wherein the storage medium is configured to store a wireless communication device, wherein the wireless communication device is configured to store information about a semiconductor sample to be stored in the apparatus.

18. The apparatus of claim 17, wherein the rear wall comprises a clip configured to contour to a shape of the wireless communication device.

19. The apparatus of claim 17, wherein the bottom wall comprises an opening under the storage medium and configured as a view port to determine the presence of the wireless communication device in the storage medium.

20. The apparatus of claim 16, wherein the bottom wall comprises an opening configured to drain a cleaning solution during a cleaning process performed on the apparatus.
