

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286869

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Griffin; Phillip H. et al.

SYSTEMS AND METHODS FOR THIRD PARTY DATA PROTECTION

Abstract

Systems and methods for protecting user data received by, stored on, and/or requested by third-party computing devices include a data entry computing system on a first network node. A data entry computing system can include a processing circuit that can identify user-entered data as sensitive user data, generate a content encryption key (CEK), generate encrypted user data by encrypting the sensitive user data with the CEK, tag the encrypted user data and the CEK with a tag readable by a database server on a network node different than the data entry computing system, the tag comprising information indicative of the encrypted user data, and transmit the encrypted user data to the database server, wherein the database server excludes a private key of a key manager on a network node different than the data entry computing system.

Inventors: Griffin; Phillip H. (Raleigh, NC), Keltner; Brian L. (Norwalk, IA), McGinnis, Jr.; Ronnie F. (Rock Hill, SC), Stapleton; Jeffrey J. (O'Fallon, MO), Suarez; Luis A. (Bolivia, NC)

Applicant: Wells Fargo Bank, N.A. (San Francisco, CA)

Family ID: 1000008619640

Assignee: Wells Fargo Bank, N.A. (San Francisco, CA)

Appl. No.: 19/215149

Filed: May 21, 2025

Related U.S. Application Data

parent US continuation 17552509 20211216 parent-grant-document US 12316615 child US 19215149

parent US continuation 16426890 20190530 parent-grant-document US 11212264 child US 17552509

Publication Classification

Int. Cl.: H04L9/40 (20220101); H04L9/08 (20060101)

U.S. Cl.:

CPC H04L63/0435 (20130101); H04L9/0822 (20130101); H04L9/0841 (20130101);
H04L9/0861 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/552,509, filed Dec. 16, 2021, entitled “SYSTEMS AND METHODS FOR THIRD PARTY DATA PROTECTION,” which is a continuation of U.S. patent application Ser. No. 16/426,890, filed May 30, 2019, now U.S. Pat. No. 11,212,264, entitled “SYSTEMS AND METHODS FOR THIRD-PARTY DATA PROTECTION,” the contents of each application are hereby incorporated by reference in their entireties and for all purposes as if completely and fully set forth herein.

TECHNICAL FIELD

[0002] The present application relates generally to systems and methods for protecting data received, stored, and/or requested by a third-party. The third-party may include a cloud-based data storage provider.

BACKGROUND

[0003] Sensitive user data may be entered by a user via a data entry system and saved to a secure data archive for later retrieval and/or use. In order to maintain security of the sensitive user data in a typical implementation, the sensitive user data is sent from a data entry system to the secure data archive over a secure connection, such as a TLS connection. The secure data archive encrypts the sensitive user data and then stores the sensitive user data to its memory. In response to a data request from a data exit entity, the secure data archive decrypts the sensitive user data and then transmits the decrypted sensitive user data to the data exit system over a secure connection, such as a TLS connection.

[0004] One vulnerability of this approach to storage and retrieval of sensitive user data is that cleartext sensitive user data is visible at the start of the secure connection when the sensitive user data is sent to the secure data archive over the secure connection. Similarly, the cleartext sensitive user data is visible at the end of the secure connection when the sensitive user data is sent to the data exit system over the secure connection. Another vulnerability is that the same entity (e.g., the secure data archive) both encrypts the sensitive user data and stores the sensitive user data. Accordingly, if an unauthorized party compromises the secure data archive, the unauthorized party can use the encryption keys stored within the secure data archive to decrypt the sensitive user data. Yet another vulnerability is that the administrators of the secure data archive might not be authorized to access the sensitive user data.

SUMMARY

[0005] A first arrangement relates to a data entry computing system on a first network node. The data entry computing system can include a processing circuit that can identify user-entered data as sensitive user data, generate a content encryption key (CEK), generate encrypted user data by encrypting the sensitive user data with the CEK, tag the encrypted user data and the CEK with a tag readable by a database server on a network node different than the data entry computing system, the tag including information indicative of the encrypted user data, and transmit the encrypted user

data to the database server, where the database server excludes a private key of a key manager on a network node different than the data entry computing system.

[0006] A second arrangement relates to a data storage and translation computing system with a key manager including a processing circuit and a memory storing a public/private key pair and a public key of the data exit entity. The processing circuit can receive a first encrypted content encryption key (CEK) and information indicative of a requestor identity of a requestor, identify a public key of the requestor based on the information indicative of the requestor identity, recover a CEK by decrypting the first encrypted CEK using a private key of the key manager, generate a second encrypted CEK that is decryptable by the requestor by encrypting the CEK using the public key of the requestor, and transmit the second encrypted CEK to a database server, the database server being configured to receive encrypted user data and the first encrypted CEK from a data entry entity, restricted from the private key of the key manager, and restricted from decrypting the encrypted user data.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1 is a block diagram illustrating an environmental view of a system for protecting user data received by, stored on, and requested by one or more third-party computing systems according to some arrangements.

[0008] FIG. 2 is a block diagram illustrating another environmental view of the system of FIG. 1 according to some arrangements.

[0009] FIG. 2A is a block diagram illustrating an environmental view of a data entry entity of FIG. 2 according to some arrangements.

[0010] FIG. 2B is a block diagram illustrating an environmental view of a database server of FIG. 2 according to some arrangements.

[0011] FIG. 2C is a block diagram illustrating an environmental view of a key manager of FIG. 2 according to some arrangements.

[0012] FIG. 2D is a block diagram illustrating an environmental view of a data exit entity of FIG. 2 according to some arrangements.

[0013] FIGS. 3A-3C are flow diagrams showing processes of protecting user data that is received by, stored on, and requested by one or more third-party computing systems, according to some arrangements.

[0014] FIG. 4 is a block diagram illustrating an environmental view of a system for protecting user data received by, stored on, and requested by one or more third-party computing systems according to some arrangements.

[0015] FIG. 5 is a block diagram illustrating another environmental view of the system of FIG. 2 according to some arrangements.

[0016] FIG. 5A is a block diagram illustrating an environmental view of a data entry entity of FIG. 5 according to some arrangements.

[0017] FIG. 5B is a block diagram illustrating an environmental view of a database server of FIG. 5 according to some arrangements.

[0018] FIG. 5C is a block diagram illustrating an environmental view of a key manager of FIG. 5 according to some arrangements.

[0019] FIG. 5D is a block diagram illustrating an environmental view of a data exit entity of FIG. 5 according to some arrangements.

[0020] FIGS. 6A-6C are flow diagrams showing processes of protecting user data that is received by, stored on, and requested by one or more third-party computing systems, according to some arrangements.

DETAILED DESCRIPTION

[0021] Referring to the figures generally, various systems, methods, and apparatuses for protecting sensitive user data that is received by, stored on, displayed by and/or used by one or more third-party computing systems. As used herein, the phrase “third-party computing system” refers to a computing system that is not managed by a data owner (e.g., a user providing sensitive user data) or a data receiver (e.g., a user requesting the sensitive user data). Accordingly, the third-party computing system can include a data entry entity that receives the sensitive user data, a database server that stores the sensitive user data, and an exit entity (e.g., requestor) that requests and displays and/or uses the sensitive user data. In some arrangements, a system for protecting sensitive user data received by, stored on, requested by, displayed by, and/or used by one or more third-party computing systems can include a data entry entity, a database server, a key manager, and a requestor or data exit entity. In some arrangements, the data entry entity, the database server, the key manager, and the data exit entity can all be separate entities on separate network nodes. In some arrangements, at least two of the data entry entity, the database server, the key manager, and the data exit entity be on the same network node. For example, in some arrangements, the data entry entity is on a first network node, the database server and the key manager are on a second network node, and the data exit entity is on a third network node. While the disclosure describes the following system and method in the context of sensitive user data, in some arrangements, the following system and method may be used to protect all user data input by the user into the data entry entity.

[0022] In some arrangements, the data entry entity includes a public key of the key manager and a processing circuit. The processing circuit includes a data receiving circuit configured to receive user data and a data encryption circuit. The data encryption circuit is configured to generate a content encryption key (CEK). The CEK is a symmetric key that, in some arrangements, can be established using another symmetric key. In some arrangements, the CEK can be established using a public key cryptography (PKC) protocol, such as a Diffie-Hellman protocol or an Elliptic Curve Diffie-Hellman protocol. The data encryption circuit is configured to generate encrypted user data by encrypting the user data with the CEK, generate an encrypted CEK by encrypting the CEK with the public key of the key manager, and tag the encrypted user data and the first encrypted CEK with a tag readable by a database server without the database server having the capability to decrypt any of the encrypted user data. In some arrangements, the tag is a cleartext tag. The tag includes information indicative of the encrypted user data and can be read by the database server. The information indicative of the user data can include a type of user data and/or an identity of a user corresponding to the user data. In some arrangements, the data entry entity is configured to transmit the encrypted user data and the encrypted CEK to the database server over a secure connection. Since the encrypted user data and the encrypted CEK are both encrypted by the data entry entity, no cleartext sensitive user data is exposed at the beginning of the secure connection.

[0023] In some arrangements, the data encryption circuit is configured to undergo a key encryption key (KEK) protocol with the key manager to generate a KEK. The data encryption circuit is configured to save the KEK to the key database. In some arrangements, the KEK is a symmetric key. In some arrangements, the KEK is an asymmetric key. For example, the KEK can be a public key of the key manager. The data encryption circuit is configured to encrypt the CEK with the KEK to generate a KEK (CEK). In some arrangements, the CEK can be derived from the KEK based on a message, a unique scheme, a random scheme, and/or a rotational scheme. The cleartext tag is not encrypted with the KEK so that the database server can read the tag. In some arrangements, the KEK is a named Key. In such arrangements, the data encryption circuit is configured to generate a name for the KEK transmit the name of the KEK to the key manager with the KEK (CEK).

[0024] In some arrangements, the database server is configured to receive the encrypted user data and the encrypted CEK from the data entry entity. The database server is configured to store the encrypted user data and the encrypted CEK to its memory. The database server includes a

processing circuit including a data identification circuit configured to receive a data request message from the data exit entity. The data request message includes information indicative of the requested user data and information indicative of an identity of the data exit entity. The data identification circuit is configured to identify the requested user data and the first encrypted CEK corresponding to the requested user data based on the tag. The data identification circuit is configured to transmit the first encrypted CEK corresponding to the requested user data and the information indicative of the identity of the data exit entity to the key manager. The data identification circuit is configured to receive a second encrypted CEK corresponding to the requested user data. The second encrypted CEK can be decrypted by the data exit entity. The data identification circuit is configured to transmit the encrypted user data and the second encrypted CEK to the data exit entity. The database server excludes the private key of the key manager and cannot decrypt the encrypted user data. As used herein, “excludes” means omits, restricts, segregates, does not generate, does not receive, does not store (e.g., write to non-volatile memory) or does not read to volatile memory. Therefore, an administrator or users of the database server cannot decrypt the encrypted user data. This allows the database server to be administered by an entity that might not be authorized to access the sensitive user data. Furthermore, even if an attacker compromises the database server, the attacker cannot decrypt the encrypted user data.

[0025] In some arrangements, the key manager includes a key database and processing circuit including a translation circuit. The key database includes a public/private key pair and certificates corresponding to each data exit entity authorized to request user data. As used herein, the term “public/private key pair” refers to an asymmetric key pair. The private key of any device described herein is not shared or stored outside of the device corresponding to the private key (e.g., the private key never leaves its secured cryptographic boundary). Each of the data exit entity certificates includes a public key of the respective data exit entity. In some arrangements, the key manager is a hardware security module (HSM). In some arrangements, the key manager is communicably and operatively coupled with an HSM. In such arrangements, the key manager may have an onboard HSM that is installed as a cryptocard, the key manager may be physically coupled to the HSM, and/or the key manager may be in communication with the HSM over a network.

[0026] The translation circuit is configured to receive the first encrypted CEK and the information indicative of the identity of the data exit entity requesting the encrypted user data, identify the public key of the data exit entity based on the information indicative of the identity of the data exit entity, and recover the cleartext CEK by decrypting the first encrypted CEK using the private key of the key manager. The translation circuit is configured to generate a second CEK that can be decrypted by the data exit entity by encrypting the CEK using the public key of the data exit entity that requested the encrypted user data. The second CEK can be decrypted by the data exit entity using its private key to recover the cleartext CEK. The translation circuit is then configured to transmit the second CEK to the database server. The key manager excludes the encrypted user data. No encrypted user data is sent to the key manager, read into volatile memory on the key manager, or stored on the key manager. Therefore, an administrator of the key manager cannot decrypt the encrypted user data. Furthermore, even if an unauthorized party compromises the key manager, the unauthorized party cannot obtain and/or decrypt the encrypted user data.

[0027] In some arrangements, the database server and the key manager are on the same network node. In some arrangements, the key manager, the HSM and the database server can be hosted in the cloud.

[0028] In some arrangements, the requestor or data exit entity includes a key database and a processing circuit. The processing circuit includes a data request circuit and a data decryption circuit. The key database includes a public/private key pair and a certificate of the key manager. The certificate of the key manager includes the public key of the key manager. The message generation circuit is configured to receive a user data request input by a user, generate a data request message including information indicative of the requested user data and information

indicative of the identity of the database server, and transmit the data request message to the database server. The data decryption circuit is configured to receive the encrypted user data and the second encrypted CEK, recover the cleartext CEK by decrypting the second CEK with the private key of the data exit entity, and recover the sensitive user data by decrypting the encrypted user data with the CEK.

[0029] Referring now to FIGS. 1-2, an environmental view of a system **100** for protecting user data that is entered into a third-party data entry device, sent to and stored on a third-party database server, and displayed and/or used by a third-party data exit computing system is shown. As used herein, the phrase “third-party computing system” means a computing system that is not managed by a data owner (e.g., a user providing sensitive user data) or a data receiver (e.g., a user requesting the sensitive user data). The sensitive user data can include identity information such as a social security number, account number, date of birth, biometric data (e.g., a stored image of a fingerprint, retina, or other body part to be used to authenticate the user) and so on. As shown in FIGS. 1-2, the system **100** includes one or more data entry entities **104**, a database server **108**, a key manager **112**, and one or more requestors or data exit entities **116** connected by a network **120**. For example, the system **100** illustrated in FIG. 1 includes four data entry entities **104A-104D** and four data exit entities **116A-116D** that are in communication with the database server **108** over the network **120**. In other arrangements, the system **100** can include a different number of data entry entities **104** and data exit entities **116**. While the data entry entity **104**, the database server **108**, the key manager **112**, and the data exit entity **116** are shown as being on separate network nodes in FIGS. 1-2, in some arrangements, the database server **108** and the key manager **112** can be on the same network node.

[0030] The data entry entity **104** is a computing system that includes a software program that requests that a user enter sensitive user data to be stored by the database server **108**. The data entry entity **104** may be administered by a third-party. The data entry entity **104** can include a web browser that includes a software application that requests that the user enter sensitive user data to be stored by the third-party data storage system **100**. In other arrangements, the data entry entity **104** can include a local software application that requests that the user enter sensitive data to be stored by the third-party data storage system **100**. In some arrangements, the data entry entity **104** is on a single network node. As shown in FIG. 2A, in the illustrated arrangement, the data entry entity **104** includes a user input/output device **204**, a network interface **208**, a memory **212**, and a processing circuit **214**. The processing circuit **214** includes a data receiving circuit **216**, a data encryption circuit **220**, and an authentication circuit **224**. The user input/output device **204** can include an input device or component of the user input/output device **204** that allows the user to provide information to the data entry entity **104**, and may include, for example, a mechanical keyboard, a touchscreen, a microphone, a camera, a fingerprint scanner, any user input device that is configured to be engaged with the data entry entity **104** via a USB, serial cable, Ethernet cable, and so on. An output device or component of the user input/output device **204** allows the user to receive information from the data entry entity **104**, and may include, for example, a digital display, a speaker, illuminating icons, LEDs, and so on.

[0031] The network interface **208** of the data entry entity **104** is adapted for and configured to establish a communication session via the network **120** with the other components of the system **100**. As used herein, a “network interface” may include any of a cellular transceiver (Code Division Multiple Access (CDMA), Global System for Mobile Communications (GSM), Long-Term Evolution (LTE), etc.), a wireless network transceiver (e.g., 802.11X, ZigBee, Bluetooth, etc.), and a combination thereof (e.g., both a cellular transceiver and a Bluetooth transceiver). As shown in FIG. 2A, the memory **212** is communicably and operatively coupled with the other components of the data entry entity **104**. The memory **212** includes a key database **228**. The key database **228** is configured to retrievably store a certificate **222** of the key manager **112** that includes a public key **226** of the key manager **112**. In some arrangements, the certificates described herein can be X.509

certificates.

[0032] The data receiving circuit **216** is configured to prompt or request the user to enter user data. For example, the data receiving circuit **216** can display the prompts or requests on a screen of the user input/output device **204**, generate audio inputs, etc. using one or more output devices of the output component of the user input/output device **204**. The prompts or requests displayed on a screen can have text entry inputs for receiving data entered by the user. The text entry inputs that are configured to receive sensitive user data can be tagged to indicate that the data entered by the user is sensitive user data. In arrangements in which the prompt or request is audio, the question can include a tag indicating that user data received in response to the prompt or request is sensitive user data.

[0033] The data encryption circuit **220** is configured to recognize one or more pieces of the user data as being sensitive user data. In some arrangements, data entry interfaces (e.g., data entry windows on a website application or a software program) can be tagged as sensitive data entry windows that receive sensitive user data, as described above. The data encryption circuit **220** is configured to generate a content encryption key (CEK) in response to determining that user data is sensitive user data. The CEK is a symmetric key. The data encryption circuit **220** is configured to generate a different CEK for each piece of sensitive user data input by the user. The data encryption circuit **220** is configured to generate encrypted user data by encrypting the sensitive user data with the CEK. The data encryption circuit **220** is configured to generate an encrypted CEK by encrypting the CEK with the public key **226** of the key manager **112**. For example, the data encryption circuit **220** can encrypt the CEK using CMS-envelope data with public key **226** of the key manager **112** from the key manager certificate **222**. Encrypting the sensitive user data with the CEK and encrypting the CEK with the public key **226** of the key manager **112** increases the speed of the encryption process since encryption with symmetric keys is faster than encryption with asymmetric keys. Since the CEK is encrypted using the public key **226** of the key manager **112**, access to the encrypted user data still is protected by the strength of asymmetric encryption.

[0034] In some arrangements, the data encryption circuit **220** is configured to generate a CMS SignedData message wrapper around the encrypted user data and the encrypted CEK, which can provide the functionality of nested SignedData (EnvelopedData) messages. In such an arrangement, the key database **228** includes a public/private key pair of the data entry entity **104** and a certificate of the database server **108**. The certificate of the database server **108** includes a public key of the database server **108**. Such arrangements do not require a secure connection, such as the secure tunnel provided by TLS.

[0035] In some arrangements, the data encryption circuit **220** is configured to generate a CMS SigncryptData message wrapper around the encrypted user data and the encrypted CEK, which can provide the functionality of nested SignedData (EnvelopedData) messages. In such an arrangement, the key database **228** includes a public/private key pair of the data entry entity **104** and a certificate of the database server **108**. The certificate of the database server **108** includes a public key of the database server **108**. Such arrangements do not require a secure connection, such as the secure tunnel provided by TLS.

[0036] In some arrangements, the data encryption circuit **220** is configured to undergo a key encryption key (KEK) protocol with the key manager **112** to generate a KEK with the key manager **112**. The data encryption circuit **220** is configured to save the KEK to the key database **228**. In some arrangements, the data encryption circuit **220** uses the same KEK for all of the CEKs that can be translated by the key manager **112**. In some arrangements, the KEK is a symmetric key. In some arrangements, the KEK is an asymmetric key. For example, the KEK can be the public key **226** of the key manager **112**. The data encryption circuit **220** is configured to encrypt the CEK with the KEK to generate a KEK (CEK). In such arrangements, the cleartext tag is not encrypted with the KEK so that the database server **108** can read the tag. In some arrangements, the CEK can be derived from the KEK based on a message, a unique scheme, a random scheme, and/or a rotational

scheme. In some arrangements, the KEK is a named Key. In such arrangements, the data encryption circuit **220** is configured to generate a name for the KEK and transmit the name of the KEK to the key manager with the KEK (CEK).

[0037] The data encryption circuit **220** is configured to tag both the encrypted user data and the encrypted CEK with a tag that is readable by the database server **108**. The tag can include information indicative of the encrypted user data. The information indicative of the encrypted user data can include information indicative of a type of user data (e.g., social security number, account number, address, birth date, biometric, etc.) and/or information indicative of an identity of the user (e.g., a name, a reference number, etc.). In some arrangements, the data encryption circuit **220** is configured to transmit the encrypted user data and the encrypted CEK to the database server **108** over a secure connection. Since the encrypted user data and the encrypted CEK are sent over the secure connection, the cleartext sensitive user data and the cleartext CEK are not visible at the entrance and exit of the secure connection. In some arrangements, the secure connection can be a TLS connection. The data encryption circuit **220** is configured to destroy the CEK and the user data in response to receiving a message from the database server **108** indicating that the encrypted user data and the encrypted CEK have been received by the database server **108**. In arrangements which the encrypted user data and the encrypted CEK are wrapped with a CMS SignedData message wrapper or in which the encrypted user data and the encrypted CEK are wrapped with a CMS SigncryptData message wrapper, the encrypted user data and the encrypted CEK do not need to be transmitted over a secure connection.

[0038] In some arrangements, the data encryption circuit **220** can receive more than one piece of sensitive user data. When more than one piece of sensitive user data is received, the data encryption circuit **220** is configured to generate a new CEK for each piece of sensitive user data as described above. The data encryption circuit **220** is configured to generate encrypted user data from each piece of sensitive user data by encrypting each piece of sensitive user data with the CEK generated for that piece of sensitive user data. The data encryption circuit **220** is configured to generate a tag for each piece of encrypted user data and each CEK corresponding to each piece of encrypted user data as described above.

[0039] The authentication circuit **224** is configured to validate the key manager certificate **222** that is stored in the key database **228**. For example, the authentication circuit **224** can transmit the key manager certificate **222** to the certificate authority that issued the key manager certificate **222** and ask the certificate authority to confirm that the key manager certificate **222** is valid. In some arrangements, the authentication circuit **224** validates the key manager certificate **222** every time encrypted user data and an encrypted CEK is sent to the database server **108**. In some arrangements, the authentication circuit **224** validates the key manager certificate **222** based on a predefined time period (e.g., hourly). In some arrangements, the authentication circuit **224** validates the key manager certificate **222** every time user data is received by the data receiving circuit **216**. The authentication circuit **224** is configured to prevent users from entering sensitive user data in response to determining that the key manager certificate **222** is expired or has been revoked. Accordingly, only data entry entities **104** having valid key manager certificates **222** can receive the encrypted user data. The authentication circuit **224** is configured to read an expiration date of the key manager certificate **222** from the key manager certificate **222**. The authentication circuit **224** is configured to notify an administrator of the data entry entity **104** in response to determining that the key manager certificate **222** will expire in less than a predefined time period. In some arrangements, the predefined time period may be ninety days. In arrangements in which the data encryption circuit **220** is configured to generate a CMS signed Data message wrapper around the encrypted user data or the data encryption circuit **220** is configured to generate a CMS SigncryptData message wrapper around the encrypted user data and the encrypted CEK, the authentication circuit **224** is configured to validate the certificate of the database server **108** as described above with respect to the key manager certificate **222**.

[0040] The database server **108** is a secure computing system that is configured to store encrypted user data received from one or more data entry entities **104** connected to the network **120**. The database server **108** may be administered by a third-party. In some arrangements, the database server **108** is hosted in the cloud. As shown in FIG. 2B, the database server **108** includes a network interface **232**, a memory **236**, and a processing circuit **238**. The processing circuit **238** includes a data identification circuit **240**. The network interface **232** is configured to establish a communication session via the network **120**. The memory **236** is communicably and operatively coupled with the other components of the database server **108**. The memory **236** includes a user information database **244** and a data request log **248**. The user information database **244** includes encrypted user data and encrypted CEKs that correspond to the encrypted user data. The data request log **248** includes list of information indicative of the encrypted user data requested by the data exit entity **116** and information indicative of the identity of the data exit entity **116**. The memory **236** excludes the certificate **222** of the key manager **112**. The memory **236** excludes a private key **249** of the key manager **112**. The certificate **222** of the key manager **112** and/or the private key **249** of the key manager **112** are not stored to the memory **236**. Accordingly, the database server **108** and/or the administrators of the database server **108** cannot decrypt the encrypted CEKs corresponding to the encrypted user data. The database server **108** and/or the administrators of the database server **108** therefore cannot decrypt the encrypted user data to access cleartext sensitive user data. Furthermore, unauthorized parties cannot access the sensitive user data even if the unauthorized parties gain access to the database server **108**. Stated another way, the database server **108** does not have access to the private keys **249** stored in the key manager **112**, cleartext CEKs, and cleartext sensitive user data. This allows the database server **108** to be administered by an entity that might not be authorized to access the sensitive user data.

[0041] The database server **108** is configured to receive the encrypted user data and the encrypted CEK corresponding to the encrypted user data from the data entry entity **104**. Stated another way, the data entry entity **104** transmits encrypted data, rather than cleartext data, to the database server **108**. Furthermore, cleartext sensitive user data and the cleartext CEK are not available to the database server **108**. The database server **108** is configured to save the encrypted user data and the encrypted CEK to the user information database **244** in the memory **236**. The database server **108** is configured to transmit a message to the data entry entity **104** to confirm that the encrypted user data and the encrypted CEK have been received.

[0042] The data identification circuit **240** is configured to receive a data request message from the data exit entity **116**. The data request message can include information indicative of the requested user data and information indicative of an identity of the data exit entity **116**. The information indicative of the requested user data can include information indicative of an identity of the user corresponding to the encrypted user data, information indicative of a type of encrypted user data, etc. The information indicative of the identity of the data exit entity **116** can include an IP address of the data exit entity **116**, an IMEI number of the data exit entity **116**, an instance of a software application running on the data exit entity **116**, etc. The data identification circuit **240** is configured to identify the encrypted user data requested by the data exit entity **116** based on the tag. For example, the data identification circuit **240** can read the information indicative of the requested user data from the data request message and compare the information indicative of the requested user data to the information indicative of the encrypted user data in each of the tags to identify a match. During this process, the data identification circuit **240** does not decrypt the encrypted user data. As mentioned above, the tags are cleartext so that the data identification circuit **240** can read the tags. The data identification circuit **240** is configured to retrieve the encrypted CEK corresponding to the requested user data. The data identification circuit **240** is configured to transmit the encrypted CEK corresponding to requested user data and the information indicative of the identity of the data exit entity **116** to the key manager **112**. The data identification circuit **240** is configured to log information indicative of each piece of user data requested and the data exit entity

116 or data exit entities **116** requesting each piece of user data in the data request log **248** stored in the memory **236**. In some arrangements, the information indicative of each piece of user data requested can include one or more pieces indicative of the encrypted user data that is included in the tag.

[0043] In some arrangements, the data identification circuit **240** is configured to receive a second encrypted CEK and the information indicative of the identity of the data exit entity **116** from the key manager **112**. The second encrypted CEK can be decrypted by the data exit entity **116** to recover the cleartext CEK, but the second encrypted CEK cannot be decrypted by the database server **108**. The second encrypted CEK includes the tag readable by the database server **108**. The data identification circuit **240** is configured to retrieve the encrypted user data including the same tag as the second encrypted CEK. The data identification circuit **240** is configured to transmit the encrypted user data and the second CEK to the data exit entity **116**. In some arrangements, the data identification circuit **240** is configured to transmit the encrypted user data and the second encrypted CEK to the data exit entity **116** over a secure connection. Since the encrypted user data and the second encrypted CEK are both encrypted, no cleartext sensitive user data is present at the entrance or exit of the secure connection. The data identification circuit **240** handles second, third, etc. data request messages from the data exit entity **116** or other data exit entities **116** as described above.

[0044] In some arrangements, the data identification circuit **240** is configured to transmit one or more pieces of encrypted user data to one or more of the data exit entities **116** according to a predefined schedule. In such arrangements, the data exit entity **116** is configured to send a message to the database server **108** that establishes the predefined schedule and an identity of one or more data entry entities **104**, information indicative of one or more types of encrypted user data, and/or one pieces of information indicative of an identity of a user to send to the data exit entity **116** according to the predefined schedule. In some arrangements, the data exit entity **116** may send this message to the database server **108** as metadata when the data exit entity **116** sends its certificate **259** to the database server **108**. In other arrangements, the data exit entity **116** may send this message to the database server **108** separately from the certificate **259**. The data identification circuit **240** is configured to identify the encrypted user data based on the tag and send the encrypted CEK corresponding to the encrypted user data to the key manager **112** as described above.

[0045] In some arrangements, the data entry entity **104** is configured to transmit instructions that include information indicative of one or more data exit entities **116** and that command the database server **108** to send the encrypted user data to one or more data exit entities **116**. In some arrangements, the instructions are included in the tag. In other arrangements, the instructions are sent with the encrypted user data in another manner, such as a message wrapper such as a CMS SignedData message wrapper or a CMS SincryptedData message wrapper. The data identification circuit **240** is configured to identify the instructions sent with the encrypted user data and send the encrypted CEK corresponding to the encrypted user data and the information indicative of the one or more data exit entities **116** to the key manager **112** as described above.

[0046] In arrangements in which the database server **108** is configured to send and/or receive messages that include CMS SignedData message wrappers or CMS SincryptedData message wrappers, the database server **108** further includes an encryption circuit **242** and an authentication circuit **246**. The memory **236** of the database server **108** includes a key database **250** including a public/private key pair of the database server **108**, a certificate (not shown) of each of the one or more data entry entities **104**, and a certificate **259** of each of the one or more the data exit entities **116**. The certificate of the data entry entity **104** includes a public key (not shown) of the data entry entity **104**. The certificate **259** of the data exit entity **116** includes a public key **261** of the data exit entity **116**. The authentication circuit **246** is similar to the authentication circuit **224** described above with respect to the data entry entity **104** and is configured to validate the certificate of the data entry entity **104** and the certificate **259** of the data exit entity **116** as described above with respect to the key manager certificate **222**. However, in response to determining that the certificate

of the data entry entity **104** or the certificate **259** of the data exit entity **116** is expired or has been revoked, the authentication circuit **246** is configured to prevent decryption of incoming messages or encryption of outgoing messages using public keys contained in the expired or revoked certificates. [0047] In arrangements in which the encryption circuit **242** is configured to receive incoming messages including CMS SignedData message wrappers, the encryption circuit **242** is configured to verify the digital signature and decrypt the CMS SignedData message wrapper using the public key of the data entry entity **104** and the private key of the database server **108**, respectively. In arrangements in which the encryption circuit **242** is configured to send messages including CMS SignedData message wrappers, the encryption circuit **242** is configured to wrap the encrypted user data and the second encrypted CEK with a CMS SignedData message wrapper using the public key **261** of the data exit entity **116** that will receive the message. The encryption circuit **242** is configured to generate a digital signature using the private key of the database server **108**. In arrangements in which the encrypted user data and the encrypted CEK are wrapped with a CMS SignedData message wrapper, the encrypted user data and the encrypted CEK do not need to be transmitted over a secure connection.

[0048] In arrangements in which the encryption circuit **242** is configured to receive messages including CMS SigncryptData message wrappers, the encryption circuit **242** is configured to verify the digital signature and decrypt the CMS SignedData message wrapper using the public key of the data entry entity **104** and the private key of the database server **108**, respectively. In arrangements in which the encryption circuit **242** is configured to send messages including CMS SigncryptData message wrappers, the encryption circuit **242** is configured to wrap the encrypted user data and the second encrypted CEK with a CMS SigncryptData message wrapper using the public key **261** of the data exit entity **116** that will receive the message and the private key of the database server **108**. In arrangements in which the encrypted user data and the encrypted CEK are wrapped with a CMS SigncryptData message wrapper, the encrypted user data and the encrypted CEK do not need to be transmitted over a secure connection.

[0049] In some arrangements, the data request message can include one or more pieces of requested user data. In such an arrangement, the data identification circuit **240** can identify each piece of encrypted user data corresponding to each piece of requested user data based on the information indicative of the encrypted user data included in the tags. The data identification circuit **240** can retrieve the encrypted CEKs corresponding to each piece of requested user data and transmit them to the key manager **112** with the information indicative of the identity of the data exit entity **116**. In some arrangements, the data request message can include the information indicative of one or more data exit entities **116** and one or more pieces of requested user data. In such arrangements, the data identification circuit **240** can retrieve the one or more CEKs corresponding to the one or more pieces of requested user data and transmit the one or more CEKs and the information indicative of the one or more data exit entities **116** to the key manager **112**.

[0050] In some arrangements, the data request message can include information indicative of the requested user data and information indicative of an identity of one or more data exit entities **116** requesting the user data. In arrangements in which the data request message indicates that more than one data exit entity **116** is requesting the user data, the data identification circuit **240** is configured to transmit the encrypted CEK corresponding to the requested user data and the information indicative of the identity of the each of the data exit entities **116** requesting the user data to the key manager **112**. The data identification circuit **240** is configured to retrieve the second encrypted CEKs from the key manager **112** corresponding to each of the data exit entities **116** based on the information indicative of the identity of each of the data exit entities **116**. The data identification circuit **240** is configured to transmit the encrypted user data and the second encrypted CEK corresponding to each respective data exit entity **116** to each of the data exit entities **116**. In some arrangements, the data identification circuit **240** transmits the encrypted user data and the second encrypted CEK over a secure connection. Since the encrypted user data and the second

encrypted CEK are both encrypted, no cleartext sensitive user data is exposed at the entrance or exit of the secure connection. In arrangements which the encrypted user data and the encrypted CEK are wrapped with a CMS SignedData message wrapper or in which the encrypted user data and the encrypted CEK are wrapped with a CMS SigncryptData message wrapper, the encrypted user data and the encrypted CEK do not need to be transmitted over a secure connection.

[0051] The key manager **112** includes a network interface **252**, a memory **256**, and a processing circuit **258**. In some arrangements, the key manager **112** is a hardware security module (HSM). In some arrangements, the key manager **112** is communicably and operatively coupled with a HSM. In such arrangements, the key manager **112** may have an onboard HSM that is installed as a cryptocard, the key manager **112** may be physically coupled to an HSM, and/or the key manager **112** may be in communication with an HSM over the network **120**.

[0052] The processing circuit **258** includes a translation circuit **260** and an authentication circuit **264**. The network interface **252** is configured to establish a communication session via the network **120**. As shown in FIG. 2C, the memory **256** is communicably and operatively coupled with the other components of the key manager **112**. The memory **256** includes a key database **268** and a CEK translation log **272**. The key database **268** includes a public/private key pair of the key manager **112** and a certificate **259** for each data exit entity **116** authorized to receive user data from the database server **108**. The certificates **259** include public keys **261** for each of the data exit entities **116** authorized to receive user data from the database server **108**. For example, in the arrangement of FIG. 1, the system **100** illustrates a certificate **259A-259D** corresponding to each of the data exit entities **116A-116D**, respectively. Each of the certificates **259A-259D** includes the public key **261A-261D**, respectively. Therefore, only data exit entities **116** having valid certificates **259** can receive encrypted user data from the database server **108**. The CEK translation log **272** includes a list of the encrypted CEKs translated by the key manager **112** and the data exit entity **116** or data exit entities **116** requesting each translated CEK. The memory **256** excludes the encrypted user data. Furthermore, the encrypted user data is never sent to the key manager **112**. Therefore, the encrypted user data is not read into a volatile memory of the key manager **112** and is not stored in the memory **256**. Since encrypted user data is not sent to the key manager **112**, the key manager **112** cannot decrypt the encrypted user data to recover the cleartext sensitive user data. Since the key manager **112** does not decrypt and then re-encrypt the encrypted user data with the public key **261** of the data exit entity **116**, the key manager **112** does not transmit or receive any encrypted user data. Therefore, an administrator of the key manager **112** cannot access the encrypted user data, let alone decrypt the encrypted user data to recover the cleartext sensitive user data. Accordingly, the encrypted user data is managed by a different entity (e.g., the database server **108**) than the key manager **112**. Furthermore, if an unauthorized party gains access to the key manager **112**, the unauthorized party cannot access the encrypted user data let alone decrypt the encrypted user data to recover the cleartext sensitive user data.

[0053] The translation circuit **260** is configured to receive the encrypted CEK and the information indicative of the identity of the data exit entity **116** from the database server **108**. The translation circuit **260** is configured to recover the cleartext CEK by decrypting the encrypted CEK with the public key **226** of the key manager **112**. The translation circuit **260** is configured to retrieve the certificate **259** and/or the public key **261** corresponding to the data exit entity **116** based on the information indicative of the identity of the data exit entity **116**. The translation circuit **260** is configured to generate a second encrypted CEK by encrypting the cleartext CEK with the public key **261** of the data exit entity **116** from the certificate **259** corresponding to the data exit entity **116** requesting the encrypted user data. As used herein, the phrase “CEK translation” refers to the process of regenerating the cleartext CEK by decrypting the encrypted CEK with the public key **226** of the key manager **112** and encrypting the cleartext CEK with the public key **261** of the data exit entity **116**. The translation circuit **260** is configured to transmit the second encrypted CEK and the information indicative of the identity of the data exit entity **116** to the database server **108**.

[0054] In some arrangements, the translation circuit **260** can receive one or more encrypted CEKs and information indicative of one or more data exit entities **116**. In such arrangements, the translation circuit **260** is configured to retrieve the certificates **259** corresponding to each of the one or more data exit entities **116**. The translation circuit **260** is configured to encrypt the one or more cleartext CEKs with the public keys **261** of each of the data exit entities **116** that have requested the encrypted user data corresponding to the one or more CEKs. The translation circuit **260** is configured to log each CEK translation request in the CEK translation log **272**. For example, the translation circuit **260** is configured to save a record of each CEK translated and the data exit entity **116** or data exit entities **116** requesting the translation in the CEK translation log **272**. In some arrangements, the translation circuit **260** is configured to log CEK translation requests from data exit entities **116** having invalid certificates **259** in the CEK translation log **272**.

[0055] In arrangements in which KEKs are used to encrypt the CEK, the translation circuit **260** is configured to undergo a KEK generation protocol with the data entry entity **104** to generate a KEK with the data entry entity **104**. The translation circuit **260** is configured to save the KEK established with the data entry entity **104** to the key database **250**. In arrangements that include one or more data entry entities **104**, the translation circuit **260** is configured to generate a KEK with each of the data entry entities **104** and save each of the KEKs to the key database **250**. The translation circuit is also configured to undergo a KEK generation protocol with the data exit entity **116** to generate a KEK with the data exit entity **116**. The translation circuit **260** is configured to save the KEK established with the data exit entity **116** to the key database **250**. In arrangements that include one or more data exit entities **116**, the translation circuit **260** is configured to generate a KEK with each of the data exit entities **116** and save each of the KEKs to the key database **250**.

[0056] In arrangements that include KEKs, the key manager **112** receives the KEK (CEK) encrypted with the public key **226** of the key manager **112**. The translation circuit **260** is configured to decrypt the KEK (CEK) using the private key **259** of the key manager **112**. The translation circuit **260** is configured to recover the cleartext CEK by decrypting the KEK (CEK) using the KEK corresponding to the data entry entity **104** that generated the CEK. The translation circuit **260** then retrieves the KEK corresponding to the data exit entity **116** requesting the encrypted user data based on the information indicative of the identity of the data exit entity **116**. The translation circuit **260** encrypts the cleartext CEK with the KEK generated with the data exit entity **116** requesting the encrypted user data to generate a second KEK (CEK). The translation circuit **260** then encrypts the second KEK (CEK) with the public key **261** of the data exit entity **116** requesting the encrypted user data to generate the second encrypted CEK.

[0057] The authentication circuit **264** is configured to validate the one or more data exit entity certificates **259** stored in the key database **268**. For example, the authentication circuit **264** can transmit the one or more data exit entity certificates **259** to the certificate authority that issued each of the one or more data exit entity certificates **259** and ask the certificate authority to confirm that each of the one or more data exit entity certificates **259** is valid. In some arrangements, the authentication circuit **264** validates the certificate of a particular data exit entity **116** every time the data exit entity **116** requests translation of one or more encrypted CEKs. In some arrangements, the authentication circuit **264** validates the one or more data exit entity certificates **259** based on a predefined time period (e.g., hourly). The authentication circuit **264** is configured to prevent translation of the cleartext CEK in response to determining that the data exit entity certificate **259** of the data exit entity **116** requesting the encrypted user data is expired or has been revoked. The authentication circuit **264** is configured to read an expiration date of the one or more data exit entity certificates **259**. Accordingly, only data exit entities **116** having valid certificates **259** can receive encrypted user data and the encrypted second CEK corresponding to the encrypted user data from the database server **108**. The authentication circuit **264** is configured to notify an administrator of the key manager **112** in response to determining that one or more of the data exit entity certificates **259** will expire in less than a predefined time period. In some arrangements, the

predefined time period may be ninety days.

[0058] In some arrangements, the key manager **112** is a hardware security module (HSM). In some arrangements, the key manager **112** and the database server **108** are on the same network node. In some arrangements, the key manager **112** and the database server **108** are on the same network node and the network node is hosted in the cloud. In some arrangements, the key manager **112** and the database server **108** are on different network nodes.

[0059] Although one database server **108** is discussed in the arrangement described above, in some arrangements, the third-party data storage system **100** can include a plurality of database servers **108** and the key manager **112** can be configured to communicate with the plurality of database servers **108**. In some arrangements, the database servers **108** can each communicate with different groups of data entry entities **104** and different groups of data exit entities **116**. In such arrangements, the key manager **112** may use a different public/private key pair and have a separate certificate for each database server **108**.

[0060] In other arrangements, the third-party data storage system **100** can include a plurality of database servers **108** and a plurality of key managers **112**. By way of non-limiting example, in some arrangements, the plurality of database servers **108** can include a first database server and a second database server and the plurality of key managers **112** can include a first key manager and a second key manager. In such an arrangement, the second database server can request user data from the first database server using a data request message similar to the data request message described above with respect to the data exit entity **116**. The first database server can retrieve the encrypted CEK corresponding to the requested user data to the first key manager. The first key manager can translate the encrypted CEK as described above using the public key of the second key manager to generate a second encrypted CEK that can be decrypted by the second key manager. The first database server can then send the encrypted user data and the second encrypted CEK to the second database server as described above. In other arrangements, the plurality of database servers can include a different number of database servers and the plurality of key managers can include a different number of key managers that can send and receive encrypted user and encrypted CEKs to and from each other. In some arrangements, the second database server communicates with the one or more data exit entities **116** as described below and the second key manager translates the second encrypted CEK to a third encrypted CEK that can be decrypted by the one or more data exit entities **116** as described above with respect to the first key manager.

[0061] The requestor or data exit entity **116** can be a computing system that includes a software program that includes a user input/output device that allows a user to request sensitive user data stored in a third-party data storage system **100**, such as the database server **108**. For example, the user can request various types of user data corresponding to various users. In some arrangements, the data exit entity **116** is on a single network node. The data exit entity **116** may be administered by a third-party. The data exit entity **116** can be a web browser that includes a software application that allows a user to request sensitive user data stored by the database server **108**. In other arrangements, the data exit entity **116** can be a computing system that includes a local software application that allows a user to request sensitive user data stored by the database server **108**. In the illustrated arrangement, the data exit entity **116** includes a user input/output device **276**, a network interface **280**, a memory **284**, and a processing circuit **286**. The processing circuit **286** includes a message generation circuit **288**, a data decryption circuit **292**, and an authentication circuit **296**.

[0062] The user input/output device **276** can include an input device or component of the user input/output device **276** that allows the user to provide information to the data exit entity **116**, and may include, for example, a mechanical keyboard, a touchscreen, a microphone, a camera, a fingerprint scanner, any user input device engageable with the data exit entity **116** via a USB, serial cable, Ethernet cable, and so on. The user input/output device **276** can include an output device or component that allows the user to receive information from the data exit entity **116**, and may include, for example, a digital display, a speaker, illuminating icons, LEDs, and so on.

[0063] The network interface **280** of the data exit entity **116** is adapted for and configured to establish a communication session via the network **120** with the other components of the system **100**. As shown in FIG. 2D, the memory **284** is communicably and operatively coupled with the other components of the data exit entity **116**. The memory **284** includes a key database **298**. The key database **298** includes the certificate **259** of the data exit entity **116** and a public/private key pair of the data exit entity **116**.

[0064] The message generation circuit **288** is configured to receive a request for sensitive user data via the user input/output device **276**. For example, the message generation circuit **288** can provide a user input interface that allows a user to enter a request for one or more pieces of sensitive user data. The message generation circuit **288** may display the prompts or requests on screen, generate audio inputs, etc. using one or more output devices of the output component of the user input/output device **276**. The message generation circuit **288** is configured to determine information indicative of the requested user data based on the request for sensitive user data input by the user. The information indicative of the requested user data can include information indicative of a type of user data (e.g., social security number, account number, address, birth date, biometric, etc.) and/or information indicative of an identity of the user (e.g., a name, a reference number, etc.). The message generation circuit **288** is configured to generate a data request message including the information indicative of the requested user data and information indicative of the identity of the data exit entity **116**. The information indicative of the identity of the data exit entity **116** (e.g., the requestor identity) can include an IP address, an IMEI number, an instance of a software application running on the data exit entity **116** or a browser running on the data exit entity **116**, etc. In some arrangements, the message generation circuit **288** is configured to transmit the data request message to the database server **108** over a secure connection. In some arrangements, the message generation circuit **288** is configured to generate a CMS SignedData message wrapper around the data request message. In some arrangements, the data encryption circuit **220** is configured to generate a CMS SigncryptData message wrapper around the data request message. In arrangements in which the message generation circuit **288** is configured to generate a CMS SignedData message wrapper or a CMS SigncryptData message wrapper around the data request message, the key database **298** includes a certificate of the database server **108** that includes a public key of the database server **108**.

[0065] In some arrangements, the user of the data exit entity **116** may request more than one piece of sensitive user data. In such an arrangement, the data request message includes all of the pieces of requested user data. In some arrangements, the user may request that one or more pieces of sensitive user data are shared with more than one data exit entity **116**. In such an arrangement, the data request message includes all of the pieces of requested user data and information indicative of the identities of the data exit entities **116** to which each piece of sensitive user data should be sent.

[0066] The data decryption circuit **292** of the data exit entity **116** is configured to receive encrypted user data and the second encrypted CEK from the database server **108**. In some arrangements, the database server **108** is configured to transmit the encrypted user data and the second encrypted CEK over a secure connection. Since the encrypted user data and the encrypted CEK are both encrypted, the cleartext sensitive user data and/or the cleartext CEK are not visible at the entrance or the exit of the secure connection. In arrangements which the encrypted user data and the second encrypted CEK are wrapped with a CMS SignedData message wrapper or in which the encrypted user data and the second encrypted CEK are wrapped with a CMS SigncryptData message wrapper, the database server **108** does not need to transmit the encrypted user data and the encrypted CEK over a secure connection. In arrangements in which the encrypted user data and the second encrypted CEK are wrapped with a CMS SigncryptData message wrapper, the data decryption circuit **292** can verify the digital signature on the CMS SignedData message and decrypt the second encrypted CEK and the encrypted user data using the public key of the database server **108** and the private key **293** of the data exit entity **116**.

[0067] In some arrangements, the data decryption circuit **292** is configured to undergo a key encryption key (KEK) protocol with the key manager **112** to generate a KEK with the key manager **112**. In some arrangements, the KEK is a symmetric key. In some arrangements, the KEK is an asymmetric key. For example, the KEK can be a public key **226** of the key manager **112**. In some arrangements, the KEK can be derived from a pre-shared derivation key (PSDK) based on a message, a unique scheme, a random scheme, and/or a rotational scheme. The data decryption circuit **292** is configured to save the KEK to the key database **298**. In some arrangements, the KEK is a named Key. In such arrangements, the KEK (CEK) received by the data exit entity **116** includes the name of the named Key. In such arrangements, the decryption circuit **292** is configured to identify the named Key based on name received with the KEK (CEK). In some arrangements, the data decryption circuit **292** uses the same KEK for all of the CEKs that can be translated by the key manager **112**. In such arrangements, the second CEK received by the data exit entity **116** is the second KEK (CEK) that is encrypted with the public key **261** of the data exit entity **116**. The data decryption circuit **292** is configured to decrypt the second KEK (CEK) using the private key **293** of the data exit entity **116** to generate the second KEK (CEK). The data decryption circuit **292** is configured to decrypt the second KEK (CEK) with the KEK established with the key manager **112** to recover the cleartext CEK.

[0068] The data decryption circuit **292** is configured to recover the cleartext CEK by decrypting the second encrypted CEK using the private key **293** of the data exit entity **116**. The data decryption circuit **292** is configured to recover the cleartext sensitive user data by decrypting the encrypted user data using the cleartext second CEK. The data decryption circuit **292** is configured to display the sensitive user data via the output interface of the user input/output device **276**. For example, the data decryption circuit **292** can display the sensitive user data on a window of a software application run on a browser of the data exit entity **116** or running locally on the data exit entity **116**.

[0069] In arrangements in which the user of the data exit entity **116** requested multiple pieces of sensitive user data, the data decryption circuit **292** decrypts each second encrypted CEK and decrypts each piece of encrypted user data and displays each piece of cleartext sensitive user data as described above. In arrangements in which one or more pieces of sensitive user data are requested by one or more data exit entity **116**, each data exit entity **116** receives one or more pieces of encrypted user data corresponding to the one or more pieces of requested user data and one or more second CEKs corresponding to each piece of the encrypted user data. Each of the second CEKs has been encrypted with the public key **261** of the data exit entity **116** receiving the encrypted user data and the encrypted CEK. The data decryption circuit **292** of each of the data exit entities **116** decrypts each second CEK and decrypts each piece of encrypted user data and displays each piece of cleartext sensitive user data as described above.

[0070] The authentication circuit **296** is configured to validate the data exit entity's certificate **259** that is stored in the key database **298**. For example, the authentication circuit **296** can transmit the data exit entity certificate **259** to the certificate authority that issued the data exit entity certificate **259** and ask the certificate authority to confirm that the data exit entity certificate **259** is valid. In some arrangements, the authentication circuit **296** validates the data exit entity certificate **259** every time encrypted user data and an encrypted second CEK is sent to the data exit entity **116**. In some arrangements, the authentication circuit **296** validates the data exit entity certificate **259** based on a predefined time period (e.g., hourly). In some arrangements, the authentication circuit **296** validates the data exit entity certificate **259** every time user data is requested via the message generation circuit **288**. The authentication circuit **296** is configured to prevent users from requesting sensitive user data in response to determining that the data exit entity certificate **259** is expired or has been revoked. The authentication circuit **296** is configured to read an expiration date of the data exit entity certificate **259** from the data exit entity certificate **259**. The authentication circuit **296** is configured to notify an administrator of the data exit entity **116** in response to determining that the

data exit entity certificate **259** will expire in less than a predefined time period. In some arrangements, the predefined time period may be ninety days. In arrangements in which the key database **298** includes the certificate of the database server **108**, the authentication circuit **296** is configured to validate the database server certificate as described above for the data exit entity certificate **259**.

[0071] Referring now to FIGS. **3A-3C**, a flow diagram of a method **300** for protecting user data received by a data entry entity, stored by a database server, and displayed by a data exit entity that may be administered by third parties is shown, according to an example arrangement. At **302**, the authentication circuit **224** of the data entry entity **104** validates the certificate **222** of the key manager **112**. For example, the authentication circuit **224** can transmit the key manager certificate **222** to the certificate authority that issued the key manager certificate **222** and ask the certificate authority to confirm that the key manager certificate **222** is valid. In some arrangements, the authentication circuit **224** validates the key manager certificate **222** based on a predefined time period. In some arrangements, the authentication circuit **224** validates the key manager certificate **222** every time user data is entered into the data entry entity **104**. In response to determining that the key manager certificate **222** is valid, the authentication circuit **224** allows entry of user data into the data entry entity **104**. In some arrangements, the authentication circuit **224** may notify an administrator of the system **100** or the data entry entity **104** in response to determining that the key manager certificate **222** will expire within a predefined time period. In response to determining that the key manager certificate **222** is invalid, the authentication circuit **224** prevents entry of the user data into the data entry entity **104**.

[0072] At **304**, the data encryption circuit **220** prompts or requests the user to enter user data into the data entry entity **104**. For example, the user input/output device **204** of the data entry entity **104** can display a prompt or a request for the user to enter user data and provide a text entry window for the user to enter the data. In another example, the user input/output device **204** of the data entry entity **104** can generate an auditory prompt or request for the user to enter data and record an acoustic user response including the user data.

[0073] At **306**, the data encryption circuit **220** of the data entry entity **104** determines that the user data is sensitive user data. For example, the text entry window and/or the prompt or request for user data can be tagged to indicate that the data entered into the text entry window and/or received in response to the prompt or request is sensitive user data. At **308**, the data encryption circuit **220** generates a CEK. The CEK is a symmetric key. At **310**, the data encryption circuit **220** generates encrypted user data by encrypting the sensitive user data with the CEK. At **312**, the data encryption circuit **220** generates the encrypted CEK by encrypting the CEK with the public key **226** of the key manager **112**. For example, the data encryption circuit **220** can encrypt the CEK using CMS-envelope data with the key manager certificate **222**. At **314**, the data encryption circuit **220** tags the encrypted user data and the encrypted CEK with a tag that is readable by the database server **108**. In some arrangements, the tag is a cleartext tag. The tag can include information indicative of the encrypted user data. For example, the information indicative of the encrypted user data can include information indicative of a type of user data corresponding to the encrypted user data and/or information indicative of an identity of a user corresponding to the encrypted user data. At **316**, the data encryption circuit **220** transmits the encrypted user data and the encrypted CEK to the database server **108**. In arrangements in which the data encryption circuit **220** determines that the data exit entity **116** has received multiple pieces of sensitive user data, the data encryption circuit **220** repeats blocks **310-320** for each piece of sensitive user data.

[0074] At **318**, the database server **108** receives the encrypted user data and the encrypted CEK from the data entry entity **104** over the secure connection. At optional block **320**, the database server **108** transmits a message to the data entry entity **104** indicating that the database server **108** has received the encrypted user data and the encrypted CEK. At optional block **322**, the data entry entity **104** destroys the user data and the CEK in response to receiving the message from the

database server **108** indicating that the database server **108** has received the encrypted user data and the encrypted CEK. At **324**, the database server **108** saves the encrypted user data to the user information database **244** of the memory **236**.

[0075] At **326**, the message generation circuit **288** of the data exit entity **116** receives a request for sensitive user data input by a user using the user input/output device **276**. At **328**, the authentication circuit **296** of the data exit entity **116** validates the certificate **259** of the data exit entity **116**. For example, the authentication circuit **296** can transmit the data exit entity certificate **259** to the certificate authority that issued the data exit entity certificate **259** and ask the certificate authority to confirm that the data exit entity certificate **259** is valid. In response to determining that the data exit entity certificate **259** is valid, the authentication circuit **296** allows entry of a user data request into the data exit entity **116**. In some arrangements, the authentication circuit **296** may notify an administrator of the system **100** or the data exit entity **116** in response to determining that the data exit entity certificate **259** will expire within a predefined time period. In response to determining that the data exit entity certificate **259** is invalid, the authentication circuit **296** prevents entry of the user data request into the data exit entity **116**.

[0076] At **330**, the message generation circuit **288** determines information indicative of the requested user data based on the request for sensitive user data input by the user of the data exit entity **116**. The information indicative of the requested user data can include information indicative of a type of user data (e.g., social security number, account number, address, birth date, biometric, etc.) and/or information indicative of an identity of the user (e.g., a name, a reference number, etc.). At **332**, the message generation circuit **288** generates a data request message including the information indicative of the requested user data and information indicative of the identity of the data exit entity **116**. The information indicative of the identity of the data exit entity **116** can include an IP address, an IMEI number, an instance of a software application running on the data exit entity **116** or a browser running on the data exit entity **116**, etc. At **334**, the message generation circuit **288** transmits the data request message to the database server **108** over a secure connection.

[0077] At **336**, the data identification circuit **240** receives the data request message from the data exit entity **116**. The data request message includes information indicative of the encrypted user data requested by the data exit entity **116** and information indicative of the identity of the data exit entity **116**. At **338**, the data identification circuit **240** identifies the requested user data based on the information indicative of the encrypted user data included in the tag. For example, the data identification circuit **240** can compare the information indicative of the requested user data to the information indicative of the encrypted user data in the tag to identify the encrypted user data that matches the requested user data. At **340**, the data identification circuit **240** retrieves the encrypted CEK corresponding to the encrypted user data that corresponds to the requested user data. At **342**, the data identification circuit **240** transmits the encrypted CEK corresponding to the requested user data and the information indicative of the identity of the data exit entity **116** to the key manager **112**. At **344**, the data identification circuit **240** logs each CEK sent to the key manager **112** and the information indicative of the data exit entity **116** requesting the user information corresponding to each CEK sent to the key manager **112** in the data request log **248**.

[0078] In some arrangements, the data request message can include one or more pieces of requested user data. In such arrangements, the data identification circuit **240** identifies each piece of encrypted user data corresponding to each piece of requested user data. The data identification circuit **240** repeats blocks **336-344** for each piece of requested user data. In some arrangements, the data request message can include the information indicative of one or more data exit entities **116** and one or more pieces of requested user data. In such arrangements, the data identification circuit **240** repeats blocks **336-344** for each piece of requested user data and transmits the one or more CEKs and the information indicative of the identities of the one or more data exit entities **116** to the key manager **112**.

[0079] At **346**, the translation circuit **260** of the key manager **112** receives the encrypted CEK

corresponding to the requested user data and the information indicative of the identity of the data exit entity **116**. At **348**, the translation circuit **260** identifies the certificate **259** for the data exit entity **116** based on the information indicative of the identity of the data exit entity **116**. At **350**, the authentication circuit **264** validates the certificate **259** of the data exit entity **116**. For example, the authentication circuit **264** can transmit the data exit entity certificate **259** to the certificate authority that issued the data exit entity certificate **259** and ask the certificate authority to confirm that the data exit entity certificate **259** is valid. In some arrangements, the authentication circuit **264** validates the data exit entity certificate **259** based on a predefined time period. In some arrangements, the authentication circuit **264** validates the data exit entity certificate **259** every time the key manager **112** receives the information indicative of the identity of the data exit entity **116**. In response to determining that the data exit entity certificate **259** is valid, the authentication circuit **264** allows translation of the CEK. In some arrangements, the authentication circuit **264** may notify an administrator of the system **100** or the key manager **112** in response to determining that the data exit entity certificate **259** will expire within a predefined time period. In response to determining that the data exit entity certificate **259** is invalid, the authentication circuit **264** prevents translation of the CEK.

[0080] At **352**, the translation circuit **260** recovers the cleartext CEK by decrypting the encrypted CEK with the private key **249** of the key manager **112**. At **354**, the translation circuit **260** generates a second encrypted CEK by encrypting the cleartext CEK with the public key **261** of the data exit entity **116**. The second encrypted CEK can be decrypted by the data exit entity **116** using its private key **293**. At **356**, the translation circuit **260** transmits the second encrypted CEK and the information indicative of the identity of the data exit entity **116** to the database server **108**. At **358**, the translation circuit **260** logs each CEK translated and the information of the identity of each data exit entity **116** requesting translation of each CEK in the CEK translation log **272**. The key manager **112** excludes the encrypted user data. The key manager **112** does not transmit or receive any encrypted user data. Accordingly, an administrator of the key manager **112** cannot access the user data, let alone decrypt the encrypted user data to recover the cleartext sensitive user data.

[0081] At **360**, the data identification circuit **240** of the database server **108** receives the second encrypted CEK and the information indicative of the identity of the data exit entity **116**. At **362**, the data identification circuit **240** retrieves the encrypted user data corresponding to the second encrypted CEK. At **362**, the data identification circuit **240** transmits the encrypted user data and the second encrypted CEK to the data exit entity **116** over a secure connection. As described herein, the database server **108** excludes the private key **249** of the key manager **112**. Therefore, the database server **108** cannot decrypt the encrypted CEKs and use the encrypted CEKs to decrypt the encrypted user data.

[0082] At **364**, the data decryption circuit **292** of the data exit entity **116** receives the encrypted user data and the second encrypted CEK from the database server **108** over the secure connection. Since the encrypted user data and the encrypted CEK are sent over the secure connection, the cleartext sensitive user data and the cleartext CEK are not visible at the entrance and the exit ends of the secure connection. At **366**, the data decryption circuit **292** recovers the cleartext CEK by decrypting the second encrypted CEK with the private key **293** of the data exit entity **116**. At **368**, the data encryption circuit **220** recovers the sensitive user data by decrypting the encrypted user data with the cleartext CEK. At **370**, the data decryption circuit **292** displays the sensitive user data to the user of the data exit entity **116**. For example, the data decryption circuit **292** can display the sensitive user data on a window of a software application run on a browser of the data exit entity **116** or running locally on the data exit entity **116**.

[0083] In some arrangements, the user may request more than one piece of user data. In such an arrangement, the data request message includes all of the pieces of requested user data. The data exit entity **116** repeats blocks **364-370** for each piece of requested user data. In some arrangements, the user may request that one or more pieces of sensitive user data are shared with more than one

data exit entity **116**. In such an arrangement, the data request message includes all of the pieces of requested user data and information indicative of the identities of the data exit entities **116** to which each piece of sensitive user data should be sent. Each of the data exit entities **116** then completes blocks **364-370** for each piece of encrypted user data received.

[0084] Referring now to FIGS. **4-5**, an environmental view of a system **400** for protecting user data that is entered into a third-party data entry device, sent to and stored on a third-party database server, and displayed and/or used by a third-party data exit computing system is shown. The sensitive user data can include identity information such as a social security number, account number, date of birth, biometric data (e.g., a stored image of a fingerprint, retina, or other body part to be used to authenticate the user). As shown in FIGS. **4-5**, the system **400** includes one or more data entry entities **404**, a database server **408**, a key manager **412**, and one or more requestors or data exit entities **416** connected by a network **420**. For example, the system **400** illustrated in FIG. **4** includes four data entry entities **404A-404D** and four data exit entities **416A-416D** that are in communication with the database server **408** over the network **420**. In other arrangements, the system **400** can include a different number of data entry entities **404** and data exit entities **416**. While the data entry entity **404**, the database server **408**, the key manager **412**, and the data exit entity **416** are shown as being on separate network nodes in FIGS. **4-5**, in some arrangements, the database server **408** and the key manager **412** can be on the same network node.

[0085] The data entry entity **404** is a computing system that includes a software program that requests that a user enter sensitive user data to be stored by the database server **408**. The data entry entity **404** may be administered by a third-party. The data entry entity **404** can include a web browser that includes a software application that requests that the user enter sensitive user data to be stored by the third-party data storage system **400**. In other arrangements, the data entry entity **404** can include a local software application that requests that the user enter sensitive data to be stored by the third-party data storage system **400**. In some arrangements, the data entry entity **404** is on a single network node. As shown in FIG. **5A**, the illustrated arrangement, the data entry entity **404** includes a user input/output device **504**, a network interface **508**, a memory **512**, and a processing circuit **514**. The processing circuit **514** includes a data receiving circuit **516**, a data encryption circuit **520**, and an authentication circuit **524**. The user input/output device **504**, the network interface **508**, the memory **512**, the data encryption circuit **520**, and the authentication circuit **524** are substantially similar to the user input/output device **204**, the network interface **208**, the memory **212**, the data receiving circuit **216**, and the authentication circuit **224**, respectively, described with respect to the data entry entity **104** and are not discussed in detail herein.

[0086] As shown in FIG. **5**, the memory **512** is communicably and operatively coupled with the other components of the data entry entity **404**. The memory **512** includes a key database **528**.

[0087] The data encryption circuit **520** is configured to undergo a public key cryptography (PKC) agreement protocol with the key manager **412**. During the PKC agreement protocol, the data encryption circuit **520** and the key manager **412** exchange public keys and compute a shared secret **526**. The data encryption circuit **520** is configured to obfuscate the shared secret **526** and store the obfuscated shared secret **526** to the memory **512**. In some arrangements, the PKC agreement protocol can be a Diffie-Hellman protocol, an elliptic curve Diffie-Hellman protocol, another post-quantum cryptography protocol, etc. The data encryption circuit **520** is configured to derive a content encryption key (CEK) from the shared secret **526**. In some arrangements, the CEK is an ephemeral key and only one CEK is derived from the shared secret **526**. One of the data encryption circuit **520** or the key manager **412** is configured to generate a name for the CEK and transmit the name to the other of the data encryption circuit **520** and the key manager **412**. As referred to herein, the phrase “first named CEK” refers to one or more CEKs generated based on the shared secret **526** generated between the data entry entity **404** and the key manager **412**. The name includes information indicative of how to recover the first named CEK **530** based on the shared secret **526**. In some arrangements, the name indicates an algorithm for regenerating the first named CEK **530**

based on the shared secret **526**. For example, the illustrated arrangement illustrates four first named CEKs **530A-530D** and four shared secrets **526A-526D**. Each of the first named CEKs **530A-530D** has been generated based on the respective shared secret **526A-526D** established between the respective data entry entity **404A-404D** and the key manager **412**. Other arrangements can include different numbers of first named CEKs **530**.

[0088] The data encryption circuit **520** is configured to recognize one or more pieces of the user data as being sensitive user data. In some arrangements, data entry interfaces (e.g., data entry windows on a website application or a software program) can be tagged as sensitive data entry windows that receive sensitive user data, as described above. In some arrangements, the same first named CEK **530** is used to encrypt each piece of sensitive user data. In arrangements that use ephemeral keys, the data encryption circuit **520** is configured to generate a different first named CEK **530** for each message and/or communication session between the data entry entity **404** and the key manager **412**. In some arrangements in which a separate CEK is desired for each piece of sensitive user data input by the user, the pieces of sensitive user data can be sent using different messages. In some arrangements in which a separate CEK is desired for each piece of sensitive user data, the data encryption circuit **520** can generate a temporary derivation key based on the shared secret **526**. The temporary derivation key is not saved to the key database **528** of the memory **512**. The data encryption circuit **520** can derive unique CEKs for each piece of sensitive user data using the temporary derivation key. The data encryption circuit **520** is configured to generate encrypted user data by encrypting the sensitive user data with the first named CEK **530**.

[0089] The data encryption circuit **520** is configured to tag the encrypted user data and the first named CEK **530** with a tag that is readable by the database server **408**. The database server **408** can read the tag without decrypting any of the encrypted user data. In some arrangements, the tag is a cleartext tag. The tag can include information indicative of the encrypted user data. The information indicative of the user data can include information indicative of a type of user data (e.g., social security number, account number, address, birth date, biometric, etc.) and/or information indicative of an identity of the user (e.g., a name, a reference number, etc.). In some arrangements, the name of the first named CEK **530** is included in the tag. In some arrangements, the data encryption circuit **520** is configured to transmit the encrypted user data and the name of the first named CEK **530** to the database server **408** over a secure connection. Since the encrypted user data is sent over the secure connection, the cleartext sensitive user data is not visible at the entrance and exit of the secure connection. In some arrangements, the secure connection can be a TLS connection. The data encryption circuit **520** is configured to destroy the first named CEK **530** and the user data in response to receiving a message from the database server **408** indicating that the encrypted user data has been received by the database server **408**.

[0090] In some arrangements, the data encryption circuit **520** can receive more than one piece of sensitive user data. When more than one piece of sensitive user data is received, the data encryption circuit **520** is configured to generate a new first named CEK **530** for each piece of sensitive user data as described above. The data encryption circuit **520** is configured to generate encrypted user data from each piece of sensitive user data by encrypting each piece of sensitive user data with the respective first named CEK **530** generated for that piece of sensitive user data. The data encryption circuit **520** is configured to generate a tag for each piece of encrypted user data and the name of each first named CEK **530** corresponding to each piece of encrypted user data as described above.

[0091] In some arrangements, the data encryption circuit **520** is configured to generate a CMS SigncryptData message wrapper around the encrypted user data and the name of the first named CEK **530**, which can provide the functionality of nested SignedData (EnvelopedData) messages. In such an arrangement, the key database **528** includes a public/private key pair of the data entry entity **404**. Such arrangements do not require a secure connection, such as the secure tunnel provided by TLS.

[0092] The database server **408** is a secure computing system that is configured to store encrypted

user data received from data entry entities **404** connected to the network **420**. The database server **408** may be administered by a third-party. In some arrangements, the database server **408** is hosted in the cloud. As shown in FIG. **4B**, the database server **408** includes a network interface **532**, a memory **536**, and a processing circuit **538**. The processing circuit **538** includes a data identification circuit **540**. The network interface **532** and the memory **536** are substantially similar to the network interface **232** and the memory **236**, respectively, described with respect to the database server **108** and are not discussed in greater detail herein.

[0093] The memory **536** is communicably and operatively coupled with the other components of the database server **408**. The memory **536** includes a user information database **544** and a data request log **548**. The user information database **544** includes encrypted user data and the names of the first named CEKs **530** that correspond to the encrypted user data. The data request log **548** includes a list of encrypted user data requested by the data exit entity **416** and information indicative of the identity of the data exit entity **416**. The memory **536** excludes the private key of the key manager **412**, the shared secret **526** generated between the data entry entity **404** and the key manager **412**, the first named CEK **530**, the shared secret **526** generated between the data exit entity **416** and the key manager **412**, and a second named CEK **534** (described in greater detail below). The private key of the key manager **412**, the shared secret **526** generated between the data entry entity **404** and the key manager **412**, the first named CEK **530**, the shared secret **526** generated between the data exit entity **416** and the key manager **412**, and the second named CEK **534** are not stored to the memory **536**. Accordingly, the database server **408** and/or the administrators of the database server **408** cannot decrypt the encrypted user data to access cleartext sensitive user data. Furthermore, unauthorized parties cannot access the sensitive user data even if the unauthorized parties gain access to the database server **408**. Stated another way, the database server **408** does not have access to the private keys stored in the key manager **412**, the shared secret **526** generated between the data entry entity **404** and the key manager **412**, the first named CEK **530**, the shared secret **526** generated between the data exit entity **416** and the key manager **412**, the second named CEK **534**, and the cleartext sensitive user data.

[0094] The database server **408** is configured to receive the encrypted user data and the name of the first named CEK **530** corresponding to the encrypted user data. In arrangements in which the data entry entity **404** transmits the encrypted user data and the name of the first named CEK **530** over a secure connection, cleartext sensitive user data is not present at the end of the secure connection. Furthermore, the database server **408** cannot recover the first named CEK **530** based on the name of the first named CEK **530**. Therefore, the database server **408** cannot decrypt the encrypted user data to access the cleartext sensitive user data. This allows the database server **408** to be administered by an entity that might not be authorized to access the sensitive user data. The database server **408** is configured to save the encrypted user data and the name of the first named CEK **530** to the user information database **544** in the memory **536**. The database server **408** is configured to transmit a message to the data entry entity **404** to confirm that the encrypted user data has been received.

[0095] The data identification circuit **540** is configured to receive a data request message from the data exit entity **416**. The data request message can include information indicative of the requested user data, information indicative of an identity of the data exit entity **416** and/or a name of a second named CEK **534**. As referred to herein, the phrase “second named CEK” refers to one or more CEKs generated based on a shared secret **542** generated between the data exit entity **416** and the key manager **412** as described in greater detail below. The information indicative of the requested user data can include information indicative of an identity of the user corresponding to the encrypted user data, information indicative of a type of user data, etc. The information indicative of the identity of the data exit entity **416** can include an IP address of the data exit entity **416**, an IMEI number of the data exit entity **416**, an instance of a software application running on the data exit entity **416**, etc. The data identification circuit **540** is configured to identify the encrypted user data

requested by the data exit entity **416** based on the information indicative of the encrypted user data included in the tag. For example, the data identification circuit **540** can read the information indicative of the requested user data from the data request message and compare the information indicative of the requested user data to the information indicative of the encrypted user data in each of the tags to identify a match. During this process, the data identification circuit **540** does not decrypt the encrypted user data. The data identification circuit **540** is configured to retrieve the encrypted user data corresponding to the requested user data. The data identification circuit **540** is configured to transmit the encrypted user data, the name of the CEK, and the information and the information indicative of the identity of the data exit entity **416** and/or the name of the second named CEK **534** to the key manager **412**. The data identification circuit **540** is configured to log each piece of user data requested and the data exit entity **416** or data exit entities **416** requesting each piece of user data in the data request log **548** stored in the memory **536**.

[0096] In some arrangements, the data identification circuit **540** receives second encrypted user data and the information indicative of the identity of the data exit entity **416** from the key manager **412**. The second encrypted user data has been translated by the key manager **412** as described in greater detail below so that the data exit entity **416** can decrypt the second encrypted user data. As described in greater detail below, translated encrypted user data is sensitive user data that has been encrypted using the second named CEK **534**. The data identification circuit **540** is configured to transmit the second encrypted user data to the data exit entity **116**. In some arrangements, the data identification circuit **540** is configured to transmit the second encrypted user data. Since the second encrypted user data is encrypted, no cleartext sensitive user data is present at the entrance or exit of the secure connection. In some arrangements, the data identification circuit **540** is configured to generate a CMS SigncryptData message wrapper around the second encrypted user data, which can provide the functionality of nested SignedData (EnvelopedData) messages. Such arrangements do not require a secure connection, such as the secure tunnel provided by TLS. The data identification circuit **540** handles second, third, etc. data request messages from the data exit entity **416** or other data exit entities **416** as described above.

[0097] In some arrangements, the data request message can include one or more pieces of requested user data. In such an arrangement, the data identification circuit **540** can identify each piece of encrypted user data corresponding to each piece of requested user data based on the information indicative of the encrypted user data in the tag. The data identification circuit **540** does not decrypt the encrypted user data or access the cleartext sensitive user data when identifying each piece of encrypted user data corresponding to each piece of requested user data. The data identification circuit **240** transmits the encrypted user data corresponding to the requested user data, the name of the first named CEK **530**, and the name of the second named CEK **534**, and/or the information indicative of the identity of the data exit entity **416** to the key manager **112**.

[0098] In some arrangements, the data request message can include the information indicative of one or more data exit entities **416** and/or the names of second named CEKs **534** previously established between the key manager **412** and one or more data exit entities **416** and one or more pieces of requested user data. In such arrangements, the data identification circuit **540** can retrieve the one or more pieces of encrypted user data corresponding to the one or more pieces of requested user data and transmit the one or more pieces of encrypted user data, the name of the first encrypted CEK **530**, and the names of the second named CEKs **534** to the key manager **412**.

[0099] In such arrangements, the data identification circuit **540** is configured to receive pieces of second encrypted user data from the key manager **412** corresponding to each of the data exit entities **416**. The data identification circuit **540** is configured to transmit the second encrypted user data to each of the data exit entities **416**. In some arrangements, the data identification circuit **540** transmits the translated encrypted user data over a secure connection. Since the second encrypted user data is encrypted, no cleartext sensitive user data is exposed at the entrance or exit of the secure connection.

[0100] In some arrangements, the data identification circuit **540** is configured to transmit one or more pieces of encrypted user data to one or more of the data exit entities **416** according to a predefined schedule. In such arrangements, the data exit entity **416** is configured to send a message to the database server **408** that establishes the predefined schedule and an identity of one or more data entry entities **404**, information indicative of one or more types of encrypted user data, and/or one pieces of information indicative of an identity of a user to send to the data exit entity **416** according to the predefined schedule. The data identification circuit **540** is configured to identify the encrypted user data based on the tag and send the encrypted user data, the name of the first named CEK **530** corresponding to the encrypted user data, and the name of each of the one or more second named CEKs **534** corresponding to each of the one or more data exit entities **416** to the key manager **412** as described above.

[0101] In some arrangements, the data entry entity **404** is configured to transmit instructions that include information indicative of one or more data exit entities **416** and that command the database server **408** to send the encrypted user data to one or more data exit entities **416**. In some arrangements, the instructions are included in the tag. In other arrangements, the instructions are sent with the encrypted user data in another manner, such as a CMS SigncryptData message wrapper. The data identification circuit **540** is configured to identify the instructions sent with the encrypted user data and send the encrypted user data, the name of the first named CEK **530**, and the information indicative of the one or more data exit entities **416** to the key manager **412** as described above.

[0102] As shown in FIG. 5C, the key manager **412** includes a network interface **552**, a memory **556**, and a processing circuit **558**. The processing circuit **558** includes a translation circuit **560**, an encryption circuit **562**, and an authentication circuit **564**. The network interface **552**, the memory **556**, and the authentication circuit **564** are substantially similar to the network interface **252**, the memory **256**, and the authentication circuit **264**, respectively, described with respect to the key manager **112** and are not discussed in detail herein.

[0103] The memory **556** includes a key database **568** and a data translation log **572**. In some arrangements, the key database **568** includes a public/private key pair of the key manager **412** and a certificate for each data exit entity **416** authorized to receive user data from the database server **408**. In such arrangements, only data exit entities **416** having valid certificates can receive encrypted user data from the database server **408**. The data translation log **572** includes a list including information indicative of the encrypted user data translated by the key manager **412** and the one or more data exit entities **416** requesting each piece of second encrypted user data. The key manager **412** does not store translated or cleartext used data in the memory **556**.

[0104] The encryption circuit **562** is configured to undergo PKC agreement protocols with the one or more data entry entities **404** and the one or more data exit entities **416** of the system **400**. During the PKC agreement protocol with the data entry entity **404**, the encryption circuit **562** and the data entry entity **404** (e.g., the data encryption circuit **520**) exchange public keys and compute the shared secret **526**. The encryption circuit **562** is configured to obfuscate the shared secret **526** and store the obfuscated shared secret **526** to the memory **556**. In some arrangements, the PKC agreement protocol can be a Diffie-Hellman protocol, an elliptic curve Diffie-Hellman protocol, another post-quantum cryptography protocol, etc. The data encryption circuit **520** is configured to derive a CEK from the shared secret **526**. For example, the data encryption circuit **520** can input the shared secret **526** into a key derivation function (KDF) to derive the CEK from the shared secret **526**. In some arrangements, the KDF is described as in PKCS #5 or NIST SP 8-63B, both of which are incorporated by reference herein. The one of the encryption circuit **562** or the data entry entity **404** is configured to generate a name for the CEK (e.g., the first named CEK **530**) and to transmit the name to the other of the data encryption circuit **520** and the data entry entity **404**. The encryption circuit **562** stores the first named CEK and the name of the first named CEK **530** to the key database **568** of the memory **556**.

[0105] During the PKC agreement protocol with the data exit entity **416**, the encryption circuit **562** and the data exit entity **416** (e.g., the data encryption circuit **520**) exchange public keys and compute the shared secret **542**. The encryption circuit **562** is configured to obfuscate the shared secret **542** and save the obfuscated shared secret **542** to the memory **556**. In some arrangements, the PKC agreement protocol can be a Diffie-Hellman protocol, an elliptic curve Diffie-Hellman protocol, another post-quantum cryptography protocol, etc. In some arrangements, the encryption circuit **562** is configured to derive a CEK from the shared secret **542**. In some arrangements, the encryption circuit **562** is configured to use a KDF to derive a temporary derivation key that can be used to derive multiple CEKs. In such an arrangement, separate CEKs can be derived for each piece of sensitive user data. One of the encryption circuit **562** or the data exit entity **416** is configured to generate a name for the CEK (e.g., the second named CEK **534**) and transmit the name to the other of the encryption circuit **562** and the data exit entity **416**. The encryption circuit **562** stores the second named CEK **534** and the name of the second named CEK **534** to the key database **568** of the memory **556**. In some arrangements in which a separate CEK is desired for each piece of sensitive user data, the encryption circuit **562** can generate a temporary derivation key based on the shared secret **542**. The temporary derivation key is not saved to the memory **556**. The encryption circuit **562** can derive unique CEKs for each piece of sensitive user data using the temporary derivation key. The illustrated arrangement illustrates four second named CEKs **534A-534D** and four shared secrets **542A-542D**. Each of the second named CEKs **534A-534D** has been generated based on the respective shared secret **542A-542D** established between the respective data exit entity **416A-416D** and the key manager **412**. Other arrangements can include different numbers of second named CEKs **534**.

[0106] The translation circuit **560** is configured to receive the encrypted user data, the name of the first named CEK **530**, and the name of the second named CEK **534** and/or the information indicative of the identity of the data exit entity **416** from the database server **408**. The translation circuit **560** is configured to recover the first named CEK **530** based on the name of the first named CEK **530**. The translation circuit **560** is configured to decrypt the encrypted user data using the first named CEK **530** to recover the cleartext sensitive user data. The translation circuit **560** is configured to recover the second named CEK **534** based on the name of the second named CEK **534**. The translation circuit **560** is configured to encrypt the cleartext sensitive user data using the second named CEK **534** to generate second encrypted user data. As used herein, data translation refers to decrypting a piece of encrypted user data with the first named CEK **530** to recover cleartext sensitive user data and encrypting the cleartext sensitive user data with the second named CEK **534** to generate second encrypted user data. The translation circuit **560** is configured to transmit the second encrypted user data and the information indicative of the identity of the data exit entity **416** to the database server **408**. In some arrangements, the translation circuit **560** is configured to transmit the second encrypted user data to the data exit entity **416**.

[0107] In some arrangements, the translation circuit **560** can receive one or more pieces of encrypted user data, the name(s) of one more first named CEKs **530**, and one or more second named CEKs **534** and/or information indicative of one or more data exit entities **416**. The translation circuit **560** is configured to recover the first named CEKs **530** based on the name(s) of the one or more first named CEKs **530**. The translation circuit **560** is configured to decrypt each piece of encrypted user data using the first named CEK **530** for that piece of encrypted user data to recover cleartext sensitive user data. The translation circuit **560** is configured to identify the second named CEKs **534** corresponding to each of the one or more data exit entities **416** that request the encrypted user data based on the names and/or the information indicative of the identity of the one or more data exit entities **416**. The translation circuit **560** is configured to encrypt the one or more pieces of cleartext sensitive user data with the second named CEKs **534** of each of the data exit entities **416** that have requested the encrypted user data. The translation circuit **260** is configured to log each translation request in the data translation log **572**. For example, the translation circuit **260**

is configured to save a record of information indicative of each piece of encrypted user data translated and the data exit entity **416** or data exit entities **416** requesting the translation in the data translation log **572**. In some arrangements, the translation circuit **260** is configured to log translation requests from data exit entities **416** having invalid certificates in the data translation log **572**.

[0108] In some arrangements, the key manager **412** is a hardware security module (HSM). In some arrangements, the key manager **412** and the database server **408** are on the same network node. In some arrangements, the key manager **412** and the database server **408** are on the same network node and the network node is hosted in the cloud. In some arrangements, the key manager **412** and the database server **408** are on different network nodes.

[0109] Although one database server **408** is discussed in the arrangement described above, in some arrangements, the third-party data storage system **400** can include a plurality of database servers **408** and the key manager **412** can be configured to communicate with the plurality of database servers **408**. In some arrangements, the database servers **408** can each communicate with different groups of data entry entities **404** and different groups of data exit entities **416**. In such arrangements, the key manager **412** may use a different public/private key pair for each database server **408**.

[0110] In other arrangements, the third-party data storage system **400** can include a plurality of database servers **408** and a plurality of key managers **412**. By way of non-limiting example, in some arrangements, the plurality of database servers **408** can include a first database server and a second database server and the plurality of key managers **412** can include a first key manager and a second key manager. In such an arrangement, the second database server can request user data from the first database server using a data request message similar to the data request message described above with respect to the data exit entity **416**. The first database server can retrieve the encrypted user data and the name of the first named CEK **530** corresponding to the requested user data and transmit the encrypted user data and the name of the first named CEK **530** to the first key manager. The first key manager can translate the encrypted user data as described above to generate second encrypted user data that can be decrypted by the second key manager. The first database server can then send the encrypted user data and the name of a second named CEK **534** established between the first key manager and the second key manager to the second database server in a manner similar to what is described above. In other arrangements, the plurality of database servers can include a different number of database servers and the plurality of key managers can include a different number of key managers that can send and receive encrypted user data and the names of previously established named CEKs to and from each other. In some arrangements, the second database server communicates with the data exit entities **416** as described below and the second key manager translates the encrypted user data as described above to generate third encrypted user data that is encrypted with a third named CEK established between the second key manager and one of data exit entities **416** to generate third encrypted user data that can be decrypted by the data exit entity **416** as described above with respect to the first key manager.

[0111] The requestor or data exit entity **416** can be a computing system that includes a software program that includes a user input/output device **576** that allows a user to request sensitive user data stored in a third-party data storage system **400**, such as the database server **408**. For example, the user can request various types of user data corresponding to various users. In some arrangements, the data exit entity **416** is on a single network node. The data exit entity **416** may be administered by a third-party. The data exit entity **416** can be a web browser that includes a software application that allows a user to request sensitive user data stored by the database server **408**. In other arrangements, the data exit entity **416** can be a computing system that includes a local software application that allows a user to request sensitive user data stored by the database server **408**. In the illustrated arrangement, the data exit entity **416** includes a user input/output device **576**, a network interface **580**, a memory **584**, and a processing circuit **586**. The processing circuit **586**

includes a message generation circuit **588**, a data decryption circuit **592**, and an authentication circuit **596**. The user input/output device **576**, the network interface **580**, the memory **584**, the message generation circuit **588**, and the authentication circuit **596** are substantially similar to the user input/output device **576**, the network interface **280**, the memory **584**, the message generation circuit **288**, and the authentication circuit **296**, respectively, of the data exit entity **116** described above and are not discussed in detail herein.

[0112] As shown in FIG. 5C, the memory **584** is communicably and operatively coupled with the other components of the data exit entity **416**. The memory **584** includes a key database **598**. The key database **598** includes a public/private key pair. The key database **598** further includes one or more second named CEKs **534**. The key database **598** includes a name that corresponds to each of the one or more second named CEKs **534**.

[0113] In some arrangements, the user of the data exit entity **416** may request more than one piece of sensitive user data. In such an arrangement, the data request message includes all of the pieces of requested user data. In some arrangements, the user may request that one or more pieces of sensitive user data are shared with more than one data exit entity **416**. In such an arrangement, the data request message includes all of the pieces of requested user data and information indicative of the identities of the data exit entities **416** to which each piece of sensitive user data should be sent.

[0114] The message generation circuit **588** is substantially similar to the message generation circuit **288** described above with respect to the data exit entity **116**. However, the message generation circuit **588** is further configured to include a name of the second named CEK **534** in the data request message. In some arrangements, the data request message includes both the name of the second named CEK **534** and the information indicative of the identity of the data exit entity **416**.

[0115] The data decryption circuit **592** is configured to undergo a PKC agreement protocol with the key manager **412**. During the PKC agreement protocol with the key manager **412**, the data decryption circuit **592** and the key manager **412** (e.g., the encryption circuit **562**) exchange public keys and compute the shared secret **542**. The data decryption circuit **592** is configured to obfuscate the shared secret **542** and store the obfuscated shared secret **542** in the memory **584**. In some arrangements, the PKC agreement protocol can be a Diffie-Hellman protocol, an elliptic curve Diffie-Hellman protocol, another post-quantum cryptography protocol, etc. The data encryption circuit **520** is configured to derive a CEK from the shared secret **542**. The one of the data decryption circuit **592** or the key manager **412** is configured to generate a name for the CEK (e.g., the second named CEK **534**) and transmit the name to the other of the data encryption circuit **520** and the key manager **412**. The data decryption circuit **592** stores the second named CEK **534** and the name of the second named CEK **534** to the key database **598** of the memory **584**. In arrangements in which the system **400** includes one or more key managers **412**, the data decryption circuit **592** is configured to undergo a PKC agreement protocol with one or more of the key managers **412** in the system **400**.

[0116] The data decryption circuit **592** of the data exit entity **416** is configured to receive the second encrypted user data from the database server **408**. In some arrangements, the database server **108** is configured to transmit the second encrypted user data over a secure connection. Since the second encrypted user data is transmitted by the database server **408**, the cleartext sensitive user data is not visible at the entrance or the exit of the secure connection.

[0117] The data decryption circuit **592** is configured to recover the cleartext sensitive user data by decrypting the second encrypted user data using the second named CEK **534**. The data decryption circuit **592** is configured to display the cleartext sensitive user data via the output interface of the user input/output device **576**. For example, the data decryption circuit **592** can display the sensitive user data on a window of a software application run on a browser of the data exit entity **416** or running locally on the data exit entity **416**.

[0118] In arrangements in which the user of the data exit entity **416** requests multiple pieces of sensitive user data, the data decryption circuit **292** decrypts each piece of second encrypted user

data and displays each piece of cleartext sensitive user data as described above.

[0119] Referring now to FIGS. 6A-6B, a flow diagram of a method **600** for protecting sensitive user data that is received by a data entry entity, stored by a database server, and displayed by a data exit entity that may be administered by third parties is shown, according to an example arrangement. Blocks that are similar to blocks described with respect to FIGS. 3A-3C are not described in greater detail herein. At **602**, the authentication circuit **524** validates the certificate of the key manager **412** similar to what is described in greater detail with respect to block **302** above. At **604**, the data encryption circuit **520** prompts or requests the user to enter user data into the data entry entity **404** similar to what is described in greater detail with respect to block **304** above. At **606**, the data encryption circuit **520** of the data entry entity **404** determines that the user data is sensitive user data similar to what is described in greater detail with respect to block **306** above. [0120] At **608**, the data encryption circuit **520** undergoes a PKC agreement protocol with the key manager **412**. During the PKC agreement protocol, the data encryption circuit **520** and the key manager **412** exchange public keys and compute a shared secret **526**. In some arrangements, the PKC agreement protocol can be a Diffie-Hellman protocol, an elliptic curve Diffie-Hellman protocol, another post-quantum cryptography protocol, etc. At **610**, the data encryption circuit **520** derives a CEK from the shared secret **526**. At **612**, the data encryption circuit **520** or the key manager **412** generate a name for the CEK (e.g., the first named CEK **530**) and transmits the name to the other of the data encryption circuit **520** and the key manager **412**. The data encryption circuit **520** saves the first named CEK **530** to the memory **584** and the key manager **412** saves the first named CEK **530** to the memory **556**.

[0121] At **614**, the data encryption circuit **520** generates encrypted user data by encrypting the sensitive user data with the first named CEK **530**. At **616**, the data encryption circuit **520** tags the encrypted user data and the name of the first named CEK **530** with a tag that is readable by the database server **408**. In some arrangements, the tag is a cleartext tag. The tag can include information indicative of the encrypted user data. For example, the information indicative of the encrypted user data can include information indicative of a type of user data corresponding to the encrypted user data and/or information indicative of an identity of a user corresponding to the encrypted user data. In some arrangements, the name of the first named CEK **530** is included in the tag. At **618**, the data encryption circuit **520** transmits the encrypted user data and the name of the first named CEK **530** to the database server **408**. In arrangements in which the data encryption circuit **520** determines that the data entry entity **404** has received multiple pieces of sensitive user data, the data encryption circuit **520** repeats blocks **610-618** for each piece of sensitive user data. [0122] At **620**, the database server **408** receives the encrypted user data and the name of the first named CEK **530** from the data entry entity **404** over the secure connection. At optional block **622**, the database server **408** transmits a message to the data entry entity **404** indicating that the database server **408** has received the encrypted user data and the name of the first named CEK **530**. At optional block **624**, the data entry entity **404** destroys the cleartext sensitive user data in response to receiving a message from the database server **408** indicating that the database server **408** has received the encrypted user data and the name of the first named CEK **530**. At **626**, the database server **408** saves the encrypted user data and the name of the first named CEK **530** to the user information database **544** of the memory **536**.

[0123] At **628**, the message generation circuit **588** of the data exit entity **416** receives a request for sensitive user data input by a user using the user input/output device **576**. At **630**, the authentication circuit **596** of the data exit entity **416** validates the certificate of the data exit entity **416** as is described in greater detail with respect to block **328** above.

[0124] At **632**, the message generation circuit **588** determines information indicative of the requested user data based on the request for sensitive user data input by the user of the data exit entity **416**. The information indicative of the requested user data can include information indicative of a type of user data (e.g., social security number, account number, address, birth date, biometric,

etc.) and/or information indicative of an identity of the user (e.g., a name, a reference number, etc.). At **634**, the message generation circuit **588** generates a data request message including the information indicative of the requested user data, the name of the second named CEK **534**, and/or information indicative of the identity of the data exit entity **416**. The information indicative of the identity of the data exit entity **416** can include an IP address, an IMEI number, an instance of a software application running on the data exit entity **416** or a browser running on the data exit entity **416**, etc. At **636**, the message generation circuit **588** transmits the data request message to the database server **408** over a secure connection.

[0125] At **638**, the data identification circuit **540** receives the data request message from the data exit entity **416**. The data request message includes information indicative of the requested user data requested by the data exit entity **416** and the name of the second named CEK **534**, and/or information indicative of the identity of the data exit entity **416**. At **640**, the data identification circuit **540** identifies the encrypted user data that corresponds to the requested user data based on the tag. For example, the data identification circuit **240** can compare the information indicative of the requested user data to the information indicative of the encrypted user data in the tag to identify the encrypted user data that matches the requested user data. The data identification circuit **540** never decrypts or reads the cleartext sensitive user data. At **642**, the data identification circuit **540** retrieves the encrypted user data that matches the requested user data. At **644**, the data identification circuit **540** transmits the encrypted user data, the name of the first named CEK **530** corresponding to the requested user data, and the name of the second named CEK **534** and/or the information indicative of the identity of the data exit entity **416** to the key manager **412**. At **646**, the data identification circuit **540** logs each piece of encrypted user data sent to the key manager **412** and the information indicative of the data exit entity **416** requesting the encrypted user data sent to the key manager **412**. In some arrangements, the data request message can include one or more pieces of requested user data. In such arrangements, data identification circuit **540** repeats blocks **632-646** for each piece of requested user data. As described herein, the database server **408** excludes the shared secret **526**, the first named CEKs **530**, and the second named CEKs **534**. Therefore, the database server **408** cannot decrypt the encrypted user data to recover the cleartext sensitive user data.

[0126] At **648**, the translation circuit **560** of the key manager **412** receives the encrypted user data corresponding to the requested user data, the name of the first named CEK **530**, the name of the second named CEK **534** and/or the information indicative of the identity of the data exit entity **416**. At **650**, the translation circuit **560** identifies the certificate for the data exit entity **416** based on the information indicative of the identity of the data exit entity **416**. At **652**, the authentication circuit **564** validates the certificate of the data exit entity **416** similar to what is described in greater detail above with respect to block **350**. In response to determining that the data exit entity certificate is valid, the authentication circuit **264** allows translation of the encrypted user data. In response to determining that the data exit entity certificate is invalid, the authentication circuit **264** prevents translation of the encrypted user data.

[0127] At **654**, the translation circuit **560** recovers the first named CEK **530** based on the name of the first named CEK **530** and the shared secret **526** established between the data entry entity **404** and the key manager **412**. At **656**, the translation circuit **560** recovers the cleartext sensitive user data by decrypting the encrypted user data with the first named CEK **530**. At **658**, the translation circuit **560** recovers the second named CEK **534** based on the name of the second named CEK **534** and the shared secret **542** established between the data exit entity **416** and the key manager **412**. At **660**, the translation circuit generates second encrypted user data by encrypting the cleartext sensitive user data with the second named CEK **534**. At **662**, the translation circuit **260** transmits the second encrypted user data and the information indicative of the identity of the data exit entity **416** to the database server **408**. At **662**, the translation circuit **560** logs information indicative of each piece of encrypted user data that has been translated and the information indicative of the

identity of each data exit entity **416** requesting translation of each piece of encrypted user data in the data translation log **572**.

[0128] At **666**, the data identification circuit **540** of the database server **408** receives the second encrypted user data and the information indicative of the identity of the data exit entity **416**. At **668**, the data identification circuit **540** transmits the encrypted user data to the data exit entity **416** over a secure connection.

[0129] At **670**, the data decryption circuit **592** of the data exit entity **416** receives the second encrypted user data from the database server **408** over the secure connection. Since the second encrypted user data is encrypted, the cleartext sensitive user data is not visible at the entrance and the exit ends of the secure connection. At **672**, the data decryption circuit **592** recovers the second named CEK **534** based on the name of the second CEK **534** and the shared secret **542**. At **674**, the data decryption circuit **592** recovers the cleartext sensitive user data by decrypting the second encrypted user data with the second named CEK **534**. At **672**, the data decryption circuit **592** displays the cleartext sensitive user data to the user of the data exit entity **416**. For example, the data decryption circuit **592** can display the cleartext sensitive user data on a window of a software application run on a browser of the data exit entity **416** or running locally on the data exit entity **416**.

[0130] In some arrangements, the user may request more than one piece of sensitive user data. In such an arrangement, the data request message includes all of the pieces of requested user data. The data exit entity **416** repeats blocks **668-672** for each piece of requested data. In some arrangements, the user may request that one or more pieces of sensitive user data are shared with more than one data exit entity **416**. In such an arrangement, the data request message includes all of the pieces of requested user data and information indicative of the identities of the data exit entities **416** to which each piece of sensitive user data should be sent. Each of the data exit entities **416** then completes blocks **668-672** for each piece of encrypted user data received.

[0131] Although the systems **100** and **400** are described separately, some arrangements may combine features of each system. For example, a system may include one or more data entry entities **104** that encrypt sensitive user data with a CEK and send the encrypted user data and the encrypted CEK to a database server described above with respect to the data entry entity **104**. This system may include one or more data exit entities **416** that decrypt and display sensitive user data using a named CEK that is based on a shared secret established with the key manager via a PKC protocol as described above with respect to the system **400**. The database server and the key manager of this arrangement combine features of the database servers **108**, **408** and the key managers **112**, **412**, respectively, as described in greater detail below. In such an arrangement, in response to determining that the encrypted user data has been encrypted by a CEK and that the data message request includes a name of a second named CEK, the data identification circuit of the database server is configured to send both the encrypted user data and the encrypted CEK to the key manager as described above with respect to the database server **108**. In such arrangements, the key manager is configured to operate as described above with respect to the key manager **112** when decrypting the encrypted CEK. However, the translation circuit of the key manager is further configured to decrypt the encrypted user data to recover the cleartext sensitive user data. The key manager is then configured to recover the second named CEK based on the name of the second CEK sent in the data request message as described above with respect to the key manager **412**. The key manager is configured to encrypt the cleartext sensitive user data with the second named CEK as described above with respect to the key manager **412** to generate the second encrypted user data that the data exit entity **416** can decrypt. The key manager is configured to send the second encrypted user data to the database server as described above with respect to the key manager **412**.

[0132] In another example, a system may include one or more data entry entities **404** as described above with respect to the system **400**. The one or more data entry entities **404** generate a shared secret with the key manager via a PKC protocol and then derive a named CEK from the shared

secret as described above with respect to the system **400**. The one or more data entry entities **404** then encrypt each piece of sensitive user data using the named CEK. This system may include one or more data exit entities **116** that receive second encrypted data that has been encrypted with a CEK that has been encrypted with the private key of each of the one or more data exit entities **116**. The database server and the key manager of this arrangement combine features of the database servers **108, 408** and the key managers **112, 412**, respectively, as described in greater detail below. In such an arrangement, the data identification circuit of the database server receives the data request message, retrieves the encrypted user data corresponding to the requested user data based on the tag, and sends the encrypted user data, the name of the first named CEK, and the information indicative of the identity of the data exit entity **116** as described with respect to the database server **408**. The key manager is configured to recover the first named CEK based on the shared secret previously established between the key manager **412** and the data entry entity **404** as described above with respect to the system **400**. In response to determining, based on the information indicative of the identity of the data exit entity **116**, that the key database includes a public key corresponding to the data exit entity **116**, the key manager is configured to generate a CEK as described above with respect to the data entry entity **104**. The key manager is configured to encrypt the cleartext sensitive user data with the CEK as described above with respect to the data entry entity **104** to generate second encrypted user data. The key manager is configured to encrypt the CEK with the public key **261** of the data exit entity **116** as described above with respect to the key manager **112**. The key manager is then configured to send the second encrypted user data and the encrypted CEK to the database server or send the second encrypted user data and the encrypted CEK to the data exit entity **116**. The data exit entity **116** can decrypt the encrypted CEK using its private key to recover the cleartext CEK and decrypt the second encrypted user data using the cleartext CEK as described above.

[0133] In some arrangements, the data entry entity includes the functionality of the data entry entity **104** as described above with respect to the system **100** and the functionality of the data entry entity **404** as described above with respect to the system **400**. Such a data entry entity can communicate with database servers **108** as described with respect to the system **100** and database servers **408** as described with respect to the system **400**. In such an arrangement, when used with the database server **108** and the key manager **112**, the database server **108** may send a message instructing the data entry entity to use the protocol of system **100**. When used with the database server **408** and the key manager **412**, the database server **408** may send a message instructing the data entry entity to use the protocol of system **400**.

[0134] In some arrangements, the data exit entity includes the functionality of the data exit entity **116** as described above with respect to the system **100** and the functionality of the data exit entity **416** as described above with respect to the system **400**. Such a data exit entity can communicate with database servers **108** as described with respect to the system **100** and database servers **408** as described with respect to the system **400**. In such an arrangement, when used with the database server **108** and the key manager **112**, the database server **108** may send a message instructing the data exit entity to use the protocol of system **100**. When used with the database server **408** and the key manager **412**, the database server **408** may send a message instructing the data exit entity to use the protocol of system **400**.

[0135] In some arrangements, the system **100** and/or the system **400** can be used to manage sensitive user data involved in real estate transactions. In such an arrangement, the data entry entity **104, 404** can include computing devices operated by real estate attorneys, bank employees, property appraisers, real estate agents, etc. The sensitive user data can include information such as a home owner and/or prospective home buyer's name, social security number, address, credit score, income, etc. The operators of the data entry entities **104, 404** have been authorized by an entity such as a bank providing a mortgage for the transaction. After authorization, the bank can send the key manager certificate to the data entry entity **104, 404** operated by the authorized operator. The

operator of the data entry entity **104, 404** can input this sensitive user data into a software program run on a browser of the data entry entity **104, 404**. The software program can identify the data entered by the operator of the data entry entity **104, 404** as sensitive user data, encrypt the sensitive user data as described above with respect to the data entry entities **104, 404**, and send the encrypted user data to the database server **108, 408**. In such an arrangement, the database server **108, 408** can be a cloud-based database stored in a cloud network. The database server **108, 408** can be operated by a third party (e.g., the database server is not managed by the data owner or the data receiver). As described above with respect to the systems **100, 400**, the database server **108, 408** cannot decrypt the encrypted user data. The key manager **112, 412** may be administered by the bank providing the mortgage.

[0136] In such an arrangement, the data exit entity **116, 416** can include computing devices operated by real estate attorneys, bank employees, property appraisers, real estate agents, etc. that need to gain access to the sensitive user data. The operators of the data exit entities **116, 416** have been authorized by an entity such as a bank providing a mortgage for the transaction. After authorization, the bank can send the key manager certificate to the data exit entity **116, 416** operated by the authorized operator and the data exit entity **116, 416** can send its certificate to the key manager **112, 412**. The operator of the data exit entity **116, 416** can input information indicative of requested user data into a software program run on a browser of the data exit entity **116, 416**. The data exit entity **116, 416**, can generate a data request message based on the information indicative of the requested user data and send the data request message to the database server **108, 408**. In some arrangements, the data exit entity **116** can receive second encrypted user data and an encrypted CEK encrypted with the public key **261** of the data exit entity **116**. The data exit entity **116** can decrypt the encrypted CEK using its private key to generate the cleartext CEK, decrypt the second encrypted user data with the cleartext CEK to recover the cleartext data, and display the cleartext sensitive user data to the operator of the data exit entity **116** as described above with respect to the data exit entity **116**. In other arrangements, the data exit entity **416** can receive second encrypted user data encrypted with the second named CEK. The data exit entity **416** can recover the second named CEK based on the shared secret generated between the key manager **412** and the data exit entity **416** and the name of the second named CEK. The data exit entity **416** can decrypt the second encrypted user data using the second named CEK to recover the cleartext sensitive user data, and display the cleartext sensitive user data to the operator of the data exit entity **416** as described above with respect to the data exit entity **416**.

[0137] In some arrangements, the system **100** and/or the system **400** can be used to manage sensitive user data involved in healthcare. In such an arrangement, the data entry entity **104, 404** can include computing devices operated by healthcare professionals such as doctors, nurses, nursing assistants, etc. The sensitive user data can include information such as a patient's name, social security number, test results, medical history information, etc. The operators of the data entry entities **104, 404** have been authorized by an entity such as the patient's insurance company or a healthcare provider network. After authorization, the insurance company or the healthcare system can send the key manager certificate to the data entry entity **104, 404** operated by the authorized operator. The operator of the data entry entity **104, 404** can input this sensitive user data into a software program run on a browser of the data entry entity **104, 404**. The software program can identify the data entered by the operator of the data entry entity **104, 404** as sensitive user data, encrypt the sensitive user data as described above with respect to the data entry entities **104, 404**, and send the encrypted user data to the database server **108, 408**. In such an arrangement, the database server **108, 408** can be a cloud-based database stored in a cloud network. The database server **108, 408** can be operated by a third party (e.g., the database server is not managed by the data owner or the data receiver). As described above with respect to the systems **100, 400**, the database server **108, 408** cannot decrypt the encrypted user data. The key manager **112, 412** may be administered by the insurance company or the healthcare provider network.

[0138] In such an arrangement, the data exit entity **116, 416** can include computing devices operated by insurance company employees or employees of the healthcare network different than the employees that operate the data entry entity **104, 404** that need to gain access to the sensitive user data. The operators of the data exit entities **116, 416** have been authorized by an entity such as the insurance company or the healthcare network. After authorization, the insurance company or healthcare network can send the key manager certificate to the data exit entity **116, 416** operated by the authorized operator and the data exit entity **116, 416** can send its certificate to the key manager **112, 412**. The operator of the data exit entity **116, 416** can input information indicative of requested user data into a software program run on a browser of the data exit entity **116, 416**. The data exit entity **116, 416**, can generate a data request message based on the information indicative of the requested user data and send the data request message to the database server **108, 408**. In some arrangements, the data exit entity **116** can receive second encrypted user data and an encrypted CEK encrypted with the private key of the data exit entity **116**. The data exit entity **116** can decrypt the encrypted CEK using its private key to generate the cleartext CEK, decrypt the second encrypted user data with the cleartext CEK to recover the cleartext sensitive user data, and display the cleartext sensitive user data to the operator of the data exit entity **116** as described above with respect to the data exit entity **116**. The operator of the data exit entity **116** can use the displayed sensitive user data to process insurance claims, review a patient's health history, etc. In other arrangements, the data exit entity **416** can receive second encrypted user data encrypted with the second named CEK. The data exit entity **416** can recover the second named CEK based on the shared secret generated between the key manager **412** and the data exit entity **416** and the name of the second named CEK. The data exit entity **416** can decrypt the second encrypted user data using the second named CEK to recover the cleartext sensitive user data, and display the cleartext sensitive user data to the operator of the data exit entity **416** as described above with respect to the data exit entity **416**. The operator of the data exit entity **416** can use the displayed sensitive user data to process insurance claims, review a patient's health history, etc.

[0139] The arrangements described herein have been described with reference to drawings. The drawings illustrate certain details of specific arrangements that implement the systems, methods and programs described herein. However, describing the arrangements with drawings should not be construed as imposing on the disclosure any limitations that may be present in the drawings.

[0140] It should be understood that no claim element herein is to be construed under the provisions of 35 U.S.C. § 112(f), unless the element is expressly recited using the phrase “means for.”

[0141] As used herein, the term “circuit” may include hardware configured to execute the functions described herein. In some arrangements, each respective “circuit” may include machine-readable media for configuring the hardware to execute the functions described herein. The circuit may be embodied as one or more circuitry components including, but not limited to, processing circuitry, network interfaces, peripheral devices, input devices, output devices, sensors, etc. In some arrangements, a circuit may take the form of one or more analog circuits, electronic circuits (e.g., integrated circuits (IC), discrete circuits, system on a chip (SOCs) circuits, etc.), telecommunication circuits, hybrid circuits, and any other type of “circuit.” In this regard, the “circuit” may include any type of component for accomplishing or facilitating achievement of the operations described herein. For example, a circuit as described herein may include one or more transistors, logic gates (e.g., NAND, AND, NOR, OR, XOR, NOT, XNOR, etc.), resistors, multiplexers, registers, capacitors, inductors, diodes, wiring, and so on).

[0142] The “circuit” may also include one or more processors communicatively coupled to one or more memory or memory devices. In this regard, the one or more processors may execute instructions stored in the memory or may execute instructions otherwise accessible to the one or more processors. In some arrangements, the one or more processors may be embodied in various ways. The one or more processors may be constructed in a manner sufficient to perform at least the operations described herein. In some arrangements, the one or more processors may be shared by

multiple circuits (e.g., circuit A and circuit B may comprise or otherwise share the same processor which, in some example arrangements, may execute instructions stored, or otherwise accessed, via different areas of memory). Alternatively or additionally, the one or more processors may be configured to perform or otherwise execute certain operations independent of one or more co-processors. In other example arrangements, two or more processors may be coupled via a bus to enable independent, parallel, pipelined, or multi-threaded instruction execution. Each processor may be implemented as one or more general-purpose processors, application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), digital signal processors (DSPs), or other suitable electronic data processing components configured to or execute instructions provided by memory. The one or more processors may take the form of a single core processor, multi-core processor (e.g., a dual core processor, triple core processor, quad core processor, etc.), microprocessor, etc. In some arrangements, the one or more processors may be external to the apparatus, for example the one or more processors may be a remote processor (e.g., a cloud based processor). Alternatively or additionally, the one or more processors may be internal and/or local to the apparatus. In this regard, a given circuit or components thereof may be disposed locally (e.g., as part of a local server, a local computing system, etc.) or remotely (e.g., as part of a remote server such as a cloud based server). To that end, a “circuit” as described herein may include components that are distributed across one or more locations.

[0143] An exemplary system for implementing the overall system or portions of the arrangements might include a general purpose computing computers in the form of computers, including a processing unit, a system memory, and a system bus that couples various system components including the system memory to the processing unit. Each memory device may include non-transient volatile storage media, non-volatile storage media, non-transitory storage media (e.g., one or more volatile and/or non-volatile memories), a distributed ledger (e.g., a blockchain), etc. In some arrangements, the non-volatile media may take the form of ROM, flash memory (e.g., flash memory such as NAND, 3D NAND, NOR, 3D NOR, etc.), EEPROM, MRAM, magnetic storage, hard discs, optical discs, etc. In other arrangements, the volatile storage media may take the form of RAM, TRAM, ZRAM, etc. Combinations of the above are also included within the scope of machine-readable media. In this regard, machine-executable instructions comprise, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions. Each respective memory device may be operable to maintain or otherwise store information relating to the operations performed by one or more associated circuits, including processor instructions and related data (e.g., database components, object code components, script components, etc.), in accordance with the example arrangements described herein.

[0144] It should also be noted that the term “input devices,” as described herein, may include any type of input device including, but not limited to, a keyboard, a keypad, a mouse, joystick or other input devices performing a similar function. Comparatively, the term “output device,” as described herein, may include any type of output device including, but not limited to, a computer monitor, printer, facsimile machine, or other output devices performing a similar function.

[0145] Any foregoing references to currency or funds are intended to include fiat currencies, non-fiat currencies (e.g., precious metals), and math-based currencies (often referred to as cryptocurrencies). Examples of math-based currencies include Bitcoin, Ethereum, Ripple, Litecoin, and the like.

[0146] It should be noted that although the diagrams herein may show a specific order and composition of method blocks, it is understood that the order of these blocks may differ from what is depicted. For example, two or more blocks may be performed concurrently or with partial concurrence. Also, some method blocks that are performed as discrete blocks may be combined, blocks being performed as a combined block may be separated into discrete blocks, the sequence of certain processes may be reversed or otherwise varied, and the nature or number of discrete

processes may be altered or varied. The order or sequence of any element or apparatus may be varied or substituted according to alternative arrangements. Accordingly, all such modifications are intended to be included within the scope of the present disclosure as defined in the appended claims. Such variations will depend on the machine-readable media and hardware systems chosen and on designer choice. It is understood that all such variations are within the scope of the disclosure. Likewise, software and web arrangements of the present disclosure could be accomplished with standard programming techniques with rule based logic and other logic to accomplish the various database searching blocks, correlation blocks, comparison blocks and decision blocks.

[0147] The foregoing description of arrangements has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure to the precise form disclosed, and modifications and variations are possible in light of the above teachings or may be acquired from this disclosure. The arrangements were chosen and described in order to explain the principals of the disclosure and its practical application to enable one skilled in the art to utilize the various arrangements and with various modifications as are suited to the particular use contemplated. Other substitutions, modifications, changes and omissions may be made in the design, operating conditions and arrangement of the arrangements without departing from the scope of the present disclosure as expressed in the appended claims.

Claims

1. A data storage and translation computing system comprising: a key manager comprising a processing circuit and a memory storing a public/private key pair and a public key of a data exit entity, the processing circuit configured to: receive a first encrypted content encryption key (CEK) and information indicative of a requestor identity of a requestor; identify a public key of the requestor based on the information indicative of the requestor identity; recover a CEK by decrypting the first encrypted CEK using a private key of the key manager; generate a second encrypted CEK that is decryptable by the requestor by encrypting the CEK using the public key of the requestor; and transmit the second encrypted CEK to a database server, wherein the database server being configured to receive encrypted user data and the first encrypted CEK from a data entry entity, restricted from the private key of the key manager, and restricted from decrypting the encrypted user data.
2. The data storage and translation computing system of claim 1, wherein the key manager omits any of the encrypted user data.
3. The data storage and translation computing system of claim 1, wherein the database server is further configured to generate a CMS SignedData message wrapper around the encrypted user data and the second encrypted CEK.
4. The data storage and translation computing system of claim 1, wherein the database server is further configured to generate a CMS SigncryptedData message wrapper around the encrypted user data and the second encrypted CEK.
5. The data storage and translation computing system of claim 1, wherein the key manager is in a hardware security module (HSM), wherein the HSM is loaded into a host of the database server, and wherein the key manager and the database server reside on a single network node.
6. The data storage and translation computing system of claim 1, wherein the requestor is a data exit entity that comprises a processing circuit and a memory storing the public key and a private key, and the processing circuit of the data exit entity is configured to generate, based on a request received from a user of the data exit entity, a data request message comprising information indicative of the user data and information indicative of the identity of the data exit entity.
7. The data storage and translation computing system of claim 6, wherein the processing circuit of the data exit entity is configured to: transmit the data request message to the database server;

receive the encrypted user data and the second encrypted CEK; recover the CEK by decrypting the second encrypted CEK using the private key; recover the user data by decrypting the encrypted user data using the CEK; and display the user data to the user of the data exit entity.

8. A method, comprising: receiving, a key manager comprising a processing circuit and a memory storing a public/private key pair and a public key of a data exit entity, a first encrypted content encryption key (CEK) and information indicative of a requestor identity of a requestor; identifying, by the key manager, a public key of the requestor based on the information indicative of the requestor identity; recovering, by the key manager, a CEK by decrypting the first encrypted CEK using a private key of the key manager; generating, by a key manager, a second encrypted CEK that is decryptable by the requestor by encrypting the CEK using the public key of the requestor; and transmitting, by the key manager, the second encrypted CEK to a database server, wherein the database server being configured to receive encrypted user data and the first encrypted CEK from a data entry entity, restricted from the private key of the key manager, and restricted from decrypting the encrypted user data.

9. The method of claim 8, wherein a key manager omits any of the encrypted user data.

10. The method of claim 8, wherein the database server is further configured to generate a CMS SignedData message wrapper around the encrypted user data and the second encrypted CEK.

11. The method of claim 8, wherein the database server is further configured to generate a CMS SigncryptedData message wrapper around the encrypted user data and the second encrypted CEK.

12. The method of claim 8, wherein a key manager is in a hardware security module (HSM), wherein the HSM is loaded into a host of the database server, and wherein the key manager and the database server reside on a single network node.

13. The method of claim 8, wherein the requestor is the data exit entity that comprises a processing circuit and a memory storing the public key and a private key, and the processing circuit of the data exit entity is configured to generate, based on a request received from a user of the data exit entity, a data request message comprising information indicative of the user data and information indicative of the identity of the data exit entity.

14. The method of claim 13, wherein the processing circuit of the data exit entity is configured to: transmit the data request message to the database server; receive the encrypted user data and the second encrypted CEK; recover the CEK by decrypting the second encrypted CEK using the private key; recover the user data by decrypting the encrypted user data using the CEK; and display the user data to the user of the data exit entity.

15. At least one non-transitory computer-readable medium of key manager comprising computer-readable instructions, such that, when executed, causes at least one processor of the key manager to: receive a first encrypted content encryption key (CEK) and information indicative of a requestor identity of a requestor; identify a public key of the requestor based on the information indicative of the requestor identity; recover a CEK by decrypting the first encrypted CEK using a private key of the key manager; generate a second encrypted CEK that is decryptable by the requestor by encrypting the CEK using the public key of the requestor; and transmit the second encrypted CEK to a database server, wherein the database server being configured to receive encrypted user data and the first encrypted CEK from a data entry entity, restricted from the private key of the key manager, and restricted from decrypting the encrypted user data, wherein the memory of the key manager stores a public/private key pair and a public key of a data exit entity, the processing circuit configured.

16. The non-transitory computer-readable medium of claim 15, wherein the key manager omits any of the encrypted user data.

17. The non-transitory computer-readable medium of claim 15, wherein the database server is further configured to generate a CMS SignedData message wrapper around the encrypted user data and the second encrypted CEK.

18. The non-transitory computer-readable medium of claim 15, wherein the database server is

further configured to generate a CMS SigncryptedData message wrapper around the encrypted user data and the second encrypted CEK.

19. The non-transitory computer-readable medium of claim 15, wherein the key manager is in a hardware security module (HSM), wherein the HSM is loaded into a host of the database server, and wherein the key manager and the database server reside on a single network node.

20. The non-transitory computer-readable medium of claim 15, wherein the requestor is a data exit entity that comprises a processing circuit and a memory storing the public key and a private key, and the processing circuit of the data exit entity is configured to generate, based on a request received from a user of the data exit entity, a data request message comprising information indicative of the user data and information indicative of the identity of the data exit entity.
