

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409545
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Chang; Chi-Tsai

Tool holder rail and tool holder including the same

Abstract

A tool holder rail and a tool holder including the same are provided, wherein the tool holder rail includes: an elongate main body extending in a longitudinal direction and including two mounting sides extending in the longitudinal direction, the two mounting sides being inclined to each other with an included angle therebetween; and two rail slots disposed on the two mounting sides, respectively, each of the two rail slots including two flanges extending in the longitudinal direction and toward each other, each of the two rail slots being configured for slidable engagement of a tool seat.

Inventors:	Chang; Chi-Tsai (Taichung, TW)
Applicant:	CHUN NIEN PLASTIC LTD. (Taichung, TW)
Family ID:	92074652
Assignee:	CHUN NIEN PLASTIC LTD. (Taichung, TW)
Appl. No.:	18/496187
Filed:	October 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250135627 A1	May. 01, 2025

Publication Classification

Int. Cl.: B25H3/00 (20060101)

U.S. Cl.:

CPC B25H3/003 (20130101);

Field of Classification Search

CPC: B25H (3/003); B25H (3/04); B25H (3/02)

USPC: 224/401; 211/113; 211/70.6; 211/13.1; 211/4; 211/94.01; 206/372; 206/378; 206/349; 206/806; 206/493; 206/376; 206/379; 206/1.5

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3239069	12/1965	Hollins	206/385	A47K 5/02
3408758	12/1967	Doring	40/310	B65D 73/0035
4905829	12/1989	Stribiak	206/349	A45C 11/24
5147038	12/1991	Pergeau	206/564	B25H 3/06
5228570	12/1992	Robinson	81/177.85	B25B 13/56
5255795	12/1992	Kitmitto	211/DIG.1	B25H 1/00
5388338	12/1994	Majors	33/376	E04F 21/241
5405025	12/1994	Melrose	211/13.1	B25H 3/06
5649625	12/1996	Ovadia	206/493	A47F 7/02
5715951	12/1997	Dembicks	206/378	B25B 13/56
5862913	12/1998	Chou	206/378	A47F 5/0823
6032797	12/1999	Kao	206/349	B25H 3/04
6092655	12/1999	Ernst	206/378	B25H 3/06
6168018	12/2000	Ramsey	206/378	B25H 3/06
6386363	12/2001	Huang	206/378	B25H 3/003
6431373	12/2001	Blick	206/378	B25H 3/003
6450338	12/2001	Chen	206/378	B25H 3/003
6571966	12/2002	Hsiao	206/379	A47F 7/0028
6886791	12/2004	Detorre	211/94.01	B63B 32/83
7066339	12/2005	Chiu	211/183	A47F 5/0807
7108132	12/2005	Shih	206/459.1	B25H 3/003
7118406	12/2005	Mu	211/70.6	H01R 25/142
7360654	12/2007	Liu	206/754	B25H 3/003
7658284	12/2009	Lin	221/70	B25H 3/003
7677391	12/2009	Pistor	206/372	B25H 3/003
7717278	12/2009	Kao	206/349	B25H 3/04
8307980	12/2011	Kao	206/378	B25H 3/04
8336709	12/2011	Geibel	206/378	B25H 3/06
8387791	12/2012	Huang	206/378	B25H 3/022
8397912	12/2012	Chen	206/379	B25H 3/003
8469190	12/2012	Chang	206/375	B25H 3/003
8499935	12/2012	Hsieh	206/349	B25H 3/04
8622369	12/2013	Kania	254/2B	B66F 5/04
9126329	12/2014	Kao	N/A	F16M 13/022
9138890	12/2014	Lee	N/A	B25H 3/003
9186790	12/2014	Kao	N/A	B25H 3/003
9527206	12/2015	Hsieh	N/A	B25H 3/04
9528303	12/2015	Lai	N/A	A47F 5/0861

9757853	12/2016	Su	N/A	B25H 3/04
9937615	12/2017	Winnard	N/A	B25H 3/04
10022857	12/2017	Kao	N/A	B25H 3/04
10040189	12/2017	Kao	N/A	A47F 7/0028
10272547	12/2018	Lai	N/A	B25B 13/06
10589416	12/2019	Hsieh	N/A	F16B 2/22
10675750	12/2019	Winnard	N/A	G09F 3/02
11091778	12/2020	Winnard	N/A	A61K 39/12
11298813	12/2021	Lelonek	N/A	B25H 5/00
11358271	12/2021	Chang	N/A	B25H 3/003
11389945	12/2021	Kao	N/A	B25H 3/04
11453113	12/2021	Hsieh	N/A	B25H 3/06
11623811	12/2022	Buhl	206/522	B65D 81/052
11667029	12/2022	Hsieh	206/372	B25H 3/04
11813730	12/2022	Chang	N/A	B25H 3/04
11850725	12/2022	Chang	N/A	B25H 3/003
11999047	12/2023	Lin	N/A	B25H 3/003
2001/0001197	12/2000	Ramsey	206/378	B25H 3/06
2004/0188366	12/2003	Tong	206/378	B25H 3/003
2005/0103664	12/2004	Shih	206/378	B25B 13/56
2005/0126943	12/2004	Liu	206/349	B65D 73/0064
2005/0218023	12/2004	Winnard	206/378	B25H 3/003
2005/0221664	12/2004	Winnard	439/510	B25H 3/003
2006/0070903	12/2005	Chiang	206/378	B25H 3/06
2006/0219647	12/2005	Shih	211/70.6	B25H 3/003
2006/0234846	12/2005	Tucker	483/26	B25H 3/04
2006/0254940	12/2005	Mu	206/378	B25H 3/003
2007/0017886	12/2006	Kao	211/94.01	A47F 7/0028
2008/0314949	12/2007	Wang	224/666	A45F 5/02
2009/0001111	12/2008	Lin	224/245	B25H 3/003
2009/0166305	12/2008	Hsieh	211/70.6	A47F 7/0028
2009/0211932	12/2008	Schmitt	206/373	B25H 3/003
2009/0218302	12/2008	Winnard	211/70.6	B25H 3/003
2010/0072094	12/2009	Taylor	206/372	B25H 3/003
2010/0072341	12/2009	Kao	248/340	B25H 3/04
2011/0089126	12/2010	Hsieh	211/70.6	B25H 3/06
2011/0233160	12/2010	Chen	211/70.6	B25H 3/06
2012/0061339	12/2011	Chang	211/70.6	B65D 73/0064
2013/0126449	12/2012	Sh	211/70.6	B25H 3/04
2013/0240394	12/2012	Wang	206/349	B25H 3/00
2013/0327665	12/2012	Jehannet	206/372	B65D 85/54
2014/0209780	12/2013	Chang	248/551	F16M 13/005
2014/0262887	12/2013	Johnson	206/349	B65D 85/24
2015/0034518	12/2014	Kao	206/372	B65D 73/0014
2015/0034572	12/2014	Kao	211/13.1	B25B 13/06
2015/0122750	12/2014	Kao	211/13.1	B25H 3/003
2015/0165615	12/2014	Lee	206/349	B25H 3/003
2015/0251310	12/2014	Ou	206/372	B25H 3/04
2016/0031074	12/2015	Su	206/349	B25H 3/003
2016/0096264	12/2015	Kao	206/378	B25H 3/06

2016/0221178	12/2015	Hsieh	N/A	B25F 1/04
2016/0265596	12/2015	Yu	N/A	F16D 3/185
2016/0271788	12/2015	Hsieh	N/A	B25H 3/04
2017/0043475	12/2016	Hsieh	N/A	B25H 3/04
2017/0232606	12/2016	Kao	211/70.6	B25H 3/003
2017/0254365	12/2016	Chen	N/A	F16D 3/221
2017/0259408	12/2016	Zhang	N/A	B25B 13/06
2019/0091842	12/2018	Chou	N/A	B25B 13/06
2019/0126461	12/2018	Mefferd	N/A	B25H 3/04
2020/0101590	12/2019	Winnard	N/A	B25H 3/003
2020/0147780	12/2019	Kukucka	N/A	B25H 3/003
2020/0198118	12/2019	Wang	N/A	B25B 13/56
2020/0376635	12/2019	Raskin	N/A	B25B 23/0035
2020/0384631	12/2019	Reed	N/A	B25H 3/04
2020/0406447	12/2019	Hsieh	N/A	B25H 3/04
2021/0060761	12/2020	Chang	N/A	B25H 3/003
2021/0122028	12/2020	Hernandez, Jr.	N/A	B25H 3/06
2021/0156434	12/2020	Yu	N/A	F16D 3/2057
2021/0339376	12/2020	Winnard	N/A	B25H 3/04
2022/0097223	12/2021	Chang	N/A	B25H 3/003
2023/0182282	12/2022	Chang	206/349	B25H 3/06
2024/0246220	12/2023	Chen	N/A	B25H 3/04
2025/0033187	12/2024	Kao	N/A	B25H 3/003

Primary Examiner: Stashick; Anthony D

Assistant Examiner: Pal; Prince

Attorney, Agent or Firm: MUNCY, GEISSLER, OLDS & LOWE, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to a tool holder rail and a tool holder including the same.

Description of the Prior Art

(2) Tools are often used to drive members to be driven, such as screws, nuts or the like. Because the members to be driven are of various sizes (or of the metric and imperial systems), it is necessary to prepare tools corresponding to members to be driven of various sizes. It is understandable that a large number of tools need to be placed and stored according to their sizes; otherwise it will be troubled when in use or not in use. Therefore, some storing racks and storage devices are developed.

(3) However, the conventional storing rack or storage device includes only single one rail for slidable engagement of a tool seat, and the only single one rail is parallel to the attachment side of the conventional storing rack or storage device. As such, it has a small capacity of storing for tools so that it requires more storing rack or storage device to store the tools.

(4) The present invention is, therefore, arisen to obviate or at least mitigate the above-mentioned disadvantages.

SUMMARY OF THE INVENTION

(5) The main object of the present invention is to provide a tool holder rail and a tool holder including the same, which is capable of storing more tools and has a small volume.

(6) To achieve the above and other objects, a tool holder rail is provided, wherein the tool holder rail includes: an elongate main body extending in a longitudinal direction and including two mounting sides extending in the longitudinal direction, the two mounting sides being inclined to each other with an included angle therebetween; and two rail slots disposed on the two mounting sides, respectively, each of the two rail slots including two flanges extending in the longitudinal direction and toward each other, each of the two rail slots being configured for slidable engagement of a tool seat.

(7) To achieve the above and other objects, a tool holder is further provided, wherein the tool holder includes: the tool holder rail and a tool seat slidably engaged within one of the two rail slots.

(8) The present invention will become more obvious from the following description when taken in connection with the accompanying drawings, which show, for purpose of illustrations only, the preferred embodiment(s) in accordance with the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a stereogram of an exemplary embodiment of the present invention;

(2) FIG. 2 is a breakdown drawing of an exemplary embodiment of the present invention;

(3) FIG. 3 is a partial breakdown drawing of an exemplary embodiment of the present invention;

(4) FIG. 4 is a cross-sectional view of an exemplary embodiment of the present invention; and

(5) FIG. 5 is a partial enlarged cross-sectional view of an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(6) Please refer to FIGS. 1 to 5 for an exemplary embodiment of the present invention. A tool holder rail **1** of the present invention includes an elongate main body **10** and two rail slots **20**.

(7) The elongate main body **10** extends in a longitudinal direction **L** and includes two mounting sides **11** extending in the longitudinal direction **L**. The two mounting sides **11** are inclined to each other with an included angle **A** therebetween. The included angle **A** ranges from 45.0 to 150.0 degrees (such as 90 degrees, 120 degrees or 135 degrees). The two rail slots **20** are disposed on the two mounting sides **11**, respectively. Each of the two rail slots **20** includes two flanges **21** extending in the longitudinal direction **L** and toward each other. Each of the two rail slots **20** is configured for slidable engagement of a tool seat. As such, it is capable of storing more tools and has a small volume with a single one a tool holder including the tool holder rail **1**.

(8) Preferably, the elongate main body **10** is integrally formed of one piece, and preferably made of metal such as aluminum, aluminum alloy or the like. The two flanges **21** of each of the two rail slots **20** are parallel to the longitudinal direction **L** and the two mounting sides **11**, which is conducive to smooth movement of the tool seat.

(9) In this embodiment, the tool holder rail **1** further includes an attachment slot **30** disposed on an attachment side **12** of the elongate main body **10**, and the two mounting sides **11** and the attachment side **12** are connected to one another so that the elongate main body **10** is of a triangle configuration. The attachment slot **30** includes two flanges extending in the longitudinal direction **L**, extending toward each other, and extending in a direction perpendicular the longitudinal direction **L**. Each of the two flanges **31** of the attachment slot **30** is thicker than each said flange of each said mounting side **11**, which provides large structural strength.

(10) The tool holder rail **1** further includes corner portions **40**, a first one of the corner portions **40** is integrally connected to and between two said flanges **21** of the two rail slots **20**, a second one of

the corner portions **40** is integrally connected to and between one of the two flanges **21** of one of the two rail slots **20** and one of the two flanges **31** of the attachment slot **30**, a third one of the corner portions **40** is integrally connected to and between one of the two flanges **21** of the other of the two rail slots **20** and the other of the two flanges **31** of the attachment slot **30**, and the two flanges **31** of the attachment slot **30** are flush with two of the corner portions **40** at the attachment side **12**. Specifically, each of the two flanges **31** of the attachment slot **30** and one of the corner portions **40** form a toothed groove therebetween. As such, the tool holder rail **1** has a strong structure and can be attached to a mounting surface stably.

(11) In this embodiment, a bottom of at least one of the two rail slots **20** includes an elongate projection **22** extending in the longitudinal direction **L** and wider than the two flanges **21** of each of the two rail slots **20**. The elongate projection **22** reinforces the structural strength of the configuration of the rail slot. Specifically, the elongate projection **22** includes an elongate toothed groove **221**. Preferably, the elongate main body **10** further includes two end openings **13**, and two caps **50** are preferably inserted in the two end openings **13** and close the two end openings **13**, respectively. Specifically, the elongate main body **10** further includes engaging holes **14**, each of the two caps **50** includes a snap bump **51** which is releasably engaged in one of the engaging holes **14**, and each of the two caps **50** further includes a through hole **52** for a fastener to disposed therethrough so that the tool holder rail **1** can be stably secured.

(12) The present invention further provides a tool holder **100**. The tool holder **100** includes the aforementioned tool holder rail **1** and a tool seat **60, 70** slidably engaged within one of the two rail slots **20**, wherein the tool seat **60, 70** is configured for mounting of a tool such as a tool bit, socket or the like. The tool seat **60** may include a rib **61** projecting to be within the elongate toothed groove **221**. Alternatively, the tool seat **70** may include a base **71** and a tool connector **72**, the base **71** is slidably engaged within one of the two rail slots **20**, and the tool connector **72** is rotatably connected to the base **71** and configured for mounting of a tool such as a tool bit.

(13) Although particular embodiments of the invention have been described in detail for purposes of illustration, various modifications and enhancements may be made without departing from the spirit and scope of the invention. Accordingly, the invention is not to be limited except as by the appended claims.

Claims

1. A tool holder rail including: an elongate main body extending in a longitudinal direction and including two mounting sides extending in the longitudinal direction, the two mounting sides being inclined to each other with an included angle therebetween; two rail slots disposed on the two mounting sides, respectively, each of the two rail slots including two flanges extending in the longitudinal direction and toward each other, each of the two rail slots being configured for slidable engagement of a tool seat; an attachment slot disposed on an attachment side of the elongate main body; and wherein the two flanges of each of the two rail slots are parallel to the longitudinal direction and the two mounting sides; wherein the two mounting sides and the attachment side are connected to one another so that the elongate main body is of a triangle configuration.
2. The tool holder rail of claim 1, wherein the included angle ranges from 45.0 to 150.0 degrees.
3. The tool holder rail of claim 1, wherein the attachment slot includes two flanges extending in the longitudinal direction, extending toward each other, and extending in a direction perpendicular the longitudinal direction.
4. The tool holder rail of claim 3, further including corner portions, wherein a first one of the corner portions is integrally connected to and between the flanges of the two rail slots, a second one of the corner portions is integrally connected to and between one of the two flanges of one of the two rail slots and one of the two flanges of the attachment slot, a third one of the corner portions is integrally connected to and between one of the two flanges of the other of the two rail slots and the

- other of the two flanges of the attachment slot, and the two flanges of the attachment slot are flush with two of the corner portions at the attachment side.
5. The tool holder rail of claim 4, wherein each of the two flanges of the attachment slot and one of the corner portions form a toothed groove therebetween.
6. The tool holder rail of claim 1, wherein a bottom of at least one of the two rail slots includes an elongate projection extending in the longitudinal direction and wider than the two flanges of each of the two rail slots.
7. The tool holder rail of claim 6, wherein the elongate projection includes an elongate toothed groove.
8. The tool holder rail of claim 1, wherein the elongate main body further includes two end openings, and two caps are inserted in the two end openings and close the two end openings, respectively.
9. The tool holder rail of claim 8, wherein the elongate main body further includes engaging holes, and each of the two caps includes a snap bump which is releasably engaged in one of the engaging holes.
10. The tool holder rail of claim 8, wherein each of the two caps includes a through hole for a fastener to disposed therethrough.
11. A tool holder including the tool holder rail of claim 1, wherein the tool seat slidably engaged within one of the two rail slots.
12. The tool holder of claim 11, wherein a bottom of at least one of the two rail slots includes an elongate projection extending in the longitudinal direction, the elongate projection includes an elongate toothed groove, and the tool seat includes a rib projecting to be within the elongate toothed groove.
13. The tool holder of claim 11, wherein the tool seat includes a base and a tool connector, the base is slidably engaged within one of the two rail slots, and the tool connector is rotatably connected to the base and configured for mounting of a tool.
-