

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409988
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Melendez; David

Can protector and cap

Abstract

Provided herein is a re-usable device that would allow for the export of, or consumption of liquid without having to remove the device from the can such as the aluminum beverage can and that would also seal the liquid inside a beverage can. A water-resistant or water-proof, insect-proof, dirt-proof synthetic cap is provided that is to be attached to the lip area of the open mouth of can or other open mouth container, such as metal, plastic or an aluminum beverage can.

Inventors:	Melendez; David (Kihei, HI)
Applicant:	Melendez; David (Kihei, HI)
Family ID:	87431558
Appl. No.:	18/161636
Filed:	January 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230242309 A1	Aug. 03, 2023

Related U.S. Application Data

us-provisional-application US 63305201 20220131

Publication Classification

Int. Cl.: B65D51/00 (20060101)

U.S. Cl.:

CPC B65D51/007 (20130101); B65D2517/0098 (20130101)

Field of Classification Search

CPC: B65D (51/007); B65D (51/20); B65D (2251/0018); B65D (2251/0071); B65D (17/4012); B65D (2517/0041); B65D (2517/0098); A47G (19/22)

USPC: 220/287

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4927048	12/1989	Howard	220/279	B65D 41/52
5078296	12/1991	Amidzich	220/838	B65D 55/16
5119955	12/1991	Granofsky	220/254.2	B65D 17/506
5139163	12/1991	Diaz	206/509	B65D 21/0219
5934495	12/1998	Chiodo	220/257.2	B65D 25/36
6015059	12/1999	Takayama	220/269	B65D 17/4012
7318534	12/2007	Turvey	220/796	B65D 41/22
8336730	12/2011	Pontes	206/508	B65D 51/20

10220984	12/2018	Vigoureux	N/A	B65D 41/22
2004/0000551	12/2003	Flink	220/717	B65D 47/06
2006/0060584	12/2005	Onoda	220/276	B65D 51/20
2007/0090081	12/2006	Briscoe	220/717	A47G 19/2272
2012/0145727	12/2011	Gammage	220/709	A47G 19/2211
2013/0043259	12/2012	Gonzalez Sanchez	220/694	B65D 51/007
2014/0110409	12/2013	Gindi	220/361	B65D 17/4012
2019/0084732	12/2018	Lamberto	N/A	B65D 1/165
2020/0038531	12/2019	McGrade	N/A	C11D 3/48
2022/0127045	12/2021	VanBuren	N/A	B65D 25/36
2022/0306443	12/2021	Ravazzoni	N/A	B67B 5/034

OTHER PUBLICATIONS

4IMPRINT USA, “Universal Soda Lid,” URL: https://www.4imprint.com/product/1269/Universal-Soda-Lid?mkid=3dsaALP&s_kwid=AL!4167!10!73598808984599!2325398373324834&utm_source=bing&utm_medium=msppc&utm_term=%2Fproduct%2F&utm_campaign=DSA-ALP%20Bing&ef_id=33567930651b1bb5b2e41f442ad9909e:G:s&msslkid=33567930651b1bb5b2e41f442ad9909e&utm_content=All%20Products retrieved from internet Jun. 20, 2024 (4 pages). cited by applicant

Smarter-Seal, “12-Pack Soda/Beverage Can Lids, Clear Color,” URL: <https://smarter-seal.com/products/smarter-seal-soda-or-beverage-can-lid-cover-or-protector-12-pack-clear>, retrieved from internet Jun. 20, 2024 (1 page). cited by applicant

Primary Examiner: Smalley; James N

Attorney, Agent or Firm: FOLEY & LARDNER LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Application No. 63/305,201, filed Jan. 31, 2022, the content of which is hereby incorporated by reference in its entirety into this disclosure.

BACKGROUND

(1) Current beverage caps are made of plastic to provide a cap or lid for a beverage that cannot be removed from the top area and which are easily misplaced. These products provided more of a cap or lid than a sealant. These products are neither water-proof nor water-resistant, nor are they intended for that purpose. Thus, a need exists in the art for a re-usable protectant for liquid inside an open mouth container such as an aluminum beverage can from outside contaminates.

(2) This disclosure satisfies this need and provides related advantages as well.

SUMMARY OF THE DISCLOSURE

(3) Provided herein is a re-usable device that would allow for the export of, or consumption of liquid from a closed container having an opening for accesses to the liquid without having to remove the device from the can such as the aluminum beverage can and that would also seal the liquid inside a beverage can when desired. One improvement of the disclosed beverage cap of this disclosure is its thin attachable inner band that wraps around the can or box that maintains the cap or lid from being removed or pulled off the can or box after a drink or use. Thus, in one aspect, a water-proof or water-resistant, insect-proof, dirt-proof synthetic cap is provided that is to be attached to the lip area of the open mouth of the can or other open mouth container, such as metal, plastic or an aluminum beverage can or box. In one aspect, when attached to a beverage can or box, the cap is intended to be used for beverage consumption while retaining sanitation precautions and/or for the protection of liquid inside an aluminum beverage can from outside elements. In one aspect, the cap is comprised of a silicon rubber material.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIGS. 1A to 1F are transparent perspective views of a combination of the cap on a 12 ounce beverage can (FIGS. 1A to 1E) or box (FIG. 1F). The figures show embodiments of the cap on a 12 ounce beverage or box can as it is placed on the open surface of the can or box. FIGS. 1A, 1C and 1D show the cap in an open position and FIGS. 1B, 1E and 1F show the cap on the can or box in a closed position.

(2) FIG. 2 shows a mock-up of a front view of an embodiment of a cap of this disclosure on a beverage can or box. Exemplary dimensions of the various elements are noted in the Figure.

(3) FIG. 3 shows a mock-up of side view of an embodiment of a cap of this disclosure on a beverage can or box. Exemplary dimensions of the various elements are noted in the Figure.

(4) FIGS. 4A and 4B shows a mock-up of a top view of an embodiment of the cap of this disclosure on a beverage can. FIG. 4A shows an embodiment without carbonation- or foam-reducing holes and FIG. 4B shows an embodiment with carbonation- or foam-reducing holes.

(5) FIG. 5 shows a mock-up of a front view of an embodiment of the cap of this disclosure on a beverage can with suggested dimension of the elements of the cap. Exemplary dimensions of the various elements are noted in the Figure.

(6) FIG. 6 shows a mock-up of a side view of an embodiment of the cap of this disclosure on a beverage can with suggested dimension of the elements of the cap. Exemplary proportions of the elements of the various elements are noted in the Figure.

(7) FIG. 7 shows an illustration of a top view of an embodiment of the cap of this disclosure on a beverage can with suggested dimension of the elements of the cap. For the purpose of illustration only, the floor is absent from this view to aid in visualizing how the band lays under the shell when the cap is shut and shows the meeting point for the inner support band and the outer band. When the cap is pulled back to access the beverage, the band or strap stays secure around the can or box.

(8) FIG. 8 shows a top view of an embodiment of the cap of this disclosure.

(9) FIG. 9 shows a first top view of an embodiment of the cap of this disclosure.

(10) FIG. 10 shows a second top view of an embodiment of the cap of this disclosure.

(11) FIGS. 11A and 11B show cut outs of the cap of this disclosure.

(12) FIGS. 12A to 12D show various views of cap of this disclosure. FIG. 12A is an underside view of the cap. FIGS. 12B to 12D show side views of the cap of this disclosure.

(13) FIG. 13 shows an embodiment of the cap of this disclosure, shown inside-out.

DETAILED DESCRIPTION OF THE DISCLOSURE

(14) As shown in the figures, an embodiment of the present disclosure is directed to a beverage can or box cap or lid comprised of a re-usable cap or lid that is easily placed on the can or box and opened to gain access to the beverage. In one embodiment, the disclosure is directed to the lid or cap. In another embodiment, the disclosure is directed to beverage can or box and the re-usable cap or lid.

(15) The term “about,” as used herein when referring to a measurable value such as an dimension or proportion of an element is meant to encompass variations of 20%, 10%, 5%, 1%, 0.5%, or even 0.1% of the specified dimension or proportion.

(16) As shown in FIGS. 1A to F, the cap 5 is place on the beverage can 10 (FIG. 1A to 1G) or box 11 (FIG. 1F). The cap 5 is placed on the top of the can is configured to engage the lip area 30 of the can or box. The cap or lid is comprised of a floor portion 6, the sidewall 15, the support band 200 and one or more tabs 100 joined to the sidewall 15 and support band 200 and contiguous to them. The one or more tabs 100 are configured to provide an anchor to affix the cap 5 on the beverage can 10 or box 11 and lift a portion of the cap 5 to allow access to the opening of the can or box 40 and the liquid or beverage contained therein. FIGS. 1A, C and D show an embodiment wherein the cap 5 is placed on a can 10. FIG. 1F shows an embodiment wherein the cap 5 is placed on a box 11. See also FIGS. 5 to 7. The floor 6 of the cap 5 covers the top of the can 50 which includes the access portal 40 to the can's contents. In one aspect, the cap 5 is perforated with one or more small (about 1/32; or about 1/16, or about 2/16; or about 3/16; or about 4/16, or about 1.0 mm, or about 1.5 mm or about 2.0 mm or above, up to about 0.5 cm) holes (300) (see FIG. 4B), which may be the same or different size or shape. There can be any suitable number of perforations, e.g., at least 5, or at least 15, or at least 20 perforations in the cap. See FIG. 4B. The sidewall 15 and support band 200 of the cap 5 are substantially perpendicular to the floor 6 but configured to encase the can when on it creating a closed container. The sidewall 15 and support band 200 are configured to engage the lip area 30 of the can. Joined to and contiguous with the sidewall 15 and support band 200 is one or more tabs 100 that serve to assist the user with placing the cap or lid 5 of the top 50 of the can or box. Using the tabs 100, the user positions the cap 5 to encompass the top 50 of the can 10 or box 11 and provides pressure to the bottom of the can 10 or box 11 such that sidewall 15 and support band 200 cover and engage the lip area 30 of the can 10 or box 11 holding the floor 6 of the cap 5 to the top 50 of the can 10 or box 11. To gain access to the can 10 or box 11 contents, the user lifts a portion of the sidewall 15 from the lip area 30, with or without use of a tab 100 to flip a portion of the floor 6 of the cap 5 to gain access to the can or box opening 40. The flipped portion 20 of the cap 5 is shown in the Figures.

(17) FIGS. 1B, E and F show the lid when it is in the closed position creating a seal on the beverage can or box. As shown in these figures, the floor 6 of the cap or lid 5 is substantially parallel to the top of the can 10 or box 11 when in the closed position. The sidewall 15 and support band 200 engage the lip area 30 to hold the cap or lid 5 to the can 10 or box 11. The one or more tabs 100 (which can be the same or different dimensions) are joined to and contiguous with the sidewall 15 and support band 200 of the cap or lid 5.

(18) FIG. 13 shows an alternative embodiment of the cap manufactured for use on a cal. In this embodiment, the cap 5 shows the inside sidewall 15 that wraps around the can, has larger dimensions, adding about from 0.5 inch to about 1.0 inch from prior embodiments (see e.g., FIGS. 2, 3, 6 and 7). In addition, in this embodiment only one central tab 100 is provided to assist with affixing the cap to the can or box.

(19) FIGS. 2 through 7 are mock-ups of the cap 5 when placed on a can 10, providing dimensions or proportions of the floor 6, sidewall 15 and the one or more tabs 100.

(20) FIGS. 8 to 10 show the dimensions or proportions of the external elements of the cap when not positioned on a can or box. FIG. 8 is the top view, FIGS. 9 and 10 are the side views showing the tabs of varying dimensions in communication with the sidewall.

(21) FIGS. 11A and 11B are cut-out views of the cap when not affixed to a can or box. FIG. 11A shows the underside of the cap, with a view of the proportional dimensions of the support band to the outer shell of the cap. This figures, as well as FIG. 11B show that the band does not, in one embodiment, completely encircle the can. In this embodiment, also shown in FIG. 8, the band possess a gap (e.g., a one and one quarter inch gap as shown in FIG. 8 that when the cap is on the can, functions as a connection point or meeting point for the inner support band. Similar to FIG. 11A, FIG. 12A shows an underside view of the cap when not placed on the can. As shown, there is a gap between the band and the outer shell that allows for a secure placement of the cap on the can.

(22) FIG. 13 shows an alternative embodiment and view of the cap of this disclosure. In this Figure, the cap is shown in inside-out view (the interior of the cap that is located up against or contiguous to the can or box when affixed to the can or box).

(23) The cap or lid 5 of this disclosure is a synthetic (e.g., a silicone rubber) beverage cap that can be applied to the top cylinder area of a beverage can 50 or top area of a beverage box 50 by covering the mouth area of the beverage can or box 40 for protection from elements such as water, dirt, and insects. To be applied, the user pulls down on the one or more tabs 100 (e.g., one three tabs 100, in FIGS. 1 to 13) provided with the cap 5 over the top area of a beverage can 10 or box 11. Making sure the open mouth 40 of the beverage can 5 lines up with the open mouth area of the cap or in the flipped open position 20. Firmly pull down the one tab (FIG. 13) or center and back tabs 100 until cap 5 (e.g., silicone rubber) is flush with the aluminum lip 30 of beverage can 5. Once ready to consume a beverage, pull up on the center tab 100 and stretch to the reverse side of the beverage can floor 6, placing and resting the center tab 100 on the reverse top 6 of a beverage can 5, opposite from the mouthpiece 40. The silicone-rubber will provide an opening around the mouth of the can for easy consumption. The silicone-rubber “support band” 200 underneath the lip of can 30 is used to keep the cap placed firmly and stable. Once ready to cover the mouth area of beverage can from outside elements, pull center tab 100 from the reverse side of the beverage can 5 and stretch to the center area beneath the lip of the mouthpiece 40. The center tab should be placed beneath the “support band” 200 just below the mouth 40 of a beverage can 5. To remove, gently pull tabs 100 upward until all of the silicone rubber has been released from aluminum beverage can 5.

(24) Focusing on the cap as a protectant that will save the customer money by covering and sealing liquid in a beverage from water, dirt, and insects. The cap of this disclosure is attractive but intended to secure a beverage lid from outside contamination. It can be produced in large quantities and sold individually to the consumer for a very low cost.

(25) Provided herein is a pliable lid for a beverage container, comprising, or consisting essentially of, or consisting of a main body having a first surface or floor 6; a second surface comprising a sidewall 15 and support band 200 substantially perpendicular to the first surface or floor 6; a can receiving recess 300; and one or more tabs 100 extending perpendicular to the main body so as to form a handle to attach the lid or cap 5 to the beverage container 10 or 11.

(26) In one aspect, the lid comprises a pliable synthetic or natural material. In another aspect, the synthetic lid comprises a synthetic polymer or rubber. In a yet further aspect, the natural material comprises rubber. In a further aspect, the second surface comprising the sidewall **15** and support band **300** substantially perpendicular to the first surface or floor **6** is positioned underneath the lip of the can **30** when affixed to the can. In a further aspect, provided herein is a pliable lid and a can or box. In a yet further aspect, further provided herein is a kit comprising a pliable lid as described herein, and optionally instructions for use. In a further aspect, provided herein is one or more beverage cans or boxes and one or more pliable lids as disclosed herein, and optionally, instructions for use.

Embodiments

(27) It is to be understood that while the disclosure has been described in conjunction with the above embodiments, that the foregoing description and examples are intended to illustrate and not limit the scope of the disclosure. Other aspects, advantages and modifications within the scope of the disclosure will be apparent to those skilled in the art to which the disclosure pertains.

(28) Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. All nucleotide sequences provided herein are presented in the 5' to 3' direction.

(29) The embodiments illustratively described herein may suitably be practiced in the absence of any element or elements, limitation or limitations, not specifically disclosed herein. Thus, for example, the terms “comprising,” “including,” “containing,” etc. shall be read expansively and without limitation. Additionally, the terms and expressions employed herein have been used as terms of description and not of limitation, and there is no intention in the use of such terms and expressions of excluding any equivalents of the features shown and described or portions thereof, but it is recognized that various modifications are possible within the scope of the disclosure.

(30) Thus, it should be understood that although the present disclosure has been specifically disclosed by specific embodiments and optional features, modification, improvement and variation of the embodiments therein herein disclosed may be resorted to by those skilled in the art, and that such modifications, improvements and variations are considered to be within the scope of this disclosure. The materials, methods, and examples provided here are representative of particular embodiments, are exemplary, and are not intended as limitations on the scope of the disclosure.

(31) The scope of the disclosure has been described broadly and generically herein. Each of the narrower species and subgeneric groupings falling within the generic disclosure also form part of the disclosure. This includes the generic description with a proviso or negative limitation removing any subject matter from the genus, regardless of whether or not the excised material is specifically recited herein.

(32) In addition, where features or aspects of the disclosure are described in terms of Markush groups, those skilled in the art will recognize that embodiments of the disclosure may also thereby be described in terms of any individual member or subgroup of members of the Markush group.

Claims

1. A pliable lid for a beverage container, comprising: a main body having: a first surface, a sidewall, and a support band, the sidewall and support band each perpendicular to the first surface and encasing the beverage container, wherein the sidewall and support band are not concentric; a beverage container receiving recess; one or more tabs extending perpendicular to the first surface so as to form a handle to attach the lid to the beverage container; wherein the support band does not completely encircle the beverage container and comprises a gap configured to connect to the sidewall of the lid.
2. The pliable lid of claim 1, wherein the support band engages a lip area of the beverage container.
3. The pliable lid of claim 1, wherein the lid comprises a pliable synthetic or natural material.
4. The pliable lid of claim 3, wherein the synthetic lid comprises a synthetic polymer or rubber.
5. The pliable lid of claim 3, wherein the natural material comprises rubber.
6. The pliable lid of claim 1, wherein the support band is positioned underneath a lip of the beverage container when affixed to the beverage container.
7. The pliable lid of claim 1, wherein the support band is radially spaced from the sidewall.
8. The pliable lid of claim 1, further comprising one or more perforations located on the surface of the lid.
9. The pliable lid of claim 1, wherein the main body and support band each comprise a silicon rubber material.
10. A beverage container comprising the pliable lid of claim 1.
11. The pliable lid of claim 1, wherein the first surface is parallel to a top of the beverage container and covers a mouth of the beverage container.
12. A kit comprising one or more beverage containers and one or more pliable lids of claim 1.
13. The pliable lid of claim 1, wherein the support band maintains the lid from being removed from the beverage container when the first surface is in an open position.
14. The pliable lid of claim 1, wherein the support band does not completely encircle a circumference of the beverage container and wherein the gap extends the entire height of the support band.
15. A pliable lid for a beverage container, comprising: a floor portion parallel to a top of the beverage container configured to move from a closed position to an open position relative to the beverage container; a sidewall extending perpendicular to the floor portion of the lid and partially encasing the beverage container when the floor portion is in the open position; one or more tabs extending from and contiguous with the sidewall; a support band perpendicular to the floor portion and encasing the beverage container around a lip area of the beverage container, the support band configured to engage a lip area of the beverage container when the floor portion is in the open position and when the floor portion is in the closed position; and wherein the support band does not completely encircle the beverage container and comprises a gap configured to connect to the sidewall of the lid.
16. The pliable lid of claim 15, wherein the sidewall is contiguous with the floor portion of the lid.
17. The pliable lid of claim 15, wherein the support band is radially spaced from the sidewall and maintains the lid from being removed from the beverage container when the floor portion is in an open position.
18. The pliable lid of claim 15, wherein the floor portion, at least one of the one or more tabs, and the sidewall are each placed on a reversed side of the beverage container when the floor portion is moved to an open position.
19. The pliable lid of claim 15, wherein the floor portion, the sidewall, the one or more tabs, and the support band each comprise a silicone rubber material.

