

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410987
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Tseng; Jui-Fu

Device for paintball air gun

Abstract

An improved device for a paintball air gun. A sliding sleeve has a channel penetrating an inside thereof. The sliding sleeve has a rear ring sleeve covered a rear end thereof and several air holes around the rear ring sleeve. The gas enters the rear ring sleeve through the air holes around the rear ring sleeve, and presses the sliding sleeve forward and moved, and a buckle of a protruding ring located in the middle of the sliding sleeve has been released by the linkage device, so that the sliding sleeve is first pushed forward by the gas, until the sliding sleeve leaves the ring plug, and then the gas is allowed to rush into the sliding sleeve, so that the sliding sleeve and the gas inside impact the paint bullet and fly out at high speed, and then the spring brings the sliding sleeve back to an original position.

Inventors:	Tseng; Jui-Fu (New Taipei, TW)
Applicant:	WORLITE INDUSTRY CO., LTD. (New Taipei, TW)
Family ID:	96174750
Assignee:	WORLITE INDUSTRY CO., LTD. (New Taipei, TW)
Appl. No.:	18/396731
Filed:	December 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250216171 A1	Jul. 03, 2025

Publication Classification

Int. Cl.: F41B11/723 (20130101); F41B11/62 (20130101)

U.S. Cl.:

Field of Classification Search

CPC: F41A (11/723); F41B (11/723)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7841330	12/2009	Liao	124/77	F41B 11/723
8261728	12/2011	Tseng	124/73	F41B 11/721
12098902	12/2023	Dobbins	N/A	F41B 11/70
2010/0170492	12/2009	Tiberius	124/31	F41B 11/62
2010/0199961	12/2009	Liao	124/71	F41B 11/721
2010/0199963	12/2009	Liao	124/75	F41B 11/723
2015/0020787	12/2014	Tseng	124/73	F41B 11/00
2021/0102639	12/2020	Wood	N/A	F16K 31/16
2023/0102220	12/2022	Wood	124/74	F41B 11/62
2023/0349665	12/2022	Dobbins	N/A	F41B 11/62
2024/0255250	12/2023	Wing	N/A	F41B 11/721

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2007064913	12/2006	WO	F41B 11/723
WO-2008097265	12/2007	WO	F41B 11/723

Primary Examiner: Weber; Jonathan C

Background/Summary

BACKGROUND OF THE PRESENT INVENTION

Field of Invention

(1) The present invention relates to a paintball air gun, and in particular to an improved device for a paintball air gun that allows the sliding sleeve to produce large-impulse sliding.

Description of Related Arts

(2) The conventional paintball air gun is as shown in FIG. 1. In the gun body, a linkage device of the trigger allows the gas bottle to supply air to a ring plug extending forward from a positioning block in the end chamber of the ballistic path. A sliding sleeve **40** is inserted into the front end of the ring plug. The sliding sleeve **40** has a ring sleeve sleeved on the front end thereof. A spring is sleeved on the ring sleeve and the sliding sleeve. The paint bullet has been pushed into the front end of the sliding sleeve in the ballistic path from the bullet chamber in advance. The sliding sleeve **40** has a two-stage channel **41** penetrating the inside thereof, several air holes **42** arranged at the rear end thereof, and a top piece **43** with holes concave inward arranged on the front end of the sliding sleeve **40**. The gas enters the sliding sleeve **40** by the air holes, and the sliding sleeve **40** is pressed forward and moved forward, and the buckle with the protruding ring in the middle of the sliding sleeve **40** has been released by the linkage device, so that the sliding sleeve is first pushed

forward by the gas, until the sliding sleeve leaves the ring plug, and then the gas rushes into the sliding sleeve, and the sliding sleeve and its internal gas impact paint bullet fly out at high speed, and then the spring brings the sliding sleeve back to its original position, wherein the sliding sleeve **40** is not easy to manufacture, and the ventilation in the sliding sleeve **40** is not smooth, the impact amount is small, and the striking force is insufficient, in order to provide the article that is more in line with the actual needs, the inventor has conducted research and development to solve the above-mentioned problems that are easily caused by conventional use.

SUMMARY OF THE PRESENT INVENTION

(3) The main purpose of the present invention is to provide an improved device for a paintball air gun that produces a sliding sleeve structure with a large impact amount, so that the sliding sleeve has the best impact force in the ballistic path.

(4) In order to achieve the above purpose, the structure of the present invention is: in a gun body, a linkage device of a trigger allows a gas bottle to supply air to a ring plug that extends forward from a positioning block in an end chamber of a ballistic path, wherein a sliding sleeve is sleeved into a front end of the ring plug, wherein a front ring sleeve is covered a front end of the sliding sleeve, wherein a spring is provided between the front ring sleeve and the sliding sleeve, wherein a paint bullet has been pushed into the front end of the sliding sleeve in the ballistic path from a bullet chamber in advance, wherein the sliding sleeve has a channel penetrating an inside thereof, wherein the sliding sleeve has a rear ring sleeve covered a rear end thereof and several air holes around the rear ring sleeve, wherein the gas enters the rear ring sleeve through the air holes around the rear ring sleeve, and presses the sliding sleeve forward and moved, and a buckle of a protruding ring located in the middle of the sliding sleeve has been released by the linkage device, so that the sliding sleeve is first pushed forward by the gas, until the sliding sleeve leaves the ring plug, and then the gas is allowed to rush into the sliding sleeve, so that the sliding sleeve and the gas inside impact the paint bullet and fly out at high speed, and then the spring brings the sliding sleeve back to an original position.

(5) In order to provide esteemed examiners with a better understanding of the techniques, means, and effects adopted in the present invention to achieve the intended objectives, a preferred embodiment is hereby presented, along with detailed explanations accompanied by views. It is believed that through this, a thorough and concrete understanding of the purpose, features, and advantages of the present invention can be obtained.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a partially exploded view of the prior art.
- (2) FIG. 2 is a perspective view of an embodiment of the present invention.
- (3) FIG. 3 is a perspective sectional view of FIG. 2 of the present invention.
- (4) FIG. 4 is a partially exploded view of FIG. 2 of the present invention.
- (5) FIG. 4a is an enlarged view of the sliding sleeve in FIG. 4 of the present invention.
- (6) FIG. 5 is an enlarged view of the right end of FIG. 4 according to the present invention.
- (7) FIG. 6 is a front sectional view of FIG. 3 of the present invention.
- (8) FIG. 7 is a sectional view of the sliding sleeve of FIG. 6 when the sliding sleeve is moved forward according to the present invention.
- (9) FIG. 8 is a sectional view of the gas in FIG. 7 according to the present invention when the gas rushes forward from the sliding sleeve and the sliding sleeve moves forward.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(10) As shown in FIGS. 2 to 8, it is an improved device for a paintball air gun according to the present invention, wherein in a gun body **10** (as shown in FIG. 2), a linkage device **12** of a trigger

11 allows a gas bottle **13** to supply air to a ring plug **17** that extends forward from a positioning block **16** in an end chamber **15** of a ballistic path **14** (as shown in FIG. 5), wherein a sliding sleeve **20** is sleeved into a front end of the ring plug **17**, wherein a front ring sleeve **18** is covered a front end of the sliding sleeve **20**, wherein a spring **19** is provided between the front ring sleeve **18** and the sliding sleeve **20**, wherein a paint bullet **30** has been pushed into the front end of the sliding sleeve **20** in the ballistic path **14** from a bullet chamber **31** in advance, wherein the sliding sleeve **20** has a channel **21** (as shown in FIGS. 4 and 4a) penetrating an inside thereof, wherein the sliding sleeve **20** has a rear ring sleeve **22** covered a rear end thereof and several air holes around the rear ring sleeve **22**, wherein the gas enters the rear ring sleeve **22** through the air holes **23** around the rear ring sleeve **22**, and presses the sliding sleeve **20** forward and moved, and a buckle of a protruding ring **24** located in the middle of the sliding sleeve **20** has been released by the linkage device **12** (as shown in FIG. 3), so that the sliding sleeve **20** is first pushed forward by the gas (as shown in FIG. 6), until the sliding sleeve **20** leaves the ring plug **17** (as shown in FIG. 7), and then the gas is allowed to rush into the sliding sleeve **20** (as shown in FIG. 8), so that the sliding sleeve **20** and the gas inside impact the paint bullet **30** and fly out at high speed, and then the spring **19** brings the sliding sleeve **20** back to an original position. The sliding sleeve **20** is allowed to slide more smoothly. Although most of them are conventional structures, the improved sliding sleeve **20** is simpler, and the sliding and impact processes are faster.

(11) In summary, the structure described above utilizes a special design where the sliding sleeve and the rear ring sleeve are separately manufactured, making it easier. The sliding sleeve structure is simpler and produces better power, which is the easiest for people to understand and implement. Therefore, it can provide excellent usability and convenience for impact paint bullets, making it a completely different structure from what is commonly known.

(12) The above are detailed descriptions and drawings of preferred embodiments of the present invention and are not intended to limit the present invention. The entire scope of the present invention shall be subject to the following claims, and the spirit of the patent scope and similar modified embodiments thereof and similar structures should be included in the present invention.

Claims

1. An improved device for a paintball air gun, wherein in a gun body, a linkage device of a trigger allows a gas bottle to supply air to a ring plug that extends forward from a positioning block in an end chamber of a ballistic path, wherein a sliding sleeve is sleeved into a front end of the ring plug, wherein a front ring sleeve is covering a front end of the sliding sleeve, wherein a spring is provided between the front ring sleeve and the sliding sleeve, wherein a paint bullet has been pushed into the front end of the sliding sleeve in the ballistic path from a bullet chamber in advance, wherein the sliding sleeve has a channel penetrating an inside thereof, wherein the sliding sleeve has a rear ring sleeve covering a rear end thereof and a plurality of air holes around the rear ring sleeve, wherein a buckle of a protruding ring at the middle of the sliding sleeves is released by the linkage device, and the gas enters the rear ring sleeve through the plurality of air holes of the rear ring sleeve to push the sliding sleeve forward until the sliding sleeve disengages from the ring plug, and then the gas enters the channel in the sliding sleeve to directly push the paint bullet, causing the paint bullet to exit the gun body, finally the spring returns the sliding sleeve to an original position.
