

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411701
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Gao; Yihai et al.

Interface generation system and interface generation method

Abstract

An interface generation system and an interface generation method are provided. A processor executes a design module, an analysis module, a metadata module, and a rendering module. The design module receives configuration data. The metadata module calls metadata according to an application program interface (API) corresponding to the configuration data and stores the metadata of a plurality of APIs. The analysis module analyzes the configuration data and the metadata to generate interface data according to the metadata of the APIs and a data feature. The rendering module displays interface content on a display according to the interface data to provide an operation interface and a data interface corresponding to the configuration data.

Inventors: Gao; Yihai (Shanghai, CN), Sun; Guoxin (Shanghai, CN)

Applicant: DIGIWIN CO., LTD. (Shanghai, CN); DATA SYSTEMS CO., LTD. (New Taipei, TW)

Family ID: 87719197

Assignee: DIGIWIN CO., LTD. (Shanghai, CN); DATA SYSTEMS CO., LTD. (New Taipei, TW)

Appl. No.: 18/461532

Filed: September 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250004798 A1	Jan. 02, 2025

Foreign Application Priority Data

CN	202310800082.7	Jun. 30, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: G06F9/451 (20180101); G06F3/048 (20130101)

U.S. Cl.:

CPC G06F9/451 (20180201);

Field of Classification Search

CPC: G06F (9/44); G06F (9/449); G06F (9/451); G06F (9/44584); G06F (9/44521)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6519571	12/2002	Guheen	705/14.66	G06Q 30/0269
6721713	12/2003	Guheen	715/202	G06Q 99/00
10775976	12/2019	Abdul-Jawad	N/A	G06F 9/54
10891127	12/2020	Ye	N/A	G06F 16/148
2006/0236254	12/2005	Mateescu	715/762	G06F 8/75
2008/0301643	12/2007	Appleton	717/124	G06Q 30/02
2017/0083585	12/2016	Chen	N/A	G06F 11/3409
2017/0090734	12/2016	Fitzpatrick	N/A	G06F 3/0486
2021/0342785	12/2020	Mann	N/A	G06F 40/186

Primary Examiner: Augustine; Nicholas

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of China application serial no. 202310800082.7, filed on Jun. 30, 2023. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The disclosure relates to an interface generation and interface configuration technology, and in particular, to an interface generation system and an interface generation method.

Description of Related Art

(3) In the development of enterprise management software, a large number of developers are needed, so as to develop interfaces featuring multiple functions and interactive functions. The interactive functions may be the input of basic data, the selection of pop-up windows, the characteristic of data fields and so on. Therefore, in the currently-available methods, developers are required to design and develop interfaces one by one according to users' needs. This results in tremendous labor costs and time costs, and the content of the interfaces cannot be adjusted in real

time according to users' needs. Therefore, how to efficiently generate a corresponding interface according to user operations is an important issue.

SUMMARY

(4) The disclosure provides an interface generation system and an interface generation method capable of generating an interface according to configuration data and metadata and implementing an interface generation function with low error rate and high efficiency.

(5) According to an embodiment of the disclosure, the disclosure provides an interface generation system including a storage device and a processor. The storage device stores a design module, an analysis module, a metadata module, and a rendering module. The processor is coupled to the storage device and executes the design module, the analysis module, the metadata module, and the rendering module. The design module receives configuration data, so that the metadata module stores metadata of a plurality of application programming interfaces (APIs) according to the configuration data. The analysis module analyzes the configuration data and the metadata to generate interface data. The rendering module displays an interface on a display according to the interface data.

(6) According to an embodiment of the disclosure, the disclosure further provides an interface generation method, and the method includes the following steps. A design module receives configuration data. A metadata module stores metadata of a plurality of application programming interfaces (APIs) according to the configuration data. An analysis module analyzes the configuration data and the metadata to generate interface data. A rendering module displays interface content on a display according to the interface data.

(7) To sum up, in the interface generation system and the interface generation method provided by the disclosure, through the configuration data and the source data of the APIs, the operation interface related to the plurality of APIs is effectively established according to the configuration data and the extraction rule, so as to be conveniently operated and used by users.

(8) To make the aforementioned more comprehensible, several embodiments accompanied with drawings are described in detail as follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic view of an interface generation system according to an embodiment of the disclosure.

(2) FIG. 2 is a flow chart of an interface generation method according to an embodiment of the disclosure.

(3) FIG. 3 is a schematic view of the interface generation system executing a plurality of modules according to an embodiment of the disclosure.

(4) FIG. 4 is a schematic view of an interface server, an electronic apparatus, and a display according to an embodiment of the disclosure.

(5) FIG. 5 is a flow chart of interface analysis and generation according to an embodiment of the disclosure.

DESCRIPTION OF THE EMBODIMENTS

(6) Descriptions of the disclosure are given with reference to the exemplary embodiments illustrated by the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

(7) FIG. 1 is a schematic view of an interface generation system according to an embodiment of the disclosure. With reference to FIG. 1, an interface generation system **100** includes a processor **110** and a storage device **120**. The processor **110** may include, for example, a central processing unit (CPU) or a programmable microprocessor for general or special use, a digital signal processor

(DSP), an application specific integrated circuit (ASIC), a programmable logic device (PLD), other similar processing circuits, or a combination of the foregoing devices.

(8) FIG. 2 is a flow chart of an interface generation method according to an embodiment of the disclosure. FIG. 3 is a schematic view of the interface generation system executing a plurality of modules according to an embodiment of the disclosure. With reference to FIG. 1, FIG. 2, and FIG. 3, the interface generation system **100** may execute the following steps **S210** to **S240** to effectively generate a corresponding interface according to user configuration. In this embodiment, the storage device **120** stores a design module **121**, an analysis module **122**, a metadata module **123**, and a rendering module **124**. In this embodiment, the design module **121**, the analysis module **122**, the metadata module **123**, and the rendering module **124** may be matched with corresponding data transmission interfaces and/or data processing modules to implement their respective functions through corresponding software and/or programs.

(9) In this embodiment, a user may input configuration data related to an application programming interface (API) by operating the interface generation system **100** or an input device (e.g., an electronic apparatus or a keyboard), so that the interface generation system **100** calls the API according to the configuration data. The interface generation system **100** creates related interface data according to a calling result (i.e., calling information) and the configuration data. In this way, the interface generation system **100** may generate an interface operation system corresponding to user settings by inputting the configuration data and the interface data into a display. Besides, the API may be, for example, a cloud application service provided by a server or a database or a cloud business application service provided by another cloud server, which is not limited by the disclosure.

(10) In step **S210**, the processor **110** executes the design module **121**, so that the design module **121** receives configuration data. In an embodiment, the user may input the configuration data into the interface generation system **100** through an input apparatus (e.g., an operation interface) or a communication device (e.g., a transceiver). The configuration data has setting parameters related to the use of the API, such as a name, a type, request content, and an extraction rule of at least one application program interface. In other words, the configuration data may include API-related data such as an API URL, an API type, an API feature, and an API parameter. The type of the API may be, for example, “purchase requisition to purchase service” or “purchase change service”, but the disclosure is not limited thereto. In this embodiment, the extraction rule is configured with a predefined algorithm and is used to describe how to extract required data from the calling information of the API. The algorithm may be, for example, JavaScript Object Notation (JSON) algorithm, but the disclosure is not limited thereto. The extraction rule may describe the position of the information in the request information and/or the response information.

(11) In an embodiment, the configuration data includes submit data configuration and query data configuration. The design module **121** calls a corresponding API according to the submitted data in the configuration data and then obtains corresponding response information. In this way, the design module **121** may treat the response information as the submitted data in the configuration data and store the response information in the storage device **120**. That is, the submitted data in the configuration data may be the data called/read from the corresponding API according to the query data.

(12) In step **S220**, the processor **110** executes the metadata module **123**, so that the metadata module **123** stores metadata of a plurality of APIs according to the configuration data. To be specific, the metadata module **123** calls the related APIs according to the configuration data and stores the metadata of the APIs. The metadata of the APIs includes a data name, a data type (e.g., character strings and values), and a data feature. The data feature may be a required feature, an optional feature (that is, not required), whether it is a business primary key, and whether it is a primary key. The primary key refers to whether the data or value is a unique and complete key that identifies data or attributes. One data table can only have one primary key, such as number. The

business primary key is unique data from the business level. The business primary key may be, for example, order number, employee number, product number, etc. The processor **110** may perform different data query logic processing according to different data types.

(13) In step **S230**, the analysis module **122** analyzes the configuration data and the metadata to generate interface data. The interface data includes interface structure data and display data (i.e., numerical value or text to be presented). In an embodiment, the analysis module **122** serializes the interface data and outputs the serialized interface data to the rendering module **124**. Serialization may be that the analysis module **122** performs organization and arrangement according to the data feature of the metadata. For instance, the analysis module **122** displays the data whose data features are all required features in the same field or form.

(14) In an embodiment, the analysis module **122** converts the interface data into data in Json format, and the analyzing module **122** outputs the interface data in Json format into the rendering module **124**. In step **S240**, the rendering module **124** displays interface content on a display according to serialized the interface data. In an embodiment, the rendering module **124** calls a corresponding API among the APIs according to the configuration data and then obtains corresponding calling data. To be specific, the rendering module **124** may automatically obtain data meeting user's needs from the corresponding API according to the setting/configuration data and then provides a data interface for the user to perform operations and queries (such as the query of the quantity of the submitted purchase order, the query of material inventory, etc.).

(15) FIG. **4** is a schematic view of an interface server, an electronic apparatus, and a display according to an embodiment of the disclosure. The interface generation system **100** includes an electronic apparatus **420** and an interface server **410**. A design module **421** is disposed in the electronic apparatus **420**, and an analysis module **412**, a metadata module **413**, and a rendering module **414** are disposed in the interface server **410**. The electronic apparatus **420** may be, for example, a personal computer (PC), a tablet computer, or a server, etc., with computing functions to be connected to the interface server **410**. The interface server **410** includes a storage device **411**, an analysis module **412**, a metadata module **413**, and a rendering module **414**. The storage device **411** is coupled to the design module **421** and the analysis module **412**. The metadata module **413** is coupled to the analysis module **412**. The rendering module **414** is coupled to the analysis module **412** and a display **430**. In this embodiment, the coupling between various modules and devices may be implemented through transceivers, and the disclosure is not limited thereto. In this embodiment, the design module **421**, the storage device **411**, the analysis module **412**, the metadata module **413**, and the rendering module **414** may be matched with corresponding data transmission interfaces and/or data processing modules to implement their respective functions through corresponding software and/or programs.

(16) In this embodiment, each of the interface server **410** and the electronic apparatus **420** includes a processing unit and a storage unit. The processing unit may include, for example, a central processing unit (CPU) or a programmable microprocessor for general or special use, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a programmable logic device (PLD), other similar processing circuits, or a combination of the foregoing devices. The storage device (**120** and **411**) may be a memory, such as a non-volatile memory (NVM). The storage device (**120** and **411**) may store related programs, units, modules, or algorithms for the processing unit to access and execute, so as to implement the related functions and operations described in the various embodiments of the disclosure.

(17) In this way, the interface server **410** and the electronic apparatus **420** (e.g., the user operation interface) may effectively establish an operation interface related to the API in the configuration data and a data logic processing service (e.g., querying, integrating, changing, deleting, adding, comparing, sorting, etc.) through the configuration data inputted by the user. More importantly, the interface server **410** may effectively establish the operation interface according to the configuration data. It does not require the user to have front-end development skills, nor does it need to be

developed through a designing device, and the screen (i.e., the operation interface or data table) may be automatically generated. The efficiency and practicality of interface generation are thereby improved.

(18) FIG. 5 is a flow chart of interface analysis and generation according to an embodiment of the disclosure. With reference to FIG. 4 and FIG. 5, the interface generation system **100** may execute the following steps S510 to S550 to continue the abovementioned process of the rendering module **414** analyzing the interface data and generating the interface content. In step S510, the rendering module **414** reads the interface data. In step S520, the rendering module **414** generates a data set according to the interface data. To be specific, the rendering module **414** generates the data set and page structure data according to the interface data. The data set is a collection of multiple pieces of data, and the data comes from the data queried by the design module **421** according to the configuration data. It is worth noting that the data set does not have a fixed structure and only needs to correspond to the page structure data to generate the interface content. The page structure data is generated according to the metadata, and the page structure data can generate different controls/widgets.

(19) In step S530, the interface server **410** generates, through the rendering module **414**, a front-end widget according to the page structure data of the interface data. To be specific, the rendering module **414** generates the corresponding front-end widget according to the page structure data. The front-end widget is a functional widget displayed on the display **430** and then executes corresponding processing logic (such as searching for purchase requisition data) according to parameters or instructions inputted by the user. The page structure data may include a data operation, data processing logic, a processing rule, a request instruction, a data arrangement rule, and other settings related to presenting data and arranging tables.

(20) In step S540, the interface server **410** bidirectionally binds, through the rendering module **414**, the data set and the front-end widget. To be specific, the rendering module **414** bidirectionally binds the data set and the front-end widget, so that the data set may change correspondingly with the adjustment of the front-end widget. In other words, when the user adjusts and modifies the interface content by operating the interface on the display **430**, the corresponding data set stored in the storage device **411** may also change accordingly. Similarly, when the data of the data set changes, the data or format on the corresponding front-end widget may also change. In an embodiment, when the user operates the widget and then changes the data in the widget, the processor may give real-time feedback to the user according to the user's operation (such as refreshing the page regularly and providing the latest data).

(21) In step S550, the rendering module **414** generates an interactive widget according to the configuration data. To be specific, the rendering module **414** generates other front-end widgets (e.g., button widget and menu widget) according to the configuration data. The rendering module **414** generates the interactive widget according to the submitted data in the configuration data and binds the interactive widget and the submitted data. The submitted data may be data that calls different APIs at the same time and is presented in the same event. The submitted data may also be a plurality of processing logic or data fields that are parallel and do not interfere with each other. The submitted data may be data obtained from the API according to the configuration data. For instance, if the submitted data includes the inventory quantity of an object A, the processor may call the inventory quantity of the object A according to the API related to the inventory in the configuration data. In this way, the submitted data may perform further logical processing on the inventory quantity of the object A.

(22) In an embodiment, the rendering module **414** displays the front-end widget and the interactive widget on the display **430**. The interactive widget may be a functional widget such as a basic data input field, a pop-up window data selection field, and a required data input window. Therefore, in this embodiment, the interface generation system **100** may provide effective and easy operation related to the configuration of the API and the generation of the operation interface. It is worth

noting that the processor may determine whether the data or field is required according to the data feature (e.g., metadata) bound to the front-end widget and the interactive widget. In other words, when a required field (widget) is not filled, the interface displays “Unable to submit”, and the next step (such as submitting data or calculating values) cannot be performed.

(23) In view of the foregoing, in the interface generation system and the interface generation method provided by the disclosure, the corresponding operation interface may be effectively established and generated according to the configuration data inputted by the user. Further, in the interface generation system and the interface generation method provided by the disclosure, the corresponding data interface may be established according to each calling operation of the API service when the user operates the interface. Further, the data and widgets generated by the related calling operations may be sorted to generate an operation interface that conforms to the user's settings. In this way, the interface generation system and the interface generation method provided by the disclosure can provide users with a convenient and efficient interface generation function. In other words, the functions and effects implemented by the interface generation system and the interface generation method provided by the disclosure can improve the development and operation convenience of the interface.

(24) Finally, it is worth noting that the foregoing embodiments are merely described to illustrate the technical means of the disclosure and should not be construed as limitations of the disclosure. Even though the foregoing embodiments are referenced to provide detailed description of the disclosure, people having ordinary skill in the art should understand that various modifications and variations can be made to the technical means in the disclosed embodiments, or equivalent replacements may be made for part or all of the technical features; nevertheless, it is intended that the modifications, variations, and replacements shall not make the nature of the technical means to depart from the scope of the technical means of the embodiments of the disclosure.

Claims

1. An interface generation system, comprising: a storage device configured to store a design module, an analysis module, a metadata module, and a rendering module; and a processor coupled to the storage device and configured to execute the design module, the analysis module, the metadata module, and the rendering module, wherein the processor executes the design module, so that the design module receives configuration data, the processor executes the metadata module, so that the metadata module stores metadata of a plurality of application programming interfaces according to the configuration data, the analysis module analyzes the configuration data and the metadata to generate interface data, and the rendering module displays an interface on a display according to the interface data, wherein the rendering module generates a data set and page structure data according to the interface data, wherein the rendering module generates a front-end widget according to the page structure data of the interface data, and the rendering module bidirectionally binds the data set and the front-end widget, thereby changing the data set correspondingly with an adjustment of the front-end widget, and the rendering module displays the front-end widget on the display.
2. The interface generation system according to claim 1, wherein the configuration data is related to a name, a type, request content, and an extraction rule of at least one of application program interfaces, wherein the design module calls a corresponding application program interface among the application program interfaces according to submitted data in the configuration data and then obtains corresponding response information.
3. The interface generation system according to claim 1, wherein the rendering module calls a corresponding application program interface among the application program interfaces according to the configuration data and then obtains corresponding calling data.
4. The interface generation system according to claim 1, wherein the rendering module generates

an interactive widget according to submitted data in the configuration data and binds the interactive widget and the submitted data.

5. The interface generation system according to claim 1, wherein the analysis module serializes the interface data and outputs a serialized interface data to the rendering module.

6. The interface generation system according to claim 1, further comprising an electronic apparatus and an interface server, wherein the design module is disposed in the electronic apparatus, and the analysis module, the metadata module, and the rendering module are disposed in the interface server.

7. The interface generation system according to claim 1, wherein the processor calls the plurality of application programming interfaces according to the configuration data and then obtains the metadata, and the metadata module stores the metadata, wherein the metadata comprises a data name, a data type, and a data feature.

8. An interface generation method, comprising: receiving, through a design module, configuration data; storing, through a metadata module, metadata of a plurality of application programming interfaces according to the configuration data; analyzing, through an analysis module, the configuration data and the metadata to generate interface data; displaying, through a rendering module, interface content on a display according to the interface data; generating, through the rendering module, a data set and page structure data according to the interface data; generating, through the rendering module, a front-end widget according to the page structure data of the interface data; bidirectionally binding, through the rendering module, the data set and the front-end widget, thereby changing the data set correspondingly with an adjustment of the front-end widget; and displaying, through the rendering module, the front-end widget on the display.

9. The interface generation method according to claim 8, further comprising: calling, through the design module, a corresponding application program interface among application program interfaces according to submitted data in the configuration data and then obtaining corresponding response information, wherein the configuration data has a name, a type, request content, and an extraction rule related to at least one of the application program interfaces.

10. The interface generation method according to claim 8, further comprising: calling, through the rendering module, a corresponding application program interface among application program interfaces and then obtaining corresponding calling data.

11. The interface generation method according to claim 8, wherein the step of displaying, through the rendering module, the interface content on the display according to the interface data further comprises: generating, through the rendering module, an interactive widget according to submitted data in the configuration data and binding the interactive widget and the submitted data.

12. The interface generation method according to claim 8, wherein the step of analyzing, through the analysis module, the configuration data and the metadata to generate the interface data further comprises: serializing, through the analysis module, the interface data; and outputting, through analysis module, a serialized interface data to the rendering module.

13. The interface generation method according to claim 8, wherein the design module is disposed in an electronic apparatus, and the analysis module, the metadata module, and the rendering module are disposed in an interface server.

14. The interface generation method according to claim 8, wherein the step of storing, through the metadata module, the metadata of the plurality of application programming interfaces according to the configuration data further comprises: calling, through a processor, the plurality of application programming interfaces according to the configuration data and then obtaining the metadata; and storing, through the metadata module, the metadata, wherein the metadata comprises a data name, a data type, and a data feature.
