

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411788
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Jin; Young-Jae et al.

Chiplet system and method for communicating between chiplets in chiplet system

Abstract

The present disclosure relates to a method for communicating between chiplets in a chiplet system. The chiplet system includes a first chiplet and a second chiplet, and the method includes, by the first chiplet, generating a die-to-die interface flit from a first protocol type transaction based on conversion information, by the first chiplet, transmitting the die-to-die interface flit to the second chiplet, and, by the second chiplet, generating a second protocol type transaction from the die-to-die interface flit based on the conversion information.

Inventors: Jin; Young-Jae (Seongnam-si, KR), Yu; Chang-Hyo (Seongnam-si, KR)

Applicant: REBELLIONS INC. (Seongnam-si, KR)

Family ID: 93670824

Assignee: REBELLIONS INC. (Seongnam-si, KR)

Appl. No.: 18/807849

Filed: August 16, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250077457 A1	Mar. 06, 2025

Foreign Application Priority Data

KR	10-2023-0114968	Aug. 30, 2023
KR	10-2023-0181259	Dec. 13, 2023

Publication Classification

Int. Cl.: G06F13/40 (20060101); **G06F13/42** (20060101); **G06F15/78** (20060101)

U.S. Cl.:

CPC **G06F13/4004** (20130101); **G06F13/4282** (20130101); **G06F15/7807** (20130101);
G06F2213/40 (20130101)

Field of Classification Search

CPC: G06F (13/4004)

USPC: 710/305

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6678535	12/2003	Narayanaswami	370/466	H04L 69/08
6898766	12/2004	Mowery	710/114	G06F 13/4045
2002/0136224	12/2001	Motley	370/477	H04L 12/4604
2005/0021874	12/2004	Georgiou	709/250	G06F 15/167
2008/0086588	12/2007	Danilak	711/103	G06F 13/385
2008/0183916	12/2007	Bellows	710/33	G06F 11/106
2013/0077635	12/2012	Deivasigamani	370/402	G06F 13/4045
2015/0016046	12/2014	Shaeffer	361/679.32	G06F 13/385
2015/0248371	12/2014	Zheng	710/315	G06F 15/7825
2016/0026742	12/2015	Schelle	711/104	H03K 19/17728
2019/0095377	12/2018	Brown	N/A	G06F 13/1673
2019/0179785	12/2018	Keeth	N/A	H01L 23/5385
2019/0243700	12/2018	Brewer	N/A	H04L 69/12
2020/0133902	12/2019	Tang	N/A	G06F 13/4027
2022/0066969	12/2021	Patrick	N/A	G06F 13/4031
2022/0070089	12/2021	Brewer	N/A	H04L 45/586
2022/0070284	12/2021	Patrick	N/A	H04L 69/18
2022/0222194	12/2021	Chandwani	N/A	G06F 13/1663
2023/0080284	12/2022	Lee	N/A	N/A
2023/0123826	12/2022	Magee	365/233.1	H03K 19/1774
2023/0162766	12/2022	Jo	365/189.05	G11C 16/08
2023/0409332	12/2022	Safranek	N/A	G06F 9/3877
2024/0045827	12/2023	Li	N/A	H04L 12/66
2024/0295989	12/2023	Kavala	N/A	G06F 13/4068
2025/0006642	12/2024	Haba	N/A	H01L 25/0655

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2018-0094113	12/2017	KR	N/A
10-2021-0135996	12/2020	KR	N/A
10-2023-0038082	12/2022	KR	N/A
10-2023-0125324	12/2022	KR	N/A
2017/123284	12/2016	WO	N/A

2020/190369	12/2019	WO	N/A
2022/149080	12/2021	WO	N/A
2023/121812	12/2022	WO	N/A

Primary Examiner: Myers; Paul R.

Attorney, Agent or Firm: BROADVIEW IP LAW, PC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2023-0114968, filed in the Korean Intellectual Property Office on Aug. 30, 2023, and Korean Patent Application No. 10-2023-0181259, filed in the Korean Intellectual Property Office on Dec. 13, 2023, the entire contents of which are hereby incorporated by reference.

BACKGROUND

Technical Field

(2) The present disclosure relates to a chiplet system and a method for communicating between chiplets in a chiplet system.

Description of the Related Art

(3) As the demand for high performance and miniaturization of semiconductor devices and electronic products using the semiconductor devices increases, various package technologies related to semiconductor devices are being developed. In recent years, along with the development of these technologies, packaging technologies using chiplets have recently been developed.

(4) Chiplet system may refer to a system that is provided by, rather than configuring chips performing various functions on one die (or substrate), dividing the chips in units of functionalities, configuring the divided chips on each of a plurality of dies (chiplet), and packaging them into one system. That is, the chiplet system was developed to overcome the limitations of existing monolithic chips, and the dies in the package may be connected to each other through a silicon interposer and the chiplets in the chiplet system communicate with each other according to a die-to-die communication standard such as universal chiplet interconnect express (UCIe).

(5) Meanwhile, the detailed configurations of each of the plurality of dies (chiplets) included in the chiplet system may be different from each other, and in this case, there is a problem that communication between a plurality of dies (chiplets) cannot be performed normally even if the standard communication standard is utilized. Accordingly, in designing the chiplet system, there is a need for a method that can configure the chiplet system regardless of the detailed configuration of each of the plurality of chiplets.

SUMMARY

(6) In order to solve one or more problems (e.g., the problems described above and/or other problems not explicitly described herein), the present disclosure provides a chiplet system and a method for communicating between chiplets in the chiplet system.

(7) According to some examples, a method for communicating between chiplets in a chiplet system, in which the chiplet system may include a first chiplet and a second chiplet, may include, by the first chiplet, generating a die-to-die interface flit from a first protocol type transaction based on conversion information, by the first chiplet, transmitting the die-to-die interface flit to the second chiplet, and, by the second chiplet, generating a second protocol type transaction from the die-to-die interface flit based on the conversion information.

(8) In some examples, the first chiplet further may include a bus system, the receiving the first data

may include receiving the first data through the bus system, the first data may include a first protocol type transaction associated with the first chiplet, the conversion information may include encoding information associated with a second protocol, in which the second protocol may be associated with the second chiplet, and the second data may include a payload of a first die-to-die interface flit associated with the second protocol.

(9) In some examples, the first chiplet may further include a physical (PHY) layer, and the transmitting by the first chiplet the die-to-die interface flit to the second chiplet may include, by the adapter layer of the first chiplet, transmitting the die-to-die interface flit to the PHY layer of the first chiplet, and, by the PHY layer of the first chiplet, transmitting the die-to-die interface flit to the second chiplet.

(10) In some examples, before generating the die-to-die interface flit, may further include, by the first chiplet and the second chiplet, exchanging the conversion information.

(11) In some examples, the conversion information may further include information on a packet ID, a payload type code, a payload type size, and a payload size.

(12) In some examples, the payload type code may include a write address code, a write data code, a write response code, a read address code, and a read data code.

(13) In some examples, the second chiplet may include a PHY layer, and the transmitting by the first chiplet the die-to-die interface flit to the second chiplet may include, by the first chiplet, transmitting the die-to-die interface flit to the PHY layer of the second chiplet.

(14) In some examples, the second chiplet may include a controller including an adapter layer and a protocol layer, and the generating by the second chiplet the second protocol type transaction from the die-to-die interface flit based on the conversion information may include, by the adapter layer of the second chiplet, extracting a payload of the die-to-die interface flit from the flit, and, by the protocol layer of the second chiplet, generating the second protocol type transaction from the payload.

(15) In some examples, the first protocol may relate to the first chiplet, the second protocol may relate to the second chiplet, and the first protocol and the second protocol may be different from each other.

(16) In some examples, the first chiplet and the second chiplet may be designed based on universal chiplet interconnect express (UCIe) standard, and the die-to-die interface flit may include a UCIe flit.

(17) According to some examples, a chiplet system, in which the chiplet system may include a first chiplet and a second chiplet, the first chiplet may be configured to generate a die-to-die interface flit from a first protocol type transaction based on conversion information, and transmit the die-to-die interface flit to the second chiplet, and the second chiplet may be configured to generate a second protocol type transaction from the die-to-die interface flit based on the conversion information.

(18) In some examples, the first chiplet may include a controller including a protocol layer and an adapter layer, and the generating the die-to-die interface flit from the first protocol type transaction based on the conversion information may include, by the protocol layer of the first chiplet, generating a payload of the die-to-die interface flit from the first protocol type transaction based on the conversion information, by the adapter layer of the first chiplet, generating a header of the die-to-die interface flit, and, by the adapter layer of the first chiplet, generating the die-to-die interface flit by combining the header and the payload.

(19) In some examples, the first chiplet may further include a PHY layer, and the transmitting the die-to-die interface flit to the second chiplet may include, by the adapter layer of the first chiplet, transmitting the die-to-die interface flit to the PHY layer of the first chiplet, and, by the PHY layer of the first chiplet, transmitting the die-to-die interface flit to the second chiplet.

(20) In some examples, before generating the die-to-die interface flit, the first chiplet and the second chiplet may exchange the conversion information.

- (21) In some examples, the conversion information may further include information on a packet ID, a payload type code, a payload type size, and a payload size.
- (22) In some examples, the payload type code may include a write address code, a write data code, a write response code, a read address code, and a read data code.
- (23) In some examples, the second chiplet may include a PHY layer, and the transmitting the die-to-die interface flit to the second chiplet may include transmitting the die-to-die interface flit to the PHY layer of the second chiplet.
- (24) In some examples, the second chiplet may include a controller including an adapter layer and a protocol layer, and the generating the second protocol type transaction from the die-to-die interface flit based on the conversion information may include, by the adapter layer of the second chiplet, extracting a payload of the die-to-die interface flit from the flit, and, by the protocol layer of the second chiplet, generating a second protocol type transaction from the payload.
- (25) In some examples, the first protocol may relate to the first chiplet, the second protocol may relate to the second chiplet, and the first protocol and the second protocol may be different from each other.
- (26) In some examples, the first chiplet and the second chiplet may be designed based on the universal chiplet interconnect express (UCIe) standard, and the die-to-die interface flit may include a UCIe flit.
- (27) According to various aspects of the present disclosure, at least one chiplet included in the chiplet system may include a conversion device that converts data based on conversion information (e.g., encoding information, decoding information) received from a partner chiplet. Accordingly, interoperability can be improved compared to a chiplet system that is capable of converting only a predetermined number of protocols. In addition, each configuration of the chiplet may be designed independently regardless of the configuration of the partner chiplet in the chiplet system.
- (28) According to various aspects of the present disclosure, a chiplet system may be configured, which is capable of encoding and decoding data based on the same conversion information, thereby enabling communication between chiplets adopting different protocols. Accordingly, interoperability can be improved compared to a chiplet system that is capable of converting only a predetermined number of protocols. In addition, each configuration of the chiplet can be designed independently regardless of the configuration of the partner chiplet in the chiplet system.
- (29) The effects of the present disclosure are not limited to the effects described above, and other effects not described herein can be clearly understood by those of ordinary skill in the art (referred to as “ordinary technician”) from the description of the claims.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objects, features and advantages of the present disclosure will be described with reference to the accompanying drawings described below, where similar reference numerals indicate similar elements, but not limited thereto, in which:
- (2) FIG. 1 is a diagram provided to explain a configuration of a chiplet;
- (3) FIG. 2 is a diagram provided to explain a configuration of a chiplet system including a plurality of chiplets;
- (4) FIG. 3 is a diagram provided to explain a method for communicating between chiplets;
- (5) FIG. 4 is a diagram provided to explain a method for transmitting a first protocol type transaction of a first chiplet to a second chiplet;
- (6) FIG. 5 is a diagram provided to explain a method for transmitting a second protocol type transaction of the second chiplet to the first chiplet;
- (7) FIG. 6 is a diagram provided to explain a format of a die-to-die interface flit;

- (8) FIG. 7 is a diagram provided to explain conversion information;
- (9) FIG. 8 is a diagram provided to explain conversion information associated with a uni-directional protocol;
- (10) FIG. 9 is a diagram provided to explain an indicator code;
- (11) FIG. 10 is a diagram provided to explain another method for performing communication between chiplets;
- (12) FIG. 11 is a diagram provided to explain conversion information;
- (13) FIG. 12 is a diagram provided to explain another method for transmitting the first protocol type transaction of the first chiplet to the second chiplet;
- (14) FIG. 13 is a flowchart provided to explain a method for communicating between chiplets in a chiplet system;
- (15) FIG. 14 is a flowchart provided to explain a method for communicating between chiplets in a chiplet system according to another aspect of the present disclosure; and
- (16) FIG. 15 is a diagram provided to explain a method for transmitting the first protocol type transaction of the first chiplet to the second chiplet according to another aspect of the present disclosure.

DETAILED DESCRIPTION

- (17) Hereinafter, example details for the practice of the present disclosure will be described in detail with reference to the accompanying drawings. However, in the following description, detailed descriptions of well-known functions or configurations will be omitted if it may make the subject matter of the present disclosure rather unclear.
- (18) In the accompanying drawings, the same or corresponding components are assigned the same reference numerals. In addition, in the following description of various examples, duplicate descriptions of the same or corresponding components may be omitted. However, even if descriptions of components are omitted, it is not intended that such components are not included in any example.
- (19) Advantages and features of the disclosed examples and methods of accomplishing the same will be apparent by referring to examples described below in connection with the accompanying drawings. However, the present disclosure is not limited to the examples disclosed below, and may be implemented in various forms different from each other, and the examples are merely provided to make the present disclosure complete, and to fully disclose the scope of the disclosure to those skilled in the art to which the present disclosure pertains.
- (20) The terms used herein will be briefly described prior to describing the disclosed example(s) in detail. The terms used herein have been selected as general terms which are widely used at present in consideration of the functions of the present disclosure, and this may be altered according to the intent of an operator skilled in the art, related practice, or introduction of new technology. In addition, in specific cases, certain terms may be arbitrarily selected by the applicant, and the meaning of the terms will be described in detail in a corresponding description of the example(s). Therefore, the terms used in the present disclosure should be defined based on the meaning of the terms and the overall content of the present disclosure rather than a simple name of each of the terms.
- (21) The singular forms “a,” “an,” and “the” as used herein are intended to include the plural forms as well, unless the context clearly indicates the singular forms. Further, the plural forms are intended to include the singular forms as well, unless the context clearly indicates the plural forms. Further, throughout the description, when a portion is stated as “comprising (including)” a component, it is intended as meaning that the portion may additionally comprise (or include or have) another component, rather than excluding the same, unless specified to the contrary.
- (22) Further, the term “module” or “unit” used herein refers to a software or hardware component, and “module” or “unit” performs certain roles. However, the meaning of the “module” or “unit” is not limited to software or hardware. The “module” or “unit” may be configured to be in an

addressable storage medium or configured to play one or more processors. Accordingly, as an example, the “module” or “unit” may include components such as software components, object-oriented software components, class components, and task components, and at least one of processes, functions, attributes, procedures, subroutines, program code segments, drivers, firmware, micro-codes, circuits, data, database, data structures, tables, arrays, and variables. Furthermore, functions provided in the components and the “modules” or “units” may be combined into a smaller number of components and “modules” or “units”, or further divided into additional components and “modules” or “units.”

(23) The “module” or “unit” may be implemented as a processor and a memory. The “processor” should be interpreted broadly to encompass a general-purpose processor, a Central Processing Unit (CPU), a microprocessor, a Digital Signal Processor (DSP), a controller, a microcontroller, a state machine, and so forth. Under some circumstances, the “processor” may refer to an application-specific integrated circuit (ASIC), a programmable logic device (PLD), a field-programmable gate array (FPGA), etc. The “processor” may refer to a combination for processing devices, e.g., a combination of a DSP and a microprocessor, a combination of a plurality of microprocessors, a combination of one or more microprocessors in conjunction with a DSP core, or any other combination of such configurations. In addition, the “memory” should be interpreted broadly to encompass any electronic component that is capable of storing electronic information. The “memory” may refer to various types of processor-readable media such as random access memory (RAM), read-only memory (ROM), non-volatile random access memory (NVRAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable PROM (EEPROM), flash memory, magnetic or marking data storage, registers, etc. The memory is said to be in electronic communication with a processor if the processor can read information from and/or write information to the memory. The memory integrated with the processor is in electronic communication with the processor.

(24) In addition, terms such as first, second, A, B, (a), (b), etc. used in the following examples are only used to distinguish certain components from other components, and the nature, sequence, order, etc. of the components are not limited by the terms.

(25) In addition, in the following examples, if a certain component is stated as being “connected,” “combined” or “coupled” to another component, it is to be understood that there may be yet another intervening component “connected,” “combined” or “coupled” between the two components, although the two components may also be directly connected or coupled to each other.

(26) In addition, as used in the following examples, “comprise” and/or “comprising” does not foreclose the presence or addition of one or more other elements, steps, operations, and/or devices in addition to the recited elements, steps, operations, or devices.

(27) In addition, the expression “each of a plurality of A” may refer to each of all components included in the plurality of A, or may refer to each of some of the components included in a plurality of A.

(28) Hereinafter, various examples of the present disclosure will be described in detail with reference to the accompanying drawings.

(29) FIG. 1 is a diagram provided to explain a configuration of a chiplet. In FIG. 1, a chiplet **100** may be at least one chiplet included in a chiplet system. In addition, the chiplet **100** may include a plurality of IP blocks **110_1** to **110_n**, a bus system **112**, a controller **120**, and a physical (PHY) layer **130**.

(30) The plurality of IP blocks **110_1** to **110_n** may be reusable logics, cells, and/or units of integrated circuit layout design. Each of the plurality of IP blocks **110_1** to **110_n** may be designed to perform a specific function and functionally combined to implement a complex multifunctional SoC. For example, an IP block may include a processor core, a memory block, a digital signal processor (DSP), a peripheral interface, a graphics device (GPU), an analog block, a communication block, a security block, a power management device, etc.

(31) The bus system **112** may serve as a passage for transmitting data and/or control signals. The bus system **112** may serve to connect between the plurality of IP blocks **110_1** to **110_n** or connect to another configuration (e.g., the controller **120**, etc.) of a chiplet **110**. In addition, the bus system **112** may use specific bus protocols (e.g., AXI3, AXI4, APB, CXS.B, DDR, etc.) for data transmission and reception between components.

(32) The controller **120** may perform a function of managing and coordinating communication and interaction between chiplets. This allows the controller **120** to process tasks such as data transmission, synchronization, and/or power management between a plurality of chiplets included in the chiplet system to control the chiplets to operate as a consistent system. The controller **120** may include a protocol layer **121** and an adapter layer **125**.

(33) The protocol layer **121** may determine a method of formatting and encoding data for data transmission between chiplets. The protocol layer **121** may support a plurality of protocols for maximizing efficiency and reducing latency. For example, the protocol layer **121** may support any protocol supported in the chiplet system, such as PCI non-Flit/Flit Mode, CXL 68B/256B Flight Mode, Streaming Protocol, etc., but is not limited thereto.

(34) The protocol layer **121** may include a conversion device **123** for implementing a protocol independent chiplet system. The conversion device **123** may include an encoder that generates a payload of a die-to-die interface flit from the received transaction and/or a decoder that generates a transaction from the payload of the received die-to-die interface flit. This will be described in more detail below with reference to FIGS. 4 and 5.

(35) The adapter layer **125** may serve to convert a communication interface between a plurality of chiplets in the chiplet system. For example, the adapter layer **125** may perform a link management function, a protocol arbitration and negotiation function, an optional error correction function (e.g., CRC, etc.).

(36) The PHY layer **130** may process physical transmission of data between chiplets. For example, the PHY layer **130** may be in charge of hardware processing related to data transmission, such as signal transmission and reception, modulation and demodulation, conversion between digital bits, etc. The PHY layer **130** may include a logical PHY **132** and an electrical PHY **134**. The logical PHY **132** may be in charge of logical processing of the PHY layer **130**. For example, the logical PHY **132** may perform functions such as serialization and deserialization (SerDes), clock data recovery and data transmission preparation, interpretation of received data, etc. The electrical PHY **134** may be in charge of electrical processing of the PHY layer **130**. For example, the electrical PHY **134** may process matters related to the characteristics of the electrical signal (e.g., voltage, signal integrity, etc.).

(37) The respective components of the chiplet **100** are shown in FIG. 1 to illustrate functional components that can be divided on the basis of functions, and in the actual physical environment, a plurality of components may be implemented as being integrated with each other. In addition, the chiplet **100** may not include at least one of the components described above, and may further include at least one other component.

(38) FIG. 2 is a diagram provided to explain a configuration of a chiplet system **200** including a plurality of chiplets **210**, **220**, **230**, and **240**. Referring to FIG. 2, the chiplet system **200** may include a plurality of chiplets. For example, the chiplet system **200** may include a first chiplet **210**, a second chiplet **220**, a third chiplet **230**, and a fourth chiplet **240**. However, the number of chiplets included in the chiplet system **200** is not limited to the above. According to various aspects, the chiplet system **200** may not include at least one of the chiplets described above, and may further include at least one other chiplet. The chiplet system **200** including a plurality of chiplets may be packaged, and thus may be referred to as a package device or an electronic device.

(39) The plurality of chiplets may be connected to each other through a first interface. For example, the first chiplet **210** and the second chiplet **220** may be connected through an interface (1-1) **251**, the first chiplet **210** and the third chiplet **230** may be connected through an interface (1-2) **252**, the

second chiplet **220** and the fourth chiplet **240** may be connected through an interface (1-3) **253**, and the third chiplet **230** and the fourth chiplet **240** may be connected through an interface (1-4) **254**.

The first interface may refer to a die-to-die interface, and may include UCIE etc., for example.

(40) Any one (e.g., the first chiplet **210**) of the plurality of chiplets may be connected to an external device (e.g., a host device **260**) through a second interface **261**. In this case, the other chiplets (e.g., the second chiplet **220**, the third chiplet **230**, and the fourth chiplet **240**) may be restricted from communicating with the external device. A chiplet (e.g., the first chiplet **210**) communicating with the external device may be referred to as a main chiplet, a primary die, a base chiplet, etc., and the other chiplets (e.g., the second chiplet **220**, the third chiplet **230**, the fourth chiplet **240**) with limited communication with the external device may be referred to as a sub-chiplet, a secondary die, a partner chiplet, etc. For example, the second interface **261** may refer to a host interface, and may include a peripheral component interconnect express (PCIe), etc.

(41) The chiplet system **200** including a plurality of chiplets may expand the functions of the host device **260** (or the host system) and perform parallel processing on at least some functions. For example, the host device **260** may manage the chiplet system and distribute tasks related to at least some functions to the chiplet system, and the chiplet system may process the distributed tasks in parallel. This enables to not only optimize and enhance the performance of the entire system including the host device **260** and the chiplet system, but also provide a scalable computing environment. The chiplet system may perform functions of a multi-processor, a memory controller, a cache, a network interface, etc.

(42) FIG. 3 is a diagram provided to explain a method for communicating between chiplets. In FIG. 3, a first chiplet **300** and a second chiplet **350** may be chiplets in the same chiplet system. In the following description, a description for a configuration that is the same as or similar to the configuration already described above in FIG. 1 may be omitted.

(43) The first chiplet **300** may use a first protocol type as a bus protocol, and the second chiplet **350** may use a second protocol type as a bus protocol. In this case, the first protocol type and the second protocol type may be different from each other, or may be the same protocol with different detailed parameters (e.g., AxSIZE, AxLen, number of user bits, etc.). For example, the first protocol type may be AXI3, and the second protocol type may be AXI4. As another example, the first protocol type may be AXI4 with 40 user bits, and the second protocol type may be AXI4 with 20 user bits.

(44) A plurality of IP blocks **310_1** to **310_n** and a controller **320** of the first chiplet **300** may transmit and receive data to and from each other through a bus system **312**. For example, a protocol layer **321** of the controller **320** may receive first protocol type transactions **314** from the plurality of IP blocks **310_1** to **310_n** of the first chiplet through the bus system **312**, and a conversion device **323** included in the protocol layer **321** may encode the transactions **314** to generate a payload of a die-to-die interface flit. As another example, the protocol layer **321** of the controller **320** may transmit the first protocol type transaction **314** decoded by the conversion device **323** to the plurality of IP blocks **310_1** to **310_n** through the bus system **312**. In this case, the die-to-die interface flit may be a UCIE flit.

(45) The protocol layer **321** and an adapter layer **325** may transmit and receive data through a flit-aware die-to-die interface (FDI) **327**. The FDI **327** may refer to an interface that recognizes and manages data in units of flits when transmitting the data. For example, the protocol layer **321** may transmit a payload of a die-to-die interface flit generated by the conversion device **323** to the adapter layer **325** through the FDI **327**. As another example, the protocol layer **321** may receive the payload of the die-to-die interface flit extracted from the adapter layer **325** through the FDI **327**.

(46) The controller **320** and a PHY layer **330** may transmit and receive data through a raw die-to-die interface (RDI) **329**. The RDI **329** may refer to an interface that directly transmits data without complex data processing or processing for the simplification of data transmission and minimized latency. For example, the adapter layer **325** of the controller **320** may generate a header and a trailer of a die-to-die interface flit, combine the same with a payload to generate a die-to-die

interface flit, and transmit the generated die-to-die interface flit to the PHY layer **330** through the RDI **329**. As another example, the PHY layer **330** may transmit a die-to-die interface flit received from the second chiplet **350** to the adapter layer **325** through the RDI **329**.

(47) The first chiplet **300** and the second chiplet **350** may transmit and receive data to and from each other through a UCIE interface **340**. For example, the first chiplet **300** and the second chiplet **350** may transmit and receive die-to-die interface flits to and from each other through the UCIE interface **340**. FIG. 3 illustrates the UCIE interface **340** as an example of the interface connecting the first chiplet **300** and the second chiplet **350**, but aspects are not limited thereto, and various die-to-die interfaces (e.g., High-Bandwidth Interconnect (HBI), Bunch of Wires (BoW), extra-short reach (XSR), etc.) may be utilized.

(48) Likewise, a PHY layer **360** and a controller **370** of the second chiplet **350** may transmit and receive data to and from each other through a RDI **362**. In addition, an adapter layer **371** and a protocol layer **373** of the controller **370** may transmit and receive data to and from each other through an FDI **375**. The controller **370** and a plurality of IP blocks **382_1** to **382_n** of the second chiplet **350** may transmit and receive a second protocol type transaction **377** to and from each other through a bus system **380**.

(49) Unlike the protocol layer **373** of the second chiplet **350**, the protocol layer **373** of the first chiplet **300** may include the conversion device **323**. The conversion device **323** may receive conversion information (encoding information) from the protocol layer **373** of the second chiplet **350** and generate a payload of the first die-to-die interface flit from the transaction **314** of the first protocol type. In addition, the conversion device **323** may receive conversion information (decoding information) from the protocol layer **373** of the second chiplet and generate the first protocol type transaction **314** from the payload of the second die-to-die interface flit transmitted from the second chiplet **350**. This will be described in more detail below with reference to FIGS. 4 and 5. In FIG. 3, the conversion device **323** illustrates the functional elements for performing encoding and decoding, and is not limited to any specific implementation method. For example, the conversion device **323** may be a hardware device including a converter that performs encoding and decoding and a register that stores encoding information and decoding information. As another example, the conversion device **323** may be software that performs encoding and decoding.

(50) As described above, at least one chiplet included in the chiplet system may include a conversion device that converts data based on conversion information (e.g., encoding information and/or decoding information) received from the partner chiplet. Accordingly, interoperability can be improved compared to a chiplet system that is capable of converting only a predetermined number of protocols. In addition, each configuration of the chiplet can be designed independently regardless of the configuration of the partner chiplet in the chiplet system.

(51) FIG. 4 is a diagram provided to explain a method for transmitting a first protocol type transaction **440** of a first chiplet **400** to a second chiplet **450**. Referring to FIG. 4, a protocol layer **410** of the first chiplet **400** may include an encoder **420** that is a conversion device, and the encoder **420** may include a CPU **422** and a sub-memory **424**.

(52) The sub-memory **424** may receive and store the transaction **440** from a plurality of IP blocks (not illustrated) through a bus system (not illustrated) of the first chiplet **400**. The sub-memory **424** may transmit the stored transaction **440** to the CPU **422**.

(53) The CPU **422** may generate a payload **426** of a UCIE flit associated with the second protocol from the transaction **440**. For example, the CPU **422** may map information included in the transaction **440** according to a specific bit order to generate the payload **426**. In this case, the bit order may refer to a bit order in which the second chiplet using the second protocol may generate a second protocol type transaction from the payload **426** without additional decoding operation. To this end, the CPU **422** may receive encoding information **472** from the second chiplet. For example, the CPU **422** may receive the encoding information **472** from a protocol layer **470** of the second chiplet.

(54) The encoding information **472** may include information associated with the second protocol of the second chiplet. For example, the encoding information **472** is a protocol between the payload **426** of the second chiplet and the second protocol type transaction, and may include information on one or more bus channels of the second chiplet, regions and sizes of bits allocated to each of one or more bus channels of the second chiplet, an indicator code indicating an operable bus channel of one or more bus channels of the second chiplet, etc. For example, the encoding information **472** refers to information encoded in the first chiplet, and may include information used for decoding in the protocol layer **470** of the second chiplet. As another example, the encoding information **472** may include information encoded and/or decoded according to the second protocol of the second chiplet. In addition, the encoding information **472** may be utilized in both directions, and thus may be the same as decoding information **518** of FIG. 5, which will be discussed below. A detailed example of the encoding information **472** will be described below with reference to FIG. 7.

(55) The CPU **422** may determine an encoding rule (e.g., a rule for mapping data according to a specific bit order) based on the received encoding information **472**, and may generate the payload **426** of a UCIE flit by encoding the transaction **440** according to the determined encoding rule. The CPU **422** may transmit the payload **426** of the UCIE flit to the adapter layer and a PHY layer **430** through the UCIE protocol. The adapter layer may generate a header and a trailer of the UCIE flit, and may combine the same with the payload **426** to generate a UCIE flit. The UCIE flit generated in this way may be transmitted to the second chiplet **450** through the PHY layer, and the UCIE protocol may also be utilized in this process.

(56) The adapter layer and a PHY layer **460** of the second chiplet may receive the UCIE flit from the first chiplet **400**. The adapter layer may extract the payload from the received UCIE flit, and transmit the extracted payload to the protocol layer **470** of the second chiplet **450** through the UCIE protocol. Because the payload of the UCIE flit is generated based on the encoding information **472**, it may be associated with the second protocol, and accordingly, the protocol layer **470** may generate a second protocol type transaction from the payload of the UCIE flit without additional operations (e.g., decoding, etc.). The protocol layer **470** may transmit a second protocol type transaction to the IP block (not illustrated) of the second chiplet **450** through a bus system (not illustrated).

(57) Although FIG. 4 illustrates that UCIE flit and the UCIE protocols are utilized to transmit the transaction **440** of the first protocol type of the first chiplet **400** to the second chiplet **450**, aspects are not limited thereto, and various die-to-die connection standards (e.g., HBI, BoW, XSR, etc.) may be utilized.

(58) Although FIG. 4 illustrates the adapter layer and the PHY layers **430** and **460** as one block, aspects are not limited thereto, and each of the adapter layer and the PHY layers **430** and **460** may be implemented as separate layers.

(59) FIG. 5 is a diagram provided to explain a method for transmitting a second protocol type transaction of the second chiplet **450** to the first chiplet **400**. Referring to FIG. 5, the protocol layer **410** of the first chiplet **400** may include a decoder **510** which is a conversion device, and the decoder **510** may include a sub-memory **512** and a CPU **514**.

(60) The protocol layer **470** of the second chiplet may receive second protocol type transactions from a plurality of IP blocks (not illustrated) through a bus system (not illustrated). The protocol layer **470** may generate a payload of a UCIE flit associated with the second protocol from the second protocol type transactions, and may transmit the payload to the adapter layer and the PHY layer **460** of the second chiplet **450** through the UCIE protocol. The adapter layer of the second chiplet may generate a header of the UCIE flit and a trailer of the UCIE flit, and combine them with the payload to generate a UCIE flit. The generated UCIE flit may be transmitted to the first chiplet **400** through the PHY layer, and the UCIE protocol may also be utilized in this process.

(61) The adapter layer and the PHY layer **430** of the first chiplet **400** may receive a UCIE flit from the second chiplet **450**. The adapter layer may extract a payload from the received UCIE flit, and

transmit the extracted payload to the protocol layer **410** of the first chiplet **400** through the UCIE protocol.

(62) The sub-memory **512** may receive a payload **516** of the UCIE flit from the adapter layer of the first chiplet **400** and store the same. The sub-memory **512** may transmit the stored payload **516** to the CPU **514**.

(63) The CPU **514** may generate a first protocol type transaction **520** from the payload **516** of the UCIE flit. For example, the CPU **514** may decode the payload **516** mapped with the data according to a specific bit order to generate the first protocol type transaction **520**. To this end, the CPU **514** may receive the decoding information **518** from the second chiplet. For example, the CPU **514** may receive the decoding information **518** from the protocol layer **470** of the second chiplet.

(64) The decoding information **518** may include information associated with the second protocol of the second chiplet. For example, the decoding information **518** is a protocol between the payload **516** of the second chiplet and the second protocol type transaction, and may include information on one or more bus channels of the second chiplet, regions and sizes of bits allocated to each of one or more bus channels of the second chiplet, an indicator code indicating an operable bus channel of one or more bus channels of the second chiplet, etc. For example, the decoding information **518** refers to information used for decoding in the first chiplet, and may include information used for encoding in the protocol layer **470** of the second chiplet. As another example, the decoding information **518** may include information encoded and/or decoded according to the second protocol of the second chiplet. In addition, the decoding information **518** may be utilized in both directions, and thus may be the same as the encoding information **472** of FIG. 4 described above. A detailed example of the decoding information **518** will be described below with reference to FIG. 7.

(65) The CPU **514** may determine a decoding rule (e.g., for decoding data included in a payload according to a specific bit order, etc.) based on the received decoding information **518**, and generate the first protocol type transaction **520** by decoding the payload **516** of the UCIE flit associated with the second protocol according to the determined decoding rule. The CPU **514** may transmit the transaction **520** to an IP block (not illustrated) of the first chiplet **400** through a bus system (not illustrated).

(66) Although FIG. 5 illustrates the adapter layer and the PHY layers **430** and **460** as one block, aspects are not limited thereto, and each of the adapter layer and the PHY layers **430** and **460** may be implemented as separate layers.

(67) Although FIG. 5 illustrates that UCIE flit and UCIE protocols are utilized to transmit the second protocol type transaction of the second chiplet **450** to the first chiplet **400**, aspects are not limited thereto, and various die-to-die connection standards (e.g., HBI, BoW, XSR, etc.) may be utilized.

(68) FIG. 6 is a diagram provided to explain a format of a die-to-die interface flit **600**. A plurality of chiplets in the chiplet system may be designed based on the UCIE standard. A plurality of chiplets in the chiplet system may be connected to each other using a UCIE interface as a die-to-die interface. The protocol layer of each of the plurality of chiplets in the chiplet system may support the UCIE standard flit-based protocol mode (e.g., PCIe non-Flit/Flit Mode, CXL 68B/256B Fleet Mode, Streaming Protocol, etc.), and each protocol mode may support a plurality of protocol modes (e.g., Raw, 68B, Standard 256B Start/End Header, Latency-Optimized 256B w/or w/o Optional Bytes). Through this, each of the plurality of chiplets in the chiplet system can perform a die-to-die interface operation by configuring protocols supported by the protocol layer into flits suitable for each protocol and transmitting and receiving them through the UCIE interface.

(69) In FIG. 6, the die-to-die interface flit **600** may be a flit generated by a chiplet designed based on the UCIE standard. The flit **600** may include a header **610**, a payload **620**, and a trailer **630**.

(70) The header **610** is positioned at the front end of the data packet and may include control information necessary for data transmission. For example, the header **610** may include addresses of destination and departure of a data packet, a priority level, a packet length, order information, etc.

In addition, the header **610** may include various metadata for processing packets correctly in the network. For example, the header **610** may include routing information, timestamp, protocol information, etc. The header **610** may assist the chiplet to correctly recognize the packet and process the packet in an appropriate manner. The header **610** may be generated by an adapter layer of a chiplet and combined with the payload **620** and the trailer **630** to be described below.

(71) The payload **620** may be positioned next to the header **610** of the flit **600** and may include actual data to be transmitted. For example, the payload **620** may include data on transactions transmitted and received between chiplets in the chiplet system, and may include a write address (WA), a write data (WD) to be written to the memory, a read address (RA) to read data, a write response (WR), etc. Each protocol layer of a plurality of chiplets in the chiplet system may generate the payload **620** by mapping the data described above according to a specific bit order to transmit a transaction to another chiplet, and the bit order may vary depending on the type of bus protocol in use.

(72) The trailer **630** may be positioned at the end of the flit **600**, and may include information for error detection and correction, end of packet indicating information, or other control information. For example, the trailer **630** may include an error check code (e.g., CRC, checksum, etc.) used for verifying if data arrives accurately without errors in the transmission process. Like the header **610**, the trailer **630** may be generated in the adapter layer of the chiplet.

(73) There may be a plurality of headers **610**, payloads **620**, and trailers **630** in the flit **600** or some may be omitted. For example, as illustrated in FIG. 6, the flit **600** may have new payload and trailer positioned next to the trailer **630**. In addition, although FIG. 6 illustrates an example of a die-to-die interface flit format, aspects are not limited thereto, and various types of flit formats may be used. The configuration of the flit **600** may also be variously changed according to the flit format.

(74) FIG. 7 is a diagram provided to explain conversion information. The conversion information may refer to information utilized by the conversion device included in the protocol layer of the chiplet. For example, the conversion information may be information utilized by the encoder to encode, from the first protocol type transaction, the payload of the die-to-die interface flit associated with the second protocol. As another example, the conversion information may be information utilized by the decoder to decode the payload of the die-to-die interface flit associated with the second protocol. The conversion information may be received from a partner chiplet (e.g., a protocol layer of a partner chiplet, etc.) using the second protocol.

(75) A first table **710** illustrated in FIG. 7 represents an example of encoding information. As illustrated, the encoding information may be a mapping table including, as labels, a transaction transmission direction (Direction), a name (Name) of data mapped to a payload of a die-to-die interface flit, bit regions (MSB, LSB) of mapped data and bit size (Size), and may include information on one or more bus channels of a partner chiplet, and information indicating a region and a size of a bit allocated to each channel. For example, the encoding information may include write address data (WA), which is data to be transmitted as information on the write address channel, and the names of detail data included in the write address data (e.g., ADDR, User, Region, QOS, Protection, Cache, Burst Length, Burst Size, Burst Type, Lock, etc.), and the bit region and bit size to which the detail data is mapped. In this case, the detail data may include a specific memory address (ADDR) for the task, a user-defined bit (Userbit) used for the task, a specific region (Region) of memory in which the task takes place, priority or quality of service (QOS) defined for the task, a security mechanism (Protection) for the task, a cache related to the task, a length of data block transmitted at a time when the task is performed, a total amount of data (Burst Size) of data transmitted when the task is performed, a type of burst transmission (Burst Type) of the task, an access restriction (Lock) to a specific resource during the task, etc.

(76) The encoding information may include information on a write address channel as well as other bus channels such as a write data channel, a read address channel, a write response channel, and a read data channel, and information indicating a region and a size of an allocated bit. In addition, the

encoding information may include an indicator code indicating an operable bus channel of one or more bus channels of the partner chiplet.

(77) A second table **720** illustrated in FIG. 7 represents an example of the decoding information. Like the encoding information, the decoding information may be a mapping table including, as labels, a transaction transmission direction (Direction), a name (Name) of data mapped to a payload of a die-to-die interface flit, bit regions (MSB, LSB) of mapped data and bit size (Size), and may include information on one or more bus channels of a partner chiplet, and information indicating a region and a size of a bit allocated to each channel. In addition, the decoding information may include an indicator code indicating an operable bus channel of one or more bus channels of the partner chiplet.

(78) Although FIG. 7 illustrates a table as an example of the encoding information and the decoding information, aspects are not limited thereto, and any format that can represent the association of each component of the encoding information and/or the decoding information may be used. In addition, the conversion information illustrated in FIG. 7 is merely an example, and the information may be partially omitted or added according to the type of bus protocol used by the chiplet. In addition, the encoding information and the decoding information of FIG. 7 may include the same information as a protocol between the transaction of the partner chiplet and the payload of the flit.

(79) FIG. 8 is a diagram provided to explain conversion information **800** associated with a uni-directional protocol. If the bus protocol of the partner chiplet is a uni-directional protocol, the conversion information may include only the encoding information for transmitting the protocol to the partner chiplet. In this case, like the encoding and decoding information of FIG. 7, the conversion information may be a mapping table including, as labels, a transaction transmission direction (Direction), a name (Name) of data mapped to the payload of a die-to-die interface flit, bit regions (MSB, LSB) of mapped data, and bit size (Size), but the transmission direction of the transaction may be one-way rather than two-way.

(80) If the protocol of the partner chiplet is AXI-S, which is a uni-directional protocol, data mapped to the payload of the interface flit may include information on actually transmitted data (TDATA), data validity (TSTRB, TKEEP), terminal indication (TLAST) of a data frame, identifier (TID), destination (TDEST) of a data stream, user-defined signal (TUSER), and function (TWAKEUP) to wake up other components in a specific situation. In addition, the conversion information may include an indicator code indicating an operable bus channel of one or more bus channels of the partner chiplet.

(81) The conversion information illustrated in FIG. 8 is merely an example, and the information may be partially omitted or added according to the type of bus protocol used by the chiplet.

(82) FIG. 9 is a diagram **900** provided to explain the indicator code. The indicator code may be a code indicating an operable bus channel of one or more bus channels of the partner chiplet. The indicator code may be mapped to the top of the payload of the die-to-die interface flit. For example, if “5b1_0000” is mapped to a portion of the payload to which the indicator code is mapped, it may mean that all bus channels WA, WD, RA, WR, and RD of the partner chiplet are not operable. On the other hand, if “5b1_1111” is mapped to a portion of the payload to which the indicator code is mapped, it may mean that all bus channels WA, WD, RA, WR, and RD of the partner chiplet are operable.

(83) The code illustrated in FIG. 9 is an example, and aspects are not limited thereto and the form of the code may vary. Likewise, the name of the bus channel shown in FIG. 9 is also an example, and aspects are not limited thereto and may vary according to the type of bus protocol used by the partner chiplet.

(84) FIG. 10 is a diagram provided to explain another method for performing communication between chiplets. In FIG. 10, a first chiplet **1000** and a second chiplet **1050** may be chiplets in the same chiplet system. In the following description, a description for a configuration that is the same

as or similar to the configuration already described above in FIG. 1 may be omitted.

(85) The first chiplet **1000** may use a first protocol type as a bus protocol, and the second chiplet **1050** may use a second protocol type as a bus protocol. In this case, the first protocol type and the second protocol type may be different from each other, or may be the same protocol with different detailed parameters (e.g., AxSIZE, AxLen, number of user-defined bits, etc.). For example, the first protocol type may be AXI3, and the second protocol type may be AXI4. As another example, the first protocol type may be AXI4 with **40** user-defined bits, and the second protocol type may be AXI4 with 20 user-defined bits.

(86) A plurality of IP blocks **1010_1** to **1010_n** and a controller **1020** of the first chiplet **1000** may transmit and receive data to and from each other through a bus system **1012**. For example, a protocol layer **1021** of the controller **1020** may receive a first protocol type transaction **1014** from the plurality of IP blocks **1010_1** to **1010_n** of the first chiplet through the bus system **1012**, and a first conversion device **1023** may encode the received transaction to generate a payload of a die-to-die interface flit. As another example, the protocol layer **1021** of the controller **1020** may transmit the first protocol type transaction **1014** decoded by the first conversion device **1023** to the plurality of IP blocks **1010_1** to **1010_n** through the bus system **1012**. In this case, the die-to-die interface flit may be a UCIE flit.

(87) The protocol layer **1021** and an adapter layer **1025** may transmit and receive data to and from each other through a flit-aware die-to-die interface (FDI) **1027**. The FDI **1027** may refer to an interface that recognizes and manages data in units of flits when transmitting the data. For example, the protocol layer **1021** may transmit the payload of the die-to-die interface flit generated by the first conversion device **1023** to the adapter layer **1025** through the FDI **1027**. As another example, the protocol layer **1021** may receive the payload of the die-to-die interface flit from the adapter layer **1025** through the FDI **1027**.

(88) The controller **1020** and a PHY layer **1030** may transmit and receive data to and from each other through a raw die-to-die interface (RDI) **1029**. The RDI **1029** may refer to an interface that directly transmits data without complex data processing or processing for the simplification of data transmission and minimized latency. For example, the adapter layer **1025** of the controller **1020** may generate a header and a trailer of a die-to-die interface flit, combine the same with a payload to generate a die-to-die interface flit, and transmit the die-to-die interface flit to the PHY layer **1030** through the RDI **1029**. As another example, the PHY layer **1030** may transmit a die-to-die interface flit received from the second chiplet **1050** to the adapter layer **1025** through the RDI **1029**.

(89) The first chiplet **1000** and the second chiplet **1050** may transmit and receive data to and from each other through a UCIE interface **1040**. For example, the first chiplet **1000** and the second chiplet **1050** may transmit and receive die-to-die interface flits to and from each other through the UCIE interface **1040**.

(90) Like the first chiplet **1000**, a PHY layer **1060** and a controller **1070** of the second chiplet **1050** may transmit and receive data to and from each other through a RDI **1062**. For example, the adapter layer **1071** of the controller **1070** may generate a header and a trailer of a die-to-die interface flit, combine the same with a payload to generate a die-to-die interface flit, and transmit the generated die-to-die interface flit to the PHY layer **1060** through the RDI **1062**. As another example, the PHY layer **1060** may transmit the die-to-die interface flit received from the first chiplet **1000** to the adapter layer **1071** through the RDI **1062**.

(91) The protocol layer **1021** and the adapter layer **1025** may transmit and receive data to and from each other through the FDI **1027**. For example, the protocol layer **1073** may transmit the payload of the die-to-die interface flit generated by the second conversion device **1079** to the adapter layer **1071** through the FDI **1075**. As another example, the protocol layer **1073** may receive the payload of the die-to-die interface flit from the adapter layer **1025** through the FDI **1075**.

(92) The first conversion device **1023** and the second conversion device **1079** may encode and decode data by referring to the same conversion information. For example, the first conversion

device **1023** may encode a first protocol type transaction based on the conversion information to generate a payload of a die-to-die interface flit. The second conversion device **1079** may decode the payload of the die-to-die interface flit transmitted from the first chiplet based on the same conversion information to generate a second protocol type transaction **1077**. As another example, the second conversion device **1079** may encode the second protocol type transaction based on the conversion information to generate a payload of a die-to-die interface flit. The first conversion device **1023** may decode the payload of the die-to-die interface flit transmitted from the second chiplet based on the same conversion information to generate the first protocol type transaction **1014**. To this end, the first chiplet **1000** and the second chiplet **1050** may exchange the conversion information during an initialization process. Details of an example of the conversion information will be described below with reference to FIG. **11**. The controller **1070** and a plurality of IP blocks **1082_1** to **1082_n** of the second chiplet **1050** may transmit and receive the second protocol type transaction **1077** to and from each other through a bus system **1080**.

(93) The first conversion device **1023** and the second conversion device **1079** in FIG. **10** illustrate the functional elements for performing encoding and decoding, and are not limited to any specific implementation method. For example, the first conversion device **1023** and the second conversion device **1079** may be hardware devices including a converter that performs encoding and decoding and a register that stores encoding information and decoding information. As another example, the first conversion device **1023** and the second conversion device **1079** may be software that performs encoding and decoding.

(94) As discussed in the above configuration, a chiplet system may be configured to encode and decode data based on the same conversion information, thereby enabling communication between chiplets adopting different protocols. Accordingly, interoperability can be improved compared to a chiplet system that is capable of converting only a predetermined number of protocols. In addition, each configuration of the chiplet can be designed independently regardless of the configuration of the partner chiplet in the chiplet system.

(95) FIG. **11** is a diagram provided to explain conversion information **1100**. As illustrated in FIG. **11**, the conversion information **1100** may be a mapping table including information on a payload header and payload data.

(96) The information on the header of the payload may include information on a packet ID, a payload type, and a payload size. For example, the information on the header of the payload may include a position in the payload and size of the bit to which the packet ID is to be mapped, a position and size of the bit to which the write address code is to be mapped, and a position and size of the bit to which the payload is to be mapped. In addition, the information on the header of the payload may include a payload type code. For example, the information on the header of the payload may include, as the payload type code, a write address code, a write data code, a write response code, a read address code, and a read data code.

(97) The information on payload data may include information on a specific payload type data. For example, the information on payload data may include information on a position and size of a bit to which the write address data is to be mapped.

(98) The first chiplet and the second chiplet included in the chiplet system may exchange conversion information in the initialization step, and determine a conversion rule based on the same conversion information. For example, in generating a payload of a die-to-die interface flit from a first protocol type transaction, the first conversion device of the first chiplet that has exchanged the conversion information **1100** illustrated in FIG. **11** may encode the data in the order of packet ID, write address code, payload size, and payload data for write address data. In addition, the second conversion device of the second chiplet that has exchanged the same conversion information may recognize that, in the upper bits of the payload of the die-to-die interface flit received from the first chiplet, the write address data is mapped in the order of packet ID, write address code, payload size, and payload data, and decode the same to generate a second protocol type transaction.

(99) FIG. 11 illustrates one example of the conversion information **1100**, but aspects are not limited thereto, and some information may be omitted or added, or other types of information may be included. In addition, the form of the conversion information **1100** is not limited to the mapping table information, and may have various other forms.

(100) FIG. 12 is a diagram provided to explain another method for transmitting a first protocol type transaction **1212** of a first chiplet **1200** to a second chiplet **1250**. In FIG. 12, for example, the first protocol type transaction of the first chiplet may be an AXI4 transaction having a burst length of 32, which is a length of data block transmitted at a time when the task is performed. In addition, the second protocol type transaction of the second chiplet may be an AXI3 transaction having a burst length of 16, which is a length of data block transmitted at a time when the task is performed.

(101) The first chiplet **1200** may exchange the conversion information (e.g., packet ID, payload type code, payload size, etc.) with the second chiplet **1250** in the initialization process, before transmitting the transaction **1212** to the second chiplet **1250**.

(102) The transaction **1212** may be transmitted to a protocol layer **1220** of the first chiplet through a bus system **1210** of the first chiplet **1200**. The protocol layer **1220** may include an encoder as a conversion device. The protocol layer **1220** may generate a payload **1232** of a die-to-die interface flit. For example, the protocol layer **1220** may map the information included in the transaction **1212** in the order of ID, Write Address Code, Write Address Size, and Write Address Data according to the conversion information to generate the payload **1232**.

(103) The payload **1232** may be transmitted to the adapter layer (not illustrated) of the first chiplet **1200**, and the adapter layer may combine a header and/or control bit (e.g., a trailer, etc.) required for a die-to-die connection with the payload **1232** to generate a flit **1242** and transmit the flit to a PHY layer **1240** of the first chiplet **1200**. The PHY layer **1240** of the first chiplet **1200** may transmit the flit **1242** to a PHY layer **1260** of the second chiplet **1250**.

(104) The PHY layer **1260** of the second chiplet **1250** may transmit the received flit **1242** to an adapter layer (not illustrated) of the second chiplet **1250**. The adapter layer of the second chiplet **1250** may extract the payload **1232** from the flit **1242**, and transmit the extracted payload to a protocol layer **1270** of the second chiplet **1250**.

(105) The protocol layer **1270** of the second chiplet **1250** may generate an AXI3 transaction **1282** based on the conversion information provided in the initialization process. The protocol layer of the second chiplet **1250** may include a decoder. For example, the protocol layer **1270** may generate the AXI3 transaction **1282** decoded according to AXI3, that is, the protocol of the second chiplet **1250**, based on the same conversion information. The transaction **1282** generated in this way may be transmitted to the IP block (not illustrated) of the second chiplet through a bus system **1290** of the second chiplet.

(106) In FIG. 12, it is described that the protocol layer **1220** of the first chiplet **1200** includes the encoder as a conversion device, and that the protocol layer **1270** of the second chiplet **1250** includes the decoder as a conversion device, but aspects are not limited thereto. That is, the protocol layer **1220** of the first chiplet **1200** may include a decoder as the conversion device, and the protocol layer **1270** of a second chiplet **1200** may include an encoder as the conversion device. In this case, the method of data transmission from the first chiplet **1200** to the second chiplet **1250** described in FIG. 12 may be applied in the same or similar manner to the method of data transmission from the second chiplet **1250** to the first chiplet **1200**.

(107) FIG. 13 is a flowchart provided to explain a method **1300** for communicating between chiplets in a chiplet system. The chiplet system may include a first chiplet and a second chiplet, in which the first chiplet may include a controller including a protocol layer. The method **1300** may be initiated by the protocol layer of the first chiplet by receiving first data, at **S1310**. By the protocol layer of the first chiplet, the conversion information may be received from the second chiplet, at **S1320**. By the protocol layer of the first chiplet, the conversion information may be received from the second chiplet, at **S1330**.

(108) The first chiplet may further include a bus system, and the protocol layer of the first chiplet may receive the first data through the bus system. In addition, the first data may include a first protocol type transaction associated with the first chiplet, and the conversion information may be encoding information associated with the second protocol. In addition, the second protocol may be associated with the second chiplet, and the second data may include the payload of the first die-to-die interface flit associated with the second protocol.

(109) The protocol layer may include a processor and a sub-memory, in which the processor may determine an encoding rule based on the encoding information associated with the second protocol and encode a first protocol type transaction according to the determined encoding rule to generate a payload of the first die-to-die interface flit, and the first protocol type transaction may be stored in the sub-memory.

(110) The first chiplet may further include an adapter layer, and the adapter layer may generate a header of the first die-to-die interface flit associated with the second protocol, and combine the header and the payload to generate the first die-to-die interface flit.

(111) If the second protocol associated with the second chiplet is a uni-directional protocol from the first chiplet to the second chiplet, the conversion information may include only the conversion information from the first chiplet to the second chiplet.

(112) The first chiplet may further include an adapter layer, and the adapter layer may receive the first data. In addition, the first data may include the payload of the second die-to-die interface flit associated with the second protocol, and the second protocol may be associated with the second chiplet. The conversion information may include the decoding information associated with the second protocol, and the second data may include the first protocol type transaction associated with the first chiplet.

(113) The protocol layer may include a processor, and the processor may determine a decoding rule based on the decoding information associated with the second protocol and decode the payload of the second die-to-die interface flit according to the determined decoding rule to generate a first protocol type transaction. In addition, the adapter layer may extract the payload from the second die-to-die interface flit.

(114) The conversion information may include the encoding or decoding information associated with the second protocol, and the second protocol may be associated with the second chiplet. In addition, the encoding or decoding information associated with the second protocol may include information on one or more bus channels of the second chiplet, and information indicating the region and size of bits allocated to each of the one or more bus channels. In addition, the conversion information may further include an indicator code that indicates an operable bus channel of one or more bus channels of the second chiplet.

(115) The flowchart and description described above are merely examples, and may be implemented differently in some examples. For example, in some examples, the order of respective operations may be changed, some of the operations may be repeatedly performed, some may be omitted, or some may be added.

(116) FIG. 14 is a flowchart provided to explain a method **1400** for communicating between chiplets in a chiplet system according to another aspect of the present disclosure. The chiplet system may include a first chiplet and a second chiplet, and the method **1400** may be initiated by the first chiplet by generating a die-to-die interface flit from a first protocol type transaction based on the conversion information, at **S1410**.

(117) The first chiplet may include a controller including a protocol layer and an adapter layer, in which the protocol layer of the first chiplet may generate a die-to-die interface flit from the first protocol type transaction based on the conversion information, and the adapter layer of the first chiplet may combine the header and the payload to generate a die-to-die interface flit.

(118) The first chiplet may further include a PHY layer, in which the adapter layer of the first chiplet may transmit the die-to-die interface flit to the PHY layer of the first chiplet, and transmit,

by the PHY layer of the first chiplet, the die-to-die interface flit to the second chiplet.

(119) By the first chiplet, the die-to-die interface flit may be transmitted to the second chiplet, at **S1420**. The second chiplet may include a PHY layer, and the first chiplet may transmit the die-to-die interface flit to the PHY layer of the second chiplet.

(120) By the second chiplet, the second protocol type transaction may be generated from die-to-die interface flit based on the conversion information, at **S1430**. The second chiplet may include a controller including an adapter layer and a protocol layer, in which the adapter layer of the second chiplet may extract a payload of a flit from the die-to-die interface flit, and the protocol layer of the second chiplet may generate a second protocol type transaction from the payload.

(121) The first chiplet and the second chiplet may exchange the conversion information. In addition, the conversion information may include information on a packet ID, a payload type code, a payload type size, and a payload size. The payload type code may include a write address code, a write data code, a write response code, a read address code, and a read data code.

(122) The first protocol may be related to the first chiplet, the second protocol may be related to the second chiplet, and the first protocol and the second protocol may be different from each other. In addition, the first and second chiplets may be designed based on the universal chiplet interconnect express (UCIe) standard, and the die-to-die interface flits may include UCIe flits.

(123) The flowchart and description described above are merely examples, and may be implemented differently in some examples. For example, in some examples, the order of respective operations may be changed, some of the operations may be repeatedly performed, some may be omitted, or some may be added.

(124) FIG. 15 is a diagram provided to explain a method for transmitting a first protocol type transaction of a first chiplet **1510** to a second chiplet **1550**, according to another aspect of the present disclosure. The first chiplet **1510** may utilize the first protocol type transaction, and in this case, the first protocol type may be AXI4. In addition, the second chiplet **1550** may utilize the second protocol type transaction, and in this case, the second protocol type may be AXI3. The first protocol type transaction may include a write address **1520** and write data **1530** having a burst length of 32, which is a length of data block transmitted at a time when the task is performed.

(125) The first chiplet **1510** may convert the first protocol type transaction into a die-to-die interface flit and transmit the converted transaction to the second chiplet **1550**. In this case, the first chiplet **1510** may modify the first protocol type transaction based on the encoding information (not illustrated) received from the second chiplet **1550**, and generate a payload **1540** of the die-to-die interface flit. The encoding information received from the second chiplet refers to information encoded in the first chiplet, and may include information used for decoding in the second chiplet,

(126) For example, the second protocol AXI3 of the second chiplet **1550** should have a write address of ARLEN [3:0] and a write data length of 16, which may be different from those supported by the first protocol AXI4 of the first chiplet **1510**. To address the issue mentioned above, when generating the transaction into the payload **1540**, the first chiplet **1510** may divide the transaction into two and generate the payload **1540**. In this case, the payload **1540** may include a portion corresponding to a first transaction including a 4-bit first write address WA1 and first write data having a length of 16, and a portion corresponding to a second transaction including a 4-bit second write address WA2 and second write data having a length of 16.

(127) The second chiplet **1550** may generate a second protocol type transaction from the payload **1540**. The process of generating the second protocol type transaction using the payload **1540** in the second chiplet **1550** may be referred to as a decoding process in the second chiplet **1550**. The payload **1540** includes data for two separate transactions, and the second chiplet **1550** may generate a plurality of second protocol type transactions **1560** and **1570**. For example, a first second protocol type transaction **1560** may include a first write address **1562** and first write data having a length of 16. Likewise, a second protocol type transaction **1570** may include a second write address **1572** and second write data **1574** having a length of 16.

(128) The method described above may be provided as a computer program stored in a computer-readable recording medium for execution on a computer. The medium may be a type of medium that continuously stores a program executable by a computer, or temporarily stores the program for execution or download. In addition, the medium may be a variety of recording means or storage means having a single piece of hardware or a combination of several pieces of hardware, and is not limited to a medium that is directly connected to any computer system, and accordingly, may be present on a network in a distributed manner. An example of the medium includes a medium configured to store program instructions, including a magnetic medium such as a hard disk, a floppy disk, and a magnetic tape, an optical medium such as a CD-ROM and a DVD, a magnetic-optical medium such as a floptical disk, and a ROM, a RAM, a flash memory, etc. In addition, other examples of the medium may include an app store that distributes applications, a site that supplies or distributes various software, and a recording medium or a storage medium managed by a server.

(129) The methods, operations, or techniques of the present disclosure may be implemented by various means. For example, these techniques may be implemented in hardware, firmware, software, or a combination thereof. Those skilled in the art will further appreciate that various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the disclosure herein may be implemented in electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such a function is implemented as hardware or software depends on design requirements imposed on the particular application and the overall system. Those skilled in the art may implement the described functions in varying ways for each particular application, but such implementation should not be interpreted as causing a departure from the scope of the present disclosure.

(130) In a hardware implementation, processing units used to perform the techniques may be implemented in one or more ASICs, DSPs, digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, microcontrollers, microprocessors, electronic devices, other electronic units designed to perform the functions described in the present disclosure, computer, or a combination thereof.

(131) Accordingly, various example logic blocks, modules, and circuits described in connection with the present disclosure may be implemented or performed with general purpose processors, DSPs, ASICs, FPGAs or other programmable logic devices, discrete gate or transistor logic, discrete hardware components, or any combination of those designed to perform the functions described herein. The general purpose processor may be a microprocessor, but in the alternative, the processor may be any related processor, controller, microcontroller, or state machine. The processor may also be implemented as a combination of computing devices, for example, a DSP and microprocessor, a plurality of microprocessors, one or more microprocessors associated with a DSP core, or any other combination of the configurations.

(132) In the implementation using firmware and/or software, the techniques may be implemented with instructions stored on a computer-readable medium, such as random access memory (RAM), read-only memory (ROM), non-volatile random access memory (NVRAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable PROM (EEPROM), flash memory, compact disc (CD), magnetic or marking data storage devices, etc. The commands may be executable by one or more processors, and may cause the processor(s) to perform certain aspects of the functions described in the present disclosure.

(133) If implemented in software, the techniques described above may be stored on a computer-readable medium as one or more instructions or codes, or may be sent via a computer-readable medium. The computer-readable media include both the computer storage media and the communication media including any medium that facilitates the transmission of a computer

program from one place to another. The storage media may also be any available media that may be accessible to a computer. By way of non-limiting example, such a computer-readable medium may include RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other media that can be used to transmit or store desired program code in the form of commands or data structures and can be accessible to a computer. In addition, any connection is properly referred to as a computer-readable medium.

(134) For example, if the software is sent from a website, server, or other remote sources using coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, wireless, and microwave, the coaxial cable, the fiber optic cable, the twisted pair, the digital subscriber line, or the wireless technologies such as infrared, wireless, and microwave are included within the definition of the medium. The disks and the discs used herein include CDs, laser disks, optical disks, digital versatile discs (DVDs), floppy disks, and Blu-ray disks, where disks usually magnetically reproduce data, while discs optically reproduce data using a laser. The combinations described above should also be included within the scope of the computer-readable media.

(135) The software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, removable disk, CD-ROM, or any other form of storage medium known. An exemplary storage medium may be connected to the processor such that the processor may read or write information from or to the storage medium. Alternatively, the storage medium may be integrated into the processor. The processor and the storage medium may be present in the ASIC. The ASIC may exist in the user terminal. Alternatively, the processor and storage medium may exist as separate components in the user terminal.

(136) Although the examples described above have been described as utilizing aspects of the currently disclosed subject matter in one or more standalone computer systems, aspects are not limited thereto, and may be implemented in conjunction with any computing environment, such as a network or distributed computing environment. Furthermore, the aspects of the subject matter in the present disclosure may be implemented in multiple processing chips or apparatus, and storage may be similarly influenced across a plurality of apparatus. Such apparatus may include PCs, network servers, and portable apparatus.

(137) Although the present disclosure has been described in connection with some aspects herein, various modifications and changes can be made without departing from the scope of the present disclosure, which can be understood by those skilled in the art to which the present disclosure pertains. Additionally, such modifications and changes should be considered to fall within the scope of the claims appended hereto.

Claims

1. A method for communicating between chiplets in a chiplet system, wherein the chiplet system includes a first chiplet and a second chiplet, the method comprising: by the first chiplet, generating a die-to-die interface flit from a first protocol type transaction based on conversion information; by the first chiplet, transmitting the die-to-die interface flit to the second chiplet; and by the second chiplet, generating a second protocol type transaction from the die-to-die interface flit based on the conversion information, wherein the conversion information includes information on a packet ID, a payload type code, a payload type size, and a payload size.

2. The method according to claim 1, wherein the first chiplet includes a controller including a protocol layer and an adapter layer, and the generating by the first chiplet the die-to-die interface flit from the first protocol type transaction based on the conversion information includes: by the protocol layer of the first chiplet, generating a payload of the die-to-die interface flit from the first protocol type transaction based on the conversion information; by the adapter layer of the first chiplet, generating a header of the die-to-die interface flit; and by the adapter layer of the first

chiplet, generating the die-to-die interface flit by combining the header and the payload.

3. The method according to claim 1, wherein the first chiplet further includes a physical (PHY) layer, and the transmitting by the first chiplet the die-to-die interface flit to the second chiplet includes: by the adapter layer of the first chiplet, transmitting the die-to-die interface flit to the PHY layer of the first chiplet; and by the PHY layer of the first chiplet, transmitting the die-to-die interface flit to the second chiplet.

4. The method according to claim 1, before generating the die-to-die interface flit, further comprising, by the first chiplet and the second chiplet, exchanging the conversion information.

5. The method according to claim 1, wherein the payload type code includes a write address code, a write data code, a write response code, a read address code, and a read data code.

6. The method according to claim 1, wherein the second chiplet includes a PHY layer, and the transmitting by the first chiplet the die-to-die interface flit to the second chiplet includes, by the first chiplet, transmitting the die-to-die interface flit to the PHY layer of the second chiplet.

7. The method according to claim 1, wherein the second chiplet includes a controller including an adapter layer and a protocol layer, and the generating by the second chiplet the second protocol type transaction from the die-to-die interface flit based on the conversion information includes: by the adapter layer of the second chiplet, extracting a payload of the die-to-die interface flit from the flit; and by the protocol layer of the second chiplet, generating the second protocol type transaction from the payload.

8. The method according to claim 1, wherein the first protocol relates to the first chiplet, the second protocol relates to the second chiplet, and the first protocol and the second protocol are different from each other.

9. The method according to claim 1, wherein the first chiplet and the second chiplet are designed based on universal chiplet interconnect express (UCIe) standard, and the die-to-die interface flit includes a UCIe flit.

10. A chiplet system, wherein the chiplet system includes a first chiplet and a second chiplet, the first chiplet is configured to generate a die-to-die interface flit from a first protocol type transaction based on conversion information, and transmit the die-to-die interface flit to the second chiplet, and the second chiplet is configured to generate a second protocol type transaction from the die-to-die interface flit based on the conversion information, wherein the conversion information includes information on a packet ID, a payload type code, a payload type size, and a payload size.

11. The chiplet system according to claim 10, wherein the first chiplet includes a controller including a protocol layer and an adapter layer, and the generating the die-to-die interface flit from the first protocol type transaction based on the conversion information includes: by the protocol layer of the first chiplet, generating a payload of the die-to-die interface flit from the first protocol type transaction based on the conversion information; by the adapter layer of the first chiplet, generating a header of the die-to-die interface flit; and by the adapter layer of the first chiplet, generating the die-to-die interface flit by combining the header and the payload.

12. The chiplet system according to claim 10, wherein the first chiplet further includes a PHY layer, and the transmitting the die-to-die interface flit to the second chiplet includes: by the adapter layer of the first chiplet, transmitting the die-to-die interface flit to the PHY layer of the first chiplet; and by the PHY layer of the first chiplet, transmitting the die-to-die interface flit to the second chiplet.

13. The chiplet system according to claim 10, wherein, before generating the die-to-die interface flit, the first chiplet and the second chiplet exchange the conversion information.

14. The chiplet system according to claim 10, wherein the payload type code includes a write address code, a write data code, a write response code, a read address code, and a read data code.

15. The chiplet system according to claim 10, wherein the second chiplet includes a PHY layer, and the transmitting the die-to-die interface flit to the second chiplet includes transmitting the die-to-die interface flit to the PHY layer of the second chiplet.

16. The chiplet system according to claim 10, wherein the second chiplet includes a controller

including an adapter layer and a protocol layer, and the generating the second protocol type transaction from the die-to-die interface flit based on the conversion information includes: by the adapter layer of the second chiplet, extracting a payload of the die-to-die interface flit from the flit; and by the protocol layer of the second chiplet, generating a second protocol type transaction from the payload.

17. The chiplet system according to claim 10, wherein the first protocol relates to the first chiplet, the second protocol relates to the second chiplet, and the first protocol and the second protocol are different from each other.

18. The chiplet system according to claim 10, wherein the first chiplet and the second chiplet are designed based on the universal chiplet interconnect express (UCIe) standard, and the die-to-die interface flit includes a UCIe flit.
