

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412486
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Vuong; Theresa D. et al.

Entertainment/educational system and associated apparatus, methods and uses

Abstract

The present specification discloses an entertainment/educational system having one or more interactive stations having associated systems comprising apparatus and activities that demonstrate various physical phenomenon. Each interactive station comprises a different system featuring differing apparatus that provides users the ability to form various types and numbers of bubbles that the users can experience and interact with. User progression and interaction with a particular set of/order of interactive stations is correlated with lessons about physical phenomena exemplified by the bubbles made at a particular station of the total stations visited. The lessons may be further enhanced by information provided to users via a poster, handout, booklet or other informative media or information provided by a guide/attendant escorting user(s) through the set of stations.

Inventors: Vuong; Theresa D. (Irvine, CA), Li; Jennifer K. (Anaheim, CA), Jung; Il Kwon (Seoul, KR)

Applicant: Vuong; Theresa D. (Irvine, CA); Li; Jennifer K. (Anaheim, CA); Jung; Il Kwon (Seoul, KR)

Family ID: 90623979

Appl. No.: 18/593766

Filed: March 01, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240221536 A1	Jul. 04, 2024

Related U.S. Application Data

continuation parent-doc US 17164730 20210201 US 11961414 child-doc US 18593766
continuation parent-doc US 16779238 20200131 US 10909883 20210202 child-doc US 17164730

us-provisional-application US 62885172 20190809
us-provisional-application US 62799555 20190131
us-provisional-application US 62799523 20190131
us-provisional-application US 62799544 20190131

Publication Classification

Int. Cl.: **G09B23/12** (20060101); **A63H33/28** (20060101)

U.S. Cl.:

CPC **G09B23/12** (20130101); **A63H33/28** (20130101);

Field of Classification Search

CPC: G09B (23/12); A63H (33/28); A63J (5/025)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1167619	12/1915	Beeler	40/408	A63H 33/28
2412732	12/1945	Holman	N/A	N/A
2452794	12/1947	Saachy	446/16	A63H 33/28
3432439	12/1968	Dickman	N/A	N/A
3903659	12/1974	Echtler	N/A	N/A
4044496	12/1976	Jernstrom	446/16	A63H 33/28
4103369	12/1977	Riordan	52/2.14	E04H 15/22
4164829	12/1978	Sadler	135/117	E04H 3/08
4303397	12/1980	Swiatosz	N/A	N/A
4775348	12/1987	Collins	446/16	A63H 33/28
4871115	12/1988	Hessey	N/A	N/A
5156333	12/1991	Worsfold	N/A	N/A
5297979	12/1993	Amron	239/289	A63H 33/28
5603185	12/1996	Murphy	N/A	N/A
5610359	12/1996	Spector	N/A	N/A
5711481	12/1997	MacDonald et al.	N/A	N/A
5957382	12/1998	Thomas	N/A	N/A
6062935	12/1999	Gross	446/15	A63H 33/28
6189453	12/2000	Lin	N/A	N/A
6361024	12/2001	Carson	N/A	N/A
6400897	12/2001	Lin	N/A	N/A
6508064	12/2002	Tomita	N/A	N/A
6817951	12/2003	Levine	N/A	N/A
6875119	12/2004	Murphy et al.	N/A	N/A
7089703	12/2005	Brereton	N/A	N/A
10279279	12/2018	Baranoff	N/A	A63H 33/005
10363492	12/2018	Thai	N/A	A63H 33/28
10500520	12/2018	Pogue	N/A	A63J 5/025

10619375	12/2019	Hanley	N/A	N/A
10905968	12/2020	Huey	N/A	A63H 33/28
11173415	12/2020	Yang	N/A	A63H 33/28
11944994	12/2023	Myers	N/A	A23F 3/00
2002/0115372	12/2001	Thai	446/16	A63H 33/28
2004/0127137	12/2003	Thai	446/16	A63H 33/28
2005/0184168	12/2004	Peng	N/A	N/A
2006/0116048	12/2005	Choi	N/A	N/A
2007/0012063	12/2006	Schock	N/A	N/A
2009/0017713	12/2008	Chung	N/A	N/A
2009/0149111	12/2008	Scherba	N/A	N/A
2010/0173558	12/2009	Huey	446/15	A63H 33/28
2015/0133021	12/2014	Huey	446/15	A63H 33/28
2016/0044960	12/2015	O'Connor	N/A	N/A
2018/0221785	12/2017	Tomazetich	N/A	N/A
2018/0345164	12/2017	Venigalla	N/A	N/A
2020/0061487	12/2019	Thai	N/A	A63H 33/28
2020/0155957	12/2019	Clayton	N/A	A63H 29/22
2020/0251016	12/2019	Vuong	N/A	A63H 33/28

OTHER PUBLICATIONS

U.S. Appl. No. 16/779,238, Publication No. US 2020/0251016, U.S. Pat. No. 10,909,883, filed Jan. 31, 2020. cited by applicant

U.S. Appl. No. 17/164,730, Publication No. US 2022/0246061, U.S. Pat. No. 11,961,414 filed Feb. 1, 2022. cited by applicant

U.S. Appl. No. 16/779,238, Publication No. US 2020/0251016, filed Jan. 31, 2020. cited by applicant

U.S. Appl. No. 17/164,730, Publication No. US 2022/0246061, filed Feb. 1, 2022. cited by applicant

Primary Examiner: Fernstrom; Kurt

Attorney, Agent or Firm: UltimatEdge IP Law Group, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This continuation claims the benefit of priority and the filing date pursuant to 35 U.S.C. § 120 to U.S. Non-Provisional application Ser. No. 17/164,730, filed Feb. 1, 2021, an application that claims the benefit of priority and the filing date pursuant to 35 U.S.C. § 120 to U.S. Non-Provisional application Ser. No. 16/779,238, filed Jan. 31, 2020, now U.S. Pat. No. 10,909,883, an application that claims the benefit of priority and the filing date pursuant to 35 U.S.C. § 119(e) to U.S. Provisional Application 62/885,172, filed Aug. 9, 2019, U.S. Provisional Application No. 62/799,523, filed Jan. 31, 2019, U.S. Provisional Application No. 62/799,544, filed January 31, and U.S. Provisional Application No. 62/799,555, filed Jan. 31, 2019, the content of each of which is herein incorporated by reference in its entirety.

FIELD

(1) The present disclosure relates in general to an entertainment/educational facility, and is more specifically directed to associated stations, systems, apparatus and methods of use that incorporate

use of bubbles for entertainment and educational purposes. More particularly and in accordance with aspects of the present disclosure, an entertainment/educational facility is provided that features multiple bubble-making stations at which a user or users are able to engage in various interactive activities utilizing bubbles.

BACKGROUND

(2) For many years, bubble play has been used as an entertainment activity for children. Specifically, bottles of bubble solution (in its simplest form, detergent and water), along with a tool for helping form bubbles, have been sold at toy stores and other retail shops for decades. Users create bubbles by immersing the tool, typically referred to as a wand or hoop, in a bubble solution and then blowing air through the wand or hoop. This air is typically supplied from their lungs onto a designated bubble-making portion of the tool which serves to form a thin sheet of the bubble solution to create one or more bubbles. These bubbles can be chased or observed by the children participating in the play. More recently, larger tools have been available, such as battery powered bubble-guns and large wands for making various sizes and numbers of bubbles, sometimes simultaneously. These tools are generally hand-held. Such tools typically create large bubbles by moving the tool so that the tool will capture air and create the bubble or bubbles.

(3) Thus, these typical play experiences limit a user to the bubbles provided by just one type of tool. It would be advantageous to a user or multiple users to visit and utilize an entertainment/educational facility and engage with various systems at a plurality of bubble-making stations where each station has an associated apparatus for making a particular type of bubble, plurality of bubbles or a substantially planar bubble solution sheet/film or a wall. Further, such a facility can provide users with additional educational and behavioral development aspects, in addition to the entertainment value associated with bubble play.

SUMMARY

(4) The present specification discloses an entertainment/educational facility comprising one or more stations. Each of the one or more stations comprising a system, the system comprising an apparatus, methods of using and/or interacting with the apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The system present in each of the one or more stations is different than the system present in any of the other of the one or more stations. The apparatus included in each system present in the one or more stations typically form a particular type of bubble element made of bubble solution, such as a bubble and/or a plurality of bubbles and/or a substantially planar bubble sheet/film or a bubble tube (substantially planar or not) that is associated with a particular bubble-making station. Activities provided by and at the various bubble-making stations, enable the user or users to enjoy, observe, make and learn about bubbles and other structures made with bubble solution and the associated underlying scientific concepts by participating in various bubble(s) and bubble sheet/film or wall making activities. Station-specific media can be in the form of live instruction and/or demonstration or in the form of a poster or posters, a handout, a monitor (such as an interactive monitor/touch-screen monitor) and a water-proof monitor or tablet (interactive or not), for example.

(5) In aspects of the present disclosure, the one or more stations may comprise a first system comprising a bubble making apparatus and educational information regarding the scientific principles of bubbles. In aspects, the bubble making apparatus may comprise a support structure and a pumping system. In aspects, the support structure includes one or more sides, a bottom, a top opening, one or more basins, a trough and a reservoir. Each of the one or more basins may have one or more sides, a bottom and a port, the port being positioned at the bottom of each of the one or more basins. Each of the one or more basins is configured to contain a bubble solution. The trough can comprise a trough bottom biased toward the reservoir in a manner that directs the bubble solution falling onto the trough bottom is directed toward the reservoir, and the reservoir is configured to contain a bubble solution. In aspects, the pumping system including one or more

pumps and one or more conduits, the one or more conduits connecting at least one pump to the port of each of the one or more basins. In operation the at least one pump continuously transports the bubble solution contained in the reservoir through the one or more conduits to the port of each of the one or more basins, thereby filling each of the one or more basins with the bubble solution.

(6) In aspects of the present disclosure, the one or more stations may comprise a second system comprising a gas producing apparatus and educational information regarding the scientific principles of bubbles. In aspects, the gas producing apparatus may comprise a base and a smoke-like fog generating apparatus. In aspects, the base comprises one or more sides, a bottom and a top surface, the top surface having one or more basins. Each of the one or more basins may comprise one or more sides and a bottom and be configured to contain a bubble solution. In aspects, the smoke-like fog generating apparatus comprises a body, a heating element and a lid. The body may include one or more sides, a bottom, a top opening opposite the bottom, with the resulting interior space defining an internal reservoir. The heating element may abut the bottom or the one or more sides of the body. The lid may include one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end. The first end of each of the one or more hoses is attached to each of the one or more ports. In use, when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses. In addition, each of the one or more basins may be configured to receive the second end of each of the one or more hoses. In operation dry ice and water placed inside internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses.

(7) In aspects of the present disclosure, the one or more stations may comprise a third system comprising a mobile gas producing apparatus and educational information regarding the scientific principles of bubbles. In aspects, the mobile gas producing apparatus may comprise a carrier and a mobile smoke-like fog generating apparatus. In aspects, the mobile smoke-like fog generating apparatus may comprise a body, a heating element, and a lid. The body may include one or more sides, a bottom, a top opening opposite the bottom, with the resulting interior space defining an internal reservoir. The heating element may abut the bottom or the one or more sides of the body. The lid may include one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end. The first end of each of the one or more hoses is attached to each of the one or more ports. In use, when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses. In addition, each of the one or more basins may be configured to receive the second end of each of the one or more hoses. In operation dry ice and water placed inside the internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses.

(8) In aspects of the present disclosure, the one or more stations may comprise a fourth system comprising an inflatable apparatus and educational information regarding the scientific principles of bubbles. In aspects, the inflatable apparatus may comprise a first inflated chamber, a second inflated chamber, and an inflation system. The first inflated chamber has a contiguous portion with the second inflated chamber, and typically an opening is present in the contiguous portion to create a pathway between the first inflated chamber and the second inflated chamber. In aspects, the first inflated chamber may be substantially spherical and curved in shape with a flat bottom. In aspects, the second inflated chamber being substantially cuboidal in shape. The second inflated chamber typically comprises an entrance enabling a user to access the second inflated chamber from outside the apparatus. The inflation system may comprise an inflation device and one or more air conduits, with the one or more air conduits connecting the inflation device to at least the first inflated chamber. In operation the inflation device expels air through the one or more conduits and into at

least the first inflated chamber, thereby inflating the first inflated chamber.

(9) In aspects of the present disclosure, the one or more stations may comprise a fifth system comprising a bubble sheet making apparatus and educational information regarding the scientific principles of bubbles. In aspects, the bubble sheet making apparatus may comprise a frame system, a lift system and a bar system. In aspects, the frame system can comprise a bottom trough, one or more vertical support members and a top support structure. The bottom trough can include one or more sides, a bottom and a top opening opposite the bottom, with the resulting interior space defining a reservoir. The bottom trough is configured to contain a bubble solution in the reservoir. The one or more vertical support members span the space between the bottom trough and the top support structure. In aspects, the lift system can include one or more pulleys and one or more lifting cords, each comprising a first end and a second end. The one or more pulleys are secured to the top support structure of the frame system. In aspects, the bar system comprising a top bar, one or more depending cords, and a bottom bar. The top bar comprises a first end, a second end and an absorbent material. Each of the one or more depending cords comprising at least a free end and composited of a collapsible material. The one or more depending cords is secured to the top bar and the at least a free end of the one or more depending cords is secured to the bottom bar. In aspects, the first end of each of the one or more lifting cords of the lift system is secured to the top bar, the one or more lifting cords then passed through the one or more pulleys, thereby having the second end of each of the one or more lifting cords on the side of the one or more pulleys opposite the side of the first end of each of the one or more lifting cords. In operation, the bar system submerged in the bubble solution contained in the bottom trough is lifted vertically upward out of the bottom trough using the lift system, thereby forming a bubble sheet using the bubble solution contained within a framework created by the top bar, one or more depending cords and the bottom bar.

(10) In aspects of the present disclosure, the one or more stations may comprise a sixth system comprising a bubble making apparatus, an activity area, and educational information regarding the scientific principles of bubbles. In aspects, the bubble making apparatus can comprise a support structure one or more bubble producing systems. In aspects, the support structure can include one or more sides, a bottom and a top, and can comprise a power system and a ventilation system. The power system can include a power supply to generate electricity and one or more electrical wires. In aspects, each of the one or more bubble producing systems can comprise a motorized bubble producing tool system and an air stream producing system. In aspects, the motorized bubble producing tool system can include a reservoir, one or more bubble producing tools attached to a central hub and a motor, with the central hub is operably linked to the motor, and the reservoir being configured to contain a bubble solution. In aspects, the air stream producing system comprising a motorized blower and a vent. The one or more electrical wires connect the power supply to the motor of the motorized bubble producing tool system and the motorized blower the air stream producing system. In operation the motorized blower continuously expels air in a generally horizontal direction through vent and outward from the front of the bubble making apparatus and the motor of the motorized bubble producing tool system continuously spins the central hub causing each of the one or more bubble producing tools to undergo a rotational cycle through the bubble solution contained in the reservoir and past air stream being expelled through the vent, thereby causing formation of a stream of bubbles. In aspects, the activity area can comprise at least one receptacle including projectiles.

(11) In aspects of the present disclosure, the one or more stations may comprise a seventh system comprising a bubble tower making apparatus and educational information regarding the scientific principles of bubbles. In aspects, the bubble tower making apparatus can comprise a base, a support frame system, and a lift system. In aspects, the base system can include a platform, a fluid trough and a base surround. Typically, the base surround is located along the outside perimeter of the fluid trough and the fluid trough is located along the outside perimeter of the platform. The fluid trough configured to contain a bubble solution. In aspects, the support frame system can include one or

more vertical support members and a top frame, with the one or more vertical support members span the space between the base system and the top frame. In aspects, the lift system can include one or more lifting pulleys, one or more control pulleys, one or more cables, and a bubble forming device, with each of the one or more cables comprising a first end and a second end. The one or more lifting pulleys and one or more control pulleys are secured to the top frame of the support frame system. The bubble forming device conforms to the shape of the fluid trough and the one or more cables are each secured to the bubble forming device. In aspects, the first end of each of the one or more cables of the lift system is secured to the bubble forming device, the one or more cables then passed through the one or more lifting pulleys and one or more controlling pulleys, thereby having the second end of each of the one or more cables on the side of the one or more lifting pulleys and one or more controlling pulleys opposite the side of the first end of each of the one or more cables. In operation, the bubble forming device submerged in the bubble solution contained in the fluid trough is lifted vertically upward out of the fluid trough using the lift system, thereby forming a bubble tower using the bubble solution contained between the bubble forming device and the bubble solution contained in the fluid trough.

(12) In aspects of the present disclosure, the one or more stations may comprise an eighth system comprising a bubble light apparatus and educational information regarding the scientific principles of bubbles. In aspects, the bubble light apparatus can comprise a support structure and a lighting system. In aspects, the support structure can include one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins including one or more sides and a bottom and configured to contain a bubble solution. In aspects, the bottom being partially or fully transparent and/or partially or fully translucent, thereby enabling light to transmit therethrough. In aspects, the lighting system including one or more light sources, at least one power supply to generate electricity, and one or more electrical wires. The one or more electrical wires connect the at least one power supply to each of the one or more light sources. In aspects, the one or more light sources are located underneath the bottom of each of one or more basins. In operation, one or more users create one or more bubbles using the bubble solution contained in the one or more basins and light being emitted from the one or more light sources shine through the one or more bubbles.

(13) In aspects of the present disclosure, the one or more stations may comprise a ninth system comprising a bubble jet apparatus and educational information regarding the scientific principles of bubbles. In aspects, the bubble jet apparatus can comprise a support structure and an air stream system. In aspects, the support structure can include one or more sides, a bottom and a top surface, the top surface having one or more basins and one or more vents, the one or more basins including one or more sides and a bottom and configured to contain a bubble solution. In aspects, the air stream system can include at least one motorized blower, one or more ducts, at least one power supply to generate electricity, and one or more electrical wires, with the one or more electrical wires connect the at least one power supply to the at least one motorized blower. The bubble jet apparatus further comprises one or more bubble making tools. In operation, one or more bubbles are formed when a user positions a bubble making tool containing the bubble solution over one of the one or more vents, thereby causing air being expelled through the one of the one or more vents to pass through the bubble making tool thereby creating the one or more bubbles from the bubble solution contained in the bubble making tool.

(14) In aspects of the present disclosure, the one or more stations may comprise a tenth system comprising a bubble pedestal apparatus and educational information regarding the scientific principles of bubbles. In aspects, the bubble pedestal apparatus can comprise a support structure and one or more casters. In aspects, the support structure can include one or more sides and a top surface, the top surface having one or more lips positioned around the perimeter of the top surface thereby defining a basin, the basin being configured to contain a bubble solution. The bubble pedestal apparatus further comprises one or more bubble making tools.

(15) The present specification also discloses systems comprising an apparatus, methods of using

and/or interacting with the apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The disclosed systems can operate inside an entertainment/educational facility as disclosed herein, or separately. When operating as a separate system, the disclosed systems can be mobile systems that are transported to a location, such as, e.g., a park, a government sponsored fair, a privately sponsored fair or event, a commercial setting, or any other location desiring employment of the systems disclosed herein. In aspects, the system disclosed herein include the first through tenth systems described herein. (16) The present specification also discloses apparatus and associated methods of using and/or interacting with the apparatus. In aspects, the apparatus disclosed herein include the first through tenth apparatus described herein.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The above and further advantages of this disclosure may be better understood by referring to the following description in conjunction with the accompanying drawings, in which like numerals indicate like structural elements and features in various figures. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles herein described and provided by exemplary embodiments and aspects of the invention.

(2) FIGS. **1A-1E** illustrate an exemplary system **100** comprising bubble-making apparatus **11** disclosed herein utilizing bubble solution with FIG. **1A** showing a front perspective view of the apparatus in use by a plurality of users; FIG. **1B** showing a front perspective view of the apparatus; FIG. **1C** showing a top view of the apparatus; FIG. **1D** showing a cross-sectional view of the apparatus; and FIG. **1E** showing a side perspective view of the apparatus;

(3) FIGS. **2A-2C** illustrate an exemplary smoke-like fog generating system **200** comprising gas producing apparatus **210** disclosed herein providing bubbles filled with smoke-like fog with FIG. **2A** showing a front perspective view of the gas producing apparatus being loaded with dry ice; FIG. **2B** showing a front perspective view of the apparatus in use by a plurality of users; and FIG. **2C** showing a cross-sectional view of the gas producing apparatus;

(4) FIGS. **3A-3B** illustrate an exemplary system **300** comprising an inflatable apparatus **310** for photo opportunities with FIG. **3A** showing a front perspective view of the apparatus in use by a user; and FIG. **3B** showing a side view of the apparatus;

(5) FIG. **4** illustrates a front perspective view an exemplary system **400** comprising bubble sheet making apparatus **410** disclosed herein to provide a bubble sheet;

(6) FIGS. **5A-5D** illustrate an exemplary system **500** comprising bubble-making apparatus **510** disclosed herein to provide a stream of bubbles with FIG. **5A** showing a front perspective view of an exemplary bubble-making station in use by a user; FIG. **5B** showing a front view of the apparatus; FIG. **5C** showing a side view of the apparatus; and FIG. **5D** showing a cross-sectional view of the apparatus;

(7) FIGS. **6A-6H** illustrate an exemplary system **600** comprising bubble tower making apparatus **610** disclosed herein to provide a large bubble wall designed to encase an individual with FIG. **6A** showing a front perspective view of the apparatus and system in use by a user; FIG. **6B** showing a side perspective view of a top portion having an exemplary pulley system of the apparatus; FIG. **6C** showing a top view of a second exemplary embodiment of a base of FIG. **6A**; FIG. **6D** showing a side view of a second exemplary embodiment of a base of FIG. **6A**; FIG. **6E** showing a top view of a third embodiment of a base of FIG. **6A**, FIG. **6F** showing a cross-sectional view of the base of FIG. **6E**; FIG. **6G** showing a top view of a fourth exemplary embodiment of the base of FIG. **6A**; and FIG. **6H** showing a side view of a fourth exemplary embodiment of the base of FIG. **6A**;

(8) FIGS. **7A-7C** illustrate an exemplary system **700** comprising bubble light apparatus **710**

disclosed herein at a bubble-making station incorporating lights with FIG. 7A showing a front perspective view of the apparatus in use by a plurality of users; FIG. 7B showing a top view of the apparatus; and FIG. 7C showing a cross-sectional view of the apparatus;

(9) FIGS. 8A-8D illustrate an exemplary system **800** comprising bubble jet apparatus **810** disclosed herein utilizing streams of forced air to create bubbles with FIG. 8A showing a front perspective view of the bubble jet apparatus in use by a user; FIG. 8B showing a top view of the apparatus; FIG. 8C showing a cross-sectional view of a first embodiment of the bubble jet apparatus of FIG. 8A; and FIG. 8D showing a cross-sectional view of a second embodiment of the bubble jet apparatus of FIG. 8A;

(10) FIGS. 9A-9B illustrate an exemplary system **900** comprising bubble pedestal apparatus **910** as disclosed herein providing at least one pedestal having an enclosed and depressed top surface that serves as a reservoir for bubble solution with FIG. 9A a front perspective view of a bubble pedestal apparatus having a substantially square geometry; and FIG. 9B showing a front perspective view of a plurality of bubble pedestal apparatus having differing geometries from one another; and

(11) FIGS. 10A-10B illustrate an exemplary system **1000** comprising mobile gas producing apparatus **1010** for creating bubbles filled with smoke-like fog as disclosed herein with FIG. 10A showing a user wearing a mobile gas producing apparatus for creating bubbles filled with smoke-like fog, the user utilizing a bubble sheet provided by the exemplary bubble making apparatus illustrated in FIG. 4A; and FIG. 10B showing a cross-sectional view of the mobile gas producing apparatus.

DETAILED DESCRIPTION

(12) The present specification discloses an entertainment/educational facility comprising a plurality of bubble-making stations disclosed herein. Each of the plurality of bubble-making stations has an associated system including methods for interacting with a bubble element and an apparatus for making a particular type of bubble element, such as, e.g., single bubbles, a plurality of bubbles, a substantially planar bubble sheet/film or wall, and/or bubbles filled with a substance differing from the surrounding ambient air. The facility, its stations and associated systems and apparatus provided in accordance with the teachings of the present disclosure serves as a way for users to have an interactive, entertaining and enjoyable learning experience based upon particular type of bubble elements, bubble-making.

(13) Besides the entertainment value associated with bubble play, each station can provide a user or users with educational and/or behavioral development features associated with the particular bubble element produced by the apparatus at that station. In accordance with the teachings of the present disclosure, an entertainment facility having multiple unique bubble-making stations can provide an environment where users can be brought and participate in a curriculum that is outlined and tailored to individual users or sets of users. For example, a science, technology, engineering and mathematics (STEM) Curriculum, where bubble-making stations and lessons are tailored to include and cover age-appropriate material, can be provided. Such a curriculum can include a booklet or handout that describes the use of each particular set of selected bubble-making stations, along with appropriate reading materials containing particular bubble-making station specific suggested activities and questions to be explored, according to the age of the particular users. An exemplary curriculum is described below.

(14) While each station has an independent system comprising at least one apparatus for making a particular type of bubble element and associated uses and methods of entertainment, education and behavioral development, in combination, a plurality of such stations form a greater system and an entertainment/educational facility providing entertainment, educational and behavioral development value.

(15) The following is a description of an entertainment/educational facility and its various exemplary bubble-making stations, systems and associated apparatus for making a bubble element and methods of using the apparatus or interacting with the bubble element. Associated scientific or

other educational principles as basin as skills that improve or advance behavioral development can be undertaken and discussed at various bubble-making stations. It is to be understood that two or more bubble-making stations, systems and apparatus serve as and function as an entertainment/educational facility. It is to be also understood that any number of bubble-making stations (e.g., stations that utilized bubble solution) may be provided and visited, and such engagement can be in any desired order. In particular embodiments, the entertainment/educational facility has a least one bubble-making station that utilizes carbon dioxide that is sublimated off of dry ice in order to provide for and create a bubble or bubbles filled with smoke-like fog, in addition to having at least one or more bubble-making station that does not utilize dry ice in water to provide a bubble or bubbles filled with smoke-like fog, but rather provides bubbles and/or a substantially planar bubble solution sheet/film or a wall that are clear and transparent.

(16) The detailed description set forth below in connection with the appended drawings is intended as a description of the concepts and teachings of the instant disclosure and is not meant to be limiting. Thus the disclosed invention is not limited to only the exemplary teachings and/or configurations of the bubble-making stations, systems, apparatus, and methods of use disclosed herein. It is further understood that the use of relational terms such as first, second, distal, proximal, and the like are used solely to distinguish one from another entity without necessarily requiring or implying any actual such relationship or order between such entities.

(17) A first exemplary bubble-making station includes a system **100** that comprises an bubble making apparatus, methods of using and/or interacting with the bubble making apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The bubble making apparatus comprises one or more basins with a bubble solution therein and a pumping system (which may or may not include a filter) that continuously supplies basin(s) with running bubble solution. One or more bubble producing tools, such as bubble wands, which may have multiple shapes with one or more hoops may be provided.

(18) Referring to FIGS. **1A-1E**, an exemplary bubble making apparatus **11** comprises a support structure **12** and a pumping system **40**. As shown in FIGS. **1A-1C**, support structure **12** of bubble making apparatus **11** generally comprises one or more sides **15**, a bottom **17**, and a top opening **19** opposite bottom **17**, the resulting top opening **19**, top opening **19** being defined by the perimeter formed by one or more sides **15**. As discussed below, support structure **12** is used to stably support one or more basins **20** for proper use by a user. Support structure **12** may be curved, defining a circle or an oval, or any cuboidal shape with square and rectangular shapes being preferred, the cuboidal shape having sharp (right-angled) or curved corners. In some embodiments, support structure **12** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, support structure **12** is generally cuboidal in shape. In some embodiments, support structure **12** is cuboidal and can have a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. The height of support structure **12** can be 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet.

(19) In addition, a perimeter formed by one or more sides **15** and top opening **19** may be curved, defining a circle or an oval, or any closed polygonal shape with triangle, square, rectangular, and pentagonal shapes. In some embodiments, the perimeter formed by one or more sides **15** and top opening **19** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, the perimeter formed by one or more sides **15** and top opening **19** is generally polygonal in shape. In some embodiments, the perimeter formed by one or more sides **15** and top opening **19** is polygonal in shape and each length of the polygon can be 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, 1 to 2 feet, 4 to 15 feet, 4 to 12 feet, 4 to 10

feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet.

(20) As best shown in FIG. 1D, a first internal space of support structure **12** is located below the plain of top opening **19** and defines a trough **13**. The shape of trough **13** is defined by the internal surface of each of the one or more sides **15** of support structure **12** and a trough bottom **23**. Still referring to FIG. 1D, a second internal space of support structure **12** defines a reservoir **30**. Reservoir **30** is typically located on one end of trough **13**.

(21) As best shown in FIG. 1D, one or more basins **20** comprise one or more sides **6** and a bottom **8** and a top edge of each of the one or more sides **6** may be rounded off or be provided having a substantially right angle. In particular configurations, support structure **12** can comprise at least one basin, for example, one or more basins, 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. Each of the one or more basins **20** can serve as a container for bubble solution **4**. Each of the one or more basins **20** are filled to a sufficient depth that may be manually delivered into basins **20**. Each of the one or more basins **20** can be of any suitable geometry, perimeter, and/or shape and any depth that provides for a sufficient area and volume to hold bubble solution **4**. In a preferred embodiment, each of the one or more basins are circular and have a flat bottom **8** and a surrounding side **6** that rises from, for example, about 0.25 inches to 0.5 inches, about 1 inch to 5 inches, about 2 to 4 inches to about 3 inches from the bottom of the basins. Each of the one or more basins **20** can have a depth of bubble solution **4** of, for example, about 0.25 inches to 0.5 inches, about 0.25 inches to about 0.75 inches, about 0.5 inch to about 1 inch, about 1 inch to about 2 inches or about 0.5 inch to about 3 inches contained therein. As shown in FIG. 1B, each basin **20** includes a port **22**, where fresh bubble solution is provided from reservoir **30** using a pump **40** and one or more conduits **42** that lead up to or through port **22**. Each of the one or more basins **20** may be made of any material which may retain a bubble solution, with materials that withstand corrosion from a bubble solution being preferred, such as, e.g., plastic, fiberglass, treated wood, glass, metal or any suitable material that can hold a bubble solution.

(22) Referring to the top view provided by FIG. 1C, one or more basins **20** may be located over top opening **19** overlooking or within trough **13** being positioned on support arms. Support arms provide for positioning of the one or more basins **20** such that overflow of bubble solution **4** contained therein falls to trough bottom **23**. In one embodiment, support arms span the open trough portion. As an example and as best seen in FIGS. 1C & 1D, each basin **20** is positioned at the open portion trough **13** using a support arm **14** (running parallel with the long side of the rectangular (cuboid) bubble making apparatus **11**) and a pair of cross support arms **16** located at either end of support arm **14**, the pair of cross support arms **16** being attached to the long side of trough **13**. In an alternative embodiment, one or more basins **20** may be supported by posts, or posts and crossbeams, the posts arising from the bottom of trough **13**. In addition to supporting the one or more basins **20**, support arms disclosed herein also provide a surface to which conduits/tubing from one or more pumps can run along or in and be secured thereto on their way to each basin. Conduits may be secured to the posts and/or support arms utilizing zip ties, hook and loop fasteners, adhesives, waterproof tape and any other suitable means.

(23) Referring to FIG. 1D, trough bottom **23** is slanted/titled such that bubble solution **4** spilling or falling onto trough bottom **23** from one or more basins **20** is biased and feeds or directs bubble solution **4** toward reservoir **30** (there can be more than one reservoir provided). There may be provided a raised lip portion spanning perpendicular to support arm **14** on bottom portion **23** of trough **13** and having a height of about 0.5 inch to 1 inch. Conduits **42** can be flexible tubing made out of plastic, silicone or vinyl or can be relatively inflexible tubing made out of, for example, PVC or a metal.

(24) As best shown in FIGS. 1C & 1D, bubble making apparatus **11** further comprises pumping system **40**. Pumping system **40** comprises one or more pumps **41** and one or more conduits **42**,

typically located at or in reservoir **30**. A pump **41** disclosed herein recirculates bubble solution **4** from reservoir **30** to the one or more basins **20** of bubble making apparatus **11** via one or more conduits **42**. An exemplary pump **41** can be a submersible pump. Referring to FIGS. **1C** & **1D**, one or more conduits **42** are connected to pump **41** and provide a pathway by which bubble solution **4** located at reservoir **30** is then delivered into each basin **20**. In one embodiment, the end of each conduit **42** is attached to port **22** at the bottom of each basin **20**. Conduit **42** runs from pump **41** in reservoir **30** to each basin **20**. It is further contemplated that one or more conduits **42** may provide bubble solution **4** to one or more basins **20** by simply being positioned over a lip **6** of each basin **20** or into and through a side of lip **6** of basin **20**, or any combination thereof. It is further contemplated that in alternative embodiments, pump **40** may be positioned outside reservoir **30** and is provided with intake conduit in bubble solution **4** and outtake tubing eventually leading to basins **20**, as long as a circulating flow of bubble solution **4** is maintained at a relatively fixed volume throughout the system, i.e. between reservoir **30** and one or more basins **20**. It is contemplated that in alternative embodiments each basin can be provided with its own pump or, as in a preferred embodiment, the pump may have attached a main tube/conduit from which additional sections of tubing/conduit branch and run to each individual basin **20**.

(25) FIG. **1E** shows an alternative embodiment of bubble making apparatus **11**, having a plurality of basins **20** but no pump **41** or reservoir **30**. In this embodiment, bubble making apparatus **11** is supplied with bubble solution **4** by simply filling each basin **20** with bubble solution **4** via manual pouring of bubble solution **4** into each basin. Such pouring can be accomplished by any number of traditional methods, such as pouring bubble solution **4** from a pitcher, bottle, bag or ladling bubble solution **4** from a vessel to reach a desired depth/amount of bubble solution **4** in each basin **20**. Accordingly, and since there is no pump **41** or reservoir **30** in this system, bottom portion **23** here can be substantially horizontal as there is no need to feed spilled bubble solution **4** to a reservoir **30** of bubble making apparatus **11**. Also shown in FIG. **1E** are exemplary bubble producing tools **8** that can vary and include wands, hoops, other instruments capable of generating bubbles from a bubble solution **4**. Such exemplary bubble producing tools **8** can have a handle and a single hoop disposed within a frame or a handle and a plurality of hoops disposed within a frame.

(26) In operation, a user manipulates bubble solution **4** contained in one or more basins **20** with a bubble producing tool **8**. When using larger bubble produce tool **8**, a user is able to create large bubbles to catch with the tool and then may be able to proceed to blow bubbles within bubbles. A bubble producing tool **8** can be further used to manipulate bubbles into various tricks and challenges. In addition, a user can also wet their hands with bubble solution **4** from a basin and catch the bubbles in the user's palms without having the bubbles pop. Further, a user can also wet the user's hands with bubble solution **4** in a basin and use the hands themselves as a "bubble producing tool" where the user blow bubbles from "frames" created by the user's fingers by passing air from the user's lungs therethrough.

(27) This first exemplary bubble-making station includes a system **100** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(28) For example, an attendant/guide can themselves make or lead a user(s) in making bubbles that stretches out really long. In the course of this process, some of these stretched out bubbles will pop while others will not and become a spherical bubble. an attendant/guide can then ask the users if they notice that the bubble(s) eventually becomes round even if it started out really long? Ask them

“why do they think that happens?”. The attendant/guide can provide the following explanation, noting that bubbles can stretch and become all kinds of odd-looking shapes, but if one seals a bubble by flipping it off a wand, the tension in the bubble membrane shrinks to the smallest possible shape for the volume of air it contains. That's why even if it had an odd shape before you sealed it, once sealed shut, the bubble will shrink into a spherical shape. This is because compared to any other shape, a sphere has the smallest surface area for the amount of volume contained therein. This principle can be tested by utilizing a triangle wand. Hold it up, the attendant/guide can ask the user(s) “Do you think that if I make a bubble with it, the bubble will be triangular? Why or why not?”. Of course, shapes other than a triangle can be utilized as wand to start a bubble off having a non-spherical shape, then once released, forming a sphere. Reference to various bubble-making station specific posters can be made.

(29) Further exercises at this station can include blowing several bubbles and fanning them up to keep them from landing on the floor and popping. The attendant/guide can point to how the air temporarily transforms the bubble into a non-spherical shape, but it always goes back into a sphere. The attendant/guide can blow a bubble inside a bubble and as the question “Why do bubbles pop?” and then point out that other than being poked or landing on something sharp, bubbles pop when the water between the soap film surfaces evaporates. Accordingly, when it's cold, those water molecules take longer to leave, so that if you blow a bubble on a calm winter day, a bubble can even freeze and last for several minutes before it pops away. The colder the outside temperature is, the higher a bubble might fly. That's because the warm air from your breath is lighter than the surrounding cold air.

(30) An attendant/guide or poster can ask additional question at this station including: 1) What is a bubble? An attendant/guide or poster can then explain that a bubble is just air wrapped in soap film. Soap film is made from soap and water (or other liquid). The outside and inside surfaces of a bubble consist of soap molecules. A thin layer of water lies between the two layers of soap molecules, sort of like a water sandwich with soap molecules for bread. They work together to hold air inside. Water molecules really like other water molecules (aka cohesion) and try to stick together as much as they can. Water molecules like each other so much that they will work really hard to stay together (aka surface tension). 2) Why a bubble is spherical in shape? An attendant/guide or poster can then explain that by using wands of various shapes (triangle, square, etc.), we can show that no matter the apparatus being used, the resulting bubble will be spherical in shape. The user can make a very long stretched out bubble, but once it's sealed, the tension in the bubble membrane shrinks to the smallest possible shape for the volume of air it contains.

Compared to any other shape, a sphere has the smallest surface area for the amount of volume. 3) What is a good way to measure how big this bubble is? And who can make the biggest bubble? An attendant/guide or poster can then lead a discussion of circumference versus diameter can follow or be provided, for example. Such a bubble-making station as described above provides for significant educational as basin as physical development. Physical development realized and facilitated at such a bubble-making station includes, but is not limited to, motor/neurological precision development and practice, improved hand-eye coordination, oral-facial muscle development through via forcing air in a user's lungs through various bubble-making tools/wands, for example. In addition, such a station can also provide pulmonary exercises for a user via interactive engagement with bubble-making apparatus that requires a user to blow their own pulmonary air through a bubble making tool, such as a bubble wand, in order to form bubbles; 4) Do you think bubbles pop from the top or from the bottom? An attendant/guide or poster can then explain how gravity pushes the liquid and bubble molecules down so that the top becomes very thin. Since bubbles usually pop when the soap film evaporates, they tend to pop from the top rather than from the bottom; and 5) What happens to a bubble when it pops? An attendant/guide or poster can then explain since there only needs to be one weak point in the circle of a bubble for it to pop, even if the rest of the bubble is strong and the molecules still stick together. After it pops, there are bits of solution and water that are still stuck

together that fly off and drop to the ground because of gravity.

(31) A second exemplary bubble-making station includes a smoke-like fog generating system **200** that comprises a gas producing apparatus, methods of using and/or interacting with the gas producing apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. In one embodiment, a gas producing apparatus disclosed herein uses carbon dioxide (CO₂) sublimated from dry ice to form bubbles filled with smoke-like fog (the cold carbon dioxide sublimating from the dry ice causing water vapor to condense and form smoke-like fog). A gas producing apparatus disclosed herein provides holdable and moldable bubbles that allows a user to easily manipulate the bubble(s) containing the smoke-like fog for recreational purposes. The user can hold the smoke-like filled bubble, create smoke-like fog filled bubble art, create bubbles inside bubbles, and various other entertaining recreational activities for enjoyment.

(32) Referring now to FIGS. 2A-2C, which show an exemplary smoke-like fog generating system **200** and gas producing apparatus **210** herein described at this second bubble-making station. Gas producing apparatus **210** includes a smoke-like fog generating apparatus **231** for generating bubbles filled with smoke-like fog and base **240**. The smoke-like fog generating apparatus **231** includes a body **218** and a lid **216**. Body **218** includes one or more sides **215**, a bottom **217**, a top opening **219** opposite bottom **217**, top opening **219** being defined by the perimeter formed by one or more sides **215**, and the resulting interior space defining an internal reservoir **212**. Internal reservoir **212** is configured so that an attendant/guide **250** can place a piece of dry ice **206** into water **232** located within internal reservoir **212**, whereby smoke-like fog **234** is generated. Internal reservoir **212** may abut a heating element **214**. Heating element **214** may be an integral part of body **218**, for example an integral part of one or more sides of body **218**. Smoke-like fog generating apparatus **231** can be configured to have an on/off switch **209** for the resistive element **214** and a dial **208** to control the amount of current applied to the heating element, to control/change the rate of carbon dioxide sublimation off of dry ice **206** in internal reservoir **212**.

(33) Referring to FIG. 2A, lid **216** is designed to the dimensions of top opening **219** of body **218** in a manner that closed or seals internal reservoir **212**. A seal, for example a rubber grommet can be placed in between lid **216** and edge of body **218** defining top opening **219** in order to create a hermetic seal to confine smoke-like fog to within the smoke-like fog generating apparatus **231**. Lid **216** may be unconnected to body **218** so that lid **216** may be completely removed and separated from body **218** in order to access internal reservoir **212**. Alternatively lid **216** may be connected to body **218** with a hinge **224** or other device known in the art so that lid **216** may be moved and internal reservoir **212** accessed. Alternatively, or in addition to hinge **224**, lid **216** may include one or more clasps, clamps or other device known in the art which may secure lid **216** to body **218**. In any embodiment, lid **216** is moved to access internal reservoir **212**. In operation, a mixture of dry ice **206** and water **232** may then be placed in internal reservoir **212**, and lid **216** may be closed top opening **219** of body **218** to reseal or reclose internal reservoir **212**.

(34) Referring to FIGS. 2A & 2B, lid **216** may further include one or more ports **226**, which fluidly connect to the interior of internal reservoir **212**. As few as one port, and as many as 60 ports are contemplated, depending on reservoir capacity, e.g., 1 to 60 ports, 1 to 10 ports, 2 to 10 ports, 2 to 8 ports, 4 to 8 ports, 3 to 7 ports, 4 to 7 ports, 4 to 6 ports, 5 ports or 6 ports. Ports **226** primary function is to act as a coupling point for a corresponding hose **220**. In the exemplary embodiment shown in FIGS. 2A & 2B, lid **216** includes six ports **226** (**226a-f**) and their corresponding hoses **220** (**220a-f**). Hoses **220** are fluidly connected each to its own port **226**. The combination of internal reservoir **212**, ports **226**, and hoses **220** form a number of continuous fluid paths from internal reservoir **212** corresponding to the number of ports **226** and hoses **220** present. The fluid path is enclosed until the fluid path reaches the second end portion of hose **220**, for example hose end portion **205** of hose **220**.

(35) Ports **226** may be evenly spaced around lid **216**. For example, if there are four ports **226**, each

port **226** may be placed every 90 degrees in a circular pattern around lid **216**. If there are five ports **226**, each port **226** may be placed every 72 degrees around lid **216**. If there are three ports **226**, each port **226** may be placed every 120 degrees around lid **216**, and so on. Ports **226** may be placed anywhere on lid **216** from the center to the perimeter along the lines defined from the center to the perimeter demarcating the arcs. In an alternative configuration, when ports **226** are placed nearer the center of lid **216**, each port **226** may be connected to a central hub structure. The hub structure may be a central raised portion of the lid, with openings that create each of ports **226**.

(36) Port **226** or plurality thereof, may include a bib **221** or boss to which a corresponding hose **220** may be connected. Only one exemplary connection will be further discussed, but it is understood that each connection may share the attributes discussed. Referring to FIG. 2C, on a first end, the hose **220b** may be connected to the port **226** using a mechanical fastener, for example, a hose clamp (not shown) that is positioned around hose **220b** and at that portion where hose **220b** fits over bib **221**, for example. Alternatively, hose **220** may be sized to provide a friction fit to the bib **221** or other connecting structure on port **226**, twist and lock connections, or may use male and female threaded fittings. Hose **220** may have a circular transverse cross section. Alternatively, hose **220** may have any other cross section which will contain the fluid being transported therethrough. The second end portion of hose **220** may have a fitting. The fitting may have a standard configuration known in the art to be adapted to connection with a corresponding fitting. For example, hose **220** may include a standard garden hose configuration or an industrial vacuum fitting. Hose **220** may have a length that allows the second end to be placed in at least one basin **228**, such as basins **228a, b, c**, etc., as exemplarily shown in FIGS. 2A & 2B.

(37) As shown in FIGS. 2A & 2B, at least one or each hose **220** may have a cap **204** which seals the second end portion of hose **220**. Cap **204** may slide over the second end portion of hose **220** and be held in place by a friction fit. Alternatively, cap **204** may be configured to connect to a fitting present on the second end portion of hose **220**. For example, cap **204** may include female threads which connect to male threads present on a fitting. As another alternative, cap **204** may friction fit on the set of male threads of a fitting located on the second end portion of hose **220**. The attachment of cap **204** prevents any smoke like fog **234** from leaving through hose **220** to which cap **204** is attached, while not affecting the flow of smoke-like fog **234** through other hoses, if there are any. Hose **220** may be made of a flexible material, for example a polymer or a plastic. Because of the flexibility, second end portion **205** of hose **220** may be pointed in almost any direction by a user.

(38) Still referring to FIGS. 2A & 2B, smoke-like fog generating apparatus **231** may be placed on a base **240**. Base **240** comprises one or more sides **242**, a bottom **244** and a top surface **246**. One or more sides **242** of base **240** may be curved, defining a circle or an oval, or any cuboidal shape with square and rectangular shapes being preferred, the cuboidal shape having sharp (right-angled) or curved corners. In some embodiments, base **240** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, base **240** is generally cuboidal in shape. In some embodiments, base **240** is cuboidal and can have a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. The height of base **240** can be 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet.

(39) Top surface **246** of base **240** can further, and optionally, include a lip around a perimeter of top surface **246**, thereby forming a reservoir designed to contain bubble solution **4**. In a preferred embodiment, the lip of top surface **246** has a height of, for example, about 0.25 inches to 0.5 inches, about 1 inch to 5 inches, about 2 to 4 inches to about 3 inches. When top surface reservoir of top surface **246** is present, one or more basins **228** become part of top surface reservoir of top surface **246** can be considered deeper areas of top surface reservoir of top surface **246** The shape

defining top surface reservoir of top surface **246** may be curved, defining a circle or an oval, or any closed polygonal shape with triangle, square, rectangular, and pentagonal shapes, the polygonal shape having sharp or curved corners. In some embodiments, top surface reservoir of top surface **246** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, top surface reservoir of top surface **246** is generally polygonal in shape. In some embodiments, top surface reservoir of top surface **246** is polygonal in shape and each length of the polygon can be 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, 1 to 2 feet, 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet.

(40) Top surface **246** may have one or more basins **228** formed in it. The number of one or more basins **228** present typically corresponding to the number of ports **226** and hoses **220** provided by smoke-like fog generating apparatus **231**. Each of the one or more basins **228** may have a basin side wall **238** and a top edge of basin side wall **238** may be rounded off or be provided having a substantially right angle. In particular configurations, base **240** can comprise one or more basins, 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. Each of the one or more basins **228** can serve as a reservoir for bubble solution **4**. Each of the one or more basins **228** are filled to a sufficient depth that may be manually delivered into basins **228**. Each of the one or more basins **228** can be of any suitable geometry, perimeter, and/or shape and any depth that provides for a sufficient area and volume to hold bubble solution **4**. In a preferred embodiment, each of the one or more basins are circular and have a flat bottom and a surrounding side that rises from, for example, about 0.25 inches to 0.5 inches, about 1 inch to 5 inches, about 2 to 4 inches to about 3 inches from the bottom of the basins. Each of the one or more basins **228** can have a depth of bubble solution **4** of, for example, about 0.25 inches to 0.5 inches, about 0.25 inches to about 0.75 inches, about 0.5 inch to about 1 inch, about 1 inch to about 2 inches or about 0.5 inch to about 3 inches contained therein. The basin may be made of any material which may retain fluid, with materials that withstand corrosion from bubble-making fluid being preferred, such as, e.g., plastic, fiberglass, treated wood, glass, or metal.

(41) FIG. 2C shows a cross-sectional view of smoke-like fog generating apparatus **231** comprising body **218** includes internal reservoir **212** and lid **216**. Body **218** and lid **216** are made from a hard material that can tolerate extreme cold temperatures of -20° C. or lower, e.g., ceramic or a metal such as steel or aluminum, or a carbon fiber composite. Body **218** and/or lid **216** may further include a layer of insulating material **230**. Insulating material **230** may be an integral part of body **218** and/or lid **216** or a separate component to smoke-like fog generating apparatus **231**. Such layer of insulating material **230** provides protection to apparatus **231** as basin as a user from the intense cold temperatures generated from dry ice **206**. When an integral part of body **218** and/or lid **216**, in some embodiments insulating material **230** is encased in the hard material comprising body **218** or lid **216** and thus is inside body **218** or lid **216**. This encasement prevents the insulating material from becoming damaged, and the system losing insulation, thereby operating less efficiently. In some embodiment, incorporation of layer of insulating material **230** may be on the inside surface of into body **218** and thus may form a shelf **233** on an upper end portion of the inside surface of body **218**. In some embodiment, when an separate component of body **218** and/or lid **216**, insulating material **230** may be located abutting the outside surface of body **218** and/or lid **216**. A seal, for example a rubber grommet or flange can be placed on shelf **233** of body **218** to create a hermetic seal along the line of contact between lid **216** and body **218**. Lid **216** may include insulating material, in order to retain heat in internal reservoir **212**.

(42) Still referring to FIG. 2C, body **218** and resulting internal reservoir **212** may be any shape, e.g. with preferred shapes of body **218** and/or internal reservoir **212** being a cylindrical shape and having a circular or oval transverse cross section, a cuboidal shape having a square transverse cross section, or a cuboidal shape having a rectangular transverse cross section. Internal reservoir **212**

may have any depth, with depths in a range of 2 inches to 24 inches being preferred. In some embodiments, body **218** and/or internal reservoir **212** may have bottom **217** that is flat while in other embodiments bottom **217** may be concave or convex in shape. Bottom **217** may be connected around an exterior edge to a first end portion of one or more walls **215**. One or more walls **215** may be straight or tapered. In one embodiment, one or more walls **215** may taper from a first defined perimeter at the first end portion to a second defined perimeter at an opposite, second end portion. The second defined perimeter may have a greater total length than the first. In this configuration, the reservoir wall forms an open-ended cone or pyramid shape, with the smaller opening of the cone or pyramid being closed by the flat circular bottom.

(43) Still referring to FIG. 2C, body **218** includes a heating element **214** which may abut internal reservoir **212**. Heating element **214** may abut internal reservoir **212** on bottom **217** and/or on one or more sides **215**. Heating element **214** may be made of an electrically resistive element, such as a wire, such that when a current is applied to the electrically resistive element, much of the energy of the current is transferred to heat. Such a wire may be made from an alloy or pure metal which provides the heating sufficient to accelerate sublimation of dry ice **206** when the dry ice **206** is placed, along with water **232**, in internal reservoir **212**. Heating element **214** may be in the shape of the wire and the amount of contact with the reservoir may be adjusted during assembly by adjusting the length of the wire. Alternatively, internal reservoir **212** itself may be made of an alloy which is electrically resistive and provides heat when a standard 110 volt/60 hz or 220 volt/50 hz electrical current is applied to it. Again, the heat generated by the electrical current would be sufficient to accelerate the sublimation of dry ice **206** in internal reservoir **212** if such heat was greater than ambient temperature. Insulated body **230** will help retain the heat added to internal reservoir **212** in order to continue the acceleration of the sublimation of the dry ice, and creation of smoke-like fog **234** from the mixture of the carbon dioxide gas and water, as will be discussed in further detail below.

(44) Heating element **214** may be electrically connected to a standard wall outlet or other source of power using an electrical cord to provide current to the heating element or reservoir, as described above. The flow of current heats the heating element **214** or internal reservoir **212**, and this heating further accelerates the sublimation of the dry ice **206**, and the formation of the smoke-like fog **234**. One end of heating element **214** may be connected to a first lead, and a second end of heating element **214** connected to a second lead wire. The lead wires may be attached to a plug configured to be inserted in a standardized wall socket. The lead wires, heating element **214**, and plug may be attached by soldering or any other method known in the art. The insulated body may include a sensor which is electrically connected to a switch in the path of the current coming to heating element **214** from, for example, a plug and cord placed in a standard wall outlet. For example, the switch may be placed in line on one of the lead wires. Once a first predetermined temperature is reached, the sensor, which is electrically connected to the switch via lead wires, or other methods known in the art, may cause the switch to open by sending an electrical signal over the connection. The sensor may then send another electrical signal over the connection, which causes the switch to close again once the sensor senses a second predetermined temperature. The second predetermined temperature is lower than the first predetermined temperature.

(45) In operation, smoke-like fog generating system **200** creates a smoke-like fog **234** that may be used to fill a bubble with the smoke-like fog **234**. Lid **216** may be opened to allow access to internal reservoir **212**. A mixture of dry ice **206** and water **232** may be placed in internal reservoir **212**. When dry ice **206** is placed in water **232**, sublimation is accelerated, and low-sinking, dense clouds of smoke-like fog **234** are created. As smoke-like fog **234** continues to build in the space defined by internal reservoir **212** and lid **216**, it begins to move through ports **226** fluidly connecting the space defined by internal reservoir **212** and lid **216** to the one or more hoses **220**. The smoke-like fog **234** originates from water **232** into which the dry ice **206** is placed, and not from atmospheric water vapor.

(46) Simultaneously and as shown in FIG. 2B, user 2 (here, user 2 at far-right) may grasp one of the one or more hoses 220 near the second end portion 205 and place the second end portion 205, including any attachments if attached thereto, to a base 240 portion having bubble solution 4 thereon or into basin 228 with bubble solution 4. Bubble solution 4 forms across the second end portion 205 of the hose 220, or across a connected attachment. As pressure builds, some portion of the smoke-like fog 234 arrives at the second end portion 205 of each of the one or more hoses 220 and the smoke-like fog 234 may form a bubble by contacting and stretching the bubble fluid, which then closes around some portion of the smoke-like fog 234, and a bubble is created with the portion of the smoke-like fog 234 in an interior of the bubble, as shown in FIG. 2B. The attachments may allow for more than one bubble to be created by having a plurality of subdivisions on the attachments. Alternatively, or in addition, the shapes of the subdivisions of the attachments may be changed to change the shape of the bubbles. In addition to bubbles filled with smoke-like fog 234, as shown being made by user 2 at the far right of FIG. 2B, bubble filled with smoke-like fog 234 may be made with a mobile apparatus for creating bubbles 1010, particular configurations being wearable, as illustrated by user 2 at the far-left of FIG. 2B. Furthermore, bubbles that are clear (that is, not filled with smoke-like fog 234) can also be made at this second exemplary station, where bubble solution 4 (either in a basin 228 or on another top portion of base 240) is utilized with a handheld bubble making tool 8 such as those shown in FIGS. 1A & 1E. A plurality of clear bubbles is shown in a basin in FIG. 2B, here, a plurality of bubbles stacked atop one another in basin 228.

(47) This second exemplary bubble-making station includes a system 200 providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(48) For example, an attendant/guide can encourage users to engage in such activities as utilizing the provided the hose and just hold onto the smoke-like fog blowing out or to create a white bubble by placing the hose end into a bubble solution and then after creating the white bubble, playing with it. While this is occurring, the attendant/guide can then proceed to explain that bubbles usually form because air becomes trapped between the soap and water molecules and that's why bubbles are transparent and we can usually see through them. In this case, the smoke-like fog provided by sublimating dry ice is trapped inside the bubble so we can see the fog. Exemplary questions can be "What happens when we pop the bubble?" An attendant/guide can then explain that all the trapped smoke-like fog from inside the bubble is no longer contained and can freely flow outside.

(49) As another example, an guide/attendant can instruct the users to wet their hand or hands and have them touch the bubble with a finger and see if the bubble pops. The guide/attendant then asks the user(s) repeat touching the bubble but this time using a dry finger. The guide/attendant can then ask "Does the bubble pop? Why didn't it pop? Was it magic or science? The attendant/guide can then explain why bubbles pop and then discuss hydrophobic and hydrophilic molecules and how they like to stick together so when the water from a user(s) finger touches the surface of the sphere, it doesn't pop the bubble. However, touching the bubble with a dry finger will pop the bubble.

(50) In another example, an attendant/guide can have the users at the station wet their hands and then create a bubble inside their palm and then create a bubble on both of their palms. Then the attendant/guide can have them try to merge the bubbles in each palm together. The guide/attendant can ask "Can bubbles merge together? And What do they think is happening here?"

(51) As a further example, an attendant/guide can themselves make or lead a user(s) in making a very large bubble by putting it on the table to the side of the bubble solution. The guide/attendant

can ask-“How does the bubble get so big? What will make it grow bigger and what will make it pop earlier than usual?”. The attendant/guide can go one to explain the various factors at play that give bubbles their particular observed characteristics, such as: a) the speed at which the smoke-like fog is coming out of the hose. The carbon dioxide gas entering the forming bubble needs to be at the appropriate speed for the bubble to grab enough molecules (soap and water) to steadily grow; b) How much bubble solution or water is available for the bubble to grow: A bubble growing is like building anything (i.e., Legos), the bubble needs materials to make it grow bigger. The bubble requires more than just a gas/air to go inside, it also needs sufficient bubble solution. The guide/attendant can ask-“If you make it here on the table versus inside the basin, how would it affect it?”.

(52) As another example, an attendant/guide can then move on to create a large white bubble (smoke-like fog filled) and then create another smaller white bubble (smoke-like fog filled) at this station and bounce the smaller bubble onto top of the bigger bubble causing it to merge with the bigger bubble. The guide/attendant can ask “Why do you think this happens?”. The attendant/guide goes on to explain surface tension for this specific scenario.

(53) An attendant or guide can point out that when dry ice was put into the apparatus it was a solid, and now it's a liquid. Ask them to touch the gas—it's not hot and it's not cold. The guide or attendant may go on to explain the different phases of a substance and what is carbon dioxide and its properties of carbon dioxide.

(54) During these demonstrations, an attendant/guide or poster can ask additional questions at this station including: 1) What are the different phases of matter? An attendant/guide or poster can then explain that the three major transitional phases of a substance are solid phase, liquid phase, and gas phase; 2) What is sublimation? An attendant/guide or poster can then explain that sublimation is the transition of a substance from the solid phase to the gas phase without passing through the intermediate liquid phase; 3) What's the big difference between regular ice and dry ice? An attendant/guide or poster can then explain that temperature of regular ice is 32° F. and dry ice is -100° F. The attendant/guide or poster can then explain how to safely handle dry ice and how it can cause severe frostbite with contact of skin over 3 seconds; 4) What is dry ice? What is the smoke that we see inside the bubble? An attendant/guide or poster can then explain that while carbon dioxide gas is invisible, the very cold gas causes water vapor in the air to condense into water droplets, thus creating fog; 5) How do they make dry ice? An attendant/guide or poster can then explain that carbon dioxide gas is pressurized in a special production machine and cooled to first form liquid carbon dioxide. The liquid is moved into chambers that convert it to blocks or other desirable forms. The attendant/guide or poster can then explain that dry ice is not available naturally and is man-made; 6) What do you think dry ice is used for usually? Have you seen dry ice anywhere? An attendant/guide or poster can then explain that dry ice is used to keep things cold. It's much colder than regular ice and is used to keep mobile items cold, like in ice cream trucks and the shipment of sensitive cold items. More recently dry ice is used for recreational purpose and to add a sensational factor, for example in restaurants for drinks or plate presentations; 7) Has anyone heard of Liquid Nitrogen? How is that different than dry ice? An attendant/guide or poster can then explain that liquid nitrogen gives off gas just like dry ice does but that liquid nitrogen is made of nitrogen and dry ice is made of carbon dioxide; and 8) Liquid nitrogen does NOT sublime. What does that mean? An attendant/guide or poster can then explain that when liquid nitrogen warms, the liquid turns into a gas where when dry ice warms it turns straight from a solid into a gas, skipping the liquid phase. Liquid nitrogen is much colder and is commonly used to freeze and remove warts. Liquid nitrogen does not occur naturally, it is made in the lab. Nitrogen from the air is forced to become a liquid (through and according to the IDEAL GAS LAW $PV=nRT$ processes).

(55) A third exemplary bubble-making station includes a mobile smoke-like fog generating system **1000**, which is similar to smoke-like fog generating system **200**. A user would walk around with mobile smoke-like fog generating system **1000** and make bubbles containing smoke-like fog **234**

on a surface (or in mid-air). Alternatively, or in addition, a user may be provided mobile smoke-like fog generating system **1000** and allowed to make bubbles filled with smoke-like fog **234**, as shown as one example in FIG. **2B** and FIG. **10A**. A mobile version of smoke-like fog generating system **200**, this mobile version provides the same scientific and educational value as the stationary version. Aspects of the mobile smoke-like fog generating system **1000** are described in U.S. Provisional Patent Application Ser. No. 62/799,555, the entire content of which is hereby incorporated by reference in its entirety.

(56) Turning to FIGS. **10A** & **10B**, mobile smoke-like fog generating system **1000** comprising a mobile apparatus **1010** is used to create a bubble or a series of bubbles. In one aspect, the instant disclosure concerns a mobile smoke-like fog generating system **1000** comprising a mobile apparatus **1010** is used to create one or more carbon dioxide filled bubbles. Such a viable, reliable and effective mobile smoke-like fog generating system **1000** as basin as the method of use of such a device is provided herein.

(57) Referring to FIG. **10B**, mobile apparatus **1010** comprises a carrier **1011** and a mobile smoke-like fog generating apparatus **1012**. Carrier **1011** may include at least one carrying compartment **1030** defining an interior portion **1036**, a flap **1032** for covering interior portion **1036** of at least one carrying compartment **1030** and one or more straps **1034** for securing mobile apparatus **1010** to or on a user, e.g., by placing one or more straps **1034** over a user's shoulders. Mobile smoke-like fog generating apparatus **1012** may be placed in interior portion **1036** of at least one carrying compartment **1030** of carrier **1011**. Carrier **1011** may be a backpack design to contain mobile smoke-like fog generating apparatus **1012** and used to support smoke-like fog generating system **1000** on a person's shoulders. Alternatively, the carrier **1011** may be any bag or apparatus that a user can wear on their person, while still retaining movement of their hands and arms.

(58) In general and similar in various aspects to smoke-like fog generating apparatus **231** above, mobile smoke-like fog generating apparatus **1012** comprises a body **1018** and a lid **1016** (FIG. **10B**). Body **1018** may include a bottom **1035**, one or more walls **1033** extending from bottom **1035**, and an open end **1037** opposite bottom **1035**, open end **1037** being defined by the perimeter formed by one or more walls **1033**, and the resulting interior space defining an internal reservoir **1022**. Lid **1016** is designed to the dimensions of open end **1037** in a manner that closed or seals internal reservoir **1022**. A seal, for example a rubber grommet can be placed in between lid **1016** and edge of body **1018** defining open end **1037** in order to create a hermetic seal to confine smoke-like fog to within the apparatus. Lid **1016** may be connected to body **1018** with a hinge **1024**, clasps, clamps, or other device known in the art so that lid **1016** may be moved and internal reservoir **1022** accessed, and then lid **1016** resealed over open end **1037**. In operation, a mixture of dry ice **1206** and water **1232** may be placed in internal reservoir **1022**, and lid **1016** may be closed to seal open end **1037** of body **1018**.

(59) Body **1018** and resulting internal reservoir **1022** may be any shape, e.g. with preferred shapes of body **1018** and/or internal reservoir **1022** being a cylindrical shape and having a circular or oval transverse cross section, a cuboidal shape having a square transverse cross section, or a cuboidal shape having a rectangular transverse cross section. Internal reservoir **1022** may have any depth, with depths in a range of 2 inches to 18 inches being preferred. In some embodiments, body **1018** and/or internal reservoir **1022** may have bottom **1035** that is flat while in others bottom **1035** may be concave or convex in shape. Bottom **1035** may be connected around an exterior edge to a first end portion of one or more walls **1033**. One or more walls **1033** may be straight or tapered. In one embodiment, one or more walls **1033** may taper from a first defined perimeter at the first end portion to a second defined perimeter at an opposite, second end portion. The second defined perimeter may have a greater total length than the first. In this configuration, the reservoir wall forms an open-ended cone or pyramid shape, with the smaller opening of the cone or pyramid being closed by the flat circular bottom. In a particular embodiment, body **1018** may further include a flange **1040** connected to the second end portion and extending outward from the second

end portion. Flange **1040** may abut a shelf (not shown) on an upper end portion of the heating element **1014** or, if so configured, abut a shelf (not shown) on an upper end portion of insulated body **1038** to position body **1018** within carrier **1011**. Body **1018** and lid **1016** of mobile apparatus **1010** may be made of a metal, for example aluminum.

(60) As shown in FIG. **10B**, one or more ports **1026** may be fluidly connected to internal reservoir **1022**. In one embodiment, one or more ports **1026** are located on one or more walls **1033** of body **1018**. Alternatively, or in addition to, lid **1016** may include one or more ports **1026**. One or more ports **1026** may also be placed near bottom **1035** of body **1018** (however not so close to bottom **1035** that water **1232** contained in internal reservoir **1022** enters hose **1020**). One or more ports **1026** may include a bib or boss to which a corresponding hose **1020** may be connected. The primary function of one or more ports **1026** is to act as a coupling point for a corresponding number of hoses **1020**.

(61) Placement of one or more ports **1026** should be in locations that will not interfere with a user placement of carrier **1011** or operation of mobile smoke-like fog generating system **1000**. In particular embodiments, four ports **1026** on lid **1016** may be placed every 90 degrees in a circular pattern around lid **1016** having a circular shape or at each of the corners of a square or rectangular lid **1016**. If there are five ports **1026**, each port **1026** may be placed every 72 degrees around circular lid **1016**, or at each of the corners and between the distalmost two ports on square or rectangle lid **1016**. If there are three ports **1026**, each port **1026** may be placed every 120 degrees around a circular lid **1016**, or in a line along the distal side of a square or rectangular lid **1016**.

(62) Hose **1020**, including a first end portion and a second end portion, may be attached to each of the one or more ports **1026**. On a first end, hose **1020** may be connected to port **1026** using a mechanical fastener, for example a hose clamp (not shown). Alternatively, and as shown in FIG. **10B**, hose **1020** may be sized to provide a friction fit to the bib or other connecting structure on port **1026**, or may use male and female threaded fittings. Hose **1020** may have a circular transverse cross section. Alternatively, hose **1020** may have any other cross section which will contain the fluid being transported therethrough. The second end of hose **1020** may have a fitting. The fitting may have a standard configuration known to the art to be adapted to connection with a corresponding fitting. For example, hose **1020** may include a standard garden hose configuration or an industrial vacuum fitting. Such fittings allow attachment of nozzles or other devices that change the flow of fog-like smoke from hose **1020** or enable attachment of second end portion of hose **1020** to another apparatus or device, such as, e.g., a basin or basin containing bubble solution **4**. Hose **1020** may have a length that allows the grasping of hose **1020** by a user when wearing mobile apparatus **1010** using carrier **1011**. Hose **1020** or a plurality thereof, may be made of a flexible material, such as, e.g., a polymer or a plastic. Because of the flexibility of hose **1020**, the second end portion of hose **1020** may be pointed in almost any direction by a user **2** or guide/attendant **250**.

(63) The combination of internal reservoir **1022**, one or more ports **1026**, and one or more hoses **1020** form a number of fluid paths from internal reservoir **1022** corresponding to the number of ports **1026** and hoses **1020**. The fluid path is enclosed until the fluid path reaches the Mobile smoke-like fog generating system **1000** may further include a heating element **1014**. In particular embodiments, heating element **1014** may be a separate component of mobile apparatus **1010** or, as shown in FIG. **10B**, an integral part of mobile apparatus **1010**. Heating element **1014** placed between insulated body **1038** and body **1018** in a manner that places body **1018** against heating element **1014**. In preferred embodiments, heating element **1014** abuts body **1018** so that heating element **1014** can heat the contents of internal reservoir **1022**. Heating element **1014** can include an electrically resistive element such that when a current is applied to the electrically resistive element, much of the energy of the current is transferred to heat. In some embodiments, an electrically resistive element is an electrically resistive wire **1042**. Wire **1042** may be made from an alloy or pure metal which provides the heating sufficient to accelerate sublimation of dry ice **1206**

when dry ice **1026** is placed along with water **1232** in internal reservoir **1022**. The shape of wire **1042** and the amount of contact with mobile apparatus **1010** may likewise be adjusted when the system is assembled. Alternatively, mobile apparatus **1010** itself may be made of an alloy which is electrically resistive and provides heat when a current is applied to it. Again, the heat generated by the electrical current would be sufficient to accelerate the sublimation of the dry ice **1026**. The current may be provided by a battery **1044**, which may have the battery terminals attached to leads extending from opposite ends of the electrically resistive wire **1042** or the reservoir, if so configured. Battery **1044** may have any voltage which provides acceleration of the sublimation and which is less than 40 pounds weight. A switch **1046** may also be provided that breaks the circuit to the battery by disconnecting one of the leads to the corresponding battery terminal. Battery **1044** may be stored in a separate compartment on the carrier, or in the same compartment as the reservoir.

(64) Mobile smoke-like fog generating system **1000** may further include an insulated body **1038**. In some embodiments, and as shown in FIG. **10B**, insulated body **1038** can be an integral portion of carrier **1011**, being located on an interior surface of interior portion **1036** and/or interior surface of flap **1032** of carrier **1011**. Insulated body **1038** can completely cover the interior surface of interior portion **1036** and/or flap **1032** of carrier **1011** or can partially cover these exterior surfaces. In some embodiments, insulated body **1038** can be an integral portion of mobile apparatus **1010**, being located on an exterior surface of body **1018** and/or an exterior surface of lid **1016** of mobile apparatus **1010**. Insulated body **1038** can completely cover the exterior surface of body **1018** and/or lid **1016** of mobile apparatus **1010** or can partially cover these exterior surfaces. When placed inside carrier **1011**, insulated body **1038** abut and surround mobile apparatus **1010** and heating element **1014** (FIG. **10B**). In other embodiments, insulated body **1038** may include an outer layer made of a material different than insulating material. This outer material can be harder than the insulating material. For example, the outer material may be a metal such as steel or aluminum, or a carbon fiber composite. This outer layer prevents the insulating material from becoming damaged, and the system losing insulation, thereby operating less efficiently. Insulated body **1038** will help retain the heat generated by heating element **1014** and thus facilitates acceleration of the sublimation of the dry ice **1206**, and creation of smoke-like fog **234**.

(65) Mobile smoke-like fog generating system **1000** may further include a basin or basin configured to receive the second end portion of hose **1020** and the basin being filled with bubble solution **4**.

(66) In operation, mobile smoke-like fog generating system **1000** generates smoke-like fog **234** that may be used to create a bubble by exposing bubble solution **4** with the smoke-like fog **234** to create one or more smoke-like fog filled bubbles. Generally, lid **1016** of mobile smoke-like fog generating apparatus **1012** may be opened to allow access to internal reservoir **1022**. A mixture of dry ice **1206** and water **1232** may be placed in internal reservoir **1022**. Water **1232** may be pre-heated when placed in internal reservoir **1022**. Blocks of dry ice **1206** of up to 18 inches×18 inches×18 inches are contemplated. When dry ice **1206** is placed in water **1232**, sublimation is accelerated, and low-sinking, dense clouds of smoke-like fog **234** are created. As the smoke-like fog **234** continues to build in the space defined by internal reservoir **1022** and lid **1016**, it begins to move through one or more ports **1026** fluidly connecting to internal reservoir **1022** and lid **1016** to the corresponding one or more hoses **1020**. The smoke-like fog **234** originates from the bulk water **1232** into which the dry ice is placed, and not from atmospheric water vapor. Thus, water **1232** serves two purposes, it both accelerates the sublimation of dry ice **1206** and provides a source of water **1232** for the creation of the smoke-like fog **234**.

(67) In embodiments containing heating element **1014**, switch **1046** may then be engaged to complete the circuit between battery **1044** and heating element **1014**, providing current to heating element **1014**. The flow of current heats heating element **1014** which in turn heats water **1232** contained in internal reservoir **1022**, and this heating further accelerates the sublimation of dry ice

1206, and the formation of smoke-like fog **234**. Switch **1046** may be engaged or disengaged, at the discretion of the user **2** or guide/attendant **250**.

(68) Simultaneously, user **2** or guide/attendant **250** may grasp one of one or more hoses **1020** near the second end portion and place the second end portion, including any attachments attached thereto into the basin or basin, which is filled with bubble solution **4**. Bubble solution **4** forms across the second end portion of hose **1020**, or across a connected attachment. As pressure builds, some portion of the smoke-like fog **234** arrives at the second end portion of each of one or more hoses **1020** and smoke-like fog **234** may form a bubble by contacting and stretching bubble solution **4**, which then closes around some portion of smoke-like fog **234**, and a bubble is created with the portion of smoke-like fog **234** in an interior of the bubble, as shown in FIG. 2B, for example. The attachments may allow for more than one bubble to be created by having a plurality of subdivisions on the attachments. Alternatively, or in addition, the shapes of the subdivisions of the attachments may be changed to change the shape of the bubbles formed therefrom. As another example, bubbles created and containing smoke-like fog **234** from mobile smoke-like fog generating system **1000** can additionally be made from a bubble sheet/film or wall made at one of the of bubble-making stations that comprise the entertainment facility herein disclosed, as exemplarily depicted in FIG. 10A.

(69) This third exemplary bubble-making station includes a system **100** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide. Examples of specific basic educational science and mathematical principles are discussed above for system **200**.

(70) A fourth exemplary station includes system **300** that comprises an inflatable apparatus, methods of using and/or interacting with the inflatable apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. System **300** is generally used for photographic or video opportunities. An inflatable apparatus includes one or more inflatable chambers. In use, one or more users enter the and optionally play within one or more inflatable chambers of the inflatable apparatus while, optionally, another user can take photographs or videos of the one or more users inside inflated apparatus.

(71) FIGS. 3A & 3B show an exemplary inflatable apparatus **310** that comprises a first inflated chamber **320**, a second inflated chamber **330**, and an inflation system **340**. First inflated chamber **320** is contiguous with a second inflated chamber **330**. Inflation system **340** comprises an inflation device **342**, such as a blower, fan or inflatable air pump, and one or more air conduits **344**, one or more conduits **344** connecting inflation device **342** to inflatable apparatus **310**. In some embodiments, one or more conduits **344** connecting inflation device **342** to at least first inflation chamber **320**. In some embodiments, one or more conduits **344** connecting inflation device **342** to at least second inflation chamber **330**. In some embodiments, one or more conduits **344** connecting inflation device **342** to both first inflation chamber **320** and second inflation chamber **330**. Inflation system **340** continuously keeps first inflated chamber **320** and, optionally, second inflated chamber **330** inflated with air. Inflatable apparatus **310** can be made of any durable material including plastic such as poly-vinyl or poly-vinyl blends. Preferably large portions of the apparatus are composed of durable transparent materials.

(72) The dimensions of first inflated chamber **320** are generally of a size that one to five users can comfortably stand within first inflated chamber **320**. The dimensions of first inflated chamber **320** can be any useful geometry including, generally and as a non-limiting example, substantially

cylindrical, substantially semi-circular, substantially cubic and the like. In one embodiment, first inflated chamber **320** is generally spherical in shape. In one embodiment, first inflated chamber **320** is designed to represent a giant bubble, being generally and substantially spherical and curved in shape with a flattened bottom portion that is in contact with a support surface, such as a floor. In some embodiments, first inflated chamber **320** can be 4 to 10 feet in diameter, 6 to 12 feet in diameter, or 8 to 15 feet in diameter. In one embodiment, first inflated chamber **320** is generally cuboidal in shape. In some embodiments, first inflated chamber **320** can be 4 to 12 feet in width, 4 to 12 feet in length and 6 to 15 feet in height. First inflated chamber **320** comprises a continuous portion with second inflated chamber **330**. Such continuous portion comprises an opening to create a pathway between first inflated chamber **320** and second inflated chamber **330**. First inflated chamber **320** can also comprise a partition **322**. Partition **322** can be provided with any desired indicia to provide a backdrop (such as a sunset, or tropical-themed background) for photographs/videos taken of the one or more users inside first inflated chamber **320**.

(73) Second inflated chamber **330** comprises an entrance **332** enabling a user to enter into second inflated chamber **330** from the outside of inflatable apparatus **310**. The dimensions of second inflated chamber **330** are generally of a size that a user can comfortably enter second inflated chamber **330** via entrance **332** from the outside of inflatable apparatus **310** and pass through second inflated chamber **330** and enter first inflated chamber **320** via the opening contained in the continuous portion shared by first inflated chamber **320** and second inflated chamber **330**. The dimensions of second inflated chamber **330** can be any useful geometry including, generally and as a non-limiting example, substantially cylindrical, substantially semi-circular, substantially cubic and the like. In one embodiment, second inflated chamber **330** is generally spherical in shape. In some embodiments, second inflated chamber **330** can be 4 to 6 feet in diameter, 6 to 8 feet in diameter, or 8 to 12 feet in diameter. In one embodiment, second inflated chamber **330** is generally cuboidal in shape. In some embodiments, second inflated chamber **330** can be 4 to 8 feet in width, 4 to 12 feet in length and 6 to 15 feet in height. Optionally, second inflated chamber **330** is provided with a plurality of inflatable supporting ribs **316**. These ribs **316** may be of any color and can be provided bounding/adjacent transparent sections **326** of wall of second inflated chamber **330**. In particular embodiments, it is contemplated that second inflated chamber **330** may not require inflation to maintain its shape and structural integrity.

(74) In operation, user **2** enters second inflated chamber **330** from the outside of apparatus **310** using entrance **332**. User **2** then passes through second inflated chamber **330** and enters first inflated chamber **320** via the opening contained in the continuous portion shared by first inflated chamber **320** and second inflated chamber **330**. User **2** can stay in first inflated chamber **320** to play, take pictures from the inside, or have someone else take pictures of user **2** from outside first inflated chamber **320**. In addition, various other interactive objects **308**, such as inflated balloons or balls or the like, can be provided within first inflated chamber **320**. Furthermore, additional smaller interactive objects **304** can be provided as ground cover to be waded through, such as smaller transparent balls, and may be provided within first inflated chamber **320** to mimic the bubbles within bubbles made by users at the various other bubble-making stations, thereby providing a bubble within a bubble perspective from the inside looking outward. In addition, or as an alternative, the interactive objects **308** and smaller interactive objects may have similar shapes, shapes that differ within and between themselves and be provided having similar or varied coloration, for example.

(75) This fourth exemplary bubble-making station includes a system **300** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media

include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(76) A fifth exemplary bubble-making station includes system **400** that comprises a bubble sheet making apparatus, methods of using and/or interacting with the bubble sheet making apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The bubble sheet making apparatus comprises a pulley system comprising one or more pulleys to create a large generally rectangular bubble sheet or screen that is manipulatable by at least one user. In use, a user pulls upon a rope to raise a collapsible frame up and from of a reservoir of a bubble solution to create a large bubble sheet. One or more users can subsequently create one or more bubbles from the large bubble sheet by simply blowing onto the large bubble sheet by using air passing over their lips, by using devices that blow air from the device/apparatus or by using bubble-making wands or tubes, for example.

(77) Turning now to FIG. 4, system **400** is shown comprising an exemplary bubble sheet making apparatus **410**. Bubble sheet making apparatus **410** comprises a frame system **420**, a lift system **430** and a bar system **440**. Frame system **420** comprises a bottom trough **422**, from which extend one or more vertical support members **424** and a top support structure **426** which is horizontally orientated. Bottom trough **422** generally comprises one or more sides **412**, a bottom **414** and a top opening **416** opposite bottom **414**, top opening **416** being defined by the perimeter formed by one or more sides **412**. Bottom trough **422** may be curved, defining a circle or an oval, or any cuboidal shape with square and rectangular shapes being preferred, the cuboidal shape having sharp (right-angled) or curved corners. In some embodiments, bottom trough **422** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, bottom trough **422** is generally cuboidal in shape. In some embodiments, bottom trough **422** is cuboidal and can have a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. The height of bottom trough **422** can be 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet. In addition, the perimeter formed by one or more sides **412** and top opening **416** may be curved, defining a circle or an oval, or any closed polygonal shape with triangle, square, rectangular, and pentagonal shapes. The resulting interior space of bottom trough **422** located below the plain of top opening **416** defines a reservoir **418**. The shape of reservoir **418** is defined by the internal surface of each of the one or more sides **412** of bottom trough **422** and bottom **414**. Each of the one or more vertical support members **424** span the space between bottom trough **422** and top support structure **426**, as exemplified in FIG. 4A as **424a**, **424b**, **424c** and **424d**,

(78) As shown in FIG. 4, one or more vertical support members **424** and top support structure **426** may be attached to bottom trough **422**. Alternatively, one or more vertical support members **424** and top support structure **426** may be free-standing from bottom trough **422**. When attached bottom trough **422** one or more vertical support members **424** may be an integral part of bottom trough **422** and be considered one component, or may be a separate component that physically secured to bottom trough **422**. For example, a first end of one or more one or more vertical support members **424** of frame system **420** may be attached to attached to bottom trough **422** as an integral part of bottom trough **422** or physically secured using mechanical fasteners, for example, nuts and bolts, screws, rivets or other fasteners known in the art, or through welding, or adhesives, or any combination of the preceding known in the art. One or more vertical support members **424** are generally 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet in height.

(79) As shown in FIG. 4, one or more vertical support members **424** comprise a first end that may be attached to bottom trough **422** and a second end that may be attached to top support structure

426. One or more vertical support members **424** may be attached to the perimeter of bottom trough **422** on the exterior. Alternatively, one or more vertical support members **424** may be placed in openings formed in bottom trough **422**. One or more vertical support members **424** may be placed equally spaced apart on bottom trough **422**. For example, if bottom trough **422** has a square cross section, one or more vertical support members **424** may be placed at or near each of the corners of the square. Alternatively, if bottom trough **422** were to be provided having an arced or curved perimeter, one or more vertical support members **424** may be placed at equal intervals along the arc or curved perimeter of bottom trough **422**. In certain embodiments, there may be four vertical support members **424**, or as few as two vertical support members **424**, and as many as eight vertical support members **424**. On a second end, each of one or more vertical support members **424** may connect to top support structure **426** (for one particular configuration, see FIG. 4). One or more vertical support members **424** are spaced apart to accommodate bar system **440** as discussed below to the interior of a perimeter defined by one or more vertical support members **424**.

(80) One or more vertical support members **424** may be of any cross-sectional shape so long as one or more vertical support members **424** have the structural integrity to support the weight of the structure above including top support structure **426**, lift system **430** and a bar system **440** in a manner that ensures bubble sheet making apparatus **410** operates correctly. For example, one or more vertical support members **424** may have a polygon transverse cross-sectional shape like a square, rectangle, or pentagonal shape or a curved transverse cross-sectional shape like a circle or oval.

(81) Bubble sheet making apparatus **410** further include a lift system **430**. As shown in FIG. 4, lift system **430** comprising one or more pulleys **432** and one or more lifting cords **434** running therethrough. Pulley system **430** is affixed to top support structure **426**. Spools may be used in place of either or both of one or more pulleys **432**. Spools may offer certain advantages in large systems with one or more lifting cords **434** and bar system **440** which weigh enough to require a user to have some further mechanical advantage to lift bar system **440** and the required portion of the attached one or more lifting cords **434**.

(82) One or more lifting cords **434** comprise a first end and a second end. A first end of each of one or more lifting cords **434** may be connected to bar system **440**. Each of the one or more lifting cords **434** may be attached at each end of a top bar of bar system **440**. Each of one or more lifting cords **434** may then run from the connection with bar system **440** through one or more pulleys **432** and may then be connected at a second end or may hang freely on the other side of the one or more pulleys **432** or drape over arm **415**, if so provided. In one embodiment, as exemplified in FIG. 4, lifting cords **434a** and **434b** are attached to top bar **442** of bar system **440** and are run through pulleys **432a**, **432b** and **432c**.

(83) The second ends of one or more lifting cords **434** may be provide a grasping portion, which may be simply a knot or a sleeve or handle, for example, such grasping portion optionally being weighted to keep tension one or more lifting cords **434** making them taut. This accomplishes several things. First, it makes it easier for a user to grasp one or more lifting cords **434**, as will be discussed in further detail below. Second, the connection of one or more lifting cords **434** at their second end prevents one or more lifting cords **434** from being pulled back out through one or more pulleys **432**. This routing of one or more lifting cords **434** offers further advantages. In addition, it keeps one or more lifting cords **434** routed up higher, and substantially horizontally, away from bar system **440** when bubble sheet making apparatus **410** is in operation. Furthermore, the routing from one or more pulleys **432** both brings one or more lifting cords **434** into closer proximity for ease of grasping by a user, and moves the second end of one or more lifting cords **434** substantially to the perimeter of bubble sheet making apparatus **410**. As will be discussed in further detail below, this routing prevents one or more lifting cords **434** from interfering with the creation of a bubble sheet **448**.

(84) Bubble sheet making apparatus **410** further includes a bar system **440**. Referring still to FIG.

4, bar system **440** comprises a top bar **442**, one or more depending cords **444**, and optionally a bottom bar **446**. Bar system **440** is collapsible due to the flexible or collapsible nature of one or more depending cords **444**. Top bar **442** is wrapped along its length in absorbent material **450** used to retain bubble solution **4**. As one example, absorbent material **450** can be made of the same material as lifting cords **434** and/or one or more depending cords **444**. For example, absorbent material **450**, lifting cords **434** and/or depending cords **444** can be made from fibers, such as hemp, cotton, polyester or blends thereof or of a differing material (such as athletic tape, having cotton fibers with polymer elastic strands woven throughout, for example).

(85) One or more depending cords **444** can be a single integral component with absorbent material **450** or can be a separate and distinct component. When a single integral component, absorbent material **450** is secured to top bar **442** by, for example wrapping around top bar **442**, in a manner where each end portion of absorbent material **450** becomes one or more depending cords **444** comprising a free end. This embodiment is exemplified in FIG. 4, where a material is wrapped around top bar **442** to become absorbent material **450** and each end portion of this material becomes depending cords **444a** and **444b**. Alternatively, when a separate distinct component, one or more depending cords **444** comprise a first end and a free end, where the first end is secured to top bar **442**.

(86) The free end of each of one or more depending cords **444** can simply hang freely down from top bar **442**, and in such configuration may be optionally weighted to keep tension on the one or more depending cords **444**, making them taut. Alternatively, the free end of one or more depending cords **444** when in a single integral component configuration (shown in dashed lines in FIG. 4) or the free end of one or more depending cords **444** when in a separate distinct component configuration can be secured to bottom bar **446**. One or more depending cords **444** is composed of material that can collapse when supported but extend due to the force of gravity. For example, one or more depending cords **444** can be made from fibers, such as hemp, cotton, polyester or blends thereof.

(87) In operation, bubble sheet making apparatus **410** has a rest position and a bubble sheet position. Bubble sheet making apparatus **410** begins in a rest position where bar system **440** is completely submerged in bubble solution **4** contained in reservoir **418** of bottom trough **422** thereby coating bar system **440** in bubble solution **4**. As described above, the one or more lifting cords **434** of lift system **430** run from bar system **440** through one or more pulleys **432** and then the free, second end portion hangs down from one or more pulleys **432**. The second end portion of one or more lifting cords **434** hangs at a height between one and five feet above the ground with a range of between two and four feet being preferred.

(88) To activate bubble sheet making apparatus **410** from the rest position to a bubble sheet position shown in FIGS. 4 & 10A, a user may then grasp the second ends of one or more lifting cords **434** and pull on one or more lifting cords **434**. As the user pulls on one or more lifting cords **434**, one or more lifting cords **434** are drawn through one or more pulleys **432**, lifting bar system **440** vertically upward from out of bottom trough **422**. As top bar **442** of bar system **440** is lifted vertically upward out of bubble solution **4** by lift system **430**, gravity causes bar system **440** to expand as one or more depending cords **444** uncoil until extended. When bar system **440** is completely lifted out of bubble solution **4** it is in the bubble sheet position. When bar system **440** is in its expanded or uncollapsed configuration it forms a framework comprising the top bar **442**, the one or more depending cords **444** and, if present the bottom bar **446** with bubble solution **4** contained within this framework creating a large bubble sheet **448**. In some embodiments, bar system **440** comprises top bar **442**, two depending cords **444** and bottom bar **446** and generally forms a rectangular shape causing bubble solution **4** contained within this framework to creating a large rectangular bubble sheet **448**. In the bubble sheet position, free end of one or more depending cords **444** when in a single integral component configuration or bottom bar **446** when in a separate distinct component configuration are substantially or completely removed from bubble solution **4**.

contained in bottom trough **422**. At this point bar system **440** is in its uncollapsed, generally rectangular shape. In the bubble sheet position, a user can observe bubble sheet **448** and/or create new bubbles out of bubble sheet **448** by passing air via lungs, a tube or straw, a device that provides an air stream, blower, or smoke-like fog as disclosed in system **1000** (see FIG. **10A**). Alternative geometries of bubble sheet **448**, such as a triangular, square or circular bubble sheet **448** may be attained by alternatively providing an appropriate/corresponding geometry of bar system **440**. In one example, a collapsible ladder-like geometry may be provided.

(89) This fifth exemplary bubble-making station includes a system **400** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(90) For example, an attendant/guide can proceed to have a user or users create a large bubble sheet and have them test its properties. The user(s) will pull up the bubble screen and the attendant/guide can ask user(s) to blow gently and see what happens. The question of “what happens when they blow hard?” can be put to the users. The attendant/guide can explain that a thin bubble film forms from the polar properties of the bubble solution on the top bar of the bar system and then travels down the cords keeping the screen intact. When a user or users blow air through the bubble sheet, they test how strong the soap molecules are to stick together (aka affinity). If the air stream is soft enough then molecules have time to adjust and retain sufficient attraction to each other, maintaining the bubble sheet, but when a user or users blow too hard, the quick force pulls the molecules apart, popping the film/sheet and/or forming a bubble or bubbles therefrom.

(91) Further, an attendant/guide can ask questions relating to the colors and light interplay with the flat bubble solution sheet. For example, an attendant/guide can ask what happens to light that comes in and goes through the bubble sheet? The attendant/guide can then explain that bubble solution will absorb and change some of the light (aka refractive index,) based on what is in bubble solution, to different colors of lights (aka wavelengths) so they bend a bit different after they leave the bubble sheet. That's why if the user(s) look really hard, the user(s) can almost see a rainbow on this film.

(92) A sixth exemplary bubble-making station includes system **500** that comprises a bubble making apparatus, methods of using and/or interacting with the bubble making apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The bubble making apparatus creates bubbles of the same or of various sizes that are projected out from and in front of the apparatus and float at varying heights and an activity area. The projecting stream of bubbles allows one or more users to pop the bubbles with various objects, for example, projectiles such as a ball, beanbag, a disc, an arrow from a bow, water from a water-projecting gun; a slingshot, or any other a gliding toy or sporting item that can be propelled or provide an airborne object/projectile to hit a bubble may be used. The apparatus can create bubbles at varying heights to allow users of different heights to pop the bubbles at different levels from the ground.

(93) The object utilized to pop the resultant bubbles from the apparatus can be anything from a ball to water from a water gun. Any object that can be used to pop a bubble can be utilized. Various games may be designed having various goals of the game. One possibility is to pop as many bubbles as possible using whatever object is available for popping within a specific amount of time. Another goal can be to place targets, such as a bullseye along a wall a user **2** can try to pop a bubble while at the same time aiming to hit the wall mounted target. In particular examples and

where the target is a bullseye, the user may endeavor to utilize the projectile to pop a bubble or bubbles and also hit the bullseye closest to its center to score points, the points corresponding to the rings of the bullseye (e.g. the closer the ring to the bullseye the higher the points). One possibility is to score baskets along the wall, where the participant can try to pop both a bubble and make a basket utilizing the same projectile in the same throw/shot.

(94) Referring to FIG. 5A, system **500** comprises a bubble making apparatus **510** to produce a stream of bubbles and an activity area **511**. As part of system **500**, an air blower **512**, such as, e.g., a fan, may be provided to augment an air stream producing system **540** and/or to push air to ventilation unit **560**. Activity area **511** comprises comprising at least one receptacle and/or one or more targets. The dimensions of activity area **511** are generally of a size of a room and provide enough space for so that a user can comfortably through projectiles at one or more targets or at the stream of bubbles being produced by bubble making apparatus **510**. In particular embodiments, activity area **511** can be 4×15 feet area, 4×20 feet area, 4×25 feet area, 4×30 feet area, 6×15 feet area, 6×20 feet area, 6×25 feet area, 6×30 feet area, 8×15 feet area, 8×20 feet area, 8×25 feet area, 8×30 feet area, 10×15 feet area, 10×20 feet area, 10×25 feet area, or 10×30 feet area.

(95) User **2** is placed in activity area **511** and positioned at a distance from bubble making apparatus **510** but within proximity of at least one receptacle **502** which may hold projectiles/toys that provide projectiles **504**. Projectiles **504** include, without limitation a bean bag, a ball, a spear and an arrow or any combination thereof. One or more targets **506** can be practically anything that can be targeted by user **2**, such as a bullseye or a balloon, for example. In this example, target **506** is shown having a basketball theme, here comprising a basket **509** and a backboard **508**. In particular configurations, target **506** or plurality thereof can be provided as a suspended target to be hit with a projectile, alone or in addition to wall mounted target(s). Apparatus **510** is activated and produces a stream of bubbles, which may or may not be directed by an air stream provided by blower **512**, here in this example shown as a fan positioned at floor level. User **2** then proceeds to endeavor to hit the bubbles and target **506**, reaching into receptacle **502** for projectiles. Various time limits, limited number of projectiles/chances to throw etc. . . . , scores can be noted and recorded to provide for some method of scoring/ranking.

(96) Turning to FIGS. 5B-5D, bubble making apparatus **510** comprises a support structure **515** and one or more bubble producing systems **520**. Support structure **515** generally comprises one or more sides **516**, a bottom **517**, and a top **518**, with one of the one or more sides optionally including a front **516f**. Support structure **515** may be curved, defining a circle or an oval, or any cuboidal shape with square and rectangular shapes being preferred, the cuboidal shape having sharp (right-angled) or curved corners. In some embodiments, support structure **515** is circular or oval in shape and have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, support structure **515** is generally cuboidal in shape. In some embodiments, support structure **515** is cuboidal in shape and can have a width of 1 to 6 feet, 2 to 6 feet, 3 to 6 feet, 4 to 6 feet, 5 to 6 feet, 1 to 5 feet, 2 to 5 feet, 3 to 5 feet, 4 to 5 feet, 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 1 to 6 feet, 2 to 6 feet, 3 to 6 feet, 4 to 6 feet, 5 to 6 feet, 1 to 5 feet, 2 to 5 feet, 3 to 5 feet, 4 to 5 feet, 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet, and a height of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet.

(97) As best seen in FIG. 5D, a cutaway view of FIG. 5B at line 5D, support structure **515** also comprises a power system **550**, and a ventilation unit **560**. Power system **550** comprises a power supply **551** that provides electricity and one or more electrical wires **552**. One or more electrical wires **552** connect power supply **551** to one or more motors **536** of a motorized bubble producing tool system **530** and one or more fans **542** of an air stream producing system **540**.

(98) Ventilation unit **560** comprising bottom vent **519** and a flow area **562** by which air may flow to an internal portion **564** of support structure **515** of bubble making apparatus **510**. Such ventilation

helps keep bubble making apparatus **510** cool from the heat generated from one or more motors **536** of a motorized bubble producing tool system **530** and one or more fans **542** of an air stream producing system **540**. In addition, this ventilation supplies air to one or more fans **542** of an air stream producing system **540**, thereby facilitating the expulsion of air in a generally horizontal direction through one or more vents **544** and outward from the front of bubble making apparatus **510**. In an alternative embodiment, conduit can be used instead of internal portion **564** of support structure **515** to provide more directed air flow to one or more motors **536** of a motorized bubble producing tool system **530** and one or more fans **542** of an air stream producing system **540**.

(99) As best seen in FIG. 5D, a cutaway view of FIG. 5B at line 5D, one or more bubble producing systems **520** each comprise a motorized bubble producing tool system **530** and an air stream producing system **540**. Turning to the upper portion of FIG. 5D, each motorized bubble producing tool system **530** comprises a reservoir **522** containing bubble solution **4**, one or more bubble producing tools **532** attached to a central hub **534** with central hub **534** operably linked to a motor **536**. Power is provided to motor **536** from power supply **550**. In one embodiment, motor **536** can vary in speed to adjust the rotational velocity of central hub **534** and how fast bubbles can be created by bubble making apparatus **510**. Still referring to FIG. 5D, air stream producing system **540** comprises a motorized blower **542**, such as a fan and a vent **544**. Vent **544** may be an open or porous aperture. Power is provided to motorized blower **542** from power supply **550**. In one embodiment, motorized blower **542** can vary in speed to adjust the distance bubbles can be pushed away from bubble making apparatus **510**.

(100) In operation, motorized blower **542** continuously expels air in a generally horizontal direction through vent **544** and outward from the front of bubble making apparatus **510**. At the same time, motor **536** continuously spins central hub **534** causing each of the one or more bubble producing tools **532** to become submerged into bubble solution **4** contained in reservoir **522**. This continuous spinning of central hub **534** then lifts each of the one or more bubble producing tools **532** from bubble solution **4** and then causes each of the one or more bubble producing tools **532** to pass by vent **544**. More particularly, air being expelled from vent **544** by air stream producing system **540** causes bubbles to be formed from bubble solution **4** contained in each of the one or more bubble producing tools **532** and propelling such formed bubbles away from bubble making apparatus **510**. Each of the one or more bubble producing tools **532** continues to rotate past air stream being expelled through vent **544** by air stream producing system **540** and become submerged again into bubble solution **4** contained in reservoir **522**, where the rotational cycle repeats to thereby provide a continuous stream of bubbles.

(101) This sixth exemplary bubble-making station includes a system **500** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(102) A seventh exemplary bubble-making station includes system **600** that comprises a bubble tower making apparatus, methods of using and/or interacting with the bubble tower making apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The bubble tower making apparatus surround a person on all sides with an open-ended bubble tube or tower made of a bubble solution.

(103) Referring to FIGS. 6A-6H, exemplary embodiments of various aspects of system **600** and bubble tower making apparatus are shown. Generally, a bubble wall apparatus comprises a base system, a support frame system, and a lift system. A base system disclosed herein comprises a

platform on which a participant stands, and a fluid trough surrounding the platform and designed to contain a bubble solution. A support frame system comprises a one or more vertical support members connected to a base system, a top frame connected to the vertical support members and including one or more cross members. A lift system is mounted onto a support frame system, a lift system comprising one or more lifting pulleys, one or more control pulleys and one or more cables, each of the one or more cables capable of being connected on a first end portion to a bubble hoop, individually passing through one or more lifting pulleys and one or more control pulleys, and capable of being connected on a second end portion to others of the one or more cables or be or may hang freely. In operation, a bubble hoop may be moved from a rest position in which a bubble hoop is located in a fluid trough to a bubble wall position in which a bubble hoop is raised some height above a fluid trough with a bubble wall formed between a fluid trough and a bubble hoop.

(104) In one particular configuration and as shown in FIG. 6A, a bubble tower making apparatus **610** includes a base system **612** that is connected to a support frame system **614** that supports a lift system **615**. While base system **612** is shown here to be connected to support frame system **614**, alternative configurations may have base system **612** and support frame system **614** not connected, e.g., support frame system **614** being free standing and a separate from base system **612**.

(105) Referring to FIG. 6A, base system **612** comprises a platform **628** and a fluid trough **630**. Fluid trough **630** surrounds platform **628** and in turn may be surrounded by a base surround **632**. Platform **628** is the innermost component of base system **612** and may include a single planar surface. Platform **628** may be large enough for substantially any person to stand on, with a perimeter of platform **628** spaced apart from any portion of the person. The planar surface may include a non-skid material which prevents the planar surface from becoming slippery if some bubble solution **4** spills onto the planar surface. Alternatively, platform **628** may include more than a single planar surface. For example, as shown in FIGS. 6G & 6H, platform **628** may include a first surface, which may be planar and a second planar surface, one or both of which may be non-horizontal and come together at a central portion and define an angle and slope to cause any bubble solution **4** that falls thereon to run off of platform **628** and into fluid trough **630**. The slope/angle of inclination of one or both planar surfaces of platform **628** from horizontal can be an amount that does not hinder standing of a user on platform **628**, yet sufficient enough to bias flow of any bubble solution **4** that falls thereon back towards fluid trough **630**. An exemplary useful angle can be from one to ten degrees, from two to five degrees being preferred.

(106) Referring to FIG. 6A, and also FIGS. 6E-6G fluid trough **630** of base system **612** surrounds platform **628** and defines its outer perimeter. Fluid trough **630** may include a first substantially vertical wall, and a second substantially vertical wall spaced apart from the first, with a bottom surface extending between the first wall and the second wall. The bottom surface may be substantially horizontal and therefor substantially perpendicular to the first wall and the second wall. Alternatively, the bottom surface may be curved. The curve may be convex, that is, the curve may extend downwardly from opposite edges. The opposite edges being where the bottom surface connects to a bottom edge of the first wall and to a bottom edge of the second wall, respectively. Fluid trough **630** may be filled manually by pouring bubble solution **4** into fluid trough **630**. Alternatively, fluid trough **630** may be filled through an opening in fluid trough **630** which is fluidly connected to a pump, which may in turn be connected to a bubble fluid reservoir (not shown). The reservoir may be located in base system **612** or external to base system **612**. Base system **612** may further include a valve which opens automatically when the pump is running and closes automatically when the pump stops running. Alternatively, the valve may be manually operated. The valve, pump, and reservoir may be connected to each other and fluid trough **630** by tubing, piping or other means known in the art. A top edge of the first wall may connect to platform **628**.

(107) Still referring to FIGS. 6A & 6E-6G, base surround **632** is exterior to fluid trough **630** and the outermost edge of base surround **632** may define a perimeter of base system **612**. Base surround

632 may include a top surface which extends outwardly from the top edge of the second wall of fluid trough **630**. The top surface of base surround **632** may be substantially horizontal.

Alternatively, as shown in FIGS. **6E** & **6F**, the top surface base surround **632** may taper from an outermost edge to innermost edge, so that bubble solution **4** present on the top surface will flow into fluid trough **630**. Base surround **632** may further include a perimeter wall. The perimeter wall may be substantially vertical. Alternatively, the perimeter wall base surround **632** may have a taper so that a bottom edge is exterior of a top edge. This gives base system **612** a larger footprint and greater stability. The perimeter wall may define a perimeter of base system **612**.

(108) As shown in FIGS. **6A**, **6C** & **6G**, base system **612** and its component platform **628**, fluid trough **630**, and base surround **632** may all be in a square or rectangular shape and proportionate in size to one another. As shown in FIG. **6E**, the outer perimeter of platform **628**, the outside edge of fluid trough **630** and the outermost edge of base surround **632** of base system **612** are rectangular in shape with curved corners and are proportionate in size to each other. However, the outer perimeter of platform **628**, fluid trough **630** and base surround **632** may vary in shape. For example, the outer perimeter of platform **628** may be curved, defining a circle or an oval, or any closed polygonal shape, with triangle, square, rectangular, and pentagonal shapes being preferred. Similarly, the outside edge of fluid trough **630** may be curved, defining a circle or an oval, or any closed polygonal shape and may have the same shape as the outer perimeter of platform **628**, or may have a different shape. Likewise, the outermost edge of base surround **632** may be curved, defining a circle or an oval, or any closed polygonal shape and may have the same shape as the outer perimeter of platform **628**, and/or the outside edge of fluid trough **630**, or the outermost edge of base surround **632** may have a different shape from either or both the outer perimeter of platform **628**, and/or the outside edge of fluid trough **630**. For example, the perimeter of base **612** may define a rectangle, the outside edge of fluid trough **630** a circle, and the outer perimeter of platform **628** a square. So long as the structural integrity and functionality of the bubble tower making apparatus are sound, any shape of the outer perimeter of platform **628**, the outside edge of fluid trough **630** and the outermost edge of base surround **632** of base system **612** are contemplated.

(109) In some embodiments, the perimeter of base **612** can be 2 to 10 feet in width, 2 to 10 feet in length and 2 inches to 12 inches in height. In some embodiments, the perimeter of base **612** can be 3 to 9 feet in width, 3 to 9 feet in length and 3 inches to 10 inches in height. In some embodiments, the perimeter of base **612** can be 4 to 8 feet in width, 4 to 8 feet in length and 4 inches to 8 inches in height.

(110) In some embodiments, the perimeter of base **612** can be 1 to 6 feet in radius and 2 inches to 12 inches in height. In some embodiments, the perimeter of base **612** can be 2 to 5 in radius and 3 inches to 10 inches in height. In some embodiments, the perimeter of base **612** can be 2 to 4 feet in radius and 4 inches to 8 inches in height.

(111) In some embodiments, the perimeter of platform **628** can be 2 to 10 feet in width, 2 to 10 feet in length and 2 inches to 12 inches in height. In some embodiments, the perimeter of platform **628** can be 3 to 9 feet in width, 3 to 9 feet in length and 3 inches to 10 inches in height. In some embodiments, the perimeter of platform **628** can be 4 to 8 feet in width, 4 to 8 feet in length and 4 inches to 8 inches in height.

(112) In some embodiments, the perimeter of platform **628** can be 1 to 6 feet in radius and 2 inches to 12 inches in height. In some embodiments, the perimeter of platform **628** can be 2 to 5 in radius and 3 inches to 10 inches in height. In some embodiments, the perimeter of platform **628** can be 2 to 4 feet in radius and 4 inches to 8 inches in height.

(113) In some embodiments, the perimeter of fluid trough **630** can be 2 to 10 feet in width, 2 to 10 feet in length and 2 inches to 12 inches in height. In some embodiments, the perimeter of fluid trough **630** can be 3 to 9 feet in width, 3 to 9 feet in length and 3 inches to 10 inches in height. In some embodiments, the perimeter of fluid trough **630** can be 4 to 8 feet in width, 4 to 8 feet in length and 4 inches to 8 inches in height.

(114) In some embodiments, the perimeter of fluid trough **630** can be 1 to 6 feet in radius and 2 inches to 12 inches in height. In some embodiments, the perimeter of fluid trough **630** can be 2 to 5 in radius and 3 inches to 10 inches in height. In some embodiments, the perimeter of fluid trough **630** can be 2 to 4 feet in in radius and 4 inches to 8 inches in height.

(115) Base system **612** may be made of a material which is resistant to breakdown by fluid, specifically bubble solution **4**, and has the rigidity to support the weight of a person up to 600 pounds and the weight of the additional structure of bubble tower making apparatus **610** which is placed thereon. Different polymers, fiberglass, and rigid plastics are contemplated, as are lightweight metals, for example, aluminum. The base may be formed from a single piece of material, or pieces of the same or different materials integrated to form base system **612**. The base may be formed by stamping or molding, for example, or painted wood.

(116) Bubble tower making apparatus **610** further includes a support frame system **614**. As shown in FIGS. **6A** & **6B**, support frame system **614** comprises one or more vertical support members **619**, and a top frame **616** comprising of one or more perimeter frame members **617** and one or more cross members **618**. Each of the one or more vertical support members **619** span the space between base system **612** and top frame **616**. Support frame system **614** may be attached to base system **612** or free-standing from base system **612**. When attached to base system **612** support frame system **614** may be an integral part of base system **612** and be considered one component, or may be a separate component that physically secured to base system **612**. For example, a first end of one or more vertical support members **619** of support frame system **614** may be attached to attached to base system **612** as an integral part of base system **612** or physically secured using mechanical fasteners, for example, nuts and bolts, screws, rivets or other fasteners known in the art, or through welding, or adhesives, or any combination of the preceding known in the art.

(117) As shown in FIGS. **6A** & **6B**, one or more vertical support members **619** comprise a first end that may be attached to base system **612** and a second end that may be attached to top frame **616**. One or more vertical support members **619** may be attached to the perimeter of base system **612** on the exterior. Alternatively, one or more vertical support members **619** may be placed in openings formed in base system **612**. One or more vertical support members **619** may be placed equally spaced apart on base system **612**. For example, if base **612** has a square cross section, one or more vertical support members **619** may be placed at or near each of the corners of the square. Alternatively, if base **612** were to be provided having a circular perimeter, one or more vertical support members **619** may be placed at equal interval arcs. For example, if there are four vertical support members **619**, each vertical member **619** may be placed at each 90-degree arc along a 360-degree perimeter. In certain embodiments, there may be four vertical support members **619**, or as few as two vertical support members **619**, and as many as eight vertical support members **619**. On a second end, each of one or more vertical support members **619** may connect to a top frame **616** (for one particular configuration, see FIG. **6B**). One or more vertical support members **619** are spaced apart to accommodate a bubble forming device **620** to the interior of a perimeter defined by one or more vertical support members **619**.

(118) One or more vertical support members **619** may be of any cross-sectional shape so long as one or more vertical support members **619** have the structural integrity to support the weight of the structure above including top frame **616** and lift system **615** in a manner that ensures bubble tower making apparatus **610** operates correctly. For example, one or more vertical support members **619** may have a polygon transverse cross-sectional shape like a square, rectangle, or pentagonal shape or a curved transverse cross-sectional shape like a circle or oval. One or more vertical support members **619** are generally 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet in height.

(119) Referring to FIGS. **6A** & **6B**, top frame **616** comprises one or more perimeter frame members **617** and one or more cross members **618**. As discussed above, one or more vertical support members **619** connect to top frame **616**. Top frame **616** may connect to one or more vertical

support members **619** directly either as an integral part of top frame **616** or via mechanical fasteners, for example, nuts and bolts, screws or rivets, or other mechanical fasteners known in the art. Alternatively, top frame **616** may connect to one or more vertical support members **619** by welding or adhesives or other methods known in the art. Top frame **616** and one or more vertical support members **619** may also connect indirectly through the use of hangers or adapters fitted to the second end of each of one or more vertical support members **619**. The hangers or adapters may include mechanical fasteners to hold one or more vertical support members **619** and one or more perimeter frame members **617** in place within the hangar or adapter.

(120) Referring to FIGS. **6A** & **6B**, top frame **616** supports lift system **615**. For example, one or more perimeter frame members **617** and/or one or more cross members **618** may support one or more lifting pulleys **624**. One or more lifting pulleys **624** may be connected to one or more perimeter frame members **617** and/or one or more cross members **618** via mechanical fasteners, for example, nuts and bolts, screws or rivets, or other mechanical fasteners known in the art.

Alternatively, one or more lifting pulleys **624** may connect to one or more perimeter frame members **617** and/or one or more cross members **618** by welding or adhesives or other methods known in the art. One or more perimeter frame members **617** and/or one or more cross members **618** may further support one or more control pulleys **626**. As shown in FIG. **6A**, one or more control pulleys **626**, and may be connected to one or more perimeter frame members **617** and/or one or more cross members **618** via mechanical fasteners, for example, nuts and bolts, screws or rivets, or other mechanical fasteners known in the art. Alternatively, one or more control pulleys **626** may connect to one or more perimeter frame members **617** and/or one or more cross members **618** by welding or adhesives or other methods known in the art.

(121) Bubble tower making apparatus **610** further include a lift system **615**. Lift system **615** comprises one or more lifting pulleys **624**, one or more control pulleys **626**, one or more cables **622** running therethrough and bubble forming device **620**. One or more cables **622** comprise a first end and a second end. A first end of each of one or more cables **622** may be connected to bubble forming device **620**. Each of one or more cables **622** may run from the connection with bubble forming device **620** through one or more lifting pulleys **624**. One or more cables **622** may then run through one or more control pulleys **626**. One or more cables **622** may then be connected at a second end or may hang freely or draped over an arm **629**, if so provided. One or more cables **622** may be attached to bubble forming device **620** at each of the corners of bubble forming device **620**. Each of one or more cables **622** may run through one or more lifting pulleys **624**, a total of four cables **622** and four lifting pulleys **624** as shown in an exemplary embodiment of FIG. **6A** Two cables **622** may then run through a common first control pulley **626a**. The remaining two cables **622** may run through a common second control pulley **626b**. One or more cables **622** may hang freely on the other side of the first control pulley **626a** and second control pulley **626b** or drape over arm **629**, if so provided.

(122) Referring still to FIG. **6A**, bubble forming device **620** may have any suitable geometry that generally comports with the geometry of fluid trough **630** to fit therein. For example, as shown in FIG. **6A** bubble tower making apparatus **610** comprises a square bubble forming device **620** that comports with the substantially square shape of fluid trough **630** to fit therein. Bubble forming device **620** can be wrapped along its length in absorbent material, which is used to retain bubble solution **4**. As one example, absorbent material can be made of the same material as one or more cables **622** (for example fibers, such as hemp, cotton, polyester or blends thereof) or of a differing material (such as athletic tape, having cotton fibers with polymer elastic strands woven throughout, for example OTHER MATERIALS?).

(123) The second ends of one or more cables **622** may be provide a grasping portion **631**, which may be simply a knot or a sleeve or handle, for example, such grasping portion **631** optionally being weighted to keep tension one or more cables **622** making them taut. This accomplishes several things. First, it makes it easier for a user to grasp one or more cables **622**, as will be

discussed in further detail below. Second, the connection of one or more cables **622** at their second end prevents one or more cables **622** from being pulled back out through one or more control pulleys **626** or one or more lifting pulleys **624**. This routing of one or more cables **622** offers further advantages. In addition, it keeps one or more cables **622** routed up higher, and substantially horizontally, away from bubble forming device **620** when bubble tower making apparatus **610** is in operation. Furthermore, the routing from one or more lifting pulleys **624** to one or more control pulleys **626** both brings one or more cables **622** into closer proximity for ease of grasping by a user, and moves the second end of one or more cables **622** substantially to the perimeter of bubble tower making apparatus **610**. As will be discussed in further detail below, this routing prevents one or more cables **622** from interfering with the creation of a bubble tower **605**.

(124) Spools may be used in place of either or both of one or more lifting pulleys **624** and one or more control pulleys **626**. Spools may offer certain advantages in large systems with one or more cables **622** and bubble forming device **620** which weigh enough to require a user to have some further mechanical advantage to lift bubble forming device **620** and the required portion of the attached one or more cables **622**.

(125) Referring to FIGS. **6A** & **6B**, lighting or other effects may also be mounted to support frame system **614**, e.g., to one or more vertical support members **619** and/or one or more perimeter members **617** and/or one or more cross members **618**. The lighting may create an effect either through refraction or diffusion of the light on or through bubble tower **605**, the formation of which is discussed in detail below, when bubble tower making apparatus **610** is in operation. Thus, lights **670** may be mounted in order that the emitted light intersects bubble tower **605**, either directly or indirectly. Lights **670** may be mounted to support frame system **614** via mechanical fasteners, for example, nuts and bolts, screws or rivets, or other mechanical fasteners known in the art. Alternatively, lights **670** may connect to support frame system **614** by welding or adhesives or other methods known in the art.

(126) In operation, bubble tower making apparatus **610** has a rest position and a bubble wall position. Bubble tower making apparatus **610** begins in a rest position where bubble forming device **620** is immersed in bubble solution **4** contained in fluid trough **630** thereby coating bubble forming device **620** in bubble solution **4**. As described above, the one or more cables **622** run from bubble forming device **620** through one or more lifting pulleys **624** and then through one or more control pulleys **626** and then the free, second end portion hangs down from one or more control pulleys **626**. The second end portion of one or more cables **622** hangs at a height between one and five feet above the ground with a range of between two and four feet being preferred. When bubble tower making apparatus **610** is at rest, a person may stand on platform **628**.

(127) To activate bubble tower making apparatus **610** from the rest position to a bubble wall position shown in FIG. **6A**, a user may then grasp the second ends of one or more cables **622**. The user may then pull on one or more cables **622**. As the user pulls on one or more cables **622**, one or more cables **622** are drawn through one or more control pulleys **626** and one or more lifting pulleys **624**, lifting bubble forming device **620** vertically upward from out of fluid trough **630**. As bubble forming device **620** moves vertically upward, bubble solution **4** is drawn between bubble forming device **620** and bubble trough **630**. Bubble solution **4** drawn between bubble forming device **620** and bubble trough **630** creates a bubble tower **605** that encases the person standing on platform **628**. The vertical shape of bubble tower **605** is a tube with a single continuous wall, and a first end anchored on bubble forming device **620** and a second end anchored in fluid trough **630**. The horizontal shape of bubble tower **605** is one that conforms to the shape of bubble forming device **620**. The height to which bubble tower **605** may be drawn is at the discretion of user. The height of bubble tower **605** may be in the range of a fraction of an inch to the height of one or more lifting pulleys **624**. From the bubble wall position, user may return bubble tower making apparatus **610** to the rest position by releasing tension on one or more cables **622**, allowing the force of gravity to act against the pulling of the user, and returning bubble forming device **620** to fluid trough **630**. As

bubble forming device **620** returns vertically downwardly to fluid trough **630**, one or more cables **622** are drawn back through one or more control pulleys **626** and one or more lifting pulleys **624** in the opposite direction in which they were withdrawn, until bubble tower making apparatus **610** returns to the rest position.

(128) This seventh exemplary bubble-making station includes a system **600** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(129) For example, after enclosing/surrounding a user(s) in bubble tower, an attendant/guide can ask “What happens right after the bubble pops? Can the user(s) see some particles of ‘broken’ bubble falling to the floor? What do they think that is?” The attendant/guide can go over what makes a bubble (It's usually air trapped inside soap and water molecules). Here, these sides are not a typical spherical bubble so how do user(s) think it works? The attendant/guide can explain to the user(s) that as long as the bubble solution has clearly defined surfaces to attach to, the same polar properties apply. There is still a water, soap, water layer, but instead of attracting to each other like in a standard spherical bubble, the bubble solution adheres to the wet surfaces of the bubble hoop and bubble solution (the square shape bubble hoop at the top and the surface layer of bubble solution at the bottom).

(130) An eighth exemplary bubble-making station includes system **700** that comprises a bubble light apparatus, methods of using and/or interacting with the bubble light apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The bubble light apparatus allows a user to create individual bubbles and/or a pile/cluster/tower of bubbles (for example, a “bubble brain” or “bubble tower”) in a predefined defined spot and shines light through the bubbles to create different lighting and colored effects.

(131) A bubble light apparatus **710** comprises a station having a plurality of defined or delineated spaced-apart locations for multiple user. Each location comprises a basin having a transparent or translucent bottom that allows the transmission of light and a light source underneath the bottom of the basin.

(132) Referring generally to FIGS. 7A, 7B, & 7C, bubble light apparatus **710** comprises a support structure **712** and a lighting system **730**. Support structure **712** comprises one or more sides **714**, a bottom **716** and a top surface **718**, with top surface **718** having one or more basins **720**. Support structure **712** is used to stably support one or more basins **720** for proper use by a user and has with an internal space to house lighting system **730**. As shown in FIGS. 7B & 7C, support structure **712** may optionally comprise one or more drains **724** and catch basin **726**. Bubble light apparatus **710** can further include controls regulating the intensity and/or color of the light being generated by lighting system **730**.

(133) One or more sides **714** of support structure **712** may be curved, defining a circle or an oval, or any cuboidal shape with square and rectangular shapes being preferred, the cuboidal shape having sharp (right-angled) or curved corners. In some embodiments, support structure **712** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, support structure **712** is generally cuboidal in shape. In some embodiments, support structure **712** is cuboidal and can have a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8

to 10 feet. The height of support structure **712** can be 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet.

(134) Top surface **718** can further, and optionally, include a lip around a perimeter of top surface **718**, thereby forming a reservoir designed to contain bubble solution **4**. In a preferred embodiment, the lip of top surface **718** has a height of, for example, about 0.25 inches to 0.5 inches, about 1 inch to 5 inches, about 2 to 4 inches to about 3 inches. This top surface reservoir of top surface **718** is independent to the one or more basins **720** which also contain bubble solution **4**. The shape defining top surface reservoir of top surface **718** may be curved, defining a circle or an oval, or any closed polygonal shape with triangle, square, rectangular, and pentagonal shapes being preferred, the polygonal shape having sharp or curved corners. In some embodiments, top surface reservoir of top surface **718** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, top surface reservoir of top surface **718** is generally polygonal in shape. In some embodiments, top surface reservoir of top surface **718** is polygonal in shape and each length of the polygon can be 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, 1 to 2 feet, 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. In some embodiment, top surface **718** can further, and optionally, be composed of a material, such as, e.g., glass, plexiglass, or plastic, that is partially or fully transparent and/or partially or fully translucent in a manner that allows light to transmit therethrough.

(135) As shown in FIG. 7A, one or more basins **720** comprise one or more sides **704** and a bottom **706**. Bottom **706** of one or more basins **720** is composed of a material, such as, e.g., glass, plexiglass, or plastic, that is partially or fully transparent and/or partially or fully translucent in a manner allows light to transmit therethrough. Top edge of each of the one or more sides **704** may be rounded off or be provided having a substantially right angle. In particular configurations, support structure **712** can comprise 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. Each of the one or more basins **720** can serve as a reservoir for bubble solution **4**. Each of the one or more basins **720** are filled to a sufficient depth that may be manually delivered into basins **720**. Each of the one or more basins **720** can be of any suitable geometry, perimeter, and/or shape and any depth that provides for a sufficient area and volume to hold bubble solution **4**. In a preferred embodiment, the basins are circular and have a flat bottom **704** and a surrounding side **706** that rises from, for example, about 0.25 inches to 0.5 inches, about 1 inch to 5 inches, about 2 to 4 inches to about 3 inches from the bottom of the basins. Each of the one or more basins **720** can have a depth of bubble solution **4** of, for example, about 0.25 inches to 0.5 inches, about 0.25 inches to about 0.75 inches, about 0.5 inch to about 1 inch, about 1 inch to about 2 inches or about 0.5 inch to about 3 inches contained therein. Each of the one or more basins **720** may be made of any material which may retain a bubble solution, with materials that withstand corrosion from a bubble solution being preferred, such as, e.g., plastic, fiberglass, treated wood, glass, metal or any suitable material that can hold a bubble solution. One or more bubble producing tools, such as bubble wands, which may have multiple shapes with one or more hoops may be provided.

(136) As best seen in FIG. 7C, lighting system **730** is located internal to support structure **712**. Lighting system **730** comprises one or more light sources **732** connected to a power supply **734** using one or more electrical wires **736**. One or more light sources **732** can include a LED-based light source. One or more light sources **732** can emit white light and/or colored light, using, for example, one or more light sources **732** integrally designed to emit colored light or one or more light sources **732** employing colored filters to produce colored light. Examples of colored light include purple, blue, green, orange, yellow and red. Power supply **734** powers the one or more light sources **732**. In some embodiments, lighting system **730** further includes a controller for controlling timing, color and/or fading of one or more light sources **732**. In one example, light source **732**

provides lights of different colors to provide shine or illumination **715** (light) of the bubbles from beneath one or more basins **720**.

(137) In some embodiments, each of one or more light sources **732** is located underneath transparent or translucent bottom **706** of each of one or more basins **720** in a manner that directs light upward from one or more light sources **732** through transparent or translucent bottom **706** of each of one or more basins **720**. In some embodiments, each of one or more light sources **732** is located underneath transparent or translucent top surface **718** of support structure **712** in a manner that directs light upward from one or more light sources **732** through transparent or translucent top surface **718**.

(138) In use, as shown in FIG. **7A**, a user **2** dips the wand(s) into bubble solution **4** and lightly blows so as to create bubbles, which may be set on top surface of bubble solution **4** present in basin **720** and/or on top surface **718**. When a sufficient number of bubbles are sitting together in a tower or pile, the pile of bubbles form and take on a configuration having, for example, the appearance of a brain, an animal, a face, a mountain or any other creative shape. The interfacing surfaces of adjacent individual bubbles create polygonal, for example, diamond shapes, three-dimensional polygonal shapes where the various individual bubbles interface with each other in the pile of bubbles. Light **715** from one or more light sources **732** shines from beneath one or more basins **720** thereby illuminating the bubbles.

(139) This eighth exemplary bubble-making station includes a system **700** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(140) For example, after formation of a bubble tower, an attendant/guide can ask a user(s) “What color do you think a bubble is?”. Then the attendant/guide and/or a user(s) proceed to pop the bubble tower and wait until the solution settles and ask “Can you see any different colors in the bubbles? Why are there different lines across the bubble solution and what do the colors mean?”. The attendant/guide can then proceed to disclose that one of the most common things people miss about bubbles is the color. Color gives us an extremely accurate tool for measuring the thickness of the soap film of the bubble. Light waves, like ocean waves, have peaks and valleys (aka crests and troughs). Red light has the longest wavelength and violet the shortest in the visible light spectrum. All waves, including light, have a unique property: if two waves combine, the waves can meet each other crest-to-crest, adding up and reinforcing the effect of each other, or they can meet crest-to-trough, cancelling each other out so that they have no effect. This combination of equal ups and downs causes complete cancellation (aka interference). This is why you see the pearly luster of an abalone shell, the beautiful colors in some bird feathers and insect wings, and the flowing patches of color in an oil slick on the street after a rain shower (iridescence)—and for the color of bubbles.

(141) White light, most of the light that is in rooms and outdoors, is made up of all colors, all wavelengths. If one of these colors is subtracted from white light (by interference, for instance) we see the complementary color. For example, if blue light is subtracted from white light, we see orange. The bubble solution surface glistens with the complementary colors produced by interference. If we were to look at a highly magnified portion of a soap bubble membrane, we would notice that light reflects off both the front (outside) and rear (inside) surfaces of the bubble, but the ray of light that reflects off the inside surface travels a longer distance than the ray which reflects from the outside surface. When the rays recombine, they can get “out of step” or phase with each other and interfere. Given a certain thickness of the bubble wall, a certain wavelength

will be cancelled, and its complementary color will be seen.

(142) Thin film interference allows us to sometime see a 'rainbow' in the bubble. When you see the reflection of the bubble getting darker, close to black in color, that means that it will likely pop at that specific point. Our eyes can't catch it fast enough, but when we use a slow-motion camera, we'll be able to see at what specific point the bubble pops.

(143) After such an explanation/discussion the attendant/guide can lead the users in making and popping bubble towers on different colored light stations and ask user(s) what color is missing from the rainbow because of the light underneath shining through the bubbles. The attendant/guide can go over what colors are complementary colors: Yellow and Purple; Red and Green; and Blue and Orange. Since there is a substantial amount of educational points regarding reflective lights, bubble properties, and geometry at this station, the curriculum can be modified based on the age-range of the station user or users. The curriculum presented at any of the bubble-making stations of the facility can be modified based on the age-range of the station user or users.

(144) A ninth exemplary bubble-making station includes system **800** that comprises a bubble jet apparatus, methods of using and/or interacting with the bubble jet apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The bubble jet apparatus provides a stream or jet of air that allows a user to quickly generate many bubbles in an immediate area, for example, hundreds of bubbles a minute, thereby providing an atmosphere in one area where users feel surrounded by bubbles floating all around them. The area can be enhanced with lights and music to create a fun and lively area where participants can dance and or simply stand still and be surrounded in bubbles.

(145) A bubble jet apparatus comprises a station having a plurality of defined or delineated spaced-apart locations for multiple user. Each location comprises a basin containing a bubble solution and next to the basin an air vent that blows air in an upwardly vertical direction. A user or users are able to create and manipulate bubbles created by using various bubble producing tool or tools in conjunction with the air provided by the one or more air vents. Bubble wands, other bubble producing tools with various sized openings, grates with numerous small openings, large wands, and/or an apparatus that creates smoke-filled bubbles, such as that of FIG. **10B** discussed above, can be used in conjunction with the upward air flow to create and keep bubbles suspended in the air.

(146) An exemplary bubble jet apparatus **810** is shown in FIGS. **8A-8D**. Referring to FIG. **8A**, bubble jet apparatus **810** comprises a support structure **812** and an air stream system **830**. Support structure **812** comprises one or more sides **814**, a bottom **816**, and a top surface **818**, with top surface **818** having one or more basins **820** and one or more vents **836**. Support structure **812** is used to stably support one or more basins **820** and one or more vents **836** for proper use by a user and has an internal space to house air stream system **830**. Bubble jet apparatus **810** can further include controls regulating the intensity and/or direction of the air being generated by air stream system **830**. In some embodiments, bubble jet apparatus **810** is portable.

(147) One or more sides **814** of support structure **812** may be curved, defining a circle or an oval, or any cuboidal shape with square and rectangular shapes being preferred, the cuboidal shape having sharp (right-angled) or curved corners. In some embodiments, support structure **812** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, support structure **812** is generally cuboidal in shape. In some embodiments, support structure **812** is cuboidal and can have a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. The height of support structure **812** can be 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet.

(148) The shape of top surface **818** of support structure **812** may be curved, defining a circle or an

oval, or any closed polygonal shape with triangle, square, rectangular, and pentagonal shapes being preferred. In some embodiments, top surface is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, top surface is generally polygonal in shape. In some embodiments, top surface is polygonal in shape and each length of the polygon can be 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, 1 to 2 feet, 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet.

(149) As best shown in FIGS. **8C** & **8D**, one or more basins **820** comprise one or more sides **804** and a bottom **806** and a top edge of one or more sides **804** may be rounded off or be provided having a substantially right angle. In particular configurations, support structure **812** can comprise 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. Each of the one or more basins **820** can serve as a reservoir for bubble solution **4**. Each of the one or more basins **820** are filled to a sufficient depth that may be manually delivered into basins **820**. Each of the one or more basins **820** can be of any suitable geometry that provides for an area to hold bubble solution **4**. In a preferred embodiment, the basins are circular and have a flat bottom **804** and a surrounding side **806** that rises from, for example, about 0.25 inches to 0.5 inches, about 1 inch to 5 inches, about 2 to 4 inches to about 3 inches from the bottom of the basins. Each of the one or more basins **820** can have a depth of bubble solution **4** of, for example, about 0.25 inches to 0.5 inches, about 0.25 inches to about 0.75 inches, about 0.5 inch to about 1 inch, about 1 inch to about 2 inches or about 0.5 inch to about 3 inches contained therein. Each of the one or more basins **820** may be made of any material which may retain a bubble solution, with materials that withstand corrosion from a bubble solution being preferred, such as, e.g., plastic, fiberglass, treated wood, glass, metal or any suitable material that can hold a bubble solution. One or more bubble producing tools, such as bubble wands, which may have multiple shapes with one or more hoops may be provided.

(150) One or more vents **836** can be provided as simple open apertures in top surface **818**, or, and as best shown in FIGS. **8C** & **8D**, one or more vents **836** may be preferentially provided with a porous covering **837**, the covering having pores that allow air to pass therethrough. Such a covered configuration of one or more vents **836** provides a safe way to provide air coming out of the internal space of support structure **812**. Providing porous covering **837** also advantageously prevents objects from falling into the internal space of support structure **812**. In some embodiments, one or more vents **836** is one vent **836**. In some embodiments, one or more vents **836** is 2 to 10 vents **836**, 3 to 9 vents **836**, 4 to 8 vents **836**, 3 to 7 vents **836**, 4 to 7 vents **836**, 5 to 7 vents **836**, 4 to 6 vents **836**, or 5 or 6 vents **836**.

(151) As best seen in FIGS. **8C** & **8D**, air stream system **830** is provided in the internal space of support structure **812**. In one embodiment and as shown in FIG. **8C** taken along line **8C** of FIG. **8B**, air stream system **830** can comprise at least one motorized blower **832**, such as one or more fans, one or more ducts **834**, and one or more vents **836** and, optionally with one or more baffles **838**. One or more baffles **838** can be provided across the internal space of support structure **812** and arranged substantially underneath one more vent **836** to deflect air blown by at least one motorized **832** up and out of one or more vents **836**. One or more baffles **838** are placed inside not to prevent air flow altogether, but to upwardly direct air, as shown by arrows in FIG. **80**. At least one motorized **832** is preferentially provided at one end of the internal space of support structure **812** (as shown) or can be located, in an alternative configuration, directly under one or more vents **836** to blow air up and outwardly. As shown the exemplary embodiment of FIG. **8C**, air duct **834** can simply be the internal space of support structure **812**. Bubble jet apparatus **810** can further comprise a power supply and electrical wires to power at least one motorized **832** as known in the art. In one alternative configuration, bubble jet apparatus **810** can optionally include one or more drains at top surface **818** fluidly connected to one or more catch basins provided within internal

space of support structure **812** to catch any bubble solution **4** that spills onto top surface **818**.

(152) In an alternative embodiment and as shown in FIG. **8D**, at least one motorized **832** can blow air through air duct **834**, where air duct **834** is a dedicated ventilation duct for directing air directly to and through one or more vents **836**. In this embodiment, air duct **834** can be made from sheet metal, aluminum plastic and the like in composition, can be ridged or flexible in nature, and can be cylindrical or cuboidal in shape. Air duct **834** can also be tube-shaped and made of a wire coil and covered with a bendable, durable plastic, for example.

(153) In use, as shown in FIG. **8A**, a user **2** dips a bubble making tool into bubble solution **4** and places the bubble making tool over a vent in a manner that allows the air being blown upward from the vent to create bubbles. Controls regulating the intensity and/or direction of the air being blown upward from the vent can be adjusted by user **2** to create different size and number of bubbles as basin as illustrate educational principles.

(154) This ninth exemplary bubble-making station includes a system **800** providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(155) For example, bubble jet system **800** provides an interactive bubble creating experience without using a user's pulmonary or motor skills allowing all individuals (impaired/handicapped or not) to enjoy and engage in bubble play. For example, educational points can revolve around the intensity of the air and the shape of the bubble producing tool being used. A blower, such as a fan within the apparatus, can have varying intensities and can be adjusted (by turning up or down the fan strength) to promote different educational principles. If a bubble producing tool, such as a bubble wand having a large diameter is used, the rate of wind must be slow enough in order to create a stable soapy membrane. If the rate of wind is too fast, there will be no resulting large bubble. Conversely, if using a smaller diameter wand, a faster rate of wind would still result in a smaller bubble due to the physics of soap film stability. Additionally, another activity may utilize a lightweight object (for example a balloon, a plastic ball) and the air blowing through the vent to teach principles of gravity, mass, and other physics-related properties.

(156) An exemplary tenth bubble-making station includes system **900** that comprises one or more bubble pedestal apparatus, methods of using and/or interacting with the bubble pedestal apparatus and station-specific media demonstrating basic educational science and mathematical principles using, e.g., a STEM curriculum. The bubble pedestal apparatus comprises a basin containing a bubble solution and giant bubble wands to make large bubbles. A user or users can complete bubble tricks, including attempts to make bubbles large enough to enclose a person, or make a multitude of bubbles of varying sizes.

(157) Turning to FIG. **9A**, an exemplary bubble pedestal apparatus **910** comprises a support structure **911** including a top surface **912** and one or more sides **914**. The perimeter of top surface **912** has one or more lips **915**, each having an internal surface **916** and an external surface **917**, the internal space defined by internal surface **916** of each of one or more lips **915** defines a basin **919**. Basin **919** can serve as a container for bubble solution **4**. Bubble pedestal apparatus **910** can optionally, be provided with casters **920** to impart mobility to the system. Exemplary casters can be four-inch casters or any useful size, depending on the desired configuration. As shown in FIG. **9A**, support structure **911** can optionally have a door **930** or plurality of doors to provide access to an internal portion of bubble pedestal apparatus **910**. Door **930** or plurality of doors can optionally have a handle **932** and, optionally a lock **914**. The internal portion of bubble pedestal apparatus **910**

may be utilized as a storage space for containers holding bubble solution **4** and bubble producing tools, such as giant wands utilized at this exemplary tenth bubble-making station, for example.

(158) In particular configurations, one or more lips **915** can have internal surface **916** that has a length that is larger, smaller or equal to an external surface of one or more lips **915**. In one example, one or more lips **915** can have an external surface of about one to five inches tall, with a height of four inches being preferred and have a thickness of about $\frac{3}{4}$ inch. One or more lips **915** can be mounted onto top surface **912** of bubble pedestal apparatus **910** such that resulting basin **919** is at about two inches from the top of one or more lips **915**, thus providing a bubble solution reservoir having a particular depth. In various embodiments, basin **919** can be from about 1 inch to 5 inches from top of one or more lips **915**, a preferred distance being two inches, that is, internal surface **916** has a height of two inches and the resultant bubble reservoir can be filled with bubble solution **4** to a depth of two inches. In this particular embodiment, exemplary bubble pedestal apparatus **910** has one or more lips **915** that is square and has four lips of equal length, each thirty-six inches in length, as one example. The height of bubble pedestal apparatus **910** can be twenty-four inches to 48 inches.

(159) Turning to FIG. **9B**, in one aspect, multiple raised pedestals of varying heights and/or shapes are provided at this an exemplary tenth bubble-making station. Pedestal apparatus **910** may be curved, defining a circle or an oval, or any cuboidal shape with square and rectangular shapes being preferred, the cuboidal shape having sharp (right-angled) or curved corners. In some embodiments, pedestal apparatus **910** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, pedestal apparatus **910** is generally cuboidal in shape. In some pedestal apparatus **910** is cuboidal and can have a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet. The height of support structure **12** can be 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet.

(160) In addition, basin **919** may be curved, defining a circle or an oval, or any closed polygonal shape, such as, e.g., a triangular shape, a square shape, a rectangular shape, or a pentagonal shape. In some embodiments, basin **919** is circular or oval and can have a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. In one embodiment, basin **919** is generally polygonal in shape. In some embodiments, basin **919** is polygonal in shape and each length of the polygon can be 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet.

(161) The user or users can then use various custom-made bubble producing tools, here giant bubble wands of various shapes and sizes, by dipping them in and withdrawing them from the bubble solution **4** to make various bubbles.

(162) Exemplary bubble wands that can be utilized at this station include a giant hoop **918**. This wand is shaped like a lollipop and can have a handle **924** from two feet to four feet in length, (or any length as desired), with a giant hoop at its distal end of from 18 inches to 36 inches in diameter. Giant hoop **918** makes giant bubbles from two feet to eight feet or more in diameter and can be used by either slowly waving it around, running with it held up or an combination of both. Giant hoop **918** can also be used to surround and substantially enclose a second participant in a bubble resulting therefrom. Giant hoop **918** can be made from flexible PVC pipe bent and and wrapped in tape, such as electrical tape (of any desired color, for example, black). In particular configurations, giant hoop includes handle **924** which may also be wrapped in a material, one example being electrical tape. Further, the circle portion of giant hoop **918** can be provided with an absorbent material. In one example athletic tape can be wrapped around circle portion of giant hoop **918** to provide the circular bubble forming portion of giant hoop **918** increased capacity to hold bubble solution **4** as compared to when not being wrapped with absorbent material.

(163) Another exemplary wand utilized at this station is called a Flower Wand **926** and is shaped

like the letter “T”. It can have a handle from 2 feet to 4 feet in length with two flower hoops on either distal portion of the two top end portions of the “T”, as shown in the hexagonal bubble pedestal in FIG. 9B. The head of the wand (top “T” end having the two flower loops) is dipped into the solution. Waving the wand slowly creates larger bubbles, waving the wand quickly creates many smaller bubbles. An additional exemplary wand that can be provided and utilized at this station is a Broom Bubble Wand. This wand is shaped like a sweeper broom, having a long handle from two feet to 4 four feet in length. At one end, there is a terminal hoop that serves as a frame that holds a plurality of small hoops 922 (here in FIG. 9B shown as four smaller hoops, although any number of hoops, such as 8-10 smaller hoops are envisioned). Smaller hoops may be mounted within or around (or a combination thereof) the larger terminal hoop. Such bubble wands are then dipped into the bubble/soap solution and many medium sized bubbles about 5-6” in length are created simultaneously as the wand is waved through the air or blown upon a plurality of users.

(164) This tenth exemplary bubble-making station includes a system 900 providing station-specific media in a setting to facilitate basic educational science and mathematical principles using, e.g., a STEM curriculum. An attendant/guide can conduct a demonstration or lead a user(s) in an activity designed to exemplified various physical phenomena. After the demonstration the attendant/guide can lead a discussion, optionally referring to bubble-making station specific media for visuals to help explain the various scientific phenomena. Non-limiting examples of station specific media include, e.g., a poster, a handout, a monitor, an interactive monitor, a touch-screen monitor, a water-proof monitor or tablet. Alternatively such information may be provided solely in the form bubble-making station specific media, without the aid of an attendant/guide.

(165) Some general information that may incorporated into any curriculum, e.g., a STEM curriculum, and any station comprising systems 100 through 1000 and may be discussed at any of the plurality of bubble-making stations herein disclosed. General discussions about bubbles that disclose to user(s) that a bubble is just air wrapped in soap film. Soap film is generally made from soap and water (or other liquid). The outside and inside surfaces of a bubble consist of soap molecules. A thin layer of water lies between the two layers of soap molecules, sort of like a water sandwich with soap molecules for bread. They work together to hold air inside. Water molecules are attracted to other water molecules (aka cohesion) and try to stick together as much as they can. Water molecule are attracted to each other so much that they will work really hard to stay together (aka surface tension). To illustrate this point, a penny experiment can be demonstrated. In this experiment, a small pipette is used to slowly and continuously put droplets of water onto the top of a penny. As water drops are added, the water forming on top of the penny will get larger and larger and will eventually form a ‘bulb’ on top of the penny. This bulb of water stored on the penny will continue to extend out past the penny's circumference because of the surface tension, cohesion, and polar properties of water. The polarity of water molecules can also be discussed in regard to characteristics such as, but not limited to, surface tension, solubility, melting and boiling points.

(166) The floor of the entertainment facility can entirely, or at the particular stations described herein, have an absorbent floor in order to absorb liquid, particularly bubble fluid, to prevent and/or minimize persons from slipping thereon) and composed of transparent material.

(167) Aspects of the present specification can also be described as follows: 1. An entertainment/educational facility comprising one or more bubble-making stations, each of the one or more stations comprising a system, wherein the system present in each of the one or more stations is different than the system present in any of the other of the one or more stations, and wherein the system comprising any one of the following systems, a first system comprising a bubble making apparatus and educational information regarding the scientific principles of bubbles, the bubble making apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom, a top opening, one or more basins, a trough and a reservoir, wherein the one or more basins each have one or more sides, a bottom and a port, the port positioned at the bottom of the one or more basins, and the one or more basins configured to contain a bubble

solution, wherein the trough comprises a trough bottom biased toward the reservoir in a manner that directs the bubble solution falling onto the trough bottom is directed toward the reservoir, and wherein the reservoir is configured to contain a bubble solution, and b) a pumping system, the pumping system including one or more pumps and one or more conduits, wherein the one or more conduits connect at least one pump to the port of each of the one or more basins, and wherein in operation the at least one pump continuously transports the bubble solution contained in the reservoir through the one or more conduits to the port of each of the one or more basins, thereby filling each of the one or more basins with the bubble solution; or a second system comprising a gas producing apparatus and educational information regarding the scientific principles of bubbles, the gas producing apparatus comprising: a) a base, the base comprising one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins each comprising one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) a smoke-like fog generating apparatus, the smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses, and wherein each of the one or more basins is configured to receive the second end of each of the one or more hoses, and wherein in operation dry ice and water placed inside internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses; or a third system comprising a mobile gas producing apparatus and educational information regarding the scientific principles of bubbles, the mobile gas producing apparatus comprising: a) a carrier, and b) a mobile smoke-like fog generating apparatus, the mobile smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses, wherein in operation dry ice and water placed inside the internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses; or a fourth system comprising an inflatable apparatus and educational information regarding the scientific principles of bubbles, the inflatable apparatus comprising: a) a first inflated chamber, the first inflated chamber being substantially spherical and curved in shape with a flat bottom, b) a second inflated chamber being substantially cuboidal in shape, the second inflated chamber comprising an entrance enabling a user access from outside the apparatus into the second inflated chamber, and c) an inflation system, the inflation system including an inflation device and one or more air conduits, wherein the one or more air conduits connect the inflation device to at least the first inflated chamber, wherein the first inflated chamber has a contiguous portion with the second inflated chamber, wherein an opening is present in the contiguous portion to create a pathway between the first inflated chamber to the second inflated chamber, and wherein in operation the inflation device expels air through the one or more conduits and into at least the first inflated chamber, thereby inflating the first inflated chamber; or a fifth system comprising a bubble sheet

making apparatus and educational information regarding the scientific principles of bubbles, the bubble sheet making apparatus comprising: a) a frame system, the frame system including a bottom trough, one or more vertical support members and a top support structure, the bottom trough including one or more sides, a bottom and a top opening opposite the bottom, the resulting interior space defining a reservoir, wherein the bottom trough is configured to contain a bubble solution, wherein the one or more vertical support members span the space between the bottom trough and the top support structure, b) a lift system, the lift system including one or more pulleys and one or more lifting cords, each of the one or more lifting cords comprising a first end and a second end, wherein the one or more pulleys are secured to the top support structure of the frame system, and c) a bar system, the bar system comprising a top bar, one or more depending cords, and a bottom bar, and each of the one or more depending cords comprising at least a free end and composited of a collapsible material, wherein the top bar comprises a first end, a second end and an absorbent material, and wherein the one or more depending cords is secured to the top bar and the at least a free end of the one or more depending cords is secured to the bottom bar, and wherein the first end of each of the one or more lifting cords of the lift system is secured to the top bar, the one or more lifting cords then passed through the one or more pulleys, thereby having the second end of each of the one or more lifting cords on the side of the one or more pulleys opposite the side of the first end of each of the one or more lifting cords, and wherein in operation, the bar system submerged in the bubble solution contained in the bottom trough is lifted vertically upward out of the bottom trough using the lift system, thereby forming a bubble sheet using the bubble solution contained within a framework created by the top bar, one or more depending cords and the bottom bar; or a sixth system comprising: a) a bubble making apparatus, the bubble making apparatus comprising: i) a support structure, the support structure having one or more sides, a bottom and a top, and comprising a power system and a ventilation system, the power system including a power supply to generate electricity and one or more electrical wires, and ii) one or more bubble producing systems, each of the one or more bubble producing systems comprising: 1) a motorized bubble producing tool system, the motorized bubble producing tool system including a reservoir, one or more bubble producing tools attached to a central hub and a motor, wherein the central hub is operably linked to the motor, and wherein the reservoir is configured to contain a bubble solution, and 2) an air stream producing system, the air stream producing system comprising a motorized blower and a vent, wherein the one or more electrical wires connect the power supply to the motor of the motorized bubble producing tool system and the motorized blower the air stream producing system, and wherein in operation the motorized blower continuously expels air in a generally horizontal direction through vent and outward from the front of the bubble making apparatus and the motor of the motorized bubble producing tool system continuously spins the central hub causing each of the one or more bubble producing tools to undergo a rotational cycle through the bubble solution contained in the reservoir and past air stream being expelled through the vent, thereby causing formation of a stream of bubbles, b) an activity area, the activity area comprising at least one receptacle including projectiles, and c) educational information regarding the scientific principles of bubbles; or a seventh system comprising a bubble tower making apparatus and educational information regarding the scientific principles of bubbles, the bubble tower making apparatus comprising: a) a base system, the base system including a platform, a fluid trough and a base surround, the fluid trough configured to contain a bubble solution, wherein the base surround is located along the outside perimeter of the fluid trough and the fluid trough is located along the outside perimeter of the platform, b) a support frame system, the support frame system including one or more vertical support members and a top frame, wherein the one or more vertical support members span the space between the base system and the top frame, and c) a lift system, the lift system including one or more lifting pulleys, one or more control pulleys, one or more cables, and a bubble forming device, each of the one or more cables comprising a first end and a second end, wherein the one or more lifting pulleys and one or more control pulleys are secured to the top

frame of the support frame system, wherein the bubble forming device conforms to the shape of the fluid trough, and wherein the one or more cables are each secured to the bubble forming device, and wherein the first end of each of the one or more cables of the lift system is secured to the bubble forming device, the one or more cables then passed through the one or more lifting pulleys and one or more controlling pulleys, thereby having the second end of each of the one or more cables on the side of the one or more lifting pulleys and one or more controlling pulleys opposite the side of the first end of each of the one or more cables, and wherein in operation, the bubble forming device submerged in the bubble solution contained in the fluid trough is lifted vertically upward out of the fluid trough using the lift system, thereby forming a bubble tower using the bubble solution contained between the bubble forming device and the bubble solution contained in the fluid trough; or an eighth system comprising a bubble light apparatus and educational information regarding the scientific principles of bubbles, the bubble light apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins including one or more sides and a bottom, the bottom being partially or fully transparent and/or partially or fully translucent, thereby enabling light to transmit therethrough, wherein each of the one or more basins is configured to contain a bubble solution, and b) a lighting system, the lighting system including one or more light sources, at least one power supply to generate electricity, and one or more electrical wires, wherein each of the one or more light sources is located underneath the bottom of each of one or more basins, and wherein the one or more electrical wires connect the at least one power supply to each of the one or more light sources, and wherein in operation, one or more users create one or more bubbles using the bubble solution contained in the one or more basins and light being emitted from the one or more light sources shine through the one or more bubbles; or a ninth system comprising a bubble jet apparatus and educational information regarding the scientific principles of bubbles, the bubble jet apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins and one or more vents, the one or more basins including one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) an air stream system, the air stream system including at least one motorized blower, one or more ducts, at least one power supply to generate electricity, and one or more electrical wires, wherein the one or more electrical wires connect the at least one power supply to the at least one motorized blower, and wherein the bubble jet apparatus further comprises one or more bubble making tools, and wherein in operation, one or more bubbles are formed when a user positions a bubble making tool containing the bubble solution over one of the one or more vents, thereby causing air being expelled through the one of the one or more vents to pass through the bubble making tool thereby creating the one or more bubbles from the bubble solution contained in the bubble making tool; or a tenth system comprising a bubble pedestal apparatus and educational information regarding the scientific principles of bubbles, the bubble pedestal apparatus comprising: a) a support structure, the support structure including one or more sides and a top surface, the top surface having one or more lips positioned around the perimeter of the top surface thereby defining a basin, wherein the basin is configured to contain a bubble solution, and b) one or more casters. wherein the bubble pedestal apparatus further comprises one or more bubble making tools. 2. A system comprising a bubble making apparatus and educational information regarding the scientific principles of bubbles, the bubble making apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom, a top opening, one or more basins, a trough and a reservoir, wherein the one or more basins each have one or more sides, a bottom and a port, the port positioned at the bottom of the one or more basins, and the one or more basins configured to contain a bubble solution, wherein the trough comprises a trough bottom biased toward the reservoir in a manner that directs the bubble solution falling onto the trough bottom is directed toward the reservoir, and wherein the reservoir is configured to contain a bubble solution, and b) a pumping system, the

pumping system including one or more pumps and one or more conduits, wherein the one or more conduits connect at least one pump to the port of each of the one or more basins, and wherein in operation the at least one pump continuously transports the bubble solution contained in the reservoir through the one or more conduits to the port of each of the one or more basins, thereby filling each of the one or more basins with the bubble solution. 3. A system comprising a gas producing apparatus and educational information regarding the scientific principles of bubbles, the gas producing apparatus comprising: a) a base, the base comprising one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins each comprising one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) a smoke-like fog generating apparatus, the smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses, and wherein each of the one or more basins is configured to receive the second end of each of the one or more hoses, and wherein in operation dry ice and water placed inside internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses. 4. A system comprising a mobile gas producing apparatus and educational information regarding the scientific principles of bubbles, the mobile gas producing apparatus comprising: a) a carrier, and b) a mobile smoke-like fog generating apparatus, the mobile smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses, and wherein in operation dry ice and water placed inside the internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses. 5. A system comprising an inflatable apparatus and educational information regarding the scientific principles of bubbles, the inflatable apparatus comprising: a) a first inflated chamber, the first inflated chamber being substantially spherical and curved in shape with a flat bottom, b) a second inflated chamber being substantially cuboidal in shape, the second inflated chamber comprising an entrance enabling a user access from outside the apparatus into the second inflated chamber, and c) an inflation system, the inflation system including an inflation device and one or more air conduits, wherein the one or more air conduits connect the inflation device to at least the first inflated chamber, and wherein the first inflated chamber has a contiguous portion with the second inflated chamber, and wherein an opening is present in the contiguous portion to create a pathway between the first inflated chamber to the second inflated chamber, and wherein in operation the inflation device expels air through the one or more conduits and into at least the first inflated chamber, thereby inflating the first inflated chamber. 6. A system comprising a bubble sheet making apparatus and educational information regarding the scientific principles of bubbles, the bubble sheet making apparatus comprising: a) a frame system, the frame system including a bottom trough, one or more vertical support members and a top support structure, the bottom

through including one or more sides, a bottom and a top opening opposite the bottom, the resulting interior space defining a reservoir, wherein the bottom trough is configured to contain a bubble solution, wherein the one or more vertical support members span the space between the bottom trough and the top support structure, b) a lift system, the lift system including one or more pulleys and one or more lifting cords, each of the one or more lifting cords comprising a first end and a second end, wherein the one or more pulleys are secured to the top support structure of the frame system, and c) a bar system, the bar system comprising a top bar, one or more depending cords, and a bottom bar, and each of the one or more depending cords comprising at least a free end and composited of a collapsible material, wherein the top bar comprises a first end, a second end and an absorbent material, and wherein the one or more depending cords is secured to the top bar and the at least a free end of the one or more depending cords is secured to the bottom bar, and wherein the first end of each of the one or more lifting cords of the lift system is secured to the top bar, the one or more lifting cords then passed through the one or more pulleys, thereby having the second end of each of the one or more lifting cords on the side of the one or more pulleys opposite the side of the first end of each of the one or more lifting cords, and wherein in operation, the bar system submerged in the bubble solution contained in the bottom trough is lifted vertically upward out of the bottom trough using the lift system, thereby forming a bubble sheet using the bubble solution contained within a framework created by the top bar, one or more depending cords and the bottom bar.

7. A system comprising: a) a bubble making apparatus, the bubble making apparatus comprising: i) a support structure, the support structure having one or more sides, a bottom and a top, and comprising a power system and a ventilation system, the power system including a power supply to generate electricity and one or more electrical wires, and ii) one or more bubble producing systems, each of the one or more bubble producing systems comprising: 1) a motorized bubble producing tool system, the motorized bubble producing tool system including a reservoir, one or more bubble producing tools attached to a central hub and a motor, wherein the central hub is operably linked to the motor, and wherein the reservoir is configured to contain a bubble solution, and 2) an air stream producing system, the air stream producing system comprising a motorized blower and a vent, wherein the one or more electrical wires connect the power supply to the motor of the motorized bubble producing tool system and the motorized blower the air stream producing system, and wherein in operation the motorized blower continuously expels air in a generally horizontal direction through vent and outward from the front of the bubble making apparatus and the motor of the motorized bubble producing tool system continuously spins the central hub causing each of the one or more bubble producing tools to undergo a rotational cycle through the bubble solution contained in the reservoir and past air stream being expelled through the vent, thereby causing formation of a stream of bubbles, b) an activity area, the activity area comprising at least one receptacle including projectiles, and c) educational information regarding the scientific principles of bubbles.

8. A system comprising a bubble tower making apparatus and educational information regarding the scientific principles of bubbles, the bubble tower making apparatus comprising: a) a base system, the base system including a platform, a fluid trough and a base surround, the fluid trough configured to contain a bubble solution, wherein the base surround is located along the outside perimeter of the fluid trough and the fluid trough is located along the outside perimeter of the platform, b) a support frame system, the support frame system including one or more vertical support members and a top frame, wherein the one or more vertical support members span the space between the base system and the top frame, and c) a lift system, the lift system including one or more lifting pulleys, one or more control pulleys, one or more cables, and a bubble forming device, each of the one or more cables comprising a first end and a second end, wherein the one or more lifting pulleys and one or more control pulleys are secured to the top frame of the support frame system, wherein the bubble forming device conforms to the shape of the fluid trough, and wherein the one or more cables are each secured to the bubble forming device, and wherein the first end of each of the one or more cables of the lift system is secured to the

bubble forming device, the one or more cables then passed through the one or more lifting pulleys and one or more controlling pulleys, thereby having the second end of each of the one or more cables on the side of the one or more lifting pulleys and one or more controlling pulleys opposite the side of the first end of each of the one or more cables, and wherein in operation, the bubble forming device submerged in the bubble solution contained in the fluid trough is lifted vertically upward out of the fluid trough using the lift system, thereby forming a bubble tower using the bubble solution contained between the bubble forming device and the bubble solution contained in the fluid trough. 9. A system comprising a bubble light apparatus and educational information regarding the scientific principles of bubbles, the bubble light apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins including one or more sides and a bottom, the bottom being partially or fully transparent and/or partially or fully translucent, thereby enabling light to transmit therethrough, wherein each of the one or more basins is configured to contain a bubble solution, and b) a lighting system, the lighting system including one or more light sources, at least one power supply to generate electricity, and one or more electrical wires, wherein each of the one or more light sources is located underneath the bottom of each of one or more basins, wherein the one or more electrical wires connect the at least one power supply to each of the one or more light sources, and wherein in operation, one or more users create one or more bubbles using the bubble solution contained in the one or more basins and light being emitted from the one or more light sources shine through the one or more bubbles. 10. A system comprising a bubble jet apparatus and educational information regarding the scientific principles of bubbles, the bubble jet apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins and one or more vents, the one or more basins including one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) an air stream system, the air stream system including at least one motorized blower, one or more ducts, at least one power supply to generate electricity, and one or more electrical wires, wherein the one or more electrical wires connect the at least one power supply to the at least one motorized blower, wherein the bubble jet apparatus further comprises one or more bubble making tools, and wherein in operation, one or more bubbles are formed when a user positions a bubble making tool containing the bubble solution over one of the one or more vents, thereby causing air being expelled through the one of the one or more vents to pass through the bubble making tool thereby creating the one or more bubbles from the bubble solution contained in the bubble making tool. 11. A system comprising a bubble pedestal apparatus and educational information regarding the scientific principles of bubbles, the bubble pedestal apparatus comprising: a) a support structure, the support structure including one or more sides and a top surface, the top surface having one or more lips positioned around the perimeter of the top surface thereby defining a basin, wherein the basin is configured to contain a bubble solution, and b) one or more casters. wherein the bubble pedestal apparatus further comprises one or more bubble making tools. 12. A bubble making apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom, a top opening, one or more basins, a trough and a reservoir, wherein the one or more basins each have one or more sides, a bottom and a port, the port positioned at the bottom of the one or more basins, and the one or more basins configured to contain a bubble solution, wherein the trough comprises a trough bottom biased toward the reservoir in a manner that directs the bubble solution falling onto the trough bottom is directed toward the reservoir, and wherein the reservoir is configured to contain a bubble solution, and b) a pumping system, the pumping system including one or more pumps and one or more conduits, wherein the one or more conduits connect at least one pump to the port of each of the one or more basins, and wherein in operation the at least one pump continuously transports the bubble solution contained in the reservoir through the one or more conduits to the port of each of the one or more basins, thereby filling each of the one or more basins with the bubble solution. 13. The bubble

making apparatus of embodiment 12, wherein the one or more sides of the support structure define a circular or oval shape. 14. The bubble making apparatus of embodiment 13, wherein the support structure is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. 15. The bubble making apparatus of any one of embodiments 12-14, wherein the one or more sides of the support structure define a cuboidal shape with sharp and/or curved corners. 16. The bubble making apparatus of embodiment 15, wherein the support structure is cuboidal in shape with a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. 17. The bubble making apparatus of any one of embodiments 12-16, wherein the support structure 2 to 5 feet, 2 to 4 feet or 2 to 3 feet in height. 18. The bubble making apparatus of any one of embodiments 12-17, wherein the one or more basins includes 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. 19. The bubble making apparatus of any one of embodiments 12-18, wherein the one or more sides of each of the one or more basins define a circular or oval shape. 20. The bubble making apparatus of any one of embodiments 12-19, wherein the at least one pump of the one or more pumps is located in the reservoir. 21. The bubble making apparatus of any one of embodiments 12-20, wherein the at least one pump of the one or more pumps is located in the trough, the at least one pump further comprising one or more conduits connecting the at least one pump to the reservoir. 22. The bubble making apparatus of any one of embodiments 12-21, further comprising one or more bubble making tools. 23. The bubble making apparatus of any one of embodiments 12-22, wherein in operation, spillage of the bubble solution into the trough directs the bubble solution toward the reservoir where the at least one pump then transports the bubble solution through the one or more conduits to the port of each of the one or more basins, thereby filling each of the one or more basins with the bubble solution. 24. A gas producing apparatus comprising: a) a base, the base comprising one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins each comprising one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) a smoke-like fog generating apparatus, the smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses, and wherein each of the one or more basins is configured to receive the second end of each of the one or more hoses. 25. The gas producing apparatus of embodiment 24, wherein the one or more sides of the base define a circular or oval shape. 26. The gas producing apparatus of embodiment 25, wherein the base is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. 27. The gas producing apparatus of any one of embodiments 24-26, wherein the one or more sides of the base define a cuboidal shape with sharp and/or curved corners. 28. The gas producing apparatus of embodiment 27, wherein the base is cuboidal in shape with a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. 29. The gas producing apparatus of any one of embodiments 24-28, wherein the base 2 to 5 feet, 2 to 4 feet or 2 to 3 feet in height. 30. The bubble making apparatus of any one of embodiments 24-29, wherein the one or more sides of each of the one or more basins define a circular or oval shape. 31.

The gas producing apparatus of any one of embodiments 24-30, wherein the one or more basins includes 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. 32. The gas producing apparatus of any one of embodiments 24-31, wherein the body and/or the lid of the smoke-like fog generating apparatus further comprise an insulating material. 33. The gas producing apparatus of any one of embodiments 24-32, wherein the smoke-like fog generating apparatus further comprises an insulating material. 34. The gas producing apparatus of any one of embodiments 24-33, wherein the one or more sides of the body define a circular or oval shape. 35. The gas producing apparatus of any one of embodiments 24-34, wherein the one or more sides of the body define a cuboidal shape with sharp and/or curved corners. 36. The gas producing apparatus of any one of embodiments 24-35, wherein the number of the one or more ports and the number of the one or more hoses present on the lid corresponds to the number of one or more basins present on top surface of the base. 37. The gas producing apparatus of any one of embodiments 24-36, wherein the one or more ports of the lid include 2 to 10 ports, 3 to 9 ports, 4 to 8 ports, 3 to 7 ports, 4 to 7 ports, 5 to 7 ports, 4 to 6 ports, or 5 or 6 ports. 38. The gas producing apparatus of any one of embodiments 24-37, wherein in operation dry ice and water placed inside internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses. 39. A mobile gas producing apparatus comprising: a) a carrier, and b) a mobile smoke-like fog generating apparatus, the mobile smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid paths until reaching the second end of each of the one or more hoses, and 40. The mobile gas producing apparatus of embodiment 39, wherein the carrier is a backpack. 41. The mobile gas producing apparatus of embodiment 39 or 40, wherein the body and/or the lid of the mobile smoke-like fog generating apparatus further comprise an insulating material. 42. The mobile gas producing apparatus of any one of embodiments 39-41, wherein the mobile smoke-like fog generating apparatus further comprises an insulating material. 43. The mobile gas producing apparatus of any one of embodiments 39-42, wherein the one or more sides of the body define a circular or oval shape. 44. The mobile gas producing apparatus of any one of embodiments 39-43, wherein the one or more sides of the body define a cuboidal shape with sharp and/or curved corners. 45. The mobile gas producing apparatus of any one of embodiments 39-44, wherein the one or more ports of the mobile smoke-like fog generating apparatus include 2 to 10 ports, 3 to 9 ports, 4 to 8 ports, 3 to 7 ports, 4 to 7 ports, 5 to 7 ports, 4 to 6 ports, or 5 or 6 ports. 46. The mobile gas producing apparatus of any one of embodiments 39-45, wherein in operation dry ice and water placed inside the internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses. 47. An inflatable apparatus comprising: a) a first inflated chamber, the first inflated chamber being substantially spherical and curved in shape with a flat bottom, b) a second inflated chamber being substantially cuboidal in shape, the second inflated chamber comprising an entrance enabling a user access from outside the apparatus into the second inflated chamber, and c) an inflation system, the inflation system including an inflation device and one or more air conduits, wherein the one or more air conduits connect the inflation device to at least the first inflated chamber, and wherein the first inflated chamber has a contiguous portion with the second inflated chamber, and wherein an opening is present in the contiguous portion to create a pathway between the first inflated chamber to the second inflated chamber. 48. The inflatable

apparatus of embodiment 47, wherein the first inflated chamber is 4 to 10 feet in diameter, 6 to 12 feet in diameter, or 8 to 15 feet in diameter. 49. The inflatable apparatus of embodiment 47 or 48, wherein the first inflated chamber further comprises a partition. 50. The inflatable apparatus of any one of embodiments 47-49, wherein the second inflated chamber is 4 to 8 feet in width, 4 to 12 feet in length and 6 to 15 feet in height. 51. The inflatable apparatus of any one of embodiments 47-50, wherein the one or more air conduits further connect the inflation device to the second inflated chamber. 52. The inflatable apparatus of any one of embodiments 47-51, wherein in operation the inflation device expels air through the one or more conduits and into at least the first inflated chamber, thereby inflating the first inflated chamber. 53. The inflatable apparatus of any one of embodiments 47-52, wherein in operation one or more users enter the inflatable apparatus using the entrance of the second inflatable chamber, move through the second inflatable chamber and enter the first inflatable chamber using the opening present in the contiguous portion. 54. A bubble sheet making apparatus comprising: a) a frame system, the frame system including a bottom trough, one or more vertical support members and a top support structure, the bottom trough including one or more sides, a bottom and a top opening opposite the bottom, the resulting interior space defining a reservoir, wherein the bottom trough is configured to contain a bubble solution, wherein the one or more vertical support members span the space between the bottom trough and the top support structure, b) a lift system, the lift system including one or more pulleys and one or more lifting cords, each of the one or more lifting cords comprising a first end and a second end, wherein the one or more pulleys are secured to the top support structure of the frame system, and c) a bar system, the bar system comprising a top bar, one or more depending cords, and a bottom bar, and each of the one or more depending cords comprising at least a free end and composited of a collapsible material, wherein the top bar comprises a first end, a second end and an absorbent material, and wherein the one or more depending cords is secured to the top bar and the at least a free end of the one or more depending cords is secured to the bottom bar, and wherein the first end of each of the one or more lifting cords of the lift system is secured to the top bar, the one or more lifting cords then passed through the one or more pulleys, thereby having the second end of each of the one or more lifting cords on the side of the one or more pulleys opposite the side of the first end of each of the one or more lifting cords. 55. The bubble sheet making apparatus of embodiment 54, wherein the one or more sides of the bottom trough define a circular or oval shape. 56. The bubble sheet apparatus of embodiment 55, wherein the bottom trough is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. 57. The bubble sheet making apparatus of any one of embodiments 54-56, wherein the one or more sides of the bottom trough define a cuboidal shape with sharp and/or curved corners. 58. The bubble sheet apparatus of embodiment 57, wherein the bottom trough is cuboidal in shape with a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. 59. The bubble sheet making apparatus of any one of embodiments 54-58, wherein the one or more vertical support members are each 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet in height. 60. The bubble sheet making apparatus of any one of embodiments 54-59, wherein the absorbent material and the one or more depending cords are separate and distinct components. 61. The bubble sheet making apparatus of embodiment 60, wherein the one or more depending cords include a first depending cord and a second depending cord, the first and second depending cords each comprising a first end and a second end, wherein the first end of each of the first and second depending cords is secured to the top bar and the second end of each of the first and second depending cords is secured to the bottom bar. 62. The bubble sheet making apparatus of any one of embodiments 54-59, wherein the absorbent material and the one or more depending cords are the same integral component. 63. The bubble sheet making apparatus of embodiment 62,

wherein the one or more depending cords include a first depending cord and a second depending cord, the first and second depending cords each comprising a free end, wherein the first free end and the second free end are each secured to the bottom bar. 64. The bubble sheet making apparatus of any one of embodiments 54-63, wherein in operation, the bar system submerged in the bubble solution contained in the bottom trough is lifted vertically upward out of the bottom trough using the lift system, thereby forming a bubble sheet using the bubble solution contained within a framework created by the top bar, one or more depending cords and the bottom bar. 65. A bubble making apparatus comprising a) a support structure, the support structure having one or more sides, a bottom and a top, and comprising a power system and a ventilation system, the power system including a power supply to generate electricity and one or more electrical wires, and b) one or more bubble producing systems, each of the one or more bubble producing systems comprising: i) a motorized bubble producing tool system, the motorized bubble producing tool system including a reservoir, one or more bubble producing tools attached to a central hub and a motor, wherein the central hub is operably linked to the motor, and wherein the reservoir is configured to contain a bubble solution, and ii) an air stream producing system, the air stream producing system comprising a motorized blower and a vent, wherein the one or more electrical wires connect the power supply to the motor of the motorized bubble producing tool system and the motorized blower the air stream producing system, and wherein in operation the motorized blower continuously expels air in a generally horizontal direction through vent and outward from the front of the bubble making apparatus and the motor of the motorized bubble producing tool system continuously spins the central hub causing each of the one or more bubble producing tools to undergo a rotational cycle through the bubble solution contained in the reservoir and past air stream being expelled through the vent, thereby causing formation of a stream of bubbles. 66. The bubble making apparatus of embodiment 65, wherein the one or more sides of the support structure define a circular or oval shape. 67. The bubble making apparatus of embodiment 66, wherein the support structure is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. 68. The bubble making apparatus of any one of embodiments 65-67, wherein the one or more sides of the support structure define a cuboidal shape with sharp and/or curved corners. 69. The bubble making apparatus of embodiment 68, wherein the support structure has a width of 1 to 6 feet, 2 to 6 feet, 3 to 6 feet, 4 to 6 feet, 5 to 6 feet, 1 to 5 feet, 2 to 5 feet, 3 to 5 feet, 4 to 5 feet, 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 1 to 6 feet, 2 to 6 feet, 3 to 6 feet, 4 to 6 feet, 5 to 6 feet, 1 to 5 feet, 2 to 5 feet, 3 to 5 feet, 4 to 5 feet, 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet, and a height of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. 70. A bubble tower making apparatus comprising: a) a base system, the base system including a platform, a fluid trough and a base surround, the fluid trough configured to contain a bubble solution, wherein the base surround is located along the outside perimeter of the fluid trough and the fluid trough is located along the outside perimeter of the platform, b) a support frame system, the support frame system including one or more vertical support members and a top frame, wherein the one or more vertical support members span the space between the base system and the top frame, and c) a lift system, the lift system including one or more lifting pulleys, one or more control pulleys, one or more cables, and a bubble forming device, each of the one or more cables comprising a first end and a second end, wherein the one or more lifting pulleys and one or more control pulleys are secured to the top frame of the support frame system, wherein the bubble forming device conforms to the shape of the fluid trough, and wherein the one or more cables are each secured to the bubble forming device, and wherein the first end of each of the one or more cables of the lift system is secured to the bubble forming device, the one or more cables then passed through the one or more lifting pulleys and one or more controlling pulleys, thereby having the second end of each of the one or more cables on the side of the one or

more lifting pulleys and one or more controlling pulleys opposite the side of the first end of each of the one or more cables. 71. The bubble tower making apparatus of embodiment 70, wherein the base system is a circular or oval shape. 72. The bubble tower making apparatus of embodiment 71, wherein the base system is 1 to 6 feet in diameter and 2 inches to 12 inches in height, 2 to 5 in diameter and 3 inches to 10 inches in height, or 2 to 4 feet in in diameter and 4 inches to 8 inches in height. 73. The bubble tower making apparatus of any one of embodiments 70-72, wherein the platform is a circular or oval shape. 74. The bubble tower making apparatus of embodiment 73, wherein the platform is 1 to 6 feet in diameter and 2 inches to 12 inches in height, 2 to 5 in diameter and 3 inches to 10 inches in height, or 2 to 4 feet in in diameter and 4 inches to 8 inches in height. 75. The bubble tower making apparatus of any one of embodiments 70-74, wherein the fluid trough is a circular or oval shape. 76. The bubble tower making apparatus of embodiment 75, wherein the fluid trough is 1 to 6 feet in diameter and 2 inches to 12 inches in height, 2 to 5 in diameter and 3 inches to 10 inches in height, or 2 to 4 feet in in diameter and 4 inches to 8 inches in height. 77. The bubble tower making apparatus of any one of embodiments 70-76, wherein the base system is a cuboidal shape with sharp and/or curved corners. 78. The bubble tower making apparatus of embodiment 77, wherein the base system is 2 to 10 feet in width, 2 to 10 feet in length and 2 inches to 12 inches in height, 3 to 9 feet in width, 3 to 9 feet in length and 3 inches to 10 inches in height, or 4 to 8 feet in width, 4 to 8 feet in length and 4 inches to 8 inches in height. 79. The bubble tower making apparatus of any one of embodiments 70-78, wherein the platform is a cuboidal shape with sharp and/or curved corners. 80. The bubble tower making apparatus of embodiment 79, wherein the platform is 2 to 10 feet in width, 2 to 10 feet in length and 2 inches to 12 inches in height, 3 to 9 feet in width, 3 to 9 feet in length and 3 inches to 10 inches in height, or 4 to 8 feet in width, 4 to 8 feet in length and 4 inches to 8 inches in height. 81. The bubble tower making apparatus of any one of embodiments 70-80, wherein the fluid trough is a cuboidal shape with sharp and/or curved corners. 82. The bubble tower making apparatus of embodiment 81, wherein the fluid trough is 2 to 10 feet in width, 2 to 10 feet in length and 2 inches to 12 inches in height, 3 to 9 feet in width, 3 to 9 feet in length and 3 inches to 10 inches in height, or 4 to 8 feet in width, 4 to 8 feet in length and 4 inches to 8 inches in height. 83. The bubble tower making apparatus of any one of embodiments 70-82, wherein the one or more vertical support members are each 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet in height. 84. The bubble tower making apparatus of any one of embodiments 70-83, wherein the bubble forming device is a circular or oval shape. 85. The bubble tower making apparatus of any one of embodiments 70-83, wherein the bubble forming device is a cuboidal shape with sharp and/or curved corners. 86. The bubble tower making apparatus of any one of embodiments 70-85, further comprising a lighting system including lights. 87. The bubble tower making apparatus of any one of embodiments 70-86, wherein in operation, the bubble forming device submerged in the bubble solution contained in the fluid trough is lifted vertically upward out of the fluid trough using the lift system, thereby forming a bubble tower using the bubble solution contained between the bubble forming device and the bubble solution contained in the fluid trough. 88. A bubble light apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins including one or more sides and a bottom, the bottom being partially or fully transparent and/or partially or fully translucent, thereby enabling light to transmit therethrough, wherein each of the one or more basins is configured to contain a bubble solution, and b) a lighting system, the lighting system including one or more light sources, at least one power supply to generate electricity, and one or more electrical wires, wherein each of the one or more light sources is located underneath the bottom of each of one or more basins, and wherein the one or more electrical wires connect the at least one power supply to each of the one or more light sources. 89. The bubble light apparatus of embodiment 88, wherein the one or more sides of the support structure define a circular or oval shape. 90. The bubble light

apparatus of embodiment 89, wherein the support structure is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. 91. The bubble light apparatus of any one of embodiments 88-90, wherein the one or more sides of the support structure define a cuboidal shape with sharp and/or curved corners. 92. The bubble light apparatus of embodiment 91, wherein the support structure is cuboidal in shape with a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. 93. The bubble making apparatus of any one of embodiments 88-92, wherein the one or more basins includes 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. 94. The bubble light apparatus of any one of embodiments 88-93, wherein the one or more sides of each of the one or more basins define a circular or oval shape. 95. The bubble light apparatus of any one of embodiments 88-94, wherein the one or more light sources emit white light. 96. The bubble light apparatus of any one of embodiments 88-95, wherein the one or more light sources emit colored light. 97. The bubble light apparatus of any one of embodiments 88-96, wherein the top surface further comprises a lip, the lip located around the perimeter of the top surface thereby forming a top surface reservoir configured to contain a bubble solution. 98. The bubble light apparatus of any one of embodiments 88-97, further comprising one or more bubble making tools. 99. The bubble light apparatus of any one of embodiments 88-98, wherein in operation, one or more users create one or more bubbles using the bubble solution contained in the one or more basins and light being emitted from the one or more light sources shine through the one or more bubbles. 100. A bubble jet apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins and one or more vents, the one or more basins including one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) an air stream system, the air stream system including at least one motorized blower, one or more ducts, at least one power supply to generate electricity, and one or more electrical wires, wherein the one or more electrical wires connect the at least one power supply to the at least one motorized blower, wherein the bubble jet apparatus further comprises one or more bubble making tools. 101. The bubble jet apparatus of embodiment 100, wherein the one or more sides of the support structure define a circular or oval shape. 102. The bubble jet apparatus of embodiment 101, wherein the support structure is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. 103. The bubble jet apparatus of any one of embodiments 100-102, wherein the one or more sides of the support structure define a cuboidal shape with sharp and/or curved corners. 104. The bubble jet apparatus of embodiment 103, wherein the support structure is cuboidal in shape with a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet. 105. The bubble jet apparatus of any one of embodiments 100-104, wherein the support structure 2 to 5 feet, 2 to 4 feet or 2 to 3 feet in height. 106. The bubble jet apparatus of any one of embodiments 100-105, wherein the one or more basins includes 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins. 107. The bubble jet apparatus of any one of embodiments 100-106, wherein the one or more sides of each of the one or more basins define a circular or oval shape. 108. The bubble jet apparatus of any one of embodiments 100-107, wherein the support structure further includes an internal space, and each of the one or more ducts is formed from the internal space. 109. The bubble jet apparatus of embodiment any one of embodiments 100-108, wherein the internal space further comprises one or more baffles, the one or more baffles positioned in a manner to direct air flow upward through each of the one or more vents. 110. The bubble jet apparatus of any one of embodiments 100-107,

wherein the one or more ducts is formed from one or more dedicated ventilation conduits, the one or more dedicated ventilation conduits connecting at least one motorized blower to each of the one or more vents. 111. The bubble jet apparatus of any one of embodiments 100-110, wherein in operation, one or more bubbles are formed when a user positions a bubble making tool containing the bubble solution over one of the one or more vents, thereby causing air being expelled through the one of the one or more vents to pass through the bubble making tool thereby creating the one or more bubbles from the bubble solution contained in the bubble making tool. 112. A bubble pedestal apparatus comprising: a) a support structure, the support structure including one or more sides and a top surface, the top surface having one or more lips positioned around the perimeter of the top surface thereby defining a basin, wherein the basin is configured to contain a bubble solution, and b) one or more casters. wherein the bubble pedestal apparatus further comprises one or more bubble making tools. 113. The bubble pedestal apparatus of embodiment 112, wherein the one or more sides of the support structure define a circular or oval shape. 114. The bubble pedestal apparatus of embodiment 113, wherein the support structure is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance. 115. The bubble pedestal apparatus of any one of embodiments 112-114, wherein the one or more sides of the support structure define a cuboidal shape with sharp and/or curved corners. 116. The bubble pedestal apparatus of embodiment 115, wherein the support structure is cuboidal in shape with a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet. 117. The bubble pedestal apparatus of any one of embodiments 112-116, wherein the basin is triangular shape, a square shape, a rectangular shape or a pentagonal shape. 118. The bubble pedestal apparatus of any one of embodiments 112-117, wherein the support structure has a height of 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet. 119. An entertainment/educational facility comprising one or more bubble-making stations, each of the one or more stations comprising a system, the system comprising any one of embodiments 2-11, wherein the system present in each of the one or more stations is different than the system present in any of the other of the one or more stations comprising the entertainment/educational facility. 120. The entertainment/educational facility of embodiment 119, wherein the one or more stations include a first station comprising a first system and a second station comprising a second system, the first and second systems comprising any one of embodiments 2-11. 121. The entertainment/educational facility of embodiment 120, wherein the one or more stations further includes a third station comprising a third system, the third system comprising any one of embodiments 2-11. 122. The entertainment/educational facility of embodiment 121, wherein the one or more stations further includes a fourth station comprising a fourth system, the fourth system comprising any one of embodiments 2-11. 123. The entertainment/educational facility of embodiment 122, wherein the one or more stations further includes a fifth station comprising a fifth system, the fifth system comprising any one of embodiments 2-11. 124. The entertainment/educational facility of embodiment 123, wherein the one or more stations further includes a sixth station comprising a sixth system, the sixth system comprising any one of embodiments 2-11. 125. The entertainment/educational facility of embodiment 124, wherein the one or more stations further includes a seventh station comprising a seventh system, the seventh system comprising any one of embodiments 2-11. 126. The entertainment/educational facility of embodiment 125, wherein the one or more stations further includes an eighth station comprising an eighth system, the eighth system comprising any one of embodiments 2-11. 127. The entertainment/educational facility of embodiment 126, wherein the one or more stations further includes a ninth station comprising a ninth system, the ninth system comprising any one of embodiments 2-11. 128. The entertainment/educational facility of embodiment 127, wherein the one or more stations further includes a tenth station comprising a tenth system, the tenth system comprising any one of embodiments 2-11. 129. An

entertainment/educational facility comprising one or more bubble-making stations, each of the one or more stations comprising a system, wherein the system present in each of the one or more stations is different than the system present in any of the other of the one or more stations comprising the entertainment/educational facility, and wherein the system comprises any one of the following systems, a first system comprising educational information regarding the scientific principles of bubbles and a bubble making apparatus according to any one of embodiments 12-23, a second system comprising educational information regarding the scientific principles of bubbles and a gas producing apparatus according to any one of embodiments 24-38, a third system comprising educational information regarding the scientific principles of bubbles and a mobile gas producing apparatus according to any one of embodiments 39-46, a fourth system comprising educational information regarding the scientific principles of bubbles and an inflatable apparatus according to any one of embodiments 47-53, a fifth system comprising educational information regarding the scientific principles of bubbles and a bubble sheet making apparatus according to any one of embodiments 54-64, a sixth system comprising educational information regarding the scientific principles of bubbles, an activity area comprising at least one receptacle including projectiles, and a bubble making apparatus according to any one of embodiments 65-69, a seventh system comprising educational information regarding the scientific principles of bubbles and a bubble tower making apparatus according to any one of embodiments 70-87, an eighth system comprising educational information regarding the scientific principles of bubbles and a bubble light apparatus according to any one of embodiments 88-99, a ninth system comprising educational information regarding the scientific principles of bubbles and a bubble jet apparatus according to any one of embodiments 100-111, or a tenth system comprising educational information regarding the scientific principles of bubbles and a bubble pedestal apparatus according to any one of embodiments 112-118. 129. The entertainment/educational facility of embodiment 128, wherein the one or more stations include a first station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, and a second station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, wherein the system of the first station is different from the system of the second station. 130. The entertainment/educational facility of embodiment 129, wherein the one or more stations include a third station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, wherein the system of the third station is different from the system of the first and second stations. 131. The entertainment/educational facility of embodiment 130, wherein the one or more stations include a fourth station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, wherein the system of the fourth station is different from the system of the first, second and third stations. 132. The entertainment/educational facility of embodiment 131, wherein the one or more stations include a fifth station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, wherein the system of the fifth station is different from the system of the first, second, third and fourth stations. 133. The entertainment/educational facility of embodiment 132, wherein the one or more stations include a sixth station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, wherein the system of the sixth station is different from the system of the first, second, third, fourth and fifth stations. 134. The entertainment/educational facility of embodiment 133, wherein the one or more

stations include a seventh station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, wherein the system of the seventh station is different from the system of the first, second, third, fourth, fifth and sixth stations. 135. The entertainment/educational facility of embodiment 134, wherein the one or more stations include an eighth station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the seventh system, the eighth system, the ninth system or the tenth system, wherein the system of the eighth station is different from the system of the first, second, third, fourth, fifth, sixth and seventh stations. 136. The entertainment/educational facility of embodiment 135, wherein the one or more stations include a ninth station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the ninth system, the eighth system, the ninth system or the tenth system, wherein the system of the eighth station is different from the system of the first, second, third, fourth, fifth, sixth, seventh and eighth stations. 137. The entertainment/educational facility of embodiment 136, wherein the one or more stations include a tenth station comprising a system selected from any one of the first system, the second system, the third system, the fourth system, the fifth system, the sixth system, the ninth system, the eighth system, the ninth system or the tenth system, wherein the system of the tenth station is different from the system of the first, second, third, fourth, fifth, sixth, seventh, eighth and ninth stations.

(168) In closing, it is to be understood that although aspects of the present specification are highlighted by referring to specific embodiments, one skilled in the art will readily appreciate that these disclosed embodiments are only illustrative of the principles of the subject matter disclosed herein. Therefore, it should be understood that the disclosed subject matter is in no way limited to a particular, article, apparatus, methodology, or materials or methods described herein, unless expressly stated as such. In addition, those of ordinary skill in the art will recognize that certain changes, modifications, permutations, alterations, additions, subtractions and sub-combinations thereof can be made in accordance with the teachings herein disclosed without departing from the spirit of the present specification. It is therefore intended that the following appended claims and claims hereafter introduced are interpreted to include all such changes, modifications, permutations, alterations, additions, subtractions and sub-combinations as are within their true spirit and scope.

(169) Certain embodiments of the present invention are described herein. Of course, variations on these described embodiments will become apparent to those of ordinary skill in the art upon reading the foregoing disclosures and teachings. The inventor expects skilled artisans to employ such variations as appropriate, and the inventors intend for the present invention to be practiced otherwise than specifically described herein. Accordingly, this invention includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described embodiments in all possible variations thereof is encompassed by the invention unless otherwise indicated herein or otherwise clearly contradicted by context.

(170) Groupings of alternative embodiments, elements, or steps of the present invention are not to be construed as limitations. Each group member may be referred to and claimed individually or in any combination with other group members disclosed herein. It is anticipated that one or more members of a group may be included in, or deleted from, a group for reasons of convenience and/or patentability. When any such inclusion or deletion occurs, the specification is deemed to contain the group as modified thus fulfilling the written description of all Markush groups used in the appended claims.

(171) Unless otherwise indicated, all numbers expressing a characteristic, item, quantity, parameter, property, term, and so forth used in the present specification and claims are to be understood as

being modified in all instances by the term “about.” As used herein, the term “about” means that the characteristic, item, quantity, parameter, property, or term so qualified encompasses a range of plus or minus ten percent above and below the value of the stated characteristic, item, quantity, parameter, property, or term. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the specification and attached claims are approximations that may vary. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical indication should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

(172) Use of the terms “may” or “can” in reference to an embodiment or aspect of an embodiment also carries with it the alternative meaning of “may not” or “cannot.” As such, if the present specification discloses that an embodiment or an aspect of an embodiment may be or can be included as part of the inventive subject matter, then the negative limitation or exclusionary proviso is also explicitly meant, meaning that an embodiment or an aspect of an embodiment may not be or cannot be included as part of the inventive subject matter. In a similar manner, use of the term “optionally” in reference to an embodiment or aspect of an embodiment means that such embodiment or aspect of the embodiment may be included as part of the inventive subject matter or may not be included as part of the inventive subject matter. Whether such a negative limitation or exclusionary proviso applies will be based on whether the negative limitation or exclusionary proviso is recited in the claimed subject matter.

(173) Notwithstanding that the numerical ranges and values setting forth the broad scope of the invention are approximations, the numerical ranges and values set forth in the specific examples are reported as precisely as possible. Any numerical range or value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements. Recitation of numerical ranges of values herein is merely intended to serve as a shorthand method of referring individually to each separate numerical value falling within the range. Unless otherwise indicated herein, each individual value of a numerical range is incorporated into the present specification as if it were individually recited herein.

(174) The terms “a,” “an,” “the” and similar references used in the context of describing the present invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. Further, ordinal indicators—such as “first,” “second,” “third,” etc.—for identified elements are used to distinguish between the elements, and do not indicate or imply a required or limited number of such elements, and do not indicate a particular position or order of such elements unless otherwise specifically stated. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided herein is intended merely to better illuminate the present invention and does not pose a limitation on the scope of the invention otherwise claimed. No language in the present specification should be construed as indicating any non-claimed element essential to the practice of the invention.

(175) When used in the claims, whether as filed or added per amendment, the open-ended transitional term “comprising” (and equivalent open-ended transitional phrases thereof like including, containing and having) encompasses all the expressly recited elements, limitations, steps and/or features alone or in combination with unrecited subject matter; the named elements, limitations and/or features are essential, but other unnamed elements, limitations and/or features may be added and still form a construct within the scope of the claim. Specific embodiments disclosed herein may be further limited in the claims using the closed-ended transitional phrases “consisting of” or “consisting essentially of” in lieu of or as an amended for “comprising.” When used in the claims, whether as filed or added per amendment, the closed-ended transitional phrase “consisting of” excludes any element, limitation, step, or feature not expressly recited in the claims. The closed-ended transitional phrase “consisting essentially of” limits the scope of a claim to the

expressly recited elements, limitations, steps and/or features and any other elements, limitations, steps and/or features that do not materially affect the basic and novel characteristic(s) of the claimed subject matter. Thus, the meaning of the open-ended transitional phrase “comprising” is being defined as encompassing all the specifically recited elements, limitations, steps and/or features as basin as any optional, additional unspecified ones. The meaning of the closed-ended transitional phrase “consisting of” is being defined as only including those elements, limitations, steps and/or features specifically recited in the claim whereas the meaning of the closed-ended transitional phrase “consisting essentially of” is being defined as only including those elements, limitations, steps and/or features specifically recited in the claim and those elements, limitations, steps and/or features that do not materially affect the basic and novel characteristic(s) of the claimed subject matter. Therefore, the open-ended transitional phrase “comprising” (and equivalent open-ended transitional phrases thereof) includes within its meaning, as a limiting case, claimed subject matter specified by the closed-ended transitional phrases “consisting of” or “consisting essentially of.” As such embodiments described herein or so claimed with the phrase “comprising” are expressly or inherently unambiguously described, enabled and supported herein for the phrases “consisting essentially of” and “consisting of.”

(176) All patents, patent publications, and other publications referenced and identified in the present specification are individually and expressly incorporated herein by reference in their entirety for the purpose of describing and disclosing, for example, the compositions and methodologies described in such publications that might be used in connection with the present disclosure.

(177) Lastly, the terminology used herein is for the purpose of describing particular embodiments only and is not intended to limit the scope of the present invention, which is defined solely by the claims. Accordingly, the present invention is not limited to that precisely as shown and described.

Claims

1. An entertainment/educational facility comprising one or more bubble-making stations, each of the one or more stations comprising a system, wherein the system present in each of the one or more stations is different than the system present in any of the other of the one or more stations, and wherein the one or more stations comprise a first system comprising a bubble jet apparatus and educational information regarding the scientific principles of bubbles, the bubble jet apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins and one or more vents, the one or more basins including one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) an air stream system, the air stream system including at least one motorized blower, at least one power supply to generate electricity, and one or more electrical wires, wherein the one or more electrical wires connect the at least one power supply to the at least one motorized blower, and wherein the bubble jet apparatus further comprises one or more bubble making tools, and wherein in operation, one or more bubbles are formed when a user positions a bubble making tool containing the bubble solution over one of the one or more vents, thereby causing air being expelled through the one of the one or more vents to pass through the bubble making tool thereby creating the one or more bubbles from the bubble solution contained in the bubble making tool.

2. A system comprising a bubble jet apparatus and educational information regarding the scientific principles of bubbles, the bubble jet apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins and one or more vents, the one or more basins including one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) an air stream system, the air stream system including at least one motorized blower, at least one

power supply to generate electricity, and one or more electrical wires, wherein the one or more electrical wires connect the at least one power supply to the at least one motorized blower, wherein the bubble jet apparatus further comprises one or more bubble making tools, and wherein in operation, one or more bubbles are formed when a user positions a bubble making tool containing the bubble solution over one of the one or more vents, thereby causing air being expelled through the one of the one or more vents to pass through the bubble making tool thereby creating the one or more bubbles from the bubble solution contained in the bubble making tool.

3. A bubble jet apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins and one or more vents, the one or more basins including one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) an air stream system, the air stream system including at least one motorized blower, at least one power supply to generate electricity, and one or more electrical wires, wherein the one or more electrical wires connect the at least one power supply to the at least one motorized blower, wherein the bubble jet apparatus further comprises one or more bubble making tools, and wherein in operation, one or more bubbles are formed when a user positions a bubble making tool containing the bubble solution over one of the one or more vents, thereby causing air being expelled through the one of the one or more vents to pass through the bubble making tool thereby creating the one or more bubbles from the bubble solution contained in the bubble making tool.

4. The bubble jet apparatus of claim 3, wherein the one or more sides of the support structure define a circular or oval shape.

5. The bubble jet apparatus of claim 4, wherein the support structure is circular or oval in shape with a cross-sectional radius of 1 to 6 feet, 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 6 feet, 2 to 5 feet, 2 to 4 feet, 2 to 3 feet, 3 to 6 feet, 3 to 5 feet, or 3 to 4 feet at its shortest distance.

6. The bubble jet apparatus of claim 3, wherein the one or more sides of the support structure define a cuboidal shape with sharp and/or curved corners.

7. The bubble jet apparatus of claim 6, wherein the support structure is cuboidal in shape with a width of 1 to 4 feet, 2 to 4 feet, 3 to 4 feet, 1 to 3 feet, 2 to 3 feet, or 1 to 2 feet and a length of 4 to 15 feet, 4 to 12 feet, 4 to 10 feet, 4 to 8 feet, 4 to 6 feet, 6 to 15 feet, 6 to 12 feet, 6 to 10 feet, 6 to 8 feet, 8 to 15 feet, 8 to 12 feet or 8 to 10 feet.

8. The bubble jet apparatus of claim 3, wherein the support structure is 1 to 5 feet, 1 to 4 feet, 1 to 3 feet, 2 to 3 feet or 1 to 2 feet in height.

9. The bubble jet apparatus of claim 3, wherein the one or more sides of the support structure define a closed polygonal shape.

10. The bubble jet apparatus of claim 3, wherein the closed polygonal shape is a triangle or pentagon.

11. The bubble jet apparatus of claim 3, wherein the one or more sides of each of the one or more basins define a circular or oval shape.

12. The bubble jet apparatus of claim 3, wherein the one or more basins is one basin.

13. The bubble jet apparatus of claim 3, wherein the one or more basins includes 2 to 10 basins, 3 to 9 basins, 4 to 8 basins, 3 to 7 basins, 4 to 7 basins, 5 to 7 basins, 4 to 6 basins, or 5 or 6 basins.

14. The bubble jet apparatus of claim 3, wherein the one or more sides of each of the one or more basins is about 1 inch to 5 inches, about 2 to 4 inches, or about 3 inches in height.

15. The bubble jet apparatus of claim 3, wherein the one or more vents is one vent.

16. The bubble jet apparatus of claim 3, wherein the one or more vents includes 2 to 10 vents, 3 to 9 vents, 4 to 8 vents, 3 to 7 vents, 4 to 7 vents, 5 to 7 vents, 4 to 6 vents, or 5 or 6 vents.

17. The bubble jet apparatus of claim 3, wherein the air stream system further comprises one or more baffles, the one or more baffles positioned in a manner to direct air flow upward through each of the one or more vents.

18. The bubble jet apparatus of claim 3, wherein the air stream system further comprises one or

more ducts, the one or more ducts forming a conduit between the at least one motorized blower and the one or more vents.

19. The bubble jet apparatus of claim 3, wherein the bubble making apparatus is portable.

20. The entertainment/educational facility of claim 1, further comprising any one or more of the following systems, a second system comprising a bubble making apparatus and educational information regarding the scientific principles of bubbles, the bubble making apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom, a top opening, one or more basins, a trough and a reservoir, wherein the one or more basins each have one or more sides, a bottom and a port, the port positioned at the bottom of the one or more basins, and the one or more basins configured to contain a bubble solution, wherein the trough comprises a trough bottom biased toward the reservoir in a manner that directs the bubble solution falling onto the trough bottom towards the reservoir, and wherein the reservoir is configured to contain a bubble solution, and b) a pumping system, the pumping system including one or more pumps and one or more conduits, wherein the one or more conduits connect at least one pump to the port of each of the one or more basins, and wherein in operation the at least one pump continuously transports the bubble solution contained in the reservoir through the one or more conduits to the port of each of the one or more basins, thereby filling each of the one or more basins with the bubble solution; or a third system comprising a gas producing apparatus and educational information regarding the scientific principles of bubbles, the gas producing apparatus comprising: a) a base, the base comprising one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins each comprising one or more sides and a bottom, wherein each of the one or more basins is configured to contain a bubble solution, and b) a smoke-like fog generating apparatus, the smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid path until reaching the second end of each of the one or more hoses, and wherein each of the one or more basins is configured to receive the second end of each of the one or more hoses, and wherein in operation dry ice and water placed inside internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses; or a fourth system comprising a mobile gas producing apparatus and educational information regarding the scientific principles of bubbles, the mobile gas producing apparatus comprising: a) a carrier, and b) a mobile smoke-like fog generating apparatus, the mobile smoke-like fog generating apparatus comprising i) a body having one or more sides, a bottom, a top opening opposite the bottom, the resulting interior space defining an internal reservoir, ii) a heating element, the heating element abutting the bottom or the one or more sides of the body, and iii) a lid, the lid including one or more ports and one or more hoses, the one or more hoses each comprising a first end and a second end, wherein the first end of each of the one or more hoses is attached to each of the one or more ports, wherein when the lid is closed over the top opening of the body, the internal reservoir, one or more ports and one or more hoses form a continuous fluid path until reaching the second end of each of the one or more hoses, wherein each of the one or more basins is configured to receive the second end of each of the one or more hoses, and wherein in operation dry ice and water placed inside the internal reservoir sublimates to produce gas that flows from the internal reservoir through the each one or more ports and each of the one or more hoses, thereby expelling the gas from the second end of each of the one or more hoses; or a fifth system comprising an inflatable apparatus and educational information regarding the scientific principles

of bubbles, the inflatable apparatus comprising: a) a first inflated chamber, the first inflated chamber being substantially spherical and curved in shape with a flat bottom, b) a second inflated chamber being substantially cuboidal in shape, the second inflated chamber comprising an entrance enabling a user access from outside the apparatus into the second inflated chamber, and c) an inflation system, the inflation system including an inflation device and one or more air conduits, wherein the first inflated chamber has a contiguous portion with the second inflated chamber, and wherein an opening is present in the contiguous portion to create a pathway between the first inflated chamber to the second inflated chamber, wherein the one or more air conduits connect the inflation device to at least the first inflated chamber, and wherein in operation the inflation device expels air through the one or more conduits and into at least the first inflated chamber, thereby inflating the first inflated chamber; or a sixth system comprising a bubble sheet making apparatus and educational information regarding the scientific principles of bubbles, the bubble sheet making apparatus comprising: a) a frame system, the frame system including a bottom trough, one or more vertical support members and a top support structure, the bottom trough including one or more sides, a bottom and a top opening opposite the bottom, the resulting interior space defining a reservoir, wherein the bottom trough is configured to contain a bubble solution, wherein the one or more vertical support members span the space between the bottom trough and the top support structure, b) a lift system, the lift system including one or more pulleys and one or more lifting cords, each of the one or more lifting cords comprising a first end and a second end, wherein the one or more pulleys are secured to the top support structure of the frame system, and c) a bar system, the bar system comprising a top bar, one or more depending cords, and a bottom bar, and each of the one or more depending cords comprising at least a free end and composed of a collapsible material, wherein the top bar comprises a first end, a second end and an absorbent material, and wherein the one or more depending cords is secured to the top bar and the at least a free end of the one or more depending cords is secured to the bottom bar, and wherein the first end of each of the one or more lifting cords of the lift system is secured to the top bar, the one or more lifting cords then passed through the one or more pulleys, thereby having the second end of each of the one or more lifting cords on the side of the one or more pulleys opposite the side of the first end of each of the one or more lifting cords, and wherein in operation, the bar system submerged in the bubble solution contained in the bottom trough is lifted vertically upward out of the bottom trough using the lift system, thereby forming a bubble sheet using the bubble solution contained within a framework created by the top bar, one or more depending cords and the bottom bar; or a seventh system comprising a bubble making apparatus and educational information regarding the scientific principles of bubbles, a) the bubble making apparatus comprising: i) a support structure, the support structure having one or more sides, a bottom and a top, and comprising a power system and a ventilation system, the power system including a power supply to generate electricity and one or more electrical wires, and ii) one or more bubble producing systems, each of the one or more bubble producing systems comprising: 1) a motorized bubble producing tool system, the motorized bubble producing tool system including a reservoir, one or more bubble producing tools attached to a central hub and a motor, wherein the central hub is operably linked to the motor, and wherein the reservoir is configured to contain a bubble solution, and 2) an air stream producing system, the air stream producing system comprising a motorized blower and a vent, wherein the one or more electrical wires connect the power supply to the motor of the motorized bubble producing tool system and the motorized blower the air stream producing system, and wherein in operation the motorized blower continuously expels air in a generally horizontal direction through vent and outward from the front of the bubble making apparatus and the motor of the motorized bubble producing tool system continuously spins the central hub causing each of the one or more bubble producing tools to undergo a rotational cycle through the bubble solution contained in the reservoir and past air stream being expelled through the vent, thereby causing formation of a stream of bubbles, and b) an activity area, the activity area comprising at least one receptacle including

projectiles, and c) educational information regarding the scientific principles of bubbles; or an eighth system comprising a bubble tower making apparatus and educational information regarding the scientific principles of bubbles, the bubble tower making apparatus comprising: a) a base system, the base system including a platform, a fluid trough and a base surround, the fluid trough configured to contain a bubble solution, wherein the base surround is located along the outside perimeter of the fluid trough and the fluid trough is located along the outside perimeter of the platform, b) a support frame system, the support frame system including one or more vertical support members and a top frame, wherein the one or more vertical support members span the space between the base system and the top frame, and c) a lift system, the lift system including one or more lifting pulleys, one or more control pulleys, one or more cables, and a bubble forming device, each of the one or more cables comprising a first end and a second end, wherein the one or more lifting pulleys and one or more control pulleys are secured to the top frame of the support frame system, wherein the bubble forming device conforms to the shape of the fluid trough, and wherein the one or more cables are each secured to the bubble forming device, and wherein the first end of each of the one or more cables of the lift system is secured to the bubble forming device, the one or more cables then passed through the one or more lifting pulleys and one or more controlling pulleys, thereby having the second end of each of the one or more cables on the side of the one or more lifting pulleys and one or more controlling pulleys opposite the side of the first end of each of the one or more cables, and wherein in operation, the bubble forming device submerged in the bubble solution contained in the fluid trough is lifted vertically upward out of the fluid trough using the lift system, thereby forming a bubble tower using the bubble solution contained between the bubble forming device and the bubble solution contained in the fluid trough; or a ninth system comprising a bubble light apparatus and educational information regarding the scientific principles of bubbles, the bubble light apparatus comprising: a) a support structure, the support structure including one or more sides, a bottom and a top surface, the top surface having one or more basins, the one or more basins including one or more sides and a bottom, the bottom being partially or fully transparent and/or partially or fully translucent, thereby enabling light to transmit therethrough, wherein each of the one or more basins is configured to contain a bubble solution, and b) a lighting system, the lighting system including one or more light sources, at least one power supply to generate electricity, and one or more electrical wires, wherein each of the one or more light sources is located underneath the bottom of each of one or more basins, and wherein the one or more electrical wires connect the at least one power supply to each of the one or more light sources, and wherein in operation, one or more users create one or more bubbles using the bubble solution contained in the one or more basins and light being emitted from the one or more light sources shine through the one or more bubbles; or a tenth system comprising a bubble pedestal apparatus and educational information regarding the scientific principles of bubbles, the bubble pedestal apparatus comprising: a) a support structure, the support structure including one or more sides and a top surface, the top surface having one or more lips positioned around the perimeter of the top surface thereby defining a basin, wherein the basin is configured to contain a bubble solution, and b) one or more casters, wherein the bubble pedestal apparatus further comprises one or more bubble making tools.
