

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12413098

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Semmens; John Daniel et al.

Systems and methods for a charging cart of a wireless harness automated measurement system

Abstract

According to some embodiments, an apparatus for charging a wireless harness automated measurement system (WHAMS) includes a charging cart, a mobile frame, a plurality of light-emitting diode (LED) indicators, and a plurality of charging slots. The charging cart may charge a plurality of wireless test modules (WTMs) of the WHAMS. The mobile aluminum frame may support the charging cart. The plurality of light-emitting diode (LED) indicators may identify a status of the plurality of the WTMs during testing of the WHAMS. The plurality of charging slots may charge the plurality of WTMs. Each of the plurality of charging slots is associated with a respective one of the plurality of LED indicators.

Inventors: Semmens; John Daniel (Sandy Springs, GA), Braddy; John Foster (Cumming, GA), Bell; Kevin (Vestal, NY), Franklin; Samuel Jasper (Marietta, GA), Garner; Gibson Richard (Marietta, GA), Masem; Amy Yuan (Lancaster, CA), Longan; Robert Blake (Santa Clarita, CA)

Applicant: Lockheed Martin Corporation (Bethesda, MD)

Family ID: 92302528

Assignee: Lockheed Martin Corporation (Bethesda, MD)

Appl. No.: 18/468156

Filed: September 15, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20250096606 A1

Mar. 20, 2025

Publication Classification

Int. Cl.: B62B3/00 (20060101); G01R31/52 (20200101); G01R31/58 (20200101); G01R31/67 (20200101); H02J7/00 (20060101); H02J13/00 (20060101); H02J50/00 (20160101); H02J50/30 (20160101); H02J50/40 (20160101)

U.S. Cl.:

CPC H02J50/005 (20200101); B62B3/005 (20130101); G01R31/52 (20200101); G01R31/58 (20200101); G01R31/67 (20200101); H02J7/0013 (20130101); H02J7/0044 (20130101); H02J13/00002 (20200101); H02J13/00022 (20200101); H02J50/30 (20160201); H02J50/402 (20200101); H02J2310/40 (20200101)

Field of Classification Search

CPC: B62B (3/005); G01R (31/50-60); G01R (31/66-69); H02J (7/0013); H02J (7/0042); H02J (7/0044); H02J (7/0045); H02J (50/005); H02J (50/10); H02J (50/12); H02J (50/402)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5072185	12/1990	Rockwell	N/A	N/A
5852796	12/1997	Stepanenko, Jr.	N/A	N/A
6222374	12/2000	Shoemaker	N/A	N/A
6718284	12/2003	Smith et al.	N/A	N/A
7881887	12/2010	Kinahan	N/A	N/A
8373383	12/2012	Dandekar et al.	N/A	N/A
8547108	12/2012	Lussier	N/A	N/A
8912800	12/2013	Gervais	N/A	N/A
8934254	12/2014	Petrick et al.	N/A	N/A
9166417	12/2014	Muramatsu et al.	N/A	N/A
9250283	12/2015	Johnson et al.	N/A	N/A
9664722	12/2016	Ordonio et al.	N/A	N/A
9810732	12/2016	Lussier	N/A	N/A
9812892	12/2016	Miller et al.	N/A	N/A
10044205	12/2017	Voelz	N/A	H02J 7/0013
10088501	12/2017	Lussier	N/A	N/A
10170920	12/2018	Robustelli et al.	N/A	N/A
10587149	12/2019	Wikstrand	N/A	N/A
10697999	12/2019	Lussier	N/A	N/A
10989737	12/2020	Lussier	N/A	N/A
10996286	12/2020	Schmier, II et al.	N/A	N/A
11271427	12/2021	Miller et al.	N/A	N/A
2011/0282607	12/2010	Tunnell	N/A	N/A
2015/0293163	12/2014	Lebreton et al.	N/A	N/A
2016/0084902	12/2015	Westbrook et al.	N/A	N/A
2016/0377665	12/2015	Caravella	324/539	G01R 1/0416
2017/0063133	12/2016	Sultenfuss	N/A	H02J 7/0042
2017/0264112	12/2016	Tandai et al.	N/A	N/A

2017/0331318	12/2016	Jankins	N/A	H02J 7/0013
2018/0017608	12/2017	Nithyanandan et al.	N/A	N/A
2019/0299942	12/2018	Shih et al.	N/A	N/A
2020/0064387	12/2019	Hulsen et al.	N/A	N/A
2020/0174058	12/2019	Schmier, II	N/A	G01R 31/69
2021/0218288	12/2020	Lu et al.	N/A	N/A
2021/0223333	12/2020	Schmier, II et al.	N/A	N/A
2021/0274649	12/2020	Szelest et al.	N/A	N/A
2021/0305831	12/2020	Wan	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102681539	12/2011	CN	N/A
203133218	12/2012	CN	N/A
103499967	12/2013	CN	N/A
104615444	12/2014	CN	N/A
104917258	12/2014	CN	N/A
104953685	12/2014	CN	N/A
109470974	12/2014	CN	N/A
204706933	12/2014	CN	N/A
105425099	12/2015	CN	N/A
205657446	12/2015	CN	N/A
106646082	12/2016	CN	N/A
106855600	12/2016	CN	N/A
107367373	12/2016	CN	N/A
108767957	12/2017	CN	N/A
110829614	12/2019	CN	N/A
108828362	12/2019	CN	N/A
111948427	12/2019	CN	N/A
112698244	12/2020	CN	N/A
212908116	12/2020	CN	N/A
213069014	12/2020	CN	N/A
214045626	12/2020	CN	N/A
214069675	12/2020	CN	N/A
111645617	12/2020	CN	N/A
114122803	12/2021	CN	N/A
0902521	12/2007	EP	N/A
2602000	12/2021	GB	N/A
100310971	12/2000	KR	N/A
100335357	12/2001	KR	N/A
200447162	12/2008	KR	N/A
101378427	12/2013	KR	N/A
20180001950	12/2017	KR	N/A
102133155	12/2019	KR	N/A
1020210107374	12/2020	KR	N/A
2013076087	12/2012	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report corresponding to European Patent Application No. 24194427.1, dated Mar. 25, 2025, 8 pages. cited by applicant

Background/Summary

TECHNICAL FIELD

(1) This disclosure relates in general to implementation of a mobile charging cart of a wireless harness automated measurement system (WHAMS), and more particularly to the WHAMS charging systems and methods.

BACKGROUND

(2) Electrical wiring harnesses are utilized in many different industries and vehicles. For example, large and complex electrical wiring harnesses with numerous electrical wires and connectors are utilized by the aerospace industry in the production of aircraft. As another example, electrical wiring harnesses are utilized by the automobile industry in the production of automobiles. Electrical wiring harnesses for vehicles such as aircraft and automobiles must typically be rigorously and thoroughly tested in order to ensure that there are no defects in connectors or electrical wires of the electrical wiring harness. For example, electrical wiring harnesses are tested to ensure there are no shorted wires, no swapped connector pins, no damaged wires, and the like.

SUMMARY OF THE DISCLOSURE

(3) According to some embodiments, a system includes a computer system and a plurality of wireless test modules. Each wireless test module includes a wireless transceiver and is operable to physically couple to an electrical wiring harness. The computer system is operable to send test instructions to the plurality of wireless test modules according to an automated test plan. Each wireless test module is operable to wirelessly receive one or more of the plurality of test instructions from the computer system using the wireless transceiver and perform one or more tests on the electrical wiring harness according to received one or more test instructions from the computer system. Each wireless test module is further operable to wirelessly communicate test results to the computer system using the wireless transceiver.

(4) According to some embodiments, a system includes a computer system and a wireless test module. The wireless test module is operable to physically couple to an electrical wiring harness. The wireless test module includes a wireless transceiver. The computer system is operable to send a plurality of test instructions to the wireless test module according to an automated test plan. The wireless test module is operable to wirelessly receive one or more of the plurality of test instructions from the computer system using the wireless transceiver and perform one or more tests on the electrical wiring harness according to the received one or more test instructions from the computer system. The wireless test module is further operable to wirelessly communicate test results to the computer system using the wireless transceiver.

(5) According to some embodiments, a system includes hot-swap connectors for connecting a chassis of a wireless test module to a variable front end of the wireless test module. The variable front end of the wireless test module is operable to mate to an aircraft connector. The hot-swap connectors include a WTM side hot-swap connector and a front end side hot-swap connector located between the chassis of the wireless test module and the variable front end of the wireless test module. The WTM side hot-swap connector is operable to mate to a front end side hot-swap connector to connect the chassis of the wireless test module to the variable front end of the wireless test module. The WTM side hot-swap connector includes a female connector, an alignment peg configured to couple to the variable front end of the wireless test module, a slip ring configured to secure the wireless test module in place, and an electrically erasable programmable read-only

memory (EEPROM) read/write wire integrated on a circuit board operable to read/write data of the aircraft connector. The front end side hot-swap connector includes a male connector, an alignment peg configured to couple to the chassis of the wireless test module, a thread configured to couple to a slip ring of a WTM side hot-swap connector, and an EEPROM integrated on a circuit board operable to store data of the aircraft connector.

(6) According to some embodiments, the WTM side hot-swap connector is further operable to attach the variable front end of the wireless test module to the chassis of the wireless test module. The WTM side hot-swap connector is further operable to detach the variable front end of the wireless test module from the chassis of the wireless test module. The WTM side hot-swap connector is further operable to transfer the data to the wireless test module when the chassis of the wireless test module and the variable front end of the wireless test module mate. The WTM side hot-swap connector is a universal connector located at an end of the chassis of the wireless test module that is attached to a front end side hot-swap connector located at an end of the variable front end of the wireless test module. The wireless test module is further operable to wirelessly communicate, using a wireless transceiver, with a computer system to transfer the data stored on an EEPROM associated with the EEPROM read/write wire. The female connector includes a plurality of contacts in a range of 48 contacts to 128 contacts. The EEPROM read/write wire is configured to couple to the chassis of the wireless test module. The WTM side hot-swap connector further includes a jumper harness configured to couple to the wireless test module. The WTM side hot-swap connector is operable to swap to a different wireless test module with address information updated automatically in real time when the wireless test module malfunctions.

(7) According to some embodiments, the front end side hot-swap connector is further operable to attach the variable front end of the wireless test module to the chassis of the wireless test module. The front end side hot-swap connector is further operable to detach the variable front end of the wireless test module from the chassis of the wireless test module. The front end side hot-swap connector is further operable to transfer the data to the wireless test module when the chassis of the wireless test module and the variable front end of the wireless test module mate. The front end side hot-swap connector is a universal connector located at an end of the variable front end of the wireless test module that is attached to a WTM side hot-swap connector located at an end of the chassis of wireless test module. The male connector includes a plurality of contacts in a range of 48 contact to 128 contacts. The front end side hot-swap connector further includes a plurality of connectors configured to couple to a wire jumper of the aircraft connector. The wireless test module is further operable to wirelessly communicate, using a wireless transceiver, with a computer system to transfer the data stored on the EEPROM. The data on the EEPROM is automatically incorporated into a testing software of the computer system without human data entry. The front end side hot-swap connector is further operable to swap to a different wireless test module with address information updated automatically in real time when the wireless test module malfunctions.

(8) According to some embodiments, a system includes a battery pack module for a wireless test module. The battery pack module includes a wireless charging battery, a wireless battery pack holder operable to contain the wireless charging battery, an injected molded pogo pin holder comprising a plurality of pogo pins, and a wireless charging receiver operable to wirelessly charge the wireless charging battery. The injected molded pogo pin holder is coupled to the wireless battery pack holder using a set of screws. The injected molded pogo pin holder is operable to couple to the wireless test module. The battery pack module includes a steel retractable spring plunger comprising pull rings operable to hold the battery pack module together by attaching to the WTM using a second set of screws. The battery pack module includes a magnet attached to the wireless charging receiver operable to latch onto the WTM. The wireless charging receiver includes a 5 Volt (V) Qi standard wireless charging receiver comprising a magnetic plate compatible with the magnet. The wireless battery pack holder is a three-dimensional (3D) printed piece comprising

a shape that allows the wireless battery pack holder to slip over an end of the WTM. The WTM is operable to perform one or more tests to validate an electrical wiring harness according to a plurality of test instructions received from a computer system. The one or more tests are selected from a plurality of tests comprising a continuity check, a voltage isolation check, a diode polarity check, and a resistance measurement check. The WTM is operable to communicate wirelessly with the computer system using WI-FI, Bluetooth, or Zigbee. The WTM includes an electrical connector that is operable to mate to a wiring harness connector of the electrical wiring harness.

(9) According to some embodiments, a system includes a computer system and a computer-implemented method for operating a plurality of wireless test modules of a WHAMS. The computer-implemented method may use a computer server to access a plurality of electrical wiring harnesses, testing criteria, and the WHAMS. Each of the plurality of electrical wiring harnesses is connected to a respective endpoint of a wireless test module of the WHAMS. The computer-implemented method may generate a test plan for the plurality of electrical wiring harnesses based on the testing criteria and select a plurality of wireless test modules using the test plan and the WHAMS. In particular, the test plan includes a map of the plurality of electrical wiring harnesses, a plurality of harness connections associated with each of the plurality of wireless test modules, a hookup file, and a plurality of testing associated with the plurality of electrical wiring harnesses. The hookup file defines the plurality of wireless test modules assigned to the plurality of harness connections. For example, the test plan is generated using additional harness information of splices, passive equipment, and resignation of loose leads. As another example, the test plan is generated to check wires and unused pins in network configurations for each of the plurality of electrical wiring harnesses. The computer-implemented method may use the plurality of wireless test modules to perform one or more tests on the plurality of electrical wiring harnesses according to the plurality of test instructions. The one or more tests are selected from a plurality of tests comprising a continuity check, a voltage isolation check, a time domain reflectometer (TDR) test, a fiberoptic test, a diode polarity check, and a resistance measurement check. The computer-implemented method may use the plurality of WTMs to wirelessly communicate test results to the computer server for display. The computer-implemented method may implement a WTM board support package to apply a core operating application for the plurality of wireless test modules to perform the one or more tests on the plurality of electrical wiring harnesses according to the plurality of test instructions. The computer-implemented method may implement a custom power controller suite to manage a plurality of batteries for the plurality of wireless test modules. The computer-implemented method may implement a two-way testing approach to perform the one or more tests on the plurality of electrical wiring harnesses according to the plurality of test instructions. The computer-implemented method may evaluate a status of test results through color coded reporting by highlighting the test results using different colors. The computer-implemented method may wirelessly communicate with the plurality of wireless test modules to update a software package and one or more smart test adaptors associated with each of the plurality of wireless test modules using part numbers and pin configuration data of the one or more smart test adaptors.

(10) According to some embodiments, a system includes a system and a computer-implemented method for operating a large module or a small module of a wireless test module. The system may include a wireless transceiver, an electrical wiring harness, and a wireless test module. The wireless test module is operable to physically couple to the electrical wiring harness. The wireless test module includes a chassis and a variable front end connected to the chassis using hot-swap connectors. The chassis includes a plurality of electrical relays designed for high voltage capable solid state multiplexing and a rechargeable battery. In particular, the chassis includes a central processing and memory block and a circuitry operable to determine measurements for manufacturing and debugging the electrical wiring harness. The variable front end includes an electrical connector operable to couple to a wiring harness connector of the electrical wiring harness. For example, the electrical connector supports up to a 128 pin connector. As another

example, the electrical connector supports up to a 48 pin connector. The variable front end is a removable portion of the wireless test module. The variable front end includes a hot-swap interface to be rapidly interchangeable for different connectors.

(11) According to some embodiments, the wireless test module is operable to wirelessly receive, using the wireless transceiver, a plurality of test instructions according to an automated test plan from a computer system. The wireless test module is further operable to perform, using the variable front end, one or more tests on the electrical wiring harness according to the plurality of test instructions. The one or more tests are selected from a plurality of tests comprising a continuity check, a voltage isolation check, a TDR test, a fiberoptic test, a diode polarity check, and a resistance measurement check. The wireless test module is further operable to wirelessly communicate, using the wireless transceiver, test results to the computer system. The wireless test module has a shape selected from a plurality of shapes comprising a prism shape, a pyramid shape, a cylindrical shape, and a sphere shape. The wireless test module is further operable to communicate wirelessly with the computer system using WI-FI, Bluetooth, or Zigbee. The wireless test module is further operable to apply pick-by-light functionality for initial hardware selection and harness hookup processes.

(12) According to some embodiments, the wireless test module is further operable to apply an internal power source to one or more electrical wires of the electrical wiring harness in order to perform a test on the electrical wiring harness, wherein the internal power source is a high voltage source or a low voltage source. The wireless test module is further operable to replace an inoperable chassis with another available unit in case of malfunction. The wireless test module is further operable to generate a low voltage output of approximately 2.4 Volts (V) for a resistance/continuity test. The wireless test module is further operable to measure resistance with an accuracy of $10\% \pm 1$ ohm for a resistance in a 1 ohm-50 ohm range. The wireless test module is further operable to measure resistance with an accuracy of $5\% \pm 1$ ohm for a resistance in a 51 ohm-250 ohm range. The wireless test module is further operable to measure resistance with an accuracy of $10\% \pm 1$ ohm for a resistance in a 251 ohm-1M ohm range. The wireless test module is further operable to generate a voltage output within a range of 100V to 500V for high voltage testing. The wireless test module is further operable to measure resistance with an accuracy in a range of 6% and 10% using high voltages. The wireless test module is further operable to identify the variable front end.

(13) According to some embodiments, a system includes an apparatus for charging a WHAMS. The apparatus includes a charging cart, a mobile aluminum frame, a plurality of light-emitting diode (LED) indicators, and a plurality of charging slots. The WHAMS include a plurality of wireless test modules. Each of the plurality of charging slots is associated with a respective wireless test module of the WHAMS. The charging cart is operable to charge the plurality of wireless test modules of the WHAMS. The mobile aluminum frame is operable to support the charging cart. The plurality of LED indicators are operable to identify a status of the plurality of the wireless test modules during setup and storage of the WHAMS.

(14) According to some embodiments, the charging cart further includes a power supply operable to supply a power of 1500 Watts (W) to charge the plurality of wireless test modules in parallel. The charging cart is a double deck charging cart with a plurality of charging slots in a range of 150 charging slots to 200 charging slots. The charging cart is a single deck charging cart with a plurality of charging slots in a range of 50 charging slots to 100 charging slots. The charging cart is a mini charging cart with a plurality of charging slots in a range of 20 charge slots to 30 charging slots. The charging cart includes a foundation assembled by a plurality of sheets and pipes, the foundation including one or more decks welded on the charging cart to allocate the plurality of charging slots. The plurality of charging slots are keyed slots to receive the plurality of WTMs to ensure the plurality of WTMs are correctly placed. The charging cart is connected to the frame using bolts. Each of the plurality of LED indicators includes a red LED and a green LED. Each of

the plurality of LED indicators turns red to indicate that an identified WTM associated with the respective LED indicator is currently charging. Each of the plurality of LED indicators turns green to indicate an identified WTM associated with the respective LED indicator to locate before testing. Each of the plurality of LED indicators turns off to indicate that an identified WTM associated with the respective LED indicator finishes charging. Each of the plurality of charging slots uses a 4 pogo pin layout to charge the plurality of wireless test modules. The 4 pogo pin layout includes a 5 Volt (V) pin, a ground pin, a green LED pin, and a red LED pin.

(15) According to some embodiments, a system includes a computer system and a calibration fixture. The calibration fixture is operable to calibrate a wireless test module of a WHAMS. The wireless test module includes a plurality of field effect transistors (FETs). The plurality of FETs may be optically isolated MOFETs. The calibration fixture includes a plurality of resistors. The calibration fixture is operable to measure a resistance calibration value by measuring a first resistance value and a second resistance value of the plurality of FETs in a plurality of internal measurement tests for the wireless test module. The calibration fixture is operable to perform a resistance accuracy test (RAT) using the plurality of resistors of the calibration fixture on the wireless test module. The RAT may select a resistor from the plurality of resistors of the calibration fixture and a test associated with the WTM, wherein the resistor is associated with a target resistor value. The RAT may measure, using the calibration fixture and the test, a plurality of calibration factors. The RAT may determine a measured resistor value using the plurality of calibration factors. The RAT may store the measured resistor value and the target resistor value in a database of the computer server. The plurality of FETs includes a high side FET having a high side resistance and a low side FET having a low side resistance. The test is selected from a plurality of tests comprising a continuity check, a voltage isolation check, a diode polarity check, and a resistance measurement check. The first resistance value of the FETs measures the high side resistance associated with the high side FET. The second resistance value of the FETs measures a summation of both the high side resistance associated with the high side FET and the low side resistance associated with the low side FET. The first resistance value is in a range of 80 ohms to 90 ohms and the second resistance value is in a range of 120 ohms to 140 ohms. The plurality of resistors have a plurality of resistor values ranging from 1 ohm to 50 Mohms. The plurality of calibration factors for a continuity test includes a high side calibration indicator on a source side, a high side calibration factor on a sink side, and an initial resistor value. The measured resistor value for the continuity test is determined by subtracting the high side calibration indicator on the source side and the high side calibration factor on the sink side from the initial resistor value. The calibration fixture is further operable to perform a plurality of RATs on the WTM using the plurality of resistors of the calibration fixture. The calibration fixture is further operable to store the plurality of calibration factors and RAT history associated with the RAT in the database of the computer server. The calibration fixture is further operable to perform a controlled periodic calibration to the WHAMS to detect a potential mode of failure using resistance of the FETs drifting over a period of time.

(16) Technical advantages of certain embodiments may include providing improved systems and methods for testing electrical wiring harnesses utilized in aircraft, automobile, or other vehicles and devices. The wireless harness automated measurement systems and methods of the present disclosure provide a unique combination of hardware flexibility and mobility for application in all phases of electrical wiring harness testing. Instead of the typical bulky testing cabinets with hard-wired adaptors, the disclosed embodiments utilize one or more wireless test modules that physically couple to an electrical wiring harness under test and then wirelessly transmit test results back to a central computer. This provides a wireless and scalable architecture that ensures the maximum utilization of the hardware. The wireless communication ability of the wireless test modules opens doors to electrical testing in environments that were previously difficult to access by hard-wired testing systems (e.g., by cabinet-style electrical relay box test systems with hard-wired test cable adaptors).

(17) Furthermore, the minimalistic equipment requirements to begin testing lowers testing entry barriers and increase the efficiency of the system. The disclosed embodiments provide simplistic information input formats that guarantees fast and automated test plan creation with little or no manual tasks required by an operator. Other technical advantages will be readily apparent to one skilled in the art from the following figures, descriptions, and claims. Moreover, while specific advantages have been enumerated above, various embodiments may include all, some, or none of the enumerated advantages.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a more complete understanding of the disclosed embodiments and their features and advantages, reference is now made to the following description, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 illustrates a wireless harness automated measurement system, according to some embodiments;
- (3) FIGS. 2A-2B illustrate testing of an electrical wiring harness by the wireless harness automated measurement system of FIG. 1, according to some embodiments;
- (4) FIG. 3 illustrates a wireless test module that may be utilized by the wireless harness automated measurement system of FIG. 1, according to some embodiments;
- (5) FIG. 4 illustrates an exploded view of the wireless test module of FIG. 3, according to some embodiments;
- (6) FIG. 5 illustrates an internal view of the wireless test module of FIG. 3, according to some embodiments;
- (7) FIG. 6 illustrates a functional block diagram of the wireless test module of FIG. 3, according to some embodiments;
- (8) FIG. 7A illustrates a WTM side hot-swap connector coupling to a variable front end of FIG. 3, according to some embodiments;
- (9) FIGS. 7B and 7C illustrate a front end side hot-swap connector coupling to the wireless test module of FIG. 3, according to some embodiments;
- (10) FIGS. 8A-8C illustrate example variable front ends that may be installed on the wireless test module of FIG. 3, according to some embodiments;
- (11) FIGS. 9A-9C illustrate a battery pack for a wireless test module, according to some embodiments;
- (12) FIG. 10 illustrates an injected molded pogo pin holder of the battery pack of FIGS. 9A-9C, according to some embodiments;
- (13) FIGS. 11A-11F illustrate charging cart systems for storing multiple wireless test modules, according to some embodiments;
- (14) FIGS. 12-14D illustrate more details of the charging cart of FIGS. 11A-11F, according to some embodiments;
- (15) FIG. 15 illustrates a calibration fixture for a wireless test module, according to some embodiments;
- (16) FIGS. 16A and 16B illustrate internal measurement tests using the calibration fixture of FIG. 15, according to some embodiments;
- (17) FIG. 17 illustrates a resistance accuracy test using the calibration fixture of FIG. 15, according to some embodiments;
- (18) FIGS. 18A and 18B illustrate example application interfaces of operating software for testing of a plurality of electrical wiring harnesses by the wireless harness automated measurement system of FIG. 1, according to particular embodiments;

(19) FIG. 19 illustrates a flow diagram illustrating an example method for testing of a wireless test module, according to particular embodiments; and

(20) FIG. 20 illustrates an example computer system that can be utilized to implement aspects of the various technologies presented herein, according to particular embodiments

DETAILED DESCRIPTION OF THE DISCLOSURE

(21) Electrical wiring harnesses are utilized in many different industries and vehicles. For example, large and complex electrical wiring harnesses with numerous electrical wires and connectors are utilized by the aerospace industry in the production of aircraft. As another example, electrical wiring harnesses are utilized by the automobile industry in the production of automobiles.

Electrical wiring harnesses for vehicles such as aircraft and automobiles must typically be rigorously and thoroughly tested in order to ensure that there are no defects in components of the electrical wiring harness such as connectors and electrical wires. For example, electrical wiring harnesses are tested to ensure there are no shorted wires, no swapped connector pins, no damaged wires, and the like.

(22) Typically, electrical wiring harnesses are tested using a large cabinet-style electrical relay box with hard-wired interfacing test cable adaptors that physically couple to both the connectors of the electrical wiring harness under test and the electrical relay box. The electro-mechanical actuation occurs in the centralized cabinet, while the hard-wired cable adaptors act as extension cords for the unique mating connectors to reach the electrical wiring harness under test. Such systems, however, may present problems in certain situations. For example, it is inefficient to use cabinet-style test machines in harness testing, such as setup, testing, repair (harness and tool), and breakdown. Typical cabinet-style test machines are large, heavy, and relatively immobile, they rely on highly customized test cable adaptor sets, and are not able to be efficiently scaled to meet changing electrical testing needs. As another example, an operator usually spends hundreds of hours in using cabinet-style test machines in harness testing per aircraft, such as troubleshooting systems to verify quality of products in aerospace, defense, and transit/rail industry. As another example, typical cabinet-style test machines need to test various independent sets of test cables and appropriate fixturing for fabrication tooling in a wire harness formboard.

(23) To address these and other problems with typical systems for testing electrical wiring harnesses, the present disclosure provides wireless harness automated measurement systems and methods. Certain disclosed embodiments utilize one or more wireless test modules (WTMs) that each physically and electrically couple to a connector of the electrical wiring harness under test. The one or more wireless test modules are utilized in a wireless harness automated measurement system (WHAMS) for a mobile test solution to validate electrical harnesses, while mitigating inefficiencies of traditional cable-based testing using the cabinet-style test machines. The wireless test modules send and receive electrical test signals through one or more wires of the electrical wiring harness and then, unlike current hard-wired solutions, wirelessly report test results back to a central computer systems such as a laptop. That is, each wireless test module is not physically connected to the central computer system but instead wirelessly communicates with the central computer system. This allows the wireless test modules to be carried to the location of the electrical wiring harness without having to worry about moving the central computing system or a bulky relay cabinet. This increases productivity and flexibility when testing the electrical wiring harnesses. In some embodiments, the wireless test modules are cylindrical in shape and are similar in size and shape to a typical flashlight. This small form factor enables a technician to easily carry multiple wireless test modules and install them on an electrical wiring harness under test that may be physically located away from the central computing system (e.g., in a next room or floor).

(24) Each wireless test module includes two main pieces: a chassis and a front end. The chassis of the wireless test module houses electronics and components (e.g., batteries, relays, etc.) for performing electrical tests on an electrical wiring harness (e.g., continuity checks, voltage isolation checks, diode polarity checks, resistance measurement checks, etc.). The removable front end of

the wireless test module contains a specific mating connector for connecting to a connector of the electrical wiring harness and is rapidly interchangeable with a common interface on the front of the wireless test module. The wireless test modules are interchangeable with one another and are not dedicated to any specific wiring harness or system. The configuration of the wireless harness automated measurement system allows for catalogues of front ends to be built for a variety of electrical connector needs while minimizing the number of wireless test modules needed for maximum hardware utilization. The hardware commonality of the wireless test module chassis also provides easy swapping in case of malfunction. If one wireless test module become inoperable, critical testing activity can continue without delay by simply replacing the inoperable wireless test module chassis with another available unit. As a result, test operators are able to complete testing of an electrical wiring harness without the requirement of test equipment troubleshooting or repair.

(25) The wireless harness automated measurement systems and methods of the present disclosure provide a unique combination of hardware flexibility and mobility for application in all phases of electrical wiring harness testing. Certain disclosed embodiments provide a wireless and scalable architecture that ensures the maximum utilization of the hardware. The wireless communication ability of the wireless test modules opens doors to electrical testing in environments that were previously difficult to access by hard-wired testing systems (e.g., by cabinet-style electrical relay box test systems with hard-wired test cable adaptors). Furthermore, the minimalistic equipment requirements to begin testing lowers testing entry barriers and increase the efficiency of the system. Certain disclosed embodiments provide simplistic information input formats that guarantees fast and automated test plan creation with little or no manual tasks required by an operator.

(26) To facilitate a better understanding of the present disclosure, the following examples of certain embodiments are given. In no way should the following examples be read to limit or define the scope of the disclosure. Embodiments of the present disclosure and its advantages may be best understood by referring to the included FIGURES, where like numbers are used to indicate like and corresponding parts.

(27) WHAMS Overall System

(28) FIG. 1 illustrates a wireless harness automated measurement system **100**, according to some embodiments. Wireless harness automated measurement system **100** includes an electrical wiring harness **110** under test, one or more wireless test modules **120** (e.g., **120A**, **120B**, **120C**, and **120D**), a central computer system **130**, and a wireless interface **140**. While a specific number of wireless test modules **120** are illustrated in FIG. 1, other embodiments may utilize any number of wireless test modules **120**.

(29) In general, wireless harness automated measurement system **100** utilizes one or more wireless test modules **120** to test the functionality of electrical wiring harness **110**. Each wireless test module **120** has a variable front end **126** (e.g., **126A**, **126B**, **126C**, and **126D**) that includes at least one connector that physically and electrically couples to a wiring harness connector **115** (e.g., **115A**, **115B**, **115C**, and **115D**) of the electrical wiring harness **110** under test. Wireless test modules **120** send and receive electrical test signals through one or more electrical wires **111** of electrical wiring harness **110** in order to perform tests such as continuity checks (e.g., pins of wiring harness connector **115** are in the wrong locations, shorted pins in wiring harness connector **115**, etc.), voltage isolation checks, diode polarity checks, and resistance measurement checks. Then, unlike typical solutions that are hard-wired to a bulky relay cabinet, wireless test modules **120** wirelessly report test results **160** back to central computer system **130** using a wireless transceiver **121** (e.g., **121A**, **121B**, **121C**, and **121D**). That is, each wireless test module **120** is not physically connected to central computer system **130** but instead wirelessly communicates with central computer system **130** using a wireless protocol such as Zigbee, Bluetooth, or WI-FI. The small form factor of wireless test modules **120**, along with their ability to wirelessly communicate with central computer system **130**, enables a technician to easily carry multiple wireless test modules **120** and coupled them to wiring harness connectors **115** on an electrical wiring harness **110** under test even

when electrical wiring harness **110** is physically located away from central computer system **130**.

(30) Electrical wiring harness **110** is a bundle of electrical wires **111**. Electrical wiring harness **110** includes one or more wiring harness connectors **115** that are coupled to one or more electrical wires **111**. For example, electrical wiring harness **110** of FIG. **1** includes four wiring harness connectors **115**: **115A-115D**. Wiring harness connector **115** may be any appropriate electrical connector and may include any number of pins or electrical contacts. Examples of wiring harness connectors **115** include signal connectors, power connectors, and the like. Electrical wiring harness **110** may be installed in any device or vehicle such as an aircraft, automobile, watercraft, spacecraft, and the like. Wireless harness automated measurement system **100** may be utilized to test electrical wiring harness **110** either before or after it has been installed in its intended device, aircraft, or vehicle.

(31) Each wireless test module **120** (**120A-120D**) is a portable test device that physically connects to a wiring harness connector **115** of electrical wiring harness **110**, performs one or more electrical tests on electrical wiring harness **110** as instructed by central computer system **130**, and/or wirelessly communicates test instructions **150** from the electrical tests back to central computer system **130**. Existing test systems for electrical wiring harnesses include large, bulky relay cabinets with hard-wired test adaptors that connect to wiring harness connectors **115**. Such systems are difficult to transport, are not easily adaptable, and are not easily scalable. However, by utilizing wireless test modules **120** that have a small form factor and are easily portable, wireless harness automated measurement system **100** may be utilized to test electrical wiring harness **110** that is located an extended distance away (e.g., in another room or floor). Furthermore, any number of wireless test modules **120** may be utilized by wireless harness automated measurement system **100** to test electrical wiring harness **110**, thereby increasing the adaptability and scalability of wireless harness automated measurement system **100** over existing hard-wired test relay cabinets.

(32) Each wireless test module **120** includes a wireless transceiver **121**, a chassis **122** (e.g., **122A**, **122B**, **122C**, and **122D**), and a variable front end **126**. Wireless transceiver **121** enables wireless test module **120** to wirelessly communicate with central computer system **130** (either directly or via wireless interface **140**) using any appropriate wireless protocol (e.g., Zigbee, Bluetooth, WI-FI, and the like). Chassis **122** is the main body of wireless test module **120** and houses components such as batteries, relays, processors, memory, and the like. Variable front end **126** is a removable portion of wireless test module **120** that includes an electrical connector that is configured to mate to a wiring harness connector **115** of electrical wiring harness **110**. For example, if wiring harness connector **115A** is a typical three-prong male electrical plug, variable front end **126** may include a three-prong female electrical plug. As another example, if wiring harness connector **115A** is a male coaxial electrical connector, variable front end **126** may include a female coaxial electrical connector. More details about wireless test module **120** and its components are discussed in more detail below in reference to FIGS. **2-8C**.

(33) Central computer system **130** may be any appropriate computing system in any suitable physical form. As example and not by way of limitation, central computer system **130** may be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) (such as, for example, a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, a tablet computer system, an augmented/virtual reality device, or a combination of two or more of these. Where appropriate, central computer system **130** may include one or more computer systems; be unitary or distributed; span multiple locations; span multiple machines; span multiple data centers; or reside in a cloud, which may include one or more cloud components in one or more networks. Where appropriate, central computer system **130** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein. As an example and not by way of limitation, central computer system **130** may perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. Central computer system **130** may

perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate. A particular example of a central computer system **130** is described in reference to FIG. **20**.

(34) Wireless interface **140** is any appropriate device that is able to provide wireless communications between central computer system **130** and wireless test modules **120**. In some embodiments, wireless interface **140** is a separate device that is communicatively coupled to (e.g., either wired to, wirelessly coupled to, or physically plugged into) central computer system **130**. In other embodiments, wireless interface **140** is internal to or incorporated within central computer system **130**. In some embodiments, wireless interface **140** is a Zigbee transceiver module, a WI-FI router, or a Bluetooth transceiver.

(35) Test instructions **150** are one or more signals, operations, commands, and the like that are wirelessly sent from central computer system **130** to wireless test module **120**. Test instructions **150** are utilized by wireless test module **120** in order to perform one or more electrical tests on electrical wiring harness **110**. The electrical tests may be, for example, a continuity check (e.g., pins of wiring harness connectors **115** are in the wrong location, pins of wiring harness connectors **115** are shorted, electrical wire **111** is damaged, etc.), a voltage isolation check, a diode polarity check, a resistance measurement check, and the like. In some embodiments, test instructions **150** are determined by central computer system **130** according to a test plan for electrical wiring harness **110**. An example of test instructions **150** is described in reference to FIGS. **18A** and **18B**.

(36) Test results **160** are one or more signals, values, pass/fail indicators, and the like that are wirelessly sent from wireless test module **120** to central computer system **130** (either directly or via wireless interface **140**). Test results **160** are results from one or more electrical test performed by wireless test module **120** on electrical wiring harness **110**. Test results **160** also include status signals and other meta data which is not directly related to harness test results. An example of test results **160** is described in reference to FIG. **18A**.

(37) FIGS. **2A-2B** illustrate various examples of testing an electrical wiring harness **110** by wireless harness automated measurement system **100**, according to some embodiments. In FIG. **2A**, two wireless test modules **120** are utilized to perform testing on electrical wiring harness **110**: a source wireless test module **120A** and a destination wireless test module **120B**. In this example, source wireless test module **120A** is physically coupled to a first wiring harness connector **115A** and destination wireless test module **120B** is physically coupled to a second wiring harness connector **115B**. Two electrical wires **111** are utilized during testing in this scenario: a first electrical wire **111A** and a second electrical wire **111B**. Second electrical wire **111B** is used as a return line in this example. Both electrical wires **111A** and **111B** are physically and electrically coupled to both source wireless test module **120A** and destination wireless test module **120B** via wiring harness connectors (e.g., wireless harness connectors **115A** and **115B** of FIG. **1**). Source wireless test module **120A** introduces a flow of electrical current on first electrical wire **111A**, and destination wireless test module **120B** internally connects first electrical wire **111A** to second electrical wire **111B** using, for example, electrical relays. Source wireless test module **120A** may then measure voltage and current across first electrical wire **111A** and second electrical wire **111B** in order to perform various electrical tests as described herein. Destination wireless test module **120B** also measures current and voltage to ensure electrical current actually reaches Destination wireless test module **120B**. Destination wireless test module **120B** includes a pin multiplexing component, such as a high voltage capable solid state multiplexing block **616**, which is configured to provide connections by transmitting a signal over one or more channels in a variety of switching and digital control applications.

(38) In other embodiments of the example of FIG. **2A**, options other than second electrical wire **111B** may be utilized for an electrical return path or ground. For example, an electrical shield within electrical wiring harness **110** may be utilized for the electrical return path or ground. As another example, an electrical jumper (e.g., a wire) may be physically connected to both source

wireless test module **120A** and destination wireless test module **120B** and used as the electrical return path or ground.

(39) In FIG. **2B**, a single wireless test module **120A** is utilized to perform testing on electrical wiring harness **110**. In this example, wireless test module **120A** is physically coupled to a first wiring harness connector (e.g., wiring harness connector **115A** of FIG. **1**) and a loopback connector (or other similar device) **202** is physically coupled to a second wiring harness connector (e.g., wiring harness connector **115B** of FIG. **1**). Two electrical wires **111** are utilized during testing in this scenario: a first electrical wire **111A** and a second electrical wire **111B**. Second electrical wire **111B** is used as a return line in this example. Both electrical wires **111A** and **111B** are physically and electrically coupled to wireless test module **120A** and are coupled to each other using the loopback device. Wireless test module **120A** introduces a flow of electrical current on first electrical wire **111A**, which is returned to wireless test module **120A** on second electrical wire **111B**. Wireless test module **120A** may then measure voltage and current across first electrical wire **111A** and second electrical wire **111B** in order to perform various electrical tests as described herein.

(40) In operation, and in reference to FIGS. **1**, **2A**, and **2B**, wireless harness automated measurement system **100** utilizes central computer system **130** and one or more wireless test modules **120** to test electrical wiring harness **110**. First, one or more wireless test modules **120** are physically connected to one or more wiring harness connectors **115** of electrical wiring harness **110**. For example, source wireless test module **120A** is physically coupled to first wiring harness connector **115A** and destination wireless test module **120B** is physically coupled to second wiring harness connector **115B** as illustrated in FIG. **2A**. As another example, wireless test module **120A** is physically coupled to first wiring harness connector **115A** and a loopback connector (or other similar device) **202** is physically coupled to second wiring harness connector **115B** as illustrated in FIG. **2B**. Next, central computer system **130** sends test instructions **150** to one or more wireless test modules **120** according to an automated test plan. More details and examples of an automated test plan used for testing electrical wiring harness **110** are discussed in more detail below. In some embodiments, test instructions **150** are sent to the one or more wireless test modules **120** using wireless interface **140**. The test instructions **150** may be sent using any appropriate wireless protocol such as WI-FI, Bluetooth, or Zigbee.

(41) After receiving test instructions **150** using wireless transceiver **121**, wireless test module **120** performs one or more tests on electrical wiring harness **110** according to received test instructions **150** from central computer system **130**. The electrical tests may be, for example, a continuity check (e.g., pins of wiring harness connectors **115** are in the wrong location, pins of wiring harness connectors **115** are shorted, electrical wire **111** is damaged, etc.), a voltage isolation check, a diode polarity check, a resistance measurement check, and the like. For example, wireless test module **120** may activate/deactivate one or more internal electrical relays and apply electrical current from an internal power source to one or more electrical wires **111** of electrical wiring harness **110** in order to perform a continuity check on electrical wiring harness **110**. Each wireless test module **120** is able to vary a voltage and an electrical current on one or more connected electrical wires **111** according to the received test instructions **150**. After performing the one or more tests on electrical wiring harness **110** according to received test instructions **150** from central computer system **130**, wireless test module **120** wirelessly transmits test results **160** back to central computer system **130** (either directly or via wireless interface **140**). Once test results **160** are received by central computer system **130**, central computer system **130** may display test results **160** received from one or more wireless test modules **120** on an electronic display.

(42) WHAMS Wireless Test Modules

(43) In some embodiments, a wireless test module is the primary electrical testing hardware of the WHAMS. The wireless test module is a cylindrical, wirelessly enabled communication and testing node capable of conducting a variety of electrical checkouts by mating with the discrete electrical

connectors of an aircraft or other electrical harness. The wireless test module may communicate with a radio transceiver powered by the central computer system **130**. As a result, the central computer system **130** sends various types of commands to the wireless test module for test execution and reporting. The wireless test module is capable of operating on its own or within scalable networks of a plurality of wireless test modules for use on large harness assemblies. (44) FIG. **3** illustrates a wireless test module **120** that may be utilized by the wireless harness automated measurement system of FIG. **1**, according to some embodiments. Each wireless test module **120** includes a wireless transceiver **121** (shown in FIG. **1**), a chassis **122**, and a variable front end **126**. Wireless test module **120** is the primary electrical testing hardware of WHAMS. In some embodiments, traditional electrical harness testing hardware includes one or more large charge cabinets and extended cables with unique test adaptors at the end. The one or more charge cabinets may be configured to house hundreds of relays and other electrical components used to conduct different test types needed for functional electrical harness verification. In particular, individual charge cabinets may test thousands of test points and can be expanded by connecting multiple charge cabinets together. However, the one or more charge cabinets are configured to be scalable in large increments of test points. For example, the one or more charge cabinets are configured to be deployable for a harness configuration requiring less than or equal to a predetermined number of test points. As a result, it is difficult to optimize the cabinet configurations of the one or more charge cabinets to reduce cost, especially for small electrical harness assemblies comprising low pin count connectors with high variety. Usually, the one or more charge cabinets include a plurality of connectors with various pin counts, types, and units for a majority of the work being completed.

(45) In some embodiments, the one or more large charge cabinets use a panel of generic connector interfaces for a plurality of test adaptor cables to plug into. The plurality of test adaptor cables are double ended and unique in length, increasing weight and fabrication cost of the traditional electrical harness testing hardware. Thus, it is difficult to transport and deploy the traditional electrical harness testing hardware in an agile manor for multi-build environment usage.

(46) In some embodiments, wireless test module **120** is configured to use smaller charge cabinets. In particular, wireless test module **120** has mobile and rapidly configurable cabinet configurations which allow wireless test module **120** to be contained in a tight form factor for full and closed loop wireless capability for electrical harness testing. Wireless test module **120** is battery powered and operates independently from other wireless test modules based on a discrete architecture. Thus, wireless test module **120** may perform one or more tests which are no longer tethered to an immediate power source or cabled test adaptors. As a result, wireless test module **120** may provide a more efficient performance for testing a variety of harness sizes and decrease the necessary non-recurring engineering (NRE) to stand up new test adaptors.

(47) In some embodiments, wireless test module **120** is a cylindrical, wirelessly enabled communication and testing node. Chassis **122** may be a circuit card assembly (CCA) chassis which houses a plurality of electronical components. Wireless test module **120** may replace an inoperable chassis **122** with another available unit in case of malfunction. In some embodiments, the variable front end **126** includes an electrical connector **302** (and back shell if applicable), a plastic adapter (such as hot-swap interface **124**, which connects electrical connector **302** to chassis **122**), and a wire harness (e.g., jumper harness **708** of FIG. **7A**) which makes the connections from electrical connector **302** to chassis **122**. Variable front end **126** is a removable portion of wireless test module **120**. Wireless test module **120** may be configured to automatically identify the test adaptor, such as variable front end **126**, which is connected to wireless test module **120**. Variable front end **126** may use electrical connector **302** to couple to a wiring harness connector of an electrical wiring harness. Thus, wireless test module **120** may be configured to physically couple to an electrical wiring harness for performing one or more electrical tests on the electrical wiring harness (e.g., continuity checks, voltage isolation checks, diode polarity checks, resistance measurement checks, etc.). In

particular, wireless test module **120** may be configured to use wireless transceiver **121** to wirelessly receive a plurality of test instructions (e.g., test instructions **150** of FIG. **1**) according to an automated test plan from the central computer system (e.g., central computer system **130** of FIG. **1**). Wireless test module **120** is configured to use variable front end **126** to perform one or more tests on the electrical wiring harness according to the plurality of test instructions in accordance with an automated test plan from the central computer system. Wireless test module **120** is configured to use wireless transceiver **121** to wirelessly communicate test results to the central computer system.

(48) FIG. **4** illustrates an exploded view of wireless test module **120** of FIG. **3**, according to some embodiments. The wireless test module **120** is a common, replicated piece of module for easy interchanging of units for easy of repair and elimination of system downtime. Variable front end **126** (shown in FIG. **1**) may be customized while chassis **122** remains consistent. For example, variable front end **126** may include a front-end side hot-swap connector **404** that is rapidly interchangeable for different connectors. Chassis **122** may be configured to house a plurality of electronic components, which allows wireless test module **120** to communicate wirelessly with the central computer system (e.g., central computer system **130** of FIG. **1**) using WI-FI, Bluetooth, or Zigbee. Wireless test module **120** may use a Zigbee communications protocol to communicate with a test software and the wireless transceiver (e.g., wireless transceiver **121** of FIG. **1**). Thus, wireless test module **120** provides a mobile and modular electric harness tester which does not use cabled test adaptors to communicate with the central computer system.

(49) FIG. **5** illustrates an internal view of wireless test module **120** of FIG. **3**, according to some embodiments. Wireless test module **120** may include a large variety of mating electrical connectors **406**. For example, wireless test module **120** may support up to 128 pin electrical connectors **406**. As another example, wireless test module **120** may support up to 48 pin electrical connectors **406**. Electrical connectors **406** may be integrated into wireless test module **120** to couple to a wiring harness connector of the electrical wiring harness.

(50) FIG. **6** illustrates a functional block diagram **600** of wireless test module **120** of FIG. **3**, according to some embodiments. The wireless test module includes a plurality of electronic components, such as a wireless block **602**, a charging and power block **604**, a central processing and memory block **606**, a lithium-ion rechargeable battery **608**, a high voltage source **610**, a low voltage source **612**, an analog measurement circuitry **614**, and a high voltage capable solid state multiplexing block **616**. High voltage capable solid state multiplexing block **616** is connected to the variable front end (e.g., variable front end **126** of FIG. **3**) of the wireless test module. In certain embodiments, central processing and memory block **606** of the wireless test module is combined with circuitry, such as analog measurement circuitry **614**, such that the wireless test module is designed to take measurements that are typically made when manufacturing and debugging cable harnesses. In some embodiments, the wireless test module includes a plurality of electrical relays designed for high voltage capable solid state multiplexing block **616**. In certain embodiments, the wireless test module includes lithium-ion rechargeable battery **608** (e.g., a 3400 milliampere-hour (mAh) lithium-ion rechargeable battery) which eliminates the need for cabled charge cabinets. As a result, the wireless test module may be configured to conduct low current, high voltage testing and communicate wirelessly with the central computer system (e.g., central computer system **130** of FIG. **1**) under battery power.

(51) In some embodiments, the wireless test module is configured to use the plurality of electronic components to conduct a variety of electrical checkouts by mating with a plurality of discrete electrical connectors of electronic wiring harnesses for aircraft and automobiles. For example, the wireless test module may use central processing and memory block **606** and analog measurement circuitry **614** to take measurements during testing of the electronic wiring harnesses for aircraft and automobiles. Likewise, the wireless test module may use central processing and memory block **606** to apply pick-by-light functionality for initial hardware selection and harness

hookup processes. As another example, the wireless test module may use wireless block **602** to communicate with a radio transceiver powered by a control laptop, such as the central computer system, which sends various types of test instructions (e.g., test instructions **150** of FIG. **1**) to the wireless test module for test execution and reporting. As another example, the wireless test module may apply an internal power source to one or more electrical wires of the electrical wiring harness in order to perform a test on the electrical wiring harness. The internal power source may include high voltage source **610** and/or low voltage source **612**.

(52) In some embodiments, the wireless test module (e.g., wireless test module **120** of FIG. **1**) includes a power button to allow a user to turn on, turn off, or reset the wireless test module. The wireless test module may be configured to use a mini-USB connector, a charging port of the wireless test module, and charging and power block **604** to charge the wireless test module. Likewise, the wireless test module may be configured to use the mini-USB connector as a software debug port to update one or more software packages of the wireless test module at a high speed. In particular, the charging port of the wireless test module may interface with a plurality of pogo pins located in each slot of a WHAMS charging cart. The plurality of pogo pins may also be used for a battery pack of the wireless test module. When the wireless test module is powered off and power is applied to the charging port, the wireless test module may be configured to power on and begin charging. The wireless test module may include a plurality of light-emitting diode (LED) indicators to facilitate visual communication with the user visually. For example, the LED indicators are orange colored and located on an end of the wireless test module **120**.

(53) In some embodiments, the wireless test module (e.g., wireless test module **120** of FIG. **1**) may be configured to operate independently or within a scalable network of wireless test modules for use on large harness assemblies. In particular, the wireless test module may be configured to generate a low voltage output of approximately 2.4 Volts (V) for a resistance/continuity test. Likewise, the wireless test module may be configured to generate a voltage output within a range of 100V to 500V for high voltage testing with a tolerance on the output voltage of $\pm 3\%$ to $\pm 2\%$. As a result, the wireless test module may be configured to measure resistance with an accuracy of $10\% \pm 1$ ohm for a resistance in a 1 ohm to 50 ohm range. The wireless test module may be configured to measure resistance with an accuracy of $5\% \pm 1$ ohm for a resistance in a 51 ohm to 250 ohm range. The wireless test module may be configured to measure resistance with an accuracy of $10\% \pm 1$ ohm for a resistance in a 251 ohm to 1 million (M) ohm range. The wireless test module may be configured to measure resistance with an accuracy in a range of 6% and 10% using high voltages. For example, the accuracy for resistance measurements using the 100V high voltage is 10% for a resistance in a 1M ohm to 50M ohm range. As another example, the accuracy for resistance measurements using the 500V high voltage is 6% for a resistance in the 1M ohm to 50M ohm range.

(54) WHAMS Hot-Swap Connectors

(55) In some embodiments, the WHAMS is configured to perform one or more electronic tests for functional automated check (FAC) on a plurality of electronic wiring harnesses for vehicles such as aircraft and automobiles. The variety in connector types on the vehicles is immense. The WHAMS may use a plurality of wireless test modules to test every unique connector of the vehicles. Because the vehicles are tested in pieces, the plurality of wireless test modules may use hot-swap connectors to separate connectors from the plurality of wireless test modules to decrease production cost and increase flexibility of the WHAMS.

(56) FIG. 7A illustrates a WTM side hot-swap connector **402** operable to couple to a variable front end (e.g., variable front end **126** of FIG. **3**), according to some embodiments. The wireless test module (e.g., wireless test module **120** of FIG. **1**) includes a pair of hot-swap connectors, such as WTM side hot-swap connector **402** and front end side hot-swap connector **404** of FIG. **4**, located between the chassis of the wireless test module and the variable front end of the wireless test module. A WHAMS may use a plurality of wireless test modules that include several types of

connectors for FAC during testing of a plurality of electrical wiring harnesses. In particular, every unique connector may be accounted for in the FAC for vehicles such as aircraft and automobiles. Traditional WHAMS includes a plurality of connectors permanently mounted to a wireless test module that contains all of the processing functions. Because at least one wireless test module is required for each unique connector, the traditional WHAMS may incur high production costs for testing the plurality of electrical wiring harnesses. The hot-swap connectors may significantly decrease production costs and increase flexibility of the WHAMS by separating the hot-swap connectors from the wireless test module. The number of wireless test modules is determined based on the number of tests required for the WHAMS.

(57) In some embodiments, WTM side hot-swap connector **402** is a custom-designed universal connector. WTM side hot-swap connector **402** may be located on an end of the chassis of the wireless test module that is attached to another custom-designed universal connector, such as a front side hot-swap connector, located at an end of the variable front end that mates with the wireless test module. Thus, WTM side hot-swap connector **402** is operable to attach the variable front end of the wireless test module to the chassis of the wireless test module. Likewise, WTM side hot-swap connector **402** is operable to detach the variable front end of the wireless test module from the chassis of the wireless test module. WTM side hot-swap connector **402** is operable to transfer data from/to the wireless test module when the chassis of the wireless test module and the variable front end of the wireless test module mate. WTM side hot-swap connector **402** is operable to swap to a different wireless test module with address information updated automatically in real time in the event the wireless test module malfunctions.

(58) In some embodiments, WTM side hot-swap connector **402** includes an alignment peg **702**, a slip ring **704**, an electrically erasable programmable read-only memory (EEPROM) read/write wire **706**, a jumper harness **708**, and a female connector, such as a surface-mount female connector **710**. Alignment peg **702** is configured to mate to the variable front end of the wireless test module. Slip ring **704** is configured to secure the wireless test module in place for quick and secure connection. Thus, the variable front end may attach and detach quickly from the wireless test module. EEPROM read/write wire **706** may be integrated on a circuit board to read/write data of the wireless test module. EEPROM read/write wire **706** may be configured to couple to the chassis of the wireless test module. The wireless test module is operable to use a wireless transceiver to wirelessly communicate with the central computer system to transfer the data stored on an EEPROM (e.g., EEPROM **726** of FIG. 7B) associated with EEPROM read/write wire **706**. jumper harness **708** is configured to couple to the wireless test module. Surface-mount female connector **710** includes a plurality of contacts in a range of 48 contacts to 128 contacts. For example, surface-mount female connector **710** may include 100 contacts.

(59) FIGS. 7B and 7C illustrate a front end side hot-swap connector **404** coupling to wireless test module **120** of FIG. 3, according to some embodiments. Front end side hot-swap connector **404** is a custom designed universal connector located on an end of the variable front end of the wireless test module that is attached to another custom designed universal connector, such as the WTM hot-swap connector, located at an end of the chassis of the wireless test module. Thus, front end side hot-swap connector **404** is operable to attach the variable front end of the wireless test module to the chassis of the wireless test module. Likewise, front end side hot-swap connector **404** is operable to detach the variable front end of the wireless test module from the chassis of the wireless test module. Front end side hot-swap connector **404** is operable to transfer data from/to the wireless test module when the chassis of the wireless test module and the variable front end of the wireless test module mate. Front end side hot-swap connector **404** is operable to swap to a different wireless test module with address information updated automatically in real time when the wireless test module malfunctions.

(60) In some embodiments, front end side hot-swap connector **404** includes an alignment peg **722**, a thread **724**, an EEPROM **726**, a plurality of connectors **728**, and a male connector, such as a

surface-mount male connector **730**. Alignment peg **722** is configured to mate to the chassis of the wireless test module. Thread **724** is configured to mate with the slip ring (e.g., slip ring **704** of FIG. **7A**) to secure the wireless test module in place for quick and secure connection. As a result, the variable front end may attach and detach quickly from the wireless test module. When attached, the variable front end is held securely in place with the slip ring and thread **724**. EEPROM **726** may be integrated on a circuit board to store data of the wireless test module. The wireless test module is operable to use a wireless transceiver to wirelessly communicate with the central computer system to transfer the data stored on EEPROM **726**. The data on EEPROM **726** may be automatically incorporated into a testing software of the central computer system without human data entry. Plurality of connectors **728** are configured to mate with a wire jumper to an aircraft connector. Surface-mount male connector **730** includes a plurality of contacts in a range of 48 contacts to 128 contacts. For example, surface-mount male connector **730** may include 100 contacts.

(61) FIGS. **8A-8C** illustrate example variable front ends **802** that may be installed on wireless test module **120** of FIG. **3**, according to some embodiments. In particular, variable front ends **802** in FIGS. **8A-8C** may couple to a wiring harness connector (e.g., wiring harness connector **115** of FIG. **1**), such as an aircraft connector, with various pins.

(62) WHAMS Battery Pack

(63) In some embodiments, a wireless test module may use a portable charging battery pack to supply extra power when the wireless test module of the WHAMS runs off power with a low battery during testing. The portable charging battery pack is configured to prolong battery life for the wireless test module of the WHAMS if the wireless test module is left uncharged for an extended period of time.

(64) FIGS. **9A-9C** illustrate a battery pack **900** for a wireless test module, according to some embodiments. Battery pack **900** provides a portable charging solution for the wireless test module to supply extra power to the wireless test module at a low battery level during testing. Battery pack **900** includes a wireless charging battery, a wireless battery pack holder **902**, an injected molded pogo pin holder **904**, and a wireless charging receiver **906**. Wireless battery pack holder **904** is operable to contain the wireless charging battery. In certain embodiments, wireless battery pack holder **904** is a three-dimensional (3D) printed piece comprising a shape that allows wireless battery pack holder **902** to slip over an end of the wireless test module. Thus, wireless battery pack holder **904** may house a plurality of components necessary to make battery pack **900** functional.

(65) In some embodiments, the injected molded pogo pin holder **904** includes a plurality of pogo pins (e.g., pogo pins **1002** of FIG. **10**). Injected molded pogo pin holder **904** is coupled to wireless battery pack holder **902** using a first set of fasteners (e.g., screws). Likewise, injected molded pogo pin holder **904** is operable to couple to the wireless test module. Wireless charging receiver **906** is operable to wirelessly charge the wireless charging battery. Thus, battery pack **900** is configured to charge the wireless test module by contacting the plurality of pogo pins with a compatible wireless charging battery pack. In particular, the battery pack includes a steel retractable spring plunger **908** that includes pull rings operable to hold battery pack **900** together by attaching to the wireless test module using a second set of fasteners (e.g., screws). Battery pack **900** includes a magnet **910** attached to wireless charging receiver **906**. Magnet **910** is operable to latch battery pack **900** onto the wireless test module. In certain embodiments, wireless charging receiver **906** includes a 5 Volt (V) Qi standard wireless charging receiver **912** that includes a magnetic plate compatible with magnet **910**.

(66) In some embodiments, battery pack **900** is configured to prolong battery life of the wireless test module, which may be left uncharged for an extended period of time. For example, battery pack **900** may couple to the wireless test module to provide extra power for performing one or more electrical tests on an electrical wiring harness (e.g., continuity checks, voltage isolation checks, diode polarity checks, resistance measurement checks, etc.). In particular, the wireless test module may include an electrical connector that is operable to mate to a wiring harness connector

of the electrical wiring harness. The wireless test module is operable to perform the one or more tests to validate the electrical wiring harness according to a plurality of test instructions received from the central computer system. In particular, the wireless test module is operable to communicate wirelessly with the central computer system using WI-FI, Bluetooth, or Zigbee.

(67) FIG. **10** illustrates injected molded pogo pin holder **904** of the battery pack of FIGS. **9A-9C**, according to some embodiments. Injected molded pogo pin holder **904** may include a plurality of pogo pins **1002**, which may be fastened (e.g., screwed) to the wireless battery pack holder.

(68) WHAMS Charging Cart

(69) In some embodiments, the WHAMS may use a mobile charging cart to charge a plurality of wireless test modules in parallel. The mobile charging cart is configured to hold and charge the plurality of wireless test modules and locate the plurality of wireless test modules when needed for testing. As a result, the mobile charging cart may ensure the plurality of wireless test modules are completely charged at time of production use. Likewise, the mobile charging cart may locate the plurality of wireless test modules through a pick by flight function which lights up the plurality of wireless test modules that is called for when needed for testing.

(70) FIGS. **11A-11F** illustrate charging cart systems **1100** for storing multiple wireless test modules, according to some embodiments. Charging cart system **1100** is mass charging apparatus that is configured to hold and charge a plurality of wireless test modules for production use. Charging cart system **1100** includes three sizes: (1) a double deck charging cart **1160**, as illustrated in FIG. **11A**, (2) a single deck charging cart **1170**, as illustrated in FIG. **11B**, and 3) a mini charging cart **1180**, as illustrated in FIG. **11C**. FIG. **11A** shows how double deck charging cart **1160** may hold a plurality of charging slots in a range of 150 charging slots to 200 charging slots. FIG. **11B** shows how single deck charging cart **1170** may hold a plurality of charging slots in a range of 50 charging slots to 100 charging slots. FIG. **11C** shows how mini charging cart **1180** may hold a plurality of charging slots in a range of 20 charging slots to 30 charging slots. For example, double deck charging cart **1160** may hold 174 charging slots. As another example, single deck charging cart **1170** may hold 87 charging slots. As another example, mini charging cart **1180** may hold 25 charging slots.

(71) In some embodiments, charging cart system **1100** includes a mobile aluminum frame **1102**, a charging cart **1150**, a plurality of LED indicators **1104**, and a plurality of charging slots **1106**. In particular, FIGS. **11D-11F** show charging cart **1160**, which includes a bottom front **1108**, a bottom middle **1110**, a bottom back **1112**, a side left **1114**, a side right **1116**, a back sheet **1118**, a front sheet **1120**, and a plurality of pipes **1122**. These components may be assembled using polyvinyl chloride (PVC) sheets and PVC pipes to support the charging cart. The PVC sheets may be 0.5 inch thick type 1 PVC sheets. The PVC pipes may be 2 inch in diameter schedule 40 PVC pipes.

(72) FIG. **11E** shows aluminum frame **1102**. Charging cart **1150** is connected to the aluminum frame **1102** using fasteners (e.g., bolts). Plurality of LED indicators **1104** of FIG. **11A** are operable to identify a status of the plurality of the wireless test modules during testing of the WHAMS. Plurality of charging slots **1106** of FIG. **11A** are operable to charge the plurality of the wireless test modules. Each of the plurality of charging slots is associated with a respective one of plurality of LED indicators **1104**. In some embodiments, the charging cart may charge more than 100 wireless test modules in parallel using a power supply which is operable to supply a power of 1500 Watts (W). As another example, the charging cart may locate the plurality of wireless test modules using a find by light function to light up one or more wireless test modules that are used for testing. As a result, the charging cart may include a foundation assembled by a plurality of PVC sheets and PVC pipes. The foundation may include one or more decks, such as sheet assemblies **1124** of FIG. **11F**, welded on the charging cart to allocate the plurality of charging slots. The plurality of charging slots are keyed slots to receive the plurality of wireless test modules to ensure the plurality of wireless test modules are correctly placed. FIG. **11F** shows how each sheet assembly **1124** may include a back sheet **1118**, a front sheet **1120**, and a plurality of PVC pipes **1122**.

(73) FIGS. **12-14D** illustrate more details of charging cart system **1100** of FIGS. **11A-11F**, according to some embodiments. FIG. **12** shows how the charging cart may be configured to use an injection molded pogo pin block **1204** to charge wireless test module **120** attached to a charging slot **1106**. In particular, injection molded pogo pin block **1204** may include a 4-pin layout **1300**, as illustrated in FIG. **13**, for charging wireless test module **120** and a light indication using an LED ring **1206** that includes a plurality of red LEDs and a plurality of green LEDs in an alternating order along LED ring **1206**. LED ring **1206** may include a ring cover **1202** (e.g., a clear polycarbonate LED ring cover).

(74) FIG. **13** shows 4-pin layout **1300** for the injection molded pogo pin block **1204** of FIG. **12**. 4-pin layout **1300** includes a power source pin **1302**, a ground pin **1304**, and a plurality of LED pins **1306**. Power source pin **1302** may be a 5 V pin. Plurality of LED pins **1306** may include a red LED pin and a green LED pin. As a result, the charging cart is configured to use the injection molded pogo pin block to charge the wireless test module and provide a light indication to assist in locating the wireless test module.

(75) FIGS. **14A** and **14B** illustrate a layout **1400** of a plurality of charging slots **1106** on a deck in charging cart system **1100** of FIGS. **11A-C**. Each of the plurality of charging slots **1106** is associated with a respective injection molded pogo pin block **1204** and a respective LED ring **1206**. FIG. **14C** shows a 1500 W single output power supply operable to supply power to the plurality of wireless test modules in the charging cart. FIG. **14D** shows a plurality of LED indicators **1104** that may assist in identifying the status of a respective wireless test module, as well as help locate where the modules are at any given time. In particular, each of the plurality of LED indicators turns red to indicate that an identified wireless test module associated with the respective LED indicator is currently charging. Each of the plurality of LED indicators turns green to indicate an identified wireless test module associated with the respective LED indicator to locate before testing. Each of the plurality of LED indicators turns off to indicate that an identified wireless test module associated with the respective LED indicator finishes charging. For example, a red LED **1402** indicates that an identified wireless test module associated with the red LED **1402** is currently charging. As another example, a green LED **1404** indicates that an identified wireless test module associated with the green LED **1404** to locate before testing. As another example, a light-off LED **1406** indicates that an identified wireless test module associated with the light-off LED **1406** finishes charging.

(76) WHAMS Calibration

(77) Certain embodiments relate to a calibration method for calibrating the wireless test module **120** of FIG. **1**. It is critical to calibrate the wireless test module of the WHAMS in order to accurately read resistance measurements when to perform one or more electrical tests on an electrical wiring harness (e.g., continuity checks, voltage isolation checks, diode polarity checks, resistance measurement checks, etc.). Before testing of the WHAMS, the wireless test module is subject to a controlled periodic calibration process to ensure the wireless test module may read resistance accurately. In particular, the wireless test module may include a plurality of field effect transistors (FETs). The plurality of FETs may be optically isolated MOFFETS. When the wireless test module is not properly calibrated, measurements of internal resistance of the plurality of FETs of the wireless test module may drift over time.

(78) FIG. **15** illustrates a calibration fixture **1500** for a wireless test module, according to some embodiments. Calibration fixture **1500** includes a switchboard **1502**, a connector **1504**, and a grounding cable **1506**. In certain embodiments, switchboard **1502** includes a plurality of switches **1508**. Connector **1504** is used to attach calibration fixture **1500** to the wireless test module. Grounding cable **1506** is used to connect calibration fixture **1500** directly to the earth. The calibration method may use calibration fixture **1500** to apply the controlled periodic calibration process in an automated approach to record the internal resistance of each of the plurality of FETs. The controlled periodic calibration process may include one or more of the following five

operations: (1) run internal measurement tests, (2) run resistance accuracy tests (RATs), (3) store calibration factors, (4) store RAT history, and (5) recall updated calibration factors at test time. Calibration fixture **1500** is configured to short the wireless test module in the internal measurement tests and the RATs to provide measurements for the internal resistance of the wireless test module in the internal measurement tests and a plurality of resistors in the RATs. As a result, the plurality of resistors may be measured and recorded regularly by a calibrated ohmmeter, such as the calibration fixture **1500**. The calibration method may determine if there is resistor shift by comparing the measurements for the plurality of resistors in the RATs to an original calibration standard.

(79) FIGS. **16A** and **16B** illustrate internal measurement tests **1600** using the calibration fixture **1500** of FIG. **15**, according to some embodiments. The wireless test module **120** includes a relay with a plurality of FETs, such as a high side FET **1602** and a low side FET **1604**. High side FET **1602** has a high side resistance. Low side FET **1604** has a low side resistance. Likewise, calibration fixture **1500** includes a first switch **1606** and a second switch **1608**. The calibration method may use first switch **1606** and/or second switch **1608** to measure different “on” resistance components of the relay of wireless test module **120**.

(80) FIG. **16A** shows first switch **1606** is turned on and second switch **1608** is turned off. When the calibration method uses calibration fixture **1500** to run calibration on wireless test module **120**, the calibration method measures a first resistance value of the plurality of FETs from a first internal measurement test for wireless test module **120**. The first resistance value measures resistance on a first path along high side FET **1602** of wireless test module **120** and calibration fixture **1500**. Thus, the first resistance value is associated with a resistance of high side FET **1602**, contact resistances, and trace/wire resistance on a calibration board. For example, the first resistance value may be in a range of 80 ohms to 90 ohms.

(81) FIG. **16B** shows first switch **1606** is turned off and second switch **1608** is turned on. When the calibration method uses calibration fixture **1500** to run calibration on wireless test module **120**, the calibration method measures a second resistance value of the plurality of FETs from a second internal measurement test for wireless test module **120**. The second resistance value measures resistance on a second path along both high side FET **1602** and/or low side FET **1604** of wireless test module **120** and calibration fixture **1500**. Thus, the second resistance value is associated with a resistance of high side FET **1602**, a resistance of low side FET **1604**, contact resistances, and trace/wire resistance on a calibration board. For example, the first resistance value may be in a range of 120 ohms to 140 ohms. As a result, the first resistance value of the FETs measures the high side resistance associated with high side FET **1602**. The second resistance value of the FETs measures a summation of both the high side resistance associated with high side FET **1602** and the low side resistance associated with low side FET **1604**.

(82) In some embodiments, the calibration method determines a resistance calibration value by subtracting the first resistance value of the plurality of FETs from the second resistance value of the plurality of FETs. The resistance calibration value is a low side calibrated value. For example, the resistance calibration value may be in a range of 40 ohms to 50 ohms. The calibration method may compare the resistance calibration value to a predetermined value. For example, if the predetermined value for low side FET **1604** is 45 ohms, the calibration method may determine that the resistance calibration value matches the predetermined value. As a result, the calibration method is configured to perform the RATs using a plurality of resistors of calibration fixture **1500**. As another example, if the predetermined value for the low side FET **1604** is 60 ohms, the calibration method may determine that the resistance calibration value does not match the predetermined value. The calibration method determines a failed result for the controlled periodic calibration process for wireless test module **120**.

(83) FIG. **17** illustrates a resistance accuracy test **1700** using calibration fixture **1500** of FIG. **15**, according to some embodiments. Resistance accuracy test **1700** is configured to validate a plurality

of resistors of calibration fixture **1500**. For example, the plurality of resistors may have resistor values in a range from 1 ohm to 50M ohms. In particular, calibration fixture **1500** may use a plurality of pins to adjust the resistor values of calibration fixture **1500**. All pins run the RATs with a 1 ohm value, and one pin runs the RATs with higher values. The calibration method selects a resistor **1702** from the plurality of resistors of calibration fixture **1500** and a test, such as a continuity test, associated with the wireless test module **120**. The selected resistor **1702** is associated with a target resistor value, such as 2 ohms. The calibration method uses calibration fixture **1500** and the test to measure a plurality of calibration factors. For example, the plurality of calibration factors for the continuity test includes a high side calibration indicator on a source side, a high side calibration factor on a sink side, and an initial resistor value.

(84) In some embodiments, the calibration method determines a measured resistor value using the plurality of calibration factors. For example, the measured resistor value for the continuity test is determined by subtracting the high side calibration indicator on the source side and the high side calibration factor on the sink side from the initial resistor value. As a result, the calibration method compares the measured resistor value to the target resistor value. When the measured resistor value matches the target resistor value, the calibration method determines the test passes. When the measured resistor value does not match the target resistor value, the calibration method determines the test fails. As a result, the calibration method may store the measured resistor value and the target resistor value in a database of the central computer server. Likewise, the calibration method may store the plurality of calibration factors and RAT history associated with the RAT in the database of the central computer server. Therefore, the calibration method may perform a plurality of RATs on wireless test module **120** using the plurality of resistors of calibration fixture **1500** to detect a potential mode of failure using resistance of the FETs drifting over a period of time.

(85) WHAMS Operating Software

(86) Some embodiments relate to a controlling method for managing a plurality of wireless test modules of a WHAMS on a plurality of electrical wiring harnesses. The plurality of wireless test modules of the WHAMS may wirelessly communicate with a central computer system. In particular, the controlling method is applied using a plurality of operating components during testing of the WHAMS: (1) a wireless test module board support component, (2) a custom power controller component, and (3) a test generation, execution, and module management component. The wireless test module board support component is configured to use a wireless test module board support package to apply a core operating application for the plurality of wireless test modules. In particular, the core operating application may implement a two-way testing approach to perform one or more electrical tests on the plurality of electrical wiring harnesses (e.g., continuity checks, voltage isolation checks, diode polarity checks, resistance measurement checks, etc.) according to the plurality of test instructions received from the central computer system.

(87) In some embodiments, the custom power controller component is configured to implement a custom power controller suite to manage a plurality of batteries for the plurality of wireless test modules. In some embodiments, the test generation, execution, and module management component is configured to implement one or more algorithms to generate a test plan and/or a graphic user interface (GUI) for running various system functions. In particular, the test plan may include a map of the plurality of electrical wiring harnesses, a plurality of harness connections associated with each of the plurality of wireless test modules, a hookup file, and one or more electrical tests associated with the plurality of electrical wiring harnesses. For example, the hookup file defines the plurality of wireless test modules assigned to the plurality of harness connections. As another example, the test plan is generated using additional harness information of splices, passive equipment, and resignation of loose leads. In particular, the test plan is generated to check wires and unused pins in network configurations for each of the plurality of electrical wiring harnesses. Thus, the test generation, execution, and module management component may interpret wire lists for the plurality of electrical wiring harnesses and generate a test plan based on testing

criteria received from a user. In particular, the test generation, execution, and module management component is configured to determine a grounding mechanism for testing each electrical wiring harnesses and use input data to analyze each electrical wiring harnesses.

(88) In some embodiments, the controlling method uses a central computer system to access a plurality of electrical wiring harnesses, the testing criteria, and a WHAMS. The controlling method generates a test plan for the plurality of electrical wiring harnesses based on the testing criteria and elect a plurality of wireless test modules using the test plan and the WHAMS. The controlling method generates a plurality of test instructions based on the test plan and the plurality of wireless test modules. The controlling method uses the plurality of wireless test modules to perform one or more tests on the plurality of electrical wiring harnesses according to the plurality of test instructions. The controlling method uses the plurality of wireless test modules to wirelessly communicate test results to the central computer system **130** for display. Furthermore, the controlling method may be used to wirelessly communicate with the plurality of wireless test modules to update a software package and/or one or more smart test adaptors associated with each of the plurality of wireless test modules using part numbers and pin configuration data of the one or more smart test adaptors.

(89) In some embodiments, the application interfaces **1800** illustrated in FIGS. **18A** and **18B** include a first user interface **1806** for test plan generation. First user interface **1806** may be implemented to define multiple harness features and monitor the creation of the test plan, send alerts of potential errors in conversion.

(90) In some embodiments, application interfaces **1800** include a second user interface **1808** for execution of test plans. Second user interface **1808** may be implemented for a user to visually inspect status of an electronic wiring harness through color coded reporting. For example, a passing test is highlighted in a green color and a failing test is highlighted in a different color, such as red, orange, or yellow, based on a condition of the failure of the failing test. In particular, the user may interact with second user interface **1808** to manage the one or more tests on the plurality of electrical wiring harnesses based on various criteria, such as source and destination reference designators involved, test status, test type, etc. As a result, second user interface **1808** provides a flexible solution to execute a test plan based on various testing conditions. After execution of the test plan, second user interface **1808** generates a final consumable report which is digitally stored and post-processed to extract the data for further utilization in troubleshooting or data analytics.

(91) In some embodiments, application interfaces **1800** include a third user interface **1810** for calibration of the plurality of wireless test modules. Third user interface **1810** may be implemented for a user to control calibration hardware of the WHAMS and automatically calibrate the plurality of the wireless test modules of the WHAMS. Thus, third user interface **1810** may be applied to validate internal relays and their compensation values of the plurality of wireless test modules.

(92) In some embodiments, application interfaces **1800** include a fourth user interface **1812** for built in test (BIT) calibration. Fourth user interface **1812** may be implemented for calibration of test types and module capabilities. For example, fourth interface **1812** may be implemented to check the health of the plurality of the wireless test modules of the WHAMS. As another example, fourth interface **1812** may implemented for a user to define parameters to increase module efficiency and establish a proper voltage for a wireless test module to conduct one or more tests, such as high and low voltage continuity, voltage isolation checks, data bus polarity and diode polarity checks, and resistance measurement checks, etc.

(93) In some embodiments, application interfaces **1800** include a fifth user interface **1814** for module software maintenance and updating. Fifth user interface **1814** may be implemented for a user to wirelessly update one or more software packages on the plurality of wireless test modules. Fifth user interface **1814** may be applied to facilitate an easy transition of new capabilities to the floor with minimal touch labor.

(94) In some embodiments, application interfaces **1800** include a sixth user interface **1816** for test

debugging and general module troubleshooting. Sixth user interface **1816** may be implemented to build one-off tests to either troubleshoot an electronic wiring harness or troubleshoot module functionality. The one-off tests may be created based on data of a selected electronic wiring harness by changing a plurality of parameters of the one-off tests for better performance.

(95) In some embodiments, the application interfaces **1800** may include a seventh user interface **1816** for test debugging and general module troubleshooting. Seventh user interface **1816** may be implemented to build one-off tests to either troubleshoot an electronic wiring harness or troubleshoot module functionality. The one-off tests may be created based on data of a selected electronic wiring harness by changing a plurality of parameters of the one-off tests for better performance.

(96) In some embodiments, the application interfaces **1800** include an eighth user interface **1818** to program smart test adaptors, such as hot-swap front ends, with their respective part numbers and pins configuration data. Once programed, eighth user interface **1818** may be implemented to identify a front end connected to a respective wireless test module and relay that information back to application interfaces **1800**. As a result, eighth user interface **1818** may be implemented to dynamically build module networks to monitor harness testing based on connectors attached to the respective wireless test module.

(97) FIGS. **18A** and **18B** illustrate example application interfaces **1800** of an operating software for testing of a plurality of electrical wiring harnesses by the wireless harness automated measurement system of FIG. **1**, according to particular embodiments. The wireless harness automated measurement system includes a plurality of wireless test modules. Each of the plurality of wireless test modules is connected to a respective electronic wiring harness for testing. FIG. **18A** shows a first test plan of calibration check on a first table **1824** for a first plurality of wireless test modules **1802**. In particular, the first test plan is generated to evaluate a status **1804** of the test results through color coded reporting. For example, a passing test is highlighted green and a failing test is highlighted red, orange, or yellow based on a condition of the failing test.

(98) FIG. **18B** shows a second test plan of high voltage isolation on a second table **1826** for a second plurality of wireless test modules **1822**. The controlling method may automatically build a map of the plurality of electrical wiring harnesses for testing. The controlling method may determine one or more connections available to each of the plurality of second plurality of wireless test modules **1822**. As a result, the controlling method may systematically build a plurality of tests to verify isolation or continuity of those connections for each of the plurality of second plurality of wireless test modules **1822**. For example, the controlling method may generate a plurality of continuity tests for each of the plurality of electrical wiring harnesses. The controlling method may validate source and destination reference designators are assigned to a wireless test module. As another example, the controlling method may generate isolation checks for each of the plurality of electrical wiring harnesses. Likewise, the second test plan is applied to check on all supposedly unused pins of electrical connectors of the plurality of electrical wiring harnesses to ensure there are no harness shorts or miss wires.

(99) In some embodiments, application interfaces **1800** may be used to call for an additional module to increase a plurality of possible routes to create a grounded circuit for testing. In particular, the controlling method may be used to perform one or more electrical tests on the plurality of electrical wiring harness, such as high and low voltage continuity, voltage isolation checks, data bus polarity and diode polarity checks, and resistance measurement checks, etc. Thus, the controlling method can use application interfaces **1800** for a user to monitor a health status and a functionality status for the plurality of wireless test modules of the WHAMS. In particular, the controlling method may determine testing conditions of the WHAMS based on the health status and the functionality status for the plurality of wireless test modules. Likewise, the controlling method may choose a plurality of actions for planning the testing of the plurality of electrical wiring harnesses, such as module identification, power off, and harness hookup. The controlling

method may allow for whole scale network changes, such as operational wireless channel and loading of different harnesses for different tests.

(100) FIG. **19** is a flow diagram illustrating an example method **1900** for testing of a wireless test module, according to particular embodiments. Method **1900** may begin at step **1910** where a plurality of electrical wiring harnesses, testing criteria, and a wireless harness automated measurement system (WHAMS) are accessed by using a computer server. In some embodiments, the WHAMS include a plurality of wireless test modules. In some embodiments, each of the plurality of electrical wiring harnesses is connected to a respective wireless test module of the WHAMS.

(101) At step **1920**, a test plan is generated for the plurality of electrical wiring harnesses. For example, the test plan may include one or more electrical tests on the plurality of electrical wiring harnesses (e.g., continuity checks, voltage isolation checks, diode polarity checks, resistance measurement checks, etc.). As another example, the test plan includes a map of the plurality of electrical wiring harnesses, a plurality of harness connections associated with each of the plurality of wireless test modules.

(102) At step **1930**, a plurality of wireless testing modules (WTMs) are determined using the test plan and the WHAMS. For example, the plurality of wireless test modules are selected based on various testing conditions. As another example, the plurality of wireless test modules are properly calibrated using a calibration fixture.

(103) At step **1940**, a plurality of test instructions are generated based on the test plan and the plurality of wireless testing modules. In some embodiments, each of the plurality of wireless test modules is operable to wirelessly receive one or more of the plurality of test instructions from the computer system. The plurality of test instructions are one or more signals, operations, commands, and the like.

(104) At step **1950**, one or more tests are performed using the plurality of wireless test modules on the plurality of electrical wiring harnesses according to the plurality of test instructions. Upon receiving the plurality of test instructions, the plurality of wireless test modules are configured to automatically perform the one or more electrical tests on the plurality of electrical wiring harnesses (e.g., continuity checks, voltage isolation checks, diode polarity checks, resistance measurement checks, etc.).

(105) At step **1960**, test results are sent to the computer system by wirelessly communicating with the computer system using the plurality of WTMs. In some embodiments, test results are collected by the computer system for the one or more electrical tests and displayed on a user interface for a user to visually inspect status of the plurality of electronic wiring harnesses through color coded reporting. For example, a passing test is highlighted in a green color and a failing test is highlighted in a different color, such as red, orange, or yellow, based on a condition of the failure of the failing test. After step **1960**, method **1900** may end.

(106) FIG. **20** illustrates an example computer system **2000**. In particular embodiments, one or more computer systems **2000** perform one or more steps of one or more methods described or illustrated herein. In particular embodiments, one or more computer systems **2000** provide functionality described or illustrated herein. In particular embodiments, software running on one or more computer systems **2000** performs one or more steps of one or more methods described or illustrated herein or provides functionality described or illustrated herein. Particular embodiments include one or more portions of one or more computer systems **2000**. Herein, reference to a computer system may encompass a computing device, and vice versa, where appropriate. Moreover, reference to a computer system may encompass one or more computer systems, where appropriate.

(107) This disclosure contemplates any suitable number of computer systems **2000**. This disclosure contemplates computer system **2000** taking any suitable physical form. As example and not by way of limitation, computer system **2000** may be an embedded computer system, a system-on-chip

(SOC), a single-board computer system (SBC) (such as, for example, a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, an interactive kiosk, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, a tablet computer system, an augmented/virtual reality device, or a combination of two or more of these. Where appropriate, computer system **2000** may include one or more computer systems **2000**; be unitary or distributed; span multiple locations; span multiple machines; span multiple data centers; or reside in a cloud, which may include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **2000** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein. As an example and not by way of limitation, one or more computer systems **2000** may perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. One or more computer systems **2000** may perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate.

(108) In particular embodiments, computer system **2000** includes a processor **2002**, memory **2004**, storage **2006**, an input/output (I/O) interface **2008**, a communication interface **2010**, and a bus **2012**. Although this disclosure describes and illustrates a particular computer system having a particular number of particular components in a particular arrangement, this disclosure contemplates any suitable computer system having any suitable number of any suitable components in any suitable arrangement.

(109) In particular embodiments, processor **2002** includes hardware for executing instructions, such as those making up a computer program. As an example and not by way of limitation, to execute instructions, processor **2002** may retrieve (or fetch) the instructions from an internal register, an internal cache, memory **2004**, or storage **2006**; decode and execute them; and then write one or more results to an internal register, an internal cache, memory **2004**, or storage **2006**. In particular embodiments, processor **2002** may include one or more internal caches for data, instructions, or addresses. This disclosure contemplates processor **2002** including any suitable number of any suitable internal caches, where appropriate. As an example and not by way of limitation, processor **2002** may include one or more instruction caches, one or more data caches, and one or more translation lookaside buffers (TLBs). Instructions in the instruction caches may be copies of instructions in memory **2004** or storage **2006**, and the instruction caches may speed up retrieval of those instructions by processor **2002**. Data in the data caches may be copies of data in memory **2004** or storage **2006** for instructions executing at processor **2002** to operate on; the results of previous instructions executed at processor **2002** for access by subsequent instructions executing at processor **2002** or for writing to memory **2004** or storage **2006**; or other suitable data. The data caches may speed up read or write operations by processor **2002**. The TLBs may speed up virtual-address translation for processor **2002**. In particular embodiments, processor **2002** may include one or more internal registers for data, instructions, or addresses. This disclosure contemplates processor **2002** including any suitable number of any suitable internal registers, where appropriate. Where appropriate, processor **2002** may include one or more arithmetic logic units (ALUs); be a multi-core processor; or include one or more processors **2002**. Although this disclosure describes and illustrates a particular processor, this disclosure contemplates any suitable processor.

(110) In particular embodiments, memory **2004** includes main memory for storing instructions for processor **2002** to execute or data for processor **2002** to operate on. As an example and not by way of limitation, computer system **2000** may load instructions from storage **2006** or another source (such as, for example, another computer system **2000**) to memory **2004**. Processor **2002** may then load the instructions from memory **2004** to an internal register or internal cache. To execute the instructions, processor **2002** may retrieve the instructions from the internal register or internal cache and decode them. During or after execution of the instructions, processor **2002** may write one or more results (which may be intermediate or final results) to the internal register or internal

cache. Processor **2002** may then write one or more of those results to memory **2004**. In particular embodiments, processor **2002** executes only instructions in one or more internal registers or internal caches or in memory **2004** (as opposed to storage **2006** or elsewhere) and operates only on data in one or more internal registers or internal caches or in memory **2004** (as opposed to storage **2006** or elsewhere). One or more memory buses (which may each include an address bus and a data bus) may couple processor **2002** to memory **2004**. Bus **2012** may include one or more memory buses, as described below. In particular embodiments, one or more memory management units (MMUs) reside between processor **2002** and memory **2004** and facilitate accesses to memory **2004** requested by processor **2002**. In particular embodiments, memory **2004** includes random access memory (RAM). This RAM may be volatile memory, where appropriate. Where appropriate, this RAM may be dynamic RAM (DRAM) or static RAM (SRAM). Moreover, where appropriate, this RAM may be single-ported or multi-ported RAM. This disclosure contemplates any suitable RAM. Memory **2004** may include one or more memories **2004**, where appropriate. Although this disclosure describes and illustrates particular memory, this disclosure contemplates any suitable memory.

(111) In particular embodiments, storage **2006** includes mass storage for data or instructions. As an example and not by way of limitation, storage **2006** may include a hard disk drive (HDD), a floppy disk drive, flash memory, an optical disc, a magneto-optical disc, magnetic tape, or a Universal Serial Bus (USB) drive or a combination of two or more of these. Storage **2006** may include removable or non-removable (or fixed) media, where appropriate. Storage **2006** may be internal or external to computer system **2000**, where appropriate. In particular embodiments, storage **2006** is non-volatile, solid-state memory. In particular embodiments, storage **2006** includes read-only memory (ROM). Where appropriate, this ROM may be mask-programmed ROM, programmable ROM (PROM), erasable PROM (EPROM), electrically erasable PROM (EEPROM), electrically alterable ROM (EAROM), or flash memory or a combination of two or more of these. This disclosure contemplates mass storage **2006** taking any suitable physical form. Storage **2006** may include one or more storage control units facilitating communication between processor **2002** and storage **2006**, where appropriate. Where appropriate, storage **2006** may include one or more storages **2006**. Although this disclosure describes and illustrates particular storage, this disclosure contemplates any suitable storage.

(112) In particular embodiments, I/O interface **2008** includes hardware, software, or both, providing one or more interfaces for communication between computer system **2000** and one or more I/O devices. Computer system **2000** may include one or more of these I/O devices, where appropriate. One or more of these I/O devices may enable communication between a person and computer system **2000**. As an example and not by way of limitation, an I/O device may include a keyboard, keypad, microphone, monitor, mouse, printer, scanner, speaker, still camera, stylus, tablet, touch screen, trackball, video camera, another suitable I/O device or a combination of two or more of these. An I/O device may include one or more sensors. This disclosure contemplates any suitable I/O devices and any suitable I/O interfaces **2008** for them. Where appropriate, I/O interface **2008** may include one or more device or software drivers enabling processor **2002** to drive one or more of these I/O devices. I/O interface **2008** may include one or more I/O interfaces **2008**, where appropriate. Although this disclosure describes and illustrates a particular I/O interface, this disclosure contemplates any suitable I/O interface.

(113) In particular embodiments, communication interface **2010** includes hardware, software, or both providing one or more interfaces for communication (such as, for example, wireless communications) between computer system **2000** and one or more other devices or system. As an example and not by way of limitation, communication interface **2010** may include a network interface controller (NIC) or network adapter for communicating with an Ethernet or other wire-based network or a wireless NIC (WNIC) or wireless adapter for communicating with a wireless network, such as a WI-FI network. This disclosure contemplates any suitable network and any

suitable communication interface **2010** for it. As an example and not by way of limitation, computer system **2000** may communicate with an ad hoc network, a personal area network (PAN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), or one or more portions of the Internet or a combination of two or more of these. One or more portions of one or more of these networks may be wired or wireless. As an example, computer system **2000** may communicate with a wireless PAN (WPAN) (such as, for example, a BLUETOOTH WPAN), a WI-FI network, a WI-MAX network, a cellular telephone network (such as, for example, a Global System for Mobile Communications (GSM) network, a Long-Term Evolution (LTE) network, or a 5G network), or other suitable wireless network or a combination of two or more of these. Computer system **2000** may include any suitable communication interface **2010** for any of these networks, where appropriate. Communication interface **2010** may include one or more communication interfaces **2010**, where appropriate. Although this disclosure describes and illustrates a particular communication interface, this disclosure contemplates any suitable communication interface.

(114) In particular embodiments, bus **2012** includes hardware, software, or both coupling components of computer system **2000** to each other. As an example and not by way of limitation, bus **2012** may include an Accelerated Graphics Port (AGP) or other graphics bus, an Enhanced Industry Standard Architecture (EISA) bus, a front-side bus (FSB), a HYPERTRANSPORT (HT) interconnect, an Industry Standard Architecture (ISA) bus, an INFINIBAND interconnect, a low-pin-count (LPC) bus, a memory bus, a Micro Channel Architecture (MCA) bus, a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCIe) bus, a serial advanced technology attachment (SATA) bus, a Video Electronics Standards Association local (VLB) bus, or another suitable bus or a combination of two or more of these. Bus **2012** may include one or more buses **2012**, where appropriate. Although this disclosure describes and illustrates a particular bus, this disclosure contemplates any suitable bus or interconnect.

(115) Herein, a computer-readable non-transitory storage medium or media may include one or more semiconductor-based or other integrated circuits (ICs) (such, as for example, field-programmable gate arrays (FPGAs) or application-specific ICs (ASICs)), hard disk drives (HDDs), hybrid hard drives (HHDs), optical discs, optical disc drives (ODDs), magneto-optical discs, magneto-optical drives, floppy diskettes, floppy disk drives (FDDs), magnetic tapes, solid-state drives (SSDs), RAM-drives, SECURE DIGITAL cards or drives, any other suitable computer-readable non-transitory storage media, or any suitable combination of two or more of these, where appropriate. A computer-readable non-transitory storage medium may be volatile, non-volatile, or a combination of volatile and non-volatile, where appropriate.

(116) Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

(117) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, feature, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable

to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Additionally, although this disclosure describes or illustrates particular embodiments as providing particular advantages, particular embodiments may provide none, some, or all of these advantages.

(118) The embodiments disclosed herein are only examples, and the scope of this disclosure is not limited to them. Particular embodiments may include all, some, or none of the components, elements, features, functions, operations, or steps of the embodiments disclosed herein. Certain embodiments are in particular disclosed in the attached claims directed to a method, a storage medium, a system and a computer program product, wherein any feature mentioned in one claim category, e.g. method, can be claimed in another claim category, e.g. system, as well. The dependencies or references back in the attached claims are chosen for formal reasons only. However, any subject matter resulting from a deliberate reference back to any previous claims (in particular multiple dependencies) can be claimed as well, so that any combination of claims and the features thereof are disclosed and can be claimed regardless of the dependencies chosen in the attached claims. The subject-matter which can be claimed includes not only the combinations of features as set out in the attached claims but also any other combination of features in the claims, wherein each feature mentioned in the claims can be combined with any other feature or combination of other features in the claims. Furthermore, any of the embodiments and features described or depicted herein can be claimed in a separate claim and/or in any combination with any embodiment or feature described or depicted herein or with any of the features of the attached claims.

Claims

1. An apparatus for charging a wireless harness automated measurement system (WHAMS), comprising: a charging cart operable to charge a plurality of wireless test modules (WTMs) of the WHAMS, wherein the charging cart includes a foundation assembled by a plurality of sheets and pipes, the foundation comprising one or more decks welded on the charging cart to position the plurality of charging slots; a mobile frame operable to support the charging cart; a plurality of light-emitting diode (LED) indicators operable to identify a status of the plurality of the WTMs during testing of the WHAMS; and a plurality of charging slots operable to charge the plurality of WTMs, wherein: each of the plurality of charging slots is associated with a respective one of the plurality of LED indicators; and each of the plurality of charging slots are keyed slots to receive one of the plurality of WTMs to ensure the plurality of WTMs are correctly placed.
2. The apparatus of claim 1, the charging cart further comprising: a power supply operable to supply a power of 1500 Watts (W) to charge the plurality of WTMs in parallel.
3. The apparatus of claim 1, wherein the charging cart is a double deck charging cart with a plurality of charging slots in a range of 150 charging slots to 200 charging slots.
4. The apparatus of claim 1, wherein the charging cart is a single deck charging cart with a plurality of charging slots in a range of 50 charging slots to 100 charging slots.
5. The apparatus of claim 1, wherein the charging cart is a mini charging cart with a plurality of charging slots in a range of 20 charge slots to 30 charging slots.
6. The apparatus of claim 1, wherein the charging cart is connected to the frame using bolts.
7. The apparatus of claim 1, wherein each of the plurality of LED indicators includes a red LED and a green LED.
8. The apparatus of claim 7, wherein: each of the plurality of LED indicators turns red to indicate that an identified WTM associated with the respective LED indicator is currently charging; each of the plurality of LED indicators turns green to indicate an identified WTM associated with the

respective LED indicator to locate before testing; and each of the plurality of LED indicators turns off to indicate that an identified WTM associated with the respective LED indicator finishes charging.

9. The apparatus of claim 7, wherein: each of the plurality of charging slots uses a 4 pogo pin layout to charge the plurality of WTMs; and the 4 pogo pin layout includes a 5 Volt (V) pin, a ground pin, a green LED pin, and a red LED pin.

10. A method comprising: receiving, using a mobile charging cart, a plurality of wireless test modules (WTMs) of a wireless harness automated measurement system (WHAMS), wherein the charging cart includes a foundation assembled by a plurality of sheets and pipes, the foundation comprising one or more decks welded on the charging cart to position the plurality of charging slots; charging, using the mobile charging cart, the plurality of WTMs, wherein the mobile charging cart includes a mobile frame operable to support the charging cart, a plurality of light-emitting diode (LED) indicators operable to identify a status of the plurality of the WTMs during testing of the WHAMS, and a plurality of charging slots operable to charge the plurality of WTMs, and wherein: each of the plurality of charging slots is associated with a respective one of the plurality of LED indicators; and each of the plurality of charging slots are keyed slots to receive one of the plurality of WTMs to ensure the plurality of WTMs are correctly placed; and identifying, using the mobile charging cart, the status of the plurality of the WTMs during testing of the WHAMS.

11. The method of claim 10, further comprising: using a power supply operable to supply a power of 1500 Watts (W) to charge the plurality of WTMs in parallel.

12. The method of claim 10, wherein the charging cart is a double deck charging cart comprising a plurality of charging slots in a range of 150 charging slots to 200 charging slots.

13. The method of claim 10, wherein the charging cart is a single deck charging cart comprising a plurality of charging slots in a range of 50 charging slots to 100 charging slots.

14. The method of claim 10, wherein the charging cart is a mini charging cart comprising a plurality of charging slots in a range of 20 charging slots to 30 charging slots.

15. The method of claim 10, wherein the charging cart is connected to the frame using bolts.

16. The method of claim 10, wherein each of the plurality of LED indicators includes a red LED and a green LED.

17. The method of claim 16, wherein: each of the plurality of LED indicators turns red to indicate that an identified WTM associated with the respective LED indicator is currently charging; each of the plurality of LED indicators turns green to indicate an identified WTM associated with the respective LED indicator to locate before testing; and each of the plurality of LED indicators turns off to indicate that an identified WTM associated with the respective LED indicator finishes charging.

18. The method of claim 16, wherein: each of the plurality of charging slots uses a 4 pogo pin layout to charge the plurality of WTMs; and the 4 pogo pin layout includes a 5 Volt (V) pin, a ground pin, a green LED pin, and a red LED pin.
