

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413518
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wood; Steven et al.

Mapping of IPsec tunnels to SD-WAN segmentation

Abstract

Generally, Software-Defined Wide Area Networks (SD-WAN) generally do not support network segmentation. The concepts disclosed herein connects IPsec SD-WAN fabric to a Virtual Routing and Forwarding (VRF) router and make use of a Software Defined Cloud Interconnect (SDCI) Router to route traffic from IPsec SD-WAN to various cloud services from the SDCI Router in the fabric. The concepts disclosed herein also provides for tunnel multi-plexing that takes incoming and outgoing traffic and maps VPNs to any service VRF associated with the cloud based services.

Inventors: Wood; Steven (Ottawa, CA), Sundararajan; Balaji (Fremont, CA), Ponnuru; Laxmikantha Reddy (San Ramon, CA), Shah; Avinash (Pleasanton, CA), Baruah; Pritam (Fremont, CA), Nataraj; Venkatesh (Union City, CA), Devendrchar; Ganesh (Milpitas, CA)

Applicant: Cisco Technology, Inc. (San Jose, CA)

Family ID: 94688239

Assignee: Cisco Technology, Inc. (San Jose, CA)

Appl. No.: 18/409701

Filed: January 10, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250071060 A1	Feb. 27, 2025

Related U.S. Application Data

us-provisional-application US 63578937 20230825

Publication Classification

Int. Cl.: H04L45/76 (20220101); H04L12/46 (20060101)

U.S. Cl.:

CPC H04L45/76 (20220501); H04L12/4633 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10826775	12/2019	Moreno	N/A	H04L 41/0893
11799831	12/2022	Vemulpali	N/A	H04L 61/5007
2016/0212098	12/2015	Roch	N/A	N/A
2016/0380823	12/2015	Shen	370/254	H04L 12/4633
2016/0380973	12/2015	Sullenberger	726/15	H04L 63/029
2017/0012870	12/2016	Blair	N/A	H04L 45/74
2020/0014661	12/2019	Mayya	N/A	H04L 49/35
2021/0036987	12/2020	Mishra	N/A	H04L 12/4641
2021/0044565	12/2020	Moreno	N/A	H04L 63/029
2021/0218598	12/2020	Ganapathy	N/A	H04L 45/64
2021/0226817	12/2020	Oswal	N/A	H04L 12/4679
2021/0399920	12/2020	Sundararajan	N/A	H04L 41/0893
2022/0052947	12/2021	Baruah	N/A	H04L 45/02
2022/0078109	12/2021	Hong	N/A	H04L 49/354
2022/0272033	12/2021	Jain	N/A	H04L 45/302
2022/0329477	12/2021	Chiganmi	N/A	H04L 41/0654
2023/0093190	12/2022	Ramachandran et al.	N/A	N/A
2023/0188502	12/2022	Thoria	726/15	H04L 12/4633
2023/0231802	12/2022	Vysotsky et al.	N/A	N/A
2023/0336377	12/2022	Hou	N/A	H04L 12/4604
2024/0406101	12/2023	Hawari	N/A	H04L 45/74

Primary Examiner: Book; Phyllis A

Attorney, Agent or Firm: Polsinelli P.C.

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This application claims priority to a U.S. Provisional Application No. 63/578,937, filed on Aug. 25, 2023, which is hereby incorporated by reference in its entirety.

BACKGROUND

(1) In a software-defined wide area network (SD-WAN), SD-WAN services are commonly deployed across a plurality of different “branches” of an SD-WAN, where each “branch” can represent a site (e.g., an office) of an interconnected network. Some branches may utilize devices that do not support segmentation, such as devices utilizing IPsec Tunnels, and generally do not connect with cloud-based networks.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Details of one or more aspects of the subject matter described in this disclosure are set forth in the accompanying drawings and the description below. However, the accompanying drawings illustrate only some typical aspects of this disclosure and are therefore not to be considered limiting of its scope. Other features, aspects, and advantages will become apparent from the description, the drawings and the claims.

(2) FIG. 1 illustrates an example of a high-level network architecture in accordance with some embodiments;

(3) FIG. 2 illustrates an example of a network topology in accordance with some embodiments.

(4) FIG. 3 illustrates an example of a diagram showing the operation of a protocol for managing an overlay network in accordance with some embodiments.

(5) FIG. 4 illustrates an example of a diagram showing the operation of virtual private networks for segmenting a network in accordance with some embodiments;

(6) FIG. 5 illustrates a network environment for enabling standard based IPsec connectivity from IPsec gateways to a VRF Router/VRF routing gateway in accordance with some embodiments;

(7) FIG. 6 illustrates a network architecture illustrating a flow of a data packet of the network traffic in accordance with some embodiments;

(8) FIG. 7 illustrates a network architecture for IPsec tunnel multiplexing in accordance with some embodiments;

(9) FIG. 8 illustrates an example method for routing packet traffic from an IPsec SD-WAN router to cloud-based services across a VRF Router/VRF routing gateway in accordance with some embodiments; and

(10) FIG. 9 shows an example of a system for implementing aspects of the present technology.

DESCRIPTION

(11) The detailed description set forth below is intended as a description of various configurations of embodiments and is not intended to represent the only configurations in which the subject matter of this disclosure can be practiced. The appended drawings are incorporated herein and constitute a part of the detailed description. The detailed description includes specific details for the purpose of providing a more thorough understanding of the subject matter of this disclosure. However, it will be clear and apparent that the subject matter of this disclosure is not limited to the specific details set forth herein and may be practiced without these details. In some instances, structures and components are shown in block diagram form in order to avoid obscuring the concepts of the subject matter of this disclosure.

Overview

(12) In some aspects, the techniques described herein relate to a method including: receiving, by a Virtual Routing and Forwarding (VRF) Router, a flow of traffic bound for a destination from a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router over an IPsec tunnel, wherein the destination of the flow of traffic is a cloud based service; determining, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; determining, by the VRF Router, a Virtual Routing and Forwarding (VRF) segment in a SD-WAN

fabric associated with the cloud based service; mapping, by the VRF Router, the VRF segment to the IP address of the LAN side; forwarding the flow of traffic originating from the LAN side of the router on the VRF segment associated with the cloud based service; and sending the flow of traffic to the destination via the VRF Router.

(13) In some aspects, the techniques described herein relate to a method, further including: receiving, by the VRF Router, the flow of traffic from the destination; determining, by the VRF Router, the IP address of the destination associated with the cloud based service and the mapping of the IP address of the LAN side to the VRF segment; and sending the flow of traffic via the IPsec tunnel to the LAN side of the SD-WAN router.

(14) In some aspects, the techniques described herein relate to a method, wherein the IP address of the LAN side of the SD-WAN router includes a IP-Security Group Tag (IP-SGT) binding.

(15) In some aspects, the techniques described herein relate to a method, wherein the IPsec tunnel performs multiplexing, the method further including: mapping, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplexing the VRF segments in the IPsec tunnel; segmenting, by the VRF Router, the one or more VRF segments based on the mapping; and sending the traffic to the one or more cloud-based destinations by the one or more VRF segments.

(16) In some aspects, the techniques described herein relate to a method, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a global VRF-Common Flow Table.

(17) In some aspects, the techniques described herein relate to a method, wherein the global VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.

(18) In some aspects, the techniques described herein relate to a method, wherein the VRF Router is a Software-Defined Cloud Interconnect (SDCI) router.

(19) In some aspects, the techniques described herein relate to a system including: a storage configured to store instructions; and a processor configured to execute the instructions and cause the processor to: receive, by a Virtual Routing and Forwarding (VRF) router, a flow of traffic bound for a destination from a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router over an IPsec tunnel, wherein the destination of the flow of traffic is a cloud based service; determine, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; determine, by the VRF Router, a Virtual Routing and Forwarding (VRF) segment in a SD-WAN fabric associated with the cloud based service; map, by the VRF Router, the VRF segment to the IP address of the LAN side; forward the flow of traffic originating from the LAN side of the router on the VRF segment associated with the cloud based service; and send the flow of traffic to the destination via the VRF Router.

(20) In some aspects, the techniques described herein relate to a method including: receiving, by a Virtual Routing and Forwarding (VRF) router, a flow of traffic bound for a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router from a cloud-based service; determining, by the VRF Router, a Virtual Routing and Forwarding (VRF) segment in a SD-WAN fabric associated with the cloud-based service; determining, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; mapping, by the VRF Router, the VRF segment to the IP address of the LAN side; forwarding the flow of traffic originating from the cloud-based service from the VRF segment associated with the cloud based service to an IPsec tunnel associated with the LAN side of the SD-WAN router; and sending the flow of traffic to the LAN side of the SD-WAN router via the IPsec tunnel.

(21) In some aspects, the techniques described herein relate to a method, further including: receiving, by the VRF Router, the flow of traffic from the LAN side of the SD-WAN router over the IPsec tunnel; determining, by the VRF Router, the VRF segment associated with the cloud based service based on the mapping of the IP address of the LAN side to the VRF segment; and sending, by the VRF Router, the flow of traffic to the cloud based service over the VRF segment.

- (22) In some aspects, the techniques described herein relate to a method, wherein the IP address of the LAN side of the SD-WAN router includes an IP-Security Group Tag (IP-SGT) binding.
- (23) In some aspects, the techniques described herein relate to a method, wherein the IPSec tunnel performs multiplexing, the method further including: mapping, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplexing the VRF segments in the IPSec tunnel; segmenting, by the VRF Router, the one or more VRF segments based on the mapping; and sending the traffic to the one or more cloud-based destinations by the one or more VRF segments.
- (24) In some aspects, the techniques described herein relate to a method, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a VRF-Common Flow Table.
- (25) In some aspects, the techniques described herein relate to a method, wherein the VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.

Example Embodiments

- (26) Various embodiments of the disclosure are discussed in detail below. While specific implementations are discussed, it should be understood that this is done for illustration purposes only. A person skilled in the relevant art will recognize that other components and configurations may be used without parting from the spirit and scope of the disclosure. Thus, the following description and drawings are illustrative and are not to be construed as limiting. Numerous specific details are described to provide a thorough understanding of the disclosure. However, in certain instances, well-known or conventional details are not described in order to avoid obscuring the description. References to one or an embodiment in the present disclosure can be references to the same embodiment or any embodiment; and, such references mean at least one of the embodiments.
- (27) Reference to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the disclosure. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Moreover, various features are described which may be exhibited by some embodiments and not by others.
- (28) The terms used in this specification generally have their ordinary meanings in the art, within the context of the disclosure, and in the specific context where each term is used. Alternative language and synonyms may be used for any one or more of the terms discussed herein, and no special significance should be placed upon whether or not a term is elaborated or discussed herein. In some cases, synonyms for certain terms are provided. A recital of one or more synonyms does not exclude the use of other synonyms. The use of examples anywhere in this specification including examples of any terms discussed herein is illustrative only, and is not intended to further limit the scope and meaning of the disclosure or of any example term. Likewise, the disclosure is not limited to various embodiments given in this specification.
- (29) Without intent to limit the scope of the disclosure, examples of instruments, apparatus, methods and their related results according to the embodiments of the present disclosure are given below. Note that titles or subtitles may be used in the examples for convenience of a reader, which in no way should limit the scope of the disclosure. Unless otherwise defined, technical and scientific terms used herein have the meaning as commonly understood by one of ordinary skill in the art to which this disclosure pertains. In the case of conflict, the present document, including definitions will control.
- (30) Additional features and advantages of the disclosure will be set forth in the description which follows, and in part will be obvious from the description, or can be learned by practice of the herein disclosed principles. The features and advantages of the disclosure can be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. These and other features of the disclosure will become more fully apparent from the following description

and appended claims, or can be learned by the practice of the principles set forth herein.

(31) Some routers have multiple LAN and WAN ports that connect LAN networks with Wide Area Network (WAN)-based provider networks. However, some of these routers do not support network segmentation because they rely on IPsec Tunnels to connect the LAN network with the WAN-based provider network. In other words, current technologies do not segment traffic coming from these types of routers. Thus, there is a need for a system, method, or computer-readable media to connect an IPsec-WAN fabric to a Virtual Routing and Forwarding (VRF) Router/VRF routing gateway implementation using network segmentation and route traffic from networks generally connected to the Internet over IPsec Tunnels to various other cloud-based services over networks that route traffic using segmentation technologies.

(32) The technology disclosed herein addresses this need in the industry. In particular, the present technology connects an IPsec-WAN fabric to a VRF Router/VRF segment base routing fabric and also makes use of a Software Defined Cloud Interconnect (SDCI) Router to route traffic from the IPsec-WAN fabric to various cloud services from the SDCI Router in the fabric.

(33) FIG. 1 illustrates an example of a network architecture **100** for implementing aspects of the present technology. An example of an implementation of the network architecture **100** is the Cisco® SD-WAN architecture. However, one of ordinary skill in the art will understand that, for the network architecture **100** and any other system discussed in the present disclosure, there can be additional or fewer component in similar or alternative configurations. The illustrations and examples provided in the present disclosure are for conciseness and clarity. Other embodiments may include different numbers and/or types of elements but one of ordinary skill the art will appreciate that such variations do not depart from the scope of the present disclosure.

(34) In this example, the network architecture **100** can comprise an orchestration plane **102**, a management plane **120**, a control plane **130**, and a data plane **140**. The orchestration plane can **102** assist in the automatic on-boarding of edge network devices **142** (e.g., switches, routers, etc.) in an overlay network. The orchestration plane **102** can include one or more physical or virtual network orchestrator appliances **104**. The network orchestrator appliance(s) **104** can perform the initial authentication of the edge network devices **142** and orchestrate connectivity between devices of the control plane **130** and the data plane **140**. In some embodiments, the network orchestrator appliance(s) **104** can also enable communication of devices located behind Network Address Translation (NAT). In some embodiments, physical or virtual Cisco® SD-WAN vBond appliances can operate as the network orchestrator appliance(s) **104**.

(35) The management plane **120** can be responsible for central configuration and monitoring of a network. The management plane **120** can include one or more physical or virtual network management appliances **122**. In some embodiments, the network management appliance(s) **122** can provide centralized management of the network via a graphical user interface to enable a user to monitor, configure, and maintain the edge network devices **142** and links (e.g., Internet transport network **160**, MPLS network **162**, 4G/LTE network **164**) in an underlay and overlay network. The network management appliance(s) **122** can support multi-tenancy and enable centralized management of logically isolated networks associated with different entities (e.g., enterprises, divisions within enterprises, groups within divisions, etc.). Alternatively or in addition, the network management appliance(s) **122** can be a dedicated network management system for a single entity. In some embodiments, physical or virtual Cisco® SD-WAN vManage appliances can operate as the network management appliance(s) **122**.

(36) The control plane **130** can build and maintain a network topology and make decisions on where traffic flows. The control plane **130** can include one or more physical or virtual network controller appliance(s) **132**. The network controller appliance(s) **132** can establish secure connections to each network device **142** and distribute route and policy information via a control plane protocol (e.g., Overlay Management Protocol (OMP) (discussed in further detail below), Open Shortest Path First (OSPF), Intermediate System to Intermediate System (IS-IS), Border

Gateway Protocol (BGP), Protocol-Independent Multicast (PIM), Internet Group Management Protocol (IGMP), Internet Control Message Protocol (ICMP), Address Resolution Protocol (ARP), Bidirectional Forwarding Detection (BFD), Link Aggregation Control Protocol (LACP), etc.). In some embodiments, the network controller appliance(s) **132** can operate as route reflectors. The network controller appliance(s) **132** can also orchestrate secure connectivity in the data plane **140** between and among the edge network devices **142**. For example, in some embodiments, the network controller appliance(s) **132** can distribute crypto key information among the network device(s) **142**. This can allow the network to support a secure network protocol or application (e.g., Internet Protocol Security (IPSec), Transport Layer Security (TLS), Secure Shell (SSH), etc.) without Internet Key Exchange (IKE) and enable scalability of the network. In some embodiments, physical or virtual Cisco® SD-WAN vSmart controllers can operate as the network controller appliance(s) **132**.

(37) The data plane **140** can be responsible for forwarding packets based on decisions from the control plane **130**. The data plane **140** can include the edge network devices **142**, which can be physical or virtual network devices. The edge network devices **142** can operate at the edges various network environments of an organization, such as in one or more data centers or colocation centers **150**, campus networks **152**, branch office networks **154**, home office networks **154**, and so forth, or in the cloud (e.g., Infrastructure as a Service (IaaS), Platform as a Service (PaaS), SaaS, and other cloud service provider networks). The edge network devices **142** can provide secure data plane connectivity among sites over one or more WAN transports, such as via one or more Internet transport networks **160** (e.g., Digital Subscriber Line (DSL), cable, etc.), MPLS networks **162** (or other private packet-switched network (e.g., Metro Ethernet, Frame Relay, Asynchronous Transfer Mode (ATM), etc.), mobile networks **164** (e.g., 3G, 4G/LTE, 5G, etc.), or other WAN technology (e.g., Synchronous Optical Networking (SONET), Synchronous Digital Hierarchy (SDH), Dense Wavelength Division Multiplexing (DWDM), or other fiber-optic technology; leased lines (e.g., T1/E1, T3/E3, etc.); Public Switched Telephone Network (PSTN), Integrated Services Digital Network (ISDN), or other private circuit-switched network; small aperture terminal (VSAT) or other satellite network; etc.). The edge network devices **142** can be responsible for traffic forwarding, security, encryption, quality of service (QOS), and routing (e.g., BGP, OSPF, etc.), among other tasks. In some embodiments, physical or virtual Cisco® SD-WAN vEdge routers can operate as the edge network devices **142**.

(38) FIG. 2 illustrates an example of a network topology **200** for showing various aspects of the network architecture **100**. The network topology **200** can include a management network **202**, a pair of network sites **204A** and **204B** (collectively, **204**) (e.g., the data center(s) **150**, the campus network(s) **152**, the branch office network(s) **154**, the home office network(s) **156**, cloud service provider network(s), etc.), and a pair of Internet transport networks **160A** and **160B** (collectively, **160**). The management network **202** can include one or more network orchestrator appliances **104**, one or more network management appliance **122**, and one or more network controller appliances **132**. Although the management network **202** is shown as a single network in this example, one of ordinary skill in the art will understand that each element of the management network **202** can be distributed across any number of networks and/or be co-located with the sites **204**. In this example, each element of the management network **202** can be reached through either transport network **160A** or **160B**.

(39) Each site can include one or more endpoints **206** connected to one or more site network devices **208**. The endpoints **206** can include general purpose computing devices (e.g., servers, workstations, desktop computers, etc.), mobile computing devices (e.g., laptops, tablets, mobile phones, etc.), wearable devices (e.g., watches, glasses or other head-mounted displays (HMDs), car devices, etc.), and so forth. The endpoints **206** can also include Internet of Things (IoT) devices or equipment, such as agricultural equipment (e.g., livestock tracking and management systems, watering devices, unmanned aerial vehicles (UAVs), etc.); connected cars and other vehicles; smart

home sensors and devices (e.g., alarm systems, security cameras, lighting, appliances, media players, HVAC equipment, utility meters, windows, automatic doors, door bells, locks, etc.); office equipment (e.g., desktop phones, copiers, fax machines, etc.); healthcare devices (e.g., pacemakers, biometric sensors, medical equipment, etc.); industrial equipment (e.g., robots, factory machinery, construction equipment, industrial sensors, etc.); retail equipment (e.g., vending machines, point of sale (POS) devices, Radio Frequency Identification (RFID) tags, etc.); smart city devices (e.g., street lamps, parking meters, waste management sensors, etc.); transportation and logistical equipment (e.g., turnstiles, rental car trackers, navigational devices, inventory monitors, etc.); and so forth.

(40) The site network devices **208** can include physical or virtual switches, routers, and other network devices. Although the site **204A** is shown including a pair of site network devices and the site **204B** is shown including a single site network device in this example, the site network devices **208** can comprise any number of network devices in any network topology, including multi-tier (e.g., core, distribution, and access tiers), spine-and-leaf, mesh, tree, bus, hub and spoke, and so forth. For example, in some embodiments, one or more data center networks may implement the Cisco® Application Centric Infrastructure (ACI) architecture and/or one or more campus networks may implement the Cisco® Software Defined Access (SD-Access or SDA) architecture. The site network devices **208** can connect the endpoints **206** to one or more edge network devices **142**, and the edge network devices **142** can be used to directly connect to the transport networks **160**.

(41) In some embodiments, “color” can be used to identify an individual WAN transport network, and different WAN transport networks may be assigned different colors (e.g., mpls, private1, biz-internet, metro-ethernet, lte, etc.). In this example, the network topology **200** can utilize a color called “biz-internet” for the Internet transport network **160A** and a color called “public-internet” for the Internet transport network **160B**.

(42) In some embodiments, each edge network device **208** can form a Datagram Transport Layer Security (DTLS) or TLS control connection to the network controller appliance(s) **132** and connect to any network control appliance **132** over each transport network **160**. In some embodiments, the edge network devices **142** can also securely connect to edge network devices in other sites via IPsec tunnels. In some embodiments, the BFD protocol may be used within each of these tunnels to detect loss, latency, jitter, and path failures.

(43) On the edge network devices **142**, color can be used help to identify or distinguish an individual WAN transport tunnel (e.g., no same color may be used twice on a single edge network device). Colors by themselves can also have significance. For example, the colors metro-ethernet, mpls, and private1, private2, private3, private4, private5, and private6 may be considered private colors, which can be used for private networks or in places where there is no NAT addressing of the transport IP endpoints (e.g., because there may be no NAT between two endpoints of the same color). When the edge network devices **142** use a private color, they may attempt to build IPsec tunnels to other edge network devices using native, private, underlay IP addresses. The public colors can include 3g, biz, internet, blue, bronze, custom1, custom2, custom3, default, gold, green, lte, public-internet, red, and silver. The public colors may be used by the edge network devices **142** to build tunnels to post-NAT IP addresses (if there is NAT involved). If the edge network devices **142** use private colors and need NAT to communicate to other private colors, the carrier setting in the configuration can dictate whether the edge network devices **142** use private or public IP addresses. Using this setting, two private colors can establish a session when one or both are using NAT.

(44) FIG. 3 illustrates an example of a diagram **300** showing the operation of OMP, which may be used in some embodiments to manage an overlay of a network (e.g., the network architecture **100**). In this example, OMP messages **302A** and **302B** (collectively, **302**) may be transmitted back and forth between the network controller appliance **132** and the edge network devices **142A** and **142B**, respectively, where control plane information, such as route prefixes, next-hop routes, crypto keys,

policy information, and so forth, can be exchanged over respective secure DTLS or TLS connections **304A** and **304B**. The network controller appliance **132** can operate similarly to a route reflector. For example, the network controller appliance **132** can receive routes from the edge network devices **142**, process and apply any policies to them, and advertise routes to other edge network devices **142** in the overlay. If there is no policy defined, the edge network devices **142** may behave in a manner similar to a full mesh topology, where each edge network device **142** can connect directly to another edge network device **142** at another site and receive full routing information from each site.

(45) OMP can advertise three types of routes: OMP routes, which can correspond to prefixes that are learned from the local site, or service side, of the edge network device **142**. The prefixes can be originated as static or connected routes, or from within, for example, the OSPF or BGP protocols, and redistributed into OMP so they can be carried across the overlay. OMP routes can advertise attributes such as transport location (TLOC) information (which can similar to a BGP next-hop IP address) and other attributes such as origin, originator, preference, site identifier, tag, and virtual private network (VPN). An OMP route may be installed in the forwarding table if the TLOC to which it points is active. TLOC routes, which can correspond to logical tunnel termination points on the edge network devices **142** that connect into the transport networks **160**. In some embodiments, a TLOC route can be uniquely identified and represented by a three-tuple, including an IP address, link color, and encapsulation (e.g., Generic Routing Encapsulation (GRE), IPsec, etc.). In addition to system IP address, color, and encapsulation, TLOC routes can also carry attributes such as TLOC private and public IP addresses, carrier, preference, site identifier, tag, and weight. In some embodiments, a TLOC may be in an active state on a particular edge network device **142** when an active BFD session is associated with that TLOC. Service routes, which can represent services (e.g., firewall, distributed denial of service (DDoS) mitigator, load balancer, intrusion prevent system (IPS), intrusion detection systems (IDS), WAN optimizer, etc.) that may be connected to the local sites of the edge network devices **142** and accessible to other sites for use with service insertion. In addition, these routes can also include VPNs; the VPN labels can be sent in an update type to tell the network controller appliance **132** what VPNs are serviced at a remote site.

(46) In the example of FIG. 3, OMP is shown running over the DTLS/TLS tunnels **304** established between the edge network devices **142** and the network controller appliance **132**. In addition, the diagram **300** shows an IPsec tunnel **306A** established between TLOC **308A** and **308C** over the WAN transport network **160A** and an IPsec tunnel **306B** established between TLOC **308B** and TLOC **308D** over the WAN transport network **160B**. Once the IPsec tunnels **306A** and **306B** are established, BFD can be enabled across each of them.

(47) FIG. 4 illustrates an example of a diagram **400** showing the operation of VPNs, which may be used in some embodiments to provide segmentation for a network (e.g., the network architecture **100**). VPNs can be isolated from one another and can have their own forwarding tables. An interface or sub-interface can be explicitly configured under a single VPN and may not be part of more than one VPN. Labels may be used in OMP route attributes and in the packet encapsulation, which can identify the VPN to which a packet belongs. The VPN number can be a four-byte integer with a value from 0 to 65530. In some embodiments, the network orchestrator appliance(s) **104**, network management appliance(s) **122**, network controller appliance(s) **132**, and/or edge network device(s) **142** can each include a transport VPN **402** (e.g., VPN number 0) and a management VPN **404** (e.g., VPN number 512). The transport VPN **402** can include one or more physical or virtual network interfaces (e.g., network interfaces **410A** and **410B**) that respectively connect to WAN transport networks (e.g., the MPLS network **162** and the Internet transport network **160**). Secure DTLS/TLS connections to the network controller appliance(s) **132** or between the network controller appliance(s) **132** and the network orchestrator appliance(s) **104** can be initiated from the transport VPN **402**. In addition, static or default routes or a dynamic routing protocol can be

configured inside the transport VPN **402** to get appropriate next-hop information so that the control plane **130** may be established and IPsec tunnels **306** (not shown) can connect to remote sites.

(48) The management VPN **404** can carry out-of-band management traffic to and from the network orchestrator appliance(s) **104**, network management appliance(s) **122**, network controller appliance(s) **132**, and/or edge network device(s) **142** over a network interface **410C**. In some embodiments, the management VPN **404** may not be carried across the overlay network.

(49) In addition to the transport VPN **402** and the management VPN **404**, the network orchestrator appliance(s) **104**, network management appliance(s) **122**, network controller appliance(s) **132**, or edge network device(s) **142** can also include one or more service-side VPNs **406**. The service-side VPN **406** can include one or more physical or virtual network interfaces (e.g., network interfaces **410C** and **410D**) that connect to one or more local-site networks **412** and carry user data traffic. The service-side VPN(s) **406** can be enabled for features such as OSPF or BGP, Virtual Router Redundancy Protocol (VRRP), QOS, traffic shaping, policing, and so forth. In some embodiments, user traffic can be directed over IPsec tunnels to other sites by redistributing OMP routes received from the network controller appliance(s) **132** at the site **412** into the service-side VPN routing protocol. In turn, routes from the local site **412** can be advertised to other sites by advertising the service VPN routes into the OMP routing protocol, which can be sent to the network controller appliance(s) **132** and redistributed to other edge network devices **142** in the network. Although the network interfaces **410A-E** (collectively, **410**) are shown to be physical interfaces in this example, one of ordinary skill in the art will appreciate that the interfaces **410** in the transport and service VPNs can also be sub-interfaces instead.

(50) FIG. 5 illustrates network environment **500** for enabling standard based IPsec connectivity from the IPsec gateways **504** of the IPsec SD-WAN **502** to the VRF Router/VRF routing gateways **520** solution, thereby enabling LAN traffic to reach cloud-based network **510** services and servers via the VRF Router/VRF routing gateway **520**. In some embodiments, the cloud-based networks **510** may be local cloud-based destinations, or may be third party cloud-based network **510** services and servers, such as Amazon Web Services (AWS) cloud, Azure cloud, Oracle cloud, Google cloud, Microsoft dynamic, CRM, GCP, or any other third-party cloud-based network **510**.

(51) In particular, in some embodiments, the present technology enables tunnel Virtual Routing and Forwarding (VRF) Multi-Plexing on a VPN (Virtual Private Network) on the VRF Router/VRF routing gateway **520**. In particular, when VRF traffic comes and goes from different cloud-based networks **510**, the VRF traffic may be translated to specific IPsec tunnels **522** such that the VRF traffic coming and going from the cloud-based networks **510** may be connected to the IPsec Gateways **504** of the IPsec SD-WAN.

(52) Furthermore, the present technology connects the IPsec gateways **504** to the VRF Router/VRF routing gateway **520** having a tunnel VRF using the IPsec tunnels **522**. As discussed further below with respect to FIG. 7, the IPsec tunnels **522** can be multiplexed, such that the VRF traffic can be mapped to a specific IPsec tunnel **522** that may be part of a group of tunnels that are multiplexed into a larger tunnel. As further discussed below, this configuration allows the VRF Router/VRF routing gateway **520** to know which specific IPsec tunnel **522** the VRF traffic is sent on.

(53) Furthermore, the present technology enables IPsec gateways **504** to export an IP-SGT (Security Group Tag) binding associated with the IPsec gateways **504** of the IPsec SD-WAN **502** using an Identity Service Engine (ISE) **508** in a global IPsec SD-WAN Fabric. Furthermore, the VRF Router/VRF routing gateway **520** will learn the IP-SGT bindings, and using the same ISE **508**, may map the IP-SGT bindings to the VRF **520** in IPsec SD-WAN Fabric. In particular, the IPsec gateways **504** are connected to an IPsec gateway controller **506** which manages all of the IPsec gateways **504**. The IPsec gateway controller **506** connects to and communicates with the ISE **508**, and is capable of taking the IP addresses and IP-SGT bindings and storing them on the ISE **508**. Furthermore, the VRF Router/VRF routing gateway **520** connects to and communicates with a SD-WAN controller **526** that is also in communication with the ISE **508**. While this SD-WAN

controller **526** may not forward or direct any of the VRF traffic itself, it is capable of identifying the source or destination of the VRF traffic coming from the cloud-based networks **510**, and sends this information to the ISE **508**. The ISE **508** then maintains a mapping table (as discussed further below) to determine which VRF traffic goes to which IPsec gateway **504**. Thus, the VRF Router/VRF routing gateway **520**, which programs and communicates with the SD-WAN controller **526**, will connect to the IPsec gateways **504** via the IPsec tunnels **522** in VPN 0 with the VRF-IP-SGT bindings mapped by the ISE **508** due to the ISE **508** connection with the IPsec gateway controller **506**. Further, because of this configuration, the VRF Router/VRF routing gateway **520** may also enable reverse traffic origination for lookup.

(54) FIG. **6** illustrates a network architecture **600** illustrating a journey of a data packet of the network traffic as it travels over the Internet **610** from a VRF Router **602** to an IPsec SD-WAN Router **604** in accordance with the concepts disclosed herein. In some embodiments, the VRF Router **602** is the same device as the VRF Router/VRF routing gateway **520**, while in other embodiments the VRF Router **602** is associated with the VRF Router/VRF routing gateway **520**. In some embodiments, the IPsec SD-WAN Router **604** is the same device as the IPsec gateways **504**, while in other embodiments the IPsec SD-WAN Router **604** is associated with the IPsec gateways **504**. In some embodiments, the IPsec gateways **504** access the cloud-based network **510** services and servers. Packet traffic on the LAN side of IPsec Router **604** is routed over a WAN interface into IPsec tunnel **606**. If it is determined that the packet traffic is bound for a destination that is part of the cloud-based network **510** service/server, the IPsec SD-WAN Router **604** updates the mapping of an IP Address on its LAN side and an IP address of the cloud-based network **510**.

(55) Next, the VRF Router **602** learns or looks up the IP-SGT bindings associated with the VRF 1 **608a** and VRF 2 **608b** (VRF collectively **608**) and the destination of the packet traffic by the SD-WAN controller **526**. If the destination of the traffic IP subnet falls in a range of IP address for IaaS (Infrastructure as a Service), the VRF Router **602** would transmit the packet traffic originating from the IPsec SD-WAN Router **604** on the VRF segment **608a** and **608b** associated with the IP-SGT binding. In order to map the incoming SD-WAN packet traffic, a global VRF-CFT (Common flow table) table of the ISE **508** that provides the mapping between the VRF and IP-SGT is updated to reflect the VRF-IP-SGT bindings mapping.

(56) As a non-limiting example illustrating this concept, if packet traffic is routed to an AWS destination cloud, and if a VRF is associated with the AWS prefix (e.g., VRF 1 **608a**), then the packet traffic originating from the IPsec SD-WAN Router **604** will get routed on VRF 1 **608a**. Similarly, if the packet traffic originating from the IPsec SD-WAN Router **604** is accessing Microsoft Dynamics 365, or CRM, then such packet traffic may land on a separate VRF associated with CRM (e.g., VRF 2 **608b**), from a SDCI Router with multi-cloud network connectivity, to Azure ER Gateway Microsoft Public Service on VRF 2 **608b**. Thus, this technology enables LAN traffic from the IPsec SD-WAN Router **604** to reach destination servers **510** via the VRF Router **602**.

(57) When the cloud-based destination **510** server responds, the packet traffic from the cloud lands on the VRF Router **602** on service side. Then, the VRF Router **602** will inspect the traffic source IP and identify the VRF context, and IP-SGT bindings and follow routing to send the packet traffic via IPsec tunnel **606** to the IPsec Router **604** that originated that specific packet flow. Furthermore, as discussed further below, the technology further enables tunnel multi-plexing to send packet traffic via the IPsec tunnel **606** to the IPsec Router **604**.

(58) FIG. **7** illustrates a network architecture **700** for IPsec tunnel multiplexing. In particular, the technology disclosed herein supports network segmentation when connecting a VRF Router/VRF Routing gateway **702** with an IPsec SD-WAN **704** over an IPsec tunnel **710** to send and receive traffic from cloud-based networks **720**. In particular, the disclosed technology may take incoming packet traffic and outgoing packet traffic, and may map a VPN 0 to any service VRF **722**. This implementation follows the following flow. First, incoming packet traffic from IPsec SD-WAN

704 is transmitted on a VPN 0 VRF Router/VRF Routing gateway **702**. From this and as discussed above, the IP-SGT binding is known and exchanged between the IPsec gateway controller **506**, the SD-WAN controller **526**, and the ISE **508** based on the packet destination in the SD-WAN Fabric. The technology then may auto-derive the VRF and map the VRF Router/VRF Routing gateway **702** incoming packet traffic to a service VRF **722** in the common flow table (CFT) of the ISE **508**. Likewise, if a packet originated on the VRF Router/VRF Routing gateway **702**, and the server happens to be on IPsec SD-WAN **704** side, the system may take the packet traffic out on service VRF **722** and send the traffic on VRF Router/VRF Routing gateway **702**. In this circumstance, the system may map inside the CFT the IPsec tunnel **710** multiplexing information so when return traffic comes back on the same IPsec tunnel **710** from IPsec SD-WAN **704** end back to VRF Router/VRF Routing gateway **702 702**, the CFT will have the VPN-Context to map it back to the service VRF **722**, and ultimately the cloud-based network **720**. Thus, the mapping of the IP-SGT binding to the VRF in the CFT enables the system to multiplex the VRF traffic into the IPsec tunnel **710** and confirm that the traffic arrives at and is sent to the correct destinations.

(59) FIG. **8** illustrates an example method **800** for routing packet traffic from IPsec SD-WAN routers to cloud-based services across the VRF Router/VRF routing gateway. Although the example method **800** depicts a particular sequence of operations, the sequence may be altered without departing from the scope of the present disclosure. For example, some of the operations depicted may be performed in parallel or in a different sequence that does not materially affect the function of the method **800**. In other examples, different components of an example device or system that implements the method **800** may perform functions at substantially the same time or in a specific sequence.

(60) According to some examples, the method includes accessing a cloud based service by a Local Area Network (LAN) side of a router at block **805**. For example, the IPsec gateways **504** illustrated in FIG. **5** may access the cloud based service by the LAN side of the router.

(61) According to some examples, the method includes routing a flow of traffic on the LAN side of the router over a Wide Area Network (WAN) interface into an IPsec tunnel at block **810**. For example, the IPsec gateways **504** illustrated in FIG. **5** may route the flow of traffic on the LAN side of the router over the WAN interface into the IPsec tunnel.

(62) According to some examples, the method includes updating a mapping of an IP address of the LAN side and an IP address of a destination associated with the cloud based service by the router at block **815**. For example, the IPsec gateway **504** illustrated in FIG. **5** may update the mapping of the IP address of the LAN side and the IP address of a destination associated with the cloud based service. In some embodiments, the flow of traffic is bound for the cloud based service.

(63) According to some examples, the method includes determining an IP-Security Group Tags (IP-SGT) binding and the destination of the traffic based on the IP Address of the LAN side and the IP Address of the destination by a Software-Defined Wide Area Network (SD-WAN) router at block **820**. For example, the VRF Router/VRF Router **602** illustrated in FIG. **6** may determine the IP-SGT binding and the destination of the traffic based on the IP Address of the LAN side and the IP Address of the destination. In some embodiments, the determination of the IP-SGT bindings only occurs if the destination IP address falls in a range of IP addresses for Infrastructure as a Service (IaaS). In some embodiments, the SD-WAN router is a Software-Defined Cloud Interconnect (SDCI) router.

(64) According to some examples, the method includes mapping the IP-SGT binding to a Virtual Routing and Forwarding (VRF) segment in a SD-WAN fabric associated with the cloud base service by the SD-WAN router at block **825**. For example, the VRF Router/VRF Router **602** illustrated in FIG. **6** may map the IP-SGT binding to the VRF segment in the SD-WAN fabric associated with the cloud base service. In some embodiments, the mapping of the IP-SGT binding to the VRF segment is updated on a global VRF-Common Flow Table (CFT).

(65) According to some examples, the method includes routing the flow of traffic originating from

the LAN side of the router on the VRF segment associated with the cloud based service at block **830**. For example, the packet traffic illustrated in FIG. **6** from the LAN side of the router may land on the VRF segment associated with the cloud based service.

(66) Further, the method comprises mapping one or more VRF segments from one or more cloud based services to a Virtual Private Network (VPN) associated with the IPsec tunnel. For example, the VRF Router/VRF routing gateway **702** illustrated in FIG. **7** may map one or more VRF segments from one or more cloud based services to a Virtual Private Network (VPN) associated with the IPsec tunnel. In some embodiments, the IPsec tunnel may perform multiplexing. In some embodiments, the mapping of the one or more VRF segments to the VPN is stored on a CFT. Further, the method comprises sending the flow of traffic via the IPsec tunnel based on the mapping.

(67) According to some examples, the method includes sending the flow of traffic to the destination via the SD-WAN router at block **835**. For example, the VRF Router/VRF Router **602** illustrated in FIG. **6** may send the flow of traffic to the destination.

(68) According to some examples, the method includes routing the flow of traffic from the cloud based service on a service side of the VRF Router/VRF Router at block **840**. For example, the VRF **608** illustrated in FIG. **6** may receive the flow of traffic from the cloud based service on a service side of the SD-WAN router.

(69) According to some examples, the method includes determining the IP address of the destination associated with the cloud based service and the mapping of the IP-SGT binding to the VRF segment by the SD-WAN router at block **845**. For example, the VRF Router/VRF Router **602** illustrated in FIG. **6** may determine the IP address of the destination associated with the cloud based service and the mapping of the IP-SGT binding to the VRF segment.

(70) According to some examples, the method includes sending the flow of traffic via the IPsec tunnel to the LAN side of the router that originated the flow of traffic at block **850**. For example, the VRF Router/VRF Router **602** illustrated in FIG. **6** may send the flow of traffic via the IPsec tunnel to the LAN side of the router that originated the flow of traffic, or the IPsec SD-WAN Router **604** illustrated in FIG. **6**.

(71) FIG. **9** shows an example of computing system **900**, which can be for example any computing device, or any component thereof in which the components of the system are in communication with each other using connection **905**. Connection **905** can be a physical connection via a bus, or a direct connection into processor **910**, such as in a chipset architecture. Connection **905** can also be a virtual connection, networked connection, or logical connection.

(72) In some embodiments, computing system **900** is a distributed system in which the functions described in this disclosure can be distributed within a datacenter, multiple data centers, a peer network, etc. In some embodiments, one or more of the described system components represents many such components each performing some or all of the function for which the component is described. In some embodiments, the components can be physical or virtual devices.

(73) Example system **900** includes at least one processing unit (CPU or processor) **910** and connection **905** that couples various system components including system memory **915**, such as read-only memory (ROM) **920** and random access memory (RAM) **925** to processor **910**.

Computing system **900** can include a cache of high-speed memory **912** connected directly with, in close proximity to, or integrated as part of processor **910**.

(74) Processor **910** can include any general purpose processor and a hardware service or software service, such as services **932**, **934**, and **936** stored in storage device **930**, configured to control processor **910** as well as a special-purpose processor where software instructions are incorporated into the actual processor design. Processor **910** may essentially be a completely self-contained computing system, containing multiple cores or processors, a bus, memory controller, cache, etc. A multi-core processor may be symmetric or asymmetric.

(75) To enable user interaction, computing system **900** includes an input device **945**, which can

represent any number of input mechanisms, such as a microphone for speech, a touch-sensitive screen for gesture or graphical input, keyboard, mouse, motion input, speech, etc. Computing system **900** can also include output device **935**, which can be one or more of a number of output mechanisms known to those of skill in the art. In some instances, multimodal systems can enable a user to provide multiple types of input/output to communicate with computing system **900**.

Computing system **900** can include communications interface **940**, which can generally govern and manage the user input and system output. There is no restriction on operating on any particular hardware arrangement, and therefore the basic features here may easily be substituted for improved hardware or firmware arrangements as they are developed.

(76) Storage device **930** can be a non-volatile memory device and can be a hard disk or other types of computer readable media which can store data that are accessible by a computer, such as magnetic cassettes, flash memory cards, solid state memory devices, digital versatile disks, cartridges, random access memories (RAMs), read-only memory (ROM), and/or some combination of these devices.

(77) The storage device **930** can include software services, servers, services, etc., that when the code that defines such software is executed by the processor **910**, it causes the system to perform a function. In some embodiments, a hardware service that performs a particular function can include the software component stored in a computer-readable medium in connection with the necessary hardware components, such as processor **910**, connection **905**, output device **935**, etc., to carry out the function.

(78) For clarity of explanation, in some instances, the present technology may be presented as including individual functional blocks including functional blocks comprising devices, device components, steps or routines in a method embodied in software, or combinations of hardware and software.

(79) Any of the steps, operations, functions, or processes described herein may be performed or implemented by a combination of hardware and software services or services, alone or in combination with other devices. In some embodiments, a service can be software that resides in memory of a client device and/or one or more servers of a content management system and perform one or more functions when a processor executes the software associated with the service. In some embodiments, a service is a program or a collection of programs that carry out a specific function. In some embodiments, a service can be considered a server. The memory can be a non-transitory computer-readable medium.

(80) In some embodiments, the computer-readable storage devices, mediums, and memories can include a cable or wireless signal containing a bit stream and the like. However, when mentioned, non-transitory computer-readable storage media expressly exclude media such as energy, carrier signals, electromagnetic waves, and signals per se.

(81) Methods according to the above-described examples can be implemented using computer-executable instructions that are stored or otherwise available from computer-readable media. Such instructions can comprise, for example, instructions and data which cause or otherwise configure a general purpose computer, special purpose computer, or special purpose processing device to perform a certain function or group of functions. Portions of computer resources used can be accessible over a network. The executable computer instructions may be, for example, binaries, intermediate format instructions such as assembly language, firmware, or source code. Examples of computer-readable media that may be used to store instructions, information used, and/or information created during methods according to described examples include magnetic or optical disks, solid-state memory devices, flash memory, USB devices provided with non-volatile memory, networked storage devices, and so on.

(82) Devices implementing methods according to these disclosures can comprise hardware, firmware and/or software, and can take any of a variety of form factors. Typical examples of such form factors include servers, laptops, smartphones, small form factor personal computers, personal

digital assistants, and so on. The functionality described herein also can be embodied in peripherals or add-in cards. Such functionality can also be implemented on a circuit board among different chips or different processes executing in a single device, by way of further example.

(83) The instructions, media for conveying such instructions, computing resources for executing them, and other structures for supporting such computing resources are means for providing the functions described in these disclosures.

(84) Aspect 1. A method comprising: receiving, by a Virtual Routing and Forwarding (VRF) Router, a flow of traffic bound for a destination from a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router over an IPsec tunnel, wherein the destination of the flow of traffic is a cloud based service; determining, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; determining, by the VRF Router, a VRF segment in a SD-WAN fabric associated with the cloud based service; mapping, by the VRF Router, the VRF segment to the IP address of the LAN side; forwarding the flow of traffic originating from the LAN side of the router on the VRF segment associated with the cloud based service; and sending the flow of traffic to the destination via the VRF Router.

(85) Aspect 2. The method of aspect 1, further comprising: receiving, by the VRF Router, the flow of traffic from the destination; determining, by the VRF Router, the IP address of the destination associated with the cloud based service and the mapping of the IP address of the LAN side to the VRF segment; and sending the flow of traffic via the IPsec tunnel to the LAN side of the SD-WAN router.

(86) Aspect 3. The method of aspect 1, wherein the IP address of the LAN side of the SD-WAN router includes a IP-Security Group Tag (IP-SGT) binding.

(87) Aspect 4. The method of aspect 3, wherein the IPsec tunnel performs multiplexing, the method further comprising: mapping, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplexing the VRF segments in the IPsec tunnel; segmenting, by the VRF Router, the one or more VRF segments based on the mapping; and sending the traffic to the one or more cloud-based destinations by the one or more VRF segments.

(88) Aspect 5. The method of aspect 3, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a global VRF-Common Flow Table.

(89) Aspect 6. The method of aspect 5, wherein the global VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.

(90) Aspect 7. The method of aspect 1, wherein the VRF Router is a Software-Defined Cloud Interconnect (SDCI) router.

(91) Aspect 8. A system comprising: a storage configured to store instructions; and a processor configured to execute the instructions and cause the processor to: receive, by a Virtual Routing and Forwarding (VRF) Router, a flow of traffic bound for a destination from a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router over an IPsec tunnel, wherein the destination of the flow of traffic is a cloud based service; determine, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; determine, by the VRF Router, a VRF segment in a SD-WAN fabric associated with the cloud based service; map, by the VRF Router, the VRF segment to the IP address of the LAN side; forward the flow of traffic originating from the LAN side of the router on the VRF segment associated with the cloud based service; and send the flow of traffic to the destination via the VRF Router.

(92) Aspect 9. The system of aspect 8, wherein the processor is configured to execute the instructions and cause the processor to: receive, by the VRF Router, the flow of traffic from the destination; determine, by the VRF Router, the IP address of the destination associated with the cloud based service and the mapping of the IP address of the LAN side to the VRF segment; and send the flow of traffic via the IPsec tunnel to the LAN side of the SD-WAN router.

- (93) Aspect 10. The system of aspect 8, wherein the IP address of the LAN side of the SD-WAN router includes a IP-Security Group Tag (IP-SGT) binding.
- (94) Aspect 11. The system of aspect 10, wherein the IPSec tunnel performs multiplexing, the wherein the processor is configured to execute the instructions and cause the processor to: map, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplex the VRF segments in the IPSec tunnel; segment, by the VRF Router, the one or more VRF segments based on the mapping; and send the traffic to the one or more cloud-based destinations by the one or more VRF segments.
- (95) Aspect 12. The system of aspect 10, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a global VRF-Common Flow Table.
- (96) Aspect 13. The system of aspect 12, wherein the global VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.
- (97) Aspect 14. The system of aspect 8, wherein the VRF Router is a Software-Defined Cloud Interconnect (SDCI) router.
- (98) Aspect 15. A method comprising: receiving, by a Virtual Routing and Forwarding (VRF) Router, a flow of traffic bound for a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router from a cloud-based service; determining, by the VRF Router, a VRF segment in a SD-WAN fabric associated with the cloud-based service; determining, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; mapping, by the VRF Router, the VRF segment to the IP address of the LAN side; forwarding the flow of traffic originating from the cloud-based service from the VRF segment associated with the cloud based service to an IPSec tunnel associated with the LAN side of the SD-WAN router; and sending the flow of traffic to the LAN side of the SD-WAN router via the IPSec tunnel.
- (99) Aspect 16. The method of aspect 1, further comprising: receiving, by the VRF Router, the flow of traffic from the LAN side of the SD-WAN router over the IPSec tunnel; determining, by the VRF Router, the VRF segment associated with the cloud based service based on the mapping of the IP address of the LAN side to the VRF segment; and sending, by the VRF Router, the flow of traffic to the cloud based service over the VRF segment.
- (100) Aspect 17. The method of aspect 15, wherein the IP address of the LAN side of the SD-WAN router includes an IP-Security Group Tag (IP-SGT) binding.
- (101) Aspect 18. The method of aspect 17, wherein the IPSec tunnel performs multiplexing, the method further comprising: mapping, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplexing the VRF segments in the IPSec tunnel; segmenting, by the VRF Router, the one or more VRF segments based on the mapping; and sending the traffic to the one or more cloud-based destinations by the one or more VRF segments.
- (102) Aspect 19. The method of aspect 17, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a VRF-Common Flow Table.
- (103) Aspect 20. The method of aspect 19, wherein the VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.

Claims

1. A method comprising: receiving, by a Virtual Routing and Forwarding (VRF) router, a flow of traffic bound for a destination from a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router over an IPSec tunnel, wherein the destination of the flow of traffic is a cloud based service; determining, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; determining, by the VRF Router, a VRF segment in a SD-WAN fabric

associated with the cloud based service; mapping, by the VRF Router, the VRF segment to the IP address of the LAN side; forwarding the flow of traffic originating from the LAN side of the router on the VRF segment associated with the cloud based service; and sending the flow of traffic to the destination via the VRF Router.

2. The method of claim 1, further comprising: receiving, by the VRF Router, the flow of traffic from the destination; determining, by the VRF Router, the IP address of the destination associated with the cloud based service and the mapping of the IP address of the LAN side to the VRF segment; and sending the flow of traffic via the IPsec tunnel to the LAN side of the SD-WAN router.

3. The method of claim 1, wherein the IP address of the LAN side of the SD-WAN router includes an IP-Security Group Tag (IP-SGT) binding.

4. The method of claim 3, wherein the IPsec tunnel performs multiplexing, the method further comprising: mapping, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplexing the VRF segments in the IPsec tunnel; segmenting, by the VRF Router, the one or more VRF segments based on the mapping; and sending the traffic to the one or more cloud-based destinations by the one or more VRF segments.

5. The method of claim 3, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a global VRF-Common Flow Table.

6. The method of claim 5, wherein the global VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.

7. The method of claim 1, wherein the VRF Router is a Software-Defined Cloud Interconnect (SDCI) router.

8. A system comprising: a storage configured to store instructions; and a processor configured to execute the instructions and cause the processor to: receive, by a Virtual Routing and Forwarding (VRF) Router, a flow of traffic bound for a destination from a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router over an IPsec tunnel, wherein the destination of the flow of traffic is a cloud based service; determine, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; determine, by the VRF Router, a VRF segment in a SD-WAN fabric associated with the cloud based service; map, by the VRF Router, the VRF segment to the IP address of the LAN side; forward the flow of traffic originating from the LAN side of the router on the VRF segment associated with the cloud based service; and send the flow of traffic to the destination via the VRF Router.

9. The system of claim 8, wherein the processor is configured to execute the instructions and cause the processor to: receive, by the VRF Router, the flow of traffic from the destination; determine, by the VRF Router, the IP address of the destination associated with the cloud based service and the mapping of the IP address of the LAN side to the VRF segment; and send the flow of traffic via the IPsec tunnel to the LAN side of the SD-WAN router.

10. The system of claim 8, wherein the IP address of the LAN side of the SD-WAN router includes an IP-Security Group Tag (IP-SGT) binding.

11. The system of claim 10, wherein the IPsec tunnel performs multiplexing, the wherein the processor is configured to execute the instructions and cause the processor to: map, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplex the VRF segments in the IPsec tunnel; segment, by the VRF Router, the one or more VRF segments based on the mapping; and send the traffic to the one or more cloud-based destinations by the one or more VRF segments.

12. The system of claim 10, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a global VRF-Common Flow Table.

13. The system of claim 12, wherein the global VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.

14. The system of claim 8, wherein the VRF Router is a Software-Defined Cloud Interconnect (SDCI) router.

15. A method comprising: receiving, by a Virtual Routing and Forwarding (VRF) Router, a flow of traffic bound for a Local Area Network (LAN) side of a Software-Defined Wide Area Network (SD-WAN) router from a cloud-based service; determining, by the VRF Router, a VRF segment in a SD-WAN fabric associated with the cloud-based service; determining, by the VRF Router, an IP address associated with the LAN side of the SD-WAN router; mapping, by the VRF Router, the VRF segment to the IP address of the LAN side; forwarding the flow of traffic originating from the cloud-based service from the VRF segment associated with the cloud based service to an IPsec tunnel associated with the LAN side of the SD-WAN router; and sending the flow of traffic to the LAN side of the SD-WAN router via the IPsec tunnel.

16. The method of claim 15, further comprising: receiving, by the VRF Router, the flow of traffic from the LAN side of the SD-WAN router over the IPsec tunnel; determining, by the VRF Router, the VRF segment associated with the cloud based service based on the mapping of the IP address of the LAN side to the VRF segment; and sending, by the VRF Router, the flow of traffic to the cloud based service over the VRF segment.

17. The method of claim 15, wherein the IP address of the LAN side of the SD-WAN router includes an IP-Security Group Tag (IP-SGT) binding.

18. The method of claim 17, wherein the IPsec tunnel performs multiplexing, the method further comprising: mapping, by the VRF Router, one or more IP-SGT bindings to one or more VRF segments associated with one or more cloud-based destinations; multiplexing the VRF segments in the IPsec tunnel; segmenting, by the VRF Router, the one or more VRF segments based on the mapping; and sending the traffic to the one or more cloud-based destinations by the one or more VRF segments.

19. The method of claim 17, wherein the mapping of the IP-SGT binding to the VRF segment is updated on a VRF-Common Flow Table.

20. The method of claim 19, wherein the VRF-Common Flow Table is stored within an Identity Service Engine associated with the VRF Router and the LAN side of the SD-WAN router.
