

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                        |
|----------------------|------------------------|
| United States Patent | 12413851               |
| Kind Code            | B2                     |
| Date of Patent       | September 09, 2025     |
| Inventor(s)          | Okuno; Yasuhiro et al. |

---

### Inspection device and inspection method

---

#### Abstract

An inspection device and an inspection method are provided. The inspection device includes: a main body portion, configured to be held by an inspector; a camera portion, disposed on the main body portion and configured to capture an inspected portion of a vehicle; and a guiding portion, configured to guide a camera direction of the camera portion to the inspector, so that an image obtained through the camera portion becomes a prescribed image suitable for inspection.

---

**Inventors:** Okuno; Yasuhiro (Tokyo, JP), Shinotsuka; Sukeyuki (Tokyo, JP), Matsuda; Shoji (Tokyo, JP), Torigai; Shunsuke (Tokyo, JP), Tanaka; Yosuke (Tokyo, JP), Kurei; Daiki (Tokyo, JP), Isobe; Koki (Tokyo, JP), Nakamoto; Kotaro (Tokyo, JP)

**Applicant:** Honda Motor Co., Ltd. (Tokyo, JP)

**Family ID:** 90243487

**Assignee:** Honda Motor Co., Ltd. (Tokyo, JP)

**Appl. No.:** 18/358950

**Filed:** July 26, 2023

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240098363 A1          | Mar. 21, 2024           |

#### Foreign Application Priority Data

|    |                |               |
|----|----------------|---------------|
| CN | 202211142349.X | Sep. 20, 2022 |
|----|----------------|---------------|

---

#### Publication Classification

**Int. Cl.:** H04N23/60 (20230101); H04N23/63 (20230101)

**U.S. Cl.:**

**CPC**            **H04N23/64** (20230101); **H04N23/633** (20230101);

## **Field of Classification Search**

**CPC:**            H04N (23/64); H04N (23/633)

---

## **References Cited**

### **U.S. PATENT DOCUMENTS**

| <b>Patent No.</b> | <b>Issued Date</b> | <b>Patentee Name</b> | <b>U.S. Cl.</b> | <b>CPC</b>  |
|-------------------|--------------------|----------------------|-----------------|-------------|
| 11290638          | 12/2021            | Duffy                | N/A             | H04N 23/634 |
| 2017/0018067      | 12/2016            | Rourke               | N/A             | G06T 7/0006 |
| 2019/0251747      | 12/2018            | Yin                  | N/A             | G06T 7/74   |
| 2019/0301845      | 12/2018            | Nickel               | N/A             | G01B 5/066  |

### **FOREIGN PATENT DOCUMENTS**

| <b>Patent No.</b> | <b>Application Date</b> | <b>Country</b> | <b>CPC</b> |
|-------------------|-------------------------|----------------|------------|
| 2000244583        | 12/1999                 | JP             | N/A        |

---

*Primary Examiner:* Perungavoor; Sath V

*Assistant Examiner:* Edwards; Tyler B

*Attorney, Agent or Firm:* JCIPRNET

---

## **Background/Summary**

### **CROSS-REFERENCE TO RELATED APPLICATION**

(1) This application claims the priority benefit of China application serial no. 202211142349.X, filed on Sep. 20, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

### **BACKGROUND**

Technical Field

(2) The disclosure relates to an inspection device and an inspection method.

Description of Related Art

(3) When the general inspection device inspects a vehicle, it is often difficult to conduct an accurate inspection by a visual manner. In recent years, research and development to obtain and support user data related to inspection is underway.

(4) Therefore, in the technologies for training or assistance related to human movements, how to perform a precise inspection on an inspection object is a topic.

(5) In order to solve the above issue, the disclosure aims to achieve precise inspection, thereby reducing the inspection time through guiding the direction of a camera.

### **SUMMARY**

(6) An embodiment of the disclosure provides an inspection device, which includes: a main body portion, configured to be held by an inspector; a camera portion, disposed on the main body portion and configured to capture an inspected portion of a vehicle; and a guiding portion, configured to

guide a camera direction of the camera portion to the inspector, so that an image obtained through the camera portion becomes a prescribed image suitable for inspection.

(7) Another embodiment of the disclosure provides an inspection method, which includes: capturing an inspected portion of a vehicle; guiding an image obtained through capturing, so that the image becomes a prescribed image suitable for inspection; and adjusting an inspection position, and inspecting the inspected portion when the inspection position is suitable for inspecting the inspected portion.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic structural diagram of an inspection device according to an embodiment of the disclosure.
- (2) FIG. 2 is a schematic circuit block diagram of an inspection device according to an embodiment of the disclosure.
- (3) FIG. 3 is a schematic diagram of an operation screen of an inspection device according to an embodiment of the disclosure.
- (4) FIG. 4A and FIG. 4B are schematic diagrams of an inspection process of an inspection device of the disclosure.
- (5) FIG. 4C is a variation example of a guide frame alignment manner.
- (6) FIG. 5 is a schematic diagram of an inspection process according to an embodiment of the disclosure.

### DESCRIPTION OF THE EMBODIMENTS

- (7) Based on the above description, an embodiment of the disclosure provides an inspection device, which includes: a main body portion, configured to be held by an inspector; a camera portion, disposed on the main body portion and configured to capture an inspected portion of a vehicle; and a guiding portion, configured to guide a camera direction of the camera portion to the inspector, so that an image obtained through the camera portion becomes a prescribed image suitable for inspection.
- (8) According to an embodiment of the disclosure, the inspection device further includes a display portion configured to display an image captured by the camera portion. The guiding portion displays a guide image in the image.
- (9) According to an embodiment of the disclosure, the inspection device further includes a position obtaining portion configured to obtain a spatial position of the main body portion.
- (10) Another embodiment of the disclosure provides an inspection method, which includes: capturing an inspected portion of a vehicle; guiding an image obtained through capturing, so that the image becomes a prescribed image suitable for inspection; and adjusting an inspection position, and inspecting the inspected portion when the inspection position is suitable for inspecting the inspected portion.
- (11) Reference will now be made in detail to the exemplary embodiments of the disclosure, examples of which are illustrated in the drawings. Wherever possible, the same reference numerals are used in the drawings and the description to refer to the same or similar parts.
- (12) FIG. 1 is a schematic structural diagram of an inspection device according to an embodiment of the disclosure. As shown in FIG. 1, according to an embodiment of the disclosure, an inspection device **100** includes a main body portion **150** that can be held by an inspector. The main body portion **150** may include an inspection portion **120** having a display portion **130**. The main body portion **150** may be designed with a holding portion **152** for the inspector to hold. In addition, an outer frame portion of the inspection portion **120** may be used as the holding portion held by the inspector. In this way, the inspector may conveniently inspect a vehicle, such as one or more

inspected portions in an engine room.

(13) The inspection device **100** may include a camera portion **110** and the display portion **130**. The camera portion **110** is, for example, disposed on the main body portion **150**, in other words, at the inspection portion **120**. The camera portion **110** can capture one or more inspected portions of the vehicle. The display portion **130** may display various operation interfaces, inspection interfaces, etc. for the inspector to operate, and the detailed operation will be described in detail below. The display portion **130** may, for example, be a liquid crystal display.

(14) In addition, according to an embodiment of the disclosure, the inspection portion **120** may be implemented using a smart terminal, and the smart terminal may, for example, be an apparatus with a camera function such as a smart phone or a tablet. In the description of the following embodiment, the smart phone will be used as an example of the inspection portion **120**, and the smart phone will be used for description if there is no confusion. When the smart phone is used as the inspection portion **120**, the camera and the screen of the smart phone itself may be respectively used as the camera portion **110** and the display portion **130**.

(15) Also, an inspection start key **160** may be disposed on the holding portion **152** of the inspection device **100**. In addition, an input interface of the inspection start key **160** may also be disposed on the touch screen of the smart phone, and the inspector may press the inspection start key **160** for the inspection device **100** to start inspecting each inspected portion of the vehicle. In addition, between the inspection start key **160** and the inspection portion **120**, the start and the end of the inspection device **100** may be controlled through a wired or wireless manner such as WiFi and Bluetooth.

(16) FIG. 2 is a schematic circuit block diagram of an inspection device according to an embodiment of the disclosure. As shown in FIG. 2, the inspection device **100** may further include a reporting portion **126** and a guiding portion **128**. The reporting portion **126** may report inspection information of the inspected portion judged based on an image obtained by the camera portion **110** to the inspector. The guiding portion **128** may guide the camera of the camera portion **110** to the inspector, so that the image obtained by the camera portion **110** becomes a prescribed image suitable for inspection. The reporting portion **126** and the guiding portion **128** may, for example, use sound or light to report to or guide the inspector.

(17) The inspection portion (the smart phone) **120** of the inspection device **100** may further include a control portion **124** and an inspection application **122**. The control portion **124** may control the above parts of the inspection portion (the smart phone) **120**. The inspection application **122** may be used to execute an inspection procedure.

(18) The inspection device **100** may further include a position obtaining portion **129** configured to obtain the spatial position of the main body portion. The position obtaining portion **129** may, for example, be an image sensor, a position sensor, an inertial sensor, a gyroscope, an accelerometer, a geomagnetic field, a global positioning system (GPS), etc., so as to estimate the position and the orientation of the inspection device **100**.

(19) Through the inspection device **100** of the embodiment of the disclosure, the inspected portion (an inspection object) is captured by the camera portion **110**. Once the inspected portion is detected in the captured image, the inspection device **100** may estimate the viewpoint position of the camera portion **110**. After that, the control portion **124** of the inspection device **100** may calculate the deviation from the inspection viewpoint position determined from the inspection object, and guide the inspector by correcting the deviation. For example, the correction manner is described in FIG. 4A later.

(20) In addition, when the inspection device **100** judges that the inspection viewpoint has reached a specified position (such as when a guide frame and a reference frame described later overlap), the inspection device **100** starts to inspect the inspected portion.

(21) FIG. 3 is a schematic diagram of an operation screen of an inspection device according to an embodiment of the disclosure. Herein, the schematic diagram of the operation flow of the

inspection device is described according to FIG. 3. As shown in FIG. 3, after starting the inspection application, a model selection button **130** and a start key **134** are displayed on the display portion **130** of the inspection device. In the example, the model selection button **130** exemplifies four types of models A to D, which may respectively represent 4 different types of vehicles. Of course, the available models are not particularly limited, and the display interface may be modified according to actual requirements. In addition, instead of the model selection button **130**, the camera portion **110** may read a barcode pattern disposed on the inspection object, so as to specify the model of the inspection object. Also, the barcode pattern in the example is a QR code as an example, but any usable barcode may be applied in the disclosure, and there is no particular limitation.

(22) Next, how to start the inspection procedure will be described based on FIG. 3. After starting the inspection application, the model selection button **130** and the start key **134** are displayed on the display portion **130** of the inspection device. The inspector, for example, selects one of the models such as the models A to D displayed on the model selection button **130**. According to an embodiment, the selection may be made through touching the touch screen of the display portion **130**. For example, the model A is selected. The model may represent a type of vehicle model. In addition, for example, the selection may automatically select the model of the inspection object through using the camera portion **110** to read a two-dimensional code (the barcode pattern) of the inspection object. In addition, the selection may also be automatically made in a factory by linking to an apparatus. For example, when the apparatus in the factory detects that the vehicle currently being inspected is the model A, the model A is automatically selected.

(23) Then, through pressing the start key **134** on the display portion **130**, the inspector may enter inspection items corresponding to the selected model to perform various inspections on, for example, the model A. After that, the inspector may press the inspection start key **160** of the inspection device **100** to start inspecting the inspected portion of the vehicle.

(24) FIG. 4A and FIG. 4B are schematic diagrams of an inspection process of an inspection device of the disclosure. Firstly, as shown in FIG. 4A, according to the operation described above, in the case where the inspector selects the model A, and presses the start key **134** and the inspection start key on the main body portion **150**, the display portion **130** enters an inspection screen. The inspection screen includes an image area **140** of the inspection object, such as the engine room of the vehicle. Also, as shown in FIG. 4A, the right side of the inspection screen includes an inspection status area **144**. The lower side of the inspection screen includes an inspection viewpoint area **142**, which may present multiple inspected portions {circle around (1)} to {circle around (10)}.

(25) A reference frame **200** and a guide frame **202** as a position guide are displayed in the image area **140** of the inspection object. The reference frame **200** basically does not move with respect to the display portion **130** and represents a central portion captured by the camera portion **110**. Also, the guide frame **202** represents a frame as the inspection viewpoint from which the image suitable for inspection (the prescribed image) may be obtained and is displayed on the display portion **130**. The guide frame **202** moves along with the rotation and the movement of the inspection device **100**. In this way, the inspector may move the inspection device **100** to align the guide frame **202** with the reference frame **200**, so as to inspect the inspected portion after positioning the inspection device **100**.

(26) Regarding the inspection viewpoint area **142**, 10 inspected portions are displayed in the example, and the inspection viewpoint area **142** presents the inspected portions {circle around (1)} to {circle around (10)}. The inspection viewpoint area **142** may be used as a presentation manner of the inspection progress. For example, each of the inspected portions {circle around (1)} to {circle around (10)} may display different colors, so that the inspector may recognize whether each of the inspected portions {circle around (1)} to {circle around (10)} has been inspected. For example, yellow represents that the inspection device **100** is being positioned, orange represents that the inspection is in progress, green represents that the inspection is completed, gray represents

that the inspection viewpoint is skipped, etc. In this way, in FIG. 4A, the inspected portion {circle around (1)} displays green, which represents that the inspected portion {circle around (1)} has been inspected. The inspected portion {circle around (2)} displays gray, which represents that the inspected portion {circle around (2)} is skipped and not inspected. The inspected portion {circle around (3)} is yellow, which represents that the inspection device **100** is being positioned for the inspected portion a. After that, after the guide frame **202** overlaps with the reference frame **200**, the image suitable for inspection (the prescribed image) is obtained. The inspected portion {circle around (3)} displays orange, which represents that the inspected portion {circle around (3)} is being inspected (under inspection).

(27) In the case where the inspection of the inspected portion {circle around (3)} is completed, the display of the inspected portion {circle around (3)} changes to green. Afterwards, in the case where the inspection of the next inspected portion is performed, a new guide frame from which the image suitable for inspection (the prescribed image) of the next inspected portion (for example, the inspected portion {circle around (4)}) may be obtained is displayed on the display portion **130**. In addition, in the case where there is no position in the image area **140** from which the image suitable for the inspection (the prescribed image) of the inspected portion {circle around (4)} may be obtained, for example, an arrow is displayed to change the image area, so as to prompt the inspector to change the camera position and the camera direction.

(28) In this way, when all the inspected portions {circle around (1)} to {circle around (10)} in the inspection viewpoint area **142** display green (or a part displays gray, that is, a part of the inspected portions is skipped), it represents that all the inspected portions {circle around (1)} to {circle around (10)} have been inspected. In this way, the inspector may clearly know the current inspection progress from the inspection viewpoint area **142**. In addition, the various color indications mentioned above are only examples, and the colors used in various statuses are not particularly limited. In addition, as long as the various statuses of the inspected portions may be distinguished, an indication manner other than colors may also be used, and the disclosure does not particularly limit the indication manner.

(29) The inspection screen displayed on the display portion **130** of the inspection device **100** may include the inspection status area **144**. The example of FIG. 4A is an inspected portion status area **144a**, a progress status area **114b**, a data transmission status area **144c**, etc.

(30) In the case where the positioning of the guide frame of the inspected portion {circle around (3)} is currently being performed, the inspected portion status area **144a** displays {circle around (3)} and yellow, which represents that the guide frame **202** of the inspection viewpoint of the inspected portion {circle around (3)} is being positioned. As mentioned above, the inspected portion status area **144a** also uses various colors to represent the various statuses of the inspected portion a. For example, yellow represents that the guide frame **202** is being positioned for the inspected portion ED, orange represents that the inspection in progress (under inspection), and green represents that the inspected portion has been inspected.

(31) The progress status area **114b** may present “next”. When the inspected portion has not been inspected, the “next” in the progress status area **114b** may present a specific color (for example, white) or other indication manners to inform the inspector that the next inspected portion will not be processed currently. In addition, when the inspected portion has been inspected, the “next” in the progress status area **114b** may change the color or the indication manner, or become a status available for the inspector to press to inform the inspector that the processing of the next inspected portion is currently being prepared. Accordingly, the inspector may clearly grasp the inspection progress of the inspected portion. In addition, when preparing for the processing of the next inspected portion, the new guide frame of the next inspected portion may be displayed.

(32) The data transmission status area **144c** is used to display a data transmission status of an inspection result of the inspected portion. As shown in FIG. 4B, still taking the inspected portion {circle around (3)} as an example, after the guide frame **202** is aligned with the reference frame

**200** or the guide frame **202** becomes the reference frame **200**, the guide frame **202** may change color to become an inspection frame **204** to automatically obtain the image suitable for inspection (the prescribed image). At this time, it represents that the inspection device **100** has been aligned with the inspected portion {circle around (3)}, and starts to enter an inspection status. It should be noted that the display image in the aligned status may be a momentary status and may not be identified.

(33) Since the inspected portion {circle around (3)} is in the inspection status at this time, the inspected portion status area **144a** displays {circle around (3)} and orange, and the “next” in the progress status area **114b** presents white or other indication manners. In addition, when inspecting the inspected portion {circle around (3)}, the inspection device **100** may transmit the inspection result of the previous inspected portion, for example, to other apparatuses, etc. At this time, the data transmission status area **144c** may, for example, display {circle around (1)}, which represents that the inspection result of the inspected portion {circle around (1)} is being transmitted. Also, in order for the inspector to recognize that data is being transmitted, a specific color or manner may be used to prompt the inspector.

(34) Also, after the inspection of the inspected portion {circle around (3)} is completed, the inspected portion status area **144a** may display green, so that the inspector may immediately know that the inspected portion {circle around (3)} has been inspected. At the same time, the “next” in the progress status area **114b** may present another color or indication manner other than white to let the inspector know that the inspection device **100** is about to inspect the next inspected portion. Also, the data transmission status area **144c** may, for example, display {circle around (3)}, which represents that the data of the inspection result of the inspected portion {circle around (3)} is being transmitted. Referring to FIG. 4A, since the inspected portion {circle around (2)} is skipped in the exemplary example, after the data of the inspection result of the inspected portion {circle around (1)} is transmitted, the data transmission status area **144c** continues to display the transmission of the data of the inspection result of the inspected portion {circle around (3)}.

(35) FIG. 4C is a variation example of a guide frame alignment manner. The image area **140** of the inspection screen may further include a leveler **210**. When the inspection position cannot be positioned using only the guide frame **202**, according to the embodiment of the disclosure, the leveler **210** may be further added on the inspection screen of the display portion **130** of the inspection device **100** to position the inspection position.

(36) FIG. 5 is a schematic diagram of an inspection process according to an embodiment of the disclosure, especially a schematic diagram of a guide frame positioning process related to the inspection viewpoint (the inspected portion). As shown in FIG. 5, there are three manners related to the positioning of the inspection viewpoint for selection, such as Steps **S12** to **S14**, Steps **S22** to **S24**, and Steps **S32** to **S38**. Further description will be given below with reference to FIG. 5.

(37) Firstly, in Step **S100**, an inspection procedure is entered and ends in Step **S116**. The inspection procedure is continuously performed in a cyclic manner until all inspected portions are inspected. Also, if an exit condition is set, the inspection procedure may also be exited if the condition is met.

(38) Next, Step **S102** is entered, and inspection position positioning is executed (start). In the entire inspection procedure **S100** to **S116**, the inspection position positioning is continuously performed until the inspection position positioning of Step **S112** (end). That is, the camera portion of the inspection device **100** is used to capture each inspected portion, while rotating or moving the main body portion **150** of the inspection device **100**, so that the guide frame **202** is aligned and overlaps with the reference frame **200** on the display portion **130**. The inspection position positioning of Step **S102** (start) to the inspection position positioning of Step **S102** (end) is continuously performed in a cyclic manner. As mentioned above, the inspection position positioning continues until the guide frame **202** on the display portion **130** overlaps with the reference frame before ending.

(39) Next, after the inspection position positioning is executed in Step **S112**, Step **S114** is entered,

at this time, the camera portion of the inspection device **100** obtains an image of the inspected portion. In other words, after the inspection position positioning in Step **S112** is completed (as shown by the inspection frame **204** of FIG. **4B**), the inspection device **100** automatically obtains the image of the inspected portion. Next, the obtained image is inspected in Step **S116**. Return to Step **S100**, the inspection procedure of the next inspected portion starts. At this time, the display portion **130** displays the guide frame suitable for the inspection viewpoint of the next inspected portion. Also, in Step **S104**, one of Steps **S12** to **S14**, Steps **S22** to **S24**, and Steps **S32** to **S38** may be selected to perform the inspection position positioning. The following will explain one by one.

(40) Firstly, the inspection position positioning manner of Steps **S12** to **S14** will be described. In Step **S12**, the inspected portion (the inspection object) is identified through an image. For example, as described above, the inspection device **100** of FIG. **1** captures the engine room of a certain type of vehicle (model), and then identifies the inspected portion.

(41) Next, in Step **S14**, the deviation from a viewpoint suitable for inspection is calculated through the identification result of the inspected portion (the inspection object). For example, the viewpoint may be estimated through identifying the inspected portion (the inspection object) and using the position in the image. There are several cases regarding specifying the range of each inspection viewpoint. For example, there are viewpoints that need to be precisely positioned otherwise cannot be inspected. Also, there are viewpoints that may be inspected within a specific range. Therefore, the inspector may adjust an appropriate inspection viewpoint according to requirements.

(42) Next, in Step **S108**, the degree of deviation is displayed on the display portion. Here, as shown in FIG. **4A**, the guide frame **202** and the reference frame **200** are displayed on the display portion **130** of the inspection device **100**, and there is deviation between the two. In Step **S110**, it is judged whether the position is suitable for inspection. For example, the inspector may repeatedly adjust the position of the inspection device **100**, so that the guide frame **202** and the reference frame **200** overlap to reach a suitable position for inspection. After that, the inspection position positioning is completed in Step **S112**.

(43) Next, the inspection position positioning manner of Steps **S22** to **S24** will be described. In Step **S22**, multiple components of an image are identified. For example, as described above, the inspection device **100** of FIG. **1** captures the engine room of a certain type of vehicle (model), and then identifies multiple components in the inspected portion.

(44) In Step **S24**, the deviation from a viewpoint suitable for inspection is calculated from the positional relationship of the components. In the manner, an appropriate viewpoint is estimated through the configuration position of the components. Likewise, there are several cases regarding specifying the range of each inspection viewpoint. For example, there are viewpoints that need to be precisely positioned otherwise cannot be inspected. Also, there are viewpoints that may be inspected within a specific range. Therefore, the inspector may adjust an appropriate inspection viewpoint according to requirements.

(45) Next, in Step **S108**, the degree of deviation is displayed on the display portion. Here, as shown in FIG. **4A**, the guide frame **202** and the reference frame **200** are displayed on the display portion **130** of the inspection device **100**, and there is deviation between the two. In Step **S110**, it is judged whether the position is suitable for inspection. For example, the inspector may repeatedly adjust the position of the inspection device **100**, so that the guide frame **202** and the reference frame **200** overlap to reach a suitable position for inspection. After that, the inspection position positioning is completed in Step **S112**.

(46) Next, the inspection position positioning manner of Steps **S32** to **S38** will be described.

(47) In Step **S32**, the inspection device **100** obtains sensing signals of an image sensor, a gyroscope, an accelerometer, a geomagnetic field, a GPS, etc. In Step **S34**, the position and the orientation of the inspection device **100** are estimated through the sensing signals obtained in Step **S32**.

(48) In Step **S36**, a filming area is specified through the estimated position and orientation of the



inspection device **100** in Step **S34**. In Step **S38**, the deviation from a viewpoint suitable for inspection is calculated with reference to position data of components. In this way, the inspection device **100** may estimate the position of the inspection device **100** using an image sensor, a position sensor, an inertial sensor, a gyroscope, an accelerometer, a geomagnetic field, a GPS, etc.

(49) Next, in Step **S108**, the degree of deviation is displayed on the display portion. Here, as shown in FIG. **4A**, the guide frame **202** and the reference frame **200** are displayed on the display portion **130** of the inspection device **100**, and there is deviation between the two. In Step **S110**, it is judged whether the position is suitable for inspection. For example, the inspector may repeatedly adjust the position of the inspection device **100**, so that the guide frame **202** and the reference frame **200** overlap to reach a suitable position for inspection. After that, the inspection position positioning is completed in Step **S112**.

(50) As mentioned above, the inspector may select a suitable processing manner for the object in Step **S104**. For example, one of Steps **S12** to **S14**, Steps **S22** to **S24**, and Steps **S32** to **S38** may be selected for the inspection position positioning. Finally, in Step **S106**, the result of the selected processing manner is output to display the degree of deviation (such as the deviation between the guide frame **202** and the reference frame **200**, see FIG. **4A**) on the display portion **130** of the inspection device **100**.

(51) Also, in the above description, between Steps **S104** and **S106**, three different processing manners are provided for the inspector to select, but it is also possible to provide only two of the three or only one of the three, which may be designed depending on requirements.

(52) Finally, it should be noted that the above embodiments are only used to illustrate, but not to limit, the technical solutions of the disclosure. Although the disclosure has been described in detail with reference to the above embodiments, persons skilled in the art should understand that the technical solutions described in the above embodiments may still be modified or some or all of the technical features thereof may be equivalently replaced. However, the modifications or replacements do not cause the essence of the corresponding technical solutions to deviate from the scope of the technical solutions of the embodiments of the disclosure.

## Claims

1. An inspection device, comprising: a main body portion, held by an inspector; a camera, disposed on the main body portion and configured to capture a first portion of a vehicle to be inspected; a display, configured to display an image captured by the camera; and a processor, configured to: determine whether the captured image satisfies a requirement for inspecting the first portion of the vehicle such that a degree of deviation between the first portion and a predetermined position in the captured image is less than a threshold value; and in response to the captured image does not satisfy the requirement for inspecting the first portion, display a reference frame on the display that displays the captured image, wherein the reference frame is at a fixed position with respect to the display, display a guide frame over the captured image on the display, wherein the guide frame is a frame that surrounds the first portion of the vehicle to be inspected and moves with movement of the inspection device, and guide the inspector to change a position and a direction of the camera to capture another image of the first portion of the vehicle until the reference frame overlaps with the guide frame on the display.
2. The inspection device according to claim 1, further comprising: a position sensor configured to obtain a spatial position of the main body portion.
3. An inspection method, comprising: capturing a first portion of a vehicle to be inspected through a camera; displaying an image captured by the camera; determining whether the captured image satisfies a requirement for inspecting the first portion of the vehicle such that a degree of deviation between the first portion and a predetermined position in the captured image is less than a threshold value; and in response to the captured image does not satisfy the requirement for inspecting the first

portion, displaying a reference frame on the display that displays the captured image, wherein the reference frame is at a fixed position with respect to the display, displaying a guide frame over the captured image on the display, wherein the guide frame is a frame that surrounds the first portion of the vehicle to be inspected and moves with movement of the inspection device, and guiding the inspector to change a position and a direction for capturing another image of the first portion of the vehicle of the camera until the reference frame overlaps with the guide frame on the display.

4. The inspection device according to claim 3, wherein the reference frame is at a central portion with respect to the display.

---