

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402674
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Genender; Alan et al.

Gown with concentric sleeves and corresponding methods

Abstract

A gown (**100**) includes a body covering portion (**101**). A first sleeve (**107**) and a second sleeve (**108**) each extend distally away from the body covering portion and terminating at a retention device (**109,110**). A first concentric sleeve (**119**) is coupled to the first sleeve at a first connection location (**121**) and extends along an exterior of the first sleeve toward the retention device. A second concentric sleeve (**120**) is coupled to the second sleeve at a second connection location (**122**) and extends along the exterior of the second sleeve toward the retention device.

Inventors:	Genender; Alan (Northbrook, IL), Putnam; Audrey (Chicago, IL)
Applicant:	Medline Industries, LP (Mundelein, IL)
Family ID:	61756875
Assignee:	Medline Industries LP (Northfield, IL)
Appl. No.:	15/285145
Filed:	October 04, 2016

Prior Publication Data

Document Identifier	Publication Date
US 20180092412 A1	Apr. 05, 2018

Publication Classification

Int. Cl.: A41D13/12 (20060101); A41D27/10 (20060101)

U.S. Cl.:

CPC A41D13/1227 (20130101); A41D27/10 (20130101); A41D13/1209 (20130101)

Field of Classification Search

CPC: A41D (13/1227); A41D (13/1209)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2668294	12/1953	Gilpin	2/114	A41D 13/1209
3868728	12/1974	Krzewinski	2/114	A41D 13/1227
D279040	12/1984	Horox	N/A	N/A
4535481	12/1984	Ruth-Larson	2/114	A41D 13/1209
4937883	12/1989	Shirai	2/113	A41D 1/04
D325459	12/1991	Keever	N/A	N/A
5142704	12/1991	Viemeister	2/171	A41D 13/1218
D351712	12/1993	Jackson	N/A	N/A
5444871	12/1994	Lopez	2/114	A41D 13/1227
D374113	12/1995	Console	N/A	N/A
6115839	12/1999	Covington et al.	N/A	N/A
D469945	12/2002	Mayer	N/A	N/A
D622934	12/2009	Graneto, III	N/A	N/A
D624280	12/2009	Halseth	N/A	N/A
D646463	12/2010	Petrovskis et al.	N/A	N/A
D681915	12/2012	Walrich et al.	N/A	N/A
D687209	12/2012	Levine	N/A	N/A
D721870	12/2014	Levine	N/A	N/A
D736493	12/2014	Pasko	N/A	N/A
D741044	12/2014	Pasko	N/A	N/A
D749819	12/2015	Czajka et al.	N/A	N/A
D764748	12/2015	Czajka et al.	N/A	N/A
2006/0041988	12/2005	Bushman	2/59	A41D 13/1227
2011/0239349	12/2010	Thompson	2/48	A41D 13/1209
2013/0036526	12/2012	Rashman	N/A	N/A
2013/0191960	12/2012	Pasko	N/A	N/A
2013/0305426	12/2012	Walrich	2/243.1	A41D 27/10
2014/0007316	12/2013	Tommarello et al.	N/A	N/A
2015/0135397	12/2014	Levine	N/A	N/A
2016/0000150	12/2015	Gucciardi	2/69	A41D 13/0015

OTHER PUBLICATIONS

“Polyethylene Thumb Loop Style Isolation Gowns”, Medline Catalog; Unkown Publication date but believed to be prior to filing of present application;

<https://www.medline.com/catalog/catalog.jsp>. cited by applicant

Moore Jr, Clese , “Notice of Allowance”, U.S. Appl. No. 29/579,902, filed Oct. 4, 2016; Mailed Jan. 31, 2018. cited by applicant

Moore Jr, Clese , “Notice of Allowance”, U.S. Appl. No. 29/586,255, filed Dec. 1, 2016; Mailed Jan. 12, 2018. cited by applicant

Moore Jr, Clese , “Restriction Requirement”, U.S. Appl. No. 29/586,255, filed Dec. 1, 2016;

Primary Examiner: Tompkins; Alissa J

Background/Summary

BACKGROUND

Technical Field

(1) This disclosure relates generally to gowns, and more particularly to gowns with sleeves.

Background Art

(2) Medical professionals frequently interact with various fluids, waste matter, and pathogens when rendering medical services. For example, when working in a decontamination area with medical instruments such as endoscopes, medical personnel may be exposed to high volumes of fluid. It is important to keep such fluids away from the skin, as such contact can result in the medical professional becoming infected or ill due to the microorganisms or pathogens present in the fluids.

(3) One common technique to try and prevent fluids from contacting the skin is by donning a gown. However, prior art gowns can actually increase the chance of fluids contacting the skin by way of their construction. Some gowns can bend and fold in ways that actually "channel" fluid down the arms of a gown to a glove, thereby increasing the risk that the medical professional's hands will contact the fluid. Such pathways put the medical services provider at risk of becoming ill. It would be advantageous to have a gown that overcomes some of the issues associated with prior art medical gowns.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a front elevation view of one explanatory gown in accordance with one or more embodiments of the disclosure.

(2) FIG. 2 illustrates a rear elevation view of one explanatory gown in accordance with one or more embodiments of the disclosure.

(3) FIG. 3 illustrates a first step of a method of using a gown in accordance with one or more embodiments of the disclosure.

(4) FIG. 4 illustrates a second step of a method of using a gown in accordance with one or more embodiments of the disclosure.

(5) FIG. 5 illustrates a third step of a method of using a gown in accordance with one or more embodiments of the disclosure.

(6) FIG. 6 illustrates a fourth step of a method of using a gown in accordance with one or more embodiments of the disclosure.

(7) FIG. 7 illustrates a fifth step of a method of using a gown in accordance with one or more embodiments of the disclosure.

(8) FIG. 8 illustrates a user wearing one explanatory gown in accordance with one or more embodiments of the disclosure.

(9) FIG. 9 illustrates a front elevation view of an alternate gown in accordance with one or more embodiments of the disclosure.

(10) FIG. 10 illustrates a rear elevation view of an alternate gown in accordance with one or more

embodiments of the disclosure.

(11) FIG. 11 illustrates a front elevation view of yet another gown in accordance with one or more embodiments of the disclosure.

(12) FIG. 12 illustrates a rear elevation view of yet another gown in accordance with one or more embodiments of the disclosure.

(13) FIG. 13 illustrates an alternate sleeve in accordance with one or more embodiments of the disclosure.

(14) FIG. 14 illustrates one explanatory method of manufacturing a gown in accordance with one or more embodiments of the disclosure.

(15) Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE DRAWINGS

(16) Embodiments of the disclosure are now described in detail. Referring to the drawings, like numbers indicate like parts throughout the views. As used in the description herein and throughout the claims, the following terms take the meanings explicitly associated herein, unless the context clearly dictates otherwise: the meaning of “a,” “an,” and “the” includes plural reference, the meaning of “in” includes “in” and “on.” Relational terms such as first and second, top and bottom, and the like may be used solely to distinguish one entity or action from another entity or action without necessarily requiring or implying any actual such relationship or order between such entities or actions. Also, reference designators shown herein in parenthesis indicate components shown in a figure other than the one in discussion. For example, talking about a device (10) while discussing figure A would refer to an element, 10, shown in figure other than figure A.

(17) Embodiments of the disclosure provide a gown having dual sleeves, i.e., a first sleeve with a second, concentric sleeve coupled to and disposed about the exterior of the first sleeve. In one embodiment, the first sleeve has a retention device, such as a thumb loop or knitted cuff, that retains the first sleeve to the arm of a wearer. A second, outer concentric sleeve is attached to the first sleeve at a connection location. The outer concentric sleeve extends along the exterior of the first sleeve toward the retention device and terminates at a termination boundary, which defines the end of the outer concentric sleeve. In one or more embodiments, the outer concentric sleeve does not extend all the way to the end of the first sleeve. Instead, when extended the first termination boundary is disposed between the retention device and the first connection location.

(18) When donning the gown, a user places their arm into the first sleeve and secures the first sleeve along their arm with the retention device. For example, if the retention device is a thumb loop, the user places their thumb into the thumb loop to keep the first sleeve from sliding up their arm when donning gloves or other objects. Where the retention device is a knitted cuff, the knitted cuff frictionally retains the first sleeve to the arm. Other types of retention devices will be obvious to those of ordinary skill in the art having the benefit of this disclosure.

(19) The user then translates the outer concentric sleeve up their arms toward their elbow, thereby exposing more of the first sleeve. A user can then don gloves. In one or more embodiments, the gloves pass about the exterior of at least a portion of the first sleeve. Once the gloves are donned, the user can then slide the outer concentric sleeve about an exterior of a portion of the glove to define an outer envelope that covers the opening of the glove. In one or more embodiments, the outer concentric sleeve includes an elastic gathering that draws the outer concentric sleeve toward the arm of the user. Accordingly, the first sleeve is covered by a portion of the glove and the outer concentric sleeve is disposed over the glove to prevent the channeling of fluids that is so problematic in prior art designs. Where extra fluid barriers are required, a second glove can be donned atop the first, as well as atop the outer concentric sleeve, to provide additional protection.

(20) Turning now to FIGS. 1 and 2, illustrated therein is one example of a gown 100 configured in

accordance with one or more embodiments of the invention. A body covering portion **101** is configured to wrap about the torso of a wearer. In one embodiment, the body covering portion **101** is impermeable to fluids. For example, in one embodiment the body covering portion **101** is manufactured from polyethylene. In another embodiment, the body covering portion **101** is manufactured from polypropylene. In yet another embodiment, the body covering portion **101** is manufactured from a non-woven fabric that is coated with polyethylene, polypropylene, or another fluid resistant coating. In still another embodiment, the body covering portion **101** is manufactured from Tyvek.sup.™ Other fluid impermeable materials suitable for use as the body covering portion **101** will be obvious to those of ordinary skill in the art having the benefit of this disclosure. For example, a woven material that includes a water resistant lining that prevents the passage of fluids through the body covering portion **101** can also be used. One or more antimicrobial layers can be added to the body covering portion **101** to further enhance antimicrobial protection.

(21) In still other embodiments, the gown **100** can be configured as a reusable gown. For example, the material from which the gown **100** is manufactured could be washable and/or capable of being sterilized so that the gown can be reused. Illustrating by example, in one embodiment, the gown **100** is manufactured from a washable fabric, such as cotton, polyester, or a cotton polyester blend. In another embodiment, the gown **100** is manufactured from non-woven fabric so as to be disposable.

(22) The length **102** of the body covering portion **101** can vary. In one embodiment, the length **102** of the body covering portion is configured to run from a wearer's shoulder to below their knee. In other embodiments, the length **102** of the body covering portion **101** is configured to run from the wearer's shoulder to a location along their mid-calf. In yet another embodiment, the length **102** of the body covering portion **101** extends from a wearer's shoulder to their feet. Other lengths will be obvious to those of ordinary skill in the art having the benefit of this disclosure.

(23) In one embodiment, the gown **100** may optionally include pockets or other surface features. In other embodiments, these features will be omitted to prevent pooling of liquids. The gown **100** may be manufactured in various colors. However, in one or more embodiments, the gown **100** is blue. However, in other embodiments the gown **100** is yellow. Other colors will be obvious to those of ordinary skill in the art having the benefit of this disclosure.

(24) The body covering portion **101** includes a front portion **103** and a rear portion **203**. The front portion **103** is configured as a frontal body covering portion in that it is configured to cover the frontal portion of some or all of a user's body, or in another embodiment the frontal portion of some or all of a user's torso, when the user is wearing the gown. The body covering portion **101** further includes a rear portion **203** that is configured to cover at least a portion of a wearer's backside. In the illustrative example of FIGS. **1** and **2**, the front portion **103** is longer than the rear portion **203**, thereby covering more of the wearer's body in the front than the rear. However, as will be described below with reference to FIGS. **11-12**, the rear portion **203** can have a substantially similar length with the front portion **103**. In another embodiment, the front portion **103** will be shorter than the rear portion **203**, thereby covering less of the wearer's body in the front than in the rear. This will vary based upon application.

(25) In one embodiment, the body covering portion **101** defines a head insertion aperture **104** through which a user may insert their head when donning the gown. In the illustrative embodiment of FIGS. **1** and **2**, the head insertion aperture **104** is disposed between the front portion **103** and the rear portion **203**, and is surrounded by shoulder portions **105,106** of the body covering portion **101**. The perimeter of the head insertion aperture **104** can take a variety of shapes. For example, in the illustrative embodiment of FIGS. **1** and **2**, the head insertion aperture **104** has an inverted curved contour. Other embodiments described below may include different head insertion aperture contours.

(26) In one embodiment, the body covering portion **101** defines an opening **201**. The front portion **103** of the gown **100** is configured, in one embodiment, to be placed against the front of the torso

of a wearer. The body covering portion **101** then wraps around and terminates at the opening **201**. The opening **201** in this embodiment has a left side **204** and a right side **205**, each of which extends upward to the rear portion **203**, which sits atop a wearer's shoulders.

(27) The opening can be used to assist in donning the gown. For instance, a user may open the opening **201** and pass their head, shoulders, and/or torso portions through the opening **201** when donning the gown. Said differently, the right side **205** and left side **204** of the opening **201** can be configured to permit the wearer to don the gown **100** by wrapping the right side **205** and left side **204** about the wearer's torso.

(28) The bottom of the gown **100** can take a variety of shapes. For example, in the illustrative embodiment of FIGS. **1** and **2**, the front base member **115** of the gown **100** is curved. Other embodiments described below may include different front contours. In this illustrative embodiment, the base member **115** takes a concave down contour, with an arched contour **116** spanning between two convex lobes **117,118**.

(29) In one embodiment, a first sleeve **107** and a second sleeve **108** extend distally from the body covering portion **101**. The first sleeve **107** and the second sleeve **108** are configured to receive wearer's arms when the medical gown **100** is donned. In one embodiment, each of the first sleeve **107** and the second sleeve **108** are configured as single, unitary pieces of liquid impervious material such as polyethylene or polypropylene. The first sleeve **107** and the second sleeve **108** can be contiguous with the body covering portion **101** in one embodiment. Alternatively, they can be attached to the body covering portion at seams (not shown). The seams can be sewn, although other attachment processes can be used as well. Examples of alternative attachment processes include adhesive bonding, mechanical or press-fit bonding, thermal bonding, sonic welding, taping, and so forth. In the illustrated embodiment of FIGS. **1** and **2**, the first sleeve **107** and second sleeve **108** are illustrated as long sleeves that cover substantially the entirety of a wearer's arms.

(30) In one or more embodiments, the sleeves **107,108** each terminate at a retention device **109,110** configured to retain the first sleeve **107** and the second sleeve **108** to the arms of a wearer. In this illustrative embodiment, each retention device **109,110** comprises a thumb loop **111,112**. However, the retention devices **109,110** can take other forms as well. Illustrating by example, as will be described below with reference to FIG. **12** below, in other embodiments the retention devices **109,110** can comprise knitted cuffs. In still other embodiments, the retention devices **109,110** can comprise drawstrings. In yet additional embodiments, the retention devices **109,110** can comprise elastic gatherings. Other retention devices **109,110** will be obvious to those of ordinary skill in the art having the benefit of this disclosure.

(31) In this illustrative embodiment, each retention device **109,110** comprises a thumb loop **111,112**. In one embodiment, the thumb loop comprises a thumb insertion aperture **113,114**, through which a wearer's thumb may be inserted to retain the first sleeve **107** and the second sleeve **108** along the wearer's arm.

(32) The thumb loops **111,112**, where included, provide several functions. One illustrative function is that they keep the sleeves **107,108** pulled along the wearer's arms and prevent the sleeves **107,108** from "riding up." Another illustrative function is that the thumb loops **111,112** prevent twisting of the sleeves **107,108** about the wearer's arm. Each thumb loop **111,112** is configured, in one embodiment, to engage the saddle of a thumb of the wearer.

(33) In one or more embodiments, a first concentric sleeve **119** and a second concentric sleeve **120** are coupled to the first sleeve **107** and the second sleeve **108**, respectively. In this illustrative embodiment, the first concentric sleeve **119** is coupled to the first sleeve **107** at a first connection location **121**, while the second concentric sleeve **120** is coupled to the second sleeve **108** at a second connection location **122**. The first connection location **121** and the second connection location **122**, in one embodiment, are disposed above the elbow of the first sleeve **107** and the second sleeve **108**, respectively. In another embodiment, the first connection location **121** and the second connection location **122** are disposed at the shoulder of the first sleeve **107** and the second

sleeve **108**, respectively. In other embodiments, the first connection location **121** and the second connection location **122** can be disposed at any location between the wrist area and the shoulder. Other locations for the first connection location **121** and the second connection location **122** will be obvious to those of ordinary skill in the art having the benefit of this disclosure.

(34) In one embodiment, the first concentric sleeve **119** and the second concentric sleeve **120** are coupled to the first sleeve **107** and the second sleeve **108** by thermal bonding. However, other coupling techniques can be used as well. Illustrating by example, in another embodiment the first concentric sleeve **119** and the second concentric sleeve **120** are coupled to the first sleeve **107** and the second sleeve **108** by adhesive bonding. In other embodiments, the first concentric sleeve **119** and the second concentric sleeve **120** are coupled to the first sleeve **107** and the second sleeve **108** by tape. Sonic welding, mechanical bonding, press-fit bonding, or other techniques can be used as well.

(35) In one embodiment, the first concentric sleeve **119** and the second concentric sleeve **120** are manufactured from the same material as the first sleeve **107** and the second sleeve **108**. For instance, if the gown **100** and the first sleeve **107** and second sleeve **108** are manufactured from polyethylene, in one embodiment the first concentric sleeve **119** and the second concentric sleeve **120** are manufactured polyethylene as well. In another embodiment, the first concentric sleeve **119** and the second concentric sleeve **120** are manufactured from a different material than that from which the first sleeve **107** and the second sleeve **108** are manufactured. For example, in one embodiment where the first sleeve **107** and the second sleeve **108** are manufactured from polypropylene, the first concentric sleeve **119** and the second concentric sleeve **120** may be manufactured from polyethylene, and so forth.

(36) In this illustrative embodiment, the first concentric sleeve **119** and the second concentric sleeve **120** extend along an exterior of the first sleeve **107** and second sleeve **108**, respectively, toward the retention devices **109,110**, which in this embodiment are thumb loops **111,112**. The first concentric sleeve **119** and the second concentric sleeve **120** extend along an exterior of the first sleeve **107** and second sleeve **108** to a first termination boundary **123** and a second termination boundary **124**, respectively.

(37) In this illustrative embodiment the first concentric sleeve **119** and the second concentric sleeve **120** do not extend along the exterior of the first sleeve **107** and second sleeve **108** all the way to the ends of the latter. To the contrary, in this illustrative embodiment the first concentric sleeve **119** and the second concentric sleeve **120** are configured to extend along an exterior of the first sleeve **107** and second sleeve **108** to the first termination boundary **123** and the second termination boundary **124**, each of which is designed to land approximately the wrist location of a wearer. Accordingly, in this illustrative embodiment the first termination boundary **123** and the second termination boundary **124** are disposed between the first connection location **121** and the first thumb loop **111**, and between the second connection location **122** and the second thumb loop **112**, respectively. This results in the first sleeve **107** and the second sleeve **108** extending beyond the first termination boundary **123** and the second termination boundary **124** in this illustrative embodiment.

(38) In one or more embodiments, the first concentric sleeve **119** comprises a first elastic gathering **125**. Similarly, the second concentric sleeve **120** comprises a second elastic gathering **126**. Each elastic gathering **125,126** is configured to draw the respective concentric sleeve toward the respective sleeve. For example, the first elastic gathering **125** is configured to draw the first concentric sleeve **119** toward the first sleeve **107** in this embodiment. Similarly, the second elastic gathering **126** is configured to draw the second concentric sleeve **120** toward the second sleeve **108**.

(39) In this illustrative embodiment, each elastic gathering **125,126** is disposed between its respective connection location and termination boundary. For example, the first elastic gathering **125** is disposed along the first concentric sleeve **119** at a location that is between the first connection location **121** and the first termination boundary **123**. Similarly, the second elastic

gathering **126** is disposed along the second concentric sleeve **120** at a location that is between the second connection location **122** and the second termination boundary **124**. However, embodiments of the disclosure are not so limited. In other embodiments, such as the one described below with reference to FIG. **12**, the elastic gatherings **125,126** can be disposed at the first termination boundary **123** and second termination boundary **124**, respectively.

(40) In this illustrative embodiment, the first elastic gathering **125** and the second elastic gathering **126** are disposed closer to their respective termination boundaries than to the connection locations at which the concentric sleeves to which the elastic gatherings are attached couples to the sleeves of the gown **100**. For example, the first elastic gathering **125** is disposed closer to the first termination boundary **123** than to the first connection location **121**. Similarly, the second elastic gathering **126** is disposed closer to the second termination boundary **124** than the second connection location **122** in this embodiment. It should be noted that the elastic gatherings **125,126** can be replaced by other gathering devices, including drawstrings, rubber bands, or other devices. In still other embodiments, the elastic gatherings **125,126** can be omitted.

(41) In one or more embodiments, the first concentric sleeve **119** and the second concentric sleeve **120** are selectively slidable along the first sleeve **107** and the second sleeve **108**, respectively, toward and away from the first connection location **121** and the second connection location **122**, respectively. For example, in this embodiment the first termination boundary **123** is selectively slidable along the first sleeve **107** toward the first connection location **121**. Similarly, the second termination boundary **124** is selectively slidable along the second sleeve **108** toward the second connection location **122**.

(42) In one or more embodiments, the gown **100** can include one or more tie members **127,128** extending from the body covering portion **101**. In this illustrative embodiment, the tie members include a first tie member **127** extending from the left side **204** and a second tie member **128** extending from the right side **205** of the gown. Accordingly, one tie member **127** is disposed on one side of the opening **201**, while the second tie member **128** is disposed on a second side of the opening. Here, the tie members **127,128** are contiguous with the body covering portion **101**. However, they can be attached to the body covering portion **101** as well. Such embodiments are described below with reference to FIGS. **9-12**.

(43) Turning now to FIGS. **3-8**, illustrated therein are the various steps of donning a gown **100** in accordance with one or more embodiments of the disclosure. Beginning with FIG. **3**, a wearer **300** can be seen donning the gown **100**. Specifically, the wearer **300** has inserted his head into the head insertion aperture **104**. Also, the wearer **300** has inserted his arms **301,302** into the arm insertion apertures **303,304** of each sleeve **107,108**. The wearer **300** has inserted his thumbs **305,306** into the thumb loops **111,112**, thereby latching the thumb loops **111,112** about the thumbs **305,306** to retain the sleeves **107,108** snugly along each arm **301,302**. The ties **127,128** are initially untied as shown in FIG. **3**. However, once tied, the ties **127,128** cinch the body covering portion **101** at the user's waist **401** as shown in FIG. **4**.

(44) Turning now to FIG. **5**, here the wearer **300** has translated **501,502** the first termination boundary **123** of the first concentric sleeve **119** and the second termination boundary **124** of the second concentric sleeve **120** toward the first connection location **121** and the second connection location **122**, respectively. This translation **501,502** reveals additional portions **503,504** of the first sleeve **107** and the second sleeve **108**, respectively, each of which was previously disposed beneath the first concentric sleeve **119** and the second concentric sleeve **120**.

(45) Turning now to FIG. **6**, the wearer **300** dons a first glove **601** and a second glove **602**. As shown in FIG. **6**, at least a portion **603,604** of the first glove **601** and the second glove **602** extends along the exterior of the first additional portion (**503**) of the first sleeve **107** and the second additional portion (**504**) of the second sleeve **108**.

(46) Turning now to FIG. **7**, the wearer **300** then retranslates **701,702** the first termination boundary **123** of the first concentric sleeve **119** and the second termination boundary **124** of the second

concentric sleeve **120** away from the first connection location **121** and the second connection location **122**, respectively. Said differently, the wearer **300** then retranslates **701,702** the first termination boundary **123** of the first concentric sleeve **119** and the second termination boundary **124** of the second concentric sleeve **120** toward the first thumb loop (**111**) and the second thumb loop (**112**), respectively. As shown in FIG. 7, this retranslation **701,702** includes placing at least a portion **703** of the first concentric sleeve **119** exterior to the portion **603** of the first glove **601**, and placing at least a portion **704** of the second concentric sleeve **120** exterior to the portion **604** of the second glove **602**.

(47) Turning now to FIG. 8, a medical professional **800** is shown wearing one embodiment of a gown **100** configured in accordance with one or more embodiments of the disclosure. The first sleeve **107** and the second sleeve **108** are covered by the base of the first glove **601** and the base of the second glove **602**. The first concentric sleeve **119** and the second concentric sleeve **120** then cover the base of the first glove **601** and the base of the second glove **602**. Advantageously, this prevents the channeling of liquids into the gloves **601,602**. Should additional protection be required, another pair of gloves can be placed atop the first glove **601** and the second glove **602**, with the additional gloves covering portions of the first concentric sleeve **119** and the second concentric sleeve **120**.

(48) Advantageously, the configuration of FIG. 8 serves to protect the medical professional **800** from coming into contact with fluids, which may contain pathogens and microorganisms carrying communicable diseases. As medical professionals generally interact with such fluids with their hands and arms, rather than other parts of their bodies, the inclusion of sealed sleeves in a gown **100**, as shown in FIG. 8, eliminates a large majority of pathways between the fluid and medical professional **800**.

(49) In one or more embodiments, the gown **100** is configured to meet the PB70 Standard of the Association for the Advancement of Medical Instrumentation (AAMI). For example, the gown **100** may have a moisture vapor transmission rate (MVTR) that allows for comfort during wearing while still meeting the Spray impact test (AATCC42), Hydrostatic Pressure testing (AATCC127) and Viral Penetration testing (ASTM-F1671) guidelines. For medical applications the gown **100** can have vapor and moisture barrier characteristics that may be required by an applicable AAMI level. In one embodiment, the gown **100** protects to an AAMI-PB70 Level-3 level or rating.

(50) Turning now to FIGS. 9 and 10, illustrated therein is an alternate gown **900** configured in accordance with embodiments of the disclosure. As before, a body covering portion **901** is configured to wrap about the torso of a wearer. The body covering portion **901** of FIG. 9 differs from the body covering portion (**101**) of FIG. 1 in that it is substantially rectangular when viewed from a plan perspective. Additionally, it fully covers the backside of a wearer, while the body covering portion (**101**) only partially covered the backside of a wearer. Other elements of the body covering portion **901** of FIG. 9 can be the same as that of FIG. 1. For example, the body covering portion **901** of FIG. 9 can be manufactured from a single, unitary layer of polyethylene or polyurethane.

(51) The body covering portion **901** includes a front portion **903** and a rear portion **1003**. The front portion **903** is configured as a frontal body covering portion in that it is configured to cover the frontal portion of some or all of a user's body, or in another embodiment the frontal portion of some or all of a user's torso, when the user is wearing the gown. The body covering portion **901** further includes a rear portion **1003** that is configured to cover substantially all of a wearer's backside. In the illustrative example of FIGS. 9 and 10, the rear portion **1003** has a shorter length than the front portion **903**, although this is but one configuration for one embodiment. In another embodiment, shown in FIGS. 11 and 12, the front portion (**1103**) will be substantially the same length as the rear portion (**1203**), and so forth. In other embodiments, the front portion **903** may be shorter than the rear portion **1003**, thereby covering less of the wearer's body in the front than in the rear.

(52) In one embodiment, the body covering portion **901** defines an opening **1001**. The front portion

903 of the gown **900** is configured, in one embodiment, to be placed against the front of the torso of a wearer. The body covering portion **901** then wraps around and terminates at the opening **1001**. The opening **1001** in this embodiment has a left side **1004** and a right side **1005** that abut due to the fact that the opening **1001** is configured as a slit that runs the length **1030** of the rear side **1003** of the back of the gown **900**. The opening **1001** can be used to assist in donning the gown as previously described.

(53) In one embodiment, a first sleeve **907** and a second sleeve **908** extend distally from the body covering portion **901**. The first sleeve **907** and the second sleeve **908** are configured to receive wearer's arms when the gown **900** is donned. As with previous embodiments, the gown **900** has sleeves **907,908** that each terminate in a thumb loop **911,912**.

(54) As with previous embodiments, a first concentric sleeve **919** and a second concentric sleeve **920** are coupled to the first sleeve **907** and the second sleeve **908**, respectively. The first concentric sleeve **919** and the second concentric sleeve **920** extend along an exterior of the first sleeve **907** and second sleeve **908**, respectively, toward the thumb loops **911,912**. The first concentric sleeve **919** and the second concentric sleeve **920** function in the same manner as previously described.

(55) In one embodiment, the gown **900** includes one or more ties **932** that can be tied together to close the opening **1001**. For example, one tie **932** can be provided shown on one of the gown **900** that wraps completely around the wearer. In another embodiment, a second tie **970** can attach to the gown **900** at a common connection point with the first tie **932**. When a wearer dons the gown **900**, they can wrap the first tie **932** around the front of their torso and the second tie **970** around the back, tying the first tie **932** and the second tie **970** together on the left side of their torso. In yet another embodiment, as shown in FIG. 12, a second tie **1270** can be attached as a mirror image of tie **1232** on the left side of the gown **1200** as well.

(56) The tie members **1232,1270** can be attached to the gown **1200** in a variety of ways. In one embodiment, the tie members **1232,1270** are sewn to the gown **1200**. In another embodiment, the tie members **1232,1270** are adhesively attached to the gown **1200**. In another embodiment, the tie members **1232,1270** are thermally bonded to the gown **1200**. Other attachment methods will be obvious to those of ordinary skill in the art. These attachment methods could be used for the ties (**932,970**) of FIGS. 9-10 as well. In the illustrative embodiments of FIGS. 9-12, the tie members are attached at hip regions of the gowns. When the tie members are tied across the opening, the body covering portion become "cinched" at the waist region about the wearer.

(57) In the embodiment of FIGS. 11-12, the gown **1200** includes a first sleeve **1107** and a second sleeve **1108**, each of which extends distally from the body covering portion **1101**. The first sleeve **1107** and the second sleeve **1108** are configured to receive wearer's arms when the medical gown **1100** is donned. As with previous embodiments, the medical gown **1100** has sleeves **1107,1108** that each terminate in a thumb loop **1111,1112**.

(58) As with previous embodiments, a first concentric sleeve **1119** and a second concentric sleeve **1120** are coupled to the first sleeve **1107** and the second sleeve **1108**, respectively. The first concentric sleeve **1119** and the second concentric sleeve **1120** extend along an exterior of the first sleeve **1107** and second sleeve **1108**, respectively, toward the thumb loops **1111,1112**.

(59) In this illustrative embodiment, the first concentric sleeve **1119** and the second concentric sleeve **1120** function generally in the same manner as previously described. However, instead of including an elastic gathering (**125,126**), in this illustrative embodiment the first concentric sleeve **1110** and the second concentric sleeve **1120** terminate at a knitted cuff **1125,1126**. The knitted cuffs **1125,1126** define the termination boundaries of each of the first concentric sleeve **1119** and the second concentric sleeve **1120** in this embodiment.

(60) Turning now to FIG. 13, illustrated therein is yet another sleeve assembly **1300** configured in accordance with one or more embodiments of the disclosure. The sleeve assembly **1300** can be used as the right sleeve, left sleeve, or combinations thereof for a medical gown in accordance with one or more embodiments of the disclosure.

(61) The sleeve assembly **1300** of FIG. **13** includes an inner sleeve **1307** and a concentric outer sleeve **1319**. The concentric outer sleeve **1319** is coupled to the inner sleeve **1307** at a connection location **1321**. As before, the concentric outer sleeve **1319** extends from the connection location **1321** along an exterior of the inner sleeve **1307** toward a retention device **1309**. In this illustrative embodiment, the retention device **1309** is a knitted cuff **1311** rather than a thumb loop. Another difference occurring in the embodiment of FIG. **13** is that the elastic gathering **1325** of the concentric outer sleeve **1319** is disposed at the termination boundary **1323** of the concentric outer sleeve **1319**. Otherwise, the sleeve assembly **1300** can be used in the same manner as described above with reference to FIGS. **3-8**.

(62) Turning now to FIG. **14**, illustrated therein is a method **1400** of manufacturing a gown in accordance with one or more embodiments of the disclosure. At step **1401**, the method **1400** includes causing a first sleeve and a second sleeve to extend from a body covering to a retention device. In one embodiment, the retention device occurring at step **1401** comprises a thumb loop. In another embodiment, the retention device occurring at step **1401** comprises a knitted cuff. Other retention devices will be obvious to those of ordinary skill in the art having the benefit of this disclosure.

(63) At step **1402**, the method **1400** includes attaching a first concentric sleeve to the first sleeve at a first connection location such that the first concentric sleeve extends along an exterior of the first sleeve toward the thumb loop. At step **1403**, the method **1400** includes attaching a second concentric sleeve to the second sleeve at a second connection location such that the second concentric sleeve extends along the exterior of the second sleeve toward the thumb loop.

(64) In one or more embodiments, optional step **1404** includes causing the first sleeve to extend beyond a first termination boundary of the first concentric sleeve such that the thumb loop of the first sleeve extends beyond the first termination boundary. Similarly, optional step **1405** can include causing the second sleeve to extend beyond a second termination boundary of the second concentric sleeve such that the thumb loop of the second sleeve extends beyond the second termination boundary. At optional step **1406**, the method **1400** can include attaching one or more ties to the body covering portion of the gown.

(65) In the foregoing specification, specific embodiments of the present disclosure have been described. However, one of ordinary skill in the art appreciates that various modifications and changes can be made without departing from the scope of the present disclosure as set forth in the claims below. Thus, while preferred embodiments of the disclosure have been illustrated and described, it is clear that the disclosure is not so limited. Numerous modifications, changes, variations, substitutions, and equivalents will occur to those skilled in the art without departing from the spirit and scope of the present disclosure as defined by the following claims. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of present disclosure. The benefits, advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential features or elements of any or all the claims.

Claims

1. A gown, comprising: a body covering portion; a first sleeve and a second sleeve, each extending distally away from the body covering portion and terminating at a thumb loop; a first concentric sleeve coupled to the first sleeve at a first connection location disposed at a shoulder of the first sleeve and extending along an exterior of the first sleeve toward the thumb loop to a first termination boundary landing at a wrist location of the first sleeve, the first termination boundary selectively slidable along the first sleeve toward the first connection location; and a second concentric sleeve coupled to the second sleeve at a second connection location disposed at a

- shoulder of the second sleeve and extending along the exterior of the second sleeve toward the thumb loop to a second termination boundary landing at a wrist location of the second sleeve, the second termination boundary selectively slidable along the second sleeve toward the second connection location.
2. The gown of claim 1, the first termination boundary disposed between the thumb loop and the first connection location.
 3. The gown of claim 2, the second termination boundary disposed between the thumb loop and the second connection location.
 4. The gown of claim 3, the first concentric sleeve comprising an elastic gathering drawing the first concentric sleeve toward the first sleeve, the elastic gathering disposed between the first connection location and the first termination boundary.
 5. The gown of claim 4, the elastic gathering disposed closer to the first termination boundary than the first connection location.
 6. The gown of claim 5, the elastic gathering disposed at the first termination boundary.
 7. The gown of claim 4, the second concentric sleeve comprising another elastic gathering drawing the second concentric sleeve toward the second sleeve, the another elastic gathering disposed between the second connection location and the second termination boundary.
 8. The gown of claim 3, the first concentric sleeve comprising a cuff defining the first termination boundary, the second concentric sleeve comprising another cuff defining the second termination boundary.
 9. The gown of claim 1, the first sleeve and the first concentric sleeve manufactured from the same material.
 10. The gown of claim 1, the first concentric sleeve manufactured from different materials.
 11. The gown of claim 1, wherein the body covering portion, the first sleeve, and the second sleeve are manufactured from polyethylene.
 12. The gown of claim 1, the body covering portion comprising a front portion and a rear portion, wherein the front portion is longer than the rear portion.
 13. The gown of claim 12, the front portion configured to cover a frontal portion of a wearer, the rear portion configured to cover only shoulders of the wearer.
 14. The gown of claim 1, wherein the body covering portion, the first sleeve, and the second sleeve comprise a single, unitary, contiguous piece of liquid impervious material.
 15. The gown of claim 1, wherein the gown is configured to meet the PB70 Standard of the Association for the Advancement of Medical Instrumentation (AAMI).
 16. The gown of claim 1, the body covering portion defining an opening comprising a slit having a left side and a right side that abut.
 17. The gown of claim 16, the slit running the length a rear side of a back of the gown.
-