

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402964
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Burbank; William A.

Robotic surgical stapler assembly configured to use stapler reload

Abstract

A robotic surgical assembly includes a drive assembly and a shaft assembly. The drive assembly is detachably mountable to a surgical robot and includes roll, pitch, and clamp/fire inputs configured to drivingly couple with respective outputs of the surgical robot. The shaft assembly is mounted to the drive assembly and configured to detachably couple with a stapler reload assembly that includes a reload roll shaft, a reload pitch shaft, and a reload clamp/fire shaft. The shaft assembly includes a roll shaft, a pitch shaft, and a clamp/fire shaft. The roll shaft is drivingly coupled with the roll input and configured to detachably couple to the reload roll shaft. The pitch shaft is drivingly coupled with the pitch input and configured to detachably couple to the reload pitch shaft. The clamp/fire shaft is drivingly coupled with the clamp/fire input and configured to detachably couple to the reload clamp/fire shaft.

Inventors:	Burbank; William A. (Sandy Hook, CT)
Applicant:	INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)
Family ID:	62076352
Assignee:	INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)
Appl. No.:	17/588761
Filed:	January 31, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220151717 A1	May. 19, 2022

Related U.S. Application Data

division parent-doc US 16346561 US 11259884 WO PCT/US2017/059706 20171102 child-doc US 17588761

Publication Classification

Int. Cl.: **A61B34/35** (20160101); **A61B17/00** (20060101); **A61B17/068** (20060101); **A61B17/072** (20060101); **A61B17/29** (20060101); **A61B34/30** (20160101); **A61B34/37** (20160101)

U.S. Cl.:

CPC **A61B34/35** (20160201); **A61B17/07207** (20130101); **A61B34/30** (20160201); **A61B34/37** (20160201); A61B2017/00367 (20130101); A61B2017/00473 (20130101); A61B2017/00477 (20130101); A61B17/068 (20130101); A61B2017/2902 (20130101); A61B2017/2927 (20130101); A61B2017/2929 (20130101); A61B2017/2931 (20130101); A61B2017/2936 (20130101); A61B2017/294 (20130101); A61B2017/2943 (20130101); A61B2034/302 (20160201)

Field of Classification Search

CPC: A61B (34/35); A61B (17/07207); A61B (34/30); A61B (34/37); A61B (17/068); A61B (2017/00367); A61B (2017/00473); A61B (2017/00477); A61B (2017/2902); A61B (2017/2927); A61B (2017/2929); A61B (2017/2931); A61B (2017/2936); A61B (2017/294); A61B (2017/2943); A61B (2034/302)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5792165	12/1997	Klieman	606/174	A61B 17/2909
9060770	12/2014	Shelton, IV	N/A	A61B 17/07207
9402687	12/2015	Parihar et al.	N/A	N/A
2003/0125716	12/2002	Wang et al.	N/A	N/A
2011/0071508	12/2010	Duval et al.	N/A	N/A
2011/0118754	12/2010	Dachs, II et al.	N/A	N/A
2011/0264114	12/2010	Choi et al.	N/A	N/A
2011/0290853	12/2010	Shelton, IV et al.	N/A	N/A
2011/0290855	12/2010	Moore	227/176.1	A61B 34/30
2012/0116391	12/2011	Houser	606/1	A61B 34/76
2012/0150154	12/2011	Brisson	606/1	A61B 34/70
2012/0292367	12/2011	Morgan	227/175.1	A61B 17/072
2013/0105545	12/2012	Burbank	227/175.1	A61B 50/13
2013/0110129	12/2012	Reid	403/326	A61B 34/30
2014/0221987	12/2013	Jeong	606/1	A61B 17/00234
2014/0276720	12/2013	Parihar	606/130	A61B 18/1445
2019/0262088	12/2018	Burbank	N/A	A61B 17/07207

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101400308	12/2008	CN	N/A
101767130	12/2009	CN	N/A
102440813	12/2011	CN	N/A
103989495	12/2013	CN	N/A
104023652	12/2013	CN	N/A
104337557	12/2014	CN	N/A
1917929	12/2007	EP	N/A
2005906	12/2007	EP	N/A
2881049	12/2014	EP	N/A
WO-2012068156	12/2011	WO	N/A
WO-2012166503	12/2011	WO	N/A
WO-2014004292	12/2013	WO	N/A
WO-2014066044	12/2013	WO	N/A
WO-2015142794	12/2014	WO	N/A

OTHER PUBLICATIONS

Balasubramaniam M et al., "An Anti Backlash Two-part Shaft Coupling with Interlocking Elastically Averaged Teeth," Precision Engineering, Jul. 2002, 29 pages. cited by applicant
Extended European Search Report for Application No. EP17867004.8, mailed on Jun. 3, 2020, 12 pages. cited by applicant
International Search Report and Written Opinion for Application No. PCT/US2017/059706, mailed on May 9, 2018, 15 pages. cited by applicant
Office Action mailed Dec. 28, 2020 for Chinese Application No. CN201780067655 filed Nov. 2, 2017, 20 pages. cited by applicant
Vertut, J, and Coiffet, P., "Robot Technology: Teleoperation and Robotics Evolution and Development," English translation, Prentice-Hall, Inc., Inglewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages. cited by applicant
Extended European Search Report for Application No. EP23200242.8, mailed on Apr. 25, 2024, 12 pages. cited by applicant

Primary Examiner: David; Shaun L

Assistant Examiner: Geiger; Rachael L

Attorney, Agent or Firm: Jones Robb, PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional application of U.S. patent application Ser. No. 16/346,561, filed May 1, 2019, which is a U.S. National Stage application of PCT/US2017/059706, filed Nov. 2, 2017, which claims the benefit of U.S. Provisional Application No. 62/416,454, filed Nov. 2, 2016, each of which is hereby incorporated by reference in its entirety.

BACKGROUND

(1) Minimally invasive surgical techniques are aimed at reducing the amount of extraneous tissue

that is damaged during diagnostic or surgical procedures, thereby reducing patient recovery time, discomfort, and deleterious side effects. As a consequence, the average length of a hospital stay for standard surgery may be shortened significantly using minimally invasive surgical techniques. Also, patient recovery times, patient discomfort, surgical side effects, and time away from work may also be reduced with minimally invasive surgery.

(2) A common form of minimally invasive surgery is endoscopy, and a common form of endoscopy is laparoscopy, which is minimally invasive inspection and surgery inside the abdominal cavity. In standard laparoscopic surgery, a patient's abdomen is insufflated with gas, and cannula sleeves are passed through small (approximately one-half inch or less) incisions to provide entry ports for laparoscopic instruments.

(3) Laparoscopic surgical instruments generally include an endoscope (e.g., laparoscope) for viewing the surgical field and tools for working at the surgical site. The working tools are typically similar to those used in conventional (open) surgery, except that the working end or end effector of each tool is separated from its handle by an extension tube (also known as, e.g., an instrument shaft or a main shaft). The end effector can include, for example, a clamp, grasper, scissor, stapler, cautery tool, linear cutter, or needle holder.

(4) To perform surgical procedures, the surgeon passes working tools through cannula sleeves to an internal surgical site and manipulates them from outside the abdomen. The surgeon views the procedure from a monitor that displays an image of the surgical site taken from the endoscope. Similar endoscopic techniques are employed in, for example, arthroscopy, retroperitoneoscopy, pelviscopy, nephroscopy, cystoscopy, cisternoscopy, sinoscopy, hysteroscopy, urethroscopy, and the like.

(5) Minimally invasive telesurgical robotic systems are being developed to increase a surgeon's dexterity when working on an internal surgical site, as well as to allow a surgeon to operate on a patient from a remote location (outside the sterile field). In a telesurgery system, the surgeon is often provided with an image of the surgical site at a control console. While viewing a three dimensional image of the surgical site on a suitable viewer or display, the surgeon performs the surgical procedures on the patient by manipulating master input or control devices of the control console. Each of the master input devices controls the motion of a servo-mechanically actuated/articulated surgical instrument. During the surgical procedure, the telesurgical system can provide mechanical actuation and control of a variety of surgical instruments or tools having end effectors that perform various functions for the surgeon, for example, holding or driving a needle, grasping a blood vessel, dissecting tissue, or the like, in response to manipulation of the master input devices.

(6) Surgical clamping and cutting instruments (e.g., non-robotic linear clamping, stapling, and cutting devices, also known as surgical staplers; and electrosurgical vessel sealing devices) have been employed in many different surgical procedures. For example, a surgical stapler can be used to resect a cancerous or anomalous tissue from a gastro-intestinal tract. Many known surgical clamping and cutting devices, including known surgical staplers, have opposing jaws that clamp tissue and an articulated knife to cut the clamped tissue.

(7) Surgical staplers are often configured to use a replaceable single use stapler cartridge. A hospital can have a number of different types (e.g., different makes and models) of surgical staplers, including different hand-held surgical staplers and/or telesurgical robotic system surgical staplers. Each type of surgical stapler, however, may be configured to use a corresponding type of stapler cartridge, thereby resulting in a hospital having to stock different types of replaceable stapler cartridges. Stocking different types of replaceable stapler cartridges results in additional expense in terms of additional inventory and resources to ensure that suitable numbers of each type of stapler cartridge are stocked.

BRIEF SUMMARY

(8) Robotic surgical assemblies detachably mountable to a surgical robot are configured to use a

replaceable stapler cartridge of a common hand-held surgical stapler. The ability to use the same replaceable stapler cartridge as the common hand-held surgical stapler can help to reduce the number and types of stapler cartridges that are stocked by a hospital, thereby reducing related expense. The use of the same stapler cartridge as the common hand-held surgical stapler can also reduce training expense and help to reduce surgical error related to having to use different types of replaceable stapler cartridges.

(9) Thus, in one aspect, a robotic surgical assembly includes a drive assembly detachably mountable to a surgical robot and a shaft assembly mounted to the drive assembly. The drive assembly includes a chassis, a roll input configured to drivingly couple with a roll output of the surgical robot, a pitch input configured to drivingly couple with a pitch output of the surgical robot, and a clamp/fire input configured to drivingly couple with a clamp/fire output of the surgical robot. The shaft assembly is elongated along a shaft axis and configured to detachably couple with a stapler reload assembly that includes an end effector operable to clamp and staple tissue, a reload roll shaft to which the end effector is pivotally mounted, a reload pitch shaft translatable along the shaft axis to reorient the end effector relative to the reload roll shaft, and a reload clamp/fire shaft drivingly coupled with the end effector and translatable along the shaft axis to actuate the end effector to clamp and staple tissue. The shaft assembly includes a roll shaft, a pitch shaft, and a clamp/fire shaft. The roll shaft is drivingly coupled with the drive assembly so that rotation of the roll input rotates the roll shaft around the shaft axis. The roll shaft has a proximal portion configured to detachably couple to the reload roll shaft. The pitch shaft is drivingly coupled with the drive assembly so that rotation of the pitch input translates the pitch shaft along the shaft axis. The pitch shaft has a proximal portion configured to detachably couple to the reload pitch shaft. The clamp/fire shaft is drivingly coupled with the drive assembly so that rotation of the clamp/fire input translates the clamp/fire shaft along the shaft axis. The clamp/fire shaft has a proximal portion configured to detachably couple to the reload clamp/fire shaft.

(10) In many embodiments of the robotic surgical assembly, the roll shaft, the pitch shaft, and the clamp/fire shaft are coaxial with the shaft axis. For example, the roll shaft can have a roll shaft lumen extending along the shaft axis. The pitch shaft can be accommodated within the roll shaft lumen and constrained to rotate with the roll shaft around the shaft axis. The pitch shaft can have a pitch shaft lumen extending along the shaft axis. The clamp/fire shaft can be accommodated within the pitch shaft lumen and constrained to rotate with the roll shaft around the shaft axis.

(11) In many embodiments of the robotic surgical assembly, the drive assembly includes output gears that are constrained to rotate around the shaft axis. For example, the drive assembly can include a roll output gear drivingly coupled with the roll input. The roll output gear can be attached to the roll shaft and constrained to rotate around the shaft axis. The drive assembly can include a pitch output gear drivingly coupled with the pitch input and constrained to rotate around the shaft axis. The pitch output gear can be drivingly coupled with the pitch shaft via a screw thread interface that converts rotation of the pitch output gear into translation of the pitch shaft along the shaft axis. The drive assembly can include a clamp/fire output gear drivingly coupled with the clamp/fire input and constrained to rotate around the shaft axis. The clamp/fire output gear can be drivingly coupled with the clamp/fire shaft via a screw thread interface that converts rotation of the clamp/fire output gear into translation of the clamp/fire shaft along the shaft axis.

(12) In many embodiments of the robotic surgical assembly, the drive assembly includes output bearings configured to constrain the output gears to rotate around the shaft axis. For example, the drive assembly can include a shaft bearing having an outer race interfaced with the chassis and an inner race interfaced with the roll output gear. The shaft bearing can be configured to constrain the roll output gear to rotation around the shaft axis. The drive assembly can include a roll output gear bearing having an outer race interfaced with the roll output gear and an inner race interfaced the pitch output gear. The roll output gear bearing can be configured to constrain the pitch output gear to rotation around the shaft axis. The drive assembly can include a pitch output gear bearing having

an outer race interfaced with the pitch output gear and an inner race interfaced with the clamp/fire output gear. The pitch output gear roller bearing can be configured to constrain the clamp/fire output gear to rotation around the shaft axis. The drive assembly can include an upper chassis supported by the chassis and a clamp/fire output gear bearing having an inner race interfaced with the upper chassis and an outer race interfaced with the clamp/fire output gear. The upper chassis can be detachably mountable to the chassis.

(13) In embodiments of the robotic surgical assembly that include output gears, the output gears are drivingly coupled with the roll input, the pitch input, and the clamp/fire input. For example, the drive assembly can include: (a) a clamp/fire input shaft rotationally coupled with the clamp/fire input; (b) a clamp/fire input gear rotationally coupled with the clamp/fire input shaft, the clamp/fire input gear having external gear teeth drivingly engaging external gear teeth of the clamp/fire output gear; and (c) clamp/fire input shaft bearings, each of the clamp/fire input shaft bearings having an outer race interfaced with the chassis and an inner race interfaced with the clamp/fire input shaft. The drive assembly can include: (a) a pitch input shaft rotationally coupled with the pitch input; (b) a pitch input gear rotationally coupled with the pitch input shaft, the pitch input gear having external gear teeth drivingly engaging external gear teeth of the pitch output gear; and (c) pitch input shaft bearings, each of the pitch input shaft bearings having an outer race interfaced with the chassis and an inner race interfaced with the pitch input shaft. The drive assembly can include: (a) a roll input shaft rotationally coupled with the roll input; (b) roll input shaft bearings, each of the roll input shaft bearings having an outer race interfaced with the chassis and an inner race interfaced with the roll input shaft; (c) a roll input gear rotationally coupled with the roll input shaft; and (d) an idler gear having external teeth drivingly engaged by external teeth of the roll input gear and drivingly engaging external teeth of the roll output gear.

(14) In another aspect, a robotic surgical method of actuating a stapler reload assembly is provided. The method includes detachably mounting a drive assembly of a robotic surgical assembly to a surgical robot so as to: (a) interface a roll output of the surgical robot with a roll input of the drive assembly; (b) interface a pitch output of the surgical robot with a pitch input of the drive assembly; and (c) interface a clamp/fire output of the surgical robot with a clamp/fire input of the drive assembly. The method further includes detachably mounting a stapler reload assembly to a distal end of a shaft assembly of the robotic surgical assembly so as to: (a) interface a roll shaft of the robotic surgical assembly with a roll shaft of the stapler reload assembly; (b) interface a pitch shaft of the robotic surgical assembly with a pitch shaft of the stapler reload assembly; and (c) interface a clamp/fire shaft of the robotic surgical assembly with a clamp/fire shaft of the stapler reload assembly. The roll shaft of the shaft assembly is rotated by actuating a roll shaft drive mechanism drivingly coupling the roll shaft of the shaft assembly with the roll input of the drive assembly by rotating the roll output of the surgical robot. The pitch shaft of the shaft assembly is translated relative to the stapler reload assembly by actuating a pitch shaft drive mechanism drivingly coupling the pitch shaft of the shaft assembly with the pitch input of the drive assembly by rotating the pitch output of the surgical robot. The clamp/fire shaft of the shaft assembly is translated relative to the stapler reload assembly by actuating a pitch shaft drive mechanism drivingly coupling the clamp/fire shaft of the shaft assembly with the pitch input of the drive assembly by rotating the pitch output of the surgical robot.

(15) In many embodiments of the robotic surgical method of actuating a stapler reload assembly, rotating the roll shaft of the shaft assembly includes rotating a roll output gear drivingly coupled with the roll input and attached to the roll shaft. For example, rotating the roll output gear can include: (a) rotating a roll input shaft rotationally coupled with the roll input, (b) rotating a roll input gear rotationally coupled with the roll input shaft, (c) interfacing external gear teeth of the roll input gear with external gear teeth of the roll idler gear, and (d) interfacing external gear teeth of the roll idler gear with external gear teeth of the roll output gear. Rotating the roll output gear can include: (a) interfacing an outer race of a shaft bearing with a chassis of the drive assembly, (b)

interfacing an inner race of the shaft bearing with the roll output gear, and (c) rotating the inner race of the shaft bearing with the roll output gear.

(16) In many embodiments of the robotic surgical method of actuating a stapler reload assembly, translating the pitch shaft of the shaft assembly includes: (a) rotating a pitch output gear drivingly coupled with the pitch input, and (b) generating translation of the pitch shaft from rotation of the pitch output gear via a screw thread interface between the pitch shaft and the pitch output gear. For example, rotating the pitch output gear can include: (a) rotating a pitch input shaft rotationally coupled with the pitch input, (b) rotating a pitch input gear rotationally coupled with the pitch input shaft, and (c) interfacing external gear teeth of the pitch input gear with external gear teeth of the pitch output gear. Rotating the pitch output gear can include: (a) interfacing an outer race of a roll output gear bearing with the roll output gear, (b) interfacing an inner race of the roll output gear bearing with the pitch output gear, (c) rotating the inner race of the roll output gear bearing with the pitch output gear, and (d) rotating the outer race of the roll output gear bearing with the roll output gear.

(17) In many embodiments of the robotic surgical method of actuating a stapler reload assembly, translating the clamp/fire shaft of the shaft assembly includes: rotating a clamp/fire output gear drivingly coupled with the clamp/fire input, and (b) generating translation of the clamp/fire shaft from rotation of the clamp/fire output gear via a screw thread interface between the clamp/fire shaft and the clamp/fire output gear. For example, rotating the clamp/fire output gear can include: (a) rotating a clamp/fire input shaft rotationally coupled with the clamp/fire input, (b) rotating a clamp/fire input gear rotationally coupled with the clamp/fire input shaft, and (c) interfacing external gear teeth of the clamp/fire input gear with external gear teeth of the clamp/fire output gear. Rotating the clamp/fire output gear can include: (a) interfacing an outer race of a pitch output gear bearing with the pitch output gear, (b) interfacing an inner race of the pitch output gear bearing with the clamp/fire output gear, (c) rotating the inner race of the pitch output gear bearing with the clamp/fire output gear, and (d) rotating the outer race of the pitch output gear bearing with the pitch output gear. Rotating the clamp/fire output gear can include: (a) interfacing an outer race of a clamp/fire output gear bearing with the clamp/fire output gear, (b) interfacing an inner race of the clamp/fire output gear bearing with an upper chassis of the drive assembly supported by the chassis of the drive assembly, and (c) rotating the outer race of the clamp/fire output gear bearing with the clamp/fire output gear.

(18) For a fuller understanding of the nature and advantages of the present invention, reference should be made to the ensuing detailed description and accompanying drawings. Other aspects, objects and advantages of the invention will be apparent from the drawings and detailed description that follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a plan view of a minimally invasive robotic surgery system being used to perform a surgery, in accordance with many embodiments.

(2) FIG. 2 is a view of a surgeon's control console for a robotic surgery system, in accordance with many embodiments.

(3) FIG. 3 is a view of a robotic surgery system electronics cart, in accordance with many embodiments.

(4) FIG. 4 diagrammatically illustrates a robotic surgery system, in accordance with many embodiments.

(5) FIG. 5 is a front view of a patient side cart (surgical robot) of a robotic surgery system, in accordance with many embodiments.

- (6) FIG. 6 is a view of a robotic surgery tool that includes a demountable stapler reload portion, in accordance with many embodiments.
- (7) FIG. 7 is a simplified schematic diagram of a minimally invasive robotic surgery system including a surgical robot, a surgical stapler base assembly mounted to the surgical robot, and a surgical stapler reload mounted to the surgical stapler base assembly, in accordance with many embodiments.
- (8) FIG. 8 is a side view of a surgical stapler base assembly mounted to a surgical robot, and a surgical stapler reload mounted to the surgical stapler base assembly, in accordance with many embodiments.
- (9) FIG. 9 is a side view of the surgical stapler base assembly and the surgical stapler reload of FIG. 8 showing the surgical stapler reload separated from the surgical stapler base assembly, in accordance with many embodiments.
- (10) FIG. 10 is a simplified schematic side view of a distal end of the surgical stapler base assembly and a proximal end of the surgical stapler reload of FIG. 8 showing the surgical stapler reload separated from the surgical stapler base assembly, in accordance with many embodiments.
- (11) FIG. 11 and FIG. 12 illustrate components of a drive assembly of the surgical stapler base assembly of FIG. 8, in accordance with many embodiments.
- (12) FIG. 13A and FIG. 13B illustrate components of the drive assembly of the surgical stapler base assembly of FIG. 8 for generating translation of a clamp/fire shaft, in accordance with many embodiments.
- (13) FIG. 14A and FIG. 14B illustrate components of the drive assembly of the surgical stapler base assembly of FIG. 8 for generating translation of a pitch shaft, in accordance with many embodiments.
- (14) FIG. 15A, FIG. 15B, and FIG. 16 illustrate components of the drive assembly of the surgical stapler base assembly of FIG. 8 for generating rotation of a roll shaft, in accordance with many embodiments.
- (15) FIG. 17 is a cross-sectional view through an output gear assembly of the surgical stapler base of FIG. 8, in accordance with many embodiments.

DETAILED DESCRIPTION

(16) In the following description, various embodiments of the present invention will be described. For purposes of explanation, specific configurations and details are set forth in order to provide a thorough understanding of the embodiments. However, it will also be apparent to one skilled in the art that the present invention may be practiced without the specific details. Furthermore, well-known features may be omitted or simplified in order not to obscure the embodiment being described.

(17) Minimally Invasive Robotic Surgery

(18) Referring now to the drawings, in which like reference numerals represent like parts throughout the several views, FIG. 1 is a plan view illustration of a Minimally Invasive Robotic Surgical (MIRS) system 10, typically used for performing a minimally invasive diagnostic or surgical procedure on a Patient 12 who is lying down on an Operating table 14. The system can include a Surgeon's Console 16 for use by a Surgeon 18 during the procedure. One or more Assistants 20 may also participate in the procedure. The MIRS system 10 can further include a Patient Side Cart 22 (surgical robot) and an Electronics Cart 24. The Patient Side Cart 22 can manipulate at least one removably coupled tool assembly 26 (hereinafter simply referred to as a "tool") through a minimally invasive incision in the body of the Patient 12 while the Surgeon 18 views the surgical site through the Console 16. An image of the surgical site can be obtained by an endoscope 28, such as a stereoscopic endoscope, which can be manipulated by the Patient Side Cart 22 to orient the endoscope 28. The Electronics Cart 24 can be used to process the images of the surgical site for subsequent display to the Surgeon 18 through the Surgeon's Console 16. The number of surgical tools 26 used at one time will generally depend on the diagnostic or surgical

procedure and the space constraints within the operating room among other factors. If it is necessary to change one or more of the tools **26** being used during a procedure, an Assistant **20** may remove the tool **26** from the Patient Side Cart **22**, and replace it with another tool **26** from a tray **30** in the operating room.

(19) FIG. **2** is a perspective view of the Surgeon's Console **16**. The Surgeon's Console **16** includes a left eye display **32** and a right eye display **34** for presenting the Surgeon **18** with a coordinated stereo view of the surgical site that enables depth perception. The Console **16** further includes one or more input control devices **36**, which in turn cause the Patient Side Cart **22** (shown in FIG. **1**) to manipulate one or more tools. The input control devices **36** can provide the same degrees of freedom as their associated tools **26** (shown in FIG. **1**) to provide the Surgeon with telepresence, or the perception that the input control devices **36** are integral with the tools **26** so that the Surgeon has a strong sense of directly controlling the tools **26**. To this end, position, force, and tactile feedback sensors (not shown) may be employed to transmit position, force, and tactile sensations from the tools **26** back to the Surgeon's hands through the input control devices **36**.

(20) The Surgeon's Console **16** is usually located in the same room as the patient so that the Surgeon may directly monitor the procedure, be physically present if necessary, and speak to an Assistant directly rather than over the telephone or other communication medium. However, the Surgeon can be located in a different room, a completely different building, or other remote location from the Patient allowing for remote surgical procedures.

(21) FIG. **3** is a perspective view of the Electronics Cart **24**. The Electronics Cart **24** can be coupled with the endoscope **28** and can include a processor to process captured images for subsequent display, such as to a Surgeon on the Surgeon's Console, or on another suitable display located locally and/or remotely. For example, where a stereoscopic endoscope is used, the Electronics Cart **24** can process the captured images to present the Surgeon with coordinated stereo images of the surgical site. Such coordination can include alignment between the opposing images and can include adjusting the stereo working distance of the stereoscopic endoscope. As another example, image processing can include the use of previously determined camera calibration parameters to compensate for imaging errors of the image capture device, such as optical aberrations.

(22) FIG. **4** diagrammatically illustrates the robotic surgery system **10**. As discussed above, the Surgeon's Console **16** can be used by a Surgeon to control the Patient Side Cart **22** (Surgical Robot) during a minimally invasive procedure. The Patient Side Cart **22** can use an imaging device, such as a stereoscopic endoscope, to capture images of the procedure site and output the captured images to the Electronics Cart **24**. As discussed above, the Electronics Cart **24** can process the captured images in a variety of ways prior to any subsequent display. For example, the Electronics Cart **24** can overlay the captured images with a virtual control interface prior to displaying the combined images to the Surgeon via the Surgeon's Console **16**. The Patient Side Cart **22** can output the captured images for processing outside the Electronics Cart **24**. For example, the Patient Side Cart **22** can output the captured images to a processor **38**, which can be used to process the captured images. The images can also be processed by a combination the Electronics Cart **24** and the processor **38**, which can be coupled together to process the captured images jointly, sequentially, and/or combinations thereof. One or more separate displays **40** can also be coupled with the processor **38** and/or the Electronics Cart **24** for local and/or remote display of images, such as images of the procedure site, or other related images.

(23) FIG. **5** and FIG. **6** show a Patient Side Cart **22** and a surgical tool **100**, respectively. The surgical tool **100** is an example of the surgical tools **26**. The Patient Side Cart **22** shown provides for the manipulation of three surgical tools **26** and an imaging device **28**, such as a stereoscopic endoscope used for the capture of images of the site of the procedure. Manipulation is provided by robotic mechanisms having a number of robotic joints. The imaging device **28** and the surgical tools **26** can be positioned and manipulated through incisions in the patient so that a kinematic remote center is maintained at the incision to minimize the size of the incision. Images of the

surgical site can include images of the distal ends of the surgical tools **26** when they are positioned within the field-of-view of the imaging device **28**.

(24) Robotic Surgical Tool Configured to Use Hand-Held Stapler Reload

(25) The surgical tool **100** includes a robotic surgical assembly **102** and a replaceable stapler reload **200** that is detachably coupled with the surgical assembly **102**. In many embodiments, the stapler reload **200** is configured for use with an existing hand-held surgical stapler.

(26) The robotic surgical assembly **102** is configured to be detachably mountable to a surgical robot (e.g., the patient side cart **22**) for use in clamping, stapling, and cutting tissue with the stapler reload **200**. The surgical assembly **102** is configured to mount to an instrument holder of the patient side cart **22**. The surgical assembly **102** includes a proximal drive assembly **104** and a shaft assembly **106** mounted to the drive assembly **104** and extending distally from the drive assembly **104** along a shaft axis **108**. The drive assembly includes a chassis **110**, a roll input member **112** mounted to the chassis **110** and rotatable relative to the chassis **110** by a respective roll output member of the patient side cart **22**, a pitch input member **114** mounted to the chassis **110** and rotatable relative to the chassis **110** by a respective pitch output member of the patient side cart **22**, and a clamp/fire input member **116** mounted to the chassis **110** and rotatable relative to the chassis **110** by a respective clamp/fire output member of the patient side cart **22**.

(27) The stapler reload **200** is a single use replaceable assembly that is detachably mountable to the shaft assembly **106**. The stapler reload **200** includes a proximal shaft assembly **202** and a stapler end effector **204**. The proximal shaft assembly **202** is detachably mountable to a distal end of the shaft assembly **106**. The end effector **204** is pivotally attached to a distal end of the proximal shaft assembly **202**. The end effector **204** includes an upper jaw **206** and a stapler cartridge assembly **208**. The stapler cartridge assembly **208** is pivotally mounted relative to the upper jaw **206** and can be actuated from an open position to a closed position to clamp tissue between the stapler cartridge assembly **208** and the upper jaw **206**. The stapler cartridge assembly **208** includes an actuation input that is translatable distally to close the stapler cartridge **208** to clamp tissue between the stapler cartridge **208** and the upper jaw **206**, to deploy staples from the stapler cartridge assembly **208**, and to cut the stapled tissue. The deployed staples penetrate through tissue clamped between the stapler cartridge **208** and the upper jaw **206** and into contact with an anvil surface of the upper jaw **206** that forms ends of the staples to retain the staples in the stapled tissue.

(28) FIG. 7 is a simplified schematic diagram of components of an embodiment of the Minimally Invasive Robotic Surgical (MIRS) system **10**. The illustrated components of the robotic surgical system **10** include includes the surgical robot **22**, the surgical stapler base assembly **102** mounted to the surgical robot **22**, a surgical stapler reload **200** mounted to the surgical stapler base assembly **102**, the electronics cart **24**, and the surgical console **16**.

(29) The surgical robot **22** includes a motor unit and instrument holder **42** to which the surgical stapler base assembly **102** is detachably mountable. The motor unit and instrument holder **42** is operable to controllably actuate the surgical stapler base assembly **102** to controllably actuate the surgical stapler reload **200**. The motor unit and instrument holder **42** includes a roll motor **44**, a roll output **46** drivingly coupled with the roll motor **44**, a pitch motor **48**, a pitch output **50** drivingly coupled with the pitch motor **48**, a clamp/fire motor **52**, and a clamp/fire output **54** drivingly coupled with the clamp/fire motor **52**. The roll motor **44** can be controllably operated to controllably rotate the roll output **46** relative to the motor unit and instrument holder **42**. Similarly, the pitch motor **48** can be controllably operated to controllably rotate the pitch output **50** relative to the motor unit and instrument holder **42** and the clamp/fire motor **52** can be controllably operated to controllably rotate the clamp/fire output **54** relative to the motor unit and instrument holder **42**.

(30) The surgical stapler base assembly **102** is configured to actuate the surgical stapler reload **200** in response to actuation of the surgical stapler base assembly **102** by the motor unit and instrument holder **42**. The base assembly **102** includes the roll input **112**, a roll drive assembly **118**, a base roll shaft **120**, the pitch input **114**, a pitch drive assembly **122**, a base pitch shaft **124**, the clamp/fire

input **116**, a clamp/fire drive assembly **126**, and a base clamp/fire shaft **128**. When the base assembly **102** is mounted to the motor unit and instrument holder **42**, the roll input **112** is drivingly coupled with the roll output **46** so that rotation of the roll output **46** generates matching rotation of the roll input **112**, the pitch input **114** is drivingly coupled with the pitch output **50** so that rotation of the pitch output **50** generates matching rotation of the pitch input **114**, and the clamp/fire input **116** is drivingly coupled with the clamp/fire output **54** so that rotation of the clamp/fire output **54** generates matching rotation of the clamp/fire input **116**. The base roll shaft **120** is drivingly coupled with the roll input **112** via the roll drive assembly **118** so that rotation of the roll input **112** generates a corresponding rotation of the base roll shaft **120** around the shaft axis **108**. The base pitch shaft **124** is drivingly coupled with the pitch input **114** via the pitch drive assembly **122** so that rotation of the pitch input **114** generates a corresponding translation of the base pitch shaft **124** along the shaft axis **108**. The base clamp/fire shaft **128** is drivingly coupled with the clamp/fire input **116** via the clamp/fire drive assembly **126** so that rotation of the clamp/fire input **116** generates a corresponding translation of the base clamp/fire shaft **128** along the shaft axis **108**.

(31) The surgical stapler reload **200** includes a reload roll shaft **210**, a reload pitch shaft **212**, a reload pitch drive assembly **214**, a reload clamp/fire shaft **216**, a reload clamp/fire drive assembly **218**, and the stapler end effector **204**. When the stapler reload **200** is mounted to the base assembly **102**, the reload roll shaft **210** is coupled to the base roll shaft **120** so that the reload roll shaft **210** rotates with the base roll shaft **120** around the shaft axis **108**, the reload pitch shaft **212** is coupled with the base pitch shaft **124** so that the reload pitch shaft **212** translates with the base pitch shaft **124** along the shaft axis **108**, and the reload clamp/fire shaft **216** is coupled with the base clamp/fire shaft **128** so that the reload clamp/fire shaft **216** translates with the base clamp/fire shaft **128** along the shaft axis **108**. The stapler end effector **204** can be pivotally mounted to the reload roll shaft **210**. The stapler end effector **204** is drivingly coupled with the reload pitch shaft **212** via the reload pitch drive assembly **214** so that translation of the reload pitch shaft **212** along the shaft axis **108** reorients the stapler end effector **204** relative to the reload roll shaft **210**. The stapler end effector **204** is also drivingly coupled with the reload clamp/fire shaft **216** via the reload clamp/fire assembly **218** so that translation of the reload clamp/fire shaft **216** along the shaft axis **108** can be used to actuate the stapler cartridge assembly **208** to clamp tissue between the stapler cartridge assembly **208** and the upper jaw **206**, to deploy staples from the stapler cartridge assembly **208**, and to cut the stapled tissue.

(32) FIG. **8** shows a side view of the surgical tool **100** with the drive assembly **104** mounted to the motor unit and instrument holder **42**. In the illustrated configuration, the motor unit and instrument holder **42** is operable to controllably rotate the roll output **46**, the pitch output **50**, and the clamp/fire output **54** to controllably actuate the surgical base assembly **102**, which thereby controllably articulates/actuate the stapler reload **200**.

(33) FIG. **9** is a side view of the surgical stapler base assembly **102** and the surgical stapler reload **200** showing the surgical stapler reload **200** separated from the surgical stapler base assembly **102**. As discussed in more detail with respect to FIG. **10**, the base assembly **102** includes a distal portion **130** configured to receive and drivingly couple with a proximal portion **220** of the stapler reload **200**.

(34) FIG. **10** is a simplified schematic side view of the distal portion **130** of the surgical stapler base assembly **102** and the proximal portion **220** of the stapler reload **200**. The distal portion **130** of the base assembly **102** includes a distal portion **132** of the base roll shaft **120**, a distal portion **134** of the base pitch shaft **124**, and a distal portion **136** of the base clamp/fire shaft **128**. The proximal portion **220** of the stapler reload **200** includes a proximal portion **222** of the reload roll shaft **210**, a proximal portion **224** of the reload pitch shaft **212**, and a proximal portion **226** of the reload clamp/fire shaft **216**. In the illustrated embodiment, the proximal portion **132** of the base roll shaft **120** includes protruding features **138** configured to be inserted into slots **228** in the reload roll shaft **210** to rotationally tie the reload roll shaft **210** to the base roll shaft **120**. In many embodiments, a

retention mechanism prevents inadvertent separation of the stapler reload **200** from the base assembly **102**. In the illustrated embodiment, the distal portion **134** of the base pitch shaft **124** includes a spring-loaded coupling feature **140** configured to be received and engage a shaped slot **230** in the proximal portion **224** of the reload pitch shaft **212** to constrain the reload pitch shaft **212** to translate with the base pitch shaft **124** along the shaft axis **108**. In a similar manner, in the illustrated embodiment the distal portion **136** of the base clamp/fire shaft **128** includes a coupling feature **142** configured to engage a coupling feature **232** of the reload clamp/fire shaft **216** to constrain the reload clamp/fire shaft **216** to translate with the base clamp/fire shaft **128** along the shaft axis **108**.

(35) FIG. **11** and FIG. **12** illustrate components of the drive assembly **100**, which is used drivingly couple the base roll shaft **120** with the roll input **112**, the base pitch shaft **124** with the pitch input **114**, and the base clamp/fire shaft **128** with the clamp/fire input **116**. The drive assembly **104** includes the chassis **110**, a roll output gear **144**, a pitch output gear **146**, a clamp/fire output gear **148**, a roll input shaft **150**, a roll input gear **152**, a roll idler gear **154**, a pitch input shaft **156**, a pitch input gear **158**, a clamp/fire input shaft **160**, and a clamp/fire input gear **162**. As described in more detail herein, the roll output gear **144**, the pitch output gear **146**, and the clamp/fire output gear **148** are coaxially mounted to rotate about the shaft axis **108**. The roll output gear **144** is rotationally tied to the base roll shaft **120** so that the base roll shaft **120** is rotated by rotating the roll output gear **144**. The base pitch shaft **124** is interfaced with the pitch output gear **146** via a screw thread so that the base pitch shaft **124** is translated along the shaft axis **108** via rotation of the pitch output gear **146**. The base clamp/fire shaft **128** is interfaced with the clamp/fire output gear **148** via a screw thread so that the base clamp/fire shaft **128** is translated along the shaft axis **108** via rotation of the clamp/fire output gear **148**. The roll input gear **152** is mounted and rotationally tied to the roll input shaft **150**, which is rotationally tied to the roll input **112**. The roll input gear **152** includes external gear teeth, which engage external gear teeth of the roll idler gear **154** to rotate the roll idler gear **154** in response to rotation of the roll input **112**. The external teeth of the roll idler gear **154** engage external gear teeth of the roll output gear **144** to rotate the roll output gear **144** in response to rotation of the roll idler gear **154**. The pitch input gear **158** is mounted and rotationally tied to the pitch input shaft **156**, which is rotationally tied to the pitch input **114**. The pitch input gear **158** includes external gear teeth, which engage external gear teeth of the pitch output gear **146** to rotate the pitch output gear **146** in response to rotation of the pitch input gear **158**. The clamp/fire input gear **162** is mounted and rotationally tied to the clamp/fire input shaft **160**, which is rotationally tied to the clamp/fire input **116**. The clamp/fire input gear **162** includes external gear teeth, which engage external gear teeth of the clamp/fire output gear **148** to rotate the clamp/fire output gear **148** in response to rotation of the clamp/fire input gear **162**.

(36) FIG. **13A** and FIG. **13B** illustrate components of the drive assembly **104** of the surgical stapler base assembly **102** for generating translation of the base clamp/fire shaft **128**. In the illustrated embodiment, the clamp/fire input **116** and the clamp/fire input shaft **160** form an integral component. In FIG. **13A**, the clamp/fire input **116**, the clamp fire input shaft **160**, the clamp/fire input gear **162**, the clamp/fire output gear **148**, and the base clamp/fire shaft **128** are shown in isolation to better illustrate how translation of the base clamp/fire shaft **128** along the shaft axis **108** is generated by rotation of the clamp/fire input **116**. Specifically, rotation of the clamp/fire input **116** relative to the chassis **110** rotates the clamp/fire input shaft **160** relative to the chassis **110**, which rotates the clamp/fire input gear **162** relative to the chassis **110**, which rotates the clamp/fire output gear **148** relative to the chassis **110**. In many embodiments, the base clamp/fire shaft **128** is constrained to rotate with the base roll shaft **120** so that rotation of the clamp/fire output gear **148** produces rotation of the clamp/fire output gear **148** relative to the base clamp/fire shaft **128** absent matching rotation of the base roll shaft **120** and the clamp/fire output gear **148**. The clamp/fire output gear **148** and the base clamp/fire shaft **128** are interfaced via a clamp/fire screw thread interface **164**. Rotation of the clamp/fire output gear **148** relative to the base clamp/fire shaft **128**

produces translation of the base clamp/fire shaft **128** along the shaft axis **108** via the clamp/fire screw thread interface **164**.

(37) FIG. **14A** and FIG. **14B** illustrate components of the drive assembly **104** of the surgical stapler base assembly **102** for generating translation of the base pitch shaft **124**. In FIG. **13A**, the pitch input **114**, the pitch input shaft **156**, the pitch input gear **158**, the pitch output gear **146**, and the base pitch shaft **124** are shown in isolation to better illustrate how translation of the base pitch shaft **124** along the shaft axis **108** is generated by rotation of the pitch input **114**. Specifically, rotation of the pitch input **114** relative to the chassis **110** rotates the pitch input shaft **156** relative to the chassis **110**, which rotates the pitch input gear **158** relative to the chassis **110**, which rotates the pitch output gear **146** relative to the chassis **110**. In many embodiments, the base pitch shaft **124** is constrained to rotate with the base roll shaft **120** so that rotation of the pitch output gear **146** produces rotation of the pitch output gear **146** relative to the base pitch shaft **124** absent matching rotation of the base roll shaft **120** and the pitch output gear **146**. The pitch output gear **146** and the base pitch shaft **124** are interfaced via a pitch screw thread interface **166**. Rotation of the pitch output gear **146** relative to the base pitch shaft **124** produces translation of the base pitch shaft **124** along the shaft axis **108** via the pitch screw thread interface **166**.

(38) FIG. **15A**, FIG. **15B**, and FIG. **16** illustrate components of the drive assembly **104** of the surgical stapler base assembly **102** for generating rotation of the base roll shaft **120**. In FIG. **15A**, the roll input **112**, the roll input shaft **150**, the roll input gear **152**, the roll idler gear **154**, the roll output gear **144**, and the base roll shaft **120** are shown in isolation to better illustrate how rotation of the base roll shaft **120** around the shaft axis **108** is generated by rotation of the roll input **112**. Specifically, rotation of the roll input **112** relative to the chassis **110** rotates the roll input shaft **150** relative to the chassis **110**, which rotates the roll input gear **152** relative to the chassis **110**, which rotates the roll idler gear **154** relative to the chassis **110**, which rotates the roll output gear **144** relative to the chassis **110**, which rotates the base roll shaft **120** relative to the chassis **110**.

(39) FIG. **17** is a cross-sectional view through the output gears **144**, **146**, **148** illustrating roller bearings used to mount the output gears **144**, **146**, **148** to the chassis **110** and constrain rotation of the output gears **144**, **146**, **148** to rotation around the shaft axis **108**. The roller bearings used to mount the output gears **144**, **146**, **148** include a shaft bearing **168**, a roll output gear bearing **170**, a pitch output gear bearing **172**, and a clamp/fire output gear bearing **174**. The shaft bearing **168** is mounted to the chassis **110** so that an outer race of the shaft bearing **168** is interfaced the chassis **110**. The roll output gear **144** is mounted to the shaft bearing **168** so that an inner race of the shaft bearing **168** is interfaced with the roll output gear **144**. The roll output gear bearing **170** is mounted inside a recess in the roll output gear **144** so that an outer race of the roll output gear bearing **170** is interfaced with the roll output gear **144**. The pitch output gear **146** is mounted to the roll output gear bearing **170** so that an inner race of the roll output gear bearing **170** is interfaced with the pitch output gear **146**. The pitch output gear bearing **172** is mounted inside a recess in the pitch output gear **146** so that an outer race of the pitch output gear bearing **172** is interfaced with the pitch output gear **146**. The clamp/fire output gear **148** is mounted to the pitch output gear bearing **172** so that an inner race of the pitch output gear bearing **172** is interfaced with the clamp/fire output gear **148**. The clamp/fire output gear bearing **174** is mounted inside a recess in the clamp/fire output gear **148** so that an outer race of the clamp/fire output gear bearing **174** is interfaced with the clamp/fire output gear **148**. Although not shown in FIG. **17**, an inner race of the clamp/fire gear bearing **174** is interfaced with an upper chassis, which is coupled with the chassis **110** and provides additional support for the output gears **144**, **146**, **148**.

(40) Other variations are within the spirit of the present invention. Thus, while the invention is susceptible to various modifications and alternative constructions, certain illustrated embodiments thereof are shown in the drawings and have been described above in detail. It should be understood, however, that there is no intention to limit the invention to the specific form or forms disclosed, but on the contrary, the intention is to cover all modifications, alternative constructions, and

equivalents falling within the spirit and scope of the invention, as defined in the appended claims. (41) The term “force” is to be construed as encompassing both force and torque (especially in the context of the following claims), unless otherwise indicated herein or clearly contradicted by context. The use of the terms “a” and “an” and “the” and similar referents in the context of describing the invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms “comprising,” “having,” “including,” and “containing” are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. The term “connected” is to be construed as partly or wholly contained within, attached to, or joined together, even if there is something intervening. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided herein, is intended merely to better illuminate embodiments of the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention.

(42) Preferred embodiments of this invention are described herein, including the best mode known to the inventors for carrying out the invention. Variations of those preferred embodiments may become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate, and the inventors intend for the invention to be practiced otherwise than as specifically described herein. Accordingly, this invention includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the invention unless otherwise indicated herein or otherwise clearly contradicted by context.

(43) All references, including publications, patent applications, and patents, cited herein are hereby incorporated by reference to the same extent as if each reference were individually and specifically indicated to be incorporated by reference and were set forth in its entirety herein.

Claims

1. A method of engaging a stapler reload assembly with a drive assembly and engaging the drive assembly with a manipulator, the method comprising: detachably mounting the drive assembly to a manipulator by: engaging a roll output of the manipulator with a roll input drivingly coupled with a roll output gear coupled to a roll shaft of the drive assembly, the roll shaft having a longitudinal axis and the output gear rotatable about the longitudinal axis of the roll shaft, engaging a pitch output of the manipulator with a pitch input drivingly coupled with a pitch output gear coupled to a pitch shaft of the drive assembly, the pitch output gear rotatable about the longitudinal axis of the roll shaft, and engaging a clamp/fire output of the manipulator with a clamp/fire input drivingly coupled with a clamp/fire output gear coupled to a clamp/fire shaft of the drive assembly, the clamp/fire output gear rotatable about the longitudinal axis of the roll shaft; and detachably mounting a stapler reload assembly to a distal end portion of a shaft assembly of the drive assembly by: coupling a roll shaft of the stapler reload assembly with the roll shaft of the drive assembly, coupling a pitch shaft of the drive assembly with a pitch shaft of the stapler reload assembly, and coupling a clamp/fire shaft of the drive assembly with a clamp/fire shaft of the stapler reload assembly.

2. The method of claim 1, wherein coupling the pitch shaft of the drive assembly with the pitch

shaft of the stapler reload assembly comprises engaging a pitch shaft coupling feature of the pitch shaft of the drive assembly with a complementary coupling feature of the pitch shaft of the stapler reload assembly.

3. The method of claim 2, wherein coupling the pitch shaft coupling feature of the pitch shaft of the drive assembly with the complementary coupling feature of pitch shaft of the stapler reload assembly comprises engaging a spring-loaded pitch shaft coupling feature of the pitch shaft of the drive assembly with a slot in the pitch shaft of the stapler reload assembly.

4. The method of claim 1, wherein coupling the pitch shaft of the drive assembly with the pitch shaft of the stapler reload assembly further comprises inserting a least a portion of the pitch shaft of the drive assembly within a recess in a portion of the pitch shaft of the stapler reload assembly.

5. The method of claim 1, wherein coupling the clamp/fire shaft of the drive assembly with the clamp/fire shaft of the stapler reload assembly comprises engaging a clamp/fire shaft coupling feature of the clamp/fire shaft of the drive assembly with a complementary coupling feature of the clamp/fire shaft of the stapler reload assembly.

6. The method of claim 1, wherein coupling the clamp/fire shaft of the drive assembly with the clamp/fire shaft of the stapler reload assembly further comprises inserting a least a portion of the clamp/fire shaft of the stapler reload assembly within a recess in a portion of the clamp/fire shaft of the drive assembly.

7. The method of claim 1, wherein detachably mounting the stapler reload assembly to the distal end portion of the shaft assembly of the drive assembly comprises aligning the longitudinal axis of the roll shaft of the shaft assembly with a longitudinal shaft axis of the stapler reload assembly.

8. The method of claim 7, wherein detachably mounting the stapler reload assembly to the distal end portion of the shaft assembly of the drive assembly comprises moving one or both of the stapler reload assembly and the shaft assembly toward one another along the longitudinal axis of the roll shaft of the shaft assembly and the longitudinal shaft axis of the stapler reload assembly.

9. The method of claim 1, wherein coupling the roll shaft of the stapler reload assembly with the roll shaft of the drive assembly comprises engaging a feature of the roll shaft of the stapler reload assembly with a complementary feature of the roll shaft of the drive assembly.

10. The method of claim 9, wherein engaging the feature of the roll shaft of the stapler reload assembly with the complementary feature of the roll shaft of the drive assembly comprises engaging a recess of the roll shaft of the stapler reload assembly with a protrusion of the roll shaft of the drive assembly.

11. The method of claim 1, wherein coupling the roll shaft of the stapler reload assembly with the roll shaft of the drive assembly rotationally fixes the roll shaft of the stapler reload assembly with the roll shaft of the drive assembly.

12. The method of claim 1, wherein coupling the pitch shaft of the drive assembly with the pitch shaft of the stapler reload assembly constrains the pitch shaft of the stapler reload assembly to move in translation with the pitch shaft of the drive assembly.

13. The method of claim 1, wherein coupling the clamp/fire shaft of the clamp/fire shaft of the drive assembly with the clamp/fire shaft of the stapler reload assembly constrains the clamp/fire shaft of the stapler reload assembly to move in translation with the clamp/fire shaft of the drive assembly.

14. The method of claim 3, wherein engaging the spring-loaded pitch shaft coupling feature of the pitch shaft of the drive assembly with a slot in the pitch shaft of the stapler reload assembly comprises moving the spring-loaded pitch shaft coupling feature distally relative to the pitch shaft of the drive assembly.
