

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403027
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Lipshaw; Moses et al.

Compression garment

Abstract

A compression garment for a limb is disclosed. The garment can include a body portion and a spine portion. Each of the body and spine portions can have a plurality of bands (e.g. bands for adjusting tension of the garment). The spine portion can be releasably attached onto the body portion such that the spine portion is positionable at different locations on the body portion to adjust a width of the garment. The bands of the body portion and/or of the spine portion can be trimmable and include a detachable fastener, whereby as a result the band can be caused to move to a plurality of different positions to adjust the garment to a plurality of different sized limbs (e.g. different sized feet).

Inventors: Lipshaw; Moses (Whitsett, NC), Richardson; Thomas (Whitsett, NC), Lynch; Karen (Whitsett, NC), Larmer; Kevin (Whitsett, NC)

Applicant: MEDI USA, L.P. (Whitsett, NC)

Family ID: 60785298

Assignee: MEDI USA, L.P. (Whitsett, NC)

Appl. No.: 17/543619

Filed: December 06, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220087848 A1	Mar. 24, 2022

Related U.S. Application Data

continuation parent-doc US 16311283 US 11395752 WO PCT/US2017/040269 20170630 child-doc US 17543619
us-provisional-application US 62356978 20160630

Publication Classification

Int. Cl.: A61F5/01 (20060101); A41B11/00 (20060101); A61F13/06 (20060101); A61F13/08 (20060101)

U.S. Cl.:

CPC A61F5/0111 (20130101); A41B11/00 (20130101); A61F13/064 (20130101); A61F13/085 (20130101); A41B2300/32 (20130101)

Field of Classification Search

CPC: A61F (5/0111); A61F (13/06); A61F (13/064); A61F (13/066); A61F (13/08); A61F (13/085); A41B (11/00); A41B (2300/32)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5897518	12/1998	Shaw	N/A	N/A
5918602	12/1998	Shaw et al.	N/A	N/A
7329232	12/2007	Lipshaw et al.	N/A	N/A
8491514	12/2012	Creighton et al.	N/A	N/A
10980675	12/2020	Lipshaw et al.	N/A	N/A
11395752	12/2021	Lipshaw	N/A	A61F 5/01
2003/0171706	12/2002	Nelson	N/A	N/A
2011/0125183	12/2010	Lipshaw et al.	N/A	N/A
2013/0283500	12/2012	Lipshaw et al.	N/A	N/A
2013/0319128	12/2012	Richardson et al.	N/A	N/A
2015/0025424	12/2014	Richardson et al.	N/A	N/A
2016/0058623	12/2015	Lipshaw et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
19638683	12/1997	DE	N/A

Primary Examiner: Nelson; Keri J

Attorney, Agent or Firm: Rimon PC

Background/Summary

FIELD (1) The present application is a Continuation application of U.S. application Ser. No. 16/311,283, filed Dec. 19, 2018, which is a United States national stage entry of International Patent Application No. PCT/US2017/040269 filed Jun. 30, 2017, which claims priority to U.S. Provisional Patent Application No. 62/356,978 filed Jun. 30, 2016. Each of these applications is incorporated by reference in its entirety.

FIELD

(1) Compression garments for the treatment of circulatory disorders such as Lymphedema.

BACKGROUND

(2) Lymphedema is swelling that occurs when excessive protein-rich lymph fluid accumulates in the interstitial tissue. This lymph fluid may contain plasma proteins, extravascular blood cells, excess water, and parenchymal products. Lymphedema is one of the most poorly understood, relatively underestimated, and least researched complications of common diseases like cancer, and thus the prevalence of lymphedema within the general population is largely unknown.

Nevertheless, for those who are diagnosed with lymphedema, the standard of care consists of meticulous skin care, manual lymphatic drainage, exercise therapy, inelastic compression bandaging and, eventually, compression garments. In regard to edema in the lower extremity, specifically the ankle-foot region, treatment can be additionally challenging due to the joint transition and increased likelihood of edema accumulation creating folds, lobules, and other abnormalities in the foot area. Individuals with edema often have limited range of motion which makes the distal ankle-foot area difficult to access for self-treatment.

(3) The frequency and duration of care is dependent on individual subject's therapeutic need and may range from 2 to 3 visits per week for 6 or more weeks depending on the severity of lymphedema and any other associated impairment.

(4) The use of compression bandaging, although proven effective in reducing edema, has its drawbacks. The application of inelastic compression bandages is time consuming and requires a skilled clinician. Furthermore, because subjects are not able to effectively bandage themselves, this treatment strategy does not promote self-care, does not provide sustained therapeutic levels of compression, and requires the subject to frequently return for follow up visits. Lastly, wearing bandages negatively impacts the subject's quality of life with regard to comfort and hygiene which can reduce compliance.

(5) Many bandage alternative wrap type garments exist on the market. These garments are primarily used after the intensive phase treatment of lymphedema to maintain the patient's limb size. Most of the wrap garments lack the ability to adapt to changes in limb size and are cost prohibitive to be used as a short term bandage replacement in the intensive phase. For those garments that are available the sizing adjustments can be complex and time consuming for practical use. The embodiments of the present disclosure address these and other related needs in the art.

SUMMARY

(6) In some embodiments, a compression garment for a limb is disclosed. The garment can include a body portion and a spine portion. Each of the body and spine portions can have a plurality of bands (e.g. bands for adjusting tension of the garment). The spine portion can be releasably attached onto the body portion such that the spine portion is positionable at different locations and angles on the body portion to adjust a width or contour of the garment. The bands of the body portion and/or of the spine portion can be trimmable and include a detachable fastener, whereby as a result the band can be caused to move to a plurality of different positions to adjust the garment to a plurality of different sized limbs (e.g. different sized feet and/or corresponding circumferences). The bands may extend at different angles from the body and/or spine portions. In certain embodiments, the limb can therefore be a foot.

(7) In some embodiments, the spine portion can include an aperture in at least one of the bands of the spine portion. At least one of the bands of the body portion can extend from a lower edge of the body portion and be caused to pass through and interlocks with the aperture. In some embodiments, passing through and interlocking the band of the body portion with the spine portion can form a heel cup or contoured surface operable to conform to and support a heel. The heel cup can also be operable to adjust a distal end of the garment to a plurality of different foot lengths and/or align an arch portion of the garment over the foot

(8) In some embodiments, the spine portion can include an inner edge that attaches onto the body portion. The inner edge can include one or more detachable fasteners. In some embodiments, the spine portion and/or the body portion can include indicia corresponding to a dimension of the limb (e.g. dimensions of the foot). For example, the dimension can correspond to a plurality of foot, arch, and/or ankle circumferences such that the spine portion can be trimmable along the indicia to conform to a specific circumference of the user. Advantageously, as the user's respective circumference can change shape during treatment, the spine portion and/or body portion can be conformed to the user's ankle without the need to replace with a separate garment or separate spine portion. In other embodiments, the dimension can correspond to a plurality of feet widths, feet circumferences, foot lengths, shoe sizes, so that the spine portion and/or body portion is trimmable along the indicia to conform to the respective dimension of the user.

(9) In some embodiments, the distal ends of one or more of the bands includes a detachable fastener tab. The one or more of the bands can be trimmable with the fastener tab being detachably positioned on the distal end.

(10) In some embodiments, the spine portion can include one or more fastener tabs.

(11) In some embodiments, the spine portion can include an inner edge that attaches onto the body portion. At least one of the bands of the spine portion can be an ankle band that extends away from an outer edge opposite the inner edge. The at least one band of the spine portion for the ankle can be longer and thinner than other of the bands of the spine portion.

(12) In some embodiments, the body portion can include a central region with an inner edge, an outer edge opposite the inner edge, an upper edge, and a lower edge. In this respect, the plurality of bands of the body portion can include at least one band extended from the outer edge and at least one band extended from the lower edge.

(13) In some embodiments, the spine portion can also include a central region with an inner edge, an outer edge opposite the inner edge, an upper edge, and a lower edge. The plurality of bands of the spine portion can include at least one band extended from the outer edge and at least one band extended from the lower edge. The plurality of bands of the spine portion can include at least one band extended between the bands that are extended from the upper and lower edges. The plurality of bands of the spine portion can include at least one band longer than the other bands and extended curved away from the outer edge substantially normal to the upper edge of the spine portion. A notch or indentation for prevention of gapping can also be disposed between the at least one band extended curved away from the outer edge and the other bands of the spine portion. The at least one band extended curved away can be configured to prevent a gap between the other bands of the body and spine portions when assembled about the limb (e.g. a foot).

(14) In some embodiments, the at least one of the body portion, spine portion, and/or corresponding bands further comprises one or more compression portions. The one or more compression portions can be inelastic. The one or more compression portions can be an upraised portion selectively positioned and operable to apply pressure to an area of the user.

(15) In some embodiments, the body portion and/or the spine portion includes a top edge, a bottom edge and a pair of opposite side edges. The body and/or spine portion can be trimmable between the edges permitting the body portion and/or spine portion to correspond to any shape of the limb.

(16) In some embodiments, the bands of the body portion and/or the spine portion are of a more elastic material and the corresponding body and/or spine portion is of an elastic or less stiff material. The stiffer material can be capable of folding and conforming to contours of the limb thereby rendering the garment less constricting. The body portion can include an inner surface and an outer surface, the outer surface being stiffer than the inner surface.

(17) In some embodiments, all of the bands are stiffer than the body and spine portions. In some embodiments, one or more of the bands of the body and/or spine portion are trimmable and comprise indicia for trimming. In some embodiments, the spine portion is angleable on the body portion at a plurality of orientations. In some embodiments, the body portion is elastic and the

spine portion is inelastic. In some embodiments, the spine portion is elastic and the body is inelastic. In some embodiments, the tension bands are substantially elastic and the body and spine portions are inelastic or include one or more inelastic portions.

(18) In some embodiments, a compression and/or tension level measuring system can be provided in the garment for indicating an actual compression level delivered to the limb by the garment, wherein the limb is a foot. The system can be configured to measure indicia the garment when the garment is donned by the foot with a card comprising a scale for measuring a separation of at least one indicia to determine an actual compression level to the foot associated with the separation. At least one end of the at least one of the bands of the body portion and the spine portion can be releasably attachable to a plurality of locations and orientations so that the at least one band is adjustable between a plurality of compression levels according to the actual compression level measured by the system.

(19) In some embodiments, the system can be disposed on the body portion and/or the spine portion and include a stretchable base layer and an upper layer attached at two spaced-apart locations on top of the stretchable base layer. A visual indicator of the actual compression level can be positioned with the upper or base layers and can be observable when the upper layer is pulled taut.

(20) In other embodiments, method of fitting a compression garment to a foot is disclosed. The method can include selectively positioning a plurality of bands on a body portion of the garment; selectively positioning a plurality of bands on a spine portion of the garment; adjusting a width of the garment by selectively attaching an edge of the spine portion onto the body portion; selectively trimming the bands and/or the spine portion; attaching a detachable fastener onto one or more of the bands; wrapping the body and spine portions around part of the foot; and wrapping each of the bands around the body and spine portions and part of the foot to apply a therapeutic compression to the foot.

(21) In other embodiments, the method can include selectively positioning an aperture in one of the bands of the spine portion, the aperture being between a proximal and a distal edge; and passing through and interlocking one of the bands of the body portion through the aperture. In some embodiments, the method can also include trimming, before the passing through and interlocking, the band of the spine portion with the aperture and/or the one of the bands of the body portion being passed through the aperture; and detachably positioning a fastener tab on a distal end of the band of the spine portion with the aperture and/or the one of the bands of the body portion being passed through the aperture. The trimming can be is along indicia corresponding to a dimension of the foot (e.g. a length of the foot).

(22) In other embodiments, the method can include trimming a sizing section of the body portion by adjusting a location of the spine portion on the body portion; trimming excess material of the body portion; and adjusting a height of the bands that are interlocking.

(23) In other embodiments, the method can include forming a heel cup by the passing through and interlocking one of the bands of the body portion through the aperture; and conforming, by the heel cup, the garment to a heel of the foot. The method can also include forming a heel cup by the passing through and interlocking one of the bands of the body portion through the aperture; adjusting, by the heel cup, a distal end of the garment to a plurality of different foot lengths; and aligning, by the heel cup, an arch portion of the garment over the foot.

(24) In other embodiments, the method can include pulling bands of the body and spine portions in opposing directions around the foot. In other embodiments, the method can include comprising: trimming the bands of the body portion and/or the spine portion to a preferred size, by measuring a dimension of the foot at one or more locations, and trimming the respective band such that the respective band corresponds to the foot at each of the one or more locations.

(25) In other embodiments, the method can include trimming the body portion and/or the spine portion to a preferred size, by: measuring a dimension of the foot at one or more locations, and

trimming the body portion and/or the spine portion such that top and bottom edges of the body portion and/or the spine portion correspond to the foot at each of the one or more locations.

(26) In other embodiments, the method can include extending at least one band of the body portion from the outer edge of the body portion and/or spine portion; and extending at least one band of the body portion from the lower edge of the body portion and/or spine portion. Each of the at least one bands can be substantially normal to the other. In some embodiments, the method can include extending another band of the spine portion between the bands extended from the upper and lower edges. In some embodiments, the method can include extending and curving upward substantially normally another band of the spine portion between the bands extended from the upper and lower edges. In some embodiments, the method can include positioning a detachable fastener on a distal end of the another band; wrapping the another band around an ankle of the foot; and detachably connecting the distal end of the another band onto the body or spine portions. In some embodiments, the method can include trimming a length of the another band, after the distal end being detachably connected on the body or spine portion; and then detachably connecting the distal end of the another band onto the body or spine portions.

(27) In some embodiments, the method can include positioning a notch or indentation between another band and the other bands of the spine portion thereby preventing formation of a gapping in the garment. In some embodiments, the method can include juxtaposing the bands of the body and spine portion between one another when wrapped around the part of the foot.

(28) In some embodiments, the method can include positioning indicia on the body portion, the spine portion, and/or one or more of the bands, the indicia corresponding to a dimension of the foot; and trimming the body portion, the spine portion, and/or one or more of the bands according to the indicia.

(29) To the accomplishment of the foregoing and related ends, certain illustrative aspects are described herein in connection with the following description and the annexed drawings. These aspects are indicative, however, of but a few of the various ways in which the principles of the claimed subject matter may be employed and the claimed subject matter is intended to include all such aspects and their equivalents. Other advantages and novel features may become apparent from the following detailed description when considered in conjunction with the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 depicts a top plan view of one exemplary embodiment of a compression garment of this disclosure in an unassembled state.
- (2) FIG. 2 depicts a top perspective view of the garment of FIG. 1 in an assembled state.
- (3) FIG. 3 depicts a side perspective view of an example garment of this disclosure during fitting and/or attachment to a patient.
- (4) FIG. 4 depicts a top plan view of one exemplary embodiment of a compression garment of this disclosure in an unassembled state.
- (5) FIG. 5 depicts an embodiment of the garment with an exemplary compression measuring system that includes indicia on an exemplary band.
- (6) FIG. 6A depicts a close up view of an example band of the garment with an exemplary multi-layer compression measuring system.
- (7) FIG. 6B depicts a close up view of plane A-A of FIG. 6A with an exemplary multi-layered compression measuring system in one of the bands prior to stretching.
- (8) FIG. 7A is a perspective view of the measurement system of FIG. 6B with a predetermined tension applied to the band.
- (9) FIG. 7B is a sectional side elevation view corresponding to FIG. 7A.

(10) FIG. 8 depicts a schematic overview of a method of assembling an example garment of this disclosure.

DETAILED DESCRIPTION

(11) Unless defined otherwise, all terms of art, notations and other scientific terms or terminology used herein have the same meaning as is commonly understood by one of ordinary skill in the art to which this disclosure belongs. In some cases, terms with commonly understood meanings are defined herein for clarity and/or for ready reference, and the inclusion of such definitions herein should not necessarily be construed to represent a substantial difference over what is generally understood in the art. All patents, applications, published applications and other publications referred to herein are incorporated by reference in their entirety. If a definition set forth in this section is contrary to or otherwise inconsistent with a definition set forth in the patents, applications, published applications and other publications that are herein incorporated by reference, the definition set forth in this section prevails over the definition that is incorporated herein by reference.

(12) As used herein, “a” or “an” means “at least one” or “one or more.”

(13) As used herein, the term “subject” is not limited to a specific species. For example, the term “subject” may refer to a patient, and frequently a human patient. However, this term is not limited to humans and thus encompasses a variety of mammalian species.

(14) As used herein, the term “elastic” as it pertains to compression garments can relate to garments and/or materials and/or portions of garments that can be stockings, wraps, or any portion thereof, both circular and flat knit, which can incorporate elastic fibers such as spandex or latex. It is this elastic fiber that enables the garment to provide compression and also to stretch in order to apply the garment to the limb. Because of the elastic nature of the garment in this respect, a consistent or static compression to the limb can be applied; when an individual changes position, such as moving from supine to standing, the limb circumference changes. This elastic nature stretches to accommodate the change in circumference and maintains a fairly consistent compression level regardless of position or movement. This is particularly beneficial when a patient experiences a reduction in limb size due to the removal of excess edema in the treated limb. However it also requires that the compression garment be removed when in a supine position because a consistent high compression level may result in pain in the limbs due to the decreased venous pressure.

(15) As used herein, the term “non-elastic” or “inelastic” can be the opposite or substantially opposite of elastic materials and/or elastic compression. Garments, or constituent materials that are non-elastic, may not stretch, or may have limited stretch when a limb circumference changes (e.g. as the result of body movement). A non-limiting example of non-elastic material can be Velcro 3610 though other material or combination of materials can be included with less or more stretch and still qualify as non-elastic as that term is used herein. Other non-limiting examples of limited stretch material can be breathoprene, neoprene, and similar laminates and/or materials that are able to be utilized in inelastic compression designs.

(16) As used herein, the term “substantially” or “substantial” is a meaningful modifier implying “approximate” rather than “perfect.” For example, the term “substantially normal” is used because it will be appreciated that a reference edge or reference line of a particular portion of the garment may not be perfectly “normal.”

(17) Compression therapy is considered the mainstay of treatment for lymphedema which relies on the application of external force in order to increase the internal pressure of the affected limb. Almost any portion of the body can suffer from swelling. Additionally, following open heart surgery, compressive support is critical for managing pain and preventing strain on the surgery site. There are several approaches to resolve these and other problems of the art.

(18) A first approach has included bandaging. This typically involves a therapist wrapping the patient's foot, and sometimes toes, in order to apply the desired level of compression. The bandages are then left in place for as long as possible. While effective, this approach requires a degree of

skill and training that is not available to everyone. As a result, individuals who are unable to treat and bandage themselves are often required to leave bandages applied by trained professionals in place for extended periods of time. This often leads to hygiene concerns and is significantly inconvenient.

(19) A second approach has included compression stockings. Compression stockings can also be used to apply therapeutic compression. They can be knit, sewn, made custom to the user's measurements, standard sized, and be composed from a variety of elastic and inelastic materials. While also effective, these stockings typically fall short when swelling reduction is needed and are primarily used for maintenance once swelling has been reduced. Due to the intended use of the products, they are tight fitting by nature which often translates into fit issues and can be challenging to don particularly for users with limited hand strength and dexterity (e.g. elderly individuals). Custom stockings made to the patient's measurements can help resolve some of the fit complications. However, even those have issues and can be prohibitively expensive.

(20) A third approach has included ankle foot wraps. This approach typically involves a wrap for applying compression to the foot and ankle and includes a body portion paired with one or more bands or straps that are used to apply compression. Ankle foot wraps provide a reasonable alternative to bandaging as they enable the user to wrap their foot more easily without training or a special skill set. However, unlike bandages, there is less flexibility with sizing. A bandage can be used to fit almost any foot regardless of shape and size, while foot wraps are more size specific (e.g. limited to sizes such as small, medium, large and only one length) and designed for the natural contours of the foot.

(21) Known foot wrap garments and stocking options also suffer from delay and reduced treatment time. For example, the patient needs to be measured prior to determining the product size, and then the patient is required to order or find a dealer location where they can purchase the product. This can take weeks which delays treatment and may waste one of the set number of therapy sessions allotted by the insurance companies.

(22) In certain embodiments a garment for a foot of the present disclosure comprises a one-size-fits-all, easy-to-use, trimmable for customized fitting, for instantly adjustable compression that resolves these and other problems of the art. Specifically, the proposed solution may be a foot wrap that resolves issues related to sizing and fit. The foot wrap may have one or more body portions that can accommodate different foot circumferences, widths, and lengths as treatment progresses and changes the shape of the foot. The herein disclosed foot wrap is operable permit the user to target specific areas along the heel and ankle region.

(23) Unlike other approaches, particularly the one shown in U.S. Pat. No. 8,376,977 by Farrow Innovations, LLC, trimming the body portion does not necessarily require indicia and effectively customizes how the wrap fits and where the interlocking bands target their compression. Trimming bands to accommodate the appropriate circumference does not require any measurements and can be done during the initial application process. In contrast to the '977 Patent, the herein disclosed solution offers the unique customization options mentioned herein. Additionally, when being used during the reduction phase of lymphedema treatment, the foot wrap can be continuously resized as foot and ankle swelling reduces.

(24) FIG. 1 depicts a top plan view of one exemplary embodiment of a compression garment **10** of this disclosure in an unassembled state, the garment being configured to wrap around a limb for compression therapy (e.g. a foot). The garment can include a body portion **20** and a spine portion **30**. Each of portions **20**, **30** can have a plurality of bands (e.g. bands **22** and/or bands **32** for adjusting tension of the garment **10**). For example, as shown, body portion **30** can have a first band **32a**, a second band **32b**, and a third band **32c**, though fewer bands **32** could be included or more than three bands **32** could be used as needed or required. The spine portion **20** can also be releasably attached onto the body portion **30** such that the spine portion **20** is positionable at different locations on the body portion **30**, for example, to adjust a dimension of the garment such

as the width. However, other dimensions of garment **10** could be adjusted by repositioning and/or reorienting spine portion **20** with respect to body portion **30**.

(25) Body portion **20** can include a central region **26** and/or one or more lateral regions. As shown, each of these regions can be formed from the same article or can be formed from separate articles or can be otherwise delineated with seams, dividers, or the like. Body portion **20** can include lateral side edges **25** that can be contoured with one or more curved edges, be a substantially straight edge, or some combination thereof. Spine portion **30** can also include a central region **36** and/or one or more lateral regions. Each of these regions can be formed from the same article or can be formed from separate articles or can be otherwise delineated with seams, dividers, or the like. Spine portion **30** can include lateral side edges **35** that can be contoured with one or more curved edges, be a substantially straight edge, or some combination thereof.

(26) Bands **22**, **32** of the body portion **20** and/or the spine portion **30** can be of a stiffer material than the corresponding regions **26**, **36** (i.e. regions **26**, **36** can be an elastic or less stiff material). The stiffer material can be capable of folding and conforming to contours of the limb thereby rendering the garment **10** less constricting when assembled on the limb. The materials of the body portion **20** and/or the spine portion **30** can also vary. For example, the body portion **20** can include an inner surface and an outer surface, the outer surface being stiffer or less flexible than the inner surface. Material properties between the body **20** and spine portions **30** can also vary. For example, the body portion **20** can be elastic or substantially elastic whereas the spine portion **20** can be inelastic or substantially inelastic.

(27) At least one of the bands **32** of the spine portion **30** can be an ankle band. For example, band **32c** can be an ankle band that is configured to extend away from an outer edge **33** opposite the inner edge **35** of the spine portion **30**. Band **32c** can be different than other bands **32** of the spine portion **30** (e.g., bands **32a** and **32b** in the depicted embodiment). For example, band **32c** can be of a different shape, be longer, thinner, or constructed with different materials and/or different elasticity profiles than bands **32a**, **32b** of the spine portion **30**. Band **32c** can also be extended and curved from edge **33** curved away from the outer edge substantially normal to the upper edge of the spine portion. As can be seen, one band **32a** can be extended from the outer edge **33** and substantially in parallel with edge **35**. Band **32a** can be oriented substantially normal to another band **32b** extended from the upper edge **31** of the spine portion **30** and away from edge **35**. Band **32c** can be extended between bands **32a**, **32b**. A notch or indentation **37** for prevention of gapping can also be disposed between band **32c** and band **32b** and/or band **32a**. However, spine portion **30** is not so limited and instead of a notch or indentation being formed on spine portion **30** itself, the bands **32a**, **32b**, **32c** could have curved or indented surfaces to prevent gapping during assembly with the limb.

(28) The body portion **20**, spine portion **30**, and/or corresponding bands **22**, **32** can also include one or more compression portions. The one or more compression portions can be inelastic. For example, if the fluctuation range of garment **10** is desirous of being adjusted, one or more compression portions of inelastic material can be positioned on the outer surface of body portion **20** and/or spine portion **30** after garment **10** has been donned by the user. In turn, an elasticity profile of the garment **10** can be adjusted from a first elasticity profile to a second elasticity profile. As a result, the range of compression fluctuation the garment **10** applies to the limb during normal wear changes. The compression portion can also be an upraised portion selectively positioned and operable to apply pressure to an area of the user.

(29) The distal end of one or more of the bands **22**, **32** can include a detachable fastener tab **24**, **34**. The respective band **22**, **32** of either portion **20**, **30** can be trimmable and the respective fastener tab **24**, **34** can be detachably positioned on the distal end. The bands **32** of the body portion **30** and/or bands **22** of the spine portion **20** can also be trimmable. For example, to adjust a respective band **22**, **32** of either portion **20**, **30**, the respective band **22**, **32** can be trimmed (e.g. length, width, or some other dimension) and then a fastener **24**, **34** can be attached to a distal end of the respective

band. The tension in respective band **22**, **32** can be adjusted by moving the distal end to a plurality of different positions to accommodate a plurality of different sized limbs and/or treatment profiles (e.g. different sized feet and/or different foot circumferences). While not depicted, the proximal end of each band **22**, **32** can also be releasably attached to respective portion **20**, **30**.

(30) The spine portion **30** can include an aperture **45** in at least one of the bands (e.g. band **32a** as shown). A corresponding band **22a** of body portion **20** in turn can extend from an edge (e.g. edge **23**) of the body portion **20**, including edge **33** and be caused to pass through the aperture **45** and interlock with corresponding band **32a**. In some embodiments, passing through and interlocking the band **32a** of the body portion **30** with the spine portion **20** can form a heel cup **48** as shown in FIG. 2 which shows a top perspective view of garment **10** in an assembled state. Cup **48** can be a contoured surface operable to conform to, receive, and/or support a heel. Cup **48** can also be operable to adjust a distal end of the garment to a plurality of different foot lengths and/or align an arch portion of garment **10** over the foot. For example, the cup **48** can be a chamber with an open upper end and curved, closed lower edge formed between interlocked bands **22a**, **32a**. Cup **48** may not necessarily be closed at the bottom but may still receive, support and otherwise conform to a heel when inserted therein.

(31) The advantage and shape of cup **48** can be seen in FIG. 3, wherein a side perspective view of garment **10** is shown during fitting and/or attachment to a foot. As shown, band **32c** can be wrapped around the ankle of the foot and be secured with fastener tab **34**. The band **32c** can be relatively long at the outset of use be capable of wrapping the ankle multiple times, or trimmed to a shorter length. In this regard, material properties of band **32c** can differ from other bands **32a**, **32b** as needed or required.

(32) Bands **22** of body portion **20** can also be adjusted relative to bands **32** of spine portion **30**. For example, band **22b** can be pulled in an opposing direction to band **32b** around the foot. The bands **22**, **32** can also be trimmed to the appropriate dimension length and then secured into its position and orientation. Advantageously, by adjusting the position of the spine portion **30** along the trimmable section of the body portion **20** (e.g. on or about edge **25** of body portion **20**), the location of the interlocking bands **22a**, **32a** can be translated or moves up or down relative to the heel of the user.

(33) Turning back to FIG. 1, inner edge **35** of spine portion **30** can attach onto the body portion **20** in a plurality of different positions and/or orientations. The inner edge **35** can include one or more detachable fasteners **34**. For example, while the embodiments of FIG. 1 show only one fastener **34** disposed on edge **35**, the embodiment of FIG. 4 shows two separate fasteners **34** with a space or gap between each fastener **34**. The spine portion **30** can be independently angleable on the body portion **20** at a plurality of orientations and positions based on edge **35** and/or any corresponding fasteners **34**.

(34) Any number of fasteners **34** with edge **35** can be used as needed or required. As also shown in FIG. 4, the spine portion **30** and/or the body portion **20** can include indicia **84** corresponding to a dimension of the limb (e.g. one or more dimensions of the foot). Indicia **84** can be on or in communication with any of bands **32**, **22**, or any other portion of either body portion **20** or spine portion **30**. Indicia **84** can be used to facilitate accurate sizing, trimming, and/or placement of garment **10** with the limb. For example, the dimension of the limb can be one of a plurality of foot circumferences, feet lengths, feet widths, feet heights, ankle or any other dimension, such that the spine portion **30** can be trimmable along the indicia **84** to conform to the respective one or more dimensions of the user. The indicia **84** can also be used for arch circumferences or circumference in the metatarsal area.

(35) Indicia **84** can be for shortening a dimension (e.g. a length) of the garment **10**, whereby the indicia **84** as shown can be the smaller numbers imprinted on body portion **20** and the spine portion **30** that can be used to correspond to a dimension of the user. As can be seen, indicia **84** may be one or more alphanumeric characters (e.g. the relatively small numbers listed) positioned on body

portion **20** and spine portion **30** by being printed, painted, glued, heat transferred, sewn onto or otherwise attached thereon. Indicia **84** could also be dots, geometric shapes, symbols, patterns, tick marks, text, or the like spaced at intervals therealong. The indicia **84** can be positioned in one or more regions **26**, **36** of the body portion **20** and/or the spine portion **30**.

(36) For example, as shown, there may be indicia **84** on or adjacent the upper edge **21** of the body portion **20**, on or adjacent the lower edge **23** of the body portion **20**, in the central region **26**, or anywhere else on the body portion **20** to be able to accurately and easily trim the body portion **20** to conform to the limb. Similarly, there may be indicia **84** on or adjacent the upper edge **31** of the spine portion **30**, on or adjacent the lower edge **33** of the spine portion **30**, in the central region **36**, or anywhere else on the spine portion **30** to be able to accurately and easily trim the spine portion **30**. In some embodiments, the body **20** and/or spine portion **30** can be trimmable between its edges so that either portion **20**, **30** can correspond to any shape of the limb. Advantageously, as the user's respective dimension changes during or as a result of treatment (e.g. the ankle circumference changes as result of the foot or ankle being reshaped through compression therapy), the spine portion **30** and/or body portion **20** and any respective bands **22**, **32** can be conformed to the user without the need to replace with a separate garment or any constituent component.

(37) Turning to FIG. 5, an exemplary compression garment **10** including band **22b** is shown with an exemplary compression measuring system. Each band **22b** as previously described may be elastic or substantially elastic along its length or longitudinal axis (e.g. the axis along which tension is to be applied). Each band **22b** may alternatively be elastic along only a part of its length. Each band **22b** may have visual indicators such as indicia **84** printed along its elastic length, or elastic axis, spaced by intervals. Each interval may have a fixed or specified length when respective band **22b** is not under tension. Each of bands **22b** may be pulled under tension around the limb (e.g. foot as depicted) at a selected location, attached to itself and/or attachable to other portions of garment **10**, using a fastener **24** and thus applying compression to that portion of the limb.

(38) As can be seen, indicia **84** may include one or more tick marks spaced along band **22b** at intervals. However, indicia **84** is not so limited and could include dots, geometric shapes, symbols, patterns, text, or the like spaced at intervals therealong for measurement with the referenced measuring device such as a calibrated scale or card upon donning of band **22b**. Each interval may be spaced at a predetermined distance from each other when the bands **32** are unstretched. In contrast, when band **22b** is under tension, the spacing between each indicia **84** may serve to accurately measure compression delivered by garment **10** to the foot at one or more multiple locations. For example, an interval between successive indicia **84** may increase when band **22b** is under tension and lengthens. The distance between successive indicia **84** may then be measured after application of garment **10** to the foot, wherein the measured distance may indicate tension in band **22b** and in turn the specific amount of compression applied by garment **10** to the foot.

(39) Systems of measuring compression levels and/or tension associated with bands **32** and garment **10** are also contemplated such as using the card **90** shown in FIG. 8. Card **90** may be used to determine tension at multiple locations of band **22b** as well as multiple locations about the limb when assembled with garment **10**. After measuring, band **22b** can optionally be removed, relocated, and/or adjusted by releasing fastener **24**, selectively positioning said fastener **24**, and re-fastening fastener **24** to the selected location, orientation, and/or desired tension. Card **90** may include reference numerals **7a-7c** disposed adjacent a plurality of edges **8a-8c** with measurement scales **9a-9c** calibrated to measure the distance between indicia **84** in the band **22b**. FIGS. 6A through 6B show certain non-limiting embodiments of a multi-layer compression measurement system **100** for use with one or more of bands (e.g. **22b**, **22a**, **32a**, **32b**, **32c**) and/or any portion of body portion **20** and/or spine portion **30**.

(40) System **100** can be installed in one or more of the bands of the garment **10** as shown in FIGS. 6A through 6B but can be incorporated in any portion of garment **10** including portions of portion **20**. FIG. 6B is a perspective view of system **100** including a stretchable base layer **121** having

indicia **84** thereon; and a stretchable upper layer **122** positioned on top of the stretchable base layer. Importantly, stretchable upper layer **122** comprises a first portion **124** and a second portion **126** joined end-to-end. Importantly as well, first portion **124** and second portion **126** can have different stiffnesses. For example, first portion **124** may be inelastic and second portion **126** may be elastic. One end of first portion **124** is attached (e.g.: sewn) to base layer **121** and one end of second portion **126** is also attached (e.g.: sewn) to base layer **121**, as illustrated. The other ends of first and second portions **124** and **126** are also attached (e.g.: sewn) together, as also illustrated. FIG. 7A is a perspective view of the measurement system **100** of FIG. 6B with a predetermined tension applied to the band **32**. FIG. 7B is a sectional side elevation view corresponding to FIG. 7A.

(41) It is to be understood that either or both of the two layers in system **100** may in turn be made of two, three or more layers or sections connected together, and therefore any references in the specification and claims to two layers refer to at least two layers, each made of one, two, three or more layers or sections connected together. Additionally, indicia **84** may be positioned on system **100** by being printed, painted, glued, heat transferred, sewn onto or otherwise attached to the upper surface of base layer **121**. In one preferred embodiment, indicia **84** comprise marking **132** and a red marking **134**. In other embodiments, the indicia may comprise a tension force scale calibrated to display different tension levels. In operation, indicia **84** can be seen by a user through window **123** in first portion **124** of top layer **122**. Other potential systems of measuring can include tension strain gauges, pressure sensors, and/or other bio-feedback sensors in one or more locations of the garment.

(42) FIG. 8 depicts a schematic overview of a method **200** of assembling an example garment of this disclosure. The method can include **205** selectively positioning a plurality of bands on a body portion of the garment; **210** selectively positioning a plurality of bands on a spine portion of the garment; **215** adjusting a width of the garment by selectively attaching an edge of the spine portion onto the body portion; **220** selectively trimming the bands and/or the spine portion; **225** attaching a detachable fastener onto one or more of the bands; **230** wrapping the body and spine portions around part of the foot; and **235** wrapping each of the bands around the body and spine portions and part of the foot to apply a therapeutic compression to the foot. Other steps can be included as described throughout this disclosure.

(43) From the perspective of the therapist or other professional facilitating donning, the herein disclosed garment advantageously allows the therapist to have one garment capable of fitting any patient without having to measure them to determine product size. This permits the therapist them to start treatment immediately, similar to bandaging. However, unlike bandaging, garments such as those embodiments herein with ankle foot wrap features simplify self-management thus allowing end-users to adjust the garment as swelling reduction is achieved. More importantly, this improves treatment results while also permitting the patient to easily remove and re-apply their garments which promotes better hygiene.

(44) Other garments and compression stocking options are limited since they delay and reduce treatment time. Specifically, the patient needs to be measured prior to determining the product size, and then the patient is required to order or find a dealer location where they can purchase the product. This can take weeks which delays treatment and may lead to increased treatment expense for patients resulting in unnecessary therapy sessions for further fitting. Additionally, if the patient has significant edema reduction, the proposed solution can simply be resized so that further reduction can be achieved, where as other options require that a smaller size garment be ordered before treatment can continue.

(45) The herein disclosed garment effectively contours the intricate shape of the human foot effectively enough to provide therapeutic compression. The herein disclosed garment overcomes those problems that have plagued the art, including trimming away an area(s) of excess material. In order for the garment to function as a form of compression therapy, the trimmed section can permit the wrap to more effectively contour the shape of the foot. The disclosed solution does just that by

enabling the user to customize one or more body portions and/or bands of the wrap in accordance with the particular foot in order to further optimize the fit and therapeutic compression.

(46) Other features and advantages of the disclosed solution will be apparent from the description herein. The examples are provided herein are solely to illustrate the invention by reference to specific embodiments. These exemplifications, while illustrating certain specific aspects of the invention, do not portray the limitations or circumscribe the scope of the disclosed invention. Many variations to those described above are possible.

Claims

1. A compression foot wrap garment for a foot, comprising: a body comprising a central region with an inner edge, an outer edge opposite the inner edge, an upper edge, and a lower edge, and a plurality of bands forming the foot wrap garment, the plurality of bands of the body comprising at least one band extended from the outer edge and at least one band extended from the lower edge, wherein at least one band of the plurality of bands is longer than the other of the plurality of bands and is extended curved away from the outer edge substantially normal to the upper edge of the body; wherein the foot wrap garment can accommodate different foot circumferences, widths, and lengths as a treatment of the foot progresses and changes the shape of the foot; wherein the bands of the body are trimmable and comprise a detachable fastener causing the band to move to a plurality of different positions to adjust the garment to a plurality of different sized feet.
2. The garment according to claim 1, wherein the body comprises an aperture in at least one of the bands, wherein at least one of the bands of the body extends from a lower edge of the body and passes through and interlocks with the aperture.
3. The garment according to claim 1, wherein the body comprises indicia corresponding to a dimension of the foot.
4. The garment according to claim 3, wherein the dimension corresponds to a plurality of feet circumferences, and wherein the body is trimmable along the indicia to conform to a circumference of the user.
5. The garment according to claim 3, wherein the dimension corresponds to a plurality of feet widths, and wherein the body is trimmable along the indicia to conform to a foot width of the user.
6. The garment according to claim 3, wherein the dimension corresponds to a plurality of arch circumferences, and wherein the body is trimmable along the indicia to conform to an arch circumference of the user.
7. The garment according to claim 1, wherein distal ends of one or more of the bands comprises a detachable fastener tab, and wherein the one or more of the bands is trimmable with the fastener tab being detachably positioned on the distal end.
8. The garment according to claim 1, wherein at least one of the bands of the body is an ankle band that extends away from an outer edge opposite the inner edge.
9. The garment according to claim 8, wherein the at least one band of the body for the ankle is longer and thinner than other of the bands of the body.
10. The garment according to claim 1, wherein a notch or indentation for prevention of gapping is disposed between the at least one band extended curved away from the outer edge and the other bands of the body.
11. The garment according to claim 1, wherein at least one of the body and/or at least one of the plurality of bands further comprises one or more compression portions.
12. The garment according to claim 11, wherein the one or more compression portions is an upraised portion selectively positioned and operable to apply pressure to an area of the user.
13. The garment according to claim 1, wherein the body comprises a top edge, a bottom edge and a pair of opposite side edges, wherein the body is trimmable between the edges permitting the body to correspond to any shape of the foot.

14. The garment according to claim 1, wherein the bands of the body are of a stiffer material and the body is of an elastic material.
 15. The garment according to claim 14, wherein the body includes an inner surface and an outer surface, the outer surface being of a different stiffness than the inner surface.
 16. The garment according to claim 1, wherein all of the bands are of a different stiffness than the body.
 17. The garment according to claim 1, wherein one or more of the bands of the body are trimmable and comprise indicia for trimming.
 18. The garment according to claim 1, wherein the bands of the body are substantially elastic and the body is inelastic or include one or more inelastic portions.
 19. The garment according to claim 1, further comprising a compression and/or tension level measuring system in the garment for indicating an actual compression level delivered to the foot by the garment.
 20. The garment according to claim 19, wherein the system is operable to measure indicia on the garment when the garment is donned by the foot with a card comprising a scale for measuring a separation of at least one indicia to determine an actual compression level to the foot associated with the separation; and wherein at least one end of the plurality of bands of the body is releasably attachable to a plurality of locations and orientations so that the plurality of bands is adjustable between a plurality of compression levels according to the actual compression level measured by the system.
 21. The garment according to claim 19, wherein the system is disposed on the body, comprising: a stretchable base layer; and an upper layer attached at two spaced-apart locations on top of the stretchable base layer; wherein a visual indicator of the actual compression level is positioned with the upper or base layers and is observable when the upper layer is pulled taut.
-