



US012403538B2

(12) **United States Patent**
Sawa et al.

(10) **Patent No.:** **US 12,403,538 B2**
(45) **Date of Patent:** **Sep. 2, 2025**

(54) **HOLE SAW**

(71) Applicant: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)

(72) Inventors: **Max R. Sawa**, Palatine, IL (US);
Geoffrey R. Piller, Grafton, WI (US);
Kenneth D. Peterson, Little Suamico, WI (US); **Travis J. DuMez**, Port Washington, WI (US); **James Ernest Pangerc**, Pewaukee, WI (US)

(73) Assignee: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/783,817**

(22) Filed: **Jul. 25, 2024**

(65) **Prior Publication Data**

US 2024/0375193 A1 Nov. 14, 2024

Related U.S. Application Data

(60) Continuation of application No. 18/606,157, filed on Mar. 15, 2024, which is a continuation of application (Continued)

(51) **Int. Cl.**
B23B 51/04 (2006.01)

(52) **U.S. Cl.**
CPC **B23B 51/0467** (2022.01); **B23B 51/0466** (2013.01); **B23B 51/0426** (2013.01); **B23B 2260/072** (2013.01); **Y10T 408/895** (2015.01)

(58) **Field of Classification Search**
CPC **B23B 51/0426**; **B23B 51/0466**; **B23B 51/0467**; **Y10T 408/895**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,505,897 A 8/1924 Kikta
2,879,036 A 3/1959 Wheeler
(Continued)

FOREIGN PATENT DOCUMENTS

CN 2865975 Y 2/2007
CN 201394679 Y 2/2010
(Continued)

OTHER PUBLICATIONS

European Patent Office Search Report for Application No. 17192777.5 dated Mar. 13, 2018, 7 pages.

(Continued)


Primary Examiner — Eric A. Gates

(74) *Attorney, Agent, or Firm* — Michael Best & Friedrich LLP

(57) **ABSTRACT**

A hole saw is movable about a rotational axis in a cutting direction to cut into a workpiece. The hole saw includes a cylindrical body with a sidewall having a first end and a second end opposite the first end, a gullet formed in the sidewall between a leading surface, a trailing surface, and a bottom surface of the sidewall, and a support aperture formed in the sidewall. The gullet extends through the first end of the body. The support aperture is entirely surrounded by the sidewall. A majority of the support aperture circumferentially overlaps with the gullet. At least a portion of the support aperture is positioned closer than the bottom surface of the sidewall to the second end. The hole saw includes a cutting tooth coupled to the first end of the sidewall adjacent the gullet and an end cap coupled to the second end of the sidewall.

11 Claims, 12 Drawing Sheets



Related U.S. Application Data

No. 18/065,305, filed on Dec. 13, 2022, which is a division of application No. 16/910,166, filed on Jun. 24, 2020, now Pat. No. 11,559,840, which is a division of application No. 15/863,253, filed on Jan. 5, 2018, now Pat. No. 10,730,119.

(60) Provisional application No. 62/443,317, filed on Jan. 6, 2017.

(56) References Cited**U.S. PATENT DOCUMENTS**

3,049,033	A	8/1962	Benjamin et al.	7,892,235	B2	2/2011	Ellis
3,080,934	A	3/1963	Berscheid	D634,343	S	3/2011	Burke, III
3,387,637	A	6/1968	Ferguson et al.	7,997,836	B2	8/2011	Kim et al.
3,905,718	A	9/1975	Luckenbill et al.	8,092,126	B2	1/2012	Tanaka
4,527,638	A	7/1985	Sanchez et al.	8,123,443	B2	2/2012	Khanger et al.
D282,369	S	1/1986	de Villiers	8,157,028	B2	4/2012	Kersten
4,728,231	A	3/1988	Kunimori et al.	8,162,945	B2	4/2012	Ellis
4,744,704	A	5/1988	Galvefors	8,172,845	B2	5/2012	Ellis
4,802,799	A	2/1989	Rachev	D664,574	S	7/2012	Burke, III
D303,118	S	8/1989	Cox	8,286,736	B2	10/2012	Weaver et al.
4,984,944	A	1/1991	Pennington, Jr. et al.	8,444,353	B2	5/2013	Khanger et al.
5,092,716	A	3/1992	Omi	D683,772	S	6/2013	Wang
5,338,135	A	8/1994	Noguchi et al.	8,475,459	B2	7/2013	Ellis
5,451,128	A	9/1995	Hattersley	D687,472	S	8/2013	Novak et al.
5,452,971	A	9/1995	Nevills	D692,470	S	10/2013	Novak et al.
5,492,187	A	2/1996	Neukirchen et al.	8,550,756	B2	10/2013	Borschert et al.
5,597,274	A	1/1997	Behner	8,573,907	B2	11/2013	Kalomeris et al.
5,599,145	A	2/1997	Reinauer et al.	8,579,554	B2	11/2013	Novak et al.
5,651,646	A	7/1997	Banke et al.	8,579,555	B2	11/2013	Novak et al.
D391,974	S	3/1998	Brutscher	D701,544	S	3/2014	Novak et al.
D392,297	S	3/1998	Brutscher	8,721,236	B2	5/2014	Kazda et al.
5,733,074	A	3/1998	Stock et al.	D706,845	S	6/2014	Richter
5,743,162	A	4/1998	Sundström	D708,650	S	7/2014	Richter
5,758,561	A	6/1998	Curtsinger et al.	D711,441	S	8/2014	Novak et al.
5,794,503	A	8/1998	Asada	9,120,162	B2	9/2015	Keightley
5,803,677	A	9/1998	Brutscher et al.	9,233,424	B2	1/2016	Grolimund et al.
5,813,802	A	9/1998	Ajimi et al.	9,248,518	B2	2/2016	Elliston et al.
5,896,800	A	4/1999	Curtsinger et al.	D765,159	S	8/2016	Novak et al.
5,904,455	A	5/1999	Krenzer et al.	D789,428	S	6/2017	Novak et al.
5,931,614	A	8/1999	Meyen et al.	9,884,373	B2	2/2018	Keightley
5,988,953	A	11/1999	Berglund et al.	10,058,931	B2	8/2018	Sussman et al.
6,007,279	A	12/1999	Malone, Jr.	D845,362	S	4/2019	Novak et al.
6,021,857	A	2/2000	Birk et al.	D871,877	S	1/2020	Terris et al.
6,065,370	A	5/2000	Curtsinger et al.	D875,798	S	2/2020	Su
D438,219	S	2/2001	Brutscher	10,730,119	B2	8/2020	Sawa et al.
6,205,902	B1	3/2001	Vuorinen	D973,733	S	12/2022	DuMez et al.
6,299,389	B1	10/2001	Barazani	11,559,840	B2	1/2023	Sawa et al.
6,551,036	B2	4/2003	Heule	2002/0050196	A1	5/2002	Fluhrer et al.
6,588,992	B2	7/2003	Rudolph	2002/0081165	A1	6/2002	Hecht
6,599,063	B1	7/2003	Capstran	2002/0137433	A1	9/2002	Lee et al.
D478,105	S	8/2003	Morton et al.	2003/0141115	A1	7/2003	Britten et al.
D478,106	S	8/2003	Morton et al.	2004/0050234	A1	3/2004	Fluhrer et al.
D478,339	S	8/2003	Morton et al.	2004/0065183	A1	4/2004	Asada
D478,919	S	8/2003	Morton et al.	2005/0188792	A1	9/2005	Asada
6,601,495	B2	8/2003	Cranna	2006/0112799	A1	6/2006	Hambleton et al.
6,623,220	B2	9/2003	Nuss et al.	2007/0160435	A1	7/2007	Chao
6,702,047	B2	3/2004	Huber	2007/0212179	A1	9/2007	Khanger et al.
6,705,807	B1	3/2004	Rudolph et al.	2008/0264231	A1	10/2008	Coe et al.
6,786,684	B1	9/2004	Ecker	2008/0267725	A1	10/2008	Mills
6,820,519	B2	11/2004	Lefebvre	2008/0298922	A1	12/2008	Oettle
6,959,775	B2	11/2005	Pedersen	2009/0000454	A1	1/2009	Baerenthaler et al.
6,981,911	B2	1/2006	Martina	2009/0044674	A1	2/2009	Neitzell
D516,594	S	3/2006	Morton	2009/0126712	A1	5/2009	Kullmann et al.
7,018,145	B2	3/2006	Mast et al.	2009/0274923	A1	11/2009	Hall et al.
7,174,823	B2	2/2007	Cranna	2009/0279972	A1	11/2009	Novak et al.
7,189,036	B1	3/2007	Watson	2010/0054885	A1	3/2010	Goetz et al.
7,241,089	B2	7/2007	Mast et al.	2010/0126326	A1	5/2010	Cloutier
7,258,180	B2	8/2007	Kersten	2011/0197736	A1	8/2011	Lizzi et al.
RE40,297	E	5/2008	Berglund et al.	2011/0217133	A1	9/2011	Ibarra et al.
7,401,667	B2	7/2008	Duscha et al.	2012/0230788	A1	9/2012	Bozic et al.
D588,175	S	3/2009	Morton	2013/0296866	A1	11/2013	Ellis
7,658,136	B2	2/2010	Rompel et al.	2014/0013916	A1	1/2014	Athad
D629,820	S	12/2010	Van Ryswyk	2014/0017023	A1	1/2014	Grollmund et al.
				2014/0023446	A1*	1/2014	Piller B23B 51/0467 408/204
				2014/0023447	A1	1/2014	Thom et al.
				2014/0255117	A1	9/2014	Tseng
				2014/0271007	A1*	9/2014	Richter B23B 51/0453 408/204
				2015/0000497	A1	1/2015	Engvall et al.
				2015/0239052	A1	8/2015	Trumble et al.
				2016/0059329	A1	3/2016	Fendeleur et al.
				2016/0166260	A1	6/2016	Ellis
				2016/0175945	A1	6/2016	Chang
				2016/0175947	A1	6/2016	Chang
				2017/0120347	A1	5/2017	Lourenco et al.
				2017/0120357	A1	5/2017	Trautner et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2018/0085833 A1 3/2018 Ward
 2018/0193926 A1 7/2018 Sawa et al.

FOREIGN PATENT DOCUMENTS

CN 201597079 U 10/2010
 CN 102689051 A 9/2012
 CN 202963637 U 6/2013
 CN 204171467 U 2/2015
 CN 204321316 U 5/2015
 CN 204565301 U 8/2015
 CN 204818283 U 12/2015
 CN 204997156 U 1/2016
 CN 205519922 U 8/2016
 DE 2422452 A1 11/1975
 DE 9417252 U1 1/1995
 DE 19623081 C1 1/1998
 DE 19810713 A1 9/1999
 DE 19910219 A1 9/1999
 DE 19913727 A1 10/1999
 DE 19939323 A1 3/2000
 DE 10042402 A1 5/2001
 DE 20101718 U1 5/2001
 DE 20113578 U1 10/2001
 DE 10253247 B3 1/2004
 DE 202004003900 U1 5/2004
 DE 102004003900 A1 8/2005
 DE 202005012328 U1 10/2005
 DE 202006010180 U1 11/2006
 DE 202006011952 U1 11/2006
 EP 0118806 A1 9/1984
 EP 0216064 A1 4/1987
 EP 0352215 A2 1/1990
 EP 0612575 A1 8/1994

EP 0715919 A1 6/1996
 EP 0729801 A1 9/1996
 EP 1024247 A1 8/2000
 EP 1078706 A2 2/2001
 EP 1080859 A1 3/2001
 EP 1431511 A1 6/2004
 EP 1852202 A1 11/2007
 EP 1944107 A2 7/2008
 EP 1944108 A2 7/2008
 EP 2502693 A1 9/2012
 EP 2987577 A1 2/2016
 FR 2302808 A1 10/1976
 FR 2421022 A1 10/1979
 GB 191517961 A 12/1915
 GB 550306 A 1/1943
 GB 2201910 A 9/1988
 JP H0966411 A 3/1973
 JP 2004268166 A 9/2004
 SU 1433650 A1 10/1988
 WO WO9706338 A1 2/1997
 WO WO2007118718 A1 10/2007
 WO WO2012159881 A2 11/2012
 WO WO2012159947 A2 11/2012
 WO WO2014180925 A1 11/2014
 WO WO2016102261 A1 6/2016
 WO WO2016102539 A1 6/2016


OTHER PUBLICATIONS

European Patent Office Search Report for Application No. 18150515.7 dated Jun. 20, 2018, 18 pages.

European Patent Office Search Report for Application No. 18150515.7 dated Sep. 18, 2018, 18 pages.

European Patent Office Extended Search Report for Application No. 20175783.8 dated Aug. 24, 2020 (16 pages).

* cited by examiner

**FIG. 1**




FIG. 2




FIG. 3





FIG. 5




FIG. 7





FIG. 6






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 15

FIG. 14




FIG. 17

FIG. 16




FIG. 19




FIG. 18

1

HOLE SAW**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of co-pending U.S. patent application Ser. No. 18/606,157, filed Mar. 15, 2024, which is a continuation of U.S. patent application Ser. No. 18/065,305, filed Dec. 13, 2022, now U.S. Pat. No. 12,233,467, which is a divisional of U.S. patent application Ser. No. 16/910,166, filed Jun. 24, 2020, now U.S. Pat. No. 11,559,840, which is a divisional of U.S. patent application Ser. No. 15/863,253, filed Jan. 5, 2018, now U.S. Pat. No. 10,730,119, which claims priority to U.S. Provisional Patent Application No. 62/443,317, filed Jan. 6, 2017, the entire contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to hole saws, and more particularly to gullets formed in the hole saws.

SUMMARY

In one aspect, a hole saw is movable about a rotational axis in a cutting direction to cut into a workpiece. The hole saw includes a cylindrical body having a sidewall with a first end and a second end opposite the first end. The cylindrical body also includes a gullet formed in the sidewall between a leading surface, a trailing surface, and a bottom surface of the sidewall. The gullet defines a central longitudinal axis extending between the first and second ends of the sidewall that is obliquely oriented relative to the rotational axis such that the gullet is angled from the first end to the bottom surface in a direction toward the cutting direction. The gullet has a dimension measured parallel to the rotational axis between the first end of the sidewall and the bottom surface of the gullet that is greater than 1.5 inches. The hole saw also includes a cutting tooth coupled to the first end of the sidewall adjacent the gullet.

In another aspect, a hole saw is movable about a rotational axis in a cutting direction to cut into a workpiece. The hole saw includes a cylindrical body having a sidewall with a first end and a second end opposite the first end. The cylindrical body also includes a gullet formed in the sidewall between a leading surface, a trailing surface, and a bottom surface of the sidewall. The gullet extends through the first end of the sidewall and defines a central longitudinal axis extending between the first and second ends of the sidewall. The central longitudinal axis is obliquely oriented relative to the rotational axis such that the gullet is angled from the first end to the bottom surface in a direction toward the cutting direction. The hole saw also includes a cutting tooth coupled to the first end of the sidewall adjacent the gullet. A dimension measured between the leading surface and a tip of the cutting tooth in a direction perpendicular to the rotational axis is between about 0.5 inches and about 0.7 inches.

In yet another aspect, a hole saw is movable about a rotational axis in a cutting direction to cut into a workpiece. The hole saw includes a cylindrical body having a sidewall with a first end and a second end opposite the first end. The cylindrical body also includes a gullet formed in the sidewall between a leading surface, a trailing surface, and a bottom surface of the sidewall. The trailing surface defines a portion having a first radius. The bottom surface has a second radius. The first radius is equal to or larger than the second radius. The gullet extends through the first end of the sidewall and

2

defines a central longitudinal axis extending between the first and second ends of the sidewall. The central longitudinal axis is obliquely oriented relative to the rotational axis such that the gullet is angled from the first end to the bottom surface in a direction toward the cutting direction. The gullet has a first dimension measured parallel to the rotational axis between the first end of the sidewall and the bottom surface of the gullet that is greater than 1.5 inches. The hole saw also includes a cutting tooth coupled to the first end of the sidewall adjacent the gullet. A second dimension measured perpendicular to the rotational axis between the leading surface and a tip of the cutting tooth is between about 0.5 inches and about 0.7 inches.

Other aspects of the invention will become apparent by consideration of the detailed description and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a hole saw according to one embodiment of the invention coupled to a power tool. FIG. 2 is an end view of the hole saw of FIG. 1.

FIG. 3 is a side view of the hole saw of FIG. 1 in a flattened state and illustrating three gullets.

FIG. 4 is a detailed view of a portion of the hole saw of FIG. 3.

FIG. 5 is a cross sectional view of the hole saw taken along line 5-5 of FIG. 2 illustrating the hole saw cutting through a workpiece.

FIG. 6 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 7 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 8 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 9 is a perspective view of a hole saw according to another embodiment of the invention.

FIG. 10 is a side view of the hole saw of FIG. 9 in a flattened state and illustrating three gullets.

FIG. 11 is a cross sectional view of the hole saw taken along line 11-11 of FIG. 9 with the hole saw cutting through two workpieces.

FIG. 12 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 13 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 14 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 15 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 16 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 17 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 18 is a planar side view of a hole saw according to another embodiment of the invention.

FIG. 19 is a planar side view of a hole saw according to another embodiment of the invention.

DETAILED DESCRIPTION

Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being

practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” or “having” and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Unless specified or limited otherwise, the terms “mounted,” “connected,” “supported,” and “coupled” and variations thereof are used broadly and encompass both direct and indirect mountings, connections, supports, and couplings. Further, “connected” and “coupled” are not restricted to physical or mechanical connections or couplings. Terms of degree, such as “about,” “substantially,” or “approximately” are understood by those of ordinary skill to refer to reasonable ranges outside of the given value, for example, general tolerances associated with manufacturing, assembly, and use of the described embodiments.

FIGS. 1-5 illustrate a hole saw **100** including a cylindrical body **105** defining a cavity **110**. The cylindrical body **105** includes a sidewall **115** having a first end **120** and a second end **125** with the second end **125** positioned opposite the first end **120**. The hole saw **100** also includes an end cap **130** coupled to the second end **125** and has an aperture **135** sized to receive an arbor **140** such that the hole saw **100** can be coupled to and driven by a tool **145** (e.g., a power drill or the like) via the arbor **140**. The tool **145** drives the hole saw **100** about a rotational axis **150** in a cutting direction **155** (FIG. 2). In the illustrated embodiment, the arbor **140** is selectively coupled to the end cap **130**, but in other embodiments, the arbor **140** can be fixedly coupled to the end cap **130**. In some embodiments, a pilot drill bit **156** (e.g., a twist drill bit, a spade drill bit, etc.) can be selectively or fixedly coupled to the arbor **140** to extend through the cavity **110** and beyond the first end **120** of the sidewall **115**. The illustrated cylindrical body **105** is made of a metallic material (e.g., low carbon steel, etc.). In other embodiments, the cylindrical body **105** can be made of a different metallic material (e.g., high carbon steel, etc.).

As best shown in FIG. 2, the sidewall **115** defines a maximum outer diameter **160**. The outer diameter **160** can be between about 1 inch and about 7 inches. In some embodiments, the outer diameter **160** can be about 1.37 inches, about 2.56 inches, about 4 inches, or about 6.25 inches. In further embodiments, the outer diameter **160** can be greater than 7 inches. The sidewall **115** also defines a maximum thickness **165**. The thickness **165** can be between about 0.07 inches and about 0.11 inches. In some embodiments, the thickness **165** can be about 0.08 inches, about 0.09 inches, about 0.1 inches, or about 0.104 inches. As best shown in FIG. 3, the sidewall **115** further defines a sidewall height or dimension **170** extending between the first end **120** and the second end **125** in a direction parallel to the rotational axis **150**. The illustrated sidewall height **170** is between about 2.5 inches and about 3 inches. In other embodiments, the sidewall height **170** can be between about 1.5 inches and about 5 inches.

In the illustrated embodiment, the sidewall **115** includes three gullets **175** equally spaced about the rotational axis **150** (e.g., each gullet **175** is spaced about 120 degrees relative to an adjacent gullet **175**). In other embodiments, the hole saw **100** can include more than three gullets **175** (e.g., four, five, six, etc.) or can include less than three gullets (e.g., two or one) with the gullets **175** equally or non-equally spaced about the rotational axis **150**. For example, the hole

saw **100** can include two gullets **175** (spaced 180 degrees apart) when the outer diameter **160** is less than about 2.25 inches.

With reference to FIG. 3, each gullet **175** defines a central longitudinal axis **180** extending between the first end **120** and the second end **125**. Each gullet **175** includes an open end **185** adjacent the first end **120** and is defined by a bottom surface **190** of the sidewall **115** opposite the open end **185**, a leading surface **195** of the sidewall **115** extending between the open end **185** and the bottom surface **190**, and a trailing surface **200** of the sidewall **115** extending between the open end **185** and the bottom surface **190**. The leading surface **195** and the trailing surface **200** of each gullet **175** are in relation to the cutting direction **155** of the hole saw **100** (i.e., the leading surface **195** is forward the trailing surface **200** as the hole saw **100** moves in the cutting direction **155**). Each trailing surface **200** includes a seat or notch **205** formed adjacent the open end **185** and a trailing surface portion **210** positioned between the notch **205** and the bottom surface **190** in a direction parallel to the rotational axis **150**. In particular, a first portion **215** of each trailing surface **200** extends between the notch **205** and the trailing surface portion **210** and a second portion **220** of each trailing surface **200** extends between the trailing surface portion **210** and the bottom surface **190**. In addition, an edge **225** is positioned between the leading surface **195** and the first end **120** that defines a substantially 90 degree edge. In other embodiments, the edge **225** can be a curved edge.

In the illustrated embodiment, all three gullets **175** include the substantially same geometry, but in other embodiments, two or more gullets **175** can include different geometries. One of the gullets **175** will be described in detail below but can be applicable to one or more of the remaining gullets **175**. The illustrated first portion **215** of the trailing surface **200** is a substantially linear surface oriented substantially parallel to the rotational axis **150**. In addition, the central longitudinal axis **180** of the gullet **175** is parallel to the rotational axis **150** so that the first portion **215** is also parallel to the central longitudinal axis **180**. In other embodiments, the first portion **215** can be a curved surface. The illustrated trailing surface portion **210** defines a first radius **230** between about 1 inch and about 1.25 inches. In other embodiments, the first radius **230** can be between about 1.25 inches and about 2 inches or the first radius **230** can be between about 0.4 inches and about 1 inch. In addition, the trailing surface portion **210** is formed in a lower half of the gullet **175** in a direction parallel to the rotational axis **150**. The illustrated second portion **220** of the trailing surface **200** is a substantially linear surface, but in other embodiments, the second portion **220** can be a curved surface. The second portion **220** is also oriented at an oblique angle **235** relative to the rotational axis **150**. The illustrated oblique angle **235** is between about 40 degrees and about 50 degrees. In other embodiments, the oblique angle **235** can be between about 50 degrees and about 70 degrees or the oblique angle **235** can be between about 20 degrees and about 40 degrees. A first angle **240** is defined between the first portion **215** and the second portion **220**. The illustrated first angle **240** is between about 130 degrees and about 140 degrees. In other embodiments, the first angle **240** can be between 140 degrees and about 170 degrees, or the first angle **240** can be between about 80 degrees and about 130 degrees. In further embodiments, the first radius **230** of the trailing surface portion **210** can be omitted such that only the first angle **240** is formed between the first portion **215** and the second portion **220**. The illustrated bottom surface **190** defines a second radius **245** between about 0.25 inches and about 0.4

5

inches. In other embodiments, the second radius **245** can be between about 0.4 inches and about 1 inch, or the second radius **245** can be between about 0.1 inches and about 0.25 inches. In some embodiments, the second radius **245** can be equal to or less than the first radius **230**. A ratio of the first radius **230** to the second radius **245** is between about 2.5 to about 5. In other embodiments, the ratio of the first radius **230** to the second radius **245** is between about 1 and about 6. In further embodiments, the ratio of the first radius **230** to the second radius **245** is between about 3 and about 4.

The illustrated leading surface **195** is a substantially linear surface oriented substantially parallel to the rotational axis **150**. A second angle **250** is defined between the second portion **220** and the leading surface **195**. The illustrated second angle **250** is between about 40 degrees and about 50 degrees. In other embodiments, the second angle **250** can be between 50 degrees and about 80 degrees or the second angle **250** can be between about 10 degrees and about 40 degrees. In further embodiments, the second radius **245** can be omitted such that only the second angle **250** is formed between the second portion **220** and the leading surface **195**.

With continued reference to FIG. 3, the gullet **175** defines a gullet height or dimension **255** extending between the first end **120** and the bottom surface **190** in a direction parallel to the rotational axis **150**. The illustrated gullet height **255** is greater than about 1.5 inches. In other embodiments, the gullet height **255** can be between about 1.7 inches and about 1.9 inches, or the gullet height **255** can be between about 1.9 inches and about 3 inches. As such, a ratio of the sidewall height **170** over the gullet height **255** is about 1.4. In other embodiments, the ratio of the sidewall height **170** over the gullet height **255** can be between about 1.1 and about 2. In further embodiments, the ratio of the sidewall height **170** over the gullet height **255** can be between about 2 and about 4. The illustrated sidewall **115** also defines a height **260** extending between the bottom surface **190** of each gullet **175** and the second end **125** of the sidewall **115**. The height **260** is between about 0.7 inches and about 0.9 inches. In other embodiments, the height **260** can be between about 0.9 inches and about 1.5 inches or the height **260** can be between about 0.1 inches and about 0.7 inches. The gullet **175** also defines a maximum gullet width **265** extending between the leading surface **195** and the trailing surface **200** in a direction perpendicular to the rotational axis **150**. In particular, the maximum gullet width **265** extends between the leading surface **195** and a point **270** located on the first portion **215** directly below the notch **205**. The illustrated maximum gullet width **265** is between about 0.75 inches and about 1.2 inches. In other embodiments, the maximum gullet width **265** can be between about 1.2 inches and about 1.5 inches, or the maximum gullet width **265** can be between about 0.4 inches and about 0.75 inches.

The hole saw **100** also includes cutting teeth **275** positioned adjacent the first end **120** of the sidewall **115**. Each cutting tooth **275** has a cutting tip **280** positioned beyond the first end **120** (i.e., above the first end **120** as illustrated in FIG. 4). In particular, the cutting teeth **275** are carbide cutting teeth that are seated within the notches **205** of the sidewall **115** and secured to the sidewall **115** (e.g., by a brazing operation or the like). The carbide cutting teeth **275** include a material hardness that is greater than a material hardness of the sidewall **115**. In other embodiments, the cutting teeth **275** can be made of a different material (e.g., hardened steel, etc.). In further embodiments, the sidewall **115** can form the cutting teeth **275** so that the cutting teeth **275** are not separately secured to the sidewall **115**. Each cutting tooth **275** includes a rake surface **285** and a relief

6

surface **290** with each rake surface **285** facing into one of the gullets **175**. Each rake surface **285** defines a positive rake angle **295** (e.g., angled toward the cutting direction **155**) relative to the rotational axis **150** between about 5 degrees and about 15 degrees. As such, a minimum gullet width **296** between each cutting tip **280** and the corresponding leading surface **195** perpendicular to the rotational axis **150** is between about 0.5 inches and about 0.7 inches. In other embodiments, the minimum gullet width **296** can be between about 0.7 inches and about 1.2 inches. In further embodiments, the minimum gullet width **296** can be greater than the maximum gullet width **265**. In yet further embodiments, the rake angle **295** can be a negative rake angle (e.g., angled away from the cutting direction **155**). A tooth angle **300** is defined between the rake surface **285** and the relief surface **290** between about 60 degrees and about 70 degrees (FIG. 4). As best shown in FIG. 2, each cutting tip **280** defines a tip width **305** between about 0.1 inches and about 0.2 inches. The tip width **305** of each cutting tooth **275** is greater than the thickness **165** of the sidewall **115**. As such, a total cutting diameter of the hole saw **100** is greater than the maximum outer diameter **160** of the sidewall **115**. In other embodiments, the tip width **305** can be substantially the same as the thickness **165** of the sidewall **115** with the cutting teeth **275** bent radially inward or outward relative to the rotational axis **150**.

With continued reference to FIG. 4, a recess or relief **310** is formed within the first end **120** of the sidewall **115** directly behind each cutting tooth **275** with a trailing portion **315** of each recess **310** angled in a direction away from the cutting direction **155**. Each recess **310** defines a recess angle **320** relative to the rake surface **285** that is less than the tooth angle **300**. As such, during a grinding process to shape the cutting teeth **275** (e.g., to shape the tooth angle **300**), the recesses **310** provide enough clearance for a grinding wheel or the like to shape the cutting teeth **275** without contacting the sidewall **115**.

Once the cutting teeth **275** are coupled to the sidewall **115**, each gullet **175** defines an area **325** between the rake surface **285**, the trailing surface **200**, the bottom surface **190**, and the leading surface **195**. In the illustrated embodiment, the area **325** of each gullet **175** is equal to or greater than 1.2 inches squared. In other embodiments, the area **325** of each gullet **175** is between about 1.2 inches squared and about 3.5 inches squared. In further embodiments, the area **325** of each gullet **175** is between about 1.2 inches squared and about 2 inches squared. As the hole saw **100** includes three gullets **175**, the total area of the illustrated gullets **175** is equal to or greater than 3.6 inches squared. Each gullet **175** also defines a volume, which is determined by multiplying the area **325** of each gullet **175** by the maximum thickness **165** of the sidewall **115**. As such, the volume of each gullet **175** is equal to or greater than 0.084 inches cubed. In some embodiments, a ratio of the tip width **305** over the volume of one of the gullets **175** is about 0.2. In other embodiments, the ratio of the tip width **305** over the volume of one of the gullets **175** can be between about 0.1 and about 1.1.

With reference to FIG. 5, the hole saw **100** is operable to cut into a workpiece **330** that defines a workpiece height **335**. In the illustrated embodiment, the workpiece height **335** is about 1.5 inches (e.g., height of a standard 2 by 4 piece of lumber). In other embodiments, the workpiece height **335** can be less than 1.5 inches. In operation, the cutting teeth **275** cut into the workpiece **330**, thereby forming workpiece chips that collect within the gullets **175**. As the hole saw **100** bores deeper into the workpiece **330**, more workpiece chips are collected within the gullets **175**.

7

Accordingly, the illustrated gullets **175** include a particular volume to accommodate the workpiece chips as the hole saw **100** cuts into the workpiece **330**. If the volume of the gullets **175** is not sufficient to accommodate the workpiece chips, the workpiece chips will build up within the gullets **175** and decrease the efficiency of the hole saw **100** cutting into the workpiece **330**. Once the hole saw **100** bores through the workpiece **330**, a cylindrical workpiece plug will be removed from the cavity **110** of the hole saw **100**. In particular, a user can grip the cylindrical workpiece plug (via their fingers) through the gullets **175** to axially slide the cylindrical workpiece plug along the rotational axis and out of the cavity **110**. The minimum gullet width **296** of each gullet **175** is sized to provide enough clearance between each cutting tip **280** and the corresponding leading surface **195** so that a user's finger avoids contact with the cutting tip **280** as the cylindrical workpiece plug is removed from the hole saw **100**.

FIG. 6 illustrates a planar view of a portion of a hole saw **400** according to another embodiment. The hole saw **400** is similar to the hole saw **100** of FIGS. 1-5; therefore, similar components are designated with similar reference numbers plus **300**. At least some differences and/or at least some similarities between the hole saws **100**, **400** will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers.

The illustrated hole saw **400** is moveable about a rotational axis **450** in a cutting direction **455** and includes a sidewall **415** having a first end **420** and a second end **425**. The sidewall **415** also includes gullets **475** (only one gullet **475** is illustrated in FIG. 6) each defining a central longitudinal axis **480**. Each gullet **475** includes a notch **505**, an open end **485**, a bottom surface **490** defining a second radius **545**, a leading surface **495**, and a trailing surface **500**. Each trailing surface **500** includes a trailing surface portion **510** defining a first radius **530**, a first portion **515**, and a second portion **520** with the trailing surface portion **510** positioned between the first portion **515** and the second portion **520**. In the illustrated embodiment, each first portion **515** is parallel to the leading surface **495**; however, in other embodiments, the first portion **515** can be obliquely angled relative to the leading surface **495**. In other embodiments, the second portion **520** can be omitted so that the trailing surface portion **510** directly connects with the bottom surface **490**. In the illustrated embodiment, the first portion **515** of each trailing surface **500** is oriented at a third angle **640** between about 5 degrees and about 15 degrees relative to the rotational axis **450** so that the first portion **515** is angled from the first end **420** to the second end **425** in a direction toward the cutting direction **455**. As a result, each central longitudinal axis **480** is also oriented between about 5 degrees and about 15 degrees relative to the rotational axis **450** so that the central longitudinal axis **480** is angled from the first end **420** to the second end **425** in a direction toward the cutting direction **455**. In other embodiments, the third angle **640** is greater than about 5 degrees. In further embodiments, the third angle **640** is less than about 15 degrees. In yet further embodiments, the third angle **640** is between about 1 degree and about 40 degrees.

The hole saw **400** also includes cutting teeth **575** (only one cutting tooth **575** is illustrated in FIG. 6) each having a cutting tip **580** and seated within one notch **505**. Each cutting tooth **575** includes a rake surface **585** and a relief surface **590**.

8

FIG. 7 illustrates a planar view of a portion of a hole saw **700** according to another embodiment. The hole saw **700** is similar to the hole saw **100** of FIGS. 1-5; therefore, similar components are designated with similar reference numbers plus **600**. At least some differences and/or at least some similarities between the hole saws **100**, **700** will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers.

The illustrated hole saw **700** is moveable about a rotational axis **750** in a cutting direction **755** and includes a sidewall **715** having a first end **720** and a second end **725**. The sidewall **715** also includes gullets **775** (only one gullet **775** is illustrated in FIG. 7) each defining a central longitudinal axis **780**. Each gullet **775** includes a notch **805**, an open end **785**, a bottom surface **790** defining a second radius **845**, a leading surface **795**, and a trailing surface **800**. Each trailing surface **800** includes a trailing surface portion **810** defining a first radius **830**, a first portion **815**, and a second portion **820** with the trailing surface portion **810** positioned between the first portion **815** and the second portion **820**. Each leading surface **795** includes a third portion **945**, a fourth portion **950**, and a support surface **955** positioned between the third portion **945** and the fourth portion **950** in a direction parallel to the rotational axis **750**. The support surface **955** is also positioned at a support surface distance **960** between about 0.7 inches and about 1 inch from the first end **720** of the sidewall **715**. In other embodiments, the support surface **955** can be formed within at least one of the gullets **775**. In the illustrated embodiment, the third portion **945** is oriented parallel to the fourth portion **950** of each leading surface **795** and the first portion **815** of each trailing surface **800**. Each third portion **945** and fourth portion **950** are also offset (e.g., nonlinear) relative to each other. In other embodiments, the third portion **945** can be obliquely angled relative to the first portion **815** and/or the fourth portion **950**. Each support surface **955** is oriented at a support angle **965** relative to the rotational axis **750**. The support angle **965** is less than 90 degrees relative to the rotational axis **750** so that the support surface **955** is angled downwardly and toward the cutting direction **755** (e.g., the support surface **955** generally faces upwardly toward the first end **720**). In other embodiments, the support angle **965** can be less than 90 degrees and greater than 75 degrees relative to the rotational axis **750**. Also, each support surface **955** is positioned above the trailing surface portion **810** in a direction parallel to the rotational axis **750**. In other embodiments, each support surface **955** can be positioned at the same height of the trailing surface portion **810** or positioned below the trailing surface portion **810**.

The hole saw **700** also includes cutting teeth **875** (only one cutting tooth **875** is illustrated in FIG. 7) each having a cutting tip **880** and seated within one notch **805**. Each cutting tooth **875** includes a rake surface **885** and a relief surface **890**.

In operation, a cylindrical workpiece plug can be removed from the hole saw **700** by using a tool (e.g., a screwdriver or the like). In particular, the tool is inserted within one of the gullets **775** below the cylindrical workpiece plug. In some embodiments, the tool engages the bottom surface **790** of the gullet **775** to leverage and push the cylindrical workpiece plug out of the first end **720**. The tool can also engage the support surface **955** to leverage and push the cylindrical workpiece plug out of the first end **720**. As the support surface **955** is angled downwardly and toward the cutting

direction **755**, the tool can be captured on the support surface **955** without sliding into the gullet **775** as the tool is used to leverage the cylindrical workpiece plug out of the hole saw **700**.

FIG. **8** illustrates a planar view of a portion of a hole saw **1000** according to another embodiment. The hole saw **1000** is similar to the hole saw **100** of FIGS. **1-5**; therefore, similar components are designated with similar references numbers plus **900**. At least some differences and/or at least some similarities between the hole saws **100**, **1000** will be discussed in detail below. In addition, components or features described with respect to only one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers.

The illustrated hole saw **1000** is moveable about a rotational axis **1050** in a cutting direction **1055** and includes a sidewall **1015** having a first end **1020** and a second end **1025**. The sidewall **1015** also includes gullets **1075** (only one gullet **1075** is illustrated in FIG. **8**) each defining a central longitudinal axis **1080**. Each gullet **1075** includes a notch **1105**, an open end **1085**, a bottom surface **1090** defining a second radius **1145**, a leading surface **1095**, and a trailing surface **1100**. Each trailing surface **1100** includes a trailing surface portion **1110** defining a first radius **1130**, a first portion **1115**, and a second portion **1120** with the trailing surface portion **1110** positioned between the first portion **1115** and the second portion **1120**. Each leading surface **1095** includes a third portion **1245**, a fourth portion **1250**, and a support surface **1255** (similar to the support surface **955** of FIG. **7**) formed on a protrusion **1270** of the sidewall **1015**, which extends into each gullet **1075**. The illustrated third portion **1245** and fourth portion **1250** are substantially collinear surfaces with the support surface **1255** oriented at a substantially 90 degree angle relative to the rotational axis **1050**.

The hole saw **1000** also includes cutting teeth **1175** (only one cutting tooth **1175** is illustrated in FIG. **8**) each having a cutting tip **1180** and seated within one notch **1105**. Each cutting tooth **1175** includes a rake surface **1185** and a relief surface **1190**.

FIGS. **9-11** illustrate a hole saw **1300** according to another embodiment. The hole saw **1300** is similar to the hole saw **100** of FIGS. **1-5**; therefore, similar components are designated with similar references numbers plus **1200**. At least some differences and/or at least some similarities between the hole saws **100**, **1300** will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers.

The illustrated hole saw **1300** is moveable about a rotational axis **1350** in a cutting direction **1355** and includes a cylindrical body **1305** having a sidewall **1315** that defines a cavity **1310** and an end cap **1330** having an aperture **1335**. The sidewall **1315** includes a first end **1320** and a second end **1325**. The sidewall **1315** defines a maximum outer diameter **1360** (FIG. **11**), a maximum thickness **1365** (FIG. **11**), and a sidewall height or dimension **1370** (FIG. **10**) extending between the first end **1320** and the second end **1325** in a direction parallel to the rotational axis **1350**. The sidewall height **1370** can be between about 3.3 inches and about 3.7 inches. In other embodiments, the sidewall height **1370** can be between about 3.7 inches and about 4.5 inches. The sidewall **1315** also includes gullets **1375** each defining a central longitudinal axis **1380** oriented at an oblique angle (e.g., between about 5 degrees and about 15 degrees) relative

to the rotational axis **1350**. Each gullet **1375** includes a notch **1405**, an open end **1385**, a bottom surface **1390** defining a second radius **1445**, a leading surface **1395**, and a trailing surface **1400**. Each trailing surface **1400** includes a trailing surface portion **1410** defining a first radius **1430**, a first portion **1415**, and a second portion **1420** with the trailing surface portion **1410** positioned between the first portion **1415** and the second portion **1420**. Each leading surface **1395** includes an edge **1425** and two support surfaces **1555a**, **1555b** (similar to the support surfaces **955**, **1255** illustrated in FIGS. **7** and **8**) so that each leading surface **1395** includes a third portion **1545**, a fourth portion **1550**, and a fifth portion **1575**. With the two support surfaces **1555a**, **1555b** formed in the leading surface **1395**, the leading surface **1395** defines a zig-zag shaped surface. The illustrated third portion **1545**, fourth portion **1550**, and fifth portion **1575** are all linear surfaces with the third portion **1545** obliquely oriented relative to the fourth portion **1550** and the fourth portion **1550** oriented substantially parallel to the fifth portion **1575**. In other embodiments, two or more of the third portion **1545**, the fourth portion **1550**, and the fifth portion **1575** can be substantially parallel relative to each other or obliquely oriented relative to each other. In further embodiments, at least one of the third portion **1545**, the fourth portion **1550**, and the fifth portion **1575** can be a curved surface. In yet further embodiments, the third portion **1545**, the fourth portion **1550**, the fifth portion **1575**, and the two support surface **1555a**, **1555b** can be omitted so that the leading surface **1395** is one linear surface. The illustrated first support surface **1555a** is positioned from the first end **1320** at a first support distance **1560a** of between about 2 inches and about 2.2 inches. The second support surface **1555b** is positioned from the first end **1320** at a second support distance **1560b** of between about 1 inch and about 1.5 inches. In other embodiments, each leading surface **1395** can include one support surface. In other embodiments, each leading surface **1395** can include more than two support surfaces.

In addition, each gullet **1375** defines an oblique angle **1435** between the second portion **1420** and the rotational axis **1350**. The oblique angle **1435** is between about 55 degrees and about 65 degrees. In particular, the oblique angle **1435** is defined between the rotational axis **1350** and a tangent line extending through a midpoint of the second portion **1420**. A first angle **1440** is defined between the first portion **1415** and the second portion **1420** that is between about 120 degrees and about 135 degrees. In particular, the first angle **1440** is defined between the first portion **1415** and a tangent line extending through a midpoint of the second portion **1420**. In other embodiments with the first portion **1415** defining a curved surface, the first angle **1440** is defined between tangent lines extending through midpoints of the first and second portions **1415**, **1420**. A second angle **1450** is defined between the second portion **1420** and the third portion **1545** that is between about 35 degrees and about 45 degrees. In particular, the second angle **1450** is defined between the third portion **1545** and a tangent line extending through a midpoint of the second portion **1420**. In other embodiments with the third portion **1545** defining a curved surface, the second angle **1450** is defined between tangent lines extending through midpoints of the second and third portions **1420**, **1545**.

As best shown in FIG. **10**, each gullet **1375** defines a gullet height or dimension **1455** extending between the first end **1320** and the bottom surface **1390** in a direction parallel to the rotational axis **1350**. The illustrated gullet height **1455** is between about 3 inches and about 3.2 inches. In other

11

embodiments, the gullet height **1455** can be between about 3.2 inches and about 4 inches, or the gullet height **1455** can be between about 2.5 inches and about 3 inches. As such, a ratio of the sidewall height **1370** over the gullet height **1455** is between about 1.05 and about 1.2. In other embodiments, the ratio can be between about 1.2 and about 2. The illustrated sidewall **1315** also defines a height **1460** extending between the bottom surface **1390** of each gullet **1375** and the second end **1325** of the sidewall **1315**. The height **1460** is between about 0.3 inches and about 0.4 inches. In other embodiments, the height **1460** can be between about 0.4 inches and about 1 inch, or the height **1460** can be between about 0.1 inches and about 0.3 inches. In addition, a maximum gullet width **1465** is defined by a point **1470** on the first portion **1415** and the fifth portion **1575** adjacent the second support surface **1555b**.

The hole saw **1300** also includes cutting teeth **1475** each having a cutting tip **1480** and seated within one notch **1405**. Each cutting tooth **1475** includes a rake surface **1485** and a relief surface **1490**. A minimum gullet width **1496** extends between each cutting tip **1480** and the corresponding leading surface **1395**. Once the cutting teeth **1475** are coupled to the sidewall **1315**, each gullet **1375** defines an area **1525** between the rake surface **1485**, the trailing surface **1400**, the bottom surface **1390**, and the leading surface **1395**. In the illustrated embodiment, the area **1525** of each gullet **1375** is equal to or greater than 3.2 inches squared. In other embodiments, the area **1525** of each gullet **1375** is between about 2 inches squared and about 4 inches squared. In further embodiments, the area **1525** of each gullet **1375** is between about 3.2 inches squared and about 4 inches squared. As the hole saw **1300** includes three gullets **1375**, the total area of the illustrated gullets **1375** is equal to or greater than 9.6 inches squared. Each gullet **1375** also defines a volume, which is determined by multiplying the area **1525** of each gullet **1375** by the maximum thickness **1365** of the sidewall **1315**. As such, the volume of each gullet **1375** is equal to or greater than 0.256 inches cubed. In other embodiments, the volume of each gullet **1375** can be between about 0.227 inches cubed and about 0.3 inches cubed.

With reference to FIG. 11, the hole saw **1300** is operable to cut into two workpieces **1530** that defines a workpiece height **1535**. In the illustrated embodiment, the workpiece height **1535** is about 3 inches (e.g., two standard 2 by 4 pieces of lumber). In other embodiments, the workpiece height **1535** can be less than 3 inches. In further embodiments, the workpiece height **1535** can be between about 1.5 inches and about 3 inches. In yet further embodiments, the two workpieces **1530** can be formed as one workpiece with the workpiece height **1535**. In operation, the cutting teeth **1475** cut into the two workpieces **1530**, thereby forming workpiece chips that collect within the gullets **1375**. As the hole saw **1300** bores deeper into the two workpieces **1530**, more workpiece chips are collected within the gullets **1375**. Accordingly, the illustrated gullets **1375** include a particular volume to accommodate the workpiece chips as the hole saw **1300** cuts into the two workpieces **1530**. Once the hole saw **1300** bores through the two workpieces **1530**, a cylindrical workpiece plug will be removed from the cavity **1310** of the hole saw **1300**. In one embodiment, a user can grip the cylindrical workpiece plug (via their fingers) through the gullets **1375** to axially slide the cylindrical workpiece plug along the rotational axis **1350** and out of the cavity **1310**. In other embodiments, a tool can be inserted into one of the gullets **1375** to be supported on one of the support surfaces **1555a**, **1555b** for a user to leverage the cylindrical workpiece plug out of the hole saw **1300**.

12

FIG. 12 illustrates a planar view of a portion of a hole saw **1600** according to another embodiment. The hole saw **1600** is similar to the hole saw **100** of FIGS. 1-5; therefore, similar components are designated with similar references numbers plus **1500**. At least some differences and/or at least some similarities between the hole saws **100**, **1600** will be discussed in detail below. In addition, components or features described with respect to only one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw **1600** can be sized to bore into the single workpiece **330** of FIG. 5 similar to the hole saw **100**, or the hole saw **1600** can be sized to bore into the two workpieces **1530** of FIG. 11 similar to the hole saw **1300**.

The illustrated hole saw **1600** is moveable about a rotational axis **1650** in a cutting direction **1655** and includes a sidewall **1615** having a first end **1620** and a second end **1625**. The sidewall **1615** also includes gullets **1675** (only one gullet **1675** is illustrated in FIG. 12) each defining a central longitudinal axis **1680**. Each gullet **1675** includes a notch **1705**, an open end **1685**, a bottom surface **1690** defining a second radius **1745**, a leading surface **1695**, and a trailing surface **1700**. Each trailing surface **1700** includes a trailing surface portion **1710** defining a first radius **1730**, a first portion **1715**, and a second portion **1720** with the trailing surface portion **1710** positioned between the first portion **1715** and the second portion **1720**. The sidewall **1615** also includes three support apertures **1880** (only one is illustrated in FIG. 12) each positioned at a substantially same location that is circumferentially between adjacent gullets **1675**. In particular, each support aperture **1880** is positioned above the bottom surfaces **1690** of the gullets **1675**. For example, each support aperture **1880** is positioned above the trailing surface portions **1710** of the gullets **1675**. Each support aperture **1880** is also positioned between adjacent gullets **1675** as to not circumferentially overlap with any portion of the gullets **1675**. Each support aperture **1880** is oblong-shaped and includes a longitudinal axis that is substantially perpendicular to the rotational axis **1650**. The support apertures **1880** function similar to the support surfaces illustrated within FIGS. 7-11 for a tool to be inserted into one of the support apertures **1880** to leverage and remove a cylindrical workpiece plug from the hole saw **1600**. In other embodiments, the sidewall **1615** can include fewer than or more than three support apertures **1880** and/or the support apertures **1880** can be located at different positions circumferentially around the sidewall **1615**.

The hole saw **1600** also includes cutting teeth **1775** (only one cutting tooth **1775** is illustrated in FIG. 12) each having a cutting tip **1780** and seated within one notch **1705**. Each cutting tooth **1775** includes a rake surface **1785** and a relief surface **1790**.

FIG. 13 illustrates a planar view of a portion of a hole saw **1900** according to another embodiment. The hole saw **1900** is similar to the hole saw **100** of FIGS. 1-5; therefore, similar components are designated with similar references numbers plus **1800**. At least some differences and/or at least some similarities between the hole saws **100**, **1900** will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw **1900** can be sized to bore into the single workpiece **330** of FIG. 5 similar to the

13

hole saw 100, or the hole saw 1900 can be sized to bore into the two workpieces 1530 of FIG. 11 similar to the hole saw 1300.

The illustrated hole saw 1900 is moveable about a rotational axis 1950 in a cutting direction 1955 and includes a sidewall 1915 having a first end 1920 and a second end 1925. The sidewall 1915 also includes gullets 1975 (only one gullet 1975 is illustrated in FIG. 13) each defining a central longitudinal axis 1980. Each gullet 1975 includes a notch 2005, an open end 1985, a bottom surface 1990 defining a second radius 2045, a leading surface 1995, and a trailing surface 2000. In particular, the second radius 2045 of each bottom surface 1990 extends directly from the trailing surface 2000 to the leading surface 1995. The sidewall 1915 also includes three support apertures 2180 (only one is illustrated in FIG. 13) each positioned below the bottom surfaces 1990. Each support aperture 2180 is also positioned as to circumferentially overlap with one of the gullets 1975.

The hole saw 1900 also includes cutting teeth 2075 (only one cutting tooth 2075 is illustrated in FIG. 13) each having a cutting tip 2080 and seated within one notch 2005. Each cutting tooth 2075 includes a rake surface 2085 and a relief surface 2090.

FIG. 14 illustrates a planar view of a portion of a hole saw 2200 according to another embodiment. The hole saw 2200 is similar to the hole saw 100 of FIGS. 1-5; therefore, similar components are designated with similar reference numbers plus 2100. At least some differences and/or at least some similarities between the hole saws 100, 2200 will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw 2200 can be sized to bore into the single workpiece 330 of FIG. 5 similar to the hole saw 100, or the hole saw 2200 can be sized to bore into the two workpieces 1530 of FIG. 11 similar to the hole saw 1300.

The illustrated hole saw 2200 is moveable about a rotational axis 2250 in a cutting direction 2255 and includes a sidewall 2215 having a first end 2220 and a second end 2225. The sidewall 2215 also includes gullets 2275 (only one gullet 2275 is illustrated in FIG. 14) each defining a central longitudinal axis 2280. Each gullet 2275 includes a notch 2305, an open end 2285, a bottom surface 2290 defining a second radius 2345, a leading surface 2295, and a trailing surface 2300. Each trailing surface 2300 includes a trailing surface portion 2310 defining a first radius 2330, a first portion 2315, and a second portion 2320 with the trailing surface portion 2310 positioned between the first portion 2315 and the second portion 2320. The first portion 2315 of each gullet 2275 defines a third angle 2440 that extends from the notch 2305 to the trailing surface portion 2310 in a direction away from the cutting direction 2255. As a result, the trailing surface portion 2310 is positioned behind the first portion 2315 relative to the cutting direction 2255. In other embodiments, the third angle 2440 can be oriented in a direction toward the cutting direction 2255 with at least a portion of the trailing surface portion 2310 positioned behind a portion of the first portion 2315 in a direction relative to the cutting direction 2255. The sidewall 2215 also includes three support apertures 2480 (only one is illustrated in FIG. 14) each positioned below a trailing surface portion 2310.

The hole saw 2200 also includes cutting teeth 2375 (only one cutting tooth 2375 is illustrated in FIG. 14) each having

14

a cutting tip 2380 and seated within one notch 2305. Each cutting tooth 2375 includes a rake surface 2385 and a relief surface 2390.

FIG. 15 illustrates a planar view of a portion of a hole saw 2500 according to another embodiment. The hole saw 2500 is similar to the hole saw 100 of FIGS. 1-5; therefore, similar components are designated with similar reference numbers plus 2400. At least some differences and/or at least some similarities between the hole saws 100, 2500 will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw 2500 can be sized to bore into the single workpiece 330 of FIG. 5 similar to the hole saw 100, or the hole saw 2500 can be sized to bore into the two workpieces 1530 of FIG. 11 similar to the hole saw 1300.

The illustrated hole saw 2500 is moveable about a rotational axis 2550 in a cutting direction 2555 and includes a sidewall 2515 having a first end 2520 and a second end 2525. The sidewall 2515 also includes gullets 2575 (only one gullet 2575 is illustrated in FIG. 15) each defining a central longitudinal axis 2580. Each gullet 2575 includes a notch 2605, an open end 2585, a bottom surface 2590 defining a second radius 2645, a leading surface 2595, and a trailing surface 2600. Each leading surface 2595 includes a support surface 2755 positioned between a third portion 2745 and a fourth portion 2750.

The hole saw 2500 also includes cutting teeth 2675 (only one cutting tooth 2675 is illustrated in FIG. 15) each having a cutting tip 2680 and seated within one notch 2605. Each cutting tooth 2675 includes a rake surface 2685 and a relief surface 2690.

FIG. 16 illustrates a planar view of a portion of a hole saw 2800 according to another embodiment. The hole saw 2800 is similar to the hole saw 100 of FIGS. 1-5; therefore, similar components are designated with similar reference numbers plus 2700. At least some differences and/or at least some similarities between the hole saws 100, 2800 will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw 2800 can be sized to bore into the single workpiece 330 of FIG. 5 similar to the hole saw 100, or the hole saw 2800 can be sized to bore into the two workpieces 1530 of FIG. 11 similar to the hole saw 1300.

The illustrated hole saw 2800 is moveable about a rotational axis 2850 in a cutting direction 2855 and includes a sidewall 2815 having a first end 2820 and a second end 2825. The sidewall 2815 also includes gullets 2875 (only one gullet 2875 is illustrated in FIG. 16) each defining a central longitudinal axis 2880. Each gullet 2875 includes a notch 2905, an open end 2885, a bottom surface 2890 defining a second radius 2945, a leading surface 2895, and a trailing surface 2900. Each trailing surface 2900 includes a trailing surface portion 2910 defining a first radius 2930, a first portion 2915, and a second portion 2920 with the trailing surface portion 2910 positioned between the first portion 2915 and the second portion 2920. The sidewall 2815 also includes three support apertures 3080 (only one is illustrated in FIG. 16). Each support aperture 3080 defines a greater area than an area of one of the gullets 2875. Each support aperture 3080 circumferentially overlaps with one of the gullets 2875 so that the leading surface 2895 of the gullet

15

2875 is positioned forward the support aperture **3080** but a portion of the support aperture **3080** is positioned behind the trailing surface **2900** of the gullet **2875** relative to the cutting direction **2855**.

The hole saw **2800** also includes cutting teeth **2975** (only one cutting tooth **2975** is illustrated in FIG. **16**) each having a cutting tip **2980** and seated within one notch **2905**. Each cutting tooth **2975** includes a rake surface **2985** and a relief surface **2990**.

FIG. **17** illustrates a planar view of a portion of a hole saw **3100** according to another embodiment. The hole saw **3100** is similar to the hole saw **100** of FIGS. **1-5**; therefore, similar components are designated with similar references numbers plus **3000**. At least some differences and/or at least some similarities between the hole saws **100**, **3100** will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw **3100** can be sized to bore into the single workpiece **330** of FIG. **5** similar to the hole saw **100** or the hole saw **3100** can be sized to bore into the two workpieces **1530** of FIG. **11** similar to the hole saw **1300**.

The illustrated hole saw **3100** is moveable about a rotational axis **3150** in a cutting direction **3155** and includes a sidewall **3115** having a first end **3120** and a second end **3125**. The sidewall **3115** also includes gullets **3175** (only one gullet **3175** is illustrated in FIG. **17**) each defining a central longitudinal axis **3180**. Each gullet **3175** includes a notch **3205**, an open end **3185**, a bottom surface **3190** defining a second radius **3245**, a leading surface **3195**, and a trailing surface **3200**. Each trailing surface **3200** includes a trailing surface portion **3210** defining a first radius **3230**, a first portion **3215**, and a second portion **3220** with the trailing surface portion **3210** positioned between the first portion **3215** and the second portion **3220**. The sidewall **3115** also includes three support apertures **3380** (only one is illustrated in FIG. **17**). Each support aperture **3380** circumferentially overlaps with one of the gullets **3175** so that a portion of the support aperture **3380** is positioned forward the leading surface **3195** but a portion of the first portion **3215** is positioned behind the support aperture **3380** relative to the cutting direction **3155**.

The hole saw **3100** also includes cutting teeth **3275** (only one cutting tooth **3275** is illustrated in FIG. **17**) each having a cutting tip **3280** and seated within one notch **3205**. Each cutting tooth **3275** includes a rake surface **3285** and a relief surface **3290**.

FIG. **18** illustrates a planar view of a portion of a hole saw **3400** according to another embodiment. The hole saw **3400** is similar to the hole saw **100** of FIGS. **1-5**; therefore, similar components are designated with similar references numbers plus **3300**. At least some differences and/or at least some similarities between the hole saws **100**, **3400** will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw **3400** can be sized to bore into the single workpiece **330** of FIG. **5** similar to the hole saw **100**, or the hole saw **3400** can be sized to bore into the two workpieces **1530** of FIG. **11** similar to the hole saw **1300**.

The illustrated hole saw **3400** is moveable about a rotational axis **3450** in a cutting direction **3455** and includes a sidewall **3415** having a first end **3420** and a second end

16

3425. The sidewall **3415** also includes three pairs of gullets **3475** (only one pair of gullets **3475** is illustrated in FIG. **18**). Each pair **3475** includes a smaller gullet **3475a** defining a central longitudinal axis **3480a** and a larger gullet **3475b** defining a central longitudinal axis **3480b**. In the illustrated embodiment, the central longitudinal axes **3480a**, **3480b** are substantially parallel; however, in other embodiments, the central longitudinal axes **3480a**, **3480b** can be obliquely angled. The smaller gullet **3475a** includes a notch **3505a**, an open end **3485a**, a bottom surface **3490a** defining a second radius **3545a**, a leading surface **3495a**, and a trailing surface **3500a**. Likewise, the larger gullet **3475b** includes a notch **3505b**, an open end **3485b**, a bottom surface **3490b** defining a second radius **3545b**, a leading surface **3495b**, and a trailing surface **3500b**. The bottom surface **3490b** of the larger gullet **3475b** is positioned closer to the second end **3425** of the sidewall **3415** than the bottom surface **3490a** of the smaller gullet **3475a**. In other embodiments, the sidewall **3415** can include fewer or more than three pairs of gullets **3475**. In the illustrated embodiment, the second radius **3545b** of the larger gullet **3475b** is greater than the second radius **3545a** of the smaller gullet **3475a**. In other embodiments, the second radius **3545b** of the larger gullet **3475b** can be equal to or less than the second radius **3545a** of the smaller gullet **3475a**.

The hole saw **3400** also includes cutting teeth **3575** (only one pair of cutting teeth **3575** are illustrated in FIG. **18**) each having a cutting tip **3580** and seated within one notch **3505a**, **3505b**. Each cutting tooth **3575** includes a rake surface **3585** and a relief surface **3590**.

FIG. **19** illustrates a planar view of a portion of a hole saw **3700** according to another embodiment. The hole saw **3700** is similar to the hole saw **100** of FIGS. **1-5**; therefore, similar components are designated with similar references numbers plus **3600**. At least some differences and/or at least some similarities between the hole saws **100**, **3700** will be discussed in detail below. In addition, components or features described with respect to one or some of the embodiments described herein are equally applicable to any other embodiments described herein and can include similar reference numbers. For example, the hole saw **3700** can be sized to bore into the single workpiece **330** of FIG. **5** similar to the hole saw **100**, or the hole saw **3700** can be sized to bore into the two workpieces **1530** of FIG. **11** similar to the hole saw **1300**.

The illustrated hole saw **3700** is moveable about a rotational axis **3750** in a cutting direction **3755** and includes a sidewall **3715** having a first end **3720** and a second end **3725**. The sidewall **3715** also includes gullets **3775** (only one gullet **3775** is illustrated in FIG. **19**) each defining a central longitudinal axis **3780** parallel to the rotational axis **3750**. Each gullet **3775** includes a notch **3805**, an open end **3785**, a bottom surface **3790** defining a second radius **3845**, a leading surface **3795**, and a trailing surface **3800**. Each trailing surface **3800** includes a trailing surface portion **3810** defining a first radius **3830**, a first portion **3815**, and a second portion **3820** with the trailing surface portion **3810** positioned between the first portion **3815** and the second portion **3820**. The sidewall **3715** also includes three support apertures **3980** (only one is illustrated in FIG. **19**). Each support aperture **3980** defines a longitudinal axis that substantially aligns with one central longitudinal axis **3780** of one gullet **3775**. In particular, each support aperture **3980** is directly below one gullet **3775**.

The hole saw **3700** also includes cutting teeth **3875** (only one cutting tooth **3875** is illustrated in FIG. **19**) each having

17

a cutting tip **3880** and seated within one notch **3805**. Each cutting tooth **3875** includes a rake surface **3885** and a relief surface **3890**.

Although the invention has been described in detail with reference to certain preferred embodiments, variations and modifications exist within the scope and spirit of one or more independent aspects of the invention as described. Various features and advantages of the invention are set forth in the following claims.

What is claimed is:

1. A hole saw movable about a rotational axis in a cutting direction to cut into a workpiece, the hole saw comprising:
a cylindrical body including

a sidewall having a first end and a second end opposite the first end,

a gullet formed in the sidewall between a first surface and a second surface having a first portion and a second portion, the second portion extending between the first surface and the first portion of the second surface, the gullet extending through the first end of the sidewall, and

a support aperture formed in the sidewall, the support aperture entirely surrounded by the sidewall and having a parallelogram shape with a first side, a second side, a third side, and a fourth side, the first side of the support aperture being parallel with the second portion of the second surface of the sidewall, the support aperture positioned closer than the second portion of the second surface of the sidewall to the second end, at least one of the first side, the second side, the third side, and the fourth side oriented oblique to the rotational axis;

a cutting tooth coupled to the first end of the sidewall adjacent the second surface of the gullet; and
an end cap coupled to the second end of the sidewall, wherein the first and second sides of the support aperture are parallel, and
wherein the third and fourth sides of the support aperture are parallel.

2. The hole saw of claim 1, wherein the first, second, third, and fourth sides of the support aperture are connected by rounded corners.

3. The hole saw of claim 1, wherein the support aperture has a rounded parallelogram shape.

4. The hole saw of claim 1, wherein the second portion of the second surface of the sidewall is linear, and wherein the first side of the support aperture is linear.

5. The hole saw of claim 4, wherein
a first arcuate surface is positioned between the first and third surfaces of the sidewall, and
a second arcuate surface is positioned between the second and third surfaces of the sidewall.

18

6. The hole saw of claim 1, wherein
the support aperture has a height measured between the first and second sides and parallel to the rotational axis, and

the height of the support aperture is greater than a shortest distance between the second portion of the second surface of the sidewall and the first side of the support aperture measured parallel to the rotational axis.

7. A hole saw movable about a rotational axis in a cutting direction to cut into a workpiece, the hole saw comprising:
a cylindrical body including

a sidewall having a first end and a second end opposite the first end,

a gullet formed in the sidewall between a first surface and a second surface having a first portion and a second portion, the second portion extending between the first surface and the first portion of the second surface, the gullet extending through the first end of the sidewall, and

a support aperture formed in the sidewall, the support aperture entirely surrounded by the sidewall and having a parallelogram shape with a first side, a second side, a third side, and a fourth side, the first side of the support aperture being parallel with the second portion of the second surface of the sidewall, the support aperture positioned closer than the second portion of the second surface of the sidewall to the second end, at least one of the first side, the second side, the third side, and the fourth side oriented oblique to the rotational axis;

a cutting tooth coupled to the first end of the sidewall adjacent the second surface of the gullet; and
an end cap coupled to the second end of the sidewall, wherein the second portion of the second surface of the sidewall is linear, and

wherein the first side of the support aperture is linear.

8. The hole saw of claim 7, wherein the first, second, third, and fourth sides of the support aperture are connected by rounded corners.

9. The hole saw of claim 7, wherein the support aperture has a rounded parallelogram shape.

10. The hole saw of claim 7, wherein
a first arcuate surface is positioned between the first and third surfaces of the sidewall, and
a second arcuate surface is positioned between the second and third surfaces of the sidewall.

11. The hole saw of claim 7, wherein
the support aperture has a height measured between the first and second sides and parallel to the rotational axis, and

the height of the support aperture is greater than a shortest distance between the second portion of the second surface of the sidewall and the first side of the support aperture measured parallel to the rotational axis.

* * * * *