

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404454
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tenore; Anthony F. et al.

System and process for converting waste plastic into fuel

Abstract

An apparatus is provided for processing reusable fuel comprising: a continuous material supply assembly; a heated airlock feeder configured to continuously receive and process the material supply received therein; a reactor configured to receive the processed material from the heated airlock feeder; and a vapor refining system configured to process vapor supplied by the reactor. The apparatus may comprise a char disposal system configured to eliminate char from the reactor. The apparatus may also comprise a thermal expansion system configured to allow thermal expansion of the reactor. A cooling system may be configured to receive processed fuel from the reactor.

Inventors: Tenore; Anthony F. (Yonkers, NY), Fowler; David (Yonkers, NY), Oluwaseun; Oluwadare (Yonkers, NY), Tenore; Anthony N. (Yonkers, NY)

Applicant: Braven Environmental, LLC (Yonkers, NY)

Family ID: 60892539

Assignee: Braven Environmental, LLC (Yonkers, NY)

Appl. No.: 18/467217

Filed: September 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240067880 A1	Feb. 29, 2024

Related U.S. Application Data

continuation parent-doc US 16907595 20200622 US 11773330 child-doc US 18467217
division parent-doc US 15641471 20170705 US 10731082 child-doc US 16907595
us-provisional-application US 62493445 20160705

Publication Classification

Int. Cl.: **C10B47/44** (20060101); **B01D53/00** (20060101); **B30B9/12** (20060101); **C10B31/08** (20060101); **C10B53/07** (20060101); **C10G1/02** (20060101); **C10G1/10** (20060101); **C10K1/02** (20060101); **C10K1/04** (20060101)

U.S. Cl.:

CPC **C10B47/44** (20130101); **B01D53/002** (20130101); **B30B9/121** (20130101); **C10B31/08** (20130101); **C10B53/07** (20130101); **C10G1/02** (20130101); **C10G1/10** (20130101); **C10K1/026** (20130101); **C10K1/04** (20130101); **B01D2257/702** (20130101); **C10G2300/1003** (20130101); **C10G2400/02** (20130101); **C10G2400/04** (20130101); **Y02P20/133** (20151101); **Y02P20/143** (20151101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
836701	12/1905	Frederick	N/A	N/A
2351422	12/1943	Gohr	N/A	N/A
2458068	12/1948	Fuller	N/A	N/A
2546846	12/1950	Atkin	N/A	N/A
2616519	12/1951	Crankshaw	N/A	N/A
2916121	12/1958	Lips	N/A	N/A
3129459	12/1963	Kullgren	N/A	N/A
3151784	12/1963	Tailor	N/A	N/A
3183553	12/1964	Slater	N/A	N/A
3455789	12/1968	Landers	N/A	N/A
3458321	12/1968	Reinhart	N/A	N/A
3797702	12/1973	Robertson	N/A	N/A
3822866	12/1973	Daester	N/A	N/A
3907259	12/1974	Leclercq	N/A	N/A
3947256	12/1975	Tsukagoshi	N/A	N/A
3962043	12/1975	Schmalfeld	N/A	N/A
3981454	12/1975	Williams	N/A	N/A
4025058	12/1976	Mizuguchi	N/A	N/A
4123332	12/1977	Rotter	N/A	N/A
4261225	12/1980	Zahradnik	N/A	N/A
4426018	12/1983	Ward	N/A	N/A
4437046	12/1983	Faillace	N/A	N/A
4437048	12/1983	Arnold	N/A	N/A
4473478	12/1983	Chivrrall	N/A	N/A
4500481	12/1984	Marx, III	N/A	N/A
4529579	12/1984	Raahauge	N/A	N/A
4640203	12/1986	Wolter	N/A	N/A

4842126	12/1988	McConnell	N/A	N/A
4875847	12/1988	Wenger	N/A	N/A
5032143	12/1990	Ritakallio	N/A	N/A
5078857	12/1991	Melton	N/A	N/A
5129995	12/1991	Agarwal	N/A	N/A
5174479	12/1991	Dufour	N/A	N/A
5205225	12/1992	Milsap, III	N/A	N/A
5394937	12/1994	Nieh	N/A	N/A
5611268	12/1996	Hamilton	N/A	N/A
5720232	12/1997	Meador	N/A	N/A
5732829	12/1997	Smith	N/A	N/A
5756871	12/1997	Wang	N/A	N/A
5762668	12/1997	Lee	N/A	N/A
5993751	12/1998	Moriarty	N/A	N/A
6063355	12/1999	Fujimura	N/A	N/A
6109902	12/1999	Goris	N/A	N/A
6126907	12/1999	Wada	N/A	N/A
6221329	12/2000	Faulkner	N/A	N/A
6270630	12/2000	Xing	N/A	N/A
6276286	12/2000	Williams	N/A	N/A
6298751	12/2000	Ide	N/A	N/A
6387221	12/2001	Schoenhard	N/A	N/A
6455789	12/2001	Allison	N/A	N/A
6534689	12/2002	Stankevitch	N/A	N/A
6634508	12/2002	Ishigaki	N/A	N/A
6758150	12/2003	Ballantine	N/A	N/A
7144558	12/2005	Smith	N/A	N/A
7301060	12/2006	Appel	N/A	N/A
7311509	12/2006	Lupke	N/A	N/A
7476298	12/2008	Stout	N/A	N/A
7692050	12/2009	Adams	N/A	N/A
7771699	12/2009	Adams	N/A	N/A
7906695	12/2010	Giercke	N/A	N/A
8003833	12/2010	Appel	N/A	N/A
8200238	12/2011	Gildea	N/A	N/A
8215477	12/2011	Basaglia	N/A	N/A
8304590	12/2011	Hopkins	N/A	N/A
8344195	12/2012	Srinakruang	N/A	N/A
8372248	12/2012	Sherry	N/A	N/A
8518218	12/2012	Ali	N/A	N/A
8548501	12/2012	Gildea	N/A	N/A
8574325	12/2012	Jensen	N/A	N/A
8609606	12/2012	Wakamiya	N/A	N/A
8677992	12/2013	Peter	N/A	N/A
8696994	12/2013	Miller	N/A	N/A
8801904	12/2013	Miller	N/A	N/A
9045693	12/2014	Wolfe	N/A	N/A
9052109	12/2014	Fowler	N/A	F23G 5/0276
9220798	12/2014	McKee	N/A	N/A
9275655	12/2015	Wilson	N/A	N/A

9624439	12/2016	Bakaya	N/A	N/A
9630345	12/2016	Alsewailem	N/A	N/A
9795940	12/2016	Miller	N/A	N/A
9863597	12/2017	Park	N/A	N/A
10233393	12/2018	Oluwaseun	N/A	N/A
10731082	12/2019	Tenore	N/A	N/A
2002/0048523	12/2001	Achtelik	N/A	N/A
2003/0047437	12/2002	Stankevitch	N/A	N/A
2003/0098227	12/2002	Okamoto	N/A	N/A
2003/0105141	12/2002	Gao	N/A	N/A
2003/0127310	12/2002	Lemmons	N/A	N/A
2003/0130548	12/2002	Lemmons	N/A	N/A
2004/0003481	12/2003	Tarrant	N/A	N/A
2004/0144698	12/2003	Hilpert	N/A	N/A
2005/0219943	12/2004	Yamane	N/A	N/A
2006/0021189	12/2005	Johnson	N/A	N/A
2006/0211899	12/2005	Lee	N/A	N/A
2007/0094929	12/2006	Kang	N/A	N/A
2007/0178326	12/2006	Hong	N/A	N/A
2007/0179326	12/2006	Baker	N/A	N/A
2007/0193408	12/2006	Martinez	N/A	N/A
2008/0038071	12/2007	Bodie	N/A	N/A
2008/0105141	12/2007	Duperon	N/A	N/A
2008/0128259	12/2007	Kostek	N/A	N/A
2008/0129259	12/2007	Endo	N/A	N/A
2008/0202983	12/2007	Smith	N/A	N/A
2008/0286557	12/2007	Tucker	N/A	N/A
2010/0008836	12/2009	Pecci	422/229	C10B 7/10
2010/0024696	12/2009	Cauley	N/A	N/A
2010/0200229	12/2009	Jefferd	N/A	N/A
2010/0202243	12/2009	Stirner	N/A	N/A
2010/0289175	12/2009	Feichtinger	N/A	N/A
2010/0289270	12/2009	Behrens	201/1	C10B 53/00
2010/0329938	12/2009	Allan	N/A	N/A
2011/0020190	12/2010	Miller	N/A	N/A
2011/0089081	12/2010	Srinakruang	N/A	N/A
2011/0290057	12/2010	Corcoran	N/A	N/A
2012/0024106	12/2011	Brotzki	N/A	N/A
2012/0024687	12/2011	Bratina	N/A	N/A
2012/0261247	12/2011	McNamara	N/A	N/A
2012/0289753	12/2011	Luengo Marin	N/A	N/A
2013/0299333	12/2012	Tucker	202/113	C10B 47/44
2014/0054815	12/2013	Houk	N/A	N/A
2014/0121426	12/2013	Tandon	N/A	N/A
2014/0262728	12/2013	Karanikas	N/A	N/A
2014/0332363	12/2013	McGolden	N/A	N/A
2014/0332444	12/2013	Weiss	N/A	N/A
2014/0339726	12/2013	Guyen	N/A	N/A
2015/0017048	12/2014	Blanchard	418/192	B30B 9/18
2015/0023826	12/2014	Desiron	N/A	N/A

2015/0053542	12/2014	Liang	201/7	C10B 49/16
2015/0064297	12/2014	Yang	N/A	N/A
2015/0073181	12/2014	Gorke	N/A	N/A
2015/0080624	12/2014	Gephart	422/200	C10G 19/00
2015/0166911	12/2014	Reed	N/A	N/A
2015/0259603	12/2014	Hallowell	N/A	N/A
2015/0314513	12/2014	Takamoto	N/A	N/A
2015/0362183	12/2014	Bertram	N/A	N/A
2015/0368563	12/2014	Funk	N/A	N/A
2016/0068771	12/2015	Appel	N/A	N/A
2017/0036378	12/2016	Yanev	N/A	N/A
2017/0218278	12/2016	Bakaya	N/A	N/A
2017/0283707	12/2016	Gephart	N/A	N/A
2017/0361329	12/2016	Behrens	N/A	N/A
2017/0361558	12/2016	Tenore	N/A	N/A
2018/0056262	12/2017	Miller	N/A	N/A
2018/0142174	12/2017	Grainger	N/A	C10J 3/60

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2660678	12/2007	CA	N/A
2668886	12/2007	CA	N/A
703609	12/2011	CH	N/A
199800382	12/1997	CL	N/A
201803679	12/2017	CL	N/A
1968765	12/2006	CN	N/A
101616970	12/2008	CN	N/A
101700692	12/2009	CN	N/A
201581050	12/2009	CN	N/A
103153450	12/2012	CN	N/A
202988144	12/2012	CN	N/A
104211629	12/2013	CN	N/A
204699419	12/2014	CN	N/A
204737927	12/2014	CN	N/A
105542830	12/2015	CN	N/A
1769235	12/1970	DE	N/A
19724146	12/1997	DE	N/A
10201869	12/2002	DE	N/A
10201869	12/2004	DE	N/A
202013007632	12/2012	DE	N/A
202013009015	12/2013	DE	N/A
2440633	12/2011	EP	N/A
739854	12/1954	GB	N/A
766003	12/1956	GB	N/A
1174133	12/1968	GB	N/A
S6060681	12/1984	JP	N/A
S6063543	12/1984	JP	N/A
60179407	12/1984	JP	N/A
S6117879	12/1985	JP	N/A
S62187791	12/1986	JP	N/A

02229588	12/1987	JP	N/A
H07505824	12/1994	JP	N/A
07256645	12/1994	JP	N/A
1995256645	12/1994	JP	N/A
8216148	12/1995	JP	N/A
H08334221	12/1995	JP	N/A
9104874	12/1996	JP	N/A
2000001677	12/1999	JP	N/A
2000017272	12/1999	JP	N/A
2001296009	12/2000	JP	N/A
2002037916	12/2001	JP	N/A
3334221	12/2001	JP	N/A
200310825	12/2002	JP	N/A
2005280254	12/2004	JP	N/A
200689742	12/2005	JP	N/A
2007529574	12/2006	JP	N/A
2007332222	12/2006	JP	N/A
2008155582	12/2007	JP	N/A
2009007537	12/2008	JP	N/A
2009096966	12/2008	JP	N/A
2009220433	12/2008	JP	N/A
2010500170	12/2009	JP	N/A
2010184297	12/2009	JP	N/A
6063543	12/2016	JP	N/A
6117879	12/2016	JP	N/A
20030051913	12/2002	KR	N/A
20030051913	12/2002	KR	N/A
20050013304	12/2004	KR	N/A
20060012934	12/2005	KR	N/A
100686370	12/2006	KR	N/A
20090117377	12/2008	KR	N/A
101006224	12/2010	KR	N/A
20120103832	12/2011	KR	N/A
101289867	12/2012	KR	N/A
20140110906	12/2013	KR	N/A
509433	12/1975	SU	N/A
9011475	12/1989	WO	N/A
0105910	12/2000	WO	N/A
2008017953	12/2007	WO	N/A
2009129233	12/2008	WO	N/A
2011132210	12/2010	WO	N/A
2014200123	12/2013	WO	N/A
2017116733	12/2016	WO	N/A
2017221181	12/2016	WO	N/A

OTHER PUBLICATIONS

CN201581050U_Eng (Espacenet machine translation of Liu) (Year: 2010). cited by examiner
CH703609A2_Eng (Espacenet machine translation of Kosior) (Year: 2012) 57 pages. cited by
applicant

CN202988144U_Eng (Patentscope machine translation of Zhu) (Year: 2013). 5 pages. cited by

applicant
DE10201869A1 | Eng (Espacenet machine translation of Bayer) (Year: 2003) 5 pages. cited by applicant
DE202013007632U1_Eng (Espacenet machine translation of Wichelmann (Year: 2013). 5 pages. cited by applicant
Examination Report (including English translation) issued in App. No. SA519400796, dated Dec. 22, 2021, 10 pages. cited by applicant
Examination Report received in Australian Application No. 2017283225 mailed May 31, 2021, 2 pages. cited by applicant
Examination Report received in Indian Patent Application No. 201827046572 mailed Dec. 2, 2020, 8 pages. cited by applicant
Examination Report received in Indian Patent Application No. 201927001910 mailed Nov. 13, 2020, 7 pages. cited by applicant
Examination Report received in Indian Patent Application No. 201927004072 mailed Nov. 24, 2020, 5 pages. cited by applicant
Examination Report received in Indian Patent Application No. 201927004293 mailed Oct. 20, 2020, 6 pages. cited by applicant
Examination Report received in New Zealand Application No. 749216 dated Feb. 27, 2020, 2 pages. cited by applicant
Examination Report received in New Zealand Application No. 749263 mailed Mar. 18, 2021, 3 pages. cited by applicant
Expert Report received in Chilean Application No. 201803174 mailed Dec. 31, 2019, 16 pages. cited by applicant
Extended European Search Report received in Application No. 17795725.5 mailed Nov. 26, 2019, 5 pages. cited by applicant
Extended European Search Report received in Application No. 17823741.8 mailed Nov. 15, 2019, 8 pages. cited by applicant
Extended European Search Report received in European Application No. 17814858.1 mailed Jan. 8, 2020, 35 pages. cited by applicant
Extended European Search Report received in European Application No. 17814859.9 dated Jan. 30, 2020, 18 pages. cited by applicant
Extended European Search Report received in European Application No. 17823725.1 dated Feb. 27, 2020, 13 pages. cited by applicant
Israeli Office Action (with English translation) for App. No. IL264100, dated Oct. 10, 2021, 10 pages. cited by applicant
KR101289867B1_Eng (Espacenet machine translation of Lim) (Year: 2013) 9 pages. cited by applicant
KR1020030051913B1_Eng (Espacenet machine translation of Ku Jae-Wan) (Year: 2007) 24 pages. cited by applicant
Non-Final Office Action in corresponding U.S. Appl. No. 15/054,903 dated Oct. 3, 2018. 19 pages. cited by applicant
Non-Final Office Action in corresponding U.S. Appl. No. 15/593,579 dated Oct. 3, 2018. cited by applicant
Non-Final Office Action in corresponding U.S. Appl. No. 15/641,471 dated Oct. 25, 2018. 37 pages. cited by applicant
Non-Final Office Action in corresponding U.S. Appl. No. 15/477,312 mailed Sep. 17, 2018, 6 pages. cited by applicant
Notification received in ARIPO Application No. AP/P/2018/011139 issued Aug. 12, 2020. 4 pages. cited by applicant
Office Action (Final Rejection) dated Oct. 11, 2022 for U.S. Appl. No. 16/907,595 (pp. 1-15). cited

by applicant
Office Action (Non-Final Rejection) dated Feb. 8, 2022 for U.S. Appl. No. 16/907,595 (pp. 1-22).
cited by applicant
Office Action (Notice of Allowance and Fees Due (PTOL-85)) dated Apr. 26, 2023 for U.S. Appl.
No. 16/907,595 (pp. 1-10). cited by applicant
Office Action received in ARIPO Application No. AP/P/2018/011206 mailed Jan. 6, 2021, 4 pages.
cited by applicant
Office Action received in ARIPO Application No. AP/P/2018/011208 mailed Jan. 7, 2021, 6 pages.
cited by applicant
Office Action received in ARIPO Application No. AP/P/2018/011237 mailed Jan. 19, 2021, 6
pages. cited by applicant
Office Action received in Australian Patent Application No. 2017293458 mailed Oct. 31, 2019, 3
pages. cited by applicant
Office Action received in Brazilian Application No. BR112018073056-4 issued Jun. 16, 2020, 12
pages. cited by applicant
Office Action received in Brazilian Application No. BR112018076425-6 mailed Aug. 10, 2020, 13
pages. cited by applicant
Office Action received in Brazilian Application No. BR112018076425-6 mailed Jan. 19, 2021, 7
pages. cited by applicant
Office Action received in Brazilian Application No. BR20112019000218-9 issued Jun. 6, 2020, 18
pages. cited by applicant
Office Action received in Brazilian Patent Application No. BR112018076624-0 mailed Oct. 28,
2020, 8 pages. cited by applicant
Office Action received in Brazilian Patent Application No. BR112019000218-9 mailed Nov. 16,
2020, 8 pages. cited by applicant
Office Action received in Canadian Application No. 3,029,578 mailed Nov. 18, 2019, 6 pages. cited
by applicant
Office Action received in Chilean Application No. 201803876 mailed Aug. 12, 2020, 31 pages.
cited by applicant
Office Action received in Chinese Application No. 2017800378727 mailed Apr. 2, 2021, 16 pages.
cited by applicant
Office Action received in Chinese Application No. 2017800378727 mailed Oct. 14, 2020, 11 pages.
cited by applicant
Office Action received in Chinese Application No. 201780038052.X mailed Jan. 13, 2021, 5 pages.
cited by applicant
Office Action received in Chinese Application No. 201780038052X issued Aug. 5, 2020, 13 pages.
cited by applicant
Office Action received in Chinese Application No. 2017800417242 mailed Oct. 20, 2020, 10 pages.
cited by applicant
Office Action received in Chinese Application No. 2017800417331 mailed Aug. 20, 2020, 19
pages. cited by applicant
Office Action received in Chinese Application No. 201780042577.0 mailed Jan. 21, 2020, 12
pages. cited by applicant
Office Action received in Chinese Application No. 2017800425770 issued Jun. 19, 2020, 6 pages.
cited by applicant
Office Action received in Chinese Patent Application No. 2017800425770 mailed Nov. 17, 2020, 7
pages. cited by applicant
Office Action received in Columbian Application No. NC2018/0013306 mailed May 31, 2021, 9
pages. cited by applicant
Office Action received in Columbian Application No. NC2018/0013306 mailed Sep. 14, 2020, 10

pages. cited by applicant
Office Action received in Columbian Application No. NC2019/0000481 mailed Jan. 20, 2021, 12 pages. cited by applicant
Office Action received in Columbian Application No. NC2019/0000496 mailed May 3, 2021, 12 pages. cited by applicant
Office Action received in Dominican Republic Application No. P2018-0250 mailed Sep. 28, 2020, 5 pages. cited by applicant
Office Action received in Dominican Republic Application No. P2018-0286 mailed Sep. 28, 2020, 6 pages. cited by applicant
Office Action received in Dominican Republic Application No. P2018-0294 mailed Sep. 28, 2020, 4 pages. cited by applicant
Office Action received in Japanese Application No. 2018-568343 mailed Jan. 8, 2020, 9 pages. cited by applicant
Office Action received in Japanese Application No. 2019-512039 mailed Jul. 2, 2020. 6 pages. cited by applicant
Office Action received in Japanese Patent Application No. 2018-566447 mailed Nov. 10, 2020, 7 pages. cited by applicant
Office Action received in Japanese Patent Application No. 2018-568870 mailed Nov. 12, 2020, 7 pages. cited by applicant
Office Action received in Korean Application No. 10-2018-7035626 mailed Aug. 21, 2020. 4 pages. cited by applicant
Office Action received in Korean Application No. 10-2019-7003338 mailed Nov. 20, 2019, 8 pages. cited by applicant
Office Action received in Korean Application No. 10-2020-7029936 mailed Apr. 30, 2021, 6 pages. cited by applicant
Office Action received in New Zealand Patent Application No. 749216 mailed Nov. 15, 2019. 3 pages. cited by applicant
Office Action received in Panamanian Application No. 92477-01, 2019. 2 pages. cited by applicant
Office Action received in Panamanian Application No. 92484-01. 2 pages. cited by applicant
Office Action received in U.S. Appl. No. 15/062,319 dated Feb. 2, 2018. cited by applicant
Office Action received in U.S. Appl. No. 15/628,844 dated Feb. 26, 2019. cited by applicant
Office Action received in U.S. Appl. No. 15/628,844 dated Sep. 11, 2019. cited by applicant
Office Action received in U.S. Appl. No. 15/628,922 dated Apr. 29, 2019. cited by applicant
Office Action received in U.S. Appl. No. 15/628,922 dated Aug. 27, 2019. cited by applicant
Office Action received in U.S. Appl. No. 15/641,471 dated Apr. 1, 2019. cited by applicant
Office Action received in U.S. Appl. No. 15/641,471 dated Aug. 15, 2019. cited by applicant
Office Action received in U.S. Appl. No. 16/263,088 dated Aug. 29, 2019. cited by applicant
Office Action received in U.S. Appl. No. 16/263,088 dated May 8, 2019. cited by applicant
Office Action received in U.S. Appl. No. 15/628,922 mailed Aug. 24, 2020. cited by applicant
Office Action received in U.S. Appl. No. 15/641,471 dated Mar. 18, 2020. cited by applicant
Office Action received in U.S. Appl. No. 15/641,471 mailed Jan. 21, 2020. cited by applicant
Office Action received in U.S. Appl. No. 15/628,844 mailed Jun. 19, 2019. cited by applicant
Office Action received in U.S. Appl. No. 15/628,922 mailed Nov. 5, 2019. cited by applicant
Official Action received in Brazilian Patent Application No. BR112018076624-0 mailed Mar. 30, 2021, 6 pages. cited by applicant
Official Action received in Brazilian Patent Application No. BR112019000051-8 mailed May 11, 2020. 6 pages. cited by applicant
Official Action received in Chile Application No. 201803174 dated Mar. 16, 2020. 16 pages. cited by applicant
Official Action received in Chilean Application No. 201803679 (3679-2018) dated Aug. 1, 2019. 3

pages. cited by applicant
Official Action received in Chilean Patent Application No. 201803676 mailed Mar. 16, 2020, 30
pages. cited by applicant
Official Action received in Chilean Patent Application No. 201803679 mailed Mar. 31, 2020, 40
pages. cited by applicant
Official Action received in Chilean Patent Application No. 201803831 mailed Mar. 16, 2020, 29
pages. cited by applicant
Official Action received in Chinese Patent Application No. 201780041724.2 mailed Apr. 2, 2021, 3
pages. cited by applicant
Official Action received in Chinese Patent Application No. 2017800417331 mailed Apr. 6, 2021, 6
pages. cited by applicant
Official Action received in Columbian Application No. NC2018/0013306 issued May 28, 2020, 20
pages. cited by applicant
Official Action received in Columbian Patent Application No. NC2019/0000773 mailed Apr. 28,
2020, 14 pages. cited by applicant
Official Action received in Columbian Patent Application No. NC2019/0000773 mailed Feb. 12,
2021. 21 pages. cited by applicant
Official Action received in Columbian Patent Application No. NC2019/0000790 mailed Feb. 8,
2021, 14 pages. cited by applicant
Official Action received in European Patent Application No. 17 823 741.8-1104 mailed Nov. 4,
2020, 5 pages. cited by applicant
Official Action received in European Patent Application No. 17823725.1 mailed Jan. 22, 2021, 8
pages. cited by applicant
Official Action received in Japanese Patent Application No. 2018-566366 mailed Feb. 9, 2021, 8
pages. cited by applicant
Official Action received in Japanese Patent Application No. 2018-566447 mailed Mar. 12, 2021, 2
pages. cited by applicant
Official Action received in Japanese Patent Application No. 2018-568343 mailed May 15, 2020, 8
pages. cited by applicant
Official Action received in Japanese Patent Application No. 2018-568870 mailed Mar. 12, 2021, 5
pages. cited by applicant
Official Action received in Japanese Patent Application No. 2019-512039 mailed Feb. 26, 2021. 5
pages. cited by applicant
Official Action received in New Zealand Patent Application No. 749216 mailed Apr. 20, 2020. 2
pages. cited by applicant
Official Action received in Panamanian Patent Application No. 92432-01 mailing date unclear, 2
pages. cited by applicant
Official Action received in Saudi Arabian Patent Application No. 518400408 mailed Mar. 31, 2021.
8 pages. cited by applicant
Official Action received in Singapore Patent Application No. 11201811050P mailed Mar. 4, 2021. 9
pages. cited by applicant
Official Action received in U.S. Appl. No. 15/628,922 mailed Apr. 9, 2020. cited by applicant
Search Report and Expert Report received in Chilean Application No. 201803676 mailed Dec. 16,
2019. 34 pages. cited by applicant
Search Report and Expert Report received in Chilean Application No. 201803831 mailed Nov. 13,
2019. 26 pages. cited by applicant
Search Report and Expert Report received in Chilean Application No. 201803876 mailed Dec. 2,
2019. 42 pages. cited by applicant
Search Report and Written Opinion received in corresponding PCT Application No.
PCT/IB2017/054058 dated Nov. 9, 2017. 7 pages. cited by applicant

Search Report and Written Opinion received in PCT Application No. PCT/IB2017/052811 mailed Aug. 7, 2017. 15 pages. cited by applicant
Search Report and Written Opinion received in PCT Application No. PCT/IB2017/053667 dated Sep. 12, 2017. 8 pages. cited by applicant
Search Report and Written Opinion received in PCT Application No. PCT/IB2017/053713 mailed Sep. 20, 2017. 13 pages. cited by applicant
U.S. Office Action dated Jun. 6, 2018 in U.S. Appl. No. 15/641,471. 39 pages. cited by applicant
U.S. Office Action dated May 3, 2018 in U.S. Appl. No. 15/062,319. 13 pages. cited by applicant
Written Opinion received in Singapore Application No. 11201810944S dated Feb. 18, 2020, 6 pages. cited by applicant
Written Opinion received in Singapore Application No. 11201810944S issued Jul. 31, 2020, 6 pages. cited by applicant
Written Opinion received in Singapore Application No. 11201810958U dated Feb. 18, 2020, 6 pages. cited by applicant

Primary Examiner: Gitman; Gabriel E

Attorney, Agent or Firm: Riverside Law LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/907,595, filed Jun. 22, 2020, entitled, "SYSTEM AND PROCESS FOR CONVERTING WASTE PLASTIC INTO FUEL", which is a divisional of U.S. application Ser. No. 15/641,471, filed Jul. 5, 2017, entitled, "SYSTEM AND PROCESS FOR CONVERTING WASTE PLASTIC INTO FUEL", which claims benefit of priority of U.S. Provisional Application No. 62/493,445, filed Jul. 5, 2016, entitled, "PROCESS FOR CONVERTING WASTE PLASTIC INTO FUEL", each of which are incorporated herein by reference in its entirety. (2) This application makes reference to U.S. Provisional Application No. 62/318,178, filed Jun. 21, 2016, entitled "CHAR SEPARATOR"; U.S. application Ser. No. 15/477,312, filed Apr. 3, 2017, entitled "CHAR SEPARATOR"; U.S. Provisional Application No. 62/319,768, filed Jun. 21, 2016, entitled "BAG PRESS SEPARATOR"; U.S. patent application Ser. No. 15/479,560, filed Apr. 5, 2017, entitled "BAG PRESS SEPARATOR"; U.S. patent application Ser. No. 15/054,903, filed May 12, 2016, entitled "CYCLONIC CONDENSING AND COOLING SYSTEM"; International Application No. PCT/IB2017/052811, filed May 17, 2017, entitled "CYCLONIC CONDENSING AND COOLING SYSTEM"; U.S. patent application Ser. No. 15/062,319, filed Jul. 8, 2016, entitled "HEATED AIRLOCK FEEDER UNIT"; International Application No. PCT/IB2017/053667, filed Jun. 20, 2017, entitled "HEATED AIRLOCK FEEDER UNIT"; U.S. patent application Ser. No. 15/593,579, filed May 12, 2017, entitled "CYCLONIC CONDENSING AND COOLING SYSTEM"; U.S. patent application Ser. No. 14/757,227, filed Dec. 8, 2015, entitled "HEATED AIRLOCK FEEDER UNIT"; U.S. Provisional Application No. 62/089,617, filed Dec. 9, 2014, entitled "FEEDING REACTOR/EXTRUDER"; U.S. Provisional Application No. 62/089,628, filed Dec. 9, 2014, entitled "CYCLONIC CONDENSATION SYSTEM"; U.S. patent application Ser. No. 14/964,521, filed Dec. 9, 2015; U.S. Patent Application filed Dec. 9, 2015, entitled "HEATED AIRLOCK FEEDER UNIT"; U.S. Application filed Dec. 9, 2015, entitled "CYCLONIC COOLING SYSTEM"; U.S. Provisional Application No. 62/270,565, filed Dec. 21, 2015, entitled "BAG PRESS FEEDER"; U.S. Provisional Application filed Dec. 13, 2015, entitled "CHAR SEPARATOR"; U.S. Provisional Application No. 62/089,635, filed Dec. 9, 2014,

entitled “RADIANT AIR CHILLER”; U.S. application Ser. No. 15/628,844, filed Jun. 21, 2017, entitled “CHAR SEPARATOR AND METHOD”; International Application No. PCT/IB2017/053713; entitled “CHAR SEPARATOR AND METHOD”; U.S. application Ser. No. 15/628,922, filed Jun. 21, 2017, entitled “BAG PRESS FEEDER ASSEMBLY”; International Application No. PCT/IB2017/053715, entitled “BAG PRESS FEEDER ASSEMBLY”. The entire contents and disclosures of these patent applications are incorporated herein by reference.

BACKGROUND

Field of the Invention

(1) The present invention relates generally to a device for heat exchanged technology. More particularly, it relates to a device for economically condensing hydrocarbon vapors in a renewable energy plant.

Background of the Invention

(2) Convention systems for producing fuel in a pyrolysis process have been utilized. Examples of known processes include U.S. Pat. No. 8,696,994 to Miller, U.S. Pat. No. 8,344,195 to Srinakruang, and U.S. Pat. No. 6,534,689 to Stankevitch. These patents teach processes that use catalyst cracking techniques that depolymerize the hydrocarbon chains and then produce fuel once the plastic is vaporized (Miller, Srinakruang, and Stankevitch).

(3) Plastic pyrolysis systems currently use large rotating vessel and large kiln apparatuses. A challenge with using large vessels is their inability to fill and discharge continuously as these systems use a batch fill to insert plastic and then heat the product with sealed ends. Although claiming to be a continuous system, they generally utilize multiple units; as one is being filled, another is emptied. Therefore, the process is not truly a continuous process but an overlapping batch process.

(4) A second problem with large vessels of conventional system includes drawbacks with the sealing mechanisms. Sealing mechanisms expand due to heat and pressure. Due to this expansion, oxygen can leak into the vessels creating a fire hazard. A third challenge with the current known art is that the start of time of the pyrolysis reaction is prolonged due to the fact that the vessel needs to be started up when it is cold and the oxygen needs to be evacuated before heating. This is an extremely time intensive process. Another problem with prior art systems includes vessels that require a cool down period before cleaning, for example, in order to access the interior structures. Extraction of the fuel and char is also conducted in a batch operation. The char removal process involved with the prior art is cumbersome and extremely dirty because of the nature of cleaning as the vessel collects char on the wall. This char has to be removed before the next batch is processed. This is very time consuming and expensive due to the low efficiency of combination of heating, cooling, and cleaning.

(5) Other systems use vats that are very similar in nature as the one described above as they must be purged of oxygen and filled with plastic then sealed, then heated, and then cleaned. These machines require large, highly machined surfaces for a good seal. The batch heating and cooling requires large amounts of energy to achieve the pyrolysis process in a timely manner. Manual labor is used in the cleaning process. This is expensive and can be hazardous. Other plastic systems are designed for a particular type of plastic only. The inability to switch from a certain homogenous stream to a mixed plastic stream requires re-configuration of the equipment. Different grades, sources, and streams of plastic have different densities and different textures that effect handling parts differently. Plastic bags, film, and light density plastics present a problem to standard shredders and feeding mechanisms due to the wrapping effect and bridging that occurs. Wrapping occurs as the plastic bags build up around the cutting shaft eventually stopping the shredder mechanism. Although knife cutting devices will work to resolve this problem, they will not allow for hard contaminants to pass through the cutting blades. The hard contaminants will damage the cutting edge and even stop the cutter rotation.

(6) Thus, there is a need for producing a more efficient re-useable energy apparatus that provides capability for optimizing usable and re-usable fuel vapors. There is also a need for providing improved systems that reduce and/or eliminate contaminants without employing added expenditures of additional equipment or additional filtering processes for achieving the same.

SUMMARY

(7) According to first broad aspect, the present invention provides an apparatus for processing reusable fuel comprising: a continuous material supply assembly; a heated airlock feeder configured to continuously receive and process the material supply received therein; a reactor configured to receive the processed material from the heated airlock feeder; and a vapor refining system configured to process vapor supplied by the reactor. The apparatus may comprise a char disposal system configured to eliminate char from the reactor. The apparatus may also comprise a thermal expansion system configured to allow thermal expansion of the reactor. A cooling system may be configured to receive processed fuel from the reactor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings, which are incorporated herein and constitute part of this specification, illustrate exemplary embodiments of the invention, and, together with the general description given above and the detailed description given below, serve to explain the features of the invention.
- (2) FIG. 1 illustrates reactor section for a re-useable energy apparatus according to one embodiment of the present invention.
- (3) FIG. 2 is a schematic illustration of a process flow according to one embodiment of the present invention.
- (4) FIG. 3 illustrates an assembled view of a bag press feeder assembly according to one embodiment of the present invention.
- (5) FIG. 4 illustrates an exploded view of the bag press feeder assembly of FIG. 2 according to one embodiment of the present invention.
- (6) FIG. 5 illustrates an alternate embodiment of a bag press feeder assembly according to another embodiment of the present invention.
- (7) FIG. 6 illustrates a cyclonic condensing and cooling system according to one embodiment of the present invention.
- (8) FIG. 7 illustrates an assembled, an exploded and an internal view of cyclones B, C, and D of FIG. 6 according to one embodiment of the present invention.
- (9) FIG. 8 illustrates an assembled view, an exploded view and an internal view of a coil condenser according to one embodiment of the present invention.
- (10) FIG. 9 illustrates an assembled and exploded view of a forced air cooling/condensing system according to one embodiment of the present invention.
- (11) FIG. 10 illustrates an assembled and partially assembled view of a scrubber/bubbler unit according to one embodiment of the present invention.
- (12) FIG. 11 illustrates an assembled and exploded view of a main liquid fuel collection tank and a flash tank for removal of hydro-carbon gases according to one embodiment of the present invention.
- (13) FIG. 12 is a schematic of the process flow of the condensing/cooling process according to one embodiment of the present invention.
- (14) FIG. 13 illustrates an assembly of burner units having an exemplary clam-type shell according to one embodiment of the present invention.
- (15) FIG. 14 illustrates an exemplary reactor assembly according to one embodiment of the present invention.

invention.

(16) FIG. 15 illustrates an exemplary burner designed as a dual gas burner unit according to one embodiment of the present invention.

(17) FIG. 16 illustrates exemplary augers utilized within a heated airlock feeder according to one embodiment of the present invention.

(18) FIG. 17 illustrates an exploded view and an assembled view of an exemplary heated airlock feeder according to one embodiment of the present invention.

(19) FIG. 18 illustrates an assembled view and an exploded view of a char separator according to one embodiment of the present invention.

(20) FIG. 19 illustrates a char discharge system according to one embodiment of the present invention.

(21) FIG. 20 illustrates a movement assembly or cart assembly for providing thermal expansion according to one embodiment of the present invention.

(22) FIG. 21 illustrates screw conveyer types of the disclosed system according to one embodiment of the present invention.

(23) FIG. 22 is an exemplary chart listing the percentage of components in a plastic pyrolysis sample according to one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Definitions

(24) Where the definition of terms departs from the commonly used meaning of the term, applicant intends to utilize the definitions provided below, unless specifically indicated.

(25) It is to be understood that the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of any subject matter claimed. In this application, the use of the singular includes the plural unless specifically stated otherwise. It must be noted that, as used in the specification and the appended claims, the singular forms “a,” “an” and “the” include plural referents unless the context clearly dictates otherwise. In this application, the use of “or” means “and/or” unless stated otherwise. Furthermore, use of the term “including” as well as other forms, such as “include,” “includes,” and “included,” is not limiting.

(26) For purposes of the present invention, the term “comprising,” the term “having,” the term “including,” and variations of these words are intended to be open-ended and mean that there may be additional elements other than the listed elements.

(27) For purposes of the present invention, directional terms such as “top,” “bottom,” “upper,” “lower,” “above,” “below,” “left,” “right,” “horizontal,” “vertical,” “up,” “down,” etc., are used merely for convenience in describing the various embodiments of the present invention. The embodiments of the present invention may be oriented in various ways. For example, the diagrams, apparatuses, etc., shown in the drawing FIGS. may be flipped over, rotated by 90° in any direction, reversed, etc.

(28) For purposes of the present invention, a value or property is “based” on a particular value, property, the satisfaction of a condition, or other factor, if that value is derived by performing a mathematical calculation or logical decision using that value, property or other factor.

(29) For purposes of the present invention, it should be noted that to provide a more concise description, some of the quantitative expressions given herein are not qualified with the term “about.” It is understood that whether the term “about” is used explicitly or not, every quantity given herein is meant to refer to the actual given value, and it is also meant to refer to the approximation to such given value that would reasonably be inferred based on the ordinary skill in the art, including approximations due to the experimental and/or measurement conditions for such given value.

(30) For the purposes of the present invention, the term “ambient air temperature” refers to generally to the temperature of the surrounding environment and more particularly the temperature

of the surrounding environment of the disclosed cyclonic condensing and cooling system.

(31) For the purposes of the present invention, the term “bubbler” refers to an apparatus that directs gas flow beneath a liquid in which gas bubbles through a liquid to filter, scrub and/or dissolve out harmful gasses/pollutants. In addition, the bubbler may serve as a back flame arrestor or a back pressure regulator.

(32) For the purposes of the present invention, the term “coil condenser” refers to a coiled tube utilized as the basic energy exchange medium between a vapor to be condensed and a liquid to be condensed. Typical surrounding liquids that may be utilized to achieve lower freezing points or inhibit rust build up may include water or water mixed with glycol.

(33) For the purposes of the present invention, the term “chiller” refers to an external refrigeration unit used to lower/reduce the temperature of a liquid used in condensation to be subsequently pumped such as through a coil condenser.

(34) For the purposes of the present invention, the term “cyclone cooler” refers to a non-electric drawing condensing device that rotates air mass in a cyclonic rotation. In application the cyclonic rotation may include a rapid inward circulation of air masses about a low-pressure center.

(35) For the purposes of the present invention, the term “daisy chain configuration” refers to an assembly wherein components are connected in sequence. The sequential connection may include a series configuration of connections of several components wherein one component is connected to the next component in line.

(36) For the purposes of the present invention, the term “de-stoner hood” refers to a device that separates solid heavy objects from entering a prescribed area. In one exemplary embodiment, the de-stoner hood may be configured to prevent heavy objects like steel or aluminum from entering into the bag press hopper of the disclosed embodiment.

(37) For the purposes of the present invention, the term “fin” refers to a thin component or appendage attached to a larger body or structure. Fins typically function as foils that produce lift or thrust, or provide the ability to steer or stabilize motion while traveling in water, air, or other fluid media. Fins are also used to increase surface areas for heat transfer purposes.

(38) For the purposes of the present invention, the term “heat exchanger” refers to a device designed to transfer heat from one matter to another. In application, the heat exchanger may be utilized to transfer heat between a solid object and a fluid (a liquid or a gas), or between two or more fluids. The fluids may be separated (such as by a solid wall) to prevent mixing or they may be in direct contact.

(39) For the purposes of the present invention, the term “identical” refers to being similar in every detail; exactly alike.

(40) For the purposes of the present invention, the term “flash point” of a volatile material refers to the lowest temperature at which vapors of the material will ignite when given or exposed to an ignition source.

(41) For the purposes of the present invention, the term “fractionation” refers to separating of a mixture of hydro-carbon chains into a group of carbon chains or fractionations.

(42) For the purposes of the present invention, the term “naphtha” refers to any of several highly volatile, flammable liquid mixtures of hydrocarbons distilled from petroleum, coal tar, and natural gas and used as fuel, as solvents, and in making various chemicals. Also called benzine, ligroin, petroleum ether, white gasoline.

(43) For the purposes of the present invention, the term “series” refers to a number of things coming one after another in spatial or temporal succession.

(44) For the purposes of the present invention, the term “scrubber” refers to a device used to remove and/or dissolve undesirable pollutants from a gas or exhaust stream.

(45) For the purposes of the present invention, the term “substantially” refers to a great or significant extent; for the most part; essentially.

(46) For the purposes of the present invention, the term “thermal cracking” refers to process used to

break down carbon chains of petroleum compounds so that a desired carbon compound is achieved. This process may involve high heat, distillation, re-boiling, and energy intensive cooling processes.

DESCRIPTION

(47) While the invention is susceptible to various modifications and alternative forms, specific embodiment thereof has been shown by way of example in the drawings and will be described in detail below. It should be understood, however that it is not intended to limit the invention to the particular forms disclosed, but on the contrary, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and the scope of the invention.

(48) This application relates the process by which waste plastic can be turned into fuel by the use of pyrolysis in a system that is able to continuously feed shredded plastic, plastic bags, and other plastic waste into an air tight pyrolysis apparatus requiring no catalyst to produce fuel. The process allows for continuous fuel segregation, discharge of Char, as well as the collection and use of generated syn-gas to supply process heat fuel.

(49) This process overcomes the problems described above with the prior art processes due to its ability to handle heavy (e.g., a dense plastic like a recycling bin) and light plastic (e.g., less dense plastic like a plastic shopping bag) without the need to reconfigure the equipment, ability to operate in continuous use, and obtain higher efficiencies of heat exchange. A continuous flow of plastic will enter the system with a continuous flow of char being collected and fuel being continuously produced. Electricity may be generated from any excessive syn-gas not used by the burners to heat the reactor, reducing the operating cost as it does not involve batch heating, cooling and cleaning of the reactor. The process is a semi-closed loop operation. External heat is applied in the first hour and a half to two hours of processing and can be in the form of natural gas, propane, diesel, and electricity. The term is referred to as the "Start-Up Time". Once the machine has been able to run continuously during the start-up phase the invention is able to operate continuously on its own gas by-product. This gas is referred to as "synthetic gas" or "syn-gas."

(50) In the disclosed system, syn-gas may be considered a by-product or waste gas that is produced when plastic material is thermally cracked into shorter carbon chains. The aforementioned disclosed process produces condensed liquids or fuels (e.g., diesel and gasoline) and non-condensable gas like a natural gas or syn-gas. The syn-gas may be routed back to burners of the disclosed system to heat components of the system as described herein. Turning to FIG. 1, a reactor section **100** for a re-useable energy apparatus is illustrated. Reactor section **100** employs a supply feeder or bag press feeder assembly **300** to feed plastic material into reactor **1400** to heated airlock feeder **1700**. Char is dispelled through a char discharge system **1900**. Vapors produced within reactor section **100** may continue throughout the reactor and be collected through an ash separator tower or char separator **1800**.

(51) A dual gas burner depicted in FIG. 10 is able to use commercial gas and syn-gas produced by the disclosed system as heating fuel. Alternating solenoid valves depicted on FIG. 10 at **1** and **2** allow for dual gas control.

(52) Bag Press Separator

(53) Processing plastic type materials, such as plastic bags, in conventional prior art systems is known to be problematic. For example, due to the characteristically light weight nature of the plastic type materials, difficulties exist for processing and feeding the same into an extruder. For instance, plastic bag materials possess an extremely low non-compressed weight averaging three pounds per cubic foot and, due to their aforementioned light weight characteristics, plastic bag materials have a tendency to spring open, float when moved and form a very large bridge when stored.

(54) Thus, the prior art does not readily provide continuous feeding and conveying of heated plastic materials. Additionally, the prior art does not easily provide systems for addressing recycled plastic materials for conversion into refined fuel products. Furthermore, prior art systems prove problematic in achieving an air lock for feeding and manipulating heated plastic materials for

subsequent processing. Therefore, there is a need for producing a more efficient re-useable energy apparatus that provides capability for processing plastic type materials into usable and/or re-usable fuel products.

(55) Plastic waste material may be shredded and fed, for example, into a reactor (e.g., a pyrolysis reactor). Applying heat above 350 degrees Celsius will cause the shredded plastic material to melt and vaporize. Ultimately, an up-stream reactor may utilize back pressure to assist in the thermal cracking of carbon chains present in the plastic material to produce a refined fuel or re-useable fuel for subsequent use.

(56) This application relates to an apparatus that may be part of a re-useable fuel processing unit. In one disclosed embodiment, an apparatus assembly may be used to feed plastic material into a reusable fuel processing unit including a pneumatic feed having a blower **302** (FIGS. **3** and **4**) as a power source. It should be appreciated that the blower **302** may be powered by the heat used to melt and vaporize the shredded plastic. The assembly may also include a screened air outlet, a plurality of press augers, a pinch conveyer system, a de-stoner hood, a receiver hopper, a low and high level indicators, ram, press screw inlet, pneumatic air cylinder, bag press inlet, outlet, and amp monitor. The pneumatic feed may be configured to move the plastic material at a fixed rate to the press feed receiver. The blower **302** is used as a power source in which air from the blower **302** is pulled through a screened hood. The screened air outlet may be substantially configured as the same identical shape as the bag press body. The press screw augers wipe the screen as they rotate allowing air flow through the bag press, ram, and receiver. A pinch conveyer system collects loose plastic material(s), such as plastic bags, and compresses them into a de-stoner hood (having a comparatively large body) allowing compressed plastic material(s) (e.g., plastic bags) to expand when disposed inside the de-stoner hood. The plastic material(s) (e.g., plastic bags) are conveyed into a receiver hopper thereby triggering a level indicator and starting a ram mechanism. The ram acts as an air cut-off gate that will push material into a press screw inlet. Once the ram starts to move, the pinch conveyer stops, thereby preventing material from entering the receiver hopper. Thus, the ram also acts as a cut-off gate. In a disclosed embodiment, the ram is pushed by a pneumatic air cylinder towards the bag press inlet. The ram may be configured to be larger than the receiver opening and designed with substantially the same identical matching face as the press screw augers. Full details of described embodiments are provided below.

(57) Turning to FIG. **3**, a disclosed bag press feeder assembly **300** may be employed as part of a re-useable fuel processing unit that is readily configured for continuously feeding recycled plastic materials and heating the same for subsequent processing into a fuel source, as described below. FIG. **4** illustrates an exploded view **400** of bag press feeder assembly **300** according to one disclosed embodiment.

(58) Plastic bag type materials are known to be difficult to process feed into conventional prior art systems due to the inherent light weight nature of their material design. Such plastic bag type materials may possess a very low non-compressed weight averaging, for example, approximately three pounds per cubic foot. Furthermore, such aforementioned materials may have a tendency to spring open, float when moved and form a very large bridge when stored. Embodiments of the disclosed design address and solve previous problems related to plastic bag conveying, receiving, storing and feeding and as described above.

(59) The disclosed bag press feeder assembly may be constructed from a variety of materials. Carbon steel may typically be employed in the disclosed design, but other alloys may be applied if required by certain conditions. Stainless steel or aluminum may also be employed within a construction design. Turning to FIGS. **3** and **4**, the design of the bag press feeder assembly **300** allows light materials to be collected and compressed into a higher density material. The inlet **402** of the unit is tangential to help allow the separation of the conveying air from the material. Eliminating air from within the disclosed design is important to remove or drastically reduce opportunities for combustion in an otherwise flammable working environment.

(60) The plastic material being collected into the receiving hopper **304** is built to a point that a photo eye will indicate the level of material. This indicator will transmit a signal to a controller to stop the flow of material when capacity is indicated. In one disclosed embodiment, a ram press is configured to pull material from receiving hopper **304** into a press chamber **308**, as material is lowered below the photo eye, more material is conveyed into receiving hopper **304**.

(61) Plastic material may enter in either a clockwise or counterclockwise rotation based on a required design. As plastic material enters and circulates in the upper section of the receiver, it drops, due to gravity, into the lower section. This section is designed to allow material to continuously fall and not bridge. The upper diameter is smaller than the base discharge area creating a negative wall that forces any materials that would swell and cause bridging to be pushed in a downward direction following the sidewall shape.

(62) Below the receiving hopper depicted on FIG. **3** at **304** is a square housing lined with ultrahigh-molecular-weight polyethylene (UHMW) or low friction plastic, that has a void filling ram device **414** (FIG. **4**) inside. In one disclosed embodiment, the housing is configured as a square geometry. Ram device **414** is powered by a pneumatic air cylinder **416**. Ram device **414** or plug, travels inside the polymer liner **418** in a linear direction. The chamber **308** is of a prescribed shape (e.g., a generally square shape profile) with external support bars and matching connection flanges or seal flanges **424** and an inlet flange **422**. A polymer liner, UHMW or nylon, is used to reduce the drag of the ram plug **414** as it is pushed.

(63) Air cylinder **416** is mounted to a support frame at the tail of the chamber depicted on FIG. **4** at **308**. The other end of the air cylinder is connected inside ram plug **414**, e.g., to a plate that matches the auger's profile. The back end of the chamber **308** is sealed to prevent air leakage with a seal plate **426**. By sealing the chamber, air movement is allowed to enter into the receiving hopper at the product inlet port **402**, through chamber **308**, through the press body, and then through the air discharge transition hood **318** and into a fan that can be located remotely.

(64) The movement of ram plug **414** slides beyond the opening depicted at **420**, allowing material to fall from the receiving hopper **304** into chamber **308** through the opening connecting flange **422**. Ram plug **414** is pulled to the rear of chamber **308** which allows for a large volume of material to drop in front of the ram to be subsequently guided and pushed into the press device. Pneumatic cylinder **416** extends and pushes Ram plug **414** into an opening **404** of the bag press feeder **322**.

(65) The bag press feeder **322** consists of a press body or vertical double body **324** with a matching inlet flange **404** and an air discharge transition hood **318**. Bag press feeder **322** connects to a support frame depicted **310** and to a lower hopper that comprise split eccentric reducers all of which may be welded to match up to the body and to the single diameter discharge flange. Within press body **324**, counter rotating double flighted augers **408**, **410** may be disposed. Augers **408**, **410** are configured to receive and grab incoming material and manipulate the same to push the material to the lower hopper.

(66) Augers **408** and **410** are located in a drum measuring approximately fourteen inches in diameter for each auger with heavy screw flight material welded solidly around the drum. The drum is designed as a lower tapered cone to match the bag press body shape. The drive shaft at **412** is supported and welded through the drum and extends into the gearbox **314**. Augers **408** and **410** are constructed where one has right-hand rotation the other has left-hand rotation. The left-hand and right-hand augers overlap. Due to this overlap augers **408**, **410** act as self-cleaning mechanisms while pushing the plastic material downward into the lower section of the bag press feeder hopper. The pressure within the bag press feeder **322** increases as material is forced from the large opening at the top of the bag press feeder into the lower small opening of the bag press feeder. An access door **326** is a plug type door used to maintain the internal shape. Plastic material is pulled into the receiving hopper at the product inlet **402** by a fan located on the backside of a screened air outlet transition hood **318**.

(67) Main augers **408** and **410** may be configured as drum style augers. The concept of the drums is

to have a large circumference preventing materials like plastic bags from wrapping completely around the drum. The disclosed design, along with overlapping, counter rotating auger flights prevents material from wrapping around the drum augers **408, 410**. The base of the drum augers has two flights ending 180 degrees apart due to the double flights. Because the drum has flights on both sides that are 180 degrees apart, the force pressure downward does not deflect the drum auger when compressing material below.

(68) As best illustrated in FIG. **4**, a drive system may be provided to connect to and control augers **408, 410**. The drive system may include a gearbox or drive mechanism **314** that may be powered, for example, by a helical gear motorized drive box or motor drive **312**. Drive mechanism **314** may be maintained, for example, within a drive housing. From inside the drive housing exits transfer shafts **434**, spur gears **436** seals and bearings. The use of a multitude of spur gears **436** (e.g., four spur gears) reduces the overall size of the gearbox **314**. In operation, the centerline difference between the two augers **408, 410** would otherwise require two large gears to meet in the middle, where the use of the four smaller spur gears makes the box smaller while maintaining equal force on all of the shafts.

(69) Accordingly, in one disclosed embodiment, a pneumatic feed is used in the disclosed design to both move the plastic material at a fixed rate to the press feed receiver **304** and to remove any heavy objects. A standard blower **302** (FIGS. **3** and **4**) may be used for the power source. The air from the blower **302** is pulled through a screened hood **318** on a back side of a material press body or bag press body **320**. In one disclosed embodiment, screen hood **318** tapers generally inwardly from a connection point onto a screened air outlet transition **402** may be configured as the same shape as the bag press body depicted at **99** creating a very small gap between augers **408** and **410** and the screen **402**. Augers **408** and **410** wipe the screen **402** as it rotates, allowing for air flow through the bag press, ram and receiver. Screen **402** maintains plastic material particles within bag press body **320** thereby preventing them from exiting at hood **318**. However, the design of the screen **402** also allows airflow through the bag press into the bag press body **320** and out through hood **318** to eliminate and/or greatly reduce an otherwise combustible operating environment.

(70) A conveyor system, such as a pinch conveyor system, may be employed to collect plastic material, such as loose bags, and compress them into a size that will be feed into a de-stoner hood **306**. De-stoner hood **306** has a large body and allows the compressed plastic bag material to expand a little once disposed within inside the de-stoner hood. The bags are then conveyed into the receiver hopper **304** into the ram housing **308**. The bags fill receiver hopper **304** to a fixed point triggering a level indicator. This will start ram **414** disposed below to push material into the press screw inlet **504**. As ram **414** starts to move, the pinch conveyor stops to prevent further material from entering the receiver hopper **304**. Ram **414** also acts as an air cutoff gate as it covers the receiver hopper opening **420**. Receiver **304** has a negative wall design. The incoming material expands when it is inside the receiver **304**. The hopper gets larger as its gets closer to the ram inlet **420**. Ram **414** is pushed by a pneumatic air cylinder **416** to the bag press inlet **504**, and at the same time cuts off the material flow due to its shape as the ram body is larger than the receiver opening **420** disposed above the ram body. Ram **414** may be configured to have a substantially identical face with the same shape and/or size as the press screw augers **408** and **410** allowing material to be pulled into the press body depicted **99**. The plastic material is forced down the augers **408** and **410** by the metal flights **406**. Disclosed embodiments provide one left hand flight auger **408** and one right hand flight auger **410** in the press body **320**.

(71) As more and more plastic material, such as plastic bags, is collected into the bag press, the plastic material is forced down and is compressed. As the plastic material (e.g., plastic bags) builds up inside the bag press body **320**, the plastic material is pushed down where the diameter of the hopper gets smaller and smaller towards a compression area at outlet **328**. The increase in material and decrease in area creates a higher density of plastic material and creates a pressurized seal.

(72) The bag press motor drive **312** may include an amp monitor. The amp monitor may be set at a

prescribed level to signal when the bag press is full and at the correct pressure. Depending upon the threshold level of the amp monitor, the motor drive is controlled to operate or not operate based upon a prescribe value or amp range. When the material is allowed to discharge, the pressure is reduced in the compression area at outlet **328** and the computer may be initialized to start the fill process while continuing to monitor the motor amps.

(73) Turning to FIG. **5**, an alternate embodiment **510** of a bag press feeder assembly **500** is shown in connection with heated airlock feeder **1700**. A negative vacuum pressure is created within bag press body **320** to draw plastic material within. Accordingly, plastic material **502** is fed into inlet **504** by airstream **506**. The disclosed configuration receives airstream **506** into inlet **504** of bag press body **320** towards auger **408** (**410**) and through screen **402** and hooded outlet **318**.

(74) A screened air outlet transition **402** may be configured as the same shape as the bag press body depicted at **99** creating a very small gap between augers **408** and **410** and the screen **402**. Augers **408** and **410** wipe the screen **402** as it rotates, allowing for air flow through the bag press, ram and receiver. Screen **402** maintains plastic material particles within bag press body **320** thereby preventing them from exiting through screen **402** and hooded outlet **318**. However, the design of the screen **402** also allows airflow through the bag press into the bag press body **320** and out through screen **402** and hooded outlet **318** to eliminate and/or greatly reduce an otherwise combustible operating environment.

(75) By design, plastic material **502** is urged towards auger **408** (**410**) via airstream **506** and the back pressure created within bag press body **320**. As more and more plastic material **502** is collected into bag press body **320**, plastic material **502** is forced in downward direction **508** as it continues to compress. As plastic material **502** builds up inside bag press body **320**, plastic material **502** is pushed downwardly where the diameter of the hopper gets smaller and smaller towards the outlet. The increase in material and decrease in area creates a higher density of material and creates a pressurized seal.

(76) Cyclonic Condensing and Cooling System

(77) Existing designs of convention systems often require an inordinate amount of space to accommodate the structure of the cooling system. In addition, such conventional cooling system configurations merely produce a low surface area inside the condensers thereby limiting their efficiency. Furthermore, the aforementioned designs do not allow for easy linkage and communication of its components such as in a daisy-chain configuration design. As a result, condensation of usable and re-useable fuel vapors may not be optimized. Accordingly, prior art designs may lead to char build-up and plugging of internal tubes within the condenser thereby reducing effectiveness of the system.

(78) Thus, there is a need for producing a more efficient heat exchange cooling system that provides capability for optimizing usable and re-usable fuel vapors. There is also a need for providing improved systems that reduce contaminants without employing added expenditures of additional equipment (such as external heat sources, electrical input or cooling media apparatus) for achieving the same.

(79) Fractionation includes the separating of a mixture of hydro-carbon chains into a group of carbon chains or fractionations. Thermal cracking is the process used by refineries to break down carbon chains of petroleum compounds so that the desired carbon compound can be achieved. This process typically involves high heat, distillation, re-boiling, and energy intensive cooling processes. This application discloses an invention that will condense vapor produced by a reactor (e.g., a pyrolysis reactor). In doing so, the disclosed system utilizes a standard cyclone; a plurality of specialized cascading cyclones with internal cyclonic rotation fins that force incoming vapor to maintain a fixed amount of rotation regardless of the vapor's velocity, heat sinks that increase condensation, reversing fins that force gases to reverse direction inside the cyclone decreasing vapor velocity to increase heat loss; a main collection tank that allows for the controlling of the fuel flash point; a compact low temperature coil cooler that uses 100 percent of the cooling surface that

allows for the production of higher quality fuel; and, bubblers/scrubbers that produce back pressure into the pyrolysis reactor.

(80) The disclosed subject matter improves on heat exchanged technology by providing a more efficient heat exchange cooling system that provides capability for optimizing usable and re-usable fuel vapors. Such vapors may be captured and utilized on any device able to run on gaseous fuel such as any non-condensable petroleum fuel.

(81) In addition, the disclosed subject matter discussed herein differs from the prior art as it employs modified rotation fins, internal cyclone heat sinks, forced gas direction reversal inside of each cyclone, the ability to control fuel flash points without an external heat source, separation of the collected fuels without an external heat source, and compact low temperature coil cooler that uses one hundred percent of the cooling surface.

(82) Furthermore, the disclosed subject matter employs a daisy-chain design configuration so that the condensation of usable re-useable fuel vapors is optimized. The disclosed cyclonic condensing and cooling system is part of a re-useable energy technology and the prior art designs would lead to Char build-up and plugging of the tubes within the condenser reducing effectiveness.

(83) Turning to FIG. 6, the disclosed subject matter is directed to a cooling system consisting of a plurality of cyclone coolers (e.g., one standard cyclone cooler and one or more specialized cyclone coolers) thereby forming the disclosed cyclonic condensing and cooling system **600**. According to disclosed embodiments, the standard cyclone cooler may be considered to be a first-type cyclone cooler having a first configuration, as explained herein. The one or more specialized cyclone coolers may be considered to be second-type cyclone coolers. Thus, the one or more second-type coolers may have a substantially identical second configurations with respect to the other one or more second-type cyclone coolers, as explained below. Yet, the first-type cyclone cooler having the first configuration is different from the second-type cyclone coolers having the second configurations, as explained below.

(84) By way of example, one standard cyclone cooler is depicted as A in FIG. 6. In an exemplary embodiment three specialized cyclone coolers are illustrated as B, C and D in FIG. 6. Each of the specialized cyclone coolers B, C and D are of the type illustrated, for example, in FIG. 7. An exemplary embodiment of the standard cyclone cooler may comprise a first configuration. An exemplary embodiment of the specialized cyclone coolers may comprise a second configuration, each of the second configurations being alike one another but different from the first configuration of the standard cyclone cooler. The disclosed cyclonic condensing and cooling system **600** may include a chiller **630**, an air heat exchanger **624**, two liquid bubblers/scrubbers **650**, a main holding or main liquid fuel collection tank **664**, and an expansion tank **638**.

(85) In an exemplary application, a pyrolysis reactor processes plastic waste material which may be shredded and fed therein. Applying heat above 350 degrees Celsius will cause the shredded plastic material to melt and vaporize. The up-stream reactor requires back pressure to assist in the thermal cracking of the carbon chains present in the plastic material. The cyclonic condensing and cooling system **600** may be employed to produce the required back pressure required by the pyrolysis reactor. Such back pressure is achieved due to the static friction of the pipe and cyclone coolers of the disclosed subject matter in addition to the water column pressure produced in the bubblers/scrubbers **650** (e.g., depicted in FIG. 10).

(86) Turning to FIG. 6, the first cyclone cooler is illustrated at **606**. First cyclone cooler is a standard cyclone cooler. A standard cyclone cooler consists of an inlet section, body wall, cone to discharge and an internal tube. When the vapor or gas stream enters the cyclone it rotates around the body and down the cone, then up through the tube and out of the cyclone. The amount of rotation on the incoming gas, dictates the amount of rotation and centripetal force it produces and particles being conveyed with the gas. This force separates the particles from the gas and drops through the cone, then out of the cyclone. The gas rotates and drops down the cone, increasing in velocity and pressure due to the smaller and smaller diameter on the cone. This action packs the gas

stream at the bottom of the cone and forces it to rise back up and through the internal tube, then out of the cyclone to the next cyclone. The rotations of the vapor within first cyclone cooler **606** are based on the velocity of the gas as it enters first cyclone cooler **606**. In the disclosed subject matter, a cyclone inlet is depicted in FIG. **6** at **602** and FIG. **7** at **602**. Inlet **602** has a diameter of about 6 inches wherein its inlet velocity can accommodate a vapor or gas stream of about 3,234 feet per minute based upon the pyrolysis reactor's rate capability based upon the following values: approximately 2,000 pounds of shredded plastic material processed per hour at about 1,150 degrees Fahrenheit. As the pyrolysis reactor has about a 7 percent char rate, the remaining volume of shredded plastic processed (after the char is removed) is about 1,860 pounds per hour processed into a gaseous state. The gas weighs 0.78 ounces per cubic foot. Thus, standard cyclone cooler **606** receives gas at a rate of about 635 cubic feet per minute. The ambient temperature is assumed to be about 70 degrees Fahrenheit for purposes of exposure to heat loss.

(87) The vapor remains in first cyclone cooler **606** for about 4 seconds. This allows for a heat loss of between about 3 and 8 degrees Fahrenheit. The fuel collected at a bottom **151a** of first cyclone cooler **606** contains carbon chains that are C-28 or larger. First cyclone cooler **606** also collects large char particles that may have travelled into cyclonic condensing and cooling system **600**. These char particles will drop out of the vapor stream and will be deposited to the discharge hopper at the bottom **674** where it mixes with fuel containing carbon chains that are C-28 and larger. This fuel char mixture may be returned and re-fed into the pyrolysis reactor for further thermo cracking via a high temperature pump **676**. The vapors leaving standard cyclone cooler **606** are traveling at a velocity of about 3,224 feet per minute and will travel through a cross over pipe **608** for about 2.9 seconds. Due to the thin wall of cross over pipe **608**, heat loss of the vapor as the vapor travels through cross over pipe **608** will be approximately 2 degrees Fahrenheit. This heat loss lowers the inlet vapor volume of the vapor entering the second cyclone cooler **610**.

(88) Turning to FIG. **7**, a cross section of specialized cyclone coolers **610**, **614**, and **618** (second cyclone cooler, third cyclone cooler and fourth cyclone cooler, respectively) of FIG. **6** illustrates the internal structure of specialized cyclone coolers (**610**, **614**, and **618**) that forces gas vapors to follow a cyclonic path to maximize vapor contact with outer the outer body of the cyclone cooler (that is contiguous to ambient temperature) in order to dissipate heat and to effect condensation.

(89) Accordingly, second cyclone cooler **610** (FIGS. **6** and **7**) is a specialized cyclone cooler constructed with a unique configuration different from the standard/first cyclone cooler **606**. As illustrated in FIG. **7**, second cyclone cooler assembly **610** is illustrated in an assembled view **700**, and exploded view **702** and an internal view **704**. Second cyclone cooler may include a body portion **710** joined to a cone **150** in a final assembled state. Contrary to the standard cyclone cooler, the second cyclone cooler has additional internal components in a disclosed arrangement of the disclosed subject matter. Specifically, in connection, body portion **710** and cone **150** house an internal structure or internal tube comprising an outer tube structure **726** and inner tube structure **718**. Inner tube structure may be regarded as an inner filler drum **720**. Outer tube structure **726** has a cavity **722**. In a final assembly, inner tube structure **718** is disposed within a cavity **722** of outer tube structure **726**. Inner tube structure **718** comprises a cavity **216** for accommodating disbursed gases therethrough.

(90) The body **728** of outer tube structure **726** includes a first set of turning fins **724** disposed along its exterior in a first rotational direction, as described below. A configuration of turning fins **724** may include an internal cyclonic rotation fin configuration. Inner tube structure **718** includes a second set of turning fins **714** disposed along its exterior traversing in a second rotational direction. A configuration of turning fins **714** may include an internal cyclonic rotation fin configuration. In one embodiment, the second rotational direction may include a reverse or opposite cyclonic rotational fin direction to turning fins **724**, as further described below.

(91) Thus, in a final assembly, inner tube structure is disposed in cavity **722** of outer tube structure **726** to form an internal tube assembly. The internal tube assembly is further disposed within the

cavity of the joined body portion **710** and cone **150**. In the final assembly configuration, a first channel **738** is formed between an exterior of the outer tube structure **726** and the interior of the body portion **710**. Additionally, a second channel is formed between an exterior of the inner tube structure **718** and an interior of the outer tube structure **726** within cavity **722**. Turning fins **724** are disposed within first channel **738** in a first direction and turning fins **714** are disposed within second channel **740** in the second direction, as discussed below.

(92) In select embodiments, the disclosed subject matter provides second cyclone cooler **610** designed with about 158 feet of turning fins **724**. The distance between turning fins **724** is about 4 inches (the pitch) with the width of the flight being about 3 inches. Turning fins **724** may be designed having 12 spiral rotations with a 36 inch outside radius. Fins **714** placed on inner tube structure **718** may include 6 spiral rotations with the same pitch and width as turning fins **724**. Turning fins **724** are attached inside the body **710** of second cyclone cooler **610** to force the amount of rotations of received gases. This makes the gases come into contact with body **710** a fixed amount of times before entering a cone **150** disposed below. The travel time through second cyclone cooler **610** is about 3.8 seconds based on the process rate of the reactor of about 2000 pounds of shredded plastic per hour. There is heat loss in second cyclone cooler **610** due to the friction produced by fins **724** as the fins act as heat sinks. As vapors cool, they condense and lose volume; loss of volume reduces the velocity of gas reducing its velocity and creating more retaining time. This assists in further heat loss within the cyclone coolers. (FIG. 12 provides a schematic of the remaining cyclonic cooling system calculated losses for the disclosed subject matter.)

(93) Third cyclone cooler **614** (FIGS. 6 and 7) is identical to second cyclone cooler **610**. Likewise, third cyclone cooler **614** is a specialized cyclone cooler being constructed with a unique configuration different from the standard/first cyclone cooler **606**. The process involved in third cyclone cooler **614** is identical to second cyclone cooler **610**; third cyclone cooler **614** being designed and constructed in the same manner as second cyclone cooler **610**. In operation, vapors leave second cyclone cooler **610** and travel to third cyclone cooler **614** via cross over pipe **612**. The cooling process continues reducing the volume of the vapor and reducing the velocity of the vapor.

(94) Fourth cyclone cooler **618** (FIGS. 6 and 7) is identical to second cyclone cooler **610** and third cyclone cooler **614**. Likewise, fourth cyclone cooler **618** is a specialized cyclone cooler being constructed with a unique configuration different from the standard/first cyclone cooler **606**. Fourth cyclone cooler **618** is designed and constructed in the same manner as second cyclone cooler **610** and third cyclone cooler **102c**. In operation, vapors leave third cyclone cooler **614** and travel to fourth cyclone cooler **618** via cross over pipe **616**. The cooling process continues reducing the volume of the vapor and reducing the velocity of the vapor. A design configuration of fourth cyclone cooler **618** may allow vapor to leave this cyclone and enter into a forced air heat exchanger **624** (see, FIGS. 6 and 9). In an exemplary design, forced air heat exchanger (air cooled condenser) **624** has a total cross sectional area of about 1600 square inches inside the oval flatten tubes. This high surface area increases the reaction time and slows the velocity of the remaining gas stream to about 150 feet per minute and reduces the heat dramatically from approximately 100 degrees Celsius to 70 degrees Celsius due to the ambient air temperature. This creates a large amount of condensation that is collected inside oval flatten tubes **912** and allowed to drip back into fourth cyclone cooler **618** disposed located directly below. This returning liquid fuel, in turn, further cools the vapor leaving third cyclone cooler **614**. The vapor travels through forced air heat exchanger **624** and is pushed into chilled cooling coils of coil condenser **630** (FIGS. 1 and 3) via pipe **628**.

(95) Turning to FIG. 8, an internal configuration **802** and exploded view **804** of coil condenser **630** is illustrated. Coil condenser **630** serves as a short carbon chain condensing unit. In an exemplary embodiment, coil condenser **630** is a cooler that is constructed with six internally coiled 1 inch tubes **810** that are submerged through a tank **816** of chilled glycol. The six 1 inch diameter stainless steel round tubes are in the form of a spiral. The spiral reduces the overall length of the 1 inch

tubing from sixty feet where it is contained in an apparatus that is about five feet in height. The six coils are generally arranged evenly around each other in a circular pattern. This creates an even distribution of the flowing gases inside the coils. The spiral shape assists in the slowing of the incoming vapors by the use of turning static pressure. These coils are attached through a top and bottom flange plate **832**. This assembly is inserted into a drum housing **816** with matching flanges **812** and **816**. The drum housing **816** is filled with a glycol product that acts as the media for the heat exchange. The glycol remains present inside this drum. A cooling coil **810** is introduced into the drum which cools the glycol. In turn the glycol cools the 1 inch tubing that is carrying the vapors inside.

(96) Cooling coil **810** is attached to a standard refrigeration system **686** (FIG. 6) and remains closed loop through the glycol drum **816**. The vapors pass through cooling coil **810**, allowing condensation to drip into the collection chamber **828**. The vapor that does not turn into condensation exits the coil condenser at **632** after the vapor circles the glycol drum. The flange connection **832** at the bottom of the glycol drum allows the liquid to go in one direction and gas to go in another. The chamber **824** between the glycol drum and the housing is the location of where the vapors travel to the gas outlet at **632**. This zone also sees the glycol temperature on the outside of the glycol drum **816** to further cool the vapor. The condensed vapor that exits coil condenser **630** as a liquid is collected in a smaller or secondary tank **654** (FIG. 6) and pumped to storage.

(97) Coil condenser **630** is designed with bolted flange connections **808** for access and service to all components of this equipment. Each cyclone cooler and the coil chiller has a tank or collection hopper below them (FIG. 6 at **674**, **660**, **658**, and **656**). In the case of the cyclone coolers, the collection discharge hopper (FIG. 6 at **674**, **151b**, **151c**, and **151d**) has a drain port, level indicator (FIG. 6 at **668**) coupling connection and a fuel outlet port (spill over) (FIG. 7 at **732**). The spillover **732** allows for the build-up of collected fuel to be discharged into a respected holding tank.

(98) The first three cyclones coolers **606**, **610**, and **614** discharge into a first hold tank also regarded as the main holding tank **664** via control ball valves **662** (FIGS. 6 and 11). The fourth cyclone **618** discharges in smaller or second holding tank also regarded as secondary tank **654** that is located beneath the chilling coil of coil condenser **630**. According to the disclosed subject matter, smaller or secondary tank **654** receives the lighter, cooler collected fuels. The lighter or cooler collected fuels may include lighter or shorter carbon chains (i.e., gasoline, naptha) as opposed to diesel which has longer carbon chains. Main holding tank **664** collects heavier heated fuels (i.e., those fuels having a higher boiler point). Disclosed embodiments provide that main holding tank **664** collects the heavier heated fuels as being filled from the cyclone coolers **606**, **610**, and **614**. Higher temperature fuels are regarded as those fuels having higher boiling points and higher flash point e.g., above 40 degrees Celsius. Although the first three cyclone coolers **606**, **610**, and **614** collect higher temperature fuels, some amount of light fuel (like benzene) may also be collected. The lighter fuels will vaporize from the heat of the holding fuels inside main holding tank **664** and drift up the tank column **678**. A pump **680** located at the top of the expansion column **678** will pull these vapors from main holding tank **664** before they can re-condense and force them into coil condenser **630**. This allows for the collection of fuel of higher quality in main holding tank **664** by rising the flash point on the collected fuel. Disclosed cyclones coolers A, B, C, D all work together to collect fuels having a range of carbon to carbon chain structure. In accordance with disclosed embodiments, the configuration of cyclonic condensing and cooling system **600** allows heavier heated fuels to be collected by cyclone coolers A, B, C, and D while the lighter fuel is capable of being collected in coil condenser **630**.

(99) The chilled gases leave coil condenser **630** and travel to two bubbler tanks **650** that are connected in sequence through pipe connection **141**. These tanks have an extended pipe from the inlet port that is submerged under the liquid water line FIG. 10 at **1014**. This submerged pipe **1014** causes back pressure to the system by the resistance of the liquid in the bubbler tank. This is referred to as water column pressure. By using two tanks to achieve the water column pressure, the

height can be divided. These bubbler tanks can contain different liquid components as needed to remove any contaminants in the remaining vapors. As illustrated in FIG. 10, the first tank is designed to hold water and is equipped with a level indicator **1022** and a PH meter **1024** to monitor the condition of the water. Water is used to remove sulfur and the buildup of sulfur will indicate a change in the PH. The second bubbler contains caustic soda. This will capture any chlorine gas in the vapors. This tank also has a PH meter **1024** and is also equipped with a level indicator **1022** and level sensor.

(100) The last tank on cyclonic condensing and cooling system **600** is a standard expansion tank **638**. Expansion tank **638** is also designed to catch any liquid droplets that may travel through cyclonic condensing and cooling system **600**. Pressure sensors and indicators monitor the reactor pressure from this point in the system.

(101) In operation, the as gases are received within the disclosed cyclonic condensing and cooling system **600**, embodiments of the disclosed subject matter force rotations of the gases through the system. Throughout rotation, the hot gases will lose heat from thermo contact loss with the outside body wall **710**. In accordance with the design of the disclosed subject matter, the incoming gasses are channeled down first channel **738** in a direction commensurate with a first rotational direction enabled by turning fins **724** and up second channel **740** commensurate with a second rotational direction mandated by the placement of turning fins **714**. In an exemplary embodiment, the second rotational direction may include a reverse rotational direction from the first rotational direction. Prior to traversing up second channel **740**, embodiments of the disclosed subject matter allow the gases to pack generally at the bottom of cone **730** like a standard cyclone whereupon they are forced to reverse rotational direction before entering the internal tube (i.e., outer tube structure **726** and inner tube structure **718**). This adds to the particle separation, because the gases come to a complete stop before reversing direction, allowing the particles to fall out of the gas stream. The design then uses the cyclone as a separator and a cooler/condenser. As hot gases lose heat, condensation is collected in the cooler area. By controlling the gas resident time inside the cyclone, a fixed condensing temperature can be achieved. By controlling this temperature, fuel can be distilled into c-chain groups between a group of cyclones.

(102) Embodiments of the disclosed cyclonic condensing and cooling system provide four cyclone coolers in series (FIG. 6 at **606**, **610**, **614**, and **618**). The first cyclone cooler **606** collects the larger particles and higher carbon chain fuels only. The next three cyclone coolers **610**, **614**, and **618** separate the fuel grades (e.g., gasoline, petroleum, derived liquid for fuel) based on condensing temperatures. Separated fuels have temperatures which cause vaporization of the fuels to ignite when exposed to an open flame. This process is referred to as a flash point. The lower the carbon chain number in the fuel, the lower the temperature of the liquid fuel, that will cause the fuel to ignite. This temperature will be referred to as the “yield flash indicator” (YFI). In order to increase the YFI, the removal of the lighter carbon chains by use of heat is required.

(103) Each cyclone collects vapor at a lower temperature than the one before it in the gas stream creating its own YFI value. Inside the internal tube FIG. 7 at **728** is a reversed set of fins **714** connected to a filler drum **720** inside the tube. The discharge of each cyclone cooler has a hopper, or discharge tank **151** to store condensed fuels. Each hopper can be directed to a holding tank by selected ball valves. A level indicator **668** is used to start the discharge of the collected fuels. The collection hopper also has a drain valve (FIG. 6 at **662**) for cleanout use.

(104) The last cyclone cooler, the fourth, in the series (FIG. 6 at **618**) will have an air contact heat exchanger **624** to insure full ambient cooling. This heat exchanger **624** condenses the last of the ambient temperature fuels and drips it back through the cyclone, acting as a reflux and cooling for the cyclone. The remaining vapors then pass through a coil type chiller **630** via a connecting pipe **628**. This is a set of five coils (FIG. 8 at **810**), e.g., averaging 65 feet in straight length each and wrapped around each other in an even spacing. The coils **810** are set inside a tube filled with glycol **816** for chilling. This glycol is chilled with refrigerated coils **826** from an air conditioner

compressor and controlled to maintain the set point temperature. The incoming vapors entering the coil condenser **630** at entrance **820**, for example, disposed at top portion **806**, will condense and drip out of the chiller housing **828**. The vapors then turn up from the bottom of the coils and travel to the gas outlet **822**. On the way to this outlet port, the gases are again exposed to the cold wall (FIG. **8** at **824**) of the glycol chamber (FIG. **8** at **816**). This creates an effectiveness of 100% use of the chilling chamber. The remaining gases are considered non-condensable at room temperature. This gas is referred to as syn-gas.

(105) The syn-gas is then passed through two sets or bubbler/scrubbers **650**. The first is filled to a fixed point with water. This water acts as a back pressure device, a flame arrester device and a scrubber. Along with the C₄, hydrogen and other gases that make up the syn-gas, some unwanted gases also travel with the syn-gas from time to time. Without good control of the plastics entering in the reactor, chorine and sulfur can be introduced. The first bubbler will catch the sulfur in the water producing a weak dibasic acid, $S_{0.sub.2} + H_{2O} = H_2SO_3$.

(106) The next bubbler also acts as a back pressure device, flame arrester and scrubber. This time it is filled with caustic soda to scrub chorine. $Cl + NaOH = NaClO$ or salt and water. The bubblers **650** are also equipped with a level control **1022** so the level of the bubbling liquids is monitored as well as a PH meter **650** at **1024** to indicate the condensing on the bubbling/scrubbing liquids.

(107) At this point the syn-gas is ready to be used. Thus, embodiments of the disclosed subject matter provide an improved means for capturing and processing excess gas for use on any device capable of running on gaseous fuel, i.e., non-condensable petroleum fuels. Accordingly, the burners for reactor-type systems are capable of utilizing the fuel of the disclosed subject matter. The syn-gas may also be used to power a generator that could power the electrical system of the reactor. The last item in the cooling system is a finish tank. This tanks act a drip collection if any liquids travel past the bubblers. It also serves as an expansion tank for the syn-gas. When the pressure inside this tank is at set point, the gas is allowed to be used.

(108) Turning to an example design construction of cyclonic condensing and cooling system **600**, disclosed embodiments may consist of four cyclones, two fuel tanks, an air cooled radiator, one glycol chilled coil condenser, two bubblers, and one expansion tank all attached to a structural steel frame. The cyclone coolers may be constructed from 10 gauge stainless steel material. This material is selected due to its ability to withstand the internal pressure of the reactor while allowing heat to pass through the metal, cooling the incoming gas. The cyclone coolers consist of a scrolled inlet, flanged body section, internal tube with fixed rotation fins, an interior baffle with reversed rotation fins, a bolted cone with support pads, and a discharge hopper with an outlet port.

(109) The internal rotation fins are welded to one side of the cyclone tube allowing for the condensed liquid to run through the fins to the discharge hopper. The internal tube also has a cone bottom to continue the vapor to pressurize inside the cyclone. Inside the internal tube is a cone drum that acts as a baffle. This baffle also has rotation fins welded to one side. The cone drum baffle has a sloped top to allow for drainage of any condensation that may occur inside. The gas inlet and outlet discharge ports have a flange connection. The cone bottom is equipped with a coupling that acts as a level indicator. The cone bottom has a discharge part with a stub in flange for rotation and connection to the discharge hopper. The discharge hopper has a drain port, two outlet ports and the level indicator coupling.

(110) The cyclone coolers (A, B, C, and D) are piped in a daisy chain configuration. The piping used between cyclone coolers is a thin wall schedule 10 stainless steel pipe with ANSI 150 flanges. This pipe is sloped from one cyclone coolers to the next and downhill to drain any condensation vapors. The last cyclone cooler in the daisy chain configuration has an air cooled heat exchanger connected to the top discharge flange. This air cooled heat exchanger reduces the remaining vapor temperature and allows for liquid to condense and return to the last cyclone where it enters the discharge hopper. This air cooled heat exchanger is constructed from oval-shaped tubing. The oval-shaped tubing is welded to the top and bottom seal plate, openings in the seal plate are welded to

the oval-shaped tubing to allow vapors to pass through the inside of the tubing. Housing surrounds the tubing section and connects to an inlet chamber and gas discharge chamber. The fan is connected to the tube section housing. This part of the system uses ambient air and forces it across the outside of the tubing to reduce the inside vapor temperature.

(111) The fuel tanks may be constructed from heavy wall schedule 40 stainless steel pipe with pipe ends and connecting ports as needed to fill and discharge the incoming fuels. The top of the main tank **664** has an expansion column to allow light vapors to be removed from the collected liquids below. The second tank **654** is a standard holding tank with inlet and outlet connections plus a coupling for level indication. The large tank **664** is constructed to allow for high temperature fuel storage and collects from the first three cyclones. The smaller tank **654** will see low temperature fuels and is used to collect fuel from the last cyclone and the coil condenser.

(112) After the vapors leave the air cooled heat exchanger **624** it enters into a chilled coil condenser **630**. The coil condenser is located above the small fuel tank **654**. The condenser consists of six 1 inch diameter stainless steel round tubes that have been rolled into a spiral. The spiral reduces the overall length of the 1 inch tubing to one tenth the length. The spiral shape also assists in the slowing of the incoming vapors by use of the turning static pressure. The coils are attached through a top and bottom flange plate. This assembly is inserted into a drum housing with matching flanges. The drum housing is filled with a glycol product that acts as the media for the heat exchange. The glycol remains resident inside this drum. A cooling coil is introduced into the drum which cools the glycol. In turn the glycol cools the 1 inch tubing that cools the vapors inside. The cooling coil is attached to a standard refrigeration system and remains closed loop through the glycol drum. The vapors passing through the 1 inch coils, cool, so the coil condenser allows the produced condensation to drip to the bottom in the collection chamber, exiting the device. The special flange connection at the bottom of the glycol drum allows for liquid to go in one direction and gas to go in another. The chamber between the glycol drum and the outside is where the remaining vapors travel. This zone also is cooled by the glycol thus it benefits from double cooling. The coil condenser is designed with bolted flange connections for access and service to all components of this equipment.

(113) The chilled gases leave the coil condenser then travel through two bubbler tanks **650**. These tanks have an extended pipe from the inlet port that is submerged under the liquid water line. This submerged pipe causes back pressure to the system by resistance of the liquid in the bubbler tank. This is referred to as water column pressure and by using two tanks the height can be divided between each one. An example is if total water column back pressure is 60 inches in one bubbler and 50 inches in the second bubbler, a total of 110 inches of water column back pressure is created. These bubbler tanks can contain different liquid components as needed to remove any contaminants in the remaining vapors. The first tank is designed to hold water and is equipped with a level indicator and a PH meter to monitor the condition of the water. Water is used to remove sulfur and the buildup of sulfur will be indicated by a change in the PH. The second bubbler contains caustic soda which will capture any chlorine gas in the vapors. This is also monitored with a PH meter and this second bubbler is also equipped with a level indicator and level sensor.

(114) The last tank on the cyclone cooling system is a standard expansion tank **638** that is designed to catch any liquid droplets that may travel through the piping. Pressure sensors and indicators mounted on this expansion tank keep track of the reactor pressure. Throughout the cyclonic condensing and cooling system **600** are differential pressure gauges. These gauges are used to identify any buildup or clog edge in the pipe or in any component of cyclonic condensing and cooling system **600**. The entire process is mounted on a bolted steel frame system. The frame system may utilize a standard A36 carbon steel frame, painted and equipped with matching connection clips for all corresponding equipment. The size and shape of the equipment is designed for quick breakdown and transport in a standard sea container.

(115) Accordingly, the disclosed cyclonic condensing and cooling system **600** improves on heat

exchanged technology as it does not require the bolting of the heat exchangers from end to end; takes up much less space than if the current technology was used; increases the surface area inside of the condensers that make up a heat exchanger; requires much lower velocity of the vapor when entering the condenser; allows for the continued release of the condensed liquid after the heat exchange and reaction, allowing the non-condensed vapors to move to the next condenser, and; prevents the build-up of char that could plug the tubes within the condensers.

(116) Heated Airlock Feeder Unit

(117) Disclosed embodiments improve on extruder technology as it allows for the continuous feeding of the reactor while using much less power, thus increasing efficiency and lowering the cost of production for the fuel product. This application relates to an apparatus that is part of a reusable fuel processing unit and allows for the continuous feeding of plastic into the unit since the apparatus described herein creates a process by which heat is tolerated in an anaerobic environment, atmospheric pressure does not leak in and out of the apparatus, air does not leak into the apparatus, and plastic in solid and heated liquid form does not cause problems within the apparatus downstream from the feeder.

(118) Accordingly, plastic waste material is shredded and fed into a pyrolysis reactor. Applied heat above 350 degrees Celsius causes the shredded plastic material to melt and vaporize. The heated airlock system is the apparatus in which the shredded plastic material is fed into the pyrolysis reactor. The main components of the heated airlock feeder system are the drive, coupling, gearbox, augers, housing, burner boxes, expansion cart, and support frame. It has been discovered that the prior art does not allow for the continuous feeding of heated plastic into the feeder while maintaining an air lock. Preferred examples of the disclosed invention include:

(119) Existing gear boxes, designed as short as possible to reduce material and labor on fabrication, have limited function with this utility patent application, as the short gear boxes are limited on taking a cantilever load as the force of trying to hold a long heavy shaft puts extreme pressure on the leading bearing resulting in reduction of the life of the bearing or requiring a heavy duty bearing to handle the force. If a heavy duty bearing is used, this results in a larger bearing creating large pockets in the gear box housing. The larger pocket reduces the ability of the housing to support the bearing, so in turn the housing will be made thicker. This increases the cost of a standard gear box. This design extends the space between the bearings and reduces load on the bearings. By spacing the bearings further apart, the cantilever load is reduced, the bearing size can be smaller and the housing can be thinner, reducing the overall cost and improving the performance. The further apart the points on connection on the bearings, the straighter the alignment on the shafts, reducing wear and increasing the life of the gear box;

(120) A flat bar attached between the cart and the frame that allows for the apparatus to expand and contract due to heat transfer as this apparatus incorporates thinner material in the reactor allowing for better heat transfer;

(121) Two heater zones, allowing plastic material to be transformed from a solid and shredded state to a liquid state; the solid and shredded plastic material at the start of the feeder and the liquid state at the end of the feeder. Between the shredded solid state and the liquid state exists plastic material in a molten state. The molten plastic material is thick and sticky and allows for the formation of the required pressure to create the airlock necessary to keep air from entering the reactor; and,

(122) The use of vapor gas (natural gas or syn-gas) and clamshell burners allowing for the external heat to be allowed in the processing of the plastic material whereas prior art used electric heater bands and internal pressure, resulting in high power consumption, to produce the heat required to process the plastic material. The use of vapor gas and clamshell burners allows for less power consumption, faster processing time, and more accurate and consistent heat production.

(123) The use of clamshell burners allows heat to be generated over the entire exterior surface of the penetrating pipe and allowing for access to the reactor tube. The use of the clamshell burners allows for a low profile to the interior reactor reducing the amount of space between the heat

source and the penetrating pipe surface, increasing the heat transfer without increasing the BTU value required by a burner system. The clamshell design combines both convection heat and radiant heat producing an even heat source around the penetrating pipe. The combining of the two types of heat is accomplished with the use of a perforated screen running the entire length of the penetrating tube and one third of the way up on the bottom inside of the clamshell burners. This design also prevents hotspots that normally occur in burner boxes. Another difference in this system compared to existing systems is that the igniting source is inside the clamshell burner box next to the perforated screen. The system contains flame sensors as well as a fan pressure switch to ensure airflow. Dual gas streams are used by adjusting the gas quantity or the air quantity, whereas existing systems use complicated air control dampers to adjust the air and gas ratio, that may cause uneven burning of the fuel creating irregular flame size. The clamshell design that is part of the heated airlock feeder is not lined with refractory on all surfaces, but only on the top half of the clamshell. The fact that the lower half of the clamshell is not lined with refractory allows any heat build-up to dissipate through the entire box surface. This design also reduces the chance of auto-ignition of the mixed gas.

(124) The disclosed embodiment allows the application of back pressure to the feed material between the cold material and the heated, melting material (molten plastic). The main components of the heated airlock feeder system are the drive, coupling, gearbox, augers, housing, clamshell burner boxes, expansion cart, and support frame. FIG. 1 depicts the entire assembly of the reusable energy reactor system. FIG. 17 depicts the heated airlock feeder that is part of the entire assembly of the re-useable energy reactor system. The drive system is a helical gear drive with a high torque ratio FIG. 17 at 1716. The gear drive is selected with the vertical footprint to reduce the system's overall length FIG. 17 at 1716. This drive is connected to a standard sheer coupling. This coupling is design to separate under overloading conditions to protect the gearbox. The coupling consists of two augers. The two augers FIG. 17 at 1602 are custom constructed. These augers are also depicted in FIG. 16. These augers are a machined three-part system. The first part of the augers are the drive shafts depicted in FIG. 16 at 1606 and 1608, one drive shaft being longer than the second drive shaft. These are elongated axially rotatable. The middle section of the augers are elongated, axially rotatable screws each having an elongated shaft with outwardly extending helical flighting along the one-half of the length of each shaft starting at the gear box FIG. 16 at 1602 and connecting to a axially rotating smooth surface auger where the smooth part of each auger at the output side of the apparatus are machined so that the space between each auger and the elongated tubular barrel housing 1702 is less than 1 inch.

(125) These augers are located inside FIG. 17 at 1702 which is inside FIG. 17 at 1720. One auger has left-hand flights, the other auger has right hand flights that overlap the left hand flights. One of the augers FIG. 17 at 1602 is longer than the other to protrude through the gearbox and connect to the drive coupling located in the gear box FIG. 17 at 1710. The augers are constructed from solid materials with connection slips for machining purposes. The augers are constructed in segments to reduce the material and labor cost to fabricate the assembly. The segments are also interchangeable for simpler fabrication. The gear drives in the gearbox 1710 are keyed into the shaft and sealed on both sides. The gearbox consists of double lip seals, bearings and spur gears. The length of the gearbox is extended to carry the cantilever load of the screw flights FIG. 17 at 1602 and 1604.

(126) All surfaces are machined on the contacting side of both items FIGS. 17 at 1602 and 1604 after welding. The housing FIG. 17 at 1702 is pre-welded before machining the interior to require a straight design. The connecting flanges at both ends and the inlet match the gearbox and the reactor bolt pattern. FIG. 17 at 1704 is machine tapered to reduce the outlet area to increase back pressure inside the heated airlock feeder (FIG. 17). This feeder assembly is welded to a reactor matching flange FIG. 17 at 1706 and then welded to the body of FIG. 17 at 1702. FIG. 17 at 1604 is welded to FIG. 17 at 1602 and then this entire assembly slides through the body of FIG. 17 at 1702 and protrudes flush to the end of FIG. 17 at 1704, the outlet ports. The gearbox and the assembly

housing rest on the support frame FIG. 17 at 1732. This assembly is bolted in the back is the main anchor point for the entire reactor. As the heated airlock feeder expands due to the heat it expands lengthwise. To address the expansion, this apparatus is supported with a cart to allow the machine to expand, without creating stress on the supports. Existing art used shorter sections that are bolted together and constructed from a very thick material to absorb the heat. This design used a thinner material for better heat transfer but requires a moveable support system.

(127) The solid, shredded plastic material (environmental temperature) is fed into the heated airlock feeder at 1708 on FIG. 17, the heat is applied at 1720 on FIG. 17, and the heated plastic material which is in a molten state is created from the solid shredded plastic material

(environmental temperature) at where 1602 connects to 1604 in FIGS. 17. 1602 and 1604, a continuous auger is located inside tubular barrel housing 1702 which is located inside 1720. The airlock is created at the end of 1604 in FIG. 17 from the back pressure from the solid, shredded plastic material (environmental temperature) pushing on it.

(128) This apparatus is used to induce heated plastic material into the main reactor and act as an airlock at the same time. By applying back pressure on the fed plastic material, between the solid, shredded plastic material and melting material (molten plastic material), a dead spot depicted on FIG. 17 at 1604 is created. At 1604 there are no flights on the shaft. This dead spot created by this process, depicted on FIG. 17 at 1604, allows molten plastic material to build up pressure by the incoming solid, shredded plastic material (environmental temperature) being fed into the apparatus at 1708 on FIG. 17. This area 1604 also has a larger shaft area, which fills the void between 1604 and 1702. This larger shaft increases the pressure inside creating an airlock effect. The discharge of the airlock feeder is also restricted at 1704 on FIG. 17 by the two openings that are greatly reduced in size compared to the opening where the solid, shredded plastic material (environmental temperature) is fed at 1708 on FIG. 17. When the feeder is shut down, the plastic material remains inside the feeder in area at 1604 on FIG. 17 because even as the feeder augers at 1602 on FIG. 17 continue to rotate, the plastic material will not be pushed out from the housing at 1702 on FIG. 17. The reason for this is because the heated molten plastic material is only pushed out when new solid, shredded plastic material (environmental temperature) is introduced. The incoming plastic material creates pressure and forces the molten plastic material in area 1604 to be displaced. This means that when the airlock feeder cools off, the remaining plastic material will turn to a solid and seal until the next run. When the next run occurs, this plastic material will melt when reheated and allow the augers at 1602 on FIG. 17 to rotate.

(129) This apparatus also heats the plastic material to a vapor and liquid state with a clamshell burner at 1720 on FIG. 17. The heating source for this airlock feeder are two clamshell heaters FIG. 17 at 1720. These two clamshell heater boxes produce the heat needed to make the airlock seal and start the vaporization of the plastic inside the feeder. The plastic material is heated from the discharge end to mid-way of the airlock feeder. By having two heater zones, the material is transformed from a liquid state on one end, to the shredded state on the other. Between this transition exist a molten plastic material. This molten plastic is thick and sticky and forms the needed pressure to create an airlock effect. These clamshell boxes come in contact with the airlock feeder with the seal FIG. 17 at 1724. This allows for greater expansion of the housing FIG. 17 at 1702 from the clamshell fire boxes because of boxes are insulated on the inside, not allowing the metal to expand as on the outside. The Heated Airlock Feeder has two clamshell box burners. One box covers FIG. 17 at 1604 of the internal auger, and the other heats the auger at 1602 of the auger. The advantage of two clamshell heater box burners is demonstrated on startup and shutdown of the reactor. Allowing the auger FIG. 17 at 1602 to cool to a point that a plastic seals is achieved to create the airlock needed for start-up a shut down. The molten plastic cools into a solid around the auger and the housing, sealing off the feeder. The ability to cool rapidly is also a big advantage of using clamshell heaters. The burners' flame can be extinguished and the fans may continue to run to cool the housing FIG. 17 at 1702.

(130) The clamshell burner boxes are used as the heated airlock feeder requires a continuous even supply of heat to produce molten plastic. The correct amount of controlled heat is vital to the process for consistent material flow. Processes of this nature require heat from all directions. The need for a high velocity airflow in a circular box would suffice for this process. Heater boxes with process structures penetrating through the box will also require a seal system to prevent leaks. Expansion of the penetrating structure in both length and diameter was considered in this design. The ability to both heat and cool are required in this process.

(131) The penetrating structure needs support capability to prevent damage to the heater box seals. The penetrating structure (pipe or tube) would need to be supported outside the heater boxes. Due to heat expansion on the penetrating structure a mobile support is required. The requirement for controlling the expansion direction is also needed to prevent warping of the penetrating structure and deflection that would damage the heater box seals requiring a controlled support system to restrict deflection in the direction that might damage the equipment. Furnace heater boxes are used in many processes to produce heat required for incinerating, cooking, melting, and for other heat required processes. When a cylinder or tube penetrates a heater box, problems with uneven heating, seal leakage and expansion may occur. Also the need to access the penetrating tube or pipe is required. A clamshell design was implemented for these reasons. The clamshell design allowed for a circular shape to match the profile of the penetrating pipe or tube. This close profile along with high velocity airflow ensures even heating around the penetrating pipe. The clamshell design has a very low profile interior to reduce the amount of space between the heat source and the penetrating pipe surface, increasing the heat transfer without increasing the BTU value required by a burner system. Compared to a standard burner box where a burner is attached on one side of the box at a distance not allowing an open flame to come into contact with the penetrating pipe, this design uses very small flame points to distribute the heat one third of the way around the penetrating pipe. This reduces the total BTU value.

(132) The disclosed design is modular construction for quick shop assembly and quick installation. This also allows for easy maintenance in the field. The modular design can be completely assembled and tested, for example, in an industry shop. Disclosed embodiments combine both types of heat, convection and radiant, producing an even heat source around the penetrating pipe. A perforated screen may be utilized to distribute the gas fuel and control the flame height while allowing airflow through the heater box. A burner package can be used to supply both the gas and air mixture for igniting. In the disclosed system, the igniting source is inside the clamshell burner box next to the perforated screen. A flame sensor is used to ensure ignition and a fan pressure switch is used to ensure airflow. Dual gases can be used by adjusting the gas quantity or the air quantity as discussed below. Existing systems use complicated air control dampers to adjust the air to gas ratio, causing uneven burning of the fuel creating irregular flame size. The air velocity and pressure must be at a fixed rate to insure the mix gas exits the perforated holes as needed as not to allow for the mix gas to ignite under the perforated screen.

(133) The disclosed design overcomes the aforementioned problem by stopping the gas flow and allowing the air to continue when the temperature is over a given set-point. When the system cools to a low set-point, gases are allowed back into the mix and reignited. This control is achieved with a standard PIO controller with thermocouples to indicate internal temperatures. The clamshell design allows for access to the refractory liner that is installed only on the top half of the clamshell. All known heater boxes are normally lined with refractory on all surfaces. The lower half of this clamshell has no refractory liner, allowing any heat buildup to dissipate through the box surface and it ensures that the surface temperature remains below the auto ignite point. The perforated screen acts as a pressure regulator between the mixed gas and the flame above. This chamber is being fed with ambient air and mixed gas, both at ambient temperature. This keeps the lower half of the clamshell cooler. Without refractory on the lower clamshell, refractory replacement is not needed.

(134) The radiant heat from the flame is not in contact with the bottom portion of the penetrating tube FIG. 17 at 1702. The airflow from the burner forces air around the penetrating tube carrying heat completely around the penetrating tube because of natural disturbance. The movement of this air regulates the radiant heat surface of the penetrating tube by pulling excessive heat into the airstream forcing the air around the penetrating tube through an exhaust port. The perforated screen has small flames running the entire length and one third around the penetrating tube. This prevents hotspots that normally occur in burner boxes. By heating the penetrating tube in all directions expansion occurs in all directions.

(135) To prevent deflection or misalignment of the penetrating tube while being heated, the expansion direction is controlled with a support system. The support attaches to the expansion tube and prevents movement from unwanted directions. As shown, for example in FIGS. 17 and 20, the cart 2006 consists of cam followers that are pinched between two structural flat bars, one on each side of the cart. The cart width is designed so that it is within one-eighth of an inch in between the width of the two structural flat bars so that it drops between the structural flat bars and ensures lateral movement. The cam followers (rollers) support the weight of the penetrating tube while preventing it from expanding up or down. This allows for the control of expansion direct action is in a lateral movement only. Typical pipe support rollers allow expansion in multiple directions. This design restricts expansion to lateral movement only keeping the penetrating tube from misaligning.

(136) The assembly is mounted on a steel skid mount frame FIG. 17 at 1732. The clamshell heater boxes consist of an upper FIG. 17 at 1720 and lower FIG. 17 at 1726 section. These sections are connected with a matching bolted flange and a seal chamber, FIG. 17 at 1724 that encompasses the penetrating tube. The gas air inlet box is mounted on the bottom section FIG. 17 at 1726 to allow air gas mix into the lower section. The lower section has a perforated metal screen FIG. 17 at 1734 welded 3 inches above the lower section FIG. 17 at 1726. This acts as an air chamber to distribute mixed air and gas through the perforated screen. The amount and diameter of the holes in the perforated screen are vital to control the flame height while allowing the volume of gas and air mix to pass through. The lower clamshell FIG. 17 at 1726 also has an air mixture box FIG. 17 at 1728 and the burner connection port FIG. 17 at 1740 connected to it. The mixer box FIG. 17 at 1728 has a flared configuration to distribute the air gas mix evenly under the perforated screen FIG. 17 at 1734. The mixer box FIG. 17 at 1728 creates some back pressure to the air gas mixture which ensures a consistent gas air ratio for each opening in the perforated screen FIG. 17 at 1734. A burner can be connected to the port FIG. 17 at 1740. The burner igniter, along with the flame indicator, is located to the top of the perforated screen FIG. 17 at 1734. An access pipe FIG. 17 at 1736 is used to penetrate through both the lower clamshell FIG. 17 at 1726 and the perforated screen FIG. 17 at 1734, for an igniter and for the flame sensor FIG. 17 at 1738 to be mounted. A continuous pilot light FIG. 17 at 1738 is installed through this pipe and stops above the perforated screen FIG. 17 at 1734. The pilot light proof of flame is required to indicate a flame is present until gas is allowed into the air gas mixture.

(137) When the heat set point is reached the gas alone, from the air gas mixture, ceases while the fan continues to run and push fresh air through the burner box. The pilot light continues to run in this phase of the heating process. Control of the heat is used with a PID controller. This controller is fed by thermocouples located on the top clamshell FIG. 17 at 1720. A wide range of temperatures can be achieved and controlled with this type of process. The ability to switch between fuel gases is also possible with this design. Two sets of solenoid valves located on the burner FIG. 17 at 1742 and have adjustable orifices to allow a fixed amount of gas to enter into a consistent amount of air. Natural gas mixed with air requires a different air mix ratio than syn-gas would require with the same air volume. Adjustment of the fixed orifices allow for switching between the gases. The expansion of the penetrating tube FIG. 17 at 1702 is controlled by the cart support FIG. 17 at 1718. This cart consists of heavy metal plate construction, resting between two flat bar retainers FIG. 17

at **1746** that are welded to a frame **FIG. 17** at **1732**. This allows the cam followers to roll on a smooth surface, preventing up and down movement. The cart width is only 118" less than the space between the flat bars **FIG. 17** at **1748**, preventing side to side movement and up and down movement while allowing left to right movement only.

(138) By preheating and vaporizing the plastic biomass material under positive pressure and high heat, the main reactor depicted in **FIG. 1** is shortened by about 40 feet to acquire the same performance as a standard reactor section would do. This reduces the reactor (**FIG. 1**) expansion length along with the auger **FIG. 17**. This reduction in size increases the torque in this area as the auger is shorter. The auger on the upper reactor depicted in **FIG. 1** at **1** is where the most torque is required due to the large amount of liquid plastic contained within the reactor. The further the plastic travels down the reactor depicted in **FIG. 1**, the more plastic material is converted to vapor and the less the auger has to work.

(139) The burner boxes depicted in **FIG. 17** at **1720** are in two section. This allows for controlled heat zones. This control is needed to maintain the airlock effect during startup and shut down of the reactor. As the reactor heats up, it will start to build pressure inside. This pressure will look for a way out of the reactor. First is the heated reactor feeder that is the apparatus that is the subject of this patent application depicted in **FIG. 17** and the second and third areas where the pressure may leave the system is at the ash discharge depicted in **FIG. 19** and at the and the ash or char separator **1800** depicted in **FIG. 18**. The char discharge system **1902** in **FIG. 19** is a seal with slide gates preventing vapor loss. The char separator **1800** depicted in **FIG. 18** allows the vapors to be removed.

(140) Char Separator

(141) The char, or carbon ash, is created when the shredded plastic that enters the reactor makes contact with the reactor's hot surface area. As the shredded plastic makes contact with the reactor's hot surface, it is thinly spread across the surface of the reactor and heat from the reactor vaporizes the shredded plastic by the disclosed design.

(142) A thin layer of the shredded plastic, as well as the contaminants contained within the shredded plastic, is left behind on the reactor's steel tubing and as is cooked to a solid char which then becomes airborne. Small particles of char, e.g., approximately 3 microns or smaller, become airborne and travel with the fuel vapors. This char is collected with the vapors and condensed into a liquid in high concentrations and makes the produced fuel a substantially, and in some cases, an extremely thick liquid, because the char is a solid particulate contained within the liquid. This particular carbon char is required to be removed from the fuel in order to produce a higher quality fuel.

(143) In one exemplary embodiment, the char separator of the disclosed application not only addresses but substantially eliminates the problems of the prior art, as discussed above. The char separator may serve as a vapor refining system for further processing or refining the fuel generated by the disclosed system. Turning to **FIG. 18**, char separator **1800** consists of a plurality of screw-type conveyor augers **1822** running in a vertical split tube **1820** that are placed so that their respective flights intersect with each other. Vertical split tube **1820** may be regarded as a support tube structure for accommodating and providing a degree of protection to additional structures, as described below. In one disclosed embodiment, three screw conveyor augers **1822** are utilized in within vertical split tube **1820**. Augers **1822** may comprise stainless steel of any grade. Augers **1822** provide for a downward rotation, cleaning each other from buildup as their flights intersect. As the hot vapors leave the reactor and enter the vertical split tube **1820**, they travel upwardly therein. The vapors lose heat as they rise up vertical split tube **1820**. The temperature in the column is controlled so that the favored hydrocarbon chain vapors pass through vertical split tube **1820** and leave vertical split tube **1820** at the discharge **1816** where the vapors are collected. As the vapors rise and the temperature of the vapors is reduced to the value at where a high carbon chain fuel will condense, it will collect on the augers **1822** where augers **1822** will push the condensed fuel back

to the reactor. The temperature of the vapor is dependent on a set point of the reactor which may vary in accordance with achieving a prescribed fuel boiling point(s). For example, in an exemplary embodiment, the vapor set point temperature may be established at approximately 700 F-800 F. The flow pattern of the vapors through char separator **1800** generally follows the auger profile of the three augers **1822** as it rises through the unit before it is exhausted.

(144) The condensed hydrocarbon fuel is a sticky substance and may be generally classified as a heavy tar with carbon particles. The vapors flowing in vertical split tube **1820** will travel across the sticky hydrocarbon fuel condensed on augers **1822** where the sticky substance will catch the carbon ash that is traveling with the vapors as the carbon ash is constantly looking for a substance to which to make contact. The collected mass on augers **1822** is then forced down into a lower reactor (e.g., separate system, not shown) where it returns to the reactor's heat returns to a heat zones through the discharge flange **1824**. The collected mass is then reheated in the lower reactor (e.g., separate system, not shown) of the re-useable fuel apparatus in which it vaporizes, breaking high carbon chains into lower carbon chains. The lower carbon chain material will then travel back through vertical split tube **1820** and any carbon ash that travels with it will stick again to augers **1822** and be returned and any lower carbon vapors will pass through vertical split tube **1820** and be discharged from exhaust port **1816** as clean vapor, for example, ultimately to a fuel cooling system. Thus, the clean vapor can be routed through a distillation column and/or a condensing unit in order to condense or cool down the condensable part of the vapor stream back to a liquid. The condensed liquid forms a diesel fuel carbon chain hydrocarbon which is an end product of the entire process.

(145) The amount of heat rise in vertical split tube **1820** can be controlled by both the RPM of the augers and the outside insulation of the column. For example, the column can be insulated by lagging on the outside to hinder heat dissipation to the surrounding. A drive system is provided to enable augers **1822** within vertical split tube **1820**. The drive system may include an auger gearbox drive **1806** that utilizes gearing to drive and control augers **1822**. In one embodiment, auger gearbox drive **1806** utilizes spur gears to control the rotation and timing of the augers **1822**. By controlling the heat in vertical split tube **1820** the carbon-chain hydrocarbon fuel selected by the heat value chosen will be allowed to pass through. Vapors comprised of condensable and noncondensable hydrocarbons can be cleaned of carbon char by the char separator **1800**, since the augers **1822** can be configured to rotate against the vapor flow. By adjustment of ample speed, various parameters can be achieved towards a desired point or outcome.

(146) Construction of vertical split tube **1820** may consists of a plurality of split tubes. In one disclosed embodiment, three split tubes **1820** may be utilized to encircle the augers, for example, as a prescribed geometrical shape such as a clover design in a final assembly depicted in FIG. **18**. A clover design shape is utilized by select embodiments, because the augers **1822** need to mesh into each other so that self-cleaning can be achieved. While a clover design is illustrated in FIG. **18**, it is readily appreciated that any design shape suitable for providing an enclosed supported structure may be utilized in the disclosed embodiment as necessary. Accordingly one skilled in the art may utilize more than three augers **1822** with accompanying different shapes to form an overall outer tube around the same. The shape is welded together and supported with a plurality of outer support bands or rings **1826** to keep and maintain the overall shape of three split tubes **1820** thereby keeping the assembled split tube structure intact throughout exposure to and/or due to heat warping.

(147) Gearbox drives **1806** may be accommodated within/throughout gearbox housing **1808**, to drive screw augers **1822** via connected drive shafts of the screw augers **1822**. In one disclosed embodiment, gearbox housing **1808** is designed with a packing seal space or air gap **1810** disposed within gearbox housing **1808**, as further described below. Gearbox housing **1808** may also comprise a support flange and seal **1812** for connecting to an exhaust housing **1814**, detailed below.

(148) A connecting flange **1818** may be provided at one end of vertical split tube **1820**. An exhaust system provided as exhaust housing **1814** having a corresponding attachment flange **74a** at one end

may be provided to attach to connecting flange **1818** to provide a final connection. In the illustrated exemplary embodiment, exhaust port **1816** is disposed in a side of exhaust housing **1814**. Another corresponding attachment flange **71a** may be provided at another end of exhaust housing **1814** for providing a final corresponding connection with support flange and seal **1812** of gearbox housing **1808**. Vertical split tube **1820** may provide a discharge flange **1824** at another end configured for connection with, for example, another reactor (e.g., separate system, not shown). A plurality of support rings **1826** may be disposed at intermediate points along a length of vertical split tube **1820** to provide support thereto and facilitate maintaining an outer peripheral shape of vertical split tube **1820**. The inner periphery of each support ring **1826** may correspond to an outer peripheral shape of vertical split tube **1820**.

(149) A thermal expansion system is provided as an expansion cart or rolling cart **1828**. Expansion cart **1828** may be provided with cam followers **1830**. In one disclosed embodiment expansion cart **1828** is disposed around a section of vertical split tube **1820**. In some select embodiments, vertical split tube **1820** may be secured to expansion cart **1828** (such as via a welded connection). As further described below, expansion cart **1828** is employed and designed to support char separator **1800** in connection with the support structure of re-usable energy reactor system **100**. In addition, while supporting char separator **1800**, expansion cart **1828** allows movement of char separator **1800** in accordance with any thermal expansion or contraction of the support structure of re-usable energy reactor system **100** due to temperature fluctuations.

(150) The discharge gases are expected to be over 500 degrees Fahrenheit and may overheat the gear box **1808**. To prevent the gearbox oil from overheating a ventilation system is provided as an air gap **1810** and therefore serves as a design feature in the unit to allow venting. Vertical split tube **1820** is attached to the lower reactor and is configured to travel or move in accordance with and to accommodate any thermal expansion of the reactor. To do so, an expansion cart or rolling cart **1828** is disposed generally at a top of vertical split tube **1820**. Expansion cart or rolling cart **1828** is further configured in supported relation along an exterior structure such as the framing of a re-usable energy reactor system **100** (FIG. 1). In one exemplary disclosed embodiment, rolling cart **1828** is configured with wheels received by corresponding tracks disposed, for example, along an accommodating structure of re-usable energy reactor system **100**. The tracks may comprise a rigid design sufficient to accommodate the weight of char separator **1800**. Since the char handler is bolted directly to the bottom reactor (which expands, contracts or elongates due to temperature fluctuations) as the reactor expands, rolling cart **1828** can roll on its associated wheels in accordance with any thermal expansion to cater to expansion in a prescribed direction.

(151) Where the column attaches to re-usable energy reactor system **100**, that section of the reactor is smaller in diameter and uses a ribbon type flight to allow for faster removal of solids while allowing vapors to pass back through the ribbon flights. This section has a reverse rotation to the main auger located within the reactor where the main auger is pushing any dry char or heavy fuel deposits towards the char discharge. This section of the main reactor has two controlled heated zones that will re-heat and help in thermal cracking the high carbon chains that are pushed back into the main reactor by char separator **1800**.

(152) Process Flow

(153) The principle characteristics of the disclosed embodiment provides continuous feed process, feedstock flexibility, and does not require a catalyst in its pyrolysis process of turning plastic waste into liquid fuel. The disclosed system overcomes some of the problems associated with prior art designs due to its continuous use and higher efficiency of heat exchange.

(154) In the case of plastic bags, a pinch conveyor depicted on FIG. 2 at **1a** and at **2a** compress the bags into an opening as depicted on FIG. 2 at **3** and introduce them into a de-stoner hood. The bags are then conveyed through a duct work depicted on FIG. 2 at **6** into the receiving hopper depicted on FIG. 2 at **9**. The de-stoner unit can be used on plastic bags, ground plastic, and shredded plastic. The incoming conveying air through the duct depicted on FIG. 2 at **6** will lift the plastic but will

allow heavier objects like rocks and metal to fall out of the opening depicted on FIG. 2 at 5. Once the plastic material is moved into the receiver depicted on FIG. 2 at 9 it drops into the ram section depicted on FIG. 2 at 11 while the ram is pulled back by the air cylinder depicted on FIG. 2 at 13 allowing the plastic to drop into the chamber. A photo-eye depicted on FIG. 2 at 10 indicates the height of plastic. By blinding the opening depicted on FIG. 2 at 11 with the ram, it can stop the air from conveying material and can stop the ram depicted on FIG. 2 at 12 pushing the material into the bag press depicted on FIG. 2 at 15.

(155) The bag press depicted on FIG. 3 is a set of twin augers with a large center diameter. The large center diameter is used so that the bags do not wrap around the center drum and plug the auger. The bags are pushed down the housing and compressed in the location shown on FIG. 2 at 18. As the bags are being forced downward, pressure causes the motor depicted on FIG. 2 at 16 to stop and to trip a current transducer depicted on FIG. 2 at 17 stopping the drive. When this drive stops, the ram movement stops and the conveying of material stops when high level is made and picked up by the photo-eye depicted on FIG. 2 at 10.

(156) The drive on the bag press depicted on FIG. 2 at 16 is on a timer that continues to push bags downward to the discharge area depicted on FIG. 2 at 18. When the drive depicted on FIG. 2 at 16 timer runs out, the motor drive depicted on FIG. 2 at 16 will try to rotate the auger depicted on FIG. 2 at 15. If the auger depicted on FIG. 2 at 15 continues to turn, indicating low material (low back pressure) inside the hopper area depicted on FIG. 2 at 18, then the feeding process reactivates.

(157) The gate depicted on FIG. 2 at 19 opens to allow plastic material to flow into the heated airlock below and is used for start-up and shut down purposes. As the material flows into the heated airlock, volume is relieved in the bag press depicted on FIG. 2 at 10 allowing for more product to be introduced into the bag press depicted on FIG. 3 via the ram. The material flowing out of the bag press is pushed into the heated airlock. This material is then pushed by a twin set of augers to the heating chambers depicted on FIG. 2 at 23 and 24. As the chambers heat the plastic, the plastic melts filling the auger housing, creating an airlock by sealing the auger to the side walls with plastic.

(158) A continuous flow of input plastic maintains the airlock seal. As the area between the melted plastic and the solid plastic is under pressure, this seals the reactor and stops the introduction of air into the reactor and prevents gasses from exiting through the inlet. The heat in the zone depicted on FIG. 2 at 24 starts to vaporize the material. The vaporized material, along with any liquid plastic, enters the next section of the reactor. The plastic is then conveyed down the reactor tube with a double flight cut and fold screw auger. The reactor is wrapped in heater boxes that create heat to vaporize the material inside the reactor tube as the material is being conveyed. The plastic material along with any vapors dropped from the upper reactor to the lower reactor continue to be conveyed to the end of the lower reactor. An opening in the lower reactor depicted on FIG. 2 at 42 is the location where any Char will fall onto a conveyor that will remove it from the reactor to a double gated hopper airlock system. The vapors continue through the reactor through an Ash Separator Tower depicted on FIG. 13.

(159) The char removing system depicted on FIG. 2 at 39 allows the molten plastic to slightly cool, causing heavy carbon chain fuel to stick to the triple screw augers depicted on FIG. 2 at 38 inside the column depicted on FIG. 2 at 39. The screw conveyors inside the column depicted on FIG. 2 at 38 rotate in a downward direction. The screw flights are interlocked within one another allowing for self-cleaning and to push any materials collected on the flights back into the reactor below depicted on FIG. 2 at 40.

(160) The material is pushed into the reactor depicted on FIG. 2 at 40 by a reverse screw conveyor depicted on FIG. 2 at 41 that is situated below the reactor. The screw conveyor depicted on FIG. 2 at 41 is a ribbon type screw that allows vapor to pass through the flights and up through the char remover depicted on FIG. 2 at 39. This ribbon type screw also allows solid particles to drop to the bottom and be conveyed back to the Char discharge area depicted on FIG. 2 at 42. Any heavy fuels

pushed down from the Char Separator that enter this chamber will be reheated, re-vaporized, and re-cracked to make lighter fuel that is passed back through the Char separation column depicted on FIG. 2 at **38**. Once the vapors pass through Char separating chamber depicted on FIG. 2 at **38** the vapors enter the cooling system depicted on FIG. 6.

(161) The first stage of this cooling system depicted on FIG. 2 at **52** is a standard cyclone that allows for some cooling to take place and collect heavier fuels. This heavy fuel can be returned to the reactor for re-cracking. After passing through the first cyclone, the vapors continue on and pass through the cyclone depicted on FIG. 2 at **52** and then enter the cyclone depicted on FIG. 2 at **53** as the vapor continues to cool. This cooling causes vapors to condense and be collected in the bottom hopper of the cyclone to be delivered to the holding tank depicted on FIG. 2 at **61**. This holding tank allows the light fuels, such as benzene, to be removed. A pump depicted on FIG. 2 at **57** pumps the benzene to a coiling condenser depicted on FIG. 8 and FIG. 2 at **68**. The vapors that remain will continue on the path through three more cyclones depicted on FIG. 2 at **53** for continuous cooling separation of the fuel. The last three cyclones contain internal force rotation fins depicted on FIG. 7.

(162) After passing through the aforementioned three cyclones, the vapors leave the last cyclone through a duct depicted on FIG. 2 at **64** that feeds into an air forced heat exchanger depicted on FIG. 2 at **77** and FIG. 6. The gas is then pushed from that point into a bubbler system depicted on FIG. 2 at **66** where particles are separated from the gas and the gas is scrubbed of unwanted chemicals. The first bubbler depicted on FIG. 2 at **66a** contains water which will separate sulfur present in the syn-gas. The gas will bubble through the water which also acts as a flame arrestor. The syn-gas then passes into the second bubbler depicted on FIG. 2 at **66b** which contains caustic soda. The caustic soda will capture any chlorine gas that may be present in the syn-gas and convert the chlorine gas into salt that will settle to the bottom of the tank for removal. The gases that remain will be syn-gas that passes into an expansion buffer tank depicted on FIG. 2 at **67** then through a coil condenser chiller depicted on FIG. 2 at **68**.

(163) The coil condenser chiller is a coil type that uses glycol for heat exchange which reduces the remaining gas temperature to a temperature of 10° F. At this temperature no atmospheric condensable gases remain. The gases flow from the chiller depicted in FIG. 2 at **68** then they are piped as depicted in FIG. 2 at **71** to the syn-gas booster system depicted on FIG. 2 at **80**. This gas can be used to generate electricity to power the system. This gas will also be used as fuel for the clam shell burners depicted in FIG. 7.

(164) The syn-gas is boosted using the pump compressor depicted on FIG. 2 at **80** and forced into a holding tank depicted on FIG. 2 at **88**. This holding tank builds pressure and is relieved with the pressure regulators depicted on FIG. 2 at **73** and allowed to return to the burners acting as the fuel heat source for the reactors. Excessive pressure may be relieved at **74** depicted on FIG. 2 and allowed to travel to a safety burner depicted on FIG. 2 at **26** where the gases may be incinerated or directed to a gas powered generator to produce electricity.

(165) Pressure safety regulators and bypasses are installed on the system in the event of a power failure. This will allow syn-gas to be re-directed for a short period of time while the reactor cools. The reactor ceases producing syn-gas within a couple of minutes due to heat loss and the fact that the internal gas pressure lowers as the reactor is cooling. The syn-gas stored in the booster tank depicted on FIG. 2 at **88** will allow the system to start on the next run from a cold start. The storage capacity allows for the system to power itself after the initial start-up. At the time of the initial (first time) start-up the system uses an auxiliary gas supply of propane as no syn-gas has been produced by the reactor. The propane tank is depicted on FIG. 2 at **84**. This propane tank is a standard commercial propane tank and is used only for initial (first time) start-up. Once the system has been online and is operating properly the supplied syn-gas will be replenished for the next run.

(166) The clam shell burners depicted in FIGS. 13 and 17 are vented to the atmosphere by a series of ductwork and slip joints. The duct work is supplied with a fan depicted on FIG. 2 at **31** that pulls

fresh air from the point depicted on FIG. 2 at 29 through the ductwork. Each firebox discharges independently into this main ductwork.

(167) The entire system capacity is controlled by a computer. All of the essential motors depicted in FIG. 2 at 16, 21, 34, and 36 have a variable frequency drive (VFD) drive to allow for variable RPM. A fixed algorithm will control all velocities and temperatures based upon the algorithm's solution based upon the inputs into the algorithm. The char leaving the system at the point depicted on FIG. 2 at 42 leaves through a twin inclined screw conveyor designed in this manner to promote self-cleaning and heat loss. The gate depicted in FIG. 2 at 45 remains open as the hopper depicted in FIG. 2 at 46 is filled to the level indicator depicted in FIG. 2 at 47. The incline char screw depicted in FIG. 2 at 43 will stop and the gate depicted in FIG. 2 at 45 will close while the gate depicted in FIG. 2 at 48 opens allowing the screw conveyor depicted in FIG. 2 at 50 to start. This process is repeated to remove the char.

(168) The disclosed process relies on the reactor to expand. The following describes the expansion of the reactor: The plastic mass and vapors enter the reactor depicted in FIG. 9 and is pulled along the upper and lower reactor by double flighted screws that are designed with cut and fold slots depicted in FIG. 21. The science of the operation is Pyrolysis, which is the act of heating without the presence of oxygen. Therefore, there can be no direct contact of the plastic feedstock to the flame source. The heat from the clam shell heaters (depicted in FIG. 13) surround the reactor tube 1402 (depicted in FIG. 14) creates a high temperature zone that starts the reaction inside of the reactor tube 1402. The reactor tubes 1402 depicted in FIG. 14 will expand due to heat. As they expand they are only allowed to travel in one direction as they are anchored due to the heated airlock feeder depicted in FIG. 17 and are supported by the carts 2006 depicted in FIG. 20. The movement of the reactor is in a lateral direction due to the fact that it is anchored on one side. The tube steel frame depicted in FIG. 2 at 91 has flat bar landings for the carts that are used to travel upon. The upper reactor 1404 is tied to the lower reactor 1406, being fixed by the connecting collar 1408 between the upper and lower reactor. This causes the pulling of the lower reactor 1406 along as the reactor expands. The lower reactor 1406 expands in the opposite direction as it is being heated. The drives depicted in FIGS. 2 at 4 and 21 are located at the ends of the reactor tubes and are also attached on roller carts to allow allowing for expansion depicted in FIG. 20 at 2010. The char conveyor system depicted in FIG. 19 is attached to rollers allowing it to be pulled along with the reactor as the reactor expands.

(169) The advantage of the disclosed two stack reactor design described above is that stacking of the reactors allows for a system that is half the length dividing the expansion between the upper and lower reactor tubes depicted in FIG. 14. The second advantage of the design of this system is that the load on the screw augers inside the reactor is reduced by reducing the length and in turn, reducing the horse power stress.

(170) The process of turning the waste plastic into fuel involves heating the waste plastic inside the reactor. As the plastic is heated inside the reactor 1400 depicted in FIG. 14 it turns to a vapor. This vapor is forced to travel down the tubes from the upper reactor to the lower reactor, traveling the entire length. The vapor is also disturbed by the screw conveyor depicted in FIG. 21 inside the reactor causing a longer path to be created by the screw conveyor flights. This allows for heat to be applied to the vapor and plastic for a longer period of time. This extended dwell time is what causes the vapors to transform into the required c-chains required for the production of fuel. Thermal cracking is used to transform the vapor product into the fuel product required. The temperature and dwell time can be adjusted by adjusting the temperature applied to the burners as well by adjusting the velocity of the screw conveyors depicted in FIG. 21.

(171) The reactor 1400 depicted in FIG. 14 is heated by the clam shell heaters 1720 depicted in FIG. 13 causing the sidewall 1410 of the reactors to heat up. This heat is transferred into the plastic product as it comes into contact with the sidewalls. The screw conveyors depicted in FIG. 21 continue to wipe the product from the wall and move it downstream through the reactor. As any

remaining products from the plastic are carried along, they turn into char. Char does not contain any moisture vapor fuels. The char travels down the screw conveyor and enters the char discharge system **1900** depicted in FIG. **19**. To insure that vapors are not carried with the Char, the last two heating zones **1750**, **1752** are increased in temperature causing any remaining vapors to continue down the reactor and away from the char discharge system **1900**.

(172) The system of the disclosed embodiment is protected with a nitrogen purge system depicted on FIG. **2** at **87**. In the event of an emergency, nitrogen gas will be piped into the reactor as nitrogen is an inert gas that will displace oxygen and prevent any incoming oxygen from entering into the hot reactor, pressurizing the void inside the reactor. The nitrogen may also be used as a fire suppression system. The control valves depicted on FIG. **2** at **90** may be configured to open under power failure if needed. The nitrogen ports to the reactor are placed in locations where the heat and vapor are the most concentrated.

(173) Having described the many embodiments of the present invention in detail, it will be apparent that modifications and variations are possible without departing from the scope of the invention defined in the appended claims. Furthermore, it should be appreciated that all examples in the present disclosure, while illustrating many embodiments of the invention, are provided as non-limiting examples and are, therefore, not to be taken as limiting the various aspects so illustrated.

(174) All documents, patents, journal articles and other materials cited in the present application are incorporated herein by reference.

(175) While the present invention has been disclosed with references to certain embodiments, numerous modification, alterations, and changes to the described embodiments are possible without departing from the sphere and scope of the present invention, as defined in the appended claims. Accordingly, it is intended that the present invention not be limited to the described embodiments, but that it has the full scope defined by the language of the following claims, and equivalents thereof.

Claims

1. A pyrolysis system for processing plastic, comprising: an extruder comprising an elongate cantilevered drive shaft connected to a drive coupling, the drive shaft being housed in a tubular barrel housing surrounded at least partially by one or more clamshell heaters, wherein the drive shaft includes auger flights; and a reactor configured to process pre-processed material supplied via the extruder at an input end, the reactor comprising: a hollow upper reactor tube including a first screw conveyor within the hollow portion of the upper reactor tube, configured to receive the pre-processed material; a hollow lower reactor tube connected to the upper reactor tube via a connecting collar, including a second screw conveyor within the hollow portion of the lower reactor tube, configured to receive partially pyrolyzed material from the upper reactor tube; and a plurality of clamshell heaters surrounding the upper and lower reactor tubes, defining a plurality of individual heating zones.
2. The system of claim 1, wherein the extruder comprises a heated airlock.
3. The system of claim 2, further comprising a material supply assembly configured to supply plastic feedstock material to the heated airlock for pre-processing.
4. The system of claim 1, further comprising a vapor processing system comprising an ash separator or char separator, configured to receive vapor produced in the reactor.
5. The system of claim 1, wherein the first and second screw conveyors are configured to wipe melted material from a wall and move it downstream through the reactor.
6. The system of claim 5, wherein the first and second screw conveyors are further configured to carry char to a char discharge system attached proximate to an output end of the reactor.
7. The system of claim 1, wherein a subset of the plurality of individual heating zones positioned

proximate to an output end of the reactor are at a higher temperature than the other individual heating zones.

8. The system of claim 1, further comprising a thermal expansion system connected to at least one of the reactor and the extruder.

9. The system of claim 1, wherein the individual heating zones are separately regulated.

10. The system of claim 1, wherein the individual heating zones are separately powered.

11. The system of claim 1, wherein the extruder is configured to process the material to a liquid or molten state, and the reactor is configured to process the liquid or molten material received from the extruder into a gaseous state.

12. The system of claim 1, wherein the upper reactor tube is above the lower reactor tube.

13. The system of claim 1, wherein the reactor comprises a stacked reactor.

14. The system of claim 1, wherein the first screw conveyor is configured to convey material in a first direction.

15. The system of claim 14, wherein the second screw conveyor is configured to convey material in a second direction different from the first direction.

16. The system of claim 1, wherein the first and second screw conveyors comprise double flighted screws.

17. The system of claim 16, wherein the double flighted screws include cut and fold slots.

18. The system of claim 1, wherein the first and second screw conveyors are driven at variable revolutions-per-minute via variable frequency drive motors.

19. The system of claim 1, wherein the one or more clamshell heaters of the extruder produce heat that allows the extruder to seal and start vaporization of plastic inside the extruder.

20. The system of claim 1, wherein the one or more clamshell heaters of the extruder are configured to heat first and second sections of the tubular barrel housing to different temperatures.
