

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404652
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Schiwal; Branden

Loader lift arm

Abstract

Disclosed embodiments include power machines and related structures of lift arms, implement carriers, follower links, and driver links which improve manufacturability, reduce component failures, and improve power machine design and functionality. In some embodiments, lift arm structures include cast lower lift arm portions. The cast lower lift arm portions include contoured upper ends which are sleeved onto contoured lower ends of upper lift arm portions to control stress points and to reduce stresses on welds. The follower link structures can include follower links which are configured to be positioned at least partially outside of the lift arm structure to improve rear visibility. The driver link structures can be configured to be laterally overlapping with innermost surfaces on the lift cylinder, but configured such that as the lift arm is raised the laterally overlapping portions are moved above the innermost surfaces of the lift cylinder.

Inventors:	Schiwal; Branden (Bismarck, ND)
Applicant:	DOOSAN BOBCAT NORTH AMERICA INC. (West Fargo, ND)
Family ID:	62117012
Assignee:	Doosan Bobcat North America, Inc. (West Fargo, ND)
Appl. No.:	18/636849
Filed:	April 16, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240344293 A1	Oct. 17, 2024

Related U.S. Application Data

continuation parent-doc US 17185150 20210225 ABANDONED child-doc US 18636849
division parent-doc US 15957170 20180419 US 10934681 20210302 child-doc US 17185150

Publication Classification

Int. Cl.: **E02F3/38** (20060101); **B22D25/00** (20060101); **B22D25/02** (20060101); **E02F3/34** (20060101); **E02F3/36** (20060101); **E02F3/42** (20060101); **E02F3/627** (20060101); A01B63/24 (20060101)

U.S. Cl.:

CPC **E02F3/38** (20130101); **B22D25/00** (20130101); **B22D25/02** (20130101); **E02F3/3414** (20130101); **E02F3/3686** (20130101); **E02F3/382** (20130101); **E02F3/422** (20130101); **E02F3/627** (20130101); A01B63/24 (20130101)

Field of Classification Search

CPC: E02F (3/422); E02F (3/382); E02F (3/3686); E02F (3/3414); E02F (3/38)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1679879	12/1927	Russell	N/A	N/A
4141160	12/1978	Olson	N/A	N/A
4159796	12/1978	Braithwaite	N/A	N/A
4260322	12/1980	Cameron	N/A	N/A
4428173	12/1983	Knell	N/A	N/A
4904151	12/1989	Biemans et al.	N/A	N/A
5599158	12/1996	Ajilore	N/A	N/A
6106217	12/1999	Knell	N/A	N/A
6325589	12/2000	Jang et al.	N/A	N/A
6386822	12/2001	Burr	N/A	N/A
D468754	12/2002	Dershem et al.	N/A	N/A
6508019	12/2002	Sasaki et al.	N/A	N/A
6616398	12/2002	Dershem et al.	N/A	N/A
6637111	12/2002	Sasaki et al.	N/A	N/A
6851886	12/2004	Anderson	N/A	N/A
7264435	12/2006	Layko et al.	N/A	N/A
D600721	12/2008	Shimomura et al.	N/A	N/A
7824145	12/2009	Kisse	N/A	N/A
7881845	12/2010	Nichols	N/A	N/A
D646302	12/2010	Lanting et al.	N/A	N/A
D646303	12/2010	Lanting et al.	N/A	N/A
D654514	12/2011	Jamieson et al.	N/A	N/A
8342789	12/2012	Yasuda et al.	N/A	N/A
8419339	12/2012	Okumura et al.	N/A	N/A
8545163	12/2012	Yasuda et al.	N/A	N/A
8556014	12/2012	Smith et al.	N/A	N/A
8616318	12/2012	Kotani et al.	N/A	N/A

8631580	12/2013	Randall et al.	N/A	N/A
8821104	12/2013	Yasuda et al.	N/A	N/A
8992158	12/2014	Springer et al.	N/A	N/A
9945093	12/2017	Belliveau	N/A	N/A
2003/0082040	12/2002	Bares	414/680	E02F 9/24
2003/0126772	12/2002	Masumoto et al.	N/A	N/A
2004/0170472	12/2003	Anderson	N/A	N/A
2007/0104566	12/2006	Layko et al.	N/A	N/A
2008/0035357	12/2007	Heitlinger	N/A	N/A
2008/0175701	12/2007	Kisse	N/A	N/A
2010/0143086	12/2009	Yasuda et al.	N/A	N/A
2010/0158653	12/2009	Webb et al.	N/A	N/A
2011/0091307	12/2010	Yasuda	414/685	E02F 9/2275
2011/0299965	12/2010	Randall et al.	N/A	N/A
2013/0158836	12/2012	Smith et al.	N/A	N/A
2013/0216347	12/2012	Breuer et al.	N/A	N/A
2015/0003949	12/2014	Kusama	N/A	N/A
2015/0071752	12/2014	Carthy et al.	N/A	N/A
2015/0336778	12/2014	Ditzler et al.	N/A	N/A
2017/0086366	12/2016	Noll	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2947209	12/2014	EP	N/A
2010059683	12/2009	JP	N/A
2010059684	12/2009	JP	N/A
2008/118308	12/2007	WO	N/A
2010023715	12/2009	WO	N/A
2008/134820	12/2017	WO	N/A

OTHER PUBLICATIONS

Invitation to Pay Additional Fees And, Where Applicable, Protest Fee mailed Jul. 13, 2018 for International Application No. PCT/US2018/028290 filed Apr. 19, 2018, 12 pages. cited by applicant

International Search Report and Written Opinion mailed Sep. 25, 2018 for International Application No. PCT/US2018/028290 filed Apr. 19, 2018, 23 pages. cited by applicant

U.S. Patent Office issued prosecution for U.S. Application No. 15/957,170, filed Apr. 19, 2018, including: Notice of Allowance and Fees Due (PTOL-85) issued Dec. 15, 2020, 8 pages; Non-Final Rejection issued Jun. 29, 2020, 10 pages; Final Rejection issued Jan. 28, 2020, 11 pages; Non-Final Rejection issued Aug. 16, 2019, 9 pages; Requirement for Restriction/Election issued Mar. 29, 2019, 7 pages; 45 pages total. cited by applicant

Communication pursuant to Article 94(3) EPC for European patent application No. 18 723 164.2, dated Nov. 11, 2020, 4 pages. cited by applicant

Non-Final Rejection for U.S. Appl. No. 17/185,150, mailed Feb. 2, 2022, 8 pages. cited by applicant

Final Rejection for U.S. Appl. No. 17/185,150, mailed Sep. 29, 2022, 15 pages. cited by applicant

Communication pursuant to Article 94(3) EPC for European patent application No. 17 823 164.2, dated Sep. 30, 2021, 7 pages. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. application Ser. No. 17/185,150, filed on Feb. 25, 2021, which published as U.S. Publication No. 2021/0180286 A1, on Jun. 17, 2021, which is a divisional of U.S. application Ser. No. 15/957,170, filed on Apr. 19, 2018, which issued as U.S. Pat. No. 10,934,681 B2, on Mar. 2, 2021, which claims the benefit of U.S. Provisional Application No. 62/487,153, which was filed on Apr. 19, 2017, the contents of which are hereby incorporated in their entireties.

BACKGROUND

(1) The present disclosure is directed toward power machines. More particularly, the present disclosure is directed toward lift arm and related structures for moving or handling material with an implement mounted on the lift arm structure.

(2) Power machines, for the purposes of this disclosure, include any type of machine that generates power to accomplish a particular task or a variety of tasks. One type of power machine is a work vehicle. Work vehicles, such as loaders, are generally self-propelled vehicles that have a work device, such as a lift arm (although some work vehicles can have other work devices) that can be manipulated to perform a work function. Work vehicles include loaders, excavators, utility vehicles, tractors, and trenchers, to name a few examples.

(3) Power machines typically include a frame, at least one work element, and a power source that can provide power to the work element to accomplish a work task. One type of power machine is a self-propelled work vehicle. Self-propelled work vehicles are a class of power machines that include a frame, work element, and a power source that can provide power to the work element. At least one of the work elements is a motive system for moving the power machine under power.

(4) Typically, power machines include a lift arm structure pivotally mounted to the frame of the power machine, with one or more lift actuators coupled between the frame and the lift arm structure to raise and lower the lift arm structure during work operations. For example, the lift arm structure can be used to raise and lower a bucket to move material. Designing lift arm structures which are less complex to manufacture but which are sufficiently strong to endure high load stresses on the lift arm structure is challenging. Further, many lift arm structure designs adversely affect visibility for the operator of the power machine.

(5) The discussion above is merely provided for general background information and is not intended to be used as an aid in determining the scope of the claimed subject matter.

SUMMARY

(6) This Summary and the Abstract are provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. The summary and the abstract are not intended to identify key features or essential features of the claimed subject matter, nor are they intended to be used as an aid in determining the scope of the claimed subject matter.

(7) Disclosed embodiments include power machines, lift arm structures, implement carriers, follower link structures, and driver link structures which improve manufacturability of the power machine, reduce component failures of the power machine, and improve power machine design and functionality. In some exemplary embodiments, lift arm structures include cast lower lift arm portions which directly pivotally couple to cast implement carrier plates. The cast lower lift arm portions include contoured upper ends which are sleeved onto contoured lower ends of upper lift arm portions to control stress points and to reduce stresses on welds between the upper and lower lift arm portions. In some embodiments, the follower link structures include cast follower links which are configured to be positioned at least partially outside of the lift arm structure to improve

rear visibility for an operator of the power machine. In some embodiments, the driver link structures are configured to be at least partially laterally spaced from the frame of the power machine such that they laterally overlap with innermost surfaces on the lift cylinder, but such that as the lift arm is raised the laterally overlapping portions are moved above the innermost surfaces of the lift cylinder.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram illustrating functional systems of a representative power machine on which embodiments of the present disclosure can be advantageously practiced.
- (2) FIG. 2 is a front perspective view of a power machine on which embodiments disclosed herein can be advantageously practiced.
- (3) FIG. 3 is a rear perspective view of the power machine shown in FIG. 2.
- (4) FIG. 4 is a side view illustration of components of another power machine on which embodiments disclosed herein can be advantageously practiced.
- (5) FIGS. 5 and 6 are perspective view illustrations of a lift arm structure of the power machine shown in FIG. 4.
- (6) FIG. 7 is a perspective view of a cast lower lift arm portion of the lift arm structure illustrated in FIGS. 5 and 6 in accordance with exemplary embodiments.
- (7) FIG. 8 is a perspective view illustration of contoured ends of the cast lower lift arm portion and of a main or upper lift arm portion in accordance with some exemplary embodiments.
- (8) FIG. 9 is a first perspective view of a cast implement carrier plate in accordance with some exemplary embodiments.
- (9) FIG. 10 is a machine side view of the implement carrier plate shown in FIG. 9.
- (10) FIG. 11 is an end view of the implement carrier plate shown in FIG. 9.
- (11) FIG. 12 is a second perspective view of the implement carrier plate shown in FIG. 9.
- (12) FIGS. 13 and 14 are perspective views of an implement carrier assembly including two cast implement carrier plates as shown in FIG. 9, with a structural tube extending therebetween.
- (13) FIG. 15 is a perspective view illustration showing the exemplary implement carrier embodiment rotatably coupled to the cast lower lift arm portions.
- (14) FIG. 16 is a rear view illustration of a portion of the power machine showing a cast follower link configuration in accordance with some exemplary embodiments.
- (15) FIG. 17 is a partial perspective view of the power machine showing the follower link configuration of FIG. 16.
- (16) FIG. 18 is an illustration of the cast follower link members connected by a structural tube.
- (17) FIGS. 19-21 are side view illustrations showing a relational positioning of a pivot attachment between a driver link of the power machine and the lift arm structure relative to a top end of a lift cylinder base in accordance with some exemplary embodiments.
- (18) FIG. 22 is another illustration of the relationship between the driver link pivot and the base end of the lift cylinder in accordance with some embodiments.

DETAILED DESCRIPTION

(19) This discussion uses illustrative embodiments to disclose various concepts. These concepts, however, are not limited in their application to the details of construction and the arrangement of components in the illustrative embodiments and are capable of being practiced or being carried out in various other ways. The terminology in this document is used for the purpose of description and should not be regarded as limiting. Words such as “including,” “comprising,” and “having” and variations thereof as used herein are meant to encompass the items listed thereafter, equivalents thereof, as well as additional items.

(20) The disclosed embodiments include power machines, lift arm structures, implement carriers, follower link structures, and driver link structures which improve manufacturability, reduce component failures, and improve power machine design. In some exemplary embodiments, lift arm structures include cast lower lift arm portions. The cast lower lift arm portions can be directly pivotally coupled to cast implement carrier plates. The cast lower lift arm portions can include, in some embodiments, contoured upper ends which are sleeved onto contoured lower ends of upper lift arm portions to control stress points and to thereby reduce stresses on welds between the upper and lower lift arm portions.

(21) In some embodiments, the follower link structures include cast follower links which are configured to be positioned at least partially outside of the lift arm structure to improve rear visibility for an operator of the power machine. Also, in some embodiments, the driver link structures are configured to be at least partially laterally spaced from the frame of the power machine such that they laterally overlap with innermost surfaces on the lift cylinder, but such that as the lift arm is raised the laterally overlapping portions are moved from below the innermost surfaces of the lift cylinder to above the innermost surfaces of the lift cylinder such that the driver link does not damage the lift cylinder. This allows for more efficient use of space to improve design features without requiring the width of the power machine to be increased.

(22) These concepts can be practiced on various power machines, as will be described below. A representative power machine on which the embodiments can be practiced is illustrated in diagram form in FIG. 1 and one example of such a power machine is illustrated in FIGS. 2-3 and described below before any embodiments are disclosed. However, as mentioned above, the embodiments below can be practiced on any of a number of power machines, including power machines of different types from the representative power machine shown in FIGS. 2-3.

(23) Power machines, for the purposes of this discussion, include a frame, at least one work element, and a power source that can provide power to the work element to accomplish a work task. One type of power machine is a self-propelled work vehicle. Self-propelled work vehicles are a class of power machines that include a frame, work element, and a power source that can provide power to the work element. At least one of the work elements is a motive system for moving the power machine under power.

(24) FIG. 1 shows a block diagram illustrating the basic systems of a power machine **100** upon which the embodiments discussed below can be advantageously incorporated and can be any of a number of different types of power machines. The block diagram of FIG. 1 identifies various systems on power machine **100** and the relationship between various components and systems. As mentioned above, at the most basic level, power machines for the purposes of this discussion include a frame, a power source, and a work element. The power machine **100** has a frame **110**, a power source **120**, and a work element **130**. Because power machine **100** shown in FIG. 1 is a self-propelled work vehicle, it also has tractive elements **140**, which are themselves work elements provided to move the power machine over a support surface and an operator station **150** that provides an operating position for controlling the work elements of the power machine. A control system **160** is provided to interact with the other systems to perform various work tasks at least in part in response to control signals provided by an operator.

(25) Certain work vehicles have work elements that can perform a dedicated task. For example, some work vehicles have a lift arm to which an implement such as a bucket is attached such as by a pinning arrangement. The work element, i.e., the lift arm can be manipulated to position the implement for performing the task. The implement, in some instances can be positioned relative to the work element, such as by rotating a bucket relative to a lift arm, to further position the implement. Under normal operation of such a work vehicle, the bucket is intended to be attached and under use. Such work vehicles may be able to accept other implements by disassembling the implement/work element combination and reassembling another implement in place of the original bucket. Other work vehicles, however, are intended to be used with a wide variety of implements

and have an implement interface such as implement interface **170** shown in FIG. **1**. At its most basic, implement interface **170** is a connection mechanism between the frame **110** or a work element **130** and an implement, which can be as simple as a connection point for attaching an implement directly to the frame **110** or a work element **130** or more complex, as discussed below.

(26) On some power machines, implement interface **170** can include an implement carrier, which is a physical structure movably attached to a work element. The implement carrier has engagement features and locking features to accept and secure any of a number of implements to the work element. One characteristic of such an implement carrier is that once an implement is attached to it, it is fixed to the implement (i.e. not movable with respect to the implement) and when the implement carrier is moved with respect to the work element, the implement moves with the implement carrier. The term implement carrier as used herein is not merely a pivotal connection point, but rather a dedicated device specifically intended to accept and be secured to various implements. The implement carrier itself is mountable to a work element **130** such as a lift arm or the frame **110**. Implement interface **170** can also include one or more power sources for providing power to one or more work elements on an implement. Some power machines can have a plurality of work element with implement interfaces, each of which may, but need not, have an implement carrier for receiving implements. Some other power machines can have a work element with a plurality of implement interfaces so that a single work element can accept a plurality of implements simultaneously. Each of these implement interfaces can, but need not, have an implement carrier.

(27) Frame **110** includes a physical structure that can support various other components that are attached thereto or positioned thereon. The frame **110** can include any number of individual components. Some power machines have frames that are rigid. That is, no part of the frame is movable with respect to another part of the frame. Other power machines have at least one portion that is capable of moving with respect to another portion of the frame. For example, excavators can have an upper frame portion that rotates with respect to a lower frame portion. Other work vehicles have articulated frames such that one portion of the frame pivots with respect to another portion for accomplishing steering functions.

(28) Frame **110** supports the power source **120**, which is capable of providing power to one or more work elements **130** including the one or more tractive elements **140**, as well as, in some instances, providing power for use by an attached implement via implement interface **170**. Power from the power source **120** can be provided directly to any of the work elements **130**, tractive elements **140**, and implement interfaces **170**. Alternatively, power from the power source **120** can be provided to a control system **160**, which in turn selectively provides power to the elements that capable of using it to perform a work function. Power sources for power machines typically include an engine such as an internal combustion engine and a power conversion system such as a mechanical transmission or a hydraulic system that is capable of converting the output from an engine into a form of power that is usable by a work element. Other types of power sources can be incorporated into power machines, including electrical sources or a combination of power sources, known generally as hybrid power sources.

(29) FIG. **1** shows a single work element designated as work element **130**, but various power machines can have any number of work elements. Work elements are typically attached to the frame of the power machine and movable with respect to the frame when performing a work task. In addition, tractive elements **140** are a special case of work element in that their work function is generally to move the power machine **100** over a support surface. Tractive elements **140** are shown separate from the work element **130** because many power machines have additional work elements besides tractive elements, although that is not always the case. Power machines can have any number of tractive elements, some or all of which can receive power from the power source **120** to propel the power machine **100**. Tractive elements can be, for example, track assemblies, wheels attached to an axle, and the like. Tractive elements can be mounted to the frame such that movement of the tractive element is limited to rotation about an axle (so that steering is

accomplished by a skidding action) or, alternatively, pivotally mounted to the frame to accomplish steering by pivoting the tractive element with respect to the frame.

(30) Power machine **100** includes an operator station **150** that includes an operating position from which an operator can control operation of the power machine. In some power machines, the operator station **150** is defined by an enclosed or partially enclosed cab. Some power machines on which the disclosed embodiments may be practiced may not have a cab or an operator compartment of the type described above. For example, a walk behind loader may not have a cab or an operator compartment, but rather an operating position that serves as an operator station from which the power machine is properly operated. More broadly, power machines other than work vehicles may have operator stations that are not necessarily similar to the operating positions and operator compartments referenced above. Further, some power machines such as power machine **100** and others, whether or not they have operator compartments or operator positions, may be capable of being operated remotely (i.e. from a remotely located operator station) instead of or in addition to an operator station adjacent or on the power machine. This can include applications where at least some of the operator controlled functions of the power machine can be operated from an operating position associated with an implement that is coupled to the power machine. Alternatively, with some power machines, a remote-control device can be provided (i.e. remote from both the power machine and any implement to which it is coupled) that is capable of controlling at least some of the operator controlled functions on the power machine.

(31) FIGS. 2-3 illustrates a loader **200**, which is one particular example of a power machine of the type illustrated in FIG. 1 where the embodiments discussed below can be advantageously employed. Loader **200** is a track loader and more particularly, a compact tracked loader. A track loader is a loader that has endless tracks as tractive elements (as opposed to wheels). Track loader **200** is one particular example of the power machine **100** illustrated broadly in FIG. 1 and discussed above. To that end, features of loader **200** described below include reference numbers that are generally similar to those used in FIG. 1. For example, loader **200** is described as having a frame **210**, just as power machine **100** has a frame **110**. Track loader **200** is described herein to provide a reference for understanding one environment on which the embodiments described below related to track assemblies and mounting elements for mounting the track assemblies to a power machine may be practiced. The loader **200** should not be considered limiting especially as to the description of features that loader **200** may have described herein that are not essential to the disclosed embodiments and thus may or may not be included in power machines other than loader **200** upon which the embodiments disclosed below may be advantageously practiced. Unless specifically noted otherwise, embodiments disclosed below can be practiced on a variety of power machines, with the track loader **200** being only one of those power machines. For example, some or all of the concepts discussed below can be practiced on many other types of work vehicles such as various other loaders, excavators, trenchers, and dozers, to name but a few examples. In particular, the features of power machine frames described below can be utilized on wheeled loaders as well. An example embodiment of such a wheeled loader, commonly referred to as a skid-steer loader, is illustrated in FIG. 4.

(32) Loader **200** includes frame **210** that supports a power system **220**, the power system can generate or otherwise providing power for operating various functions on the power machine. Frame **210** also supports a work element in the form of a lift arm structure **230** that is powered by the power system **220** and can perform various work tasks. As loader **200** is a work vehicle, frame **210** also supports a traction system **240**, which is also powered by power system **220** and can propel the power machine over a support surface. The lift arm structure **230** in turn supports an implement carrier interface **270**, which includes an implement carrier **272** that can receive and securing various implements to the loader **200** for performing various work tasks and power couplers **274**, which are provided to selectively provide power to an implement that might be connected to the loader. The loader **200** can be operated from within a cab **250** from which an

operator can manipulate various control devices **260** to cause the power machine to perform various functions. Cab **250** can be pivoted back about an axis that extends through mounts **254** to access components as needed for maintenance and repair.

(33) Referring still to FIGS. **2** and **3**, the elements of frame **210** discussed herein are provided for illustrative purposes and are not the only type of frame that a power machine on which the embodiments can be practiced can employ. Frame **210** of loader **200** includes an undercarriage or lower portion **211** of the frame and a mainframe or upper portion **212** of the frame that is supported by the undercarriage. A tailgate **280** is provided in the rear of the machine to selectively provide access to an engine compartment. The mainframe **212** of loader **200** is attached to the undercarriage **211** such as with fasteners or by welding the undercarriage to the mainframe. Mainframe **212** includes a pair of upright portions **214A** and **214B** located on either side and toward the rear of the mainframe that support lift arm structure **230** and to which the lift arm structure **230** is pivotally attached. The lift arm structure **230** is illustratively pinned to each of the upright portions **214A** and **214B**. The combination of mounting features on the upright portions **214A** and **214B** and the lift arm structure **230** and mounting hardware (including pins used to pin the lift arm structure to the mainframe **212**) are collectively referred to as joints **216A** and **216B** (one is located on each of the upright portions **214**) for the purposes of this discussion. Joints **216A** and **216B** are aligned along an axis **218** so that the lift arm structure is capable of pivoting, as discussed below, with respect to the frame **210** about axis **218**. Other power machines may not include upright portions on either side of the frame, or may not have a lift arm structure that is mountable to upright portions on either side and toward the rear of the frame. For example, some power machines may have a single arm, mounted to a single side of the power machine or to a front or rear end of the power machine. Other machines can have a plurality of work elements, including a plurality of lift arms, each of which is mounted to the machine in its own configuration. Frame **210** also supports a pair of tractive elements **242A** and **242B** on either side of the loader **200**, which on loader **200** are track assemblies.

(34) The lift arm structure **230** shown in FIG. **1** is one example of many different types of lift arm structures that can be attached to a power machine such as loader **200** or other power machines on which embodiments of the present discussion can be practiced. The lift arm structure **230** has a pair of lift arms **234** that are disposed on opposing sides of the frame **210**. A first end of each of the lift arms **234** is pivotally coupled to the power machine at joints **216** and a second end **232B** of each of the lift arms is positioned forward of the frame **210** when in a lowered position as shown in FIG. **2**. The lift arm structure **230** is moveable (i.e. the lift arm structure can be raised and lowered) under control of the loader **200** with respect to the frame **210**. That movement (i.e. the raising and lowering of the lift arm structure **230**) is described by a travel path, shown generally by arrow **237**. For the purposes of this discussion, the travel path **237** of the lift arm structure **230** is defined by the path of movement of the second end **232B** of the lift arm structure.

(35) Each of the lift arms **234** of lift arm structure **230** as shown in FIG. **2** includes a first portion **234A** and a second portion **234B** that is pivotally coupled to the first portion **234A**. The first portion **234A** of each lift arm **234** is pivotally coupled to the frame **210** at one of the joints **216** and the second portion **234B** extends from its connection to the first portion **234A** to the second end **232B** of the lift arm structure **230**. The lift arms **234** are each coupled to a cross member **236** that is attached to the first portions **234A**. Cross member **236** provides increased structural stability to the lift arm structure **230**. A pair of actuators **238**, which on loader **200** are hydraulic cylinders configured to receive pressurized fluid from power system **220**, are pivotally coupled to both the frame **210** and the lift arms **234** at pivotable joints **238A** and **238B**, respectively, on either side of the loader **200**. The actuators **238** are sometimes referred to individually and collectively as lift cylinders. Actuation (i.e., extension and retraction) of the actuators **238** cause the lift arm structure **230** to pivot about joints **216** and thereby be raised and lowered along a fixed path illustrated by arrow **237**. Each of a pair of control links **217** are pivotally mounted to the frame **210** and one of

the lift arms **232** on either side of the frame **210**. The control links **217** help to define the fixed travel path of the lift arm structure **230**. The lift arm structure **230** shown in FIG. 2 is representative of one type of lift arm structure that may be coupled to the power machine **100**. Other lift arm structures, with different geometries, components, and arrangements can be pivotally coupled to the loader **200** or other power machines upon which the embodiments discussed herein can be practiced without departing from the scope of the present discussion. For example, other machines can have lift arm structures with lift arms that each has one portion (as opposed to the two portions **234A** and **234B** of lift arm **234**) that is pivotally coupled to a frame at one end with the other end being positioned in front of the frame. Other lift arm structures can have an extendable or telescoping lift arm. Still other lift arm structures can have several (i.e. more than two) portions segments or portions. Some lift arms, most notably lift arms on excavators but also possible on loaders, may have portions that are controllable to pivot with respect to another segment instead of moving in concert (i.e. along a pre-determined path) as is the case in the lift arm structure **230** shown in FIG. 2. Some power machines have lift arm structures with a single lift arm, such as is known in excavators or even some loaders and other power machines. Other power machines can have a plurality of lift arm structures, each being independent of the other(s).

(36) An exemplary implement interface **270** is provided at a second end **234B** of the arm **234**. The implement interface **270** includes an implement carrier **272** that can accept and securing a variety of different implements to the lift arm **230**. Such implements have a machine interface that is configured to be engaged with the implement carrier **272**. The implement carrier **272** is pivotally mounted to the second end **234B** of the arm **234**. Implement carrier actuators **235** are operably coupled the lift arm structure **230** and the implement carrier **272** and are operable to rotate the implement carrier with respect to the lift arm structure.

(37) The implement interface **270** also includes an implement power source **274** available for connection to an implement on the lift arm structure **230**. The implement power source **274** includes pressurized hydraulic fluid port to which an implement can be coupled. The pressurized hydraulic fluid port selectively provides pressurized hydraulic fluid for powering one or more functions or actuators on an implement. The implement power source can also include an electrical power source for powering electrical actuators and/or an electronic controller on an implement. The implement power source **274** also exemplarily includes electrical conduits that are in communication with a data bus on the excavator **200** to allow communication between a controller on an implement and electronic devices on the loader **200**.

(38) The lower frame **211** supports and has attached to it a pair of tractive elements **242A** and **242B**. Each of the tractive elements **242A** and **242B** has a track frame that is coupled to the lower frame **211**. The track frame supports and is surrounded by an endless track, which rotates under power to propel the loader **200** over a support surface. Various elements are coupled to or otherwise supported by the track frame for engaging and supporting the endless track and cause it to rotate about the track frame. For example, a sprocket is supported by the track frame and engages the endless track to cause the endless track to rotate about the track frame. An idler is held against the track by a tensioner (not shown) to maintain proper tension on the track. The track frame also supports a plurality of rollers, which engage the track and, through the track, the support surface to support and distribute the weight of the loader **200**.

(39) Display devices are provided in the cab to give indications of information relatable to the operation of the power machines in a form that can be sensed by an operator, such as, for example audible and/or visual indications. Audible indications can be made in the form of buzzers, bells, and the like or via verbal communication. Visual indications can be made in the form of graphs, lights, icons, gauges, alphanumeric characters, and the like. Displays can be dedicated to provide dedicated indications, such as warning lights or gauges, or dynamic to provide programmable information, including programmable display devices such as monitors of various sizes and capabilities. Display devices can provide diagnostic information, troubleshooting information,

instructional information, and various other types of information that assists an operator with operation of the power machine or an implement coupled to the power machine. Other information that may be useful for an operator can also be provided.

(40) The description of power machine **100** and loader **200** above is provided for illustrative purposes, to provide illustrative environments on which the embodiments discussed below can be practiced. While the embodiments discussed can be practiced on a power machine such as is generally described by the power machine **100** shown in the block diagram of FIG. **1** and more particularly on a loader such as skid-steer loader **200**, unless otherwise noted or recited, the concepts discussed below are not intended to be limited in their application to the environments specifically described above.

(41) FIG. **4** is a side view of a portion, including a lift arm structure **330**, of a power machine **300**, which is another power machine on which disclosed embodiments can be implemented. FIG. **5** illustrates a portion of the lift arm structure **330** of FIG. **4**. In FIG. **4**, frame **310** and lift arm structure **330** of power machine **300** are illustrated, while other power machine components are omitted to better illustrate certain features. In power machine **300**, lift arm structure **330** includes a pair of main lift arm portions **334**. Each of the main lift arm portions **334** includes a first portion **334A** and a second portion **334B** that is pivotally coupled to the first portion **334A**. The first portion **334A** of each main lift arm **334** is pivotally coupled to the frame **310** (which represents a first end **332A** of the lift arm **334**) at one of the joints **316** and the second portion **334B** extends from its connection to the first portion **334A** to a second end **332B** of the lift arm **334**. The main lift arm portions **334** are each coupled to a cross member **336** that is attached to the first portions **334A** and to a cross member **335** that is attached to the second portions **334B**.

(42) An implement carrier **372** is rotatably mounted, by a pivotal attachment **371**, to cast lower lift arm portions **339**. Although not necessarily a part of the power machine **300**, an implement **373** is shown mounted on implement carrier **372** for illustrative purposes. In an exemplary embodiment, implement **373** is a bucket type of implement for a loader type of power machine.

(43) On each side of frame **310**, a lift cylinder or actuator **338** is pivotally attached to the frame at pivot attachment **338A**. The lift cylinder **338** is also pivotally attached at pivot attachment **338B** to the lift arm structure **330**. The first portion **324A** acts as a follower link and is pivotally attached at pivot attachment **316** to frame **310** and at pivot attachment **375B** to the second or main portion **334B** of the lift arm structure **330**. A driver link **380** is pivotally attached at pivot attachment **380A** to frame **310** and at pivot attachment **380B** to lift arm structure **330** (on the main or second portion **334B**). The driver link, the follower link, the frame of the loader and the rest of the lift arm provide a four-bar linkage arrangement for the lift arm assembly **330**. More detailed discussions of these various components are provided below with reference to FIGS. **5-22**.

(44) Lift Arm Structure

(45) FIGS. **5-6** shows the lift arm structure **330** in greater detail. FIG. **7** illustrates an embodiment of lower lift arm portion **339** that is formed from a casting in greater detail, and FIG. **8** illustrates features of upper or main lift arm portion **334** and cast lower lift arm portion **339** at a junction **332** where the two lift arm portions are welded together. While some embodiments of lift arm structures may not have cast lower lift arms, the embodiment shown in FIGS. **5-8** illustrate cast lower lift arms. Near the junction **332** between the respective main lift arm portions **334** and cast lower lift arm portions **339**, the lower lift arm portions **339** sloping downwardly more dramatically than the main portion from the main lift arm portions **334** (in some embodiments, the main lift arm portions need not slope downwardly) a “knee” is formed in exemplary embodiments. The term knee is used to describe the departure area between the main portion and the lower portion, even when, as is the case in the embodiment shown in FIGS. **5-6**, there is no movable joint between the main lift arm portion and the lower lift arm portion. As shown in FIGS. **5-6**, the two (left and right) cast lower lift arm portions **339** can have the same features, but can be mirror or reverse images of each other or at least substantially similar. While in this respect the cast lower lift arm portions may not be

identical, a description of only one cast lower lift arm portion is provided below. Those of skill in the art will understand that the features discussed on one cast lower lift arm portion **339** can be implemented on a corresponding lower lift arm portion for the opposite side of the lift arm structure and that other features, not discussed herein may be present on one or the other without departing from the scope of this discussion.

(46) Cast lower lift arm portions **339**, in this embodiment, have hollow interiors and several cast features that provide improvements over conventional lower lift arm portions that are formed from one or more pieces of steel welded or otherwise fastened together. For example, cast lower lift arm portions **339** are formed to include inward offset or bend regions **396** which taper the width of the lift arm structure **330** from a width which is wider than the frame of the power machine down to a width necessary for attachment of the implement carrier and any attached implement. Forming this laterally inward bend or offset using traditional methods requires the welding of multiple different individual metal plates or pieces, which causes manufacturing to be more expensive and complex, and introduces a large number of welds, which can fail under exposure to repeated high stresses. Using a cast lower lift arm portion or member, the laterally inward bend or offset **396** can be formed to narrow the lift arm structure without requiring additional metal pieces or welds. This simplifies manufacturing, and produces a stronger lower lift arm portion which is less prone to stress failures. Further, using a cast lower lift arm portion allows for tighter control of tolerances of the part shape and dimensions than can be reasonably be achieved by welding multiple pieces together. If such dimensions are not tightly controlled, they can result in configurations in which the tilt cylinder (not shown) can be over-extended or over-retracted and thereby damaged or other misalignments can introduce unwanted stresses into the lift arm.

(47) In lift arm structure **330**, cast lower lift arm portions **339** include other features such as pivot attachment bores or apertures **390** for connecting the tilt cylinder (not shown) between lower lift arm portion **339** and the implement carrier **372** (shown in FIG. 4), and pivot attachment bores or apertures **392** for the pivotal attachment of the implement carrier directly to the cast lower lift arm portion. Also, structural tube bores or apertures **394** are formed in the lower lift arm portions and configured to receive a structural tube **335** that is a cross-member that extends between respective left and right lower lift arm portions **339** to provide strength and stability by resisting torque and other forces introduced into the lift arm.

(48) FIG. 7 provides a perspective view of a cast lower lift arm portion **339** according to one illustrative embodiment. Cast lower lift arm portion **339** includes features which strengthen the lift arm structure and allow for deformation of portions of the cast material to reduce stress on welds between the lower lift arm portion **339** and structural tube **335**, or between lower lift arm portion **339** and upper or main lift arm portion **334**. For example, cast lower lift arm portion **339** includes a boss **402** surrounding structural tube aperture **394** to facilitate cast material deformation to absorb load stresses and thereby prevent transfer of those stresses to welds between the structural tube and lower lift arm portion **339**. Also, lower lift arm portion **339** includes a contoured top end **405** which is configured to be received at least partially into a corresponding contoured bottom end **410** (shown in FIG. 8) of the upper or main lift arm portion **334**, with the contoured ends joined at a junction **332**. The shapes of the contoured ends and resulting junction **332** control the placement of the highest tension and compression stress points to reduce stress on welds between the upper and lower lift arm portions.

(49) Referring more specifically to FIG. 8, contoured bottom end **410** of upper or main lift arm portion **334** is sleeved over part of contoured top end **405** of cast lower lift arm portion **339**. A weld is placed in a channel **415** (the weld is not shown in FIG. 8) formed between contoured ends **405** and **410** of cast lower lift arm portion **339** and upper or main lift arm portion **334**. The shapes of the contoured ends of lift arm portions **339** and **334** are designed to control the location of the highest tension (under load) point between the upper and lower lift arm portions, and the highest compression (under load) point between the two lift arm portions. For example, with the contour

illustrated in FIG. 8, point **420** represents an example of the highest tension point, while point **425** is an example of the highest compression point. To control the location of these points, and to provide for regions of controlled deformation of one or both lift arm portions **334** and **339**, a protruding kink section **430** is formed by the contoured top end **405** of the cast lift arm portion **339**. A corresponding inlet kink section **435** is formed in the contoured bottom end **410** of upper or main lift arm portion **334** and is configured to receive the protruding kink section **430**. This configuration forms a top extending member **440** of the upper or main lift arm portion **334**, with the top extending member **440** extending further toward the knee region of lower lift arm portion **339** than other parts of the upper or main lift arm portion **334**. A bottom extending member **445** is also formed by the contoured bottom end **410** of the upper or main lift arm portion **334** and is separated from top extending member **440** by inlet kink section **435**. In this configuration, with top extending member **440** extending further than bottom extending member **445**, the top extending member is configured to bend, deflect or deform slightly under heavily loaded conditions to absorb stresses and thereby reduce the stresses on weld **415**.

(50) Implement Carrier Structure

(51) FIGS. **9-12** illustrate one embodiment of a cast implement carrier plate **500** of implement carrier **372** shown in FIG. **4**. FIGS. **13-14** are perspective view illustrations of implement carrier **372**, which includes two cast implement carrier plates **500** coupled together with a structural tube **510** that is a cross-member welded to each plate **500**. Each cast implement carrier plate **500** is configured to be pivotally attached or coupled to a different one of the pair of lower lift arm portions **339** of the lift arm structure at respective pivot attachments **371** discussed above and as shown in FIG. **15**. The two (left and right) cast implement carrier plates can have the same features, but can be mirror or reverse images of each other. While the cast implement carrier plates may be mirror images of each other instead of identical, a description of only one implement carrier plate is shown in FIGS. **9-12** and discussed herein for brevity's sake. In some embodiments, each of the left and right cast implement carrier plates may have features that differ from the other that are not discussed herein. None of those differences will cause the implement carrier plates to depart from the scope of this discussion.

(52) As shown best in FIGS. **9-12**, each cast implement carrier plate **500** has a rear or power machine side **520** and an opposing front or implement interface side **530**. The implement interface side **530** is configured to directly interface the implement (in other words, the casting itself is positioned directly against the implement). On rear side **520**, each plate **500** has bores or apertures **540** for pivot attachment **371** (shown in FIG. **4**) to pivotally attach the cast plate to lower lift arm portions **339**. On the same rear side, each plate also includes bores or apertures **545** for pivot attachments between a tilt cylinder (not shown) and the cast plate to control tilt functions for an implement mounted on the implement carrier **372**. On an inside end of each of the cast implement carrier plates, a structural tube or cross-member receiving collar **550** is included in the casting. Further, each structural tube receiving collar has side apertures **555** formed therein to allow for welds **560** (shown in FIGS. **13-14**) and for improved deformability of collars **550** to absorb stress forces on the implement carrier plate **500**. By allowing deformation of the cast implement carrier material in the region of collar **550**, stress forces on welds **560** and **565** between the collar and the structural tube **510** are reduced.

(53) Carrier plate **500** has a tilt stop machined surface **570** configured to contact the lower lift arm portion **339** or other stop surface to prevent further movement (in one direction) of the implement carrier relative to the lift arm portion. Surface **570** is machined onto the cast implement carrier plate to tightly control the maximum degree of extension of the tilt cylinder to prevent damage to the cylinder due to over-extension. Also, other surfaces of carrier plate **500** can be machined after casting to closely control dimensions and tolerances. For example, bores **540** and **545** can be machined, as can the aperture within collar **550**.

(54) After casting carrier plate **500** and machining any necessary surfaces, the implement locking

mechanisms can be added to the carrier plate. For example, as shown in FIGS. **13** and **14**, levers **580**, spring mechanisms **585**, and locking pins **590** can be added. These locking components are used for locking an implement into its position mounted on the implement interface side **530** of the cast plates **500**.

(55) Follower Link Structure

(56) FIGS. **16-17** show partial rear and rear perspective views of power machine **300** illustrating follower links **375** in accordance with some exemplary embodiments. FIG. **18** illustrates the follower links **375** and structural tube **610** that is a cross-member separate from the power machine **300**. In some embodiments, follower links **375** are formed as single pieces using a casting technique. In other embodiments, follower links can be otherwise constructed.

(57) The follower links **375** include a structural tube (or cross-member) receiving collar **630** and an extension member **640** which extends from the collar **630** down to a pivot bore **650** used to provide the pivot attachment **375A** (also referred to as pivot **316** on FIG. **4**) to upright portions **615** of frame **310**. The extension member has a first portion **641** which is at least partially in-line with a main portion of the lift arm structure of the power machine when viewed from directly behind the power machine and a second portion **642** positioned outward from the first portion such that the link casting lift arm attachment point is outside of the lift arm structure. The first portion **641** can be angled outward to transition between positions which are in-line with the main portions of the lift arm and positions which are outward. By positioning the follower link outside of the main lift arm portion, visibility from an operator compartment rearward is advantageously improved. The structural tube **610** extends between the collar **630** of each of the follower links **375**. The collar **630** allows the follower link material to twist or deform to reduce the stress on the weld between the structural tube and the follower link. As shown in FIG. **17**, a pivot attachment **375B** couples the lift arm structure **330** to the follower link **375**.

(58) Using a cast material for follower links **375** provides numerous advantages. For example, using a casting allows close control of dimensions and tolerances between the lift arm pivot bore **650** and the pivot bore in collar **630**. It also allows material to be removed from the follower link casting, while at the same time making the follower link stronger due in part to less usage of welds. As can be seen in FIG. **16**, extension members **640** of follower links **375** are positioned outside of upper or main lift arm portions **334** from collar **630** at least part of the way toward the pivotal attachments of the follower links to the upright portions **615** of the power machine frame. This provides improved rear visibility for an operator of the power machine.

(59) Driver Link Structure and Path

(60) FIGS. **19-21** illustrate portions of the power machine **300** with the lift arm structure in various states of being raised, by lift cylinder **338**, relative to the fully lowered state shown in FIG. **4**. Of particular importance, power machine **300** is configured such that the paths of the driver link **380** and lift cylinder **338** can allow these components to be placed in close proximity to each other and to the frame **310**, without the driver link **380** contacting the lift cylinder **338**. The driver link **380** and follower link **375** are configured such that when the driver link pivot attachment **380B** to the lift arm structure **330** crosses the lift cylinder **338**, the pivot attachment **380B** is above the uppermost or top position **660** of the base of the lift cylinder. Pivot attachment **380A** is positioned behind a rear axle of the loader as is shown in FIG. **19**.

(61) The driver link is configured such that the main lift arm portion pivot attachment **380B** follows a movement arc that moves above the top **660** of the lift cylinder body as the main lift arm portion is raised and lowered by the lift cylinder. **338**. In some embodiments, when the main lift arm portion is in a fully lowered position, the main lift arm portion pivot attachment **380B** of the driver link is positioned rearward of the top **660** of the lift cylinder body, but when the main lift arm portion is in a fully raised position, pivot attachment **380B** is positioned forward of the top of the lift cylinder body. In addition, the main lift arm portion pivot attachment **380B** is positioned behind and above the pivot attachment **380A** throughout its travel path from a fully lowered position (as is

shown in FIG. 19) to a fully raised position (as is shown in FIG. 21).

(62) As can be seen in FIG. 4, when the lift arm structure 330 is down and the lift cylinder 338 is fully retracted, the pivot attachment 380B is below the top 660 of the base of the lift cylinder. As the lift cylinder is extended (FIGS. 19-21) to raise the lift arm, the pivot 380B is higher than the top 660 of the lift cylinder base when the pivot passes (inward of) the lift cylinder. This configuration allows these components to be placed closer together and doesn't require widening of the power machine. FIG. 22 shows the pivot 380B having an outermost surface 670 at a position laterally from the frame 310 of the power machine that would interfere with the inner most surface 680 of the base of the lift cylinder 338, but which is positioned to be above the top 660 of the base of the lift cylinder when the pivot 380B passes near the lift cylinder. In some embodiments, the maximum distance between the driver link 380 and the frame is greater than the minimum distance between the tilt cylinder and the frame, while at least a portion of the driver link is positioned between the tilt cylinder and the frame. Stated another way, a portion of the driver link 380 extends beyond the closest position of the lift cylinder 338 relative to the frame. As shown in FIG. 22, the driver link 380 has a clevis 384 on an end at which the driver link is coupled to the lift arm. The clevis end allows a main portion 382 the driver link to be narrow so as to be positioned closer to the frame of the machine.

(63) Although the present disclosure has been described by referring to various embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the disclosure.

Claims

1. A power machine comprising: a frame; a lift arm having a forward end; a driver link, the driver link pivotally coupled to the frame using a frame pivot attachment such that the driver link pivots about a first pivot axis relative to the frame and the driver link pivotally coupled to the lift arm using a lift arm pivot attachment such that the driver link pivots about a second pivot axis relative to the lift arm; a lift cylinder pivotally coupled to the frame and to the lift arm and configured to raise and lower the forward end of the lift arm, the lift cylinder comprising a lift cylinder body and a rod, wherein the rod extends from a top end of the lift cylinder body; tractive elements configured for rotation; wherein the frame pivot attachment is positioned such that the first pivot axis is rearward of an axis of rotation of a rearmost tractive element; and wherein the lift arm pivot attachment is positioned lower than and rearward of the top end of the lift cylinder body when the lift arm's forward end is in a fully lowered position, such that, when the lift arm pivot attachment crosses from a position rearward of the lift cylinder body top to a position forward of the lift cylinder body top as the lift arm's forward end is raised by the lift cylinder, the lift arm pivot attachment is higher than the top end of the lift cylinder body.
 2. The power machine of claim 1, and further comprising an operating position which serves as an operator station.
 3. The power machine of claim 2, wherein a main portion of the driver link is positioned inboard, toward the frame of the power machine, of the lift cylinder body, and a portion of the lift cylinder body is positioned inboard, toward the frame of the power machine, of a portion of the lift arm pivot attachment which encircles the second pivot axis.
 4. The power machine of claim 1, wherein a main portion of the driver link is positioned inboard, toward the frame of the power machine, of the lift cylinder body, and a portion of the lift cylinder body is positioned inboard, toward the frame of the power machine, of a portion of the lift arm pivot attachment which encircles the second pivot axis.
 5. The power machine of claim 1, further comprising an axle establishing the axis of rotation.
 6. The power machine of claim 1, wherein the driver link comprises the lift arm pivot attachment.
-

