

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12405722
B2
September 02, 2025
Ochenas; Jonathan et al.

User interface device for industrial vehicle

Abstract

A processing device comprising a graphical user interface in an industrial vehicle is provided. The processing device comprises a touch screen display that receives touch gesture commands from a vehicle operator, memory storing executable instructions, and a processor in communication with the memory. The processor when executing the executable instructions: defines a plurality of widgets, wherein each widget comprises a visual representation of a current state of an associated function of the vehicle, displays a subset of the plurality of widgets on a portion of the touch screen display defining a plurality of widget spaces, and displays an icon tray on the touch screen display comprising one or more icons, in which at least one of the one or more icons corresponds to a respective one of the plurality of widgets.

Inventors: Ochenas; Jonathan (Mooresville, NC), Neubert; Katharine (Vancouver, WA)
Applicant: Crown Equipment Corporation (New Bremen, OH)
Family ID: 60629812
Assignee: Crown Equipment Corporation (New Bremen, OH)
Appl. No.: 17/820909
Filed: August 19, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220391064 A1	Dec. 08, 2022

Related U.S. Application Data

continuation parent-doc US 15815788 20171117 ABANDONED child-doc US 17820909
us-provisional-application US 62425099 20161122

Publication Classification

Int. Cl.: G06F3/048 (20130101); B66F9/075 (20060101); B66F9/24 (20060101); B66F17/00 (20060101); G06F3/02 (20060101); G06F3/041 (20060101); G06F3/04817 (20220101); G06F3/0482 (20130101); G06F3/0488 (20220101); G06F3/04883 (20220101); H04L12/40 (20060101); B60K35/10 (20240101)

U.S. Cl.:

CPC G06F3/0488 (20130101); B66F9/0755 (20130101); B66F9/0759 (20130101); B66F9/24 (20130101); B66F17/003 (20130101); G06F3/02 (20130101); G06F3/041 (20130101); G06F3/048 (20130101); G06F3/04817 (20130101); G06F3/0482 (20130101); G06F3/04883 (20130101); H04L12/40 (20130101); B60K35/10 (20240101); B60K2360/1438 (20240101)

Field of Classification Search

CPC: G06F (3/0488); G06F (3/02); G06F (3/041); G06F (3/048); G06F (3/04817); G06F (3/0482); G06F (3/04883); G06F (3/0483); G06F (2203/04803); G06F (3/0416); B66F (9/0755); B66F (9/0759); B66F (9/24); B66F (17/003); H04L

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3010595	12/1960	Stone	N/A	N/A
3319816	12/1966	Christenson	N/A	N/A
3410433	12/1967	Brown	N/A	N/A
3542161	12/1969	Minski	N/A	N/A
3854820	12/1973	Hansen	N/A	N/A
3937339	12/1975	Geis et al.	N/A	N/A
4062269	12/1976	Chichester et al.	N/A	N/A
4074794	12/1977	Scholl	N/A	N/A
4122957	12/1977	Allen et al.	N/A	N/A
4130183	12/1977	Tjornemark	N/A	N/A
4162869	12/1978	Hitomi et al.	N/A	N/A
4212375	12/1979	Peterson et al.	N/A	N/A
4235308	12/1979	Davis	N/A	N/A
4279328	12/1980	Ahlbom	N/A	N/A
4411582	12/1982	Nakada	N/A	N/A
4439102	12/1983	Allen	N/A	N/A
4491918	12/1984	Yuki et al.	N/A	N/A
4499541	12/1984	Yuki et al.	N/A	N/A
4509127	12/1984	Yuki et al.	N/A	N/A
4511974	12/1984	Nakane et al.	N/A	N/A
4517645	12/1984	Yuki et al.	N/A	N/A
4520443	12/1984	Yuki et al.	N/A	N/A
4547844	12/1984	Adams	N/A	N/A
4598797	12/1985	Schultz	N/A	N/A
4612623	12/1985	Bazarnik	N/A	N/A
4634332	12/1986	Kamide et al.	N/A	N/A
4708577	12/1986	Fratzke	N/A	N/A
4782920	12/1987	Gaibler et al.	N/A	N/A
4957408	12/1989	Ohkura	N/A	N/A
5006829	12/1990	Miyamoto et al.	N/A	N/A
5011358	12/1990	Andersen et al.	N/A	N/A
5056437	12/1990	Maddock	N/A	N/A
5088879	12/1991	Ranly	N/A	N/A
5208753	12/1992	Acuff	N/A	N/A
5224815	12/1992	Abels et al.	N/A	N/A
5238086	12/1992	Aoki et al.	N/A	N/A
5555957	12/1995	Dreher et al.	N/A	N/A
5586620	12/1995	Dammeyer et al.	N/A	N/A
5594471	12/1996	Deeran et al.	N/A	N/A
5704051	12/1996	Lane et al.	N/A	N/A
5734377	12/1997	Fukuzaki	N/A	N/A
5738187	12/1997	Dammeyer et al.	N/A	N/A
5749696	12/1997	Johnson	N/A	N/A
5791440	12/1997	Lonzinski et al.	N/A	N/A
5880684	12/1998	Diekhans et al.	N/A	N/A
5890086	12/1998	Wellman et al.	N/A	N/A
5956255	12/1998	Flamme	N/A	N/A
5994650	12/1998	Eriksson et al.	N/A	N/A
5995001	12/1998	Wellman et al.	N/A	N/A
6005299	12/1998	Hengst	N/A	N/A
6039141	12/1999	Denny	N/A	N/A
6049813	12/1999	Danielson et al.	N/A	N/A
6073069	12/1999	Kim	N/A	N/A
6100476	12/1999	Adamietz et al.	N/A	N/A
6128007	12/1999	Seybold	N/A	N/A
6128553	12/1999	Gordon et al.	N/A	N/A
6138795	12/1999	Kamiya	N/A	N/A
6164415	12/1999	Takeuchi et al.	N/A	N/A

6209913	12/2000	Ishikawa et al.	N/A	N/A
6282464	12/2000	Obradovich	N/A	N/A
6331866	12/2000	Eisenberg	N/A	N/A
6343237	12/2001	Rossow et al.	N/A	N/A
6345694	12/2001	Volker	N/A	N/A
6369717	12/2001	Damiani et al.	N/A	N/A
6429773	12/2001	Schuyler	N/A	N/A
6437701	12/2001	Muller	N/A	N/A
6494527	12/2001	Bischoff	N/A	N/A
6539289	12/2002	Ogino et al.	N/A	N/A
6600418	12/2002	Francis et al.	N/A	N/A
6640114	12/2002	Bae	N/A	N/A
6648581	12/2002	Gibson	N/A	N/A
6667726	12/2002	Damiani et al.	N/A	N/A
6686911	12/2003	Levin et al.	N/A	N/A
6724403	12/2003	Santoro et al.	N/A	N/A
6817824	12/2003	Winkler	N/A	N/A
7010404	12/2005	Ichijo et al.	N/A	N/A
7028264	12/2005	Santoro et al.	N/A	N/A
7089098	12/2005	Rogg et al.	N/A	N/A
7154480	12/2005	Iesaka	N/A	N/A
7165643	12/2006	Bozem et al.	N/A	N/A
D537374	12/2006	Smiley	N/A	N/A
7172050	12/2006	Amamiya	N/A	N/A
7192236	12/2006	Upmeyer	N/A	N/A
7216024	12/2006	Abels et al.	N/A	N/A
7219769	12/2006	Yamanouchi et al.	N/A	N/A
7225413	12/2006	Kuenzner et al.	N/A	N/A
7237203	12/2006	Kuenzner	N/A	N/A
7274970	12/2006	Schuchard	N/A	N/A
7287625	12/2006	Harris	N/A	N/A
7322444	12/2007	Allerding et al.	N/A	N/A
7360175	12/2007	Gardner et al.	N/A	N/A
7372473	12/2007	Venolia	N/A	N/A
7376907	12/2007	Santoro et al.	N/A	N/A
7415352	12/2007	Olcott	N/A	N/A
7418670	12/2007	Goldsmith	N/A	N/A
7477268	12/2008	Venolia	N/A	N/A
7595722	12/2008	Heimermann et al.	N/A	N/A
7599776	12/2008	Sonderegger et al.	N/A	N/A
7612673	12/2008	Onderko et al.	N/A	N/A
7672768	12/2009	Narisawa et al.	N/A	N/A
7683771	12/2009	Loeb	N/A	N/A
7706947	12/2009	Bozem et al.	N/A	N/A
7806470	12/2009	Steege et al.	N/A	N/A
7822513	12/2009	Wulff	N/A	N/A
7857090	12/2009	Ruhter et al.	N/A	N/A
7872587	12/2010	Hindryckx et al.	N/A	N/A
7896358	12/2010	Hoff	N/A	N/A
7909561	12/2010	Addleman et al.	N/A	N/A
7922899	12/2010	Vasta et al.	N/A	N/A
7987431	12/2010	Santoro et al.	N/A	N/A
7992686	12/2010	McCabe	N/A	N/A
8001483	12/2010	de Souza et al.	N/A	N/A
8055405	12/2010	Baginski et al.	N/A	N/A
8083034	12/2010	Bordwell et al.	N/A	N/A
8108090	12/2011	Bauer	N/A	N/A
8125457	12/2011	Lawson et al.	N/A	N/A
8201097	12/2011	Kondo et al.	N/A	N/A
8207841	12/2011	Watson et al.	N/A	N/A
8230976	12/2011	Baldini	N/A	N/A
8239251	12/2011	Wellman	N/A	N/A
8265836	12/2011	Yamada et al.	N/A	N/A
8340873	12/2011	Finley et al.	N/A	N/A

8362893	12/2012	Ishikawa	N/A	N/A
8443943	12/2012	McCabe et al.	N/A	N/A
8482534	12/2012	Pryor	N/A	N/A
8515629	12/2012	Medwin et al.	N/A	N/A
8521373	12/2012	Behncke et al.	N/A	N/A
8536996	12/2012	Watson et al.	N/A	N/A
8549432	12/2012	Warner	N/A	N/A
8565913	12/2012	Emanuel et al.	N/A	N/A
8583314	12/2012	de Oliveira et al.	N/A	N/A
8627073	12/2013	Kherani et al.	N/A	N/A
8632082	12/2013	Lantz et al.	N/A	N/A
8649964	12/2013	Kizaki	N/A	N/A
8682401	12/2013	Ebner et al.	N/A	N/A
8694194	12/2013	Waltz et al.	N/A	N/A
8701044	12/2013	Kolletzki	N/A	N/A
8706920	12/2013	Fleizach et al.	N/A	N/A
8713467	12/2013	Goldenberg et al.	N/A	N/A
8731785	12/2013	McCabe et al.	N/A	N/A
8756002	12/2013	Sathish	N/A	N/A
8763759	12/2013	Viereck et al.	N/A	N/A
8781642	12/2013	Tarasinski et al.	N/A	N/A
8799799	12/2013	Cervelli et al.	N/A	N/A
8811265	12/2013	Horvath	N/A	N/A
8836545	12/2013	Eckstein et al.	N/A	N/A
8849510	12/2013	Tanaka	N/A	N/A
8892241	12/2013	Weiss	N/A	N/A
8892294	12/2013	Waltz et al.	N/A	N/A
8907778	12/2013	Waller et al.	N/A	N/A
8977441	12/2014	Grimes et al.	N/A	N/A
9002626	12/2014	Waltz et al.	N/A	N/A
9008856	12/2014	Ricci et al.	N/A	N/A
9025827	12/2014	Holeva et al.	N/A	N/A
9057221	12/2014	Warr	N/A	N/A
9075468	12/2014	Becker et al.	N/A	N/A
9080319	12/2014	Oates, Jr. et al.	N/A	N/A
9128575	12/2014	Lee	N/A	N/A
9160854	12/2014	Daddi et al.	N/A	N/A
9181965	12/2014	Pirotais	N/A	N/A
9235553	12/2015	Fitch et al.	N/A	N/A
9278839	12/2015	Gilbride et al.	N/A	N/A
9361000	12/2015	Furue et al.	N/A	N/A
9434585	12/2015	Gilbride et al.	N/A	N/A
9448692	12/2015	Mierau et al.	N/A	N/A
9575628	12/2016	Meegan et al.	N/A	N/A
9658738	12/2016	Park et al.	N/A	N/A
9723457	12/2016	Brahmi et al.	N/A	N/A
9740304	12/2016	Chandel et al.	N/A	N/A
9760644	12/2016	Khvostichenko et al.	N/A	N/A
9792013	12/2016	Fleizach et al.	N/A	N/A
9952703	12/2017	Hoen et al.	N/A	N/A
10073708	12/2017	Kardamilas	N/A	N/A
10138101	12/2017	Svensson et al.	N/A	N/A
10282088	12/2018	Kim et al.	N/A	N/A
10430073	12/2018	Castaneda et al.	N/A	N/A
10754466	12/2019	Ochenas et al.	N/A	N/A
10936183	12/2020	Ochenas et al.	N/A	N/A
10949083	12/2020	Castaneda et al.	N/A	N/A
11054890	12/2020	Ochenas et al.	N/A	N/A
2002/0070852	12/2001	Trauner et al.	N/A	N/A
2002/0084887	12/2001	Arshad et al.	N/A	N/A
2003/0205433	12/2002	Hagman	N/A	N/A
2004/0031649	12/2003	Schiebel et al.	N/A	N/A
2004/0150674	12/2003	Takahashi et al.	N/A	N/A
2004/0200644	12/2003	Paine et al.	N/A	N/A

2004/0233234	12/2003	Chaudhry et al.	N/A	N/A
2004/0249538	12/2003	Osaki et al.	N/A	N/A
2005/0102081	12/2004	Patterson	N/A	N/A
2005/0113944	12/2004	Santarossa	N/A	N/A
2005/0172239	12/2004	Liu et al.	N/A	N/A
2006/0015818	12/2005	Chaudhri et al.	N/A	N/A
2006/0182582	12/2005	Sharpton	N/A	N/A
2006/0224945	12/2005	Khan et al.	N/A	N/A
2007/0007080	12/2006	Manthey et al.	N/A	N/A
2007/0111672	12/2006	Saintoyant et al.	N/A	N/A
2007/0210901	12/2006	Ahrens et al.	N/A	N/A
2007/0213869	12/2006	Bandringa et al.	N/A	N/A
2007/0233304	12/2006	Baginski et al.	N/A	N/A
2007/0236475	12/2006	Wherry	N/A	N/A
2008/0015955	12/2007	Ehrman et al.	N/A	N/A
2008/0055273	12/2007	Forstall	N/A	N/A
2008/0067005	12/2007	Hagman	N/A	N/A
2008/0082930	12/2007	Omernick	715/765	G06F 3/04886
2008/0154712	12/2007	Wellman	N/A	N/A
2008/0211779	12/2007	Pryor	N/A	N/A
2008/0244414	12/2007	Marcoullier et al.	N/A	N/A
2009/0057065	12/2008	Akaki et al.	N/A	N/A
2009/0058872	12/2008	Boettcher et al.	N/A	N/A
2009/0059004	12/2008	Bochicchio	N/A	N/A
2009/0101447	12/2008	Durham et al.	N/A	N/A
2009/0125850	12/2008	Karstens	N/A	N/A
2009/0236183	12/2008	Bordwell	187/234	B66F 3/46
2009/0265059	12/2008	Medwin et al.	N/A	N/A
2009/0267921	12/2008	Pryor	N/A	N/A
2009/0271778	12/2008	Mandyam et al.	N/A	N/A
2009/0326717	12/2008	Vaherto	N/A	N/A
2010/0005419	12/2009	Miichi et al.	N/A	N/A
2010/0023865	12/2009	Fulker et al.	N/A	N/A
2010/0039247	12/2009	Ziegler et al.	N/A	N/A
2010/0100512	12/2009	Brodin et al.	N/A	N/A
2010/0223332	12/2009	Maxemchuk et al.	N/A	N/A
2010/0277438	12/2009	Kawashima et al.	N/A	N/A
2011/0088979	12/2010	Bandringa et al.	N/A	N/A
2011/0106294	12/2010	Bebbington	N/A	N/A
2011/0106365	12/2010	Miyake et al.	N/A	N/A
2011/0119614	12/2010	Powell et al.	N/A	N/A
2011/0234389	12/2010	Mellin	N/A	N/A
2011/0238259	12/2010	Bai et al.	N/A	N/A
2011/0252369	12/2010	Chaudri	N/A	N/A
2011/0320978	12/2010	Horodezky et al.	N/A	N/A
2012/0012425	12/2011	Hayase et al.	N/A	N/A
2012/0053754	12/2011	Pease et al.	N/A	N/A
2012/0096979	12/2011	Trujillo	N/A	N/A
2012/0110493	12/2011	Cabral	N/A	N/A
2012/0223812	12/2011	Kail et al.	N/A	N/A
2012/0229394	12/2011	Ehrl et al.	N/A	N/A
2012/0229493	12/2011	Kim et al.	N/A	N/A
2012/0235804	12/2011	Gilbride et al.	N/A	N/A
2012/0256843	12/2011	Epple et al.	N/A	N/A
2012/0275892	12/2011	Allerding et al.	N/A	N/A
2012/0284656	12/2011	Chaudhri	715/765	G06F 3/04842
2012/0284658	12/2011	Hirvonen	N/A	N/A
2012/0284673	12/2011	Lamb et al.	N/A	N/A
2013/0004282	12/2012	Grimes et al.	N/A	N/A
2013/0050131	12/2012	Lee et al.	N/A	N/A
2013/0075203	12/2012	Sayles	N/A	N/A
2013/0081716	12/2012	Pirotais	N/A	N/A
2013/0093685	12/2012	Kalu et al.	N/A	N/A
2013/0101173	12/2012	Holeva et al.	N/A	N/A

2013/0103236	12/2012	Mehrgan	N/A	N/A
2013/0110329	12/2012	Kinoshita et al.	N/A	N/A
2013/0111410	12/2012	Okada et al.	N/A	N/A
2013/0132246	12/2012	Amin et al.	N/A	N/A
2013/0145360	12/2012	Ricci	N/A	N/A
2013/0152003	12/2012	Ricci et al.	N/A	N/A
2013/0159931	12/2012	Lee et al.	N/A	N/A
2013/0166146	12/2012	Tanaka	N/A	N/A
2013/0167080	12/2012	Ari et al.	N/A	N/A
2013/0169549	12/2012	Seymour et al.	N/A	N/A
2013/0176223	12/2012	Lee et al.	N/A	N/A
2013/0194228	12/2012	Tuzar	N/A	N/A
2013/0205258	12/2012	Ecker et al.	N/A	N/A
2013/0241720	12/2012	Ricci et al.	N/A	N/A
2013/0254675	12/2012	De Andrade et al.	N/A	N/A
2013/0285949	12/2012	Manabe et al.	N/A	N/A
2013/0290887	12/2012	Sun et al.	N/A	N/A
2013/0305354	12/2012	King et al.	N/A	N/A
2014/0068477	12/2013	Roh	N/A	N/A
2014/0081429	12/2013	Miles et al.	N/A	N/A
2014/0082565	12/2013	Suzuki	N/A	N/A
2014/0088827	12/2013	Yashiro et al.	N/A	N/A
2014/0109080	12/2013	Ricci	N/A	N/A
2014/0114530	12/2013	Fitch et al.	N/A	N/A
2014/0123072	12/2013	Bhowmick et al.	N/A	N/A
2014/0133906	12/2013	Frelich et al.	N/A	N/A
2014/0139354	12/2013	Miyazaki	N/A	N/A
2014/0173516	12/2013	Hwang et al.	N/A	N/A
2014/0188576	12/2013	de Oliveira et al.	N/A	N/A
2014/0236389	12/2013	Higgins et al.	N/A	N/A
2014/0258908	12/2013	Miyoshi	N/A	N/A
2014/0278621	12/2013	Medwin et al.	N/A	N/A
2014/0302774	12/2013	Burke	N/A	N/A
2014/0320293	12/2013	Hunter et al.	N/A	N/A
2014/0380243	12/2013	Furue et al.	N/A	N/A
2015/0062017	12/2014	Barabas et al.	N/A	N/A
2015/0064668	12/2014	Manci et al.	N/A	N/A
2015/0113462	12/2014	Chen et al.	N/A	N/A
2015/0130712	12/2014	Hirai	N/A	N/A
2015/0169077	12/2014	Lee	N/A	N/A
2015/0175397	12/2014	Lynn et al.	N/A	N/A
2015/0177362	12/2014	Gutierrez et al.	N/A	N/A
2015/0225218	12/2014	Strand	N/A	N/A
2015/0226560	12/2014	Chandrasekar et al.	N/A	N/A
2015/0243167	12/2014	Stählin	N/A	N/A
2015/0268746	12/2014	Cuddihy et al.	N/A	N/A
2015/0298549	12/2014	Tamura	N/A	N/A
2015/0324067	12/2014	Cabral	N/A	N/A
2016/0012707	12/2015	McKinley et al.	N/A	N/A
2016/0026838	12/2015	Gillet et al.	N/A	N/A
2016/0041803	12/2015	Markov et al.	N/A	N/A
2016/0054849	12/2015	Steiger	N/A	N/A
2016/0077688	12/2015	Shim	N/A	N/A
2016/0082960	12/2015	Slaton et al.	N/A	N/A
2016/0088146	12/2015	Ying et al.	N/A	N/A
2016/0196041	12/2015	Lavoie	N/A	N/A
2016/0306503	12/2015	Youtsey	N/A	N/A
2016/0313875	12/2015	Williams et al.	N/A	N/A
2016/0347248	12/2015	Manci et al.	N/A	N/A
2016/0374002	12/2015	Tuluca	N/A	N/A
2017/0024058	12/2016	Aubry	N/A	N/A
2017/0091704	12/2016	Wolf et al.	N/A	N/A
2017/0120723	12/2016	Sura et al.	N/A	N/A
2017/0178536	12/2016	Manci et al.	N/A	N/A

2017/0185266	12/2016	Dai	N/A	N/A
2017/0249745	12/2016	Fiala	N/A	N/A
2018/0107320	12/2017	Im et al.	N/A	N/A
2018/0126507	12/2017	Rivers et al.	N/A	N/A
2018/0143732	12/2017	Ochenas et al.	N/A	N/A
2021/0157438	12/2020	Castaneda et al.	N/A	N/A
2022/0147210	12/2021	Ochenas et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101324787	12/2007	CN	N/A
101802817	12/2009	CN	N/A
103135916	12/2012	CN	N/A
103407891	12/2012	CN	N/A
203269495	12/2012	CN	N/A
103477304	12/2012	CN	N/A
103631423	12/2013	CN	N/A
103748625	12/2013	CN	N/A
104077073	12/2013	CN	N/A
105593802	12/2015	CN	N/A
2709640	12/1977	DE	N/A
1781055	12/1979	DE	N/A
10039382	12/2001	DE	N/A
10144751	12/2002	DE	N/A
10259704	12/2002	DE	N/A
10131839	12/2003	DE	N/A
102005022476	12/2005	DE	N/A
102007023774	12/2007	DE	N/A
102008027695	12/2008	DE	N/A
102008033386	12/2009	DE	N/A
102009032492	12/2010	DE	N/A
102010005034	12/2010	DE	N/A
102010018140	12/2010	DE	N/A
102010022171	12/2010	DE	N/A
102010028911	12/2010	DE	N/A
102010055971	12/2011	DE	N/A
102011012415	12/2011	DE	N/A
102011012416	12/2011	DE	N/A
102011018520	12/2011	DE	N/A
102011018802	12/2011	DE	N/A
102011103029	12/2011	DE	N/A
102011103214	12/2011	DE	N/A
102012204694	12/2012	DE	N/A
102013006412	12/2013	DE	N/A
102014113555	12/2015	DE	N/A
102015107260	12/2015	DE	N/A
102016117013	12/2017	DE	N/A
416171	12/1990	EP	N/A
376206	12/1994	EP	N/A
712062	12/2000	EP	N/A
812799	12/2000	EP	N/A
1203743	12/2004	EP	N/A
1247686	12/2005	EP	N/A
1468958	12/2006	EP	N/A
1179466	12/2006	EP	N/A
1447374	12/2007	EP	N/A
1553044	12/2007	EP	N/A
1604942	12/2007	EP	N/A
1714822	12/2008	EP	N/A
2272788	12/2010	EP	N/A
1350668	12/2011	EP	N/A
2468678	12/2011	EP	N/A
2123596	12/2011	EP	N/A
2439165	12/2011	EP	N/A
2511677	12/2011	EP	N/A

2512163	12/2011	EP	N/A
2518009	12/2011	EP	N/A
2527288	12/2011	EP	B66F 9/20
2527288	12/2012	EP	N/A
2631760	12/2012	EP	N/A
2412661	12/2013	EP	N/A
2518000	12/2013	EP	N/A
2649820	12/2013	EP	N/A
2799388	12/2013	EP	N/A
2647591	12/2013	EP	N/A
2470465	12/2014	EP	N/A
2653429	12/2014	EP	N/A
2653430	12/2014	EP	N/A
2848437	12/2014	EP	N/A
1655263	12/2014	EP	N/A
2172413	12/2014	EP	N/A
2886507	12/2014	EP	N/A
2574589	12/2014	EP	N/A
2889253	12/2014	EP	N/A
2889258	12/2014	EP	N/A
2916505	12/2014	EP	N/A
2924551	12/2014	EP	N/A
2993155	12/2014	EP	N/A
2930603	12/2014	EP	N/A
2848575	12/2015	EP	N/A
2993155	12/2015	EP	N/A
2889254	12/2016	EP	N/A
2889255	12/2016	EP	N/A
2889256	12/2016	EP	N/A
2338720	12/2016	EP	N/A
2518003	12/2016	EP	N/A
3023382	12/2017	EP	N/A
2975982	12/2011	FR	N/A
2975981	12/2015	FR	N/A
1387670	12/1974	GB	N/A
2352521	12/2000	GB	N/A
2360500	12/2002	GB	N/A
2460326	12/2008	GB	N/A
2437629	12/2009	GB	N/A
63192398	12/1987	JP	N/A
H0624700	12/1993	JP	N/A
7002496	12/1994	JP	N/A
07242400	12/1994	JP	N/A
8091794	12/1995	JP	N/A
3166413	12/2000	JP	N/A
2003246598	12/2002	JP	N/A
2004083273	12/2003	JP	N/A
3572318	12/2003	JP	N/A
2005126017	12/2004	JP	N/A
2005324934	12/2004	JP	N/A
2010006601	12/2009	JP	N/A
2010008891	12/2009	JP	N/A
2012214155	12/2011	JP	N/A
2012234278	12/2011	JP	N/A
5109964	12/2011	JP	N/A
2013091471	12/2012	JP	N/A
5278997	12/2012	JP	N/A
2014115578	12/2013	JP	N/A
6135698	12/2016	JP	N/A
1020140051228	12/2013	KR	N/A
1992004693	12/1991	WO	N/A
1998034812	12/1997	WO	N/A
0248955	12/2001	WO	N/A
2008083982	12/2007	WO	N/A

2009026663	12/2008	WO	N/A
2009091639	12/2008	WO	N/A
2011033015	12/2010	WO	N/A
2012110207	12/2011	WO	N/A
2013074899	12/2012	WO	N/A
2013158079	12/2012	WO	N/A
2014120248	12/2013	WO	N/A
2015001875	12/2014	WO	N/A
2015151619	12/2014	WO	N/A
2017015046	12/2016	WO	N/A

OTHER PUBLICATIONS

Mouton, Benjamin; Extended European Search Report dated Mar. 22, 2023; European Application No. 23150212.1; European Patent Office; Munich, Germany. cited by applicant

Nocentini, Ilario; Extended European Search Report dated Feb. 3, 2023; European Application No. 22200980.5; European Patent Office; Munich, Germany. cited by applicant

Mouton, Benjamin; Office Action dated May 17, 2023; European Application No. 21210326; European Patent Office; Berlin, Germany. cited by applicant

Garay, Peter; Examination Report No. 1 dated Jul. 17, 2023; Australian Application No. 2022252727; IP Australia. cited by applicant

Weng, Pei Yong; Office Action; U.S. Appl. No. 17/164,953; Feb. 27, 2023; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant

Notification of Reason for Refusal dated Jan. 11, 2022; Korean Application No. 10-2019-7017939; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant

Notice of acceptance for patent application dated Jan. 4, 2022; Australian Application No. 2017363529; IP Australia. cited by applicant

Notification of Reason for Refusal dated Jan. 26, 2022; Korean Application No. 10-2019-7017420; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant

Notice of acceptance for patent application dated Jan. 25, 2022; Australian Application No. 2017363528; IP Australia. cited by applicant

Notice of acceptance patent application dated Mar. 16, 2022; Australian Application No. 2017366572; IP Australia. cited by applicant

Examination Report No. 2 for standard patent application dated Mar. 4, 2022; Australian Application No. 2017363525; IP Australia. cited by applicant

Extended European Search Report dated Mar. 24, 2022; European Application No. 21210326.1; European Patent Office; Munich, Germany. cited by applicant

Office Action dated Mar. 31, 2022; Mexican Application No. MX/a/2019/005877; Mexican Institute of Industrial Property; Mexico City, Mexico. cited by applicant

Office Action dated Mar. 31, 2022; Mexican Application No. MX/a/2019/005882; Mexican Institute of Industrial Property; Mexico City, Mexico. cited by applicant

Forkliftbrad, Rack Height Select, Sep. 24, 2013, YouTube, <https://www.youtube.com/watch?v=mMUW00P73Do> (Year: 2013). cited by applicant

Final Office Action dated May 26, 2022; U.S. Appl. No. 17/164,953; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant

Decision on Appeal dated Jul. 5, 2022; U.S. Appl. No. 15/815,788; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant

Request for the Submission of an Opinion dated Jul. 13, 2022; Korean Application No. 10-2019-7017420; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant

Decision of Patent Grant dated Jul. 11, 2022; Korean Application No. 10-2019-7017939; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant

Request for the Submission of an Opinion dated Sep. 13, 2022; Korean Application No. 10-2018-7004426; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant

Examination report No. 3 for standard patent application dated Sep. 27, 2022; Australian Application No. 2017363525; IP Australia. cited by applicant

Non-Final Office Action dated Oct. 14, 2022; U.S. Appl. No. 17/164,953; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant

Non-Final Office Action dated Sep. 29, 2022; U.S. Appl. No. 17/649,117; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant

Levy, Amy M.; Notice of Allowance; U.S. Appl. No. 15/210,049; May 16, 2019; United States Patent & Trademark Office; Alexandria, VA. cited by applicant

Levy, Amy M.; Office Action; U.S. Appl. No. 15/210,049; Aug. 7, 2018; United States Patent & Trademark Office; Alexandria, VA. cited by applicant

Levy, Amy M.; Final Office Action; U.S. Appl. No. 15/210,049; Nov. 30, 2018; United States Patent & Trademark Office; Alexandria, VA. cited by applicant

Android Developers Blog, "Touch Mode," Dec. 1, 2008, available at <https://android-developers.googleblog.com/2008/12/touch-mode.html>. cited by applicant

Android Developers, "Optimizing Navigation for TV," Apr. 9, 2012, available at <https://stuff.mit.edu/afs/sipb/project/android/docs/training/tv/optimizing-navigation-tv.html>. cited by applicant

Android Developers, "View—Android SDK," Jul. 11, 2012, available at

<http://tool.oschina.net/uploads/apidocs/android/reference/android/view/View.html>. cited by applicant
 Brochure, "Fendt Variotronic," Variotronic/1.0-EN/06-11/4.5-E, document creation date Jun. 8, 2011, 24 pages. cited by applicant
 Operator Manual, Fendt™ "VarioDoc—VarioGuide," Nov. 2011, selected pages (16 pages total). cited by applicant
 Operator's Manual, Fendt "VarioDoc," Nov. 2015, 128 pages. cited by applicant
 Operator's Manual, Fendt "VarioGuide: VarioGuide Novatel and VarioGuide Trimble," Nov. 2015, 158 pages. cited by applicant
 Apps4android, "Implementing Accessibility on Android," Apr. 18, 2012, available at <http://www.apps4android.org/?p=3628>. cited by applicant
 "iEFIS Panel User Manual," Jul. 9, 2012, 44 pages. cited by applicant
 Karlson, A.K. and Bederson, B.B., "Direct Versus Indirect Input Methods for One-Handed Touchscreen Mobile Computing," Human-Computer Interaction Lab, University of Maryland, Apr. 2007, 10 pages. cited by applicant
 Wytttenbach, Joel; Youtube video; "Fendt 3 point hitch"; published Feb. 1, 2013; <https://www.youtube.com/watch?v=Vvdw7InNpWE>. cited by applicant
 Youtube video; "Aero-TV: Big, Bright and Beautiful—MGL iEFIS Challenger 10.4" Display System"; Aero-News Network; published Nov. 21, 2013; <https://www.youtube.com/watch?v=-qZIW4a36ak>. cited by applicant
 Youtube video; Honeywell; "Bendix King KSN770 Fms Safety Display"; Avweb; published Sep. 10, 2013; <https://www.youtube.com/watch?v=iYMZPoGGtms>. cited by applicant
 Youtube video; Pretorian Technologies Ltd.; "iOS 7 Switch Control—An Introduction"; published Sep. 17, 2013; <https://www.youtube.com/watch?v=SnDA2pbBsTQ>. cited by applicant
 Ogasawara, Todd; Youtube video; "T-Mobile G1 Trackball Demo"; Oct. 22, 2008; <https://www.youtube.com/watch?v=Tq3lwVszW40>. cited by applicant
 Wytttenbach, Joel; Youtube video; "Driving a Fendt"; published Feb. 2, 2013; <https://www.youtube.com/watch?v=tyX5UPYWFR8&t=7s>. cited by applicant
 Internet video; fendt.tv; "Operating the new Varioterminal"; Sep. 4, 2010; https://www.fendt.tv/en/home/operating-the-new-variorterminal_1312.aspx. cited by applicant
 Internet video; fendt.tv; "Fendt Variotronic"; Nov. 10, 2013; https://www.fendt.tv/en/home/fendt-variortronic-the-leading-edge-through-integration_1612.aspx. cited by applicant
 "Mazda3 Navigation System—Information Guide", Maple Shade Mazda; https://www.youtube.com/watch?v=CzSW38Uu_5s; published on Oct. 9, 2013. cited by applicant
 "The Tech Inside, Episode 3: 2014 Mazda 6"; PhoneDog; <https://www.youtube.com/watch?v=odpnSuUefNg>; published on Aug. 1, 2013. cited by applicant
 "2013 and 2014 CX-5 Navigation System Tutorial"; Don Mealey's Sport Mazda; <https://www.youtube.com/watch?v=y9v1dvxsFDU>; published on Jul. 27, 2013. cited by applicant
 "How-To-Use: 2013 Mazda CX-9 Navigation Tutorial Video"; RamseyMazdaNJ; <https://www.youtube.com/watch?v=P584CUo8Hno>; published on Jul. 10, 2013. cited by applicant
 "Mazda CX-5—Navigation System—Information Guide"; Maple Shade Mazda; <https://www.youtube.com/watch?v=JLTMeOalaaM>; published on Jul. 23, 2013. cited by applicant
 "2014 Ford Fiesta MyFord Touch Infotainment Review"; Alex on Autos; <https://www.youtube.com/watch?v=p6FM6mwfLGU>; published Dec. 4, 2013. cited by applicant
 "Navigating Infotainment With a Navigation System"; AutoHow2; <https://www.youtube.com/watch?v=zuQ-ZKeu6Fk&feature=youtu> published on Nov. 4, 2013. cited by applicant
 "Take a Tour of the Latest BMW iDrive system"; bmwopenroad; <https://www.youtube.com/watch?v=XdnOjevFWIE>; published on Jul. 30, 2010. cited by applicant
 "BMW X5 touchscreen"; Naessenselectronics; <https://www.youtube.com/watch?v=VNReXZFKZI4>; published on Jul. 11, 2012. cited by applicant
 Joe Bruzek; "Mazda Turns Up Connectivity With New System"; Cars.com; published on Nov. 14, 2013; <https://www.cars.com/articles/2013/11/mazda-turns-up-connectivity-with-new-system/>; downloaded on Sep. 12, 2018. cited by applicant
 "Using Infotainment with a Navigation System—Buick LaCrosse" video transcription; AutoHow2—Informative Automotive Videos; <http://www.autohow2.com/video/using-infotainment-with-navigation-buick-lacrosse>; downloaded on Sep. 12, 2018. cited by applicant
 "Fendt Teach In," <https://www.youtube.com/watch?v=b16uS4SnDEs>; published on May 10, 2013. cited by applicant
 "Fendt touchscreen overview," <https://www.youtube.com/watch?v=idPm92i3cY0>; published on Feb. 3, 2013. cited by applicant
 "Fendt Variotronic," <https://www.youtube.com/watch?v=EEYAnEzennA>; published on May 4, 2010. cited by applicant
 Bengtsson, Johan; International Search Report and Written Opinion of the International Search Authority; International Application No. PCT/US2016/042230; Oct. 10, 2016; European Patent Office; Rijswijk, Netherlands. cited by applicant
 "Intelliview™ IV 10.4" Color Touchscreen Display"; Farm with Precision with New Holland; <http://newhollandrochester.com/wp-content/uploads/pdf-front/145865207194354078.pdf>. cited by applicant
 "Winmate's Military Grade Rugged Console Panel PC and Display"; Jun. 25, 2014; <http://www.army-technology.com/contractors/computers/winmate-communication/pressreleases/presswinmates-military-grade-rugged-console-panel-pc-and-display>. cited by applicant
 "Jungheinrich Presents New Reach Truck"; Mar. 19, 2013; Jungheinrich; <http://www.jungheinrich.com/en/press/article/nl/310-jungheinrich-presents-new-reach-truck/>. cited by applicant
 "Linde Safety Pilot: A technical breakthrough"; Industrial Vehicle Technology International report; Apr. 25, 2014; <http://www.ivtinternational.com/news.php?NewsID=58313>. cited by applicant
 Kaiser, Tiffany; "Microsoft Brings Live Tiles to Infotainment Systems with 'Windows in the Car' Concept"; Apr. 7, 2014; <http://www.dailytech.com/microsoft+brings+live+tiles+to+infotainment+systems+with+windows+in+the+car+concept/article34667.htm>

cited by applicant
Michelangelo, Barba; International Search Report and Written Opinion of the International Searching Authority; International Application No. PCT/US2017/062137; Feb. 26, 2018; European Patent Office; Rijswijk, Netherlands. cited by applicant
“Next Generation of Winmate G-Win Series with Intel's® latest quad-core Bay Trail processor,” <http://www.army-technology.com/contractors/computers/winmate-communication/pressreleases/pressnext-generation-g-win-series>; published May 7, 2014. cited by applicant
Michelangelo, Barba; International Search Report and Written Opinion of the International Searching Authority; International Application No. PCT/US2017/062140; Feb. 26, 2018; European Patent Office; Rijswijk, Netherlands. cited by applicant
Michelangelo, Barba; International Search Report and Written Opinion of the International Searching Authority; International Application No. PCT/US2017/062145; Feb. 26, 2018; European Patent Office; Rijswijk, Netherlands. cited by applicant
Michelangelo, Barba; International Search Report and Written Opinion of the International Searching Authority; International Application No. PCT/US2017/062130; Mar. 1, 2018; European Patent Office; Rijswijk, Netherlands. cited by applicant
Intermec Vehicle-Mount Computers Deliver Next Generation Technology to the Forklift, Boosting Productivity and Performance; Intermeic; News Release; Jan. 2, 2012; Everett, Washington; https://www.intermec.com/about_us/newsroom/press_releases/2012-02-01-CV41-CV61-Forklift-Vehicle-Mount-Computers.aspx. cited by applicant
Operator Manual for Crown RM 6000 Series Truck, Document No. PF18574 Rev. 5/17, © 2010, four pages; Crown Equipment Corporation. cited by applicant
“Mastering ease of use with Topcon System 350,” Topcon Precision Agriculture; <https://www.youtube.com/watch?v=far-XW8qKMY>; published on Oct. 19, 2012. cited by applicant
“Topcon X30 and System 350,” Topcon Precision Agriculture; https://www.youtube.com/watch?v=mBa_Xk7HjU; published on Nov. 17, 2011. cited by applicant
Yeow, Leslie; Official Action dated Jul. 7, 2023; Canadian Application No. 3,039,800; Canadian Intellectual Property Office, Quebec, Canada. cited by applicant
Yeow, Leslie; Official Action dated Jul. 7, 2023; Canadian Application No. 3,040,308; Canadian Intellectual Property Office, Quebec, Canada. cited by applicant
Clime, Adrian; Official Action dated Jul. 10, 2023; Canadian Application No. 3,039,802; Canadian Intellectual Property Office, Quebec, Canada. cited by applicant
Yeow, Leslie; Office Action dated Jul. 26, 2023; Canadian Application No. 3,040,305; CIPO; Quebec, Canada. cited by applicant
Larracilla, Edgar Flores; Second Office Action dated Oct. 17, 2023; Mexican Application No. MX/a/2019/005883; IMPI; Mexico City, Mexico. cited by applicant
Weng, Pei Young; Notice of Allowance dated Oct. 18, 2023; U.S. Appl. No. 17/164,953; United States Patent and Trademark Office, Alexandria, Virginia. cited by applicant
“Topcon demonstrates iPad-like X30 console,” Topcon Precision Agriculture; <https://www.youtube.com/watch?v=jISTF8e6UTA>; published on Oct. 2, 2011. cited by applicant
Vu, Toan H.; Office Action; U.S. Appl. No. 15/815,778; Oct. 18, 2019; United States Patent and Trademark Office; Alexandria, VA. cited by applicant
Abou El Seoud, Mohamed; Final Office Action; U.S. Appl. No. 15/815,788; Nov. 14, 2019; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Australian Examination Report No. 1 dated Oct. 8, 2020; Australian Application No. 2016296471; IP Australia. cited by applicant
Communication Pursuant to Article 94(3) EPC dated Oct. 8, 2020; European Patent Application No. 17812130; European Patent Office; Berlin, Germany. cited by applicant
Communication Under Rule 71(3) EPC dated Oct. 7, 2020; European Patent Application No. 17811772; European Patent Office; Berlin, Germany; p. 8. cited by applicant
Final Office Action dated Oct. 1, 2020; U.S. Appl. No. 15/815,788; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Vu, Toan H.; Office Action; U.S. Appl. No. 15/815,778; Sep. 3, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Notification of the First Office Action; Chinese Application No. 201680034684.4; Jul. 22, 2020; China National Intellectual Property Administration; Beijing, China. cited by applicant
Song, Daeho D.; Advisory Action; U.S. Appl. No. 15/815,801; Jul. 14, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Andrea C. Leggett; Notice of Allowance and Fees Due; U.S. Appl. No. 15/815,810; Apr. 17, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Abou El Seoud, Mohamed; Office Action; U.S. Appl. No. 15/815,788; May 14, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Vu, Toan H.; Office Action; U.S. Appl. No. 15/815,778; Apr. 29, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Song, Daeho D.; Office Action; U.S. Appl. No. 15/815,801; Apr. 22, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Johan Bengtsson; Communication pursuant to Article 94(3); European Application No. 16742538.8; Mar. 16, 2020; European Patent Office; Berlin, Germany. cited by applicant
Song, Daeho D.; Office Action; U.S. Appl. No. 15/815,801; Dec. 23, 2019; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Leggett, Andrea C.; Office Action; U.S. Appl. No. 15/815,810; Dec. 30, 2019; United States Patent and Trademark Office; Alexandria,

Virginia. cited by applicant
Bengtsson, Johan EPC Official Action; European Application No. 16742538.8; Jul. 10, 2019; European Patent Office; Munich, Germany. cited by applicant
Weng, Pei Yong; Office Action; U.S. Appl. No. 16/562,881; Jul. 10, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Weng, Pei Yong; Notice of Allowance; U.S. Appl. No. 16/562,881; Nov. 4, 2020; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
First Search; Chinese Application No. 201680034684.4; Jul. 16, 2020; China National Intellectual Property Administration; Beijing, China. cited by applicant
Andrea C. Leggett; Office Action; U.S. Appl. No. 15/815,810; Jun. 14, 2019; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Abou El Seoud, Mohamed; Office Action; U.S. Appl. No. 15/815,788; Jun. 20, 2019; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Notice of Allowance dated Nov. 16, 2020; U.S. Appl. No. 15/815,801; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Final Office Action dated Dec. 16, 2020; U.S. Appl. No. 15/815,778; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Benjamin Mouton; Communication pursuant to Article 94(3); European Application No. 17817363.9; Nov. 11, 2020; European Patent Office; Berlin, Germany. cited by applicant
Notification of Second Office Action dated Mar. 3, 2021; Chinese Application No. 201680034684.4; China National Intellectual Property Administration; Beijing, China. cited by applicant
Communication pursuant to Article 94(3) EPC dated Feb. 23, 2021; European Application No. 17825310; European Patent Office; Berlin, Germany. cited by applicant
Examiner's Answer dated Apr. 19, 2021; U.S. Appl. No. 15/815,788; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Notification of Reason for Refusal dated Jul. 21, 2021; Korean Application No. 10-2019-7017939; Korean Intellectual Property Office. cited by applicant
Notification of Reason for Refusal dated Jul. 21, 2021; Korean Application No. 10-2019-7017594; Korean Intellectual Property Office. cited by applicant
Notification of Reason for Refusal dated Jul. 19, 2021; Korean Application No. 10-2019-7017500; Korean Intellectual Property Office. cited by applicant
Notification of the Third Office Action dated Jul. 14, 2021; Chinese Application No. 201680034684.4; China National Intellectual Property Administration. cited by applicant
Examination Report No. 1 dated Sep. 28, 2021; Australian Application No. 2017363529; IP Australia. cited by applicant
Notification of Decision to Grant Patent Right for Invention dated Oct. 9, 2021; Chinese Application No. 2017800676853; China National Intellectual Property Administration; Beijing, China. cited by applicant
Summons to attend oral proceedings pursuant to Rule 115(1) EPC dated Sep. 15, 2021; European Application No. 17817363.9; European Patent Office; Berlin, Germany. cited by applicant
Communication pursuant to Article 94(3) EPC dated Jul. 15, 2021; European Application No. 17812130.7; European Patent Office; Berlin, Germany. cited by applicant
Examination Report No. 1 dated Oct. 12, 2021; Australian Application No. 2017366572; IP Australia. cited by applicant
Examination Report No. 1 dated Oct. 12, 2021; Australian Application No. 2017363525; IP Australia. cited by applicant
Examination Report No. 1 dated Oct. 12, 2021; Australian Application No. 2017363528; IP Australia. cited by applicant
First Search dated Sep. 16, 2021; Chinese Application No. 2017800676853; Chinese National Intellectual Property Administration; Beijing, China. cited by applicant
First Search dated Sep. 27, 2021; Chinese Application No. 2017800676849; Chinese National Intellectual Property Administration; Beijing, China. cited by applicant
Notification of First Office Action dated Oct. 8, 2021; Chinese Application No. 2017800676849; China National Intellectual Property Administration; Beijing, China. cited by applicant
Notification to Grant Patent Right for Invention dated Dec. 3, 2021; Chinese Application No. 201680034684.4; The State Intellectual Property Office of People's Republic of China; Beijing, China. cited by applicant
The First Office Action dated Nov. 26, 2021; Chinese Application No. 201780067690.4; The State Intellectual Property Office of People's Republic of China; Beijing, China. cited by applicant
Office Action dated Jan. 24, 2022; U.S. Appl. No. 17/164,953; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
The First Office Action dated Nov. 29, 2021; Chinese Application No. 201780067691.9; The State Intellectual Property Office of People's Republic of China; Beijing, China. cited by applicant
First Search dated Nov. 19, 2021; Chinese Application No. 201780067691.9; The State Intellectual Property Office of People's Republic of China; Beijing, China. cited by applicant
Grant of Patent dated Jan. 7, 2022; Korean Application No. 10-2019-7017500; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant
Grant of Patent dated Jan. 7, 2022; Korean Application No. 10-2019-7017594; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant
Clime, Adrian; Official Action dated Mar. 25, 2024; Canadian Application No. 3,039,802; Canadian Intellectual Property Office;

Quebec, Canada. cited by applicant
Yeow, Leslie; Official Action dated May 1, 2024; Canadian Patent Application No. 3,040,305; CIPO; Quebec, Canada. cited by applicant
Written Decision on Registration dated Jan. 17, 2023; Korean Application No. 10-2019-7017420; Korean Intellectual Property Office; Daejeon, Republic of Korea. cited by applicant
Abou El Seoud, Mohamed; Final Office Action dated Feb. 9, 2023; U.S. Appl. No. 17/649,117; United States Patent and Trademark Office; Alexandria, Virginia. cited by applicant
Garay, Peter; Examination Report No. 1 dated May 19, 2025; Australian Application No. 2024200735; IP Australia; Canberra, Australia cited by applicant

Primary Examiner: El Seoud; Mohamed Abou

Attorney, Agent or Firm: Stevens & Showalter LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 15/815,788, filed Nov. 17, 2017, entitled “USER INTERFACE DEVICE FOR INDUSTRIAL VEHICLE,” by Jonathan Ochenas, et al., which claims the benefit of U.S. Provisional Application No. 62/425,099, filed Nov. 22, 2016, both of which are hereby incorporated by reference in their entirety. This application is related to U.S. patent application Ser. No. 15/210,049 (now U.S. Pat. No. 10,430,073), entitled “PROCESSING DEVICE HAVING A GRAPHICAL USER INTERFACE FOR INDUSTRIAL VEHICLE,” by Anthony T. Castaneda, et al., filed on Jul. 14, 2016, which claims the benefit of U.S. Provisional Patent Application Ser. No. 62/193,840, filed on Jul. 17, 2015, both of which are hereby incorporated by reference in their entirety. This application is also related to the following applications: U.S. patent application Ser. No. 15/815,778 (now U.S. Pat. No. 11,054,980), entitled “USER INTERFACE DEVICE FOR INDUSTRIAL VEHICLE,” by Jonathan Ochenas, et al.; U.S. patent application Ser. No. 15/815,801 (now U.S. Pat. No. 10,936,183), entitled “USER INTERFACE DEVICE FOR INDUSTRIAL VEHICLE,” by Jonathan Ochenas, et al.; and U.S. patent application Ser. No. 15/815,810 (now U.S. Pat. No. 10,754,466), entitled “USER INTERFACE DEVICE FOR INDUSTRIAL VEHICLE,” by Jonathan Ochenas, et al., all of which are hereby incorporated by reference in their entirety.

FIELD OF THE INVENTION

(1) The present invention relates to electronic systems for use in an industrial vehicle that interacts with and presents information to a vehicle operator via a graphical user interface.

BACKGROUND OF THE INVENTION

(2) Industrial vehicles, such as forklift trucks and other materials handling trucks, are often equipped with a user interface that allows a vehicle operator to perform a variety of functions, such as accessing and viewing information programmed into the truck, entering new information, and viewing images from onboard cameras. When entering or accessing information, the operator may be required to scroll or click through large amounts of information across multiple screens or scroll through numerous options within a menu. In addition, operators working in cold environments, such as freezers, typically must wear gloves, which increases the difficulty of navigating through multiple screens and menus.

SUMMARY OF THE INVENTION

(3) Various aspects and embodiments of the present disclosure address various technical problems associated with the need for an operator of a materials handling vehicle to spend excess time scrolling, clicking or reviewing a large amount of information to locate needed information for viewing on a vehicle user interface screen during operation of the vehicle. The present disclosure provides a first technical solution which involves detecting activation of an icon corresponding to a widget and, in response to detecting activation of the one icon, automatically moving the corresponding widget to a designated widget space for operator use. Hence, an operator need not manually search through multiple widgets, find and move the desired widget to a screen display as the desired widget is automatically moved to the screen upon activation of the corresponding icon. Another technical solution involves detecting activation of an icon corresponding to a widget and, in response to detecting the activation of the one icon, allowing a first menu portion of the one widget to be displayed. Hence, an operator may access a menu portion of the one widget when needed and desired upon activation of the corresponding icon and inadvertent access to or appearance of the menu portion is prevented when the corresponding icon is not activated. A further technical solution involves changing a state of a portion of a widget, such as an outline of a widget, upon a vehicle function being completed, e.g., a carriage assembly reaching a desired height, which is advantageous as this provides an operator with quick and clear confirmation that the vehicle function has been successfully executed. Yet another technical solution involves detecting activation of an icon corresponding to a widget and, in response, moving the widget to a predefined widget space, moving the widget from the predefined widget space in response to an operator command to move the widget away from the widget space and automatically moving the widget back to the predefined widget space in response to a command related to a vehicle operation. Such a solution provides a user interface that is flexible so as to allow an operator to move the widget corresponding to an activated icon away from the predefined widget space when the operator wishes to view another widget for additional information yet automatically returns the widget corresponding to the activated icon to the predefined widget space in response to a command related to a vehicle operation, thereby saving the operator time as the operator need not manually look and move the widget corresponding to the activated icon back to the predefined widget space. Other technical problems and corresponding solutions are set out herein.

(4) In accordance with a first aspect of the present disclosure, a processing device comprising a graphical user interface in an

industrial vehicle is provided. The processing device comprises a screen display, such as a touch screen display that receives gesture commands from a vehicle operator, memory storing executable instructions, and a processor in communication with the memory. The processor when executing the executable instructions defines a plurality of widgets, in which each widget comprises a visual representation of a current state of an associated function of the industrial vehicle, controls the display of or causes to be displayed a subset of the plurality of widgets on a portion of the screen display defining a plurality of widget spaces, and controls the display of or causes to be displayed an icon tray or icon row on the screen display comprising one or more icons, in which at least one of the one or more icons corresponds to a respective one of the plurality of widgets.

(5) The processor when executing the executable instructions in an example embodiment defines the icon tray as a separate portion of the screen display from the plurality of widget spaces, the icon tray being spaced apart from the plurality of widget spaces. The processor when executing the executable instructions may lock one of the plurality of widgets in position in a locked widget space upon activation of an icon corresponding to the one widget. The widget may be spaced away from its corresponding icon. The processor when executing the executable instructions may detect the activation of the icon corresponding to the one widget, and in response to detecting the activation, automatically move the one widget to the locked widget space and shift the remaining one or more widgets in the subset to the one or more remaining widget spaces. The processor when executing the executable instructions may shift a position of one or more of the widgets of the subset on the touch screen display following detection of a gesture command on the touch screen display.

(6) The processor when executing the executable instructions may control or cause display of a first menu associated with one of the plurality of widgets when the one widget is displayed in one of the plurality of widget spaces on the screen display and a first menu portion of the one widget is activated by the vehicle operator. In some particular embodiments, the first menu may comprise a list, a sidebar, or a scroll wheel, in which a display of options in the first menu may be altered by one of a tap gesture, swipe gesture, a slide gesture, or a rotating gesture on the touch screen display and in which the options within the first menu may be color-coded with a different color. In other particular embodiments, the first menu portion of the one widget may be activated by the vehicle operator touching or selecting the first menu portion. In further particular embodiments, the processor when executing the executable instructions may define a plurality of sub-menus, each sub-menu corresponding to a particular option within the first menu, in which one sub-menu may be displayed on the screen display after the corresponding option within the first menu has been selected and a sub-menu portion of the one widget is activated.

(7) The processor when executing the executable instructions may further color code at least a portion of the one sub-menu using a same color associated with the corresponding option within the first menu. In some embodiments, one or more of the first menu or the sub-menus may be displayed within the one widget. In other embodiments, one or more of the first menu or the sub-menus may be displayed in a separate window that is temporarily superimposed over one or more of the widget spaces. In further embodiments, the processor when executing the executable instructions may define the one widget as a rack height select (RHS) widget, the RHS widget comprising a workspace zone menu defining the first menu, in which the workspace zone menu comprises a plurality of workspace zones, each workspace zone having a corresponding sub-menu comprising a plurality of stored rack heights associated with the workspace zone. It is also contemplated that the first menu may comprise parameters or categories other than the zone. For example, the first menu may comprise a listing of racks designated by type, name and/or number. In some particular embodiments, at least a portion of a visual depiction of each workspace zone comprises a different color, and at least a portion of a visual depiction of each corresponding sub-menu comprises a same color as the associated workspace zone.

(8) The processor when executing the executable instructions may define one of the plurality of widgets as a rack height select (RHS) widget comprising a workspace zone selection portion defining a first menu portion, in which a rack height selection portion defines a sub-menu portion, and a load presence indicator. In some particular embodiments, the processor when executing the executable instructions may control or cause display of the RHS widget in one of the widget spaces, detect a selection of a particular workspace zone and a particular stored rack height related to the particular workspace zone, in which after the selection of the particular workspace zone and the particular stored rack height, the workspace zone selection portion comprises an identifier of the particular workspace zone selected, the rack height selection portion comprises an identifier of the particular stored rack height selected, and the load presence indicator comprises a visual indication of a presence or an absence of a detected load. In other particular embodiments, the processor when executing the executable instructions may override the indication of the absence of a detected load upon activation of the load presence indicator by the vehicle operator.

(9) In some embodiments, the processing device may further comprise a vehicle network system connecting the processor to at least one vehicle network bus, in which the processor extracts a current position of a carriage assembly and a current sensed load weight. The processor when executing the executable instructions may define one of the plurality of widgets as a capacity data monitoring (CDM) widget comprising a visual representation of the current position of the carriage assembly and the current sensed load weight.

(10) The processing device may further comprise a vehicle operator control section comprising one or more physical input control elements, in which the one or more physical input control elements are used to make selections on the screen display. In some particular embodiments, the one or more physical input control elements may comprise at least one of a five-button control, a rotary control knob, a trigger switch on a multifunction control handle, or a trigger switch on an armrest.

(11) The processor when executing the executable instructions may determine if a speed of the vehicle is below a threshold speed, and change one or more of the widgets of the subset on the touch screen display following detection of a gesture command on the touch screen display and if the speed of the vehicle is below the threshold speed.

(12) The processor when executing the executable instructions may move one of the plurality of widgets to a predefined widget space upon activation of an icon corresponding to the one widget.

(13) In accordance with a second aspect of the present disclosure, a processing device comprising a graphical user interface is provided. The processing device comprises a screen display, memory storing executable instructions, and a processor in

communication with the memory. The processor when executing the executable instructions defines a plurality of widgets, in which each widget comprises a visual representation of a current state of an associated function, controls or causes display of a subset of the plurality of widgets on a portion of the screen display defining a plurality of widget spaces, controls or causes display of an icon tray on the screen display comprising one or more icons, in which at least one of the one or more icons corresponds to a respective one of the plurality of widgets, detects activation of the one of the one or more icons corresponding to the one widget, and in response to detecting the activation of the one icon, locks the respective one widget in position in one of the widget spaces.

(14) The processor when executing the executable instructions may, in response to detecting the activation of the one icon, automatically move the one widget to the locked widget space and shift the remaining one or more widgets in the subset to the one or more remaining widget spaces.

(15) In accordance with a third aspect of the present disclosure, a processing device comprising a graphical user interface in an industrial vehicle is provided. The processing device comprises a screen display, memory storing executable instructions, and a processor in communication with the memory. The processor when executing the executable instructions defines one or more widgets each comprising a visual representation of a current state of an associated function of the industrial vehicle, controls or causes display of at least one of the one or more widgets on a portion of the screen display defining one or more widget spaces, controls or causes display of an icon tray on the screen display comprising one or more icons, in which at least one of the one or more icons corresponds to a respective one of the one or more widgets, detects activation of the one icon corresponding to the one widget, in response to detecting the activation of the one icon, allows a first menu portion of the one widget to be displayed, controls or causes display of a first menu associated with the one widget.

(16) In an embodiment, the processor when executing the executable instructions may, in response to detecting the activation of the one icon, allow a first menu portion of the one widget to be activated, detect activation of the first menu portion, and, in response to detecting the activation of the first menu portion, control or cause display of the first menu associated with the one widget.

(17) The processor when executing the executable instructions may, further in response to detecting the activation of the one icon, lock the one widget in position in a first widget space on the screen display.

(18) In accordance with a fourth aspect of the present invention, a processing device comprising a graphical user interface in an industrial vehicle is provided. The processing device comprises a screen display, memory storing executable instructions, and a processor in communication with the memory. The processor when executing the executable instructions defines one or more widgets, each widget comprising a visual representation of a current state of an associated function of the industrial vehicle, and controls or causes display of a rack height select (RHS) widget on a portion of the screen display defining one or more widget spaces, in which the RHS widget comprises a portion that changes state upon a related vehicle function being completed, e.g., a carriage assembly reaching a desired height. The outline of the RHS widget, defining the portion, may become one of darker, wider or both darker and wider upon a related vehicle function being completed, e.g., a carriage assembly reaching a desired height.

(19) In accordance with a fifth aspect of the present invention, a processing device comprising a graphical user interface in an industrial vehicle is provided. The processing device comprises a screen display, memory storing executable instructions, and a processor in communication with the memory. The processor when executing the executable instructions defines a plurality of widgets, in which each widget comprises a visual representation of a current state of an associated function of the industrial vehicle, controls or causes display of a subset of the plurality of widgets on a portion of the screen display defining a plurality of widget spaces, controls or causes display of an icon tray on the screen display comprising one or more icons, in which at least one of the one or more icons corresponds to a respective one of the plurality of widgets, detects activation of the one of the one or more icons corresponding to the one widget. The processor when executing the executable instructions, in response to detecting the activation of the one icon, moves the respective one widget to a predefined widget space, moves the respective one widget from the predefined widget space in response to an operator command, and moves the one widget back to the predefined widget space in response to a command related to a vehicle operation.

(20) The command related to a vehicle operation may comprise one of a command to activate a traction motor to effect vehicle movement or a command to lift or lower a carriage assembly.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) While the specification concludes with claims particularly pointing out and distinctly claiming the present invention, it is believed that the present invention will be better understood from the following description in conjunction with the accompanying Drawing Figures, in which like reference numerals identify like elements, and wherein:

(2) FIG. 1A is a perspective view of an industrial vehicle in accordance with principles of the present disclosure;

(3) FIG. 1B is a top view of an operator's compartment of an industrial vehicle in accordance with principles of the present disclosure;

(4) FIG. 2A is a block diagram of an industrial vehicle computing enterprise in accordance with principles of the present disclosure;

(5) FIG. 2B is a block diagram of a special purpose processing device on an industrial vehicle in accordance with principles of the present disclosure;

(6) FIG. 3 is an illustration of the processing device of FIG. 2B, implemented as a graphical user interface having a touch screen display and a corresponding vehicle operator control section in accordance with principles of the present disclosure;

(7) FIG. 4 is a block diagram of operational modules executed by a processor of the special purpose processing device of FIG.

2B in accordance with principles of the present disclosure;

(8) FIG. 5 is a schematic diagram illustrating an array of widgets for display on a display screen of the processing device of FIG. 3 in accordance with principles of the present disclosure;

(9) FIGS. 6A and 6B are schematic screen shots of the display screen of the processing device of FIG. 3 in accordance with principles of the present disclosure;

(10) FIGS. 7A-7I are schematic screen shots of the display screen of the processing device of FIG. 3 in accordance with principles of the present disclosure;

(11) FIGS. 8-11 are flowcharts of exemplary computer-implemented processes for defining and controlling display of one or more items on a display screen of a display and processing device, in accordance with principles of the present disclosure; and

(12) FIG. 12 is a block diagram of a computer processing system capable of implementing any of the systems, modules, or methods described herein, in accordance with principles of the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

(13) In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration, and not by way of limitation, specific preferred embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized and that changes may be made without departing from the spirit and scope of the present invention.

(14) With reference to FIGS. 1A and 1B, an exemplary industrial vehicle **100** (hereinafter “vehicle”) is shown. While the present disclosure is made with reference to the illustrated vehicle **100**, which comprises a reach truck, it will be apparent to those of skill in the art that the vehicle **100** may comprise a variety of other industrial vehicles, such as a stock picker, a turret truck, a tow tractor, a rider pallet truck, a walkie stacker truck, a counterbalance forklift truck, etc. and the following description of the invention with reference to the figures should not be limited to a reach truck unless otherwise specified. The vehicle **100** comprises a main body or power unit **112** and one or more wheels, including a pair of fork-side first wheels **160A**, **160B** coupled to a pair of outriggers **180A**, **180B** (only one first wheel **160A** and one outrigger **180A** are shown in FIG. 1A) and a powered and steered second wheel **120** located underneath a frame **114** of the power unit **112**. An overhead guard **130** comprises one or more vertically extending supports, such as support structures **132A**, **132B**, affixed to the frame **114**, see FIG. 1A, structure **132B** is not shown in FIG. 1B.

(15) The vehicle **100** further comprises a load handling assembly **140**, which generally comprises a mast assembly **142** and a carriage assembly **144**. The mast assembly **142** is positioned between the outriggers **180A**, **180B** and may comprise, for example, a fixed mast member **146** affixed to the frame **114** and nested first and second movable mast members **148**, **150**. It is noted that the vehicle **100** may comprise additional or fewer movable mast members than the two members **148**, **150** shown in FIG. 1A. The carriage assembly **144** may comprise, for example, a lifting carriage (not shown) vertically movable along the mast assembly **142**, a fork carriage assembly **154** coupled to the lifting carriage for vertical movement with the lifting carriage and a fork structure coupled to the fork carriage assembly **154** comprising a pair of forks **156A**, **156B** (only one fork **156A** is shown in FIG. 1A) for carrying a load **116**, such as a loaded pallet. The fork carriage assembly **154** may comprise a base carriage (not shown) coupled to the lifting carriage and a support carriage (not shown) coupled to the base carriage, which is moveable laterally and may also pivot relative to the base carriage. The forks **156A**, **156B** are coupled to the support carriage. The carriage assembly **144** is movable generally vertically along the mast assembly **142** and may further comprise a reach assembly (not shown) positioned between the lifting carriage and the fork carriage assembly **154** for horizontally extending the fork carriage assembly **154** away from and toward the mast assembly **142**.

(16) A battery (not shown), which is housed in a compartment within the frame **114**, supplies power to a traction motor (not shown) that is connected to the second wheel **120** and to one or more hydraulic motors (not shown). The hydraulic motor(s) supply power to several different systems, such as one or more hydraulic cylinders (not shown) for effecting generally vertical movement of the movable mast members **148**, **150** relative to the fixed mast member **146** and generally vertical movement of the carriage assembly **144** relative to the second movable mast member **150** of the mast assembly **142**, as shown by arrow A in FIG. 1A; generally longitudinal movement of the reach assembly (commonly referred to as “reach”), as shown by arrow B; generally transverse or lateral movement of the support carriage and the forks **156A**, **156B** relative to the base carriage (commonly referred to as “sideshifting”), as shown by arrow C; and pivotable movement of the support carriage and forks **156A**, **156B** relative to the base carriage. Hence, the carriage assembly **144** moves relative to the second movable mast member **150** and also moves with the first and second movable mast members **148**, **150** relative to the fixed mast member **146**. The traction motor and the second wheel **120** define a drive mechanism for effecting movement of the vehicle **100** across a floor surface.

(17) An operator's compartment **122** is located within the main body **112** for receiving an operator driving or operating the vehicle **100**. The operator's compartment **122** comprises a variety of control elements including one or more handles, knobs, levers, switches, buttons, sliders, encoders, and combinations thereof, along with one or more devices that display information to the operator and/or receive operator input. For example, a tiller knob **124** is provided within the operator's compartment **122** for controlling steering of the vehicle **100**. An armrest **170** located adjacent to an operator seat **128** comprises a control panel **126** for receiving input from the operator. In the embodiment shown in FIGS. 1A and 1B, the control panel **126** on the armrest **170** comprises a plurality of fingertip levers **172** which, in the illustrated embodiment, may control carriage assembly (fork) raise/lower, fork tilt, fork sideshifting, fork extend or reach and the like. The control panel **126** may also comprise a switch (not labeled) for controlling a travel direction of the vehicle (forward or backward) and a rotary control knob **162** for controlling a rack height select function, e.g., wherein the vehicle is programmed to define a set of fork stop locations for each of a plurality of rack beam heights in respective storage zones. The control panel **126** may also comprise one or more dual-axis control levers or a multifunction control handle (not shown) in place of, or in addition to, the fingertip levers **172**. In embodiments in which the control panel **126** comprises levers, the traction motor may be actuated by depression of a floor pedal (not shown). In a

further embodiment, the control panel **126** may include a one-click button or trigger switch (not shown) for controlling a rack height select function. In yet another embodiment, where a multifunction control handle (not shown) is used in place of the fingertip levers **172**, a trigger switch may be provided on the multifunction control handle for controlling a rack height select function. In embodiments in which the control panel **126** comprises a multifunction control handle, the traction motor may be actuated by operation of the multifunction control handle.

(18) In the embodiment shown in FIG. **1B**, the power unit comprises a console **138** upon which may be mounted a display and processing unit **151** (also referred to herein as a “display unit”) comprising a screen display **152** and a five-button keypad **164** comprising up, down, right, left, and enter buttons for entering information and commands, navigating through menus on the screen display **152**, making selections, etc., as described herein. As described herein, the screen display **152** may be implemented as a touch screen (also referred to herein as a touch screen display). The rotary control knob **162** may be used in addition to, or in place of, one or more of the functions of the five-button keypad **164**. The operator may press a tilt release lever or button **138A** located on the console **138** to tilt the display unit **151** toward or away from the operator.

(19) In FIG. **1B**, the display and processing unit **151** is depicted as being located in front of the operator's seat **128**. However, the display unit **151** may be placed at other locations in the operator's compartment **122**, so long as the display unit **151** is easily viewed and accessed by the operator. For example, the display unit **151** may be located in an area **166** (shown with dashed lines), which includes a dashboard area adjacent to the console **138**. The area **166** also includes an optional extension of the console **138** along a right side of the operator's compartment **122**. Location of the display unit **151** in the area **166**, for example, allows the operator easy access to the screen display **152** and the five-button keypad **164** without moving his or her arm from the armrest **170**.

(20) In some embodiments, the display unit **151** may be mounted, for example, on one of the support structures **132A**, **132B**. Some vehicles **100**, such as those designed to operate in cold storage, may include an enclosed cabin (not shown) comprising the operator's compartment **122**, and the display unit **151** may be mounted elsewhere in the operator's compartment **122**, such as on one or more additional support structures (not shown). In other embodiments, the display unit **151** may comprise a separate or standalone device, such as a tablet or laptop computer. In addition, although the rotary control knob **162** is depicted in FIG. **1B** as being located on the armrest **170**, the rotary control knob **162** in some embodiments may be located elsewhere within the operator's compartment **122**, e.g., on the display unit **151** (see FIG. **3**).

(21) Turning now to FIG. **2A**, a general diagram of an industrial vehicle computing enterprise comprising a computer system **200** is illustrated in accordance with various aspects of the present disclosure. The illustrated computer system **200** is a special purpose (particular) system that operates in a manner that enables industrial vehicles, e.g., vehicles **100**, to communicate wirelessly across a computer enterprise. The computer system **200** comprises a plurality of hardware processing devices (designated generally by reference numeral **202**) that are linked together by one or more networks (designated generally by reference numeral **204**). The networks **204**, which may comprise wired or wireless networks, provide communications links between the various processing devices **202** and may be supported by networking components **206** that interconnect the processing devices **202**. The networking components **206** may comprise, for example, routers, hubs, firewalls, network interfaces, wired or wireless communications links and corresponding interconnections, cellular stations and corresponding cellular conversion technologies (e.g., to convert between cellular and TCP/IP), etc.

(22) The processing devices **202** may comprise any device capable of communicating over the respective networks **204**. In certain contexts and roles, the processing device **202** is intended to be mobile (e.g., a hardware-based processing device **202** provided on the vehicles **100**). In this regard, the vehicles **100** include a processing device **202** that may communicate wirelessly to the network **204** to carry out the features described herein. Under such circumstances, the vehicles **100** may wirelessly communicate through one or more access points **210** to a corresponding networking component **206**. The vehicles **100** may also be equipped with WiFi, cellular, or other suitable technology that allows the processing device **202** on the vehicles **100** to communicate directly with a remote device (e.g., over the network(s) **204**).

(23) The illustrative computer system **200** also comprises a hardware server **212** (e.g., a web server, a file server, and/or other processing device) that supports an analysis engine **214** and one or more corresponding data sources (designated generally by reference numeral **216**). The analysis engine **214** and data sources **216** may provide resources to one or more of the processing devices **202**, including the processing devices **202** installed on the vehicles **100**.

(24) With reference to FIG. **2B**, an exemplary processing device **202** is described in detail. The processing device **202** is equivalent to, and an exemplary embodiment of, the processing device **202** on the vehicle **100**, as shown in FIG. **2A**. The processing device **202** in FIG. **2B** is a special purpose, particular hardware computer, such as a device that mounts to or is otherwise integrated with the vehicle **100**. The processing device **202** may comprise one or more processors coupled to memory to carry out executable instructions stored in the memory. However, the execution environment of the processing device **202** is further tied into the native electronics of the vehicle **100**, making it a particular machine different from a general purpose computer.

(25) The processing device **202** illustrated in FIG. **2B** may be implemented as an information linking device that comprises the necessary circuitry to implement communication with a remote server (e.g., server **212** in FIG. **2A**), data and information processing for processing vehicle data, and wired (and optionally wireless) communication to components of the corresponding vehicle **100** to which the processing device **202** is mounted. In accordance with aspects of the present disclosure, the processing device **202** (also referred to as a display and processing device) may be implemented as a main module **218** and a service module **220**, which couple together to create an integrated processing device **202**, e.g., the display and processing unit **151** (FIG. **3**). The service module **220** (which also includes a graphical user interface module) is field-replaceable and may comprise part of the display and processing unit **151**. The service module **220** comprises the screen display **152**, the five-button keypad **164**, and the graphical user interface module defining any necessary data processing circuitry. In this regard, the service module **220** in conjunction with a control module **226**, discussed below, define a graphical user interface for the processing device **202**. It is

also contemplated that the main module **218** and the service module **220** may not be integral such that the main module **218** is separate from the display unit **151**.

(26) In some embodiments, the processing device **202** is connected to a transceiver **222** for wireless communication. Although a single transceiver **222** is illustrated in FIG. 2B for convenience, in practice, one or more wireless communication technologies may be provided (e.g., WiFi, Bluetooth®, and/or cellular). For example, the transceiver **222** may be able to communicate with a remote server (e.g., server **212** of FIG. 2A) via 802.11 across the access points **210** of FIG. 2A. The transceiver **222** may also optionally support other wireless communication, such as radio frequency (RF), infrared (IR) or any other suitable technology or combination of technologies. For example, using a cellular-to-IP bridge (not shown), the transceiver **222** may be able to use a cellular signal to communicate directly with a remote server, e.g., a manufacturer server (not shown). The transceiver **222** connects to the processing device **202** via a suitable electrical connection **224**, e.g., an Ethernet connection. However, the transceiver **222** may connect to the processing device **202** using other suitable connections. Alternatively, the transceiver **222** may be built-in or otherwise integral with the processing device **202**.

(27) The processing device **202** also comprises data processing circuitry (illustrated generally as the control module **226**) having a processor (μ P) coupled to a memory for implementing executable instructions, including the relevant processes, or aspects thereof, as set out and described more fully herein. The control module **226** may also comprise other necessary processing circuitry and software, such as for implementing a display engine, camera processing engine, data processing engine(s), etc. In this regard, the control module **226** may comprise additional support circuitry, e.g., video ports, camera ports, input/output ports, etc. Moreover, the memory may comprise memory that stores processing instructions, as well as memory for data storage, e.g., to implement one or more databases, data stores, registers, arrays, etc. Additionally, the control module **226** implements processes such as operator login, pre-use inspection checklists, data monitoring, and other features, examples of which are described more fully in U.S. Pat. No. 8,060,400, the entirety of which is hereby incorporated by reference herein.

(28) The processing device **202** may also optionally comprise vehicle power enabling circuitry **228** to selectively enable or disable the vehicle **100** and/or to selectively enable or disable select components or functions of the vehicle **100**. In some embodiments, the vehicle power enabling circuitry **228** may partially or fully enable the vehicle **100** for operation, e.g., depending upon a proper operator login, a particular vehicle condition, etc. For example, the vehicle power enabling circuitry **228** may selectively provide power to components via a suitable power connection (not shown) or otherwise command certain vehicle components not to respond to vehicle operator control via vehicle messaging, e.g., across one or more vehicle communication busses.

(29) Still further, the processing device **202** comprises a monitoring input/output (I/O) module **230** to communicate via wired or wireless connection between the control module **226** and one or more peripheral devices mounted to or otherwise associated with the vehicle **100**, such as one or more cameras, sensors, meters, encoders, switches, etc. (not separately labeled; collectively represented by reference numeral **232**). The monitoring I/O module **230** may optionally be connected to other devices, e.g., third party devices **234**, such as one or more RFID scanners, displays, meters, bar code scanners, cameras, or other devices to convey information to the control module **226**.

(30) The processing device **202** is coupled to and/or communicates with other vehicle system components via a suitable vehicle network system **236**. The vehicle network system **236** may comprise at least one wired or wireless network, bus, or other communications capability or combination thereof that allows electronic components of the vehicle **100** to communicate with each other. As an example, the vehicle network system **236** may comprise a controller area network (CAN) bus, ZigBee, Bluetooth®, Local Interconnect Network (LIN), time-triggered data-bus protocol (TTP), RS422 bus, Ethernet, universal serial bus (USB), other suitable communications technology, or combinations thereof.

(31) As will be described more fully herein, utilization of the vehicle network system **236** enables seamless integration of the components of the vehicle **100** with the processing device **202**, and in particular, the control module **226**. By way of example, the vehicle network system **236** enables communication between the control module **226** and a fob (via a fob reader **240**), a keypad, a card reader, or any other suitable device for receiving operator login identification, as well as one or more native vehicle components, such as a vehicle control module, controllers (e.g., traction controller, hydraulics controller, etc.), modules, devices, bus-enabled sensors, displays, lights, light bars, sound generating devices, headsets, microphones, haptic devices, etc. (designated generally by reference numeral **238**). The control module **226** may also facilitate the communication of information from any electronic peripheral devices **232** or third party devices **234** associated with the vehicle **100** (e.g., via the monitoring I/O module **230**) that integrate with and communicate over the vehicle network system **236**.

(32) Referring now to FIG. 3, an example display and processing unit **151** is illustrated. As noted above, the display unit **151** can implement functions and/or features of the display and processing device **202** of FIG. 2B. As described herein, the display unit **151** may be used in or with an industrial vehicle, e.g., vehicle **100**, and may be mounted to the power unit console **138**, as noted above, or otherwise integrated with the vehicle **100**. It will be apparent to those of skill in the art that the display unit **151** may also be used with other types of vehicles, e.g., automobiles, etc., and in other non-vehicular settings.

(33) The display unit **151** comprises a housing **304** having a front face **306** defining a display section **308** comprising the screen display **152** and a vehicle operator control section **310**. The screen display **152** within the display section **308** may comprise, for example, an LCD screen, a light emitting diode (LED) screen, a plasma screen, etc. The screen display **152** may comprise any known technology, e.g., a touch screen display, so as to receive and respond to gesture commands, e.g., implemented by the operator directly touching or tapping the touch screen display **152**, pressing against or releasing from the touch screen display **152**, swiping, sliding, or rotating a finger along or across the touch screen display **152**, and performing other touch gesture functions or combinations thereof. The terms “gesture command” and “touch gesture command” also include gesture commands that do not require direct physical contact with the screen display **152** such as when an operator moves a finger adjacent to but spaced a small distance from the touch screen display **152** in a swiping, sliding, rotating or other motion.

(34) The vehicle operator control section **310** may comprise one or more physical input control elements, such as buttons,

switches, sliders, encoders, knobs, etc., that are used to receive operator input, e.g., making selections on the touch screen display **152**. One or more multifunction control handles, keypads, keyboards (not shown), or combinations thereof may be provided in place of the vehicle operator control section **310**. As shown in FIG. **3**, the vehicle operator control section **310** comprises the five-button keypad **164** including an up direction button **164A**, a right direction button **164B**, a left direction button **164C**, a down direction button **164D**, and an enter button **164E**. The vehicle operator control section **310** may optionally comprise one or more additional input elements or devices, such as a rotary control knob **164F**, which may be used in conjunction with or in place of the rotary control knob **162** located on the armrest (see FIG. **1B**) and may perform similar functions.

(35) Referring generally to FIGS. **2B** and **3**, the control module **226** comprises a hardware processor coupled to physical memory and is capable of carrying out computer-executed processes in a hardware system. In this regard, the processes, architectures, and organizations described herein may be implemented on computer-readable hardware that stores machine-executable program code, where the program code instructs the processor to implement the described features. The processor of the control module **226** executes the program code stored in the memory to implement a graphical user interface control architecture that transmits information to and receives information from the graphical user interface module of the service module **220**. In particular, the control module **226** provides several distinct control functions that impact the manner in which the service module **220** presents and receives information via the touch screen display **152** when interacting with the vehicle operator. For example, as described herein, the processor of the control module **226** may define one or more widgets and/or one or more icons and may control or cause the touch screen display **152** to display one or more of the widgets and/or icons.

(36) With reference to FIG. **4**, a logical organization of software code stored in memory that is controlled, read and manipulated by the control module **226** to effect control of the service module **220** by the control module **226**, which modules **220** and **226** define the graphical user interface of the processing device **202**, is illustrated. The features in FIG. **4** are set out in simplified block diagram form and may be executed by the control module **226** of FIG. **2B** (e.g., a microprocessor coupled to memory), and comprises a graphical user interface (GUI) controller module **402** that controls a plurality of sub-algorithms (modules) that affect the manner in which the processing device **202** (FIG. **2B**) interacts with the operator. In this regard, the GUI controller module **402** communicates with each sub-algorithm/module and further communicates with the graphical user interface module of the service module **220** (FIG. **2B**) to present information to the operator via a display screen, e.g., the touch screen display **152** (FIG. **3**), and to receive information from the operator, e.g., via touch/gesture controls received through touching the touch screen display **152** and/or interacting with one or more physical control elements in the vehicle operator control section **310** of the display unit **151** (FIG. **3**) or the control panel **126** (FIG. **1B**).

(37) In embodiments in which the screen display **152** comprises a touch screen, the GUI controller module **402** receives and processes touch gesture commands when the operator touches the touch screen display **152**, such as touch, tap, press, release, swipe, scroll, etc. Received touch gesture commands may comprise, for example, a first touch gesture command implemented as an up swipe gesture command, a second touch gesture command implemented as a right swipe gesture command, a third touch gesture command implemented as a left swipe gesture command, a fourth touch gesture command implemented as a down swipe gesture command, and a fifth touch gesture command implemented as a select gesture command (e.g., pressing and releasing, tapping, etc.).

(38) In other embodiments, the GUI controller module **402** receives and processes operator input from one or more of the control elements in the vehicle operator control section **310** of the display unit **151** (FIG. **3**). The GUI controller module **402** may implement a set of controls that comprise hardware control equivalents to the touch gesture commands recognized by the touch screen display **152**. For example, the GUI controller module **402** may process a first control designated as an “up” control (e.g., via the operator pressing the up direction button **164A** of FIG. **3**), a second control designated as a “right” control (e.g., via the operator pressing the right direction button **164B**), a third control designated as a “left” control (e.g., via the operator pressing the left direction button **164C**), a fourth control designated as a “down” control (e.g., via the operator pressing the down direction button **164D**), and a fifth control designated as a “select” control (e.g., via the operator pressing the enter button **164E**). The various controls may also be implemented on a single input device, e.g., a keypad or a rotary control knob, or via additional separate control elements.

(39) In this regard, the control module **226** (FIG. **2B**), e.g., implemented as the GUI controller module **402**, is communicably connected to the touch screen display **152** (FIG. **3**), as described herein. The control module **226** detects interactions with the touch screen display **152** and/or one or more of the control elements in the vehicle operator control section **310** or the rotary control knob **162**, **164F**. For example, the control module **226** maps the up swipe gesture command on the touch screen display **152** (e.g., the operator places a finger on the touch screen display **152** and swipes upward) and operation of the down control to a same first graphical user interface command. The control module **226** maps the right swipe gesture command on the touch screen display **152** (e.g., the operator places a finger on the touch screen display and swipes to the right) and operation of the left control to a same second graphical user interface command. The control module **226** likewise maps the left swipe gesture command on the touch screen display **152** (e.g., the operator places a finger on the touch screen display and swipes to the left) and operation of the right control to a same third graphical user interface command. The control module **226** also maps the down swipe gesture command on the touch screen display **152** (e.g., the operator places a finger on the touch screen display **152** and swipes downward) and operation of the up control to a same fourth graphical user interface command. The control module **226** yet further maps the select gesture command on the touch screen display **152** (e.g., touch, press, release, etc.) and operation of the select control to a same fifth graphical user interface command. These graphical user interface commands may vary in function depending upon what is currently being displayed on the display **152**, examples of which are described in greater detail herein.

(40) The control module **226** may similarly map operator commands associated with the rotary control knob **162**, **164F**. For example, the control module **226** maps rotation of the rotary control knob **162**, **164F** to the left and operation of the left control

to a same (second) graphical user interface command. The control module **226** maps rotation of the rotary control knob **162**, **164F** to the right and operation of the right control to a same (third) graphical user interface command. The control module may map depression of the rotary control knob **162**, **164F** and operation of the select control to a same (fifth) graphical user interface command.

(41) The up and down commands or controls may be used to navigate vertically, e.g., up and down within various menus provided in the screen display **152** of the display unit **151** (FIG. 3), as described herein in detail. The up and down commands or controls may also be used to scroll up and down in an image that is too large to display in its entirety in the area of the screen display **152**, to increment and decrement a value that the operator provides as an input, etc. The right and left commands or controls may be used to navigate laterally, e.g., to scroll across the widgets and to expose additional widgets; scroll through, drill into, and back out of multilayer menus; scroll to the right or left of an image that is too large to fit in the area of the screen display **152**; modify data entry values, etc. Moreover, a combination of the up and down commands or controls, as well as the right and left commands or controls, may be used to scroll across text or other data that is too large to fit in the area of the screen display **152**. Operation of the “select” command or control enables the operator to, for example, execute an enter command, select or activate a menu option, accept a value, trigger an action, clear a message, set or stop a timer, or otherwise interact with the information displayed via the display unit **151**.

(42) The redundancy of the commands and controls generated by touching the touch screen display **152**, and using the corresponding control elements (e.g., buttons **164A-164E** in FIG. 3) in the vehicle operator control section **310** facilitates operation of the display unit **151**, even in harsh environments. For example, some operators must wear gloves, such as during operation in refrigerated areas of a warehouse. Moreover, the positioning of the buttons **164A-164E** in close proximity (e.g., on the same housing) to the touch screen display **152** facilitates operator interaction by keeping the operator consistently focused in a common area regardless of interaction with the touch screen display **152** or tactile control elements (e.g., buttons) when interacting with the display unit **151**. Thus, in this configuration, the buttons **164A-164E** are co-located with, for example, the touch screen display **152**.

(43) The GUI controller module **402** also facilitates customization of the user interaction experience. For example, the GUI controller module **402** communicates with a user management module **404** and a system management module **406**. A user management module **404** may store personalized settings that are passed from the control module **226** (FIG. 2B), such as in response to an operator logging into a corresponding vehicle **100** using a fob via the fob reader **240** (FIG. 2B), or via logging onto the vehicle **100** using the display unit **151**. The system management module **406** may be utilized to control the allowable operator-specific settings, e.g., by limiting, disabling, enabling, etc., features. In an illustrative example, the user management module **404** may be used to store a vehicle operator performance or skill level, a theme preference, a language preference, unit measurement preference (e.g., metric or English), widget arrangement, etc. A generic template may be provided where there is no customization data available for a specific vehicle operator. In a further illustrative example, the system management module **406** limits and controls the ability of the vehicle operator to configure themes, language preference, widget arrangement, widget customization, etc. One or more of these features may be temporarily overridden or permanently locked out, e.g., by a system supervisor, from appearing as a user settable parameter. For example, the available themes may be set or limited based upon a vehicle operator level, truck level, company level, etc., and may be temporarily overridden for certain vehicle-specific functionality, e.g., to provide an inspection checklist, to provide certain diagnostic information, etc.

(44) The GUI controller module **402** further communicates with a vehicle management module **408**. The vehicle management module **408** stores and controls information about the specific vehicle **100** on which the processing device **202** (FIG. 2B) is installed. For example, the vehicle management module **408** may comprise information about a maximum fork height, maximum weight, battery charge, or other vehicle-specific characteristics.

(45) The GUI controller module **402** still further communicates with a language format module **410**, which may be used to set a preferred language for the display of text on the screen display **152** (FIG. 3). In particular, the language format module **410** manages the strings that are to be translated and pushed to the screen display **152**, as well as the font, text alignment, direction, and other features that affect readability of the desired information by the operator. The GUI controller module **402** still further communicates with a communication module **412**, which controls the communication of the GUI controller module **402** with other vehicle controllers, modules, devices, sensors, third party devices, etc., as set out in FIGS. 2A and 2B.

(46) The GUI controller module **402** further communicates with a message system module **414**. The message system module **414** may control the messaging that is presented to the operator, as well as the manner in which the messaging is presented to the operator. For example, a message may be displayed across a portion of the screen display **152**, e.g., across a bottom third, across one widget space (**606**, **608** in FIG. 6A), or across the entire screen display **152** (FIG. 3). The GUI controller module **402** also communicates with a dashboard module **416**. The dashboard module **416** controls icons, the icon order, widgets, the widget order, and the menu systems that are presented on the screen display **152**. The dashboard module **416** is also responsible for screen management, e.g., storing the current screen, next screen, previous screen, etc., and for tracking the menus, calibration, checklists, icon display, widget display, messaging, text and video messaging, etc. The GUI controller module **402** further communicates with a user I/O module **418** to translate inputs provided by the operator into instructions that are interpreted to facilitate a vehicle operator interaction experience when interacting with the graphical user interface module of the service module **220** (FIG. 2B), which may be implemented as part of the display unit **151** (FIG. 3). For example, the user I/O module **418** may process input received via touch gesture commands from the operator touching the touch screen display **152**, via the physical control elements in the vehicle operator control section **310** or via the control panel **126** (FIG. 1B).

(47) In accordance with aspects of the present disclosure, the screen display **152** may be utilized to display one or more widgets, each of which is defined by an application program forming part of the dashboard module **416** that provides a visual representation on the screen display **152**. In an embodiment, computer instructions are provided in the form of an application program stored in memory that instructs the processor of the control module **226** what a particular widget looks like, how it

behaves and how it responds to operator actions and/or vehicle-related information. The visual representation provides information to the operator and allows the operator to interface with the control module **226**. For example, widgets may provide visual representations of a current state of one or more associated vehicle features, functions, or operations (e.g., a battery charge, a current vehicle speed, etc.) and/or one or more ancillary conditions (e.g., environmental condition such as the current time). In an exemplary embodiment, widgets may be used to represent the current state of the vehicle speed, fork height, load weight, battery charge, clock, stop watch, odometer, trip meter, hour meter, time, and date.

(48) In this regard, the widgets represent “live” or real-time data. With reference to FIGS. **2A** and **2B**, the current state of data values may be obtained, for example, by the processor of the control module **226** communicating with (e.g., querying, polling, reading from, etc.) one or more vehicle control modules, sensors, etc. (e.g., one or more electronic peripheral devices **232**) across the vehicle network system **236**, via the monitoring I/O module **230**, or a combination thereof. The current state data may also be ascertained by polling or otherwise querying a remote server, e.g., the server **212**, which extracts relevant data from the data sources **216**, e.g., a vehicle data repository, and communicates that relevant data back to the control module **226**.

Furthermore, the control module **226** may read the current state from a designated memory on the vehicle **100**, e.g., a master state data repository (not labeled). For example, a process on the vehicle **100** (e.g., a process executed by the controller/processor in the control module **226**) may be tasked with cyclically collecting and refreshing vehicle state information in the designated memory, e.g., every 100 milliseconds or less. The designated memory thus defines a vehicle state lookup table that may be accessed to make decisions based on a current operating state of the vehicle **100**. The current state data may also include data regarding the vehicle operator performance or skill level.

(49) By way of example, by continually data logging operator-based performance and/or vehicle operation data, one or more of the widgets may provide a dashboard view of key vehicle and/or operator performance measures. In this regard, the overall data provided in a widget need not be limited to data collected by or stored in a specific vehicle. In some embodiments, one or more of the widgets may reflect all of the relevant vehicle data associated with the logged in operator, regardless of which vehicle the operator is currently operating. In other embodiments, one or more of the widgets may tie into third party databases to display other information, such as operational information, messages, information from a warehouse management system, feeds (such as from news, sports, and weather), etc. Thus, the processing device **202** is communicably connected to a communications device (e.g., the transceiver **222**) such that the processing device **202** receives from a remote server (e.g., the server **212**), information that is not extracted from the vehicle **100**.

(50) With reference to FIG. **5**, the widgets may be organized into an array **500**. The array **500** dictates, for example, which widgets will be presented on the screen display **152** (FIG. **3**) and the order in which the widgets will be presented. For example, a first widget **502(1)** is designated as a leftmost widget, followed by widgets **502(2)**, **502(3)** . . . **502(N)**, in which N is any reasonable number. The vehicle operator may add as many widgets as are available or as are limited via preferences set in the user management module **404** (FIG. **4**). Moreover, the operator may rearrange the order of presentation of the widgets so that the widgets are ordered as desired, as described herein. One or more widgets, e.g., widgets **502(1)** and **502(2)**, may be used to set a “Home Screen,” which may be displayed as a default or to which the operator may return. The Home Screen may, for example, display the two widgets representing the most important features for the operator. The widgets may also be configured and ordered from the screen display **152**, e.g., via input from the operator, or the widgets may be set or preset by the system supervisor or via a remote computer, which wirelessly sends the widgets and widget order to the vehicle **100**, such as through the remote server **212** (FIG. **2A**).

(51) Referring now to FIGS. **6A** and **6B**, an exemplary display screen **600** is illustrated, which may be implemented as a touch screen. The display screen **600** is an example of a graphical user interface display, which may be presented by the screen display **152** of the display unit **151** (FIG. **3**). The display screen **600** may be conceptually broken down into several sections comprising a menu selection section **602**, a first docked status tray **604A**, a second docked status tray **604B**, and one or more widget spaces, which are illustrated as a first widget space **606** and a second widget space **608**. Although the display screen **600** is depicted herein as comprising one menu selection section, two status trays, and two widget spaces, it will be apparent to those of skill in the art that different configurations of the display screen **600** are possible. For example, the upper portion of the display screen **600** may comprise only one status tray or three or more status trays. In addition, the display screen **600** may comprise three or more widget spaces. However, a size of the display screen **600** may dictate the number of available widget spaces and/or status trays.

(52) As shown in FIG. **6B**, the menu selection section **602** may be used to access a menu, e.g., a drop down menu **602a**, relating to one or more general vehicle settings and to the general operation and appearance of the display screen **600**. Selection of one of the options in the drop down menu **602a** may result in the display of one or more sub-menus (not shown) with additional options related to the selected option. One or more of the options in the drop-down menu **602a** and/or sub-menu(s) may comprise an associated number or value (not shown) that may be viewed and/or changed by clicking or selecting on the option. The operator may access the menu **602a** or sub-menu(s) and make selections as described herein. In some embodiments (not shown), the menu **602a** may be displayed over both widget spaces **606**, **608**.

(53) One status tray, e.g., the first status tray **604A**, or a portion thereof may be used to display information such as one or more identifiers related to the operator, the vehicle, the vehicle owner, etc. One status tray, e.g., the second status tray **604B**, or a portion thereof may comprise an icon row or an icon tray that is used to dock a predetermined number of system status icons (**730** in FIG. **7A**). The first and second widget spaces **606**, **608** each display a widget comprising a visual representation of a current state of an associated ancillary condition or vehicle feature or function. The term “a current state of an associated function of a vehicle” is intended to encompass “the current state of an associated ancillary operation, condition or vehicle feature or function.” In the exemplary display screen **600** shown in FIGS. **6A** and **6B**, two widgets N-2, N-3 are displayed, e.g., according to the order set by the array **500** (FIG. **5**). Thus, because widget N-2 is displayed in the first widget space **606**, widget N-3 is displayed in the second widget space **608**. Moving the widgets to the right would shift widget N-2 into the second widget

space **608** and a new widget, widget N-1, into the first widget space **606** (not shown). Likewise, moving the widgets to the left would shift the widget N-3 into the first widget space **606** and widget N-4 into the second widget space **608** (not shown). This process may continue so that the operator may scroll through all of the assigned widgets in the array **500**. At widget N-1 and N-N, the scrolling may stop or wrap around to the next adjacent widget in the array **500**.

(54) An optional widget position indicator **610** may be utilized to illustrate the number and position of the displayed widgets within the array **500**. In the embodiment shown, the widget position indicator **610** comprises circles, but in other embodiments (not shown) the widget position indicator **610** may comprise another shape, e.g., squares, triangles, etc. A number of circles **610(1)** . . . **610(N)** may correspond to a number of widgets available within the array **500**, see FIGS. **6A** and **6B**. For example, as shown in FIG. **7B**, there are nine widgets available for display, as indicated by circles **610(1)** to **610(9)**. In FIGS. **6A** and **6B**, a portion or subset of the available widgets, e.g., widgets N-2 and N-3, is displayed on the display screen **600**, and the widget position indicator **610** may also indicate a current position of the displayed widgets N-2, N-3 within the array **500**. For example, widgets N-2 and N-3 are the second and third widgets in the array, as indicated by the second and third circles **610(2)**, **610(3)** in the widget position indicator **610** being solid. The remaining widgets, i.e., widgets N-1 and N-4 to N-N are off the display screen **600**, as indicated by the corresponding first and fourth through Nth circles **610(1)**, **610(4)**-**610(N)** being open.

(55) With reference to FIGS. **7A**-**7C**, several aspects of the general functionality of the screen display **152** of the display unit **151** (FIG. **3**) will be discussed in detail. An exemplary display screen **600**, which may be implemented as a touch screen, is illustrated and may comprise an example of a graphical user interface display, which may be presented by the screen display **152**. Although reference is made to elements and features of particular icons and widgets, those of skill in the art will appreciate that the described elements and features are not limited to these particular icons and widgets. In addition, labeling of some elements is omitted for clarity. As shown in FIG. **7A**, display screen **600** is conceptually broken down into a menu selection section **602**, a first status tray **604A**, and a second status tray **604B**, as represented by the dashed lines. The first status tray **604A** comprises one or more identifiers **720**, such as the operator's name, e.g., "J. SMITH," the name of another person actively logged into the vehicle, a vehicle name, a company name, a location, etc. The second status tray **604B** comprises an icon tray with one or more system status icons **730**. The first widget space **606** comprises a capacity data monitoring (CDM) widget **740**, and the second widget space **608** comprises a speedometer widget **750**. The widget position indicator **610** indicates that there are nine widgets available for display and that the CDM and speedometer widgets **740**, **750** are widgets N-1 and N-2 in the associated array **500** of widgets (FIG. **5**), as indicated by the first and second circles **610(1)**, **610(2)** being solid and the remaining circles **610(3)** to **610(9)** being open.

(56) Each icon **730** corresponds to a current state of an associated vehicle feature, function, or operation or an ancillary condition. For example, the icons **730** depicted in FIG. **7A** comprise a rack height select (RHS) icon **730A**, a steer wheel/travel direction indicator icon **730B**, a performance icon **730C**, a messaging icon **730D**, a battery condition icon **730E**, and a clock icon **730F**. In some embodiments, one or more of the icons **730** displayed in the second status tray **604B** may be locked or fixed in position on the display screen **600**, e.g., in the icon tray, and may be changed, for example, only by a system supervisor or fleet manager. For example, in some embodiments, the RHS icon **730A** may be activated or inactivated by the operator, as described herein, but may be removed or otherwise altered only by the system supervisor or fleet manager. One or more of the icons **730** may comprise an indicator that provides a visual representation of the current state of the associated vehicle feature, function, or operation or ancillary condition. For example, the steer wheel/travel direction indicator icon **730B** comprises an arrow within a circle (not separately labeled) indicating a general steer wheel/travel direction within a 360° plane, the messaging icon **730D** comprises a message bubble with a "1" to indicate that the operator has one message, the battery icon **730E** displays "86" to indicate that the battery charge is currently 86%, etc. Thus, the operator may use the icons **730** to quickly determine the current state of the corresponding vehicle features, functions, or operations or ancillary conditions, without the need to display a corresponding widget in one of the widget spaces **606**, **608**.

(57) In some embodiments, at least one of the icons **730** corresponds to a respective one of the widgets. The corresponding widget may be displayed in one of the widget spaces **606**, **608**, or the corresponding widget may be available in the array **500** (FIG. **5**) but is currently off the display screen **600**. For example, as shown in FIGS. **7A** and **7B**, the RHS icon **730A** corresponds to an RHS widget **760**, which is off the screen in FIG. **7A** and is displayed in the first widget space **606** in FIG. **7B**.

Alternatively, the corresponding widget may be installed on the vehicle **100**, i.e., stored in memory, but is not currently in the array **500** of widgets available for display. In a particular embodiment, the last widget in the array may comprise an "add" widget (not shown) that, when touched or selected, displays a menu as described herein that lists additional available widgets for selection and insertion into the array **500**. In other embodiments, one or more of the icons **730** may not include a corresponding widget. For example, the clock icon **730F** may not include a corresponding widget. Each icon may be defined by an application program (similar to the widget application program) forming part of the dashboard module **416** that provides a simple visual representation on the screen display **152**. In an embodiment, computer instructions are provided in the form of an application program stored in memory that instructs the processor of the control module **226** what a particular icon looks like, how it behaves and how it responds to operator actions and/or vehicle-related information.

(58) In further embodiments, one or more of the icons **730** may appear only when a particular condition is satisfied or occurs. For example, the messaging icon **730D** may appear in the second status tray **604B** only upon receipt of a new message, and a maintenance icon (not shown) may appear only upon receipt of an indication of a problem with a vehicle component or system. In yet further embodiments, one or more of the icons **730** may be removed from the second status tray **604B** when a particular condition is satisfied or occurs.

(59) The performance icon **730C** may be used to set a vehicle mode (e.g., training, economy, or full performance mode).

(60) In some embodiments, selection or activation of one of the icons locks the corresponding widget into place on the display screen **600** in a designated or "locked" widget space. As used herein, "activation" is intended to comprise touching, tapping, clicking, or otherwise selecting a portion of the display screen where the icon is located using one or more touch gestures and/or

one or more physical control elements, such as the physical control elements found in the vehicle operator control section **310** (FIG. 3) or the control panel **126** (FIG. 1B), e.g., the rotary control knob **162** or trigger switch (not shown). For example, upon the touch screen **600** sensing an operator touching or tapping the corresponding portion of the touch screen **600** where the icon is located, the icon becomes activated. The activated icon becomes deactivated when an operator touches or taps the corresponding portion of the touch screen **600** where the activated icon is located. The locked widget space may comprise any one of the widget spaces, e.g., the first or the second widget space **606**, **608**. The widget corresponding to the activated icon may already be located in the locked widget space, in which case the corresponding widget will be locked in place in its current location upon activation of the icon and, in one embodiment, will not move from the locked widget space unless the corresponding icon is deactivated. If three or more widget spaces are provided, the locked widget space may comprise a center widget space. If none of the icons is activated, any widget located in the designated or “locked” widget space is not locked in position.

(61) However, the widget corresponding to the activated icon may be located in one of the other widget spaces or may be off the display screen **600**. In some embodiments, the widget corresponding to the activated icon may not be in the array **500** (FIG. 5) of widgets currently available for display on the display screen **600** but is installed on the vehicle **100**, i.e., stored in memory. In all cases in which the corresponding widget is not currently displayed in the locked widget space, the remaining widgets may be shifted to the right or left to allow the corresponding widget to move to the locked widget space. In some embodiments, the movement of the corresponding widget and shifting of the remaining widgets may occur automatically upon detecting activation of the icon such that the corresponding widget immediately moves to the locked widget space and becomes locked in position. In other embodiments, the remaining widgets will be shifted only upon detection of a touch gesture or actuation of one or more control elements following activation of the icon. In further embodiments, selection of an icon and movement of the corresponding widget into the locked widget space may automatically reorganize the array **500** of widgets to place the widget corresponding to the selected icon in the first position in the array **500**, e.g., the first widget **502(1)**. In yet further embodiments, activation of an icon for a widget that is not currently in the array **500** and display of the widget on the display screen **600** upon activation of the corresponding icon may also result in the introduction of an additional circle (not shown) in the widget position indicator **610** to indicate the presence of the additional widget.

(62) For example, with reference to FIGS. 7A and 7B, the CDM widget **740** in FIG. 7A is located in the first widget space **606**, and the speedometer widget **750** is located in the second widget space **608**. In FIG. 7B, the RHS icon **730A'** has been activated, and the corresponding RHS widget **760** has been moved into a locked widget space, e.g., the first widget space **606** at the leftmost side of the display screen **600**. The remaining widgets **740**, **750** have been shifted to the right, i.e., the CDM widget **740** has been shifted into the second widget space **608** in FIG. 7B and the speedometer widget **750** has been moved off the display screen **600** to the right.

(63) One or more characteristics of a visual appearance of the activated icon may be altered upon activation. For example, as shown in FIG. 7B, the activated RHS icon **730A'** is underlined **735**. Alternatively, or in addition to the underlining **735**, a box (not shown) may appear around the activated icon and/or a color or appearance of one or more portions of the activated icon may change (not shown). For example, the text “RHS” in the activated RHS icon **730A'** may be changed to italics and/or may be changed from a default color to another color (e.g., from white to orange upon activation) or a combination thereof to clearly indicate to the operator that the icon has been activated. In addition, a portion of the background of the activated icon may also change color or appearance upon activation (not shown).

(64) In addition, one or more characteristics of the widget position indicator **610** may be altered to indicate that a widget has been locked into place in the locked widget space. For example, as shown in FIG. 7B, the first circle **610(1)** in the widget position indicator **610** is changed, for example, from solid black, as indicated in FIG. 7A, to a different color (e.g., orange) to indicate that the corresponding widget has been locked into place. A background pattern, shape (not shown), or other characteristic of the widget position indicator or combinations thereof may also be changed to indicate that a widget has been locked into place. Where the locked widget space comprises the second widget space **608** or another widget space, one or more characteristics of the corresponding circle **610(2)** . . . **610(N)** in the widget position indicator **610** may also be changed (not shown).

(65) Prior to activation of an icon and locking of the corresponding widget into the locked widget space, the operator may scroll through the widgets using one or more touch gestures and/or one or more physical control elements, as described herein, and the widgets in both widget spaces will change as the operator cycles through the array **500** (FIG. 5). In some embodiments, the operator may change a widget's current position in the array **500** by pressing and holding on the widget and dragging and dropping the widget to the desired location (not shown). After activation of an icon and locking of the corresponding widget into the locked widget space as shown, for example, in FIG. 7B, only the widgets in the remaining widget space(s) may be changed by scrolling. For example, following activation of the RHS icon **730A'** and locking of the RHS widget **760** in the locked (first) widget space **606** in FIG. 7B, the operator scrolls to the left through the remaining widgets, which generates the display screen **600** shown in FIG. 7C. The speedometer widget **750**, which was previously off the display screen **600** to the right, moves back into the second widget space **608**. Because the RHS widget **760** is now locked into place in the first widget space **606**, the CDM widget **740** moves off the display screen **600** to the left. In the widget position indicator **610**, the first circle **610(1)** corresponding to the RHS widget **760** remains orange. The second circle **610(2)**, which now corresponds to the CDM widget **740** is open, as the CDM widget **740** has moved off the display screen **600**, and the third circle **610(3)**, which now corresponds to the speedometer widget **750**, is solid.

(66) In some embodiments, activation of an icon may move the corresponding widget to a predefined widget space but does not lock the widget in place. For example, activation of the RHS icon **730A** may cause the RHS widget **760** to move into a predefined widget space, e.g., the first widget space **606** as shown in FIG. 7B, but the operator may then scroll through the widgets as before, i.e., the RHS widget **760** may be moved off the screen (not shown) in response to an operator command to

move the widget. Receipt of an operator command related to a vehicle operation may cause the corresponding widget to immediately move back to the predefined widget space. For example, if the operator has moved the RHS widget **760** off the display screen **600**, receipt of a command to activate the traction motor to effect vehicle movement or receipt of a command to lift or lower the carriage assembly **144** (FIG. **1A**) or actuation of the trigger switch (not shown) may cause the RHS widget **760** to move back to the first widget space **606**. In other embodiments, receipt of an operator command related to a vehicle operation may cause a corresponding widget to move to a predefined widget space. For example, receipt of a command to lift or lower the carriage assembly **144** (FIG. **1A**) or actuation of the trigger switch (not shown) may cause the RHS widget **760** to move into the first widget space, as shown in FIG. **7B**.

(67) In all embodiments, movement of the corresponding widget to a locked or a predefined widget space on the display screen **600** in response to a particular operator command may save time for the operator and help to increase productivity, as there is no need for the operator to manually search for the appropriate widget and/or move the widget back onto the display screen **600** if the operator has navigated away from the widget. Thus, the processing device **202** disclosed herein, as implemented, for example, in the display unit **151**, provides a smart and flexible user interface that ensures that the operator receives the most relevant information at the correct time with the least operator input.

(68) In additional embodiments, upon movement of a widget into a predetermined widget space (by scrolling, by activation of the corresponding icon, etc.), a message (not shown) related to the widget may optionally be displayed. If the predetermined widget space is, for example, the first widget space **606**, the message may be temporarily superimposed over the second widget space **608** and may appear only when a predefined condition is met. For example, if a battery condition widget (not shown) is moved into the first widget space **606** and the battery charge is below a certain level, a message, e.g., “Low Battery,” may appear to alert the operator that the battery may need to be changed soon. In addition, if the operator moves the speedometer widget **750** into the first widget space **606**, a message, e.g., “Speed Too High,” may appear if the operator is exceeding a speed limit.

(69) In further embodiments, the control module **226**, which is communicably coupled to one or more vehicle system modules via the vehicle network system **236** (FIG. **2B**), may extract data related to a current vehicle state, as described herein, and use this data to alter a display of the widgets and/or icons on the display screen **600**. For example, display unit **151** (FIG. **3**) may be configured to have one or more “home” positions and/or “home” screens that each display one or more widgets that are relevant to a current vehicle state or a current task. These features help to ensure that the vehicle operator has ready access to the information that is most relevant to the current task without the need to search through all of the widgets available on the vehicle **100**, which may help to increase operator productivity.

(70) In some particular embodiments, the control module **226** extracts from a traction control module (not shown), directly or via a memory or current vehicle state lookup table, an indication as to whether the traction control is engaged. If the current operating state of the traction control module indicates that the traction controls are engaged, the control module **226** causes the display screen to “snap” back to a designated “home” position, such as the first two widgets in the array **500** (FIG. **5**). In addition, when traveling, the display screen **600** may also automatically change to a “motion home screen” that shows relevant travel-related widgets, such as the speedometer widget **750**.

(71) In other particular embodiments, the control module **226** extracts from a hydraulic valve control module (not shown) an indication as to whether the forks **156A**, **156B** (FIG. **1A**) are engaged in a lift operation on the vehicle **100**. Where the current operating state indicates that the forks **156A**, **156B** are engaged in a lift operation, the control module **226** causes the display screen **600** to snap to a designated “lift” home position or “lift home screen” having relevant widgets, such as the CDM widget **740** and the RHS widget **760**.

(72) In yet further embodiments, the control module **226** may use the extracted data related to the current vehicle state to selectively disable operation of one or more portions of the display unit **151**. The display screen **600** may continue to display the current state of one or more vehicle features, functions, or operations, but the touch layer may be fully or partially disabled such that the display screen **600** is unresponsive to touch gesture commands. The control module **226** may also optionally disable one or more of the control elements in the vehicle operator control section **310** (FIG. **3**). These features may help to reduce operator distraction and increase operator productivity by ensuring that the vehicle operator remains focused on the current task.

(73) In some particular embodiments, if the current operating state of the traction control module indicates that the traction controls are engaged, as described herein, the control module **226** may lock the display screen **600** so that the operator cannot scroll through other widgets or otherwise leave the home position.

(74) In other particular embodiments, the control module **226** extracts a speed of the vehicle **100** based upon information received from the vehicle network bus, e.g., a vehicle network system **236** (FIG. **2B**) and selectively disables one or more portions of the display unit **151**. For example, all touch gesture commands may be disabled if the control module **226** determines that the vehicle speed is above a threshold speed. When the control module **226** determines that the speed of the vehicle **100** is below the threshold speed, the control module **226** may enable full operation of the display unit **151**, e.g., one or more of the widgets displayed on the display screen **600** may be changed.

(75) In yet further particular embodiments, the display of the icons and/or widgets on the display screen **600** may be customized based on static vehicle information, such as a vehicle type (e.g., forklift vs. stock picker), a vehicle model, etc., and/or one or more operator-based metrics, such as a current level of completion of a task (e.g., percentage of picks per shift), an operator skill or performance level, a level of correct vehicle operation or environmental behaviors, etc. For example, less skilled operators may benefit from the constant display of the icons and/or widgets corresponding to a steer wheel/travel direction **730B** and a vehicle speed **750**, while more skilled operators may wish to monitor different vehicle operations and systems. These features help to ensure that the display screen **600** presents each individual vehicle operator with the relevant and useful information.

(76) With reference to FIGS. **7A-7I**, several features of the widgets will be described in detail. Although reference is made to elements and features of particular icons and widgets, e.g., the RHS icon **730A**, **730A'** and the CDM and RHS widgets **740**, **760**,

those of skill in the art will appreciate that the described elements and features are not limited to these particular icons and/or widgets. In addition, labeling of some elements in the Figures is omitted for clarity.

(77) As shown in FIG. 7A, the CDM widget **740** may comprise a visual representation **744** corresponding to the forks (e.g., **156A**, **156B** in FIG. 1A), including a numerical indication **747** of a current position of the carriage assembly (**144** in FIG. 1A), e.g., a current fork height (“4 in”), and a current sensed or detected load weight **748** (“0 lbs”). The current fork height may also be indicated by a position of a pointer **749** along a scale **742**, which may comprise a plurality of tick marks (not separately labeled) corresponding to height increments from, for example, 0 inches to a maximum lift height for the vehicle **100**. The CDM widget **740** may also comprise a fork tilt indicator **745** and a fork centering indicator **746**. The fork tilt indicator **745** in FIG. 7A indicates that the forks are currently level, while the fork tilt indicator **745'** in FIG. 7G indicates that the tips of the forks are tilted up. The fork tilt indicator **745** may similarly indicate that the tips of the forks are tilted down (not shown). The fork centering indicator **746** may indicate that the forks are positioned to the left or right of a centerline of the vehicle **100** (not shown).

(78) Data related to the detected load weight and the current fork height, tilt, and/or centering may be obtained as described herein and provided to the CDM widget **740** for display. For example, the processor of the control module **226** is in communication with one or more vehicle control modules, sensors, etc. (e.g., **232**), across the vehicle network system **236**, via the monitoring I/O module **230**, or a combination thereof (FIG. 2B). After extraction of the relevant information by the processor of the control module **226**, the CDM widget **740** provides visual representations corresponding to each parameter.

(79) As shown in FIG. 7B, the RHS feature of the vehicle **100** has been turned on or activated via the RHS icon **730A'**, as indicated by the underlining **735** and/or other visual indicator. The RHS icon **730A'** may be activated using touch gesture commands, using one or more of the control elements **164A-164F** in the vehicle operator control section **310** (FIG. 3), or using one or more of the physical control elements in the control panel **126** (FIG. 1B), such as the rotary control knob **162** (FIG. 1B) or a trigger switch (not shown) as described herein. For example, the operator may use the up, down, right, and left buttons **164A-164D** to navigate to the RHS icon **730A** (FIG. 7A) and pressing the enter button **164E** to activate the RHS icon **730A'** (FIG. 7B). The operator may similarly turn the rotary control knob **162** or **164F** to the right or left to navigate to the RHS icon **730A** and depress the rotary control knob **162**, **164F** to activate the RHS icon **730A'**. When the control elements **164A-164F** and/or the rotary control knob **162**, **164F** are used, the display screen **600** may include a focus area or focus state, such as an outline box or highlighted background (not shown), to visually indicate a current location of a cursor or a current selection, which assists the operator in navigating to the desired portion of the display screen **600**. As noted above, after the RHS icon **730A'** is activated, the RHS widget **760** is locked into a locked widget space, e.g., the first widget space **606** in FIG. 7B.

(80) The RHS widget **760** may comprise a first menu portion **761**, a sub-menu portion **762**, and a pallet presence indicator **763**, as shown in FIG. 7B. As described herein, the first menu portion **761** displays information related to an option selected from a first menu **764** (FIG. 7D), and the sub-menu portion **762** may be used to display and select additional options corresponding to the option selected in the first menu **764**. In some embodiments, as shown in FIG. 7B, activation of the RHS icon **730A'** allows the first menu portion **761** to be displayed. In one embodiment, after the RHS icon is activated, the first menu **764** is displayed upon activation of the first menu portion **761** by the operator, as noted below. This feature ensures that the operator receives the most relevant information at the correct time with the least operator input. It also prevents the first menu portion **761** from being inadvertently activated when the RHS function has not been activated via activation of the RHS icon.

(81) The operator may access the first menu **764** by activating the first menu portion **761** using one or more touch gestures and/or the one or more control elements in the vehicle operator control section **310** (FIG. 3) or the control panel **126** (FIG. 1B). For example, the operator may activate the first menu portion **761** via a touch gesture, e.g., by touching or tapping within the area encompassed by the box with dashed lines around “Stacker Pallets” at the top of the RHS widget **760** in FIG. 7B, or by performing an equivalent function using one or more physical control elements. An arrow or other visual indication (not labeled) within the first menu portion **761**, e.g., to the right of the text “Stacker Pallets,” may indicate that additional options are available for selection, e.g., via the first menu **764**.

(82) As shown in FIG. 7D, the display screen **600** then displays the first menu **764** comprising one or more options available for selection. The first menu **764** may be displayed in a variety of formats, such as a list, a sidebar (not shown), or a scroll wheel (not shown). An optional indicator **764a** may appear adjacent to the currently selected option, e.g., “Stacker Pallets.” In some embodiments, the first menu **764** may be displayed within the widget **760**, as shown in FIG. 7D. In other embodiments, the first menu **764** may be displayed in a separate window that is temporarily superimposed over one or more of the widget spaces. For example, as shown in FIG. 7C, a window **770** may be displayed over a portion of the first widget space **606**.

(83) In some embodiments, the options contained in the first menu **764** (also referred to herein as a workspace zone menu) comprise a list of available workspace zones. As described herein, one or more workspace zones may be stored in a memory of the vehicle **100**. Each zone may correspond to, for example, a particular work site, warehouse, room, or other workspace, or area or portion thereof. The zones may be customized by a vehicle owner or other end user based on the various zone(s) in which the vehicle **100** will be used. For example, the number of available zones may be customized, and each zone may be assigned a zone identifier, e.g., a name (e.g., “Stacker Pallets” in FIG. 7B), a number, a color, or other identifying feature or combination thereof, which is displayed in the first menu portion **761** (also referred to herein as a zone selection portion). In one particular embodiment, the operator may only activate the zone selection portion **761** if the RHS icon **730A'** has been activated. In this embodiment, if the RHS icon **730A** has not been activated, then touching a portion of the zone selection portion **761** does not result in display of the first menu **764**.

(84) In other embodiments (not shown), the options listed in the first menu **764** may comprise parameters or categories other than the zone. In one particular embodiment, the options may comprise a listing of racks designated by type, name, and/or number. For example, a first menu may comprise a listing of racks such as: Fixed Rack #1; Portable Rack #1; Fixed Rack #2; Portable Rack #2. Each rack will have corresponding programmed rack heights and may be independent of a zone or location of

the rack. In another particular embodiment, the options may comprise a job type, e.g., pickup or put away.

(85) With reference to the embodiment shown in FIG. 7D, the operator may select one of the options displayed in the workspace zone menu **764** or alter the display of the options using one or more touch gestures and/or one or more physical control elements in the vehicle operator control section **310** or the control panel **126** (FIG. 1B). For example, the operator may touch or tap the name of the desired workspace zone, e.g., “Freezer,” on the display screen **600** to select the workspace zone. In some embodiments, the workspace zone menu **764** may comprise additional zones located above and/or below the currently displayed zones. By swiping or sliding a finger along the display screen **600** over the names of the zones or near the indicator **764a**, the operator may scroll through the available zones. When the operator makes selections using one or more of the physical control elements, the display screen **600** may use the focus area or state (not shown) to visually indicate the current cursor location or current selection. For example, a background of the zone selection portion **761**, such as the area encompassed by the box with dashed lines around the text “Stacker Pallets” in FIG. 7B, may become highlighted or shaded (not shown) to indicate that the zone selection portion **761** is the current selection. The focus state may also include, for example, an outline box around the current selection.

(86) Following selection of the desired option in the workspace zone menu **764**, the display screen **600** reverts back to a display of the RHS widget **760** with the new selected workspace zone. For example, if the operator selects “Freezer” in the workspace zone menu **764** shown in FIG. 7D, the display screen **600** changes to the display depicted in FIG. 7E, in which the zone selection portion **761'** now displays the zone identifier corresponding to the selected “Freezer” zone.

(87) In addition, as shown in FIG. 7H, one or more functions of each widget may also be accessed via a general menu **766**, which may be displayed after the operator touches or selects an appropriate portion of the widget (not shown). The general menu **766** may be displayed within the widget or within the same widget space (as shown) or over another portion of the display screen **600**, such as over a portion of the second widget space **608** (not shown). The general menu **766** may comprise one or more options related to individual functions in a multifunction widget, e.g., “Select Zone” (accesses the first menu **764**) and “Pallet Presence” (accesses the pallet presence indicator **763**). In particular, the general menu **766** for the RHS widget **760** may be used to select the desired workspace zone when the operator is using, for example, one or more of the physical control elements in the vehicle operator control section **310** (FIG. 3) or the control panel **126** (FIG. 1B). The operator moves the focus area over the outer periphery of the RHS widget **760** shown in FIG. 7B and presses the enter button **164E** or depresses the rotary control knob **162** or **164F** to display the general menu **766**. The operator selects the “Select Zone” option in the same manner, after which the display screen **600** lists the available zones in the first menu **764**, as shown in FIG. 7D. The operator may then select the desired workspace zone as described.

(88) With reference to FIG. 7B, the sub-menu portion **762** may be used to select and display additional options that correspond to the option selected in the first menu **764** (FIG. 7D). In some embodiments, the additional options may comprise a plurality of programmed rack heights, and the sub-menu portion **762** (also referred to herein as a rack height selection portion) may comprise one or more of a rack height identifier **762a** and a sidebar **762b** comprising a plurality of tabs. The rack height selection portion **762** may comprise, for example, the area encompassed by the box with dashed lines around the text “Height 3, 85 in.” and the tabs in FIG. 7B. As described herein, one or more programmed rack heights may be stored in a memory of the vehicle **100** for each workspace zone or rack in the first menu **764**. Each programmed rack height corresponds to a desired height of the carriage assembly **144** (FIG. 1A) and may be customized by the end user. For example, the number of available rack heights and height values may be customized.

(89) The rack height identifier **762a** may comprise information related to a currently displayed rack height, such as a name (“Height 3”), a number, a color, or other identifying feature or combination thereof. As shown in FIG. 7B, a numerical programmed rack height, e.g., “85 in.,” may optionally be displayed in the rack height identifier **762a** in addition to or in place of the name of the selected rack height. Each tab in the sidebar **762b** corresponds to one programmed rack height. The sidebar **762b** is defined by one or more tabs corresponding to one or more programmed rack heights in the workspace zone designated in the first menu portion **761**, e.g., the “Stacker Pallets” zone as shown in FIGS. 7B and 7G. The additional options displayed in the rack height selection portion **762** are limited to those available for the particular option selected in the workspace zone menu **764**. For example, when the “Stacker Pallets” zone is selected, the additional options available in the rack height selection portion **762** will comprise only the programmed rack heights for the “Stacker Pallets” zone.

(90) When the first menu provides a listing of rack designations, the additional options available for selection in the sub-menu portion may comprise a plurality of programmed rack heights. Each rack designation in the first menu may have a corresponding set of one or more programmed rack heights in the sub-menu portion. For example, Fixed Rack #1 will have a first set of programmed rack heights and Fixed Rack #2 will have a second set of programmed rack heights, wherein the first and second sets may be different.

(91) In some embodiments, the rack height selection portion **762** displays information related to the last rack height selected by the operator. In other embodiments, the rack height select portion **762** displays information related to a default rack height, e.g., a next higher or lower available rack height based on a current position of the fork carriage assembly **144** (FIG. 1A) and/or a previous direction of travel of the fork carriage assembly **144**, both of which may be detected as described herein. In some embodiments, a visual appearance of a tab **762b'** corresponding to the currently displayed rack height is altered to reflect its selection. For example, as shown in FIG. 7B, the tab **762b'** is elongated with respect to the other tabs in the sidebar **762b**.

(92) In the illustrated embodiment, the operator may select a programmed rack height via the sidebar **762b** using one or more touch gestures and/or one or more physical control elements in the vehicle operator control section **310** (FIG. 3) or the control panel **126** (FIG. 1B). In general, the RHS feature is not available until the RHS icon **730A** is activated. When the RHS feature is off, the vehicle may be in “free” or “RHS-inactive” mode in which the operator may lower and lift the carriage assembly **144** (FIG. 1A) to any height upon continuous activation of a lifting or lowering operation, for example, via actuation of a corresponding fingertip lever **172** (FIG. 1B). Thus, when the RHS icon **730A** is not activated, an operator may not activate the

first menu portion **761**, may not access the first menu **764** and may not select a programmed rack height via the sidebar **762b**. Following activation of the RHS icon **730A** and selection of a rack height using any of the methods described herein, continuous activation of a lifting or lowering operation will cause the carriage assembly **144** to raise or lower to, and automatically stop at, a selected rack height.

(93) In one embodiment, the operator may select the desired rack height using one or more touch gestures. For example, the operator may scroll through the tabs in the sidebar **762b**, such that when each tab is touched, information regarding that tab's corresponding rack height is displayed in the rack height identifier **762a**. Thus, an operator may touch a tab in the sidebar **762b** corresponding to the desired rack height or swipe a finger along the tabs and select the tab corresponding to the desired rack height. Releasing touch of a selected tab in the sidebar **762B** causes the corresponding programmed rack height to be selected. As shown in FIG. 7G, the operator has selected the fifth programmed rack height, which is reflected in the sidebar **762b** by elongated fifth tab **762b'** corresponding to the fifth programmed rack height. Upon selection of the tab **762b'** corresponding to the desired rack height, one or more additional characteristic(s) related to the visual appearance of the tab **762b'** may be altered. For example, a background color or pattern of the tab **762b'** may change, as shown in FIG. 7G. After the desired programmed height is selected, the carriage assembly **144** will lift or lower to the selected rack height upon continuous activation of a lifting or lowering operation via actuation of a corresponding fingertip lever **172** (FIG. 1B) or use of the multifunction control handle (not shown) by the operator.

(94) In other embodiments, the rack height identifier **762a** may comprise a scroll wheel that allows the operator to scroll through the available programmed rack heights by swiping or sliding his finger up or down along the text displayed in the rack height identifier **762a**. The scroll wheel may wrap around and repeat when the operator reaches the last option at the top or bottom of the list. The scroll wheel defines a sub-menu providing a listing of programmed rack heights corresponding to the workspace zone designated in the first menu portion **761**, which, in FIG. 7B, is the "Stacker Pallets" zone. In one embodiment, only a single programmed rack height is visible at any given time in the rack height identifier scroll wheel. In other embodiments, two or more programmed rack heights are visible in the rack height identifier scroll wheel (not shown).

(95) In further embodiments, the operator may use one or more physical control elements located in the vehicle operator control section **310** (FIG. 3) to accomplish the same functions. For example, the operator may use the right or left direction buttons **164B**, **164C** to navigate to the sidebar **762b** and may use the up or down direction buttons **164A**, **164D** to navigate through the tabs. The operator may press the enter button **164E** to select one of the tabs.

(96) In yet further embodiments, the operator may use one or more physical control elements located in the control panel **126** (FIG. 1B) to select a rack height. For example, with "Height 2" displayed in the rack height identifier **762a**, and the second tab elongated, the operator may actuate a trigger switch (not shown) provided on the control panel **126** once to select the third tab **762b'**, after which a visual appearance of the tab **762b'** changes to reflect its selection (shown in FIG. 7B as being elongated). The operator may toggle to "Height 4" (not shown) by actuating the trigger a second time, "Height 5" (see FIG. 7G) by actuating the trigger a third time, etc. Upon each actuation of the trigger switch, the rack height identifier **762a** displays the next available rack height and that rack height comprises a selected rack height unless the trigger switch is actuated again, and the visual appearance of the corresponding tab **762b'** is changed to reflect its selection. To select a programmed rack height that is below the currently displayed height, e.g., "Height 2" (not shown), the operator actuates the trigger until the top of the list of programmed rack heights is reached, after which the list wraps around and the operator may begin toggling up the list from the lowest programmed rack height until the desired height is reached. After the desired programmed height is selected, the carriage assembly **144** will lift or lower to the selected rack height upon continuous activation of a lifting or lowering operation by the operator.

(97) In yet further embodiments, a trigger switch is provided on a multifunction control handle and when the RHS icon **730A** is activated but no programmed height is selected, the display screen **600** may display the RHS widget **760**. During lifting or lowering of the carriage assembly **144** via the multifunction control handle, the height shown on the display screen will automatically change to a next available programmed rack height. As the carriage assembly **144** is moving, the operator may select the next available programmed rack height, and the carriage assembly **144** will stop at the selected rack height. For example, following activation of the RHS icon **730A'** and selection of the "Stacker Pallets" zone, the operator begins a lifting operation without first choosing a programmed rack height. During the continuous lifting operation and while the carriage assembly **144** is between racks, the operator actuates the trigger switch (not shown) when the operator wishes for the carriage assembly **144** to stop at the next available programmed rack height, and the carriage assembly **144** will stop at that next available programmed rack height, e.g., the fifth programmed height in FIG. 7G.

(98) In all embodiments, a visual appearance of one or more portions of the visual depiction of the first menu **764**, the first menu portion **761** and the options contained therein, and/or the sub-menu portion **762** (including one or more of the rack height identifier **762a** and the sidebar **762b**) may be altered to indicate selection of a particular option, e.g., a workspace zone, and/or a particular additional option, e.g., a rack height. In some embodiments, each option within the first menu **764** may be color-coded with a different color, and one or more of the items displayed in the first menu portion **761** and/or the sub-menu menu portion **762** may comprise a same color associated with the corresponding option in the first menu **764**.

(99) For example, as shown in FIGS. 7B and 7E, a color of the zone selection portion **761**, e.g., a line **761a**, **761a'** beneath the zone identifier and the arrow (not labeled) to the right of the text in the zone selection portion, may correspond to a color assigned to the currently selected workspace zone. One or more additional characteristics of the zone selection portion **761**, e.g., the text of the zone identifier, a background area, etc. (not shown), may also be color-coded. Each zone may be associated with a different color to allow the operator to quickly and easily identify and select the desired workspace zone. These assigned colors may also be reflected in the visual appearance of the options, e.g., the names of the zones, the lines beneath each zone (not labeled), etc., contained in the workspace zone menu **764** (FIG. 7D). In addition, a color of one or more portions of the visual depiction of the rack height selection portion **762**, including the rack height identifier **762a** and/or the sidebar **762b**, may

correspond to a color assigned to the selected zone. For example, the color of the text displayed in the rack height identifier **762**, **762a'** and the color of the elongated tab **762b'** may correspond to the assigned color of the selected zone.

(100) In some embodiments, the visual appearance of one or more portions of the CDM widget **750** and/or the RHS widget **760** may also change to indicate that the carriage assembly **144** (FIG. 1A) has arrived at the selected rack height. For example, one or more of a color, a thickness, etc. of an outline **765** (FIG. 7G) of the RHS widget **760** may change to provide a visual confirmation to the operator that the carriage assembly **144** has reached the desired/selected programmed rack height. In FIG. 7G, outline **765** is shown darker and having an increased thickness or width to indicate to the operator that the carriage assembly **144** has reached the selected height of 129 inches, Height 5. In other embodiments, an audible tone may sound as the carriage assembly **144** passes each programmed rack height, and an audible tone or message may sound to indicate that the carriage assembly **144** has arrived at the selected rack height. These features provide confirmation to the operator that the selected function has been successfully executed and that the vehicle **100** is ready for the next operation, e.g., the carriage assembly **144** is at the expected position. In addition to the audible confirmation, the change in the outline **765** of the RHS widget **760** provides a confirmation that may be observed with a quick glance, which reduces operator distraction and provides enhanced usability.

(101) In addition, in some embodiments, a display of a portion of the CDM widget **740** and/or the RHS widget **760** may change in real time as the carriage assembly **144** raises or lowers. Movement of the carriage assembly **144** may be indicated by a corresponding upward or downward movement of the forks **744** and the pointer **749** along the scale **742** and by a corresponding increase or decrease in the numerical indication **747** of the rack height in the CDM widget **740**. In addition, if a programmed rack height has not been selected by a user prior to movement of the carriage assembly **144**, the information displayed in the rack height selection portion **762** may change as the forks approach each programmed rack height. With reference to FIG. 7G, following selection of "Height 5" the operator activates a continuous lifting operation causing the carriage assembly **144** to raise upwardly toward the corresponding programmed rack height of 129 inches. This movement of the carriage assembly **144** may be indicated, in real time with the actual movement of the carriage assembly **144**, by an upward movement of the forks **744** and the pointer **749** along the scale **742** in the CDM widget **740** to a new position corresponding to the programmed height of "129 in." and by the updated numerical indication **747'** of the rack height, as shown in FIG. 7G. In the case where a programmed rack height is not selected prior to movement of the carriage assembly **144**, but instead, will be selected via a trigger switch on a multifunction control handle during movement of the carriage assembly **144**, the name of the rack height (e.g., "Height 3," "Height 4," etc.) and the numerical rack height (e.g., "94 in.," "109 in.," etc.) displayed in the rack height identifier **762a** may change as the carriage assembly **144** approaches each programmed rack height. The location of the elongated tab **762b'**, **762b"** may also change as the carriage assembly approaches each programmed rack height.

(102) The real-time display feature may be particularly helpful in embodiments in which the operator selects a programmed rack height during a lifting or lowering operation. For example, during lifting and lowering operations, the information displayed in the rack height selection portion **762** of the RHS widget **760** indicates the next available programmed rack height so that the operator may, for example, actuate the trigger switch (not shown) to select the upcoming programmed rack height. The operator may also use the location of the forks **744** along the scale **742** and the numerical indication **747** shown in the CDM widget **740** to gauge the current position of the carriage assembly **144** and the proximity to the next programmed rack height.

(103) As illustrated herein, the rack height selection feature may be used in conjunction with the zone selection feature, but those of skill in the art will appreciate that the two features may be used independently. Combined use of the two features helps to eliminate confusion between similar, but slightly different, programmed rack heights that may exist in different workspace zones. For example, different zones in a large warehouse may comprise rack heights that are only inches apart. In the absence of zones, it may be difficult for the operator to easily determine whether the forks have been raised to the correct height. Combined use of the two features also reduces the number of programmed rack heights through which the operator must search. For example, a vehicle **100** that is used in several locations may store a large number of programmed rack heights. Without zones, the operator must search through all of the available rack heights, which adds time and difficulty to the selection process and decreases operator productivity, particularly in environments required gloved operation. For embodiments where a trigger switch is provided and used, having corresponding programmed heights defined for separate workspace zones makes use of the trigger switch during a lifting operation more usable as the operator is presented only with corresponding programmed heights in the selected workspace zone in which the operator is working.

(104) The pallet presence indicator **763** will now be described in more detail. As shown in FIG. 7B, the pallet presence indicator **763** comprises a load presence indicator **763a** and a load weight indicator **763b** and provides a visual indication of a presence or an absence of a detected load on, for example, the forks **156A** (FIG. 1A). The pallet presence indicator **763** may be displayed within the RHS widget **760**, as shown in FIG. 7B. Alternatively, the pallet presence indicator **763** may be implemented as a separate widget and/or icon (not shown). One or more sensors **232** (FIG. 2B), such as a pressure transducer in a hydraulic cylinder (not shown) of the load handling assembly **140** (FIG. 1A), may sense a weight of a load **116** on the forks **156A**. The control module **226** extracts from the monitoring input/output (I/O) module **230** (FIG. 2B) information received from the sensor(s) and provides this information for display on the display screen **600** via the pallet presence indicator **763**.

(105) As shown in FIG. 7B, when no load is detected, the load presence indicator **763a** contains a dashed outline of a box, and the load weight indicator **763b** displays a notification, such as displaying the text "Empty." In addition, when no load is detected, the current detected load weight **748** in the CDM widget **740** may also display "0 lbs."

(106) In FIGS. 7F and 7G, a load of 2,300 pounds is detected, as reflected in the pallet presence indicator **763'**. The load presence indicator **763a'** comprises a solid box and the load weight indicator **763b'** comprises a display of "2300" to reflect the presence of a detected load weighing 2,300 pounds. The current load weight **748'** in the CDM widget **740** has also been changed to display "2300 lbs." Also as shown in FIGS. 7F and 7G, the RHS feature may be used in conjunction with a load offset feature. For example, upon detection of a load on the forks, the load offset feature causes the fork carriage to stop at a slightly

higher point (as compared to unloaded forks). This height difference may be reflected in the programmed height displayed in the rack height identifier **762**. For example, the numerical programmed rack height displayed in the rack height identifier **762a** for “Height 3” is increased from “85 in.” in FIG. 7B (no load) to “94 in.” in the rack height identifier **762a'** in FIG. 7F (a detected load of 2,300 pounds) to reflect the increased height needed to ensure that the load, e.g., a pallet, and the loaded forks will clear the rack. In addition, a numerical programmed rack height for “Height 5” may be “120 in.” for unloaded forks (not shown), but because a 2,300 pound load is detected, the rack height identifier **762a'** displays a programmed rack height of “129 in.,” as shown in FIG. 7G.

(107) However, some loads (typically <500 pounds) may be too light for automatic detection by the one or more pressure sensors, causing the control module **226** (FIG. 2B) to incorrectly indicate the absence of a detected load. As discussed herein, when the load is not properly sensed, the programmed rack height is not adjusted to accommodate the loaded forks, and one or more of the vehicle's features may not function properly. In these situations, the pallet presence indicator **763** comprises an override function that permits the operator to manually indicate the presence of a load by activating a portion of the pallet presence indicator **763**. For example, when the operator knows that a load **116** is present on the forks **156A** (FIG. 1A) but the pallet presence indicator **763** incorrectly indicates the absence of a load (FIG. 7B), the operator may activate the override function by touching, tapping, clicking, or otherwise activating the pallet presence indicator **763**. In some embodiments, a portion of the display screen **600** corresponding to the pallet presence indicator **763**, e.g., an area enclosed by the oval shape, may comprise a touch-sensitive region or “button.”

(108) As shown in FIG. 7I, the override function has been activated by the operator, for example, by touching and releasing the area on the screen defining or otherwise activating the pallet presence indicator **763** in FIG. 7B. One or more characteristics of the pallet presence indicator **763'** may change to reflect activation of the override function. For example, a background color and/or pattern within the pallet presence indicator may change, as shown in FIG. 7I. In addition, the load presence indicator **763a'** comprises a solid box and the load weight indicator **763b'** displays a notification, such as “Loaded,” to reflect that the override function has been activated. The programmed rack height displayed in the rack height identifier **762a'** is also updated to 94 in. to ensure that the loaded forks clear the rack. In some embodiments, the pallet presence indicator **763'** will reset to “Empty” (FIG. 7B) when the fork carriage reaches the programmed rack height, unless a load is sensed. When a load is sensed, (e.g., as shown in FIGS. 7F and 7G), the override function may be disabled, and the pallet presence indicator **763'** will reset to “Empty” (FIG. 7B) only when no weight is detected.

(109) With reference to FIGS. 7F and 7G, several additional features of the CDM widget **740** will be described in detail. In addition to providing information about the detected load weight and current fork height, tilt, and centering, the CDM widget **740** may also provide a visual indicator of a maximum lift height based on a detected load. When a load **116** is present on the forks **156A**, **156B** (FIG. 1A), the vehicle **100** typically has a maximum lift height to which the carriage assembly **144** (FIG. 1A) should be raised for the weight of that particular load. The control module **226** (FIG. 2B) may determine a maximum lift height for the load based on a variety of parameters, such as the maximum lift height of the vehicle, a maximum lift weight capability of the vehicle, a current fork tilt, etc. A portion of the scale **742**, e.g., areas **742a**, **742b**, as shown with dashed lines, may be color-coded to provide a visual indication of lift restrictions.

(110) When no load is detected or the detected load requires no lift height restrictions, both areas **742a**, **742b** of the scale **742** may comprise a uniform, default color, e.g., green (not shown), to provide a highly visible indication to the operator that all lift heights are within the lift capacity of the vehicle **100**. In some embodiments, the CDM widget **740** may comprise an indicator (not shown) representing a percentage of capacity, e.g., an indication that the carriage assembly **144** has been raised to 80% of the determined maximum lift height.

(111) Upon detection of a load requiring a lift height restriction, the control module **226** (FIG. 2B) may change a color of one or more portions of the CDM widget **740**, in which the color(s) provide the operator with a visual indicator of the maximum lift height for that load. For example, as shown in FIGS. 7F and 7G, a load of 2,300 pounds is detected, which, in the illustrated embodiment, requires a lift height restriction. A portion, e.g., area **742a**, of the scale **742** may remain, for example, green, to indicate that lift heights within this area are within the lift capacity of the vehicle **100**. Another portion, e.g., area **742b**, of the scale **742** may be changed to another color, such as yellow or red (not shown), to provide a highly visible indication to the operator that lift heights within area **742b** of the scale **742** exceed the lift capacity of the vehicle **100**. In some embodiments (not shown), a color of one or more portions of the visual representation corresponding to the forks **744** and/or the pointer **749** may also change based on whether the forks **156A** are at a lift height that is within the lift capacity of the vehicle **100** or that has exceeded the lift capacity of the vehicle **100**. In other embodiments, the control module **226** (FIG. 2B) may limit or restrict operation of the vehicle **100**, e.g., vehicle speed and acceleration, etc. In further embodiments, a numerical indication of the maximum lift height (not shown) may be placed on the scale **742**, e.g., at the junction between areas **742a**, **742b**.

(112) When the detected load weight exceeds a maximum lift capacity of the vehicle **100**, the entire scale **742**, including areas **742a** and **742b**, may comprise a different uniform color, e.g., red (not shown), to provide a highly visible indication to the operator that the current load should not be lifted to any height. In this situation, the control module **226** may allow very limited movement of the vehicle **100**, e.g., operation at a speed below a certain threshold or over a predetermined distance, and may optionally completely disable operation of the vehicle **100**.

(113) In some embodiments, a color-coded message (not shown) may be displayed on the display screen **600** to notify or warn the operator that, for example, a determined maximum lift height for the detected load has been exceeded, the detected load exceeds a determined maximum lift capacity of the vehicle, and/or that the forks **156A** (FIG. 1A) are nearing the determined maximum lift height. In other embodiments, the control module **226** may trigger one or more audible and/or visual warnings, such as a spoken warning, audible tones, flashing lights on the display screen **600** or the vehicle **100**, etc., upon detection of one or more of the above conditions. In all embodiments, when lift height restrictions exist, an audible tone or message may sound when the carriage assembly **144** approaches a maximum height and/or when the height of the carriage assembly **144** exceeds the

maximum height.

(114) FIGS. **8-11** are flowcharts illustrating computer-implemented processes to define and control display of one or more items on a screen display of a display and processing device, e.g., the display and processing unit **151**. The computer-implemented processes can be carried out using, for example, computer-readable hardware (e.g., computer-readable hardware memory, computer readable storage media, etc.) comprising computer instructions (e.g., in the form of program code) that instruct a processor to implement the described computer-implemented process. For example, the processes illustrated in FIGS. **8-11** can be carried out by the control module **226** (FIG. **2B**). In this regard, the flowcharts depicted in FIGS. **8-11** each outline an algorithm that is executed by the processor.

(115) FIG. **8** is a flowchart illustrating a computer-implemented process **800** to define and control display of a plurality of items, e.g., widgets, on a screen display. The process begins at Step **810** in which the processor defines a plurality of widgets via execution of an application program corresponding to each widget. Each widget comprises a visual representation of a current state of an associated function of an industrial vehicle. In Step **820**, the processor controls display of a subset of the plurality of widgets on a portion of the screen display defining a plurality of widget spaces, and at Step **830**, the processor controls display of an icon tray on the screen display comprising one or more icons, wherein each of the one or more icons may be defined via execution of a corresponding application program. At least one of the icons corresponds to a respective one of the plurality of widgets. As shown in FIG. **8**, the process may continue to Step **840** in which the processor detects activation of the one icon corresponding to the one widget, and in response to detecting the activation of the one icon, locks the respective one widget in position in a locked widget space in Step **850**.

(116) FIG. **9** is a flowchart illustrating a computer-implemented process **900** to define and control display of one or more items, e.g., widgets, on a screen display. The process begins at Step **910** in which the processor defines one or more widgets. Each widget comprises a visual representation of a current state of an associated function of an industrial vehicle. At Step **920**, the processor controls display of at least one of the one or more widgets on a portion of the screen display defining one or more widget spaces, and at Step **930**, the processor controls display of an icon tray on the screen display comprising one or more icons. At least one of the icons corresponds to a respective one of the one or more widgets. The processor detects activation of the one icon corresponding to the one widget at Step **940**, and in response to detecting the activation of the one icon, allows a first menu portion of the one widget to be displayed in Step **950**. At Step **960**, the processor controls display of a first menu associated with the one widget.

(117) FIG. **10** is a flowchart illustrating a computer-implemented process **1000** to define and control display of one or more items on a screen display. The process begins at Step **1010** in which the processor defines one or more widgets. Each widget comprises a visual representation of a current state of an associated function of an industrial vehicle. At Step **1020**, the processor controls display of a rack height select (RHS) widget on a portion of the screen display defining one or more widget spaces. The RHS widget comprises a portion, e.g., an outline, that changes state upon a related vehicle function being completed, e.g., a carriage assembly of the industrial vehicle reaching a desired height.

(118) FIG. **11** is a flowchart illustrating a computer-implemented process **1100** to define and control display of a plurality of items on a screen display. The process begins at Step **1110** in which the processor defines a plurality of widgets. Each widget comprises a visual representation of a current state of an associated function of an industrial vehicle. At Step **1120**, the processor controls display of a subset of the plurality of widgets on a portion of the screen display defining a plurality of widget spaces, and at Step **1130**, the processor controls display of an icon tray on the screen display comprising one or more icons. At least one of the icons corresponds to a respective one of the plurality of widgets. The processor detects activation of the one icon corresponding to the one widget at Step **1140**, and in response to detecting the activation of the one icon, moves the respective one widget to a predefined widget space in Step **1150**. At Step **1160**, the processor moves the respective one widget from the predefined widget space in response to an operator command to move the widget away from the predefined widget space, and at Step **1170**, the processor moves the one widget back to the predefined widget space in response to a command related to a vehicle operation.

(119) In addition to, or in place of, the use of one or more touch gestures or physical control elements in the vehicle operator control section **310** (FIG. **3**) or the control panel **126** (FIG. **1B**), the operator may make one or more selections using a voice control system (not shown), examples of which are described more fully in U.S. Pat. No. 7,017,689, the entirety of which is hereby incorporated by reference herein. The operator may be equipped with a headset (not shown), and/or the display unit **151** or a portion of the control panel **126** may comprise a microphone (not shown). The voice control system is programmed to receive and recognize one or more predetermined verbal commands from the operator. The vehicle control system then translates each verbal command into a signal for processing by, for example, the control module **226** and/or one or more control modules or controllers **238** (FIG. **2B**), which transmits an appropriate output command to control operation of the display unit **151** (FIG. **3**) and/or the vehicle **100**.

(120) For example, receipt of the verbal command ACTIVATE RHS ICON or ACTIVATE RHS WIDGET may activate the RHS icon **730A** and move the RHS widget **760** (FIG. **7B**) to a predefined widget space in a manner similar to the movement of the RHS widget **760** upon activation of the RHS icon **730A** using one or more touch gestures or physical control elements, as described herein. Receipt of the verbal commands SELECT ZONE or SELECT RACK HEIGHT may activate or cause the display of the zone selection portion **761** or the rack height selection portion **762**, respectively, of the RHS widget **760** in a manner similar to the activation or display following the use of one or more touch gestures or physical control elements, as described herein.

(121) Referring now to FIG. **12**, a schematic block diagram illustrates an exemplary computer system **800** for implementing the control module **226** of FIG. **2B**. The exemplary computer system **800** comprises one or more (hardware) microprocessors **810** and corresponding (hardware) memory **820** (e.g., random access memory and/or read only memory) that are connected to a system bus **830**. Information may be passed between the system bus **830** and an optional data bus **850** by a suitable bridge **840**.

The data bus **850** is used to interface peripherals with the one or more microprocessors **810**, such as storage **860** (e.g., solid state hard disk drive); removable media storage device(s) **870** (e.g., flash drives, etc.); I/O devices **880** (e.g., the graphical user interface module of the service module **220** of FIG. 2B, a universal serial bus (USB) interface, etc.); and one or more adapters **890**. The adapters **890**, where provided, allow the microprocessor **810** to communicate across one or more of the vehicle network systems (e.g., **236** of FIG. 2B). In this regard, example adapters **890** may comprise Bluetooth®, Ethernet, CAN bus, RS422, LIN Bus, WiFi, cellular, etc.

(122) This list of peripherals is presented by way of illustration, and is not intended to be limiting. Other peripheral devices may be suitably integrated into the computer system **800**. The memory **820**, storage **860**, removable media insertable into the removable media storage **870**, or combinations thereof may be used to implement the methods, configurations, interfaces and other aspects set out and described herein.

(123) The microprocessor(s) **810** control operation of the exemplary computer system **800**. Moreover, one or more of the microprocessor(s) **810** execute computer readable code that instructs the microprocessor(s) **810** to implement the methods and processes herein. The computer readable code may be stored for instance, in the memory **820**, storage **860**, removable media storage device(s) **870**, or other suitable tangible storage medium accessible by the microprocessor(s) **810**. The memory **820** may also function as a working memory, e.g., to store data, an operating system, etc.

(124) The methods and processes herein may be implemented as a machine-executable method executed on a computer system, e.g., one or more general or particular computing devices such as the processing devices **202** of FIGS. 2A and 2B, on a system **800** of FIG. 12, or combinations thereof. In this regard, the methods and processes herein may be implemented on a computer-readable storage device (e.g., computer-readable storage hardware) that stores machine-executable program code, where the program code instructs a processor to implement the described method/process. The methods and processes herein may also be executed by a processor coupled to memory, where the processor is programmed by program code stored in the memory, to perform the described method.

(125) Computer program code for carrying out operations for any aspect or embodiment of the present disclosure may be written in any combination of one or more programming languages. The program code may execute fully or partially on the computer system **800**. In the latter scenario, the remote computer may be connected to the computer system **800** through any type of network connection, e.g., using the network adapter **890** of the computer system **800**. In implementing computer aspects of the present disclosure, any combination of computer-readable medium may be utilized. The computer-readable medium may be a computer readable signal medium, a computer-readable storage medium, or a combination thereof. Moreover, a computer-readable storage medium may be implemented in practice as one or more distinct mediums.

(126) A computer-readable storage medium is a tangible device/hardware that may retain and store a program (instructions) for use by or in connection with an instruction execution system, apparatus, or device, e.g., a computer or other processing device set out more fully herein. Notably, a computer-readable storage medium does not encompass a computer-readable signal medium. Thus, a computer readable storage medium, as used herein, is not to be construed as being transitory signals per se, such as radio waves or other freely propagating electromagnetic waves through a transmission media. Specific examples of the computer-readable storage medium may include, but are not limited to, the following: a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM), Flash memory, or any suitable combination of the foregoing. In particular, a computer-readable storage medium comprises computer-readable hardware such as a computer-readable storage device, e.g., memory. As used herein, a computer-readable storage device and computer-readable hardware are physical, tangible implementations that are non-transitory.

(127) By non-transitory, it is meant that, unlike a transitory propagating signal per se, which will naturally cease to exist, the contents of the computer-readable storage device or computer-readable hardware that define the claimed subject matter persists until acted upon by an external action. For instance, program code loaded into random access memory (RAM) is deemed non-transitory in that the content will persist until acted upon, e.g., by removing power, by overwriting, deleting, modifying, etc. Moreover, since hardware comprises physical element(s) or component(s) of a corresponding computer system, hardware does not encompass software, per se. The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the disclosure. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(128) The description of the present disclosure has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited only to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the invention.

(129) Having thus described the invention of the present application in detail and by reference to embodiments thereof, it will be apparent that modifications and variations are possible without departing from the scope of the invention defined in the appended claims.

Claims

1. An industrial vehicle comprising: a carriage assembly comprising one or more forks; a lift control for causing the carriage assembly to be lifted or lowered when actuated; and a processing device comprising a graphical user interface, the processing device comprising a touch screen display, a memory storing executable instructions, and a processor in communication with the memory, wherein the processor when executing the executable instructions: defines a plurality of widgets, each widget comprising a visual representation of a current state of an associated function of the industrial vehicle, wherein the plurality of

widgets comprises a rack height select (RHS) widget and a capacity data monitoring (CDM) widget, wherein the CDM widget comprises a scale, a current sensed load weight, a visual representation of the one or more forks, and a numerical indication of a current position of the carriage assembly, and the rack height select (RHS) widget comprises a load presence indicator providing a visual indication of a presence or an absence of a detected load; controls display of at least one of the plurality of widgets on a portion of the screen display defining one or more widget spaces; controls display of an icon tray on the screen display comprising one or more icons, wherein one icon of the one or more icons corresponds to an RHS feature; when the one icon is activated, activates the RHS feature and allows a selection of a programmed rack height, such that when a vehicle operator actuates the lift control, the carriage assembly will automatically stop at the selected programmed rack height, wherein the RHS widget changes in real time to indicate a position of the carriage assembly with respect to the selected programmed rack height; when the one icon is not activated, the RHS feature is inactive, such that when the vehicle operator actuates the lift control, the carriage assembly will move to any height upon continuous activation of the lift control by the vehicle operator; controls display of the current sensed load weight adjacent to the visual representation of the one or more forks and causes the current sensed load weight, the visual representation of the one or more forks, and the numerical indication of a current position of the carriage assembly to move vertically along the scale to indicate, in real-time, a current position of the carriage assembly and the current sensed load weight; and upon activation of a touch-sensitive region of the load presence indicator on the touch screen display by the vehicle operator, overrides the indication of the absence of a detected load.

2. The industrial vehicle of claim 1, wherein a visual appearance of the one icon changes upon activation.

3. The industrial vehicle of claim 1, wherein the processor when executing the executable instructions: defines a plurality of widget spaces; and in response to detecting the activation of the one icon, moves the RHS widget to a predefined widget space on the screen display.

4. The industrial vehicle of claim 1, wherein the processor when executing the executable instructions: defines a plurality of widget spaces; and in response to detecting the activation of the one icon, locks the RHS widget in position in a first widget space on the screen display.

5. The industrial vehicle of claim 4, wherein the processor when executing the executable instructions: further in response to detecting the activation of the one icon, shifts the remaining one or more widgets to the one or more remaining widget spaces.

6. The industrial vehicle of claim 1, wherein the processor when executing the executable instructions: defines the icon tray as a separate portion of the screen display from the plurality of widget spaces, the icon tray being spaced apart from the plurality of widget spaces.

7. The industrial vehicle of claim 1, wherein the RHS widget comprises a workspace zone menu comprising a plurality of workspace zones, each workspace zone having a corresponding sub-menu comprising a plurality of programmed rack heights associated with the workspace zone.

8. The industrial vehicle of claim 7, wherein when the one icon is activated, the processor when executing the executable instructions: displays the workspace zone menu comprising the plurality of workspace zones; receives a selection of one workspace zone of the plurality of workspace zones; and displays an identifier of the one workspace zone.

9. The industrial vehicle of claim 8, wherein the processor when executing the executable instructions: displays the sub-menu corresponding to the one workspace zone; receives a selection of one programmed rack height of the plurality of programmed rack heights within the sub-menu; and displays an identifier of the one programmed rack height.

10. The industrial vehicle of claim 7, wherein the processor when executing the executable instructions: color-codes at least a portion of each workspace zone with a different color; and color-codes at least a portion of each sub-menu with a same color associated with the corresponding workspace zone.

11. The industrial vehicle of claim 1, further comprising: a vehicle network system connecting the processor to at least one vehicle network bus, wherein the processor extracts a current position of a carriage assembly and the current sensed load weight.

12. The industrial vehicle of claim 1, further comprising a vehicle operator control section comprising one or more physical input control elements, wherein the one or more physical input control elements are used to make selections on the screen display.

13. The industrial vehicle of claim 12, wherein the one or more physical input control elements comprise at least one of a five-button control, a trigger switch, or a rotary control knob.

14. The industrial vehicle of claim 1, wherein: the screen display comprises a touch screen display that receives touch gesture commands from the vehicle operator; and the processor when executing the executable instructions: controls display of a subset of the plurality of widgets on the portion of the screen display defining the one or more widget spaces; determines if a speed of the industrial vehicle is below a threshold speed; when the speed of the industrial vehicle is below the threshold speed, changes one or more of the widgets of the subset on the touch screen display following detection of a touch gesture on the touch screen display; and when the speed of the industrial vehicle is above the threshold speed, disables one or more portions of the touch screen display.

15. The industrial vehicle of claim 1, wherein: the icon corresponding to the RHS feature comprises text; and the text changes appearance when the one icon is activated.

16. The industrial vehicle of claim 4, wherein: the plurality of widgets comprise one or more widgets available for display, the one or more widgets available for display being arranged in an array; the screen display further comprises a widget position indicator illustrating a number and a relative position within the array of the one or more widgets available for display; and in response to detecting the activation of the one icon, the processor when executing the executable instructions: alters one or more characteristics of a portion of the widget position indicator corresponding to the RHS widget to indicate that the RHS widget is locked in position in the first widget space on the screen display.

17. An industrial vehicle comprising: a carriage assembly; a lift control for causing the carriage assembly to be lifted or lowered when actuated; and a processing device comprising a graphical user interface, a touch screen display, a memory storing

executable instructions, and a processor in communication with the memory, wherein the processor when executing the executable instructions: defines one or more widgets, each widget comprising a visual representation of a current state of an associated function of the industrial vehicle, wherein the one or more widgets comprise a rack height select (RHS) widget comprising a load presence indicator providing a visual indication of a presence or an absence of a detected load; controls display of at least one of the one or more widgets on a portion of the touch screen display defining one or more widget spaces; controls display of an icon tray on the touch screen display comprising one or more icons, wherein one icon of the one or more icons corresponds to a rack height select (RHS) feature; when the one icon is activated, activates the RHS feature and allows a selection of a programmed rack height, such that when a vehicle operator actuates the lift control, the carriage assembly will automatically stop at the selected programmed rack height; when the one icon is not activated, the RHS feature is inactive, such that when the vehicle operator actuates the lift control, the carriage assembly will move to any height upon continuous activation of the lift control by the vehicle operator; and upon activation of a touch-sensitive region of the load presence indicator on the touch screen display by the vehicle operator, overrides the indication of the absence of a detected load.

18. The industrial vehicle of claim 17, wherein the processor when executing the executable instructions: changes one or more characteristics of the load presence indicator on the touch screen display to reflect activation of the portion of the load presence indicator.
