

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405759
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Bar-Zeev; Avi et al.

Gaze-based user interactions

Abstract

In an exemplary process for interacting with user interface objects using an eye gaze, a placement point for a selected object is designated at a first position based on a gaze position. In response to a user input, the placement point is moved to a second position that is not based on the gaze position, and the object is placed at the second position.

Inventors: Bar-Zeev; Avi (Oakland, CA), Burgoyne; Ryan S. (Sunnyvale, CA), Chalmers; Devin W. (Oakland, CA), Deliz Centeno; Luis R. (Fremont, CA), Nair; Rahul (Hayward, CA), Oriol; Timothy R. (San Jose, CA), Palangie; Alexis H. (Palo Alto, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 63858220

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 18/209931

Filed: June 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230325140 A1	Oct. 12, 2023

Related U.S. Application Data

continuation parent-doc US 17486646 20210927 US 11714592 child-doc US 18209931
continuation parent-doc US 16828852 20200324 US 11132162 20210928 child-doc US 17486646
continuation parent-doc WO PCT/US2018/053428 20180928 PENDING child-doc US 16828852
us-provisional-application US 62734678 20180921
us-provisional-application US 62566073 20170929

Publication Classification

Int. Cl.: **G06F3/14** (20060101); **G02B27/00** (20060101); **G02B27/01** (20060101); **G06F3/01** (20060101); **G06F3/0346** (20130101); **G06F3/04815** (20220101); **G06F3/04842** (20220101); **G06T7/73** (20170101); **G06T19/00** (20110101); **G06V20/20** (20220101); **G06V40/20** (20220101); **H04B5/70** (20240101)

U.S. Cl.:

CPC **G06F3/1423** (20130101); **G02B27/0093** (20130101); **G02B27/017** (20130101); **G06F3/013** (20130101); **G06F3/017** (20130101); **G06F3/0346** (20130101); **G06F3/04815** (20130101); **G06F3/04842** (20130101); **G06T7/74** (20170101); **G06T19/006** (20130101); **G06V20/20** (20220101); **G06V40/20** (20220101); **H04B5/70** (20240101); G02B2027/0187 (20130101)

Field of Classification Search

CPC: G06F (3/013); G06F (3/017); G06F (3/04815); G06F (3/04842); G06F (3/1423)

USPC: 715/863

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5664133	12/1996	Malamud	345/902	G06F 3/0482
5949432	12/1998	Gough	345/629	G06F 3/0481
8408706	12/2012	Yahav	351/209	H04N 13/239
9007301	12/2014	Raffle	345/156	G09G 3/003
10110678	12/2017	Hebsur et al.	N/A	N/A
10248399	12/2018	Yoon	N/A	N/A
10353532	12/2018	Holz	N/A	G06F 3/04847
11132162	12/2020	Bar-Zeev	N/A	G06F 3/04815
11550444	12/2022	Josephson	N/A	G06F 3/013
11714592	12/2022	Bar-Zeev	715/863	G06F 3/1423
2002/0113943	12/2001	Trajkovic	351/209	G02B 27/0093
2004/0150584	12/2003	Chuman	348/E13.057	H04N 13/395
2005/0175218	12/2004	Vertegaal	345/157	G06T 7/254

2007/0162872	12/2006	Hong	715/828	G06F 3/0482
2008/0154494	12/2007	Kato	701/454	G01C 21/3638
2008/0181452	12/2007	Kwon	382/103	G06V 40/19
2008/0211766	12/2007	Westerman	345/156	G06F 3/0482
2008/0307360	12/2007	Chaudhri	715/835	G06F 3/0481
2011/0037712	12/2010	Kim	345/173	G06F 3/0488
2011/0161890	12/2010	Anderson	715/863	H04N 21/42201
2012/0249416	12/2011	Maciocci	345/156	H04N 9/3173
2013/0007668	12/2012	Liu et al.	N/A	N/A
2013/0042296	12/2012	Hastings	726/1	G06Q 50/184
2013/0050258	12/2012	Liu	345/633	G06F 3/013
2013/0050432	12/2012	Perez	348/47	G06F 3/011
2013/0141419	12/2012	Mount	345/419	G09G 3/003
2013/0241805	12/2012	Gomez	345/8	G06F 3/013
2013/0283208	12/2012	Bychkov	715/810	G06F 3/0425
2013/0328762	12/2012	McCulloch	345/156	G06F 3/016
2014/0043227	12/2013	Skogo	345/156	G06F 1/325
2014/0096076	12/2013	Ashbrook	715/808	G06F 3/013
2014/0160001	12/2013	Kinnebrew	345/156	G06F 3/0482
2014/0184550	12/2013	Hennessey	345/173	G06F 3/041
2014/0201844	12/2013	Buck	726/26	G06F 21/554
2014/0204002	12/2013	Bennet	345/7	G06F 3/017
2014/0240471	12/2013	Srinivasa et al.	N/A	N/A
2014/0253592	12/2013	Cho	345/633	G06V 30/142
2014/0333666	12/2013	Poulos	345/633	G06T 19/006
2015/0084857	12/2014	Kimura	345/156	G06F 1/163
2015/0100803	12/2014	Chen	715/740	H04L 12/28
2015/0103149	12/2014	McNamer et al.	N/A	N/A
2015/0130716	12/2014	Sridharan	345/158	G06F 3/017
2015/0138079	12/2014	Lannsjö	345/156	G06F 3/013
2015/0199005	12/2014	Haddon	345/163	G06F 3/013
2015/0205494	12/2014	Scott	345/158	G06F 3/04842
2015/0268821	12/2014	Ramsby	715/765	G06V 40/19
2015/0293592	12/2014	Cheong	345/173	G06F 1/163
2015/0317518	12/2014	Fujimaki	345/633	G02B 27/017

2015/0317837	12/2014	Sholudko	345/633	G06F 3/167
2015/0323990	12/2014	Maltz	345/173	G02B 27/0179
2015/0347114	12/2014	Yoon	717/176	H04L 12/2832
2015/0362729	12/2014	Jang	345/8	G02B 27/017
2016/0005229	12/2015	Lee et al.	N/A	N/A
2016/0018645	12/2015	Haddick et al.	N/A	N/A
2016/0018654	12/2015	Haddick	345/8	G02B 27/017
2016/0025981	12/2015	Burns	345/156	G02B 27/0093
2016/0026242	12/2015	Burns	345/633	G06F 3/04817
2016/0026253	12/2015	Bradski	345/8	H04N 13/128
2016/0085301	12/2015	Lopez	345/156	H04N 17/002
2016/0116980	12/2015	George-Svahn	345/173	G06F 3/041
2016/0179336	12/2015	Ambrus	715/768	G02B 27/017
2016/0182877	12/2015	Deluca	348/54	H04N 13/368
2016/0241767	12/2015	Cho	N/A	G06F 3/04842
2016/0262614	12/2015	Ninomiya	N/A	A61B 3/113
2016/0267708	12/2015	Nistico	N/A	H04N 13/344
2016/0274762	12/2015	Lopez	N/A	G06T 19/006
2016/0284123	12/2015	Hare et al.	N/A	N/A
2016/0292759	12/2015	Gonzalez Miranda	N/A	G06F 3/04845
2016/0295038	12/2015	Rao	N/A	H04N 1/00214
2016/0313875	12/2015	Williams	N/A	G06F 1/163
2016/0371888	12/2015	Wright	N/A	G06F 3/011
2016/0379418	12/2015	Osborn	345/589	G06T 19/20
2017/0038829	12/2016	Lanier	N/A	G06T 19/006
2017/0060230	12/2016	Faaborg	N/A	G06F 3/017
2017/0078825	12/2016	Mangiat	N/A	G06F 3/017
2017/0090566	12/2016	George-Svahn	N/A	G06F 3/04883
2017/0099481	12/2016	Held	N/A	H04N 13/383
2017/0134553	12/2016	Jeon	N/A	H04W 4/08
2017/0153701	12/2016	Mahon	N/A	G06F 3/0482

2017/0185156	12/2016	Shotton	N/A	G06F 3/0484
2017/0185276	12/2016	Lee	N/A	G06F 3/04847
2017/0194768	12/2016	Powers	N/A	H04N 23/65
2017/0221276	12/2016	Osborn et al.	N/A	N/A
2017/0237974	12/2016	Samec	348/53	H04N 13/122
2017/0318019	12/2016	Gordon	N/A	G06V 40/67
2018/0004283	12/2017	Mathey-Owens	N/A	G06F 3/04842
2018/0054487	12/2017	Hebsur	N/A	H04L 43/08
2018/0081171	12/2017	Park	N/A	G02B 27/017
2018/0095635	12/2017	Valdivia	N/A	G02B 27/0093
2018/0096202	12/2017	Stathacopoulos et al.	N/A	N/A
2018/0204385	12/2017	Sarangdhar	N/A	H04L 12/282
2018/0249086	12/2017	Ozawa	N/A	G05D 1/0038
2019/0025910	12/2018	Gilra	N/A	G06F 3/0481
2019/0122420	12/2018	Terahata	N/A	G06T 19/20
2019/0244416	12/2018	Tamaoki	N/A	G09G 5/377
2019/0318660	12/2018	Kimoto	N/A	B25J 13/06
2019/0378423	12/2018	Bachrach et al.	N/A	N/A
2020/0192622	12/2019	Stoyles	N/A	G06F 3/011
2020/0201444	12/2019	Stoyles et al.	N/A	N/A
2020/0225746	12/2019	Bar-zeev et al.	N/A	N/A
2020/0225747	12/2019	Bar-zeev et al.	N/A	N/A
2020/0301553	12/2019	Taylor	N/A	G06F 3/04812
2021/0096726	12/2020	Faulkner	N/A	G06F 1/1686
2021/0097776	12/2020	Faulkner	N/A	G06V 40/113
2021/0240331	12/2020	Olson	N/A	G06F 3/013
2021/0365228	12/2020	Stoyles et al.	N/A	N/A
2022/0012002	12/2021	Bar-zeev et al.	N/A	N/A
2022/0083303	12/2021	Stoyles et al.	N/A	N/A
2022/0245900	12/2021	Tan et al.	N/A	N/A
2023/0376261	12/2022	Stoyles et al.	N/A	N/A
2023/0393796	12/2022	Stoyles et al.	N/A	N/A
2024/0103614	12/2023	Dryer	N/A	G06F 3/013
2024/0104871	12/2023	Brewer	N/A	G06F 1/1694
2024/0411497	12/2023	Stoyles et al.	N/A	N/A
2025/0103133	12/2024	Pastrana et al.	N/A	N/A

2025/0190161	12/2024	Stoyles et al.	N/A	N/A
--------------	---------	----------------	-----	-----

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102843523	12/2011	CN	N/A
103164017	12/2012	CN	N/A
103460256	12/2012	CN	N/A
103765346	12/2013	CN	N/A
104516497	12/2014	CN	N/A
105009039	12/2014	CN	N/A
105393190	12/2015	CN	N/A
105493501	12/2015	CN	N/A
106164818	12/2015	CN	N/A
106371206	12/2016	CN	N/A
106415444	12/2016	CN	N/A
106462231	12/2016	CN	N/A
106462733	12/2016	CN	N/A
106951069	12/2016	CN	N/A
107003521	12/2016	CN	N/A
0513584	12/1991	EP	N/A
1055200	12/2002	EP	N/A
2940556	12/2014	EP	N/A
2947546	12/2014	EP	N/A
3118722	12/2016	EP	N/A
2004-37149	12/2003	JP	N/A
2004-513403	12/2003	JP	N/A
2004-517359	12/2003	JP	N/A
2005-157329	12/2004	JP	N/A
2008-158583	12/2007	JP	N/A
2009-64395	12/2008	JP	N/A
2012-221498	12/2011	JP	N/A
2015-90635	12/2014	JP	N/A
2015-126857	12/2014	JP	N/A
2016-502120	12/2015	JP	N/A
2016-85588	12/2015	JP	N/A
2016-192132	12/2015	JP	N/A
10-2002-0086590	12/2001	KR	N/A
10-2007-0067332	12/2006	KR	N/A
10-2015-0125472	12/2014	KR	N/A
2013/144807	12/2012	WO	N/A
2014/033306	12/2013	WO	N/A
2014/204755	12/2013	WO	N/A
2015/110852	12/2014	WO	N/A
2015/140106	12/2014	WO	N/A
2015/142966	12/2014	WO	N/A
2016/045784	12/2015	WO	N/A

2016/099706	12/2015	WO	N/A
2017/031089	12/2016	WO	N/A
2017/096097	12/2016	WO	N/A
2017/112692	12/2016	WO	N/A
2023/049170	12/2022	WO	N/A

OTHER PUBLICATIONS

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/534,102, mailed on Sep. 27, 2022, 2 pages. cited by applicant

Brief Communication regarding Oral Proceedings received for European Patent Application No. 18786644.7, mailed on Feb. 27, 2023, 3 pages. cited by applicant

Businesswire, "SMI Gaze Interaction Powers Google Glass Prototype", Online Available at: <https://www.youtube.com/watch?v=R3xxqap7DmQ&t=1s>, Mar. 3, 2015, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/828,857, mailed on Sep. 1, 2021, 3 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 18786644.7, mailed on Mar. 27, 2023, 9 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/534,102, mailed on Nov. 30, 2022, 14 pages. cited by applicant

Howmuchtech, "5 Best Smart Glasses of 2022", Online Available at: <https://www.youtube.com/watch?v=xll2Ycc6Fv0&t=162s>, Dec. 24, 2021, 6 pages. cited by applicant

Kunhee et al., "Distant 3D Object Grasping with Gaze-supported Selection", The 12th International Conference on Ubiquitous Robots and Ambient Intelligence (URAI 2015), Oct. 28-30, 2015, pp. 541-544. cited by applicant

Liu et al., "Video avatar-based remote video collaboration", Journal of Beijing University of Aeronautics and Astronautics, vol. 41, No. 6, Jun. 2015, pp. 1087-1094. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 18786644.7, mailed on Mar. 24, 2023, 5 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/052,081, mailed on Jul. 14, 2021, 16 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/394,114, mailed on Jul. 6, 2022, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/534,102, mailed on Jul. 7, 2022, 14 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201880051530.5, mailed on Apr. 8, 2022, 5 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201880052303.4, mailed on Mar. 9, 2022, 4 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201880055893.6, mailed on Mar. 30, 2022, 4 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-7006018, mailed on Apr. 18, 2022, 4 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/802,188, mailed on Jul. 29, 2021, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/828,857, mailed on Jul. 14, 2021, 6 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/052,081, mailed on Jan. 14, 2022, 7 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/394,114, mailed on Feb. 7, 2023, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/394,114, mailed on Oct. 21, 2022, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/534,102, mailed on Jan. 11, 2023, 8 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201880051530.5, mailed on Sep. 6, 2021, 18 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201880052303.4, mailed on Sep. 27, 2021, 20 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201880055893.6, mailed on Sep. 6, 2021, 21 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-142308, mailed on Oct. 31, 2022, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-7006018, mailed on Oct. 9, 2021, 9 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7022762, mailed on Jan. 27, 2023, 6 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7022762, mailed on Jul. 19, 2022, 9 pages. cited by applicant

Special Effect, "Open Drive—Eye Gaze Games | Eye Gaze Controls & Options", Online Available at: <https://www.youtube.com/watch?v=IJi2aOdSau8&t=63s>, Mar. 18, 2022, 3 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 18786644.7, mailed on Nov. 10, 2022, 5 pages. cited by applicant

Takase et al., "Gestural Interface and the Intuitive Interaction with Virtual Objects", ICROS-SICE International Joint Conference, 2009, pp. 3260-3263. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/229,059, mailed on Mar. 7, 2024, 15 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2023-7022376, mailed on Jan. 30, 2024, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/394,114, mailed on Jun. 14, 2023, 2 pages. cited by applicant

Decision of Rejection received for Japanese Patent Application No. 2021-142308, mailed on May 15, 2023, 4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/394,114, mailed on Jun. 2, 2023, 11 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/534,102, mailed on May 2, 2023, 8 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7022762, mailed on Apr. 11, 2023, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2023-7022376, mailed on Jul. 26, 2023, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/229,059, mailed on Apr. 26, 2024, 2 pages. cited by applicant

Chatterjee et al., "Gaze+Gesture: Expressive, Precise and Targeted Free-Space Interactions", ICMI '15: Proceedings of the 2015 ACM on International Conference on Multimodal Interaction, online available at: <https://dl.acm.org/doi/10.1145/2818346.2820752>, Nov. 9-13, 2015, pp. 131-138. cited by applicant

Extended European Search Report received for European Patent Application No. 23219457.1,

mailed on Apr. 16, 2024, 10 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/033501, mailed on Feb. 26, 2024, 21 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/033549, mailed on Jan. 15, 2024, 15 pages. cited by applicant
Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2023/033501, mailed on Jan. 5, 2024, 15 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/235,693, mailed on Jul. 3, 2024, 25 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/229,059, mailed on Jul. 11, 2024, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/235,693, mailed on Aug. 28, 2024, 11 pages. cited by applicant
Office Action received for Chinese Patent Application No. 202210616910.7, mailed on Aug. 8, 2024, 19 pages (10 pages of English Translation and 9 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 202210618012.5, mailed on Aug. 9, 2024, 16 pages (9 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2023-149802, mailed on Jul. 29, 2024, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant
Extended European Search Report received for European Patent Application No. 23173161.3, mailed on Oct. 30, 2023, 9 pages. cited by applicant
Office Action received for Chinese Patent Application No. 201980028660.1, mailed on Oct. 18, 2023, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant
Notice of Allowance received for Chinese Patent Application No. 201980028660.1, mailed on Feb. 27, 2024, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2023-7022376, mailed on Oct. 21, 2024, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant
Decision to Grant received for Japanese Patent Application No. 2023-149802, mailed on Dec. 3, 2024, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 202210616910.7, mailed on Nov. 22, 2024, 17 pages (9 pages of English Translation and 8 pages of Official Copy). cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/235,693, mailed on Feb. 20, 2025, 2 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/235,693, mailed on Dec. 13, 2024, 10 pages. cited by applicant
Notice of Allowance received for Chinese Patent Application No. 202210618012.5, mailed on Jan. 1, 2025, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant
Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2024/045209, mailed on Dec. 10, 2024, 11 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/045209, mailed on Jan. 31, 2025, 14 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/033501, mailed on Apr. 3, 2025, 16 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/033549, mailed on Apr. 3, 2025, 10 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/802,188, mailed on Mar. 23, 2021, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/802,320, mailed on Apr. 9, 2021, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/828,852, mailed on Jan. 27,

2021, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/828,852, mailed on Jun. 8, 2021, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/828,857, mailed on Jun. 10, 2021, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/486,646, mailed on Aug. 23, 2022, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/486,646, mailed on Dec. 28, 2022, 2 pages. cited by applicant
Decision to Grant received for Japanese Patent Application No. 2020-512573, mailed on Aug. 2, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant
Final Office Action received for U.S. Appl. No. 16/802,188, mailed on May 14, 2021, 18 pages. cited by applicant
Final Office Action received for U.S. Appl. No. 16/828,852, mailed on Mar. 9, 2021, 16 pages. cited by applicant
Final Office Action received for U.S. Appl. No. 17/486,646, mailed on Oct. 5, 2022, 20 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2018/053415, mailed on Apr. 9, 2020, 10 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2018/053422, mailed on Apr. 9, 2020, 10 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2018/053427, mailed on Apr. 9, 2020, 14 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2018/053428, mailed on Apr. 9, 2020, 8 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2019/028980, mailed on Nov. 19, 2020, 10 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2018/053415, mailed on Dec. 13, 2018, 14 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2018/053422, mailed on Dec. 19, 2018, 13 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2018/053427, mailed on Mar. 25, 2019, 18 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2018/053428, mailed on Jan. 25, 2019, 9 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2019/028980, mailed on Aug. 16, 2019, 14 pages. cited by applicant
Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2018/053427, mailed on Feb. 1, 2019, 13 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/802,188, mailed on Dec. 16, 2020, 15 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/802,320, mailed on Dec. 24, 2020, 19 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/828,852, mailed on Nov. 9, 2020, 14 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/828,857, mailed on Feb. 17, 2021, 12 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/486,646, mailed on Jun. 15, 2022, 17 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 16/802,320, mailed on Apr. 30, 2021, 9 pages.

cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/828,852, mailed on Jul. 27, 2021, 10 pages.

cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/486,646, mailed on Mar. 22, 2023, 9 pages.

cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/370,363, mailed on May 29, 2025, 14 pages.

cited by applicant

Office Action received for European Patent Application No. 18786644.7, mailed on Apr. 28, 2021, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-512573, mailed on Apr. 12, 2021, 7 pages (4 pages of English Translation and 3 pages of Official Copy). cited by applicant

Stellmach et al., "Look & Touch: Gaze-supported Target Acquisition", CHI'12: Proceedings of the SIGCHI Conference on Human Factors in Computing Systems; Available online at:

<https://dl.acm.org/doi/10.1145/2207676.2208709>, May 5-10, 2012, pp. 2981-2990. cited by applicant

Stellmach et al., "Still Looking: Investigating Seamless Gaze-supported Selection, Positioning, and Manipulation of Distant Targets", CHI'13: Proceedings of the SIGCHI Conference on Human Factors in Computing Systems; Available online at:

<https://dl.acm.org/doi/10.1145/2470654.2470695>, Apr. 27-May 2, 2013, pp. 285-294. cited by applicant

Wang, Zichuan, "Transmissive smart glasses based on image recognition and gesture tracking", Innovation Technology Frontier, pp. 26-28 (Official Copy Only). {See Communication under Rule 37 CFR § 1.98(a) (3)}. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/811,647, mailed on Jun. 30, 2025, 12 pages. cited by applicant

Primary Examiner: Nabi; Reza

Attorney, Agent or Firm: DLA Piper LLP (US)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/486,646, entitled "Gaze-based User Interactions", filed Sep. 27, 2021, which is a continuation of U.S. patent application Ser. No. 16/828,852, entitled "Gaze-based User Interactions" filed Mar. 24, 2020, now U.S. Pat. No. 11,132,162, which is a continuation of International Application No. PCT/US2018/053428, entitled "Gaze-Based User Interactions," filed Sep. 28, 2018, which claims priority to: U.S. Patent Application Ser. No. 62/734,678, entitled "Gaze-based User Interactions," filed Sep. 21, 2018; U.S. Patent Application Ser. No. 62/566,206, entitled "Gaze-based User Interactions," filed Sep. 29, 2017; U.S. Patent Application Ser. No. 62/566,073, entitled "Accessing Functions of External Devices Using Reality Interfaces," filed Sep. 29, 2017; and U.S. Patent Application Ser. No. 62/566,080, entitled "Controlling External Devices Using Reality Interfaces," filed Sep. 29, 2017, which are hereby incorporated by reference in their entirety for all purposes.

BACKGROUND

1. Field

(1) The present disclosure relates generally to user interfaces for interacting with an electronic device, and more specifically to interacting with an electronic device using an eye gaze.

2. Description of Related Art

(2) Conventional electronic devices use input mechanisms, such as keyboards, buttons, joysticks, and touch-screens, to receive inputs from a user. Some conventional devices also include a screen that displays content responsive to a user's input. Such input mechanisms and displays provide an interface for the user to interact with an electronic device.

BRIEF SUMMARY

(3) The present disclosure describes techniques for interacting with an electronic device using an eye gaze. According to some embodiments, a user uses his or her eyes to interact with user interface objects displayed on the electronic device. The techniques provide a more natural and efficient interface by, in some exemplary embodiments, allowing a user to operate the device using primarily eye gazes and eye gestures (e.g., eye movement, blinks, and stares). Techniques are also described for using eye gaze to quickly designate an initial position (e.g., for selecting or placing an object) and then moving the designated position without using eye gaze, as precisely locating the designated position can be difficult using eye gaze due to uncertainty and instability of the position of a user's eye gaze. The techniques can be applied to conventional user interfaces on devices such as desktop computers, laptops, tablets, and smartphones. The techniques are also advantageous for computer-generated reality (including virtual reality and mixed reality) devices and applications, as described in greater detail below.

(4) According to some embodiments, an affordance associated with a first displayed object is displayed and a gaze direction or a gaze depth is determined. A determination is made whether the gaze direction or the gaze depth corresponds to a gaze at the affordance. A first input representing an instruction to take action on the affordance is received while the gaze direction or the gaze depth is determined to correspond to a gaze at the affordance, and the affordance is selected responsive to receiving the first input.

(5) According to some embodiments, a first affordance and a second affordance are concurrently displayed and a first gaze direction or a first gaze depth of one or more eyes is determined. A determination is made whether the first gaze direction or the first gaze depth corresponds to a gaze at both the first affordance and the second affordance. In response to determining that the first gaze direction or the first gaze depth corresponds to a gaze at both the first affordance and the second affordance, the first affordance and the second affordance are enlarged.

(6) According to some embodiments, an electronic device adapted to display a field of view of a three-dimensional computer generated reality environment and the field of view is rendered from a viewing perspective. A first object is displayed concurrently with a second object, where the first object is presented closer than the second object from the viewing position. A gaze position is determined. In accordance with a determination that the gaze position corresponds to a gaze at the first object, the display of the second object is visually altered. In accordance with a determination that the gaze position corresponds to a gaze at the second object, the display of the first object is visually altered.

(7) According to some embodiments, a first user input is received at a first time. In response to receiving the first user input, a selection point is designated at a first position corresponding to a gaze position at the first time. While maintaining designation of the selection point a second user input is received. In response to receiving the second user input, the selection point is moved to a second position different than the first position, where moving the selection point to the second position is not based on the gaze position. While the selection point is at the second position, a third user input is received. In response to receiving the third user input, the selection point is confirmed at the second position.

(8) According to some embodiments, a first user input is received at a first time. In response to receiving the first user input, a first object of a plurality of objects corresponding to a gaze position at the first time is designated. While maintaining designation of the first object, a second user input is received. In response to receiving the second user input, designation of the first object is ceased

and a second object of the plurality of objects is designated, where designating the second object is not based on the gaze position. While maintaining designation of the second object, a third user input is received. In response to receiving the third user input, the second object is selected.

(9) According to some embodiments, an object is selected. While maintaining selection of the object, a first user input is received at a first time. In response to receiving the first user input, a placement point is designated at a first position based on a gaze position at the first time, where the first position corresponds to the gaze position at the first time. While maintaining designation of the placement point, a second user input is received. In response to receiving the second user input, the placement point is moved to a second position different than the first position, where moving the placement point to the second position is not based on the gaze position. A third user input is received, and in response to receiving the third user input, the selected object is placed at the second position.

Description

DESCRIPTION OF THE FIGURES

- (1) For a better understanding of the various described embodiments, reference should be made to the Detailed Description below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.
- (2) FIGS. 1A and 1B depict exemplary systems for use in various computer-generated reality technologies, including virtual reality and mixed reality.
- (3) FIGS. 1C-1E illustrate embodiments of the system in the form of mobile devices.
- (4) FIGS. 1F-1H illustrate embodiments of the system in the form of head mounted display (HMD) devices.
- (5) FIG. 1I illustrates an embodiment of the system in the form of a head-up display (HUD) device.
- (6) FIG. 2 illustrates a user viewing an object, according to various embodiments.
- (7) FIG. 3 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (8) FIG. 4 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (9) FIG. 5 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (10) FIG. 6 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (11) FIG. 7 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (12) FIG. 8 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (13) FIG. 9 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (14) FIG. 10 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (15) FIG. 11 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (16) FIG. 12 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (17) FIG. 13 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.
- (18) FIG. 14 illustrates a user interface for interacting with an electronic device using an eye gaze,

according to various embodiments.

(19) FIG. 15 illustrates a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.

(20) FIG. 16 depicts a flow chart of an exemplary process for interacting with an electronic device using an eye gaze, according to various embodiments.

(21) FIG. 17 depicts a flow chart of an exemplary process for interacting with an electronic device using an eye gaze, according to various embodiments.

(22) FIG. 18 depicts a flow chart of an exemplary process for interacting with an electronic device using an eye gaze, according to various embodiments.

(23) FIGS. 19A-19Y illustrate a user interface for interacting with an electronic device using an eye gaze, according to various embodiments.

(24) FIG. 20 depicts a flow chart of an exemplary process for interacting with an electronic device using an eye gaze, according to various embodiments.

(25) FIG. 21 depicts a flow chart of an exemplary process for interacting with an electronic device using an eye gaze, according to various embodiments.

(26) FIG. 22 depicts a flow chart of an exemplary process for interacting with an electronic device using an eye gaze, according to various embodiments.

DETAILED DESCRIPTION

(27) The following description sets forth exemplary methods, parameters, and the like. It should be recognized, however, that such description is not intended as a limitation on the scope of the present disclosure but is instead provided as a description of exemplary embodiments.

(28) Various embodiments of electronic systems and techniques for using such systems in relation to various computer-generated reality technologies, including virtual reality and mixed reality (which incorporates sensory inputs from a physical environment), are described.

(29) A physical environment (or real environment) refers to a physical world that people can sense and/or interact with without aid of electronic systems. Physical environments, such as a physical park, include physical articles (or physical objects or real objects), such as physical trees, physical buildings, and physical people. People can directly sense and/or interact with the physical environment, such as through sight, touch, hearing, taste, and smell.

(30) In contrast, a computer-generated reality (CGR) environment refers to a wholly or partially simulated environment that people sense and/or interact with via an electronic system. In CGR, a subset of a person's physical motions, or representations thereof, are tracked, and, in response, one or more characteristics of one or more virtual objects simulated in the CGR environment are adjusted in a manner that comports with at least one law of physics. For example, a CGR system may detect a person's head turning and, in response, adjust graphical content and an acoustic field presented to the person in a manner similar to how such views and sounds would change in a physical environment. In some situations (e.g., for accessibility reasons), adjustments to characteristic(s) of virtual object(s) in a CGR environment may be made in response to representations of physical motions (e.g., vocal commands).

(31) A person may sense and/or interact with a CGR object using any one of their senses, including sight, sound, touch, taste, and smell. For example, a person may sense and/or interact with audio objects that create a 3D or spatial audio environment that provides the perception of point audio sources in 3D space. In another example, audio objects may enable audio transparency, which selectively incorporates ambient sounds from the physical environment with or without computer-generated audio. In some CGR environments, a person may sense and/or interact only with audio objects.

(32) Examples of CGR include virtual reality and mixed reality.

(33) A virtual reality (VR) environment (or virtual environment) refers to a simulated environment that is designed to be based entirely on computer-generated sensory inputs for one or more senses. A VR environment comprises a plurality of virtual objects with which a person may sense and/or

interact. For example, computer-generated imagery of trees, buildings, and avatars representing people are examples of virtual objects. A person may sense and/or interact with virtual objects in the VR environment through a simulation of the person's presence within the computer-generated environment, and/or through a simulation of a subset of the person's physical movements within the computer-generated environment.

(34) In contrast to a VR environment, which is designed to be based entirely on computer-generated sensory inputs, a mixed reality (MR) environment refers to a simulated environment that is designed to incorporate sensory inputs from the physical environment, or a representation thereof, in addition to including computer-generated sensory inputs (e.g., virtual objects). On a virtuality continuum, a mixed reality environment is anywhere between, but not including, a wholly physical environment at one end and virtual reality environment at the other end.

(35) In some MR environments, computer-generated sensory inputs may respond to changes in sensory inputs from the physical environment. Also, some electronic systems for presenting an MR environment may track location and/or orientation with respect to the physical environment to enable virtual objects to interact with real objects (that is, physical articles from the physical environment or representations thereof). For example, a system may account for movements so that a virtual tree appears stationary with respect to the physical ground.

(36) Examples of mixed realities include augmented reality and augmented virtuality.

(37) An augmented reality (AR) environment refers to a simulated environment in which one or more virtual objects are superimposed over a physical environment, or a representation thereof. For example, an electronic system for presenting an AR environment may have a transparent or translucent display through which a person may directly view the physical environment. The system may be configured to present virtual objects on the transparent or translucent display, so that a person, using the system, perceives the virtual objects superimposed over the physical environment. Alternatively, a system may have an opaque display and one or more imaging sensors that capture images or video of the physical environment, which are representations of the physical environment. The system composites the images or video with virtual objects, and presents the composition on the opaque display. A person, using the system, indirectly views the physical environment by way of the images or video of the physical environment, and perceives the virtual objects superimposed over the physical environment. As used herein, a video of the physical environment shown on an opaque display is called "pass-through video," meaning a system uses one or more image sensor(s) to capture images of the physical environment, and uses those images in presenting the AR environment on the opaque display. Further alternatively, a system may have a projection system that projects virtual objects into the physical environment, for example, as a hologram or on a physical surface, so that a person, using the system, perceives the virtual objects superimposed over the physical environment.

(38) An augmented reality environment also refers to a simulated environment in which a representation of a physical environment is transformed by computer-generated sensory information. For example, in providing pass-through video, a system may transform one or more sensor images to impose a select perspective (e.g., viewpoint) different than the perspective captured by the imaging sensors. As another example, a representation of a physical environment may be transformed by graphically modifying (e.g., enlarging) portions thereof, such that the modified portion may be representative but not photorealistic versions of the originally captured images. As a further example, a representation of a physical environment may be transformed by graphically eliminating or obfuscating portions thereof.

(39) An augmented virtuality (AV) environment refers to a simulated environment in which a virtual or computer generated environment incorporates one or more sensory inputs from the physical environment. The sensory inputs may be representations of one or more characteristics of the physical environment. For example, an AV park may have virtual trees and virtual buildings, but people with faces photorealistically reproduced from images taken of physical people. As

another example, a virtual object may adopt a shape or color of a physical article imaged by one or more imaging sensors. As a further example, a virtual object may adopt shadows consistent with the position of the sun in the physical environment.

(40) There are many different types of electronic systems that enable a person to sense and/or interact with various CGR environments. Examples include head mounted systems, projection-based systems, heads-up displays (HUDs), vehicle windshields having integrated display capability, windows having integrated display capability, displays formed as lenses designed to be placed on a person's eyes (e.g., similar to contact lenses), headphones/earphones, speaker arrays, input systems (e.g., wearable or handheld controllers with or without haptic feedback), smartphones, tablets, and desktop/laptop computers. A head mounted system may have one or more speaker(s) and an integrated opaque display. Alternatively, a head mounted system may be configured to accept an external opaque display (e.g., a smartphone). The head mounted system may incorporate one or more imaging sensors to capture images or video of the physical environment, and/or one or more microphones to capture audio of the physical environment. Rather than an opaque display, a head mounted system may have a transparent or translucent display. The transparent or translucent display may have a medium through which light representative of images is directed to a person's eyes. The display may utilize digital light projection, OLEDs, LEDs, uLEDs, liquid crystal on silicon, laser scanning light source, or any combination of these technologies. The medium may be an optical waveguide, a hologram medium, an optical combiner, an optical reflector, or any combination thereof. In one embodiment, the transparent or translucent display may be configured to become opaque selectively. Projection-based systems may employ retinal projection technology that projects graphical images onto a person's retina. Projection systems also may be configured to project virtual objects into the physical environment, for example, as a hologram or on a physical surface.

(41) FIGS. 1A and 1B depict exemplary system **100** for use in various computer-generated reality technologies, including virtual reality and mixed reality.

(42) In some embodiments, as illustrated in FIG. 1A, system **100** includes device **100a**. Device **100a** includes various components, such as processor(s) **102**, RF circuitry(ies) **104**, memory(ies) **106**, image sensor(s) **108**, orientation sensor(s) **110**, microphone(s) **112**, location sensor(s) **116**, speaker(s) **118**, display(s) **120**, and touch-sensitive surface(s) **122**. These components optionally communicate over communication bus(es) **150** of device **100a**.

(43) In some embodiments, elements of system **100** are implemented in a base station device (e.g., a computing device, such as a remote server, mobile device, or laptop) and other elements of the system **100** are implemented in a head-mounted display (HMD) device designed to be worn by the user, where the HMD device is in communication with the base station device. In some embodiments, device **100a** is implemented in a base station device or a HMD device.

(44) As illustrated in FIG. 1B, in some embodiments, system **100** includes two (or more) devices in communication, such as through a wired connection or a wireless connection. First device **100b** (e.g., a base station device) includes processor(s) **102**, RF circuitry(ies) **104**, and memory(ies) **106**. These components optionally communicate over communication bus(es) **150** of device **100b**. Second device **100c** (e.g., a head-mounted device) includes various components, such as processor(s) **102**, RF circuitry(ies) **104**, memory(ies) **106**, image sensor(s) **108**, orientation sensor(s) **110**, microphone(s) **112**, location sensor(s) **116**, speaker(s) **118**, display(s) **120**, and touch-sensitive surface(s) **122**. These components optionally communicate over communication bus(es) **150** of device **100c**.

(45) In some embodiments, system **100** is a mobile device, such as in the embodiments described with respect to device **100a** in FIGS. 1C-1E. In some embodiments, system **100** is a head-mounted display (HMD) device, such as in the embodiments described with respect to device **100a** in FIGS. 1F-1H. In some embodiments, system **100** is a wearable HUD device, such as in the embodiments described with respect to device **100a** in FIG. H.

(46) System **100** includes processor(s) **102** and memory(ies) **106**. Processor(s) **102** include one or more general processors, one or more graphics processors, and/or one or more digital signal processors. In some embodiments, memory(ies) **106** are one or more non-transitory computer-readable storage mediums (e.g., flash memory, random access memory) that store computer-readable instructions configured to be executed by processor(s) **102** to perform the techniques described below.

(47) System **100** includes RF circuitry(ies) **104**. RF circuitry(ies) **104** optionally include circuitry for communicating with electronic devices, networks, such as the Internet, intranets, and/or a wireless network, such as cellular networks and wireless local area networks (LANs). RF circuitry(ies) **104** optionally includes circuitry for communicating using near-field communication and/or short-range communication, such as Bluetooth®.

(48) System **100** includes display(s) **120**. In some embodiments, display(s) **120** include a first display (e.g., a left eye display panel) and a second display (e.g., a right eye display panel), each display for displaying images to a respective eye of the user. Corresponding images are simultaneously displayed on the first display and the second display. Optionally, the corresponding images include the same virtual objects and/or representations of the same physical objects from different viewpoints, resulting in a parallax effect that provides a user with the illusion of depth of the objects on the displays. In some embodiments, display(s) **120** include a single display. Corresponding images are simultaneously displayed on a first area and a second area of the single display for each eye of the user. Optionally, the corresponding images include the same virtual objects and/or representations of the same physical objects from different viewpoints, resulting in a parallax effect that provides a user with the illusion of depth of the objects on the single display.

(49) In some embodiments, system **100** includes touch-sensitive surface(s) **122** for receiving user inputs, such as tap inputs and swipe inputs. In some embodiments, display(s) **120** and touch-sensitive surface(s) **122** form touch-sensitive display(s).

(50) System **100** includes image sensor(s) **108**. Image sensor(s) **108** optionally include one or more visible light image sensor, such as charged coupled device (CCD) sensors, and/or complementary metal-oxide-semiconductor (CMOS) sensors operable to obtain images of physical objects from the real environment. Image sensor(s) also optionally include one or more infrared (IR) sensor(s), such as a passive IR sensor or an active IR sensor, for detecting infrared light from the real environment. For example, an active IR sensor includes an IR emitter, such as an IR dot emitter, for emitting infrared light into the real environment. Image sensor(s) **108** also optionally include one or more event camera(s) configured to capture movement of physical objects in the real environment. Image sensor(s) **108** also optionally include one or more depth sensor(s) configured to detect the distance of physical objects from system **100**. In some embodiments, system **100** uses CCD sensors, event cameras, and depth sensors in combination to detect the physical environment around system **100**. In some embodiments, image sensor(s) **108** include a first image sensor and a second image sensor. The first image sensor and the second image sensor are optionally configured to capture images of physical objects in the real environment from two distinct perspectives. In some embodiments, system **100** uses image sensor(s) **108** to receive user inputs, such as hand gestures. In some embodiments, system **100** uses image sensor(s) **108** to detect the position and orientation of system **100** and/or display(s) **120** in the real environment. For example, system **100** uses image sensor(s) **108** to track the position and orientation of display(s) **120** relative to one or more fixed objects in the real environment.

(51) In some embodiments, system **100** includes microphones(s) **112**. System **100** uses microphone(s) **112** to detect sound from the user and/or the real environment of the user. In some embodiments, microphone(s) **112** includes an array of microphones (including a plurality of microphones) that optionally operate in tandem, such as to identify ambient noise or to locate the source of sound in space of the real environment.

(52) System **100** includes orientation sensor(s) **110** for detecting orientation and/or movement of

system **100** and/or display(s) **120**. For example, system **100** uses orientation sensor(s) **110** to track changes in the position and/or orientation of system **100** and/or display(s) **120**, such as with respect to physical objects in the real environment. Orientation sensor(s) **110** optionally include one or more gyroscopes and/or one or more accelerometers.

(53) FIGS. **1C-1E** illustrate embodiments of system **100** in the form of device **100a**. In FIGS. **1C-1E**, device **100a** is a mobile device, such as a cellular phone. FIG. **1C** illustrates device **100a** carrying out a virtual reality technique. Device **100a** is displaying, on display **120**, a virtual environment **160** that includes virtual objects, such as sun **160a**, birds **160b**, and beach **160c**. Both the displayed virtual environment **160** and virtual objects (e.g., **160a**, **160b**, **160c**) of the virtual environment **160** are computer-generated imagery. Note that the virtual reality environment depicted in FIG. **1C** does not include representations of physical objects from the real environment **180**, such as physical person **180a** and physical tree **180b**, even though these elements of real environment **180** are within the field of view of image sensor(s) **108** of device **100a**.

(54) FIG. **1D** illustrates device **100a** carrying out a mixed reality technique, and in particular an augmented reality technique, using pass-through video. Device **100a** is displaying, on display **120**, a representation **170** of the real environment **180** with virtual objects. The representation **170** of the real environment **180** includes representation **170a** of person **180a** and representation **170b** of tree **180b**. For example, the device uses image sensor(s) **108** to capture images of the real environment **180** that are passed through for display on display **120**. Device **100a** overlays hat **160d**, which is a virtual object generated by device **100a**, on the head of the representation **170a** of person **180a**. Device **100a** tracks the location and/or orientation of physical objects with respect to the position and/or orientation of device **100a** to enable virtual objects to interact with physical objects from the real environment in the augmented reality environment. In this embodiment, device **100a** accounts for movements of device **100a** and person **180a** to display hat **160d** as being on the head of the representation **170a** of person **180a**, even as device **100a** and person **180a** move relative to one another.

(55) FIG. **1E** illustrates device **100a** carrying out a mixed reality technique, and in particular an augmented virtuality technique. Device **100a** is displaying, on display **120**, a virtual environment **160** with representations of physical objects. The virtual environment **160** includes virtual objects (e.g., sun **160a**, birds **160b**) and representation **170a** of person **180a**. For example, device **100a** uses image sensor(s) **108** to capture images of person **180a** in real environment **180**. Device **100a** places representation **170a** of person **180a** in virtual environment **160** for display on display **120**. Device **100a** optionally tracks the location and/or orientation of physical objects with respect to the position and/or orientation of device **100a** to enable virtual objects to interact with physical objects from real environment **180**. In this embodiment, device **100a** accounts for movements of device **100a** and person **180a** to display hat **160d** as being on the head of representation **170a** of person **180a**. Notably, in this embodiment, device **100a** does not display a representation of tree **180b** even though tree **180b** is also within the field of view of the image sensor(s) of device **100a**, in carrying out the mixed reality technique.

(56) FIGS. **1F-1H** illustrate embodiments of system **100** in the form of device **100a**. In FIGS. **1F-1H**, device **100a** is a HMD device configured to be worn on the head of a user, with each eye of the user viewing a respective display **120a** and **120b**. FIG. **1F** illustrates device **100a** carrying out a virtual reality technique. Device **100a** is displaying, on displays **120a** and **120b**, a virtual environment **160** that includes virtual objects, such as sun **160a**, birds **160b**, and beach **160c**. The displayed virtual environment **160** and virtual objects (e.g., **160a**, **160b**, **160c**) are computer-generated imagery. In this embodiment, device **100a** simultaneously displays corresponding images on display **120a** and display **120b**. The corresponding images include the same virtual environment **160** and virtual objects (e.g., **160a**, **160b**, **160c**) from different viewpoints, resulting in a parallax effect that provides a user with the illusion of depth of the objects on the displays. Note that the virtual reality environment depicted in FIG. **1F** does not include representations of physical objects

from the real environment, such as person **180a** and tree **180b** even though person **180a** and tree **180b** are within the field of view of the image sensor(s) of device **100a**, in carrying out the virtual reality technique.

(57) FIG. 1G illustrates device **100a** carrying out an augmented reality technique using pass-through video. Device **100a** is displaying, on displays **120a** and **120b**, a representation **170** of real environment **180** with virtual objects. The representation **170** of real environment **180** includes representation **170a** of person **180a** and representation **170b** of tree **180b**. For example, device **100a** uses image sensor(s) **108** to capture images of the real environment **180** that are passed through for display on displays **120a** and **120b**. Device **100a** is overlaying a computer-generated hat **160d** (a virtual object) on the head of representation **170a** of person **180a** for display on each of displays **120a** and **120b**. Device **100a** tracks the location and/or orientation of physical objects with respect to the position and/or orientation of device **100a** to enable virtual objects to interact with physical objects from real environment **180**. In this embodiment, device **100a** accounts for movements of device **100a** and person **180a** to display hat **160d** as being on the head of representation **170a** of person **180a**.

(58) FIG. 1H illustrates device **100a** carrying out a mixed reality technique, and in particular an augmented virtuality technique, using pass-through video. Device **100a** is displaying, on displays **120a** and **120b**, a virtual environment **160** with representations of physical objects. The virtual environment **160** includes virtual objects (e.g., sun **160a**, birds **160b**) and representation **170a** of person **180a**. For example, device **100a** uses image sensor(s) **108** to capture images of person **180a**. Device **100a** places the representation **170a** of the person **180a** in the virtual environment for display on displays **120a** and **120b**. Device **100a** optionally tracks the location and/or orientation of physical objects with respect to the position and/or orientation of device **100a** to enable virtual objects to interact with physical objects from real environment **180**. In this embodiment, device **100a** accounts for movements of device **100a** and person **180a** to display hat **160d** as being on the head of the representation **170a** of person **180a**. Notably, in this embodiment, device **100a** does not display a representation of tree **180b** even though tree **180b** is also within the field of view of the image sensor(s) **108** of device **100a**, in carrying out the mixed reality technique.

(59) FIG. 1I illustrates an embodiment of system **100** in the form of device **100a**. In FIG. 1I, device **100a** is a HUD device (e.g., a glasses device) configured to be worn on the head of a user, with each eye of the user viewing a respective heads-up display **120c** and **120d**. FIG. 1I illustrates device **100a** carrying out an augmented reality technique using heads-up displays **120c** and **120d**. The heads-up displays **120c** and **120d** are (at least partially) transparent displays, thus allowing the user to view the real environment **180** in combination with heads-up displays **120c** and **120d**. Device **100a** is displaying, on each of heads-up displays **120c** and **120d**, a virtual hat **160d** (a virtual object). The device **100a** tracks the location and/or orientation of physical objects in the real environment with respect to the position and/or orientation of device **100a** and with respect to the position of the user's eyes to enable virtual objects to interact with physical objects from real environment **180**. In this embodiment, device **100a** accounts for movements of device **100a**, movements of the user's eyes with respect to device **100a**, and movements of person **180a** to display hat **160d** at locations on displays **120c** and **120d** such that it appears to the user that the hat **160d** is on the head of person **180a**.

(60) With reference now to FIGS. 2-15, exemplary techniques for interacting with an electronic device using an eye gaze are described.

(61) FIG. 2 depicts a top view of user **200** whose gaze is focused on object **210**. The user's gaze is defined by the visual axes of each of the user's eyes. The direction of the visual axes define the user's gaze direction, and the distance at which the axes converge defines the gaze depth. The gaze direction can also be referred to as the gaze vector or line-of-sight. In FIG. 2, the gaze direction is in the direction of object **210** and the gaze depth is the distance **D** relative to the user.

(62) In some embodiments, the center of the user's cornea, the center of the user's pupil, and/or the

center of rotation of the user's eyeball are determined to determine the position of the visual axis of the user's eye, and can therefore be used to determine the user's gaze direction and/or gaze depth. In some embodiments, gaze depth is determined based on a point of convergence of the visual axes of the user's eyes (or a location of minimum distance between the visual axes of the user's eyes) or some other measurement of the focus of a user's eye(s). Optionally, the gaze depth is used to estimate the distance at which the user's eyes are focused.

(63) In FIG. 2, rays **201A** and **201B** are cast along the visual axes of the left and right eyes of user **200**, respectively, and are optionally used to determine the user's gaze direction and/or gaze depth in what is referred to as ray casting. FIG. 2 also depicts cones **202A** and **202B** having angular extents **203A** and **203B**, respectively. Cones **202A** and **202B** are also cast along the visual axes of the left and right eyes of user **200**, respectively, and are optionally used to determine the user's gaze direction and/or gaze depth in what is referred to as cone casting. Gaze direction and gaze depth often cannot be determined with absolute accuracy or precision due to factors such as eye motion, sensor motion, sampling frequency, sensor latency, sensor resolution, sensor misalignment, etc. Accordingly, in some embodiments, an angular resolution or (estimated) angular error is associated with gaze direction. In some embodiments, a depth resolution is associated with gaze depth. Optionally, the angular extent of the cone(s) (e.g., angular extents **203A** and **203B** of cones **202A** and **202B**, respectively) represents the angular resolution of the user's gaze direction.

(64) FIG. 3 depicts electronic device **300** with display **302**. Electronic device **300** displays virtual environment **304**, which includes virtual object **306**. In some embodiments, environment **304** is a CGR environment (e.g., a VR or MR environment). In the illustrated embodiment, object **306** is an affordance with which user **200** can interact using a gaze. In some embodiments, affordance **306** is associated with a physical object (e.g., an appliance or other device that can be controlled via interaction with affordance **306**). FIG. 3 also depicts a view from above user **200** that shows the gaze direction of user **200**. The visual axes of each of the user's eyes are extrapolated onto a plane of the displayed representation of virtual environment **304**, which corresponds to the plane of display **302** of device **300**. Spot **308** represents the gaze direction of user **200** on display **302**.

(65) As shown in FIG. 3, the gaze direction of user **200** corresponds to the direction of affordance **306**. The term “affordance” refers to a graphical user interface object with which a user can interact. Examples of affordances include user-interactive images (e.g., icons), buttons, and text (e.g., hyperlinks). Electronic device **300** is configured to determine the gaze direction of user **200**. Device **300** captures data from a sensor directed toward the user and determines the gaze direction based on the data captured from the sensor. In some embodiments in which a three-dimensional representation of a scene is presented, such as the embodiment described below with respect to FIGS. 9-12, device **300** also (or alternatively) determines a gaze depth and whether the gaze depth corresponds to affordance **306**. Optionally, determining whether the gaze depth corresponds to the depth of the affordance is based at least in part on the depth resolution of the gaze depth.

(66) In the illustrated embodiment, device **300** includes image sensor **310**, which is directed toward user **200** and captures image data of the eyes of user **200**. In some embodiments, device **300** includes an event camera that detects event data from a user (e.g., the user's eyes) based on changes in detected light intensity over time and uses the event data to determine gaze direction and/or gaze depth. Optionally, device **300** uses both image data and event data (e.g., from an image sensor and a separate event camera or a sensor configured to capture image data and event data) to determine gaze direction and/or gaze depth. Optionally, device **300** uses ray casting and/or cone casting to determine the gaze direction and/or gaze depth.

(67) Based on the gaze direction, device **300** determines that the gaze direction corresponds to affordance **306**, since the gaze direction is in the same direction as affordance **306** (e.g., rays or cones cast from the eyes of user **200** at least partially intersect affordance **306** or are within a margin of error of affordance **306**). Optionally, determining that the gaze direction corresponds to affordance **306** is based at least in part on an angular resolution of the gaze direction. In some

embodiments in which a three-dimensional representation of a scene is presented, device **300** also (or alternatively) determines whether the gaze depth corresponds to a depth of affordance **306**. Optionally, determining whether the gaze depth corresponds to the depth of the affordance is based at least in part on a depth resolution of the gaze depth. Optionally, affordance **306** is also located at the gaze depth (or within a depth range that is based on the depth resolution of the gaze depth).

(68) In some embodiments, a gaze direction and/or gaze depth is determined to continue to correspond to a gaze at an affordance even after the gaze direction and/or gaze depth no longer overlaps with the affordance (e.g., once the gaze direction and/or gaze depth is initially determined to correspond to a gaze at the affordance, the gaze direction and/or gaze depth is considered to correspond to a gaze at the affordance for at least a predetermined amount of time or for a predetermined amount of time after the user looks away from the affordance).

(69) While the gaze direction is determined to correspond to a gaze at affordance **306**, device **300** receives an input (referred to as a “confirming action”) that represents an instruction to take action on the affordance corresponding to the first object. For example, the confirming action is received while user **200** is determined to be looking at affordance **306**.

(70) In response to receiving the confirming action, device **300** selects affordance **306**. That is, affordance **306** is selected in response to the combination of the user looking at affordance **306** and providing a confirming action. The confirming action is beneficial for preventing false positives (e.g., incorrect determinations by device **300** that user **200** desires to select or act upon affordance **306**). Non-limiting examples of a confirming action include an eye gesture, a body gesture, a voice input, a controller input, or a combination thereof.

(71) Examples of an eye gesture include a single blink, multiple blinks, a predetermined number of blinks, a predetermined number of blinks within a predetermined amount of time, a blink of a predetermined duration (e.g., eyes closed for one second), a blink pattern (e.g., one slow blink followed by two rapid blinks), a wink, a wink with a particular eye, a wink pattern (e.g., left, right, left, each with a specified duration), an predetermined eye motion (e.g., a quick look up), a “long” look or dwell (e.g., continuously maintaining the gaze direction in the direction of affordance **306** (or in a direction corresponding to affordance **306**) for a predetermined amount of time), or an eye motion that meets some other predetermined criteria.

(72) Examples of a hand gesture include placement of a hand at a location corresponding to the location of affordance **306** (e.g., between the user and the display of affordance **306**), a wave, a pointing motion (e.g., at affordance **306**), or a gesture with a predefined motion pattern. In some embodiments, the hand gesture confirming action depends on the location of the hand gesture (e.g., the hand gesture must be at a particular location). In some embodiments, the hand gesture confirming action does not depend on the location of the hand gesture (e.g., the hand gesture is location-independent).

(73) Example of a voice input include a voice command (e.g., “pick that up” or “turn on the light”). In some embodiments, the voice input explicitly identifies the object associated with affordance **306** (e.g., “select the box”). In some embodiments, the voice input does not explicitly identify the object associated with the affordance and instead refers to the object using a pronoun that is otherwise ambiguous (e.g., “grab that”).

(74) With respect to a controller input, in some embodiments, device **300** is in communication with a controller that is configured to receive inputs via, for example, a button, trigger, joystick, scroll wheel, knob, keyboard, or touch-sensitive surface (e.g., a touchpad or touch-sensitive display). In some embodiments, the controller and device **300** are connected wirelessly or via a wired connection. Examples of a controller input include a press of a button, a pull of a trigger, a movement of a joystick, a rotation of a scroll wheel, a rotation of a knob, a press of a button on a keyboard, or a contact or gesture (e.g., tap or swipe) on a touch-sensitive surface.

(75) In some embodiments, selecting affordance **306** includes applying focus on affordance **306**. Optionally, device **300** provides an indication that affordance **306** has been selected. In some

embodiments, the indication includes an audio output (e.g., a beep), a visual indication (e.g., outlining or highlighting the selected affordance), or haptic output. Optionally, affordance **306** remains selected for a predetermined amount of time (e.g., focus is maintained on affordance **306** for the predetermined amount of time). Optionally, affordance **306** remains selected until a deselection input is received. In some embodiments, the deselection input is the same input as the confirming action. In some embodiments, the deselection input is a different input than the confirming action. In some embodiments, the deselection input includes an eye gesture, a body gesture, a voice input, a controller input, or a combination or portion thereof, such as the exemplary inputs described above.

(76) In some embodiments, affordance **306** remains selected until an action associated with affordance **306** (or the object with which it is associated) is performed. FIG. 4 illustrates an exemplary action performed on affordance **306**. While affordance **306** is selected, device **300** receives an input (e.g., an eye gesture, a body gesture, a voice input, a controller input, or a combination or portion thereof, such as the exemplary inputs described above). In the illustrated example, the input includes user **200** changing the position of his eyes such that his gaze direction moves on display **302** from location **308** to location **400** shown in FIG. 4. In response to receiving the input, device **300** performs an action associated with affordance **306** in accordance with the input. In some embodiments, an action associated with affordance **306** is performed in response to the input that causes device **300** to select affordance **306** (e.g., selecting affordance **306** includes performing the action associated with affordance **306**). In the example illustrated in FIG. 4, device **300** moves affordance **306** in accordance with the change in the gaze direction of user **200**, translating affordance **306** upward and to the left on display **302** from the location of affordance **306** shown in FIG. 3 to the location shown in FIG. 4.

(77) In addition to moving an affordance, exemplary actions include transforming the affordance or a representation of an object associated with the affordance (e.g., rotating, twisting, stretching, compressing, enlarging, and/or shrinking affordance **306**) and changing the state of a device associated with the affordance (e.g., turning a lamp on or off). For example, in some embodiments, the affordance is a virtual dial associated with a thermostat. A user can select the virtual dial and then adjust the temperature of the thermostat. In some embodiments, some aspect of the position of an affordance (or object associated therewith) is automatically determined when an object is moved. For example, if a virtual picture frame that is initially lying flat on a horizontal surface is moved to a wall, the frame is automatically rotated to a vertical orientation to lay flat against the wall.

(78) Turning now to FIG. 5, techniques related to resolving and selecting closely spaced objects are described. FIG. 5 depicts virtual environment **500** displayed on device **300**. In some embodiments, environment **500** is a CGR environment (e.g., a VR or MR environment). Virtual environment **500** includes affordance **502** and affordance **504**, each associated with a respective box on top of virtual table **506** and displayed concurrently on display **302**. The dashed circle represents gaze direction **508** of user **200** determined by device **300**. The radius of the circle represents the angular uncertainty of gaze direction **508**. As illustrated in FIG. 5, gaze direction **508** overlaps both affordance **502** and affordance **504**, indicating that user **200** is interested in one of the affordances. Although gaze direction **508** is directed slightly more toward affordance **502**, the angular uncertainty of gaze direction **508** is greater than the angular separation between affordance **502** and affordance **504**, which prevents device **300** from determining with a sufficiently high level of confidence that gaze direction **508** corresponds to a specific one of affordance **502** and affordance **504**. In other words, device **300** cannot resolve with sufficient confidence which affordance user **200** desires to select. Instead, device **300** determines that gaze direction **508** corresponds to both affordance **502** and affordance **504**. In some embodiments in which a three-dimensional representation of a scene is presented, a depth separation between the affordances may be less than the angular resolution or depth resolution of the gaze position.

(79) In response to determining that gaze direction **508** corresponds to both affordance **502** and affordance **504**, device **300** enlarges affordance **502** and affordance **504**. FIG. 6 illustrates affordance **502** and affordance **504** after being enlarged (e.g., zoomed in). Affordance **502** and affordance **504** appear as though they have been moved from the top of table **506** and positioned closer to user **200**. In FIG. 6, affordance **502** and affordance **504** are enlarged by the same amount such that their relative size and position remain the same (e.g., affordance **502** continues to appear to be in front of affordance **504**). Zooming in affordance **502** and affordance **504** increases the angular extent of affordance **502** and affordance **504** and increases the angular separation between affordance **502** and affordance **504**. Optionally, the amount of zooming is based on the size of the affordances and/or the resolution of the gaze direction (e.g., affordance **502** and affordance **504** are enlarged such that affordance **504** is a predetermined minimum size). In some embodiments, affordance **502** and affordance **504** are zoomed so that device **300** can resolve (with a predetermined level of confidence) which affordance user **200** is attempting to focus on.

(80) In some embodiments, affordance **502** and affordance **504** are enlarged in accordance with a determination that the gaze of user **200** meets predefined criteria (e.g., gaze direction **508** corresponds to both affordance **502** and affordance **504** continuously for a predetermined amount of time or for a predetermined amount of time within a predefined window of time (e.g., 3 seconds during a 4 second window)). In some embodiments, affordance **502** and affordance **504** are enlarged in response to device **300** receiving an input (e.g., an eye gesture, a hand gesture, a voice input, or a controller input as described above) while gaze direction **508** corresponds to both affordance **502** and affordance **504**. In this way, user **200** can have improved control over when device zooms content. Also, in this way, device **300** can reduce or limit the instances in which it invokes zooming functionality to resolve gaze ambiguities to instances where resolution is necessary, thereby reducing strain on the user and improving the user's experience. Optionally, the affordances corresponding to the gaze direction are enlarged in accordance with the input (e.g., a long and/or hard button press results in more enlarging than a short and/or soft button press). In some embodiments, the affordances are enlarged in accordance with a voice command (e.g., "zoom in 40%"). This allows user **200** to have increased control over the zooming.

(81) Enlarging affordance **502** and affordance **504** provides user **200** with an improved view of the affordances and allows user **200** to more easily and confidently select one of the affordances. For example, as shown in FIG. 6, after affordance **502** and affordance **504** are enlarged, user **200** decides that he wants to select affordance **502** and moves his line of sight to gaze direction **510** on affordance **502**. Notably, gaze direction **510** no longer overlaps with affordance **504**. Accordingly, device **300** determines (e.g., with a relatively high degree of confidence) that gaze direction **510** corresponds to the direction of affordance **502** (and does not correspond to the direction of affordance **504**). While gaze direction **510** is determined to correspond to the direction of enlarged affordance **502**, user **200** selects affordance **502** with a confirming action, such as one of the confirming actions discussed above. Optionally, device **300** performs an action associated with affordance **502** responsive to, and in accordance with, the confirming input by user **200** for selecting enlarged affordance **502** and/or in response to a further input while affordance **502** is selected. In response to the confirming input by user **200** for selecting enlarged affordance **502**, device **300** optionally reduces (e.g., zooms out) affordance **502** and affordance **504** back to a previous state (e.g., the sizes and positions prior to being enlarge, depicted in FIG. 5). In some embodiments, affordance **502** remains selected after being reduced to the previous state.

(82) In the embodiment described above with respect to FIGS. 5-6, device **300** enlarges only affordances **502** and **504**. In some embodiments, device **300** displays an enlarged view of at least a portion of an environment that surrounds affordance **502** and affordance **504** in addition to enlarging affordance **502** and affordance **504**. FIG. 7 depicts an exemplary embodiment in which device **300** determines a portion of virtual environment **500** that surrounds and includes the affordances corresponding to gaze direction **508**. The portion is designated by rectangle **700** and

includes, for example, a portion of table **506** in addition to affordances **502** and **504**. As shown in FIG. **8**, in response to determining that gaze direction **508** corresponds to both affordance **502** and affordance **504**, device **300** enlarges the portion of virtual environment **500** designated by rectangle **700**, including affordance **502** and affordance **504**. Although a portion of virtual environment **500** is enlarged along with in affordances **502** and **504**, the affordances can still be selected and acted upon as described above with respect to FIGS. **5-6**. Furthermore, although the embodiments described above refer to a virtual environment, similar techniques can be applied to other CGR environments, including mixed reality environments. For example, in some embodiments, a device includes a transparent display that displays affordances **502** and **504** overlaid on a user's live view of a physical environment. The device also includes a user sensor for capturing user eye data and a scene sensor for capturing images of the physical environment over which affordances **502** and **504** are displayed. In response to determining that a user's gaze direction corresponds to affordances **502** and **504**, the exemplary device captures data of at least the physical environment surrounding affordances **502** and **504** and displays an enlarged representation (e.g., image) of the physical environment surrounding affordances **502** and **504**.

(83) In the embodiments described above, affordances **502** and **504** are displayed in a two-dimensional representation of a virtual environment. In some embodiments, affordances are displayed in a three-dimensional (3D) representation of an environment on, for example, virtual reality HMD **100a** depicted in FIGS. **1F-1H**. FIG. **9** illustrates a 3D representation of virtual environment **902** displayed on HMD **900**. In some embodiments, environment **902** is a CGR environment (e.g., a VR or MR environment). Virtual environment **902** includes affordance **904** and affordance **906**. Affordance **904** has a first depth and affordance **906** has a second depth that is greater than the first depth of affordance **904**. Since virtual environment **902** is a 3D representation, device **900** determines a gaze position, which in the illustrated embodiment includes a gaze direction and a gaze depth, based on data captured from the eyes of the user. In some embodiments, determining a gaze position includes determining a gaze direction, but not necessarily a gaze depth. In some embodiment, determining a gaze position includes determining a gaze depth, but not necessarily a gaze direction.

(84) In FIG. **9**, the radius of the cylinder surrounding gaze position **908** represents the angular resolution of the gaze direction, and the length of the cylinder represents the depth resolution of the gaze depth (e.g., the uncertainty in the gaze depth). Based on the gaze direction, angular resolution, gaze depth, and depth resolution, device **900** determines whether the position of affordance **904** and/or affordance **906** correspond to the gaze position. In some embodiments, device **900** determines whether position of affordance **904** and/or affordance **906** correspond to the gaze position based on the gaze direction (and optionally the angular resolution) regardless of the gaze depth, or based on the gaze depth (and optionally the depth resolution) regardless of the gaze direction.

(85) In some embodiments, device **900** enhances the display of the more distant affordance (e.g., affordance **906**) in response to determining that the gaze position corresponds to both affordance **904** and affordance **906**. According to the embodiment depicted in FIG. **10**, affordance **906** is enhanced by making affordance **906** brighter relative to affordance **904** (e.g., by increasing the brightness of affordance **906**, decreasing the brightness of affordance **904**, or a combination of both). In some embodiments, enhancing an affordance includes altering the visual appearance of the affordance itself (e.g., by making the affordance brighter or changing the color of the affordance). In some embodiments, enhancing an affordance includes degrading the visual appearance of other aspects of an environment (e.g., by making another affordance or the surrounding environment appear blurry). Similarly, in a 2D representation of a 3D environment, a smaller object or an object that has a greater depth value in the 3D environment is optionally enhanced.

(86) In some embodiments, in response to device **900** determining that gaze position **908**

corresponds to both affordance **904** and affordance **906** (e.g., that device **900** cannot resolve which affordance the user is looking at), device **900** enlarges affordance **904** and affordance **906**. In some embodiments that provide a 3D representation, an affordance is enlarged from the perspective of the user by moving the affordance toward the user and displaying the affordance at a depth that appears closer to the user. FIG. **11** depicts an embodiment similar to the embodiment depicted in FIG. **6**, in which affordance **904** and affordance **906** are enlarged (e.g., moved closer to the user) while maintaining their relative size and position. FIG. **12** depicts an embodiment in which affordance **904** and affordance **906** are enlarged and re-positioned relative to each other such that affordance **904** and affordance **906** are displayed side by side at the same depth. It should be recognized that an analogous technique can also be applied to a 2D representation of an environment. For example, when gaze direction **508** is determined to correspond to a gaze at both affordance **502** and affordance **504** as described above with respect to FIG. **5**, affordance **502** and affordance **504** are optionally enlarged by different amounts relative to each other, and/or re-positioned relative to each other such that affordance **502** and affordance **504** are displayed side-by-side. Furthermore, when affordance **904** and affordance **906** are enlarged, device **900** can further determine whether an updated gaze position corresponds to one of the enlarged affordances and select and/or perform an action on an affordance in a manner analogous to the techniques described previously with respect to FIGS. **3-4** and **6-8**.

(87) Turning now to FIG. **13**, techniques for altering the display of objects based on object depth are described. FIG. **13** again depicts device **300**. Device **300** displays environment **1300** (e.g., a CGR environment) with object **1302** and object **1304** concurrently displayed. As depicted in FIG. **13**, object **1302** appears closer (e.g., has a smaller depth value) than object **1304**. Also, from the perspective displayed in FIG. **13**, object **1302** partially obstructs the view of object **1304**. Gaze position **1306** is located on object **1302**. Gaze position **1306** optionally includes either gaze direction or gaze depth, or both. Device **300** optionally determines whether gaze position corresponds to object **1302** and/or object **1304** based on either gaze direction or gaze depth, or both, according to any of the techniques described above.

(88) Device **300** visually alters object **1302** and/or object **1304** based on whether gaze position **1306** corresponds to object **1302** or object **1304**. Device **300** determines whether gaze position **1306** corresponds to object **1302** or object **1304** according to any of the techniques described above. In some embodiments, in response to determining that gaze position **1306** corresponds to object **1302**, device **300** visually alters the display of object **1304**; and in response to determining that gaze position **1306** corresponds to object **1304**, device **300** visually alters the display of object **1302**. For example, if the user's focus, as determined by either direction or depth, or both, is determined to be on one of the objects, the visual appearance of the other object is altered in order to emphasize the object of the user's focus. As depicted in FIG. **14**, device **300** determines that gaze position **1306** corresponds to object **1302**, and in response, visually alters object **1304** in a way that emphasizes object **1302** and/or de-emphasizes object **1304**. Examples of visually altering an object that de-emphasizes the object include making the object appear blurry or fuzzy, decreasing the resolution of the object, decreasing the brightness of the object, decreasing the contrast of the object, increasing the transparency of the object, and ceasing to display the object. In some embodiments, device **300** visually alters object **1302** or object **1304** in response to receiving an input (e.g., an eye gesture, a hand gesture, a voice input, or a controller input) and determining that gaze position **1306** corresponds to object **1302** or object **1304**, respectively. Optionally, device **300** alters object **1302** and object **1304** in accordance with a determination that the directions of both objects correspond to the gaze direction, indicating that one of the objects is likely obstructing the other and that distinguishing the objects would be advantageous.

(89) Optionally, device **300** also visually alters the display of the object corresponding to the gaze position (e.g., object **1302**) to enhance the appearance of the object. Examples of visually enhancing an object include making the object appear sharper, increasing the resolution of the

object, increasing the brightness of the object, increasing the contrast of the object, decreasing the transparency of the object, highlighting the object, and causing the object to appear.

(90) In FIG. 15, the user has moved his gaze position from gaze position **1306** to location **1500** corresponding to object **1304**. In response, device **300** visually alters object **1302** and returns object **1304** to the appearance initially displayed in FIG. 13. In the embodiment illustrated in FIG. 15, device **300** makes object **1302** semi-transparent so that the user can better see the object on which he is attempting to focus. Optionally, device **300** removes object **1302** to provide an unobstructed view of object **1304**.

(91) It should be recognized that the embodiments discussed above with respect to FIGS. 2-15 are exemplary and are not intended to be limiting. For example, although the embodiments in FIGS. 2-12 are described with respect to a virtual environment, the techniques can be applied analogously to other CGR environments, including mixed reality environments.

(92) Turning now to FIG. 16, a flow chart of exemplary process **1600** for interacting with an electronic device using an eye gaze is depicted. Process **1600** can be performed using a user device (e.g., **100a**, **300**, or **900**). The user device is, for example, a handheld mobile device, a head-mounted device, or a head-up device. In some embodiments, process **1600** is performed using two or more electronic devices, such as a user device that is communicatively coupled to another device, such as a base device. In these embodiments, the operations of process **1600** are distributed in any manner between the user device and the other device. Further, the display of the user device can be transparent or opaque. Process **1600** can be applied to CGR environments, including virtual reality and mixed reality environments, and to affordances that correspond to virtual objects or physical objects. Although the blocks of process **1600** are depicted in a particular order in FIG. 16, these blocks can be performed in other orders. Further, one or more blocks of process **1600** can be partially performed, optionally performed, combined with another block(s), and/or additional blocks can be performed.

(93) At block **1602**, the device displays an affordance associated with a first object (e.g., a displayed object).

(94) At block **1604**, the device determines a gaze direction or a gaze depth (e.g., of one or more eyes). In some embodiments, data is captured from a sensor directed toward the user, and the gaze direction or the gaze depth is determined based on the data captured from the sensor. In some embodiments, determining the gaze direction or the gaze depth includes determining the gaze direction. In some embodiments, determining the gaze direction or the gaze depth includes determining the gaze depth. Optionally, the gaze direction or the gaze depth is determined using ray casting or cone casting. Optionally, an angular extent of a cone used for the cone casting is based on the angular resolution of the gaze direction.

(95) At block **1606**, the device determines whether the gaze direction or the gaze depth corresponds to a gaze at the affordance. In some embodiments, determining that the gaze direction or the gaze depth corresponds to the depth of the affordance includes determining that the gaze is directed to the affordance. In some embodiments, determining that the gaze is directed to the affordance is based at least in part on the angular resolution of the gaze direction. In some embodiments, determining that the gaze direction or the gaze depth corresponds to a gaze at the affordance includes determining that the gaze depth corresponds to the depth of the affordance. In some embodiments, determining that the gaze depth corresponds to the depth of the affordance is based at least in part on the depth resolution of the gaze depth.

(96) At block **1608**, while the gaze direction or the gaze depth is determined to correspond to a gaze at the affordance, the device receives a first input representing an instruction to take action on the affordance corresponding to the first object. In some embodiments, the first input includes an eye gesture, a hand gesture, a voice input, and/or a controller input.

(97) At block **1610**, the device selects the affordance responsive to receiving the first input. Optionally, while the affordance is selected, a second input is received and an action associated

with the selected affordance is performed in response to receiving the second input and in accordance with the second input. In some embodiments, second input includes an eye gesture, a hand gesture, a voice input, or an input on a controller.

(98) Turning now to FIG. 17, a flow chart of exemplary process **1700** for interacting with an electronic device using an eye gaze is depicted. Process **1700** can be performed using a user device (e.g., **100a**, **300**, or **900**). The user device is, for example, a handheld mobile device, a head-mounted device, or a head-up device. In some embodiments, process **1700** is performed using two or more electronic devices, such as a user device that is communicatively coupled to another device, such as a base device. In these embodiments, the operations of process **1700** are distributed in any manner between the user device and the other device. Further, the display of the user device can be transparent or opaque. Process **1700** can be applied to CGR environments, including virtual reality and mixed reality environments, and to affordances that correspond to virtual objects or physical objects. Although the blocks of process **1700** are depicted in a particular order in FIG. 17, these blocks can be performed in other orders. Further, one or more blocks of process **1700** can be partially performed, optionally performed, combined with another block(s), and/or additional blocks can be performed.

(99) At block **1702**, the device displays a first affordance and a second affordance. Optionally, the first affordance and the second affordance are displayed concurrently. In some embodiments, the first affordance and the second affordance are displayed with a two-dimensional representation or a three-dimensional representation of an environment (e.g., a CGR environment) that includes the first affordance and the second affordance. Optionally, the first affordance is displayed at a first depth in a three-dimensional representation of the environment and the second affordance is displayed at a second depth in the three-dimensional representation of the environment, where the first depth is different than the second depth.

(100) At block **1704**, the device determines a first gaze direction or a first gaze depth (e.g., of one or more eyes). In some embodiments, data is captured from a sensor directed toward the user, and the gaze direction or the gaze depth is determined based on the data captured from the sensor. Optionally, gaze direction or the gaze depth is determined using ray casting or cone casting. In some embodiments, an angular extent of a cone used for the cone casting is based on an angular resolution of the gaze direction.

(101) At block **1706**, the device determines whether the first gaze direction or the first gaze depth corresponds to a gaze at both the first affordance and the second affordance. Optionally, in response to determining that the first gaze direction or the first gaze depth corresponds to both the first affordance and the second affordance, the display of the first affordance is enhanced in accordance with the first depth being greater than the second depth; and the display of the second affordance is enhanced in accordance with the second depth being greater than the first depth. In some embodiments, the gaze direction is determined, and determining that the gaze direction or the gaze depth corresponds to both the first affordance and the second affordance includes determining that the gaze direction corresponds to both the first affordance and the second affordance. Optionally, determining that the gaze direction corresponds to both the first affordance and the second affordance is based at least in part on the angular resolution of the gaze direction. In some embodiments, determining the gaze direction or the gaze depth includes determining the gaze depth, and determining that the gaze direction or the gaze depth corresponds to both the first affordance and the second affordance includes determining that the gaze depth corresponds to both the first affordance and the second affordance. Optionally, determining that the gaze depth corresponds to both the first affordance and the second affordance is based at least in part on the depth resolution of the gaze depth.

(102) At block **1708**, the device enlarges the first affordance and the second affordance responsive to determining that the first gaze direction or the first gaze depth corresponds to a gaze at both the first affordance and the second affordance. In some embodiments, the first affordance and the

second affordance are enlarged in accordance with a determination that the user's gaze meets predefined criteria. In some embodiments, a third input is received, and the first affordance and the second affordance are enlarged in response to determining that the first gaze direction or the first gaze depth corresponds to both the first affordance and the second affordance and receiving the third input. In some embodiments, the third input includes an eye gesture, a hand gesture, a voice input, or a controller input. In some embodiments, enlarging the first affordance and the second affordance includes displaying an enlarged view of at least a portion of an environment (e.g., a CGR environment) that surrounds the first affordance and the second affordance. In some embodiments, the enlarged view of the at least a portion of the environment that surrounds the first affordance and the second affordance is a representation of a virtual environment. In some embodiments, the enlarged view of the at least a portion of the environment that surrounds the first affordance and the second affordance is a representation of a physical environment. In some embodiments, enlarging the first affordance and the second affordance includes displaying the first affordance at a third depth in a three-dimensional representation of the environment and displaying the second affordance at a fourth depth in the three-dimensional representation of the environment, where the third depth is the same as the fourth depth.

(103) Optionally, after enlarging the first affordance and the second affordance, a second gaze direction or a second gaze depth is determined, and the second gaze direction or the second gaze depth is determined to correspond to a gaze at the first affordance. While the second gaze direction or the second gaze depth is determined to correspond to a gaze at the first affordance, a first input representing user instruction to take action on the first affordance is received, and the first affordance is selected responsive to receiving the first input. Optionally, the first input includes an eye gesture, a hand gesture, a voice input, or a controller input.

(104) In some embodiments, the first affordance or the second affordance is reduced in response to receiving the first input. Optionally, while the first affordance is selected, a second input is received, and an action associated with the first affordance in accordance with the second input is performed in response to receiving the second input. In some embodiments, the second input includes an eye gesture, a hand gesture, a voice input, or a controller input.

(105) Turning now to FIG. 18, a flow chart of exemplary process **1800** for interacting with an electronic device using an eye gaze is depicted. Process **1800** can be performed using a user device (e.g., **100a**, **300**, or **900**). The user device is, for example, a handheld mobile device, a head-mounted device, or a head-up device. In some embodiments, process **1800** is performed using two or more electronic devices, such as a user device that is communicatively coupled to another device, such as a base device. In these embodiments, the operations of process **1800** are distributed in any manner between the user device and the other device. Further, the display of the user device can be transparent or opaque. Process **1800** can be applied to CGR environments, including virtual reality and mixed reality environments, and to virtual objects, physical objects, and representations thereof. Although the blocks of process **1800** are depicted in a particular order in FIG. 18, these blocks can be performed in other orders. Further, one or more blocks of process **1800** can be partially performed, optionally performed, combined with another block(s), and/or additional blocks can be performed.

(106) The device is adapted to display a field of view of a three-dimensional computer generated reality environment. The field of view is rendered from a viewing perspective. At block **1802**, the device displays a first object and a second object. Optionally, the first object and the second object are displayed concurrently. In some embodiments, the first object and the second object are displayed such that the first object appears to be (e.g., is presented as) closer than the second object from the viewing perspective.

(107) At block, **1804**, the device determines a gaze position (e.g., of one or more eyes). In some embodiments, data is captured from a sensor directed toward the user, and the gaze position is determined based on the data captured from the sensor. In some embodiments, the gaze position is

determined using ray casting or cone casting. Optionally, an angular extent of a cone used for the cone casting is based on the angular resolution of a gaze direction.

(108) At block **1806**, the device determines whether the gaze position corresponds to a gaze at the first object or the second object. In some embodiments, the gaze direction is determined, and determining that the gaze position corresponds to a gaze at the first object or the second object includes determining that the gaze is directed at the first object or the second object. Optionally, determining whether the gaze is directed to the first object or the second object is based at least in part on the angular resolution of the gaze direction. In some embodiments, the gaze depth is determined, and determining that the gaze position corresponds to a gaze at the first object or the second object includes determining that the gaze depth corresponds to a depth of the first object or the second object (e.g., as presented in the field of view). Optionally, determining that the gaze depth corresponds to the depth of the first object or the second object is based at least in part on the depth resolution of the gaze depth.

(109) At block **1808**, the device visually alters the display of the second object in accordance with a determination that the gaze position corresponds to a gaze at the first object. In some embodiments, the second object is altered in response to determining that the gaze position corresponds to a gaze at the first object and receiving an input. The input optionally includes an eye gesture, a hand gesture, a voice input, or a controller input. Optionally, the device enhances the display (e.g., display resolution) of the first object. Optionally, after visually altering the second object, the device determines a second gaze position of the user, and in accordance with a determination that the second gaze position corresponds to a gaze at the second object, visually alters the display of the first object and displays the second object according to its initial appearance.

(110) At block **1810**, the device visually altering the display of the first object in accordance with a determination that the gaze position corresponds to a gaze at the second object. In some embodiments, the first object is altered in response to determining that the gaze position corresponds to a gaze at the second object and receiving an input. The input optionally includes an eye gesture, a hand gesture, a voice input, or a controller input. Optionally, the device enhances the display (e.g., display resolution) of the second object.

(111) Executable instructions for performing the features of methods **1600**, **1700**, and/or **1800** described above are, optionally, included in a transitory or non-transitory computer-readable storage medium (e.g., memory(ies) **106**) or other computer program product configured for execution by one or more processors (e.g., processor(s) **102**). Further, some operations in method **1600** (e.g., block **1610**) are, optionally, included in method **1700** and/or method **1800**, some operations in method **1700** (e.g., block **1708**) are, optionally, included in method **1600** and/or method **1800**, and some operations in method **1800** (e.g., blocks **1806**, **1808**, and/or **1810**) are, optionally, included in method **1600** and/or method **1700**.

(112) Turning to FIGS. **19A-19Y**, techniques are described that provide a dual-modality for, e.g., selecting and/or placing objects (e.g., virtual objects, physical objects, and affordances corresponding to virtual and physical objects) in a CGR environment. In a first mode (e.g., “gaze-engaged” mode), a position or object is initially designated based on the position of a user's gaze. After the initial designation, a second mode (e.g., “gaze-disengaged” mode) is used to move the designated position or designate a different object without using gaze. Gaze position can be rapidly moved by a user, which makes it effective for quickly identifying a general area. As discussed above, however, there is uncertainty in the position of a user's gaze, which makes it difficult to designate a precise position using gaze. Displaying a persistent visual indicator at the estimated gaze position may be ineffective for designating a precise position, as the indicator can distract the user and cause the user's gaze to follow the indicator rather than focus on the desired designation point. The dual-modality technique allows a user to quickly make a rough initial designation, and then make fine adjustments independent of gaze (e.g., based solely on manual inputs) to designate a particular point or object.

(113) FIG. 19A illustrates user **200**, who uses device **1900** to interact with virtual environment **1902**. In some embodiments, environment **1902** is a CGR environment (e.g., a VR or MR environment). Device **1900** includes virtual reality HMD **1900a** and input device **1900b**. In some embodiments, HMD **1900a** is device **100a** (e.g., in FIGS. 1F-1I) and input device **1900b** is in communication with HMD **1900a** (e.g., via communication bus(es) **150**, shown in FIGS. 1A-1B). View **1902a** illustrates a view of virtual environment **1902** displayed to user **200** on HMD **1900a**, and view **1902b** illustrates a perspective view of virtual environment **1902** including user **200**. FIG. 19A also illustrates input device **1900b**, which includes a touch-sensitive surface **1904** (e.g., touch-sensitive surface **122** in FIGS. 1A-1B) that allows user **200** to provide inputs to interact with virtual environment **1902**. Device **1900** includes sensor(s) (e.g., image sensor(s) on HMD **1900A**) to determine gaze **1906** (e.g., gaze direction and/or gaze depth) of user **200** (as described above). In some embodiments, device **1900** includes sensor(s) configured to detect various types of user inputs, including (but not limited to) eye gestures, body gestures, and voice inputs. In some embodiments, input device includes a controller configured to receive button inputs (e.g., up, down, left, right, enter, etc.).

(114) Virtual environment **1902** includes stack of photos **1908**, which includes individual photos **1908a-1908e**, lying on table **1912**. Gaze **1906** seen in view **1902b** indicates that user **200** is looking at stack of photos **1908**. In some embodiments, the lines representing gaze **1906** are not visible in virtual environment **1902**, as shown for example in view **1902a**.

(115) As shown in FIG. 19A, device **1900** receives user input **1910a** (e.g., a touch gesture on touch-sensitive surface **1904**) while gaze **1906** is directed at stack of photos **1908**. In some embodiments, user input **1910a** includes an eye gesture, a body gesture, a voice input, a controller input, or a combination thereof, in addition to or instead of a touch gesture on touch-sensitive surface **1904**.

(116) In some embodiments, the response to user input **1910a** depends on the characteristics of user input **1910a**. For example, in accordance with a determination that user input **1910a** is a first type of input (e.g., a tap on touch-sensitive surface **1904**), the entire stack of photos **1908** is selected, as indicated by focus indicator **1914** (e.g., bold border) around stack of photos **1908** in FIG. 19B. In some embodiments, device **1900** de-selects stack of photos **1908** in response to receiving further input (e.g., selection of an exit button).

(117) Alternatively, in accordance with a determination that user input **1910a** is a different type of input (e.g., a touch and hold on touch-sensitive surface **1904**), photos **1908a-1908e** are presented, as illustrated in FIG. 19C, so that user **200** can more easily select a particular photo from stack **1908**. In FIG. 19C, photos **1908a-1908e** are moved from table **1912** and presented upright and spread out in the middle of the field of view of user **200**. In response to receiving user input **1910a**, photo **1908a** in the far left position is designated (e.g., tentatively selected). Designation of photo **1908a** is indicated by focus indicator **1914**, which includes a bold border around photo **1908a**. In some embodiments, focus indicator **1914** includes a pointer, cursor, dot, sphere, highlighting, outline, or ghost image that visually identifies the designated object. In some embodiments, device **1900** un-designates photo **1908a** and returns photos **1908** to table **1912** in response to receiving further input (e.g., selection of an exit button or liftoff of a touch).

(118) The responses illustrated in FIG. 19B and FIG. 19C are both based on gaze **1906**, and more specifically, the gaze position of user **200** at the time of user input **1910a**. Stack of photos **1908** is either selected (FIG. 19B) or designated and re-presented for further selection due to the gaze position of user **200** being positioned on stack of photos **1908**. When the response to user input is based on gaze **1906**, device **1900** is in a gaze-engaged mode and gaze **1906** of user **200** is engaged with user input. Gaze-engaged mode is indicated in FIG. 19A by gaze **1906** being illustrated by solid lines.

(119) In some embodiments, the response to user input **1910a** depends on whether gaze **1906** corresponds to more than one selectable object. In some embodiments, device **1900** does not confirm selection if there is ambiguity or uncertainty about the object to be selected. For example,

device **1900** displays photos **1908a-1908e** and designates photo **1908a** (FIG. **19C**) in accordance with a determination that the position of gaze **1906** corresponds to a plurality of unresolvable selectable objects (e.g., stack of photos **1908**). In some such embodiments, in accordance with a determination that the position of gaze **1906** corresponds to only a single selectable object (e.g., mug **1918** illustrated in FIG. **19M** described below), device **1900** selects the single selectable object (e.g., instead of designating an object or providing the capability to further refine the selection).

(120) In the illustrated embodiment, in response to receiving user input **1910a**, device **1900** also switches to a gaze-disengaged mode in which a response to a user input is not based on gaze **1906** of user **200** and gaze **1906** is disengaged from further user input. Gaze-disengaged mode is indicated in FIG. **19C** by gaze **1906** being illustrated by broken lines.

(121) Turning to FIG. **19D**, while photo **1908a** is designated, device **1900** receives user input **1910b**. In FIG. **19D**, user input **1910b** includes a left-to-right swipe or drag gesture. In some embodiments, user input **1910b** is a continuation of user input **1910a** (e.g., user input **1910a** includes a contact that is maintained on touch-sensitive surface **1904**, and user input **1910b** includes movement of the contact). In some embodiments, user input **1910b** includes a press of a directional button or an oral command (“move right”). In response to receiving user input **1910b**, focus indicator **1914** is moved from photo **1908a** in accordance with (e.g., in the direction of) user input **1910b** to designate photo **1908b**, as shown in FIG. **19E**.

(122) Notably, since gaze **1906** is disengaged, photo **1908b** is designated in response to receiving user input **1910b** despite gaze **1906** being positioned on photo **1908a** at the time of user input **1910b**. Focus indicator **1914** is moved to a position (e.g., object) that does not correspond to the position of gaze **1906**. More generally, moving focus indicator **1914** to designate photo **1908b** is not based on gaze **1906**. In some embodiments, focus indicator **1914** is moved based solely on characteristics of user input **1910b** (e.g., position, direction, speed, duration, etc.).

(123) As illustrated in FIG. **19E**, gaze **1906** remains disengaged, and in response to receiving further user input **1910c** while gaze **1906** is positioned on photo **1908a**, focus indicator **1914** is moved from photo **1908b** to designate photo **1908c**, as shown in FIG. **19F**.

(124) Turning to FIG. **19G**, while photo **1908c** is designated, device **1900** receives user input **1910d** (e.g., click, double tap, or finger liftoff). In response to receiving user input **1910d**, the currently designated object, photo **1908c**, is selected. In response to receiving user input **1910d**, focus indicator **1914** remains on photo **1908c** and the other photos **1908a**, **1908b**, **1908d**, and **1908e** are returned to table **1912**, as shown in FIG. **19H**. Also, gaze **1906** of user **200** is re-engaged in response to receiving user input **1910d**.

(125) The technique described with respect to FIGS. **19A-19H** provides a dual-mode operation in which user **200** can efficiently select a particular object (e.g., one of photos **1908**) that would be difficult to distinguish using gaze alone when photos **1908** are stacked on table **1912** (e.g., due to uncertainty in gaze position). User **200** can use gaze **1906** to quickly designate a group of objects, and then use inputs independent from gaze **1906** to navigate the group of objects and select a particular one.

(126) Turning to FIG. **19I**, while maintaining selection of photo **1908c**, user **200** moves gaze **1906** to a position on wall **1916** in environment **1902** between photo **1908f** and photo **1908g**. In response to movement of gaze **1906**, photo **1908c** is moved to the position corresponding to the gaze position. In some embodiments, photo **1908c** remains at the position shown in FIG. **19I** or is moved and/or modified visually (e.g., so as not to obstruct the view of user **200** of virtual environment **1902**) until a placement position for photo **1908c** is designated or selected, as described below.

(127) While photo **1908c** is positioned as shown in FIG. **19I**, device **1900** receives user input **1910e** (e.g., a touch on touch-sensitive surface **1904**). In response to receiving user input **1910e**, a placement position for photo **1908c** is designated based on the position of gaze **1906** at the time of user input **1910e**. As shown in FIG. **19J**, in response to receiving user input **1910e**, selected photo

1908c is placed at the position of gaze **1906** and remains selected, and gaze **1906** is disengaged. In some embodiments, the placement position is indicated by a pointer, cursor, dot, sphere, highlighting, outline, or ghost image (e.g., of the object being placed).

(128) In some embodiments, the response to user input **1910e** depends on the characteristics of user input **1910e**. In some embodiments, in accordance with user input **1910e** including a first type of input (e.g., a touch on touch-sensitive surface **1904**), device **1900** designates a tentative placement position for photo **1908c** on wall **1916**, photo **1908c** remains selected, and gaze **1906** is disengaged, as discussed above; and in accordance with user input **1910e** including a second type of input (e.g., a click on touch-sensitive surface **1904**), photo **1908c** is placed on wall **1916**, photo **1908c** is de-selected, and gaze **1906** is re-engaged. Accordingly, by using different inputs, user **200** can choose to either designate a tentative placement position and maintain selection of photo **1908c** to adjust the position with further input (as discussed below) or accept the gaze position as the placement position and de-select photo **1908c**.

(129) Returning to FIG. **19J**, while photo **1908c** remains selected and positioned at the initially designated position, device **1900** receives user input **1910f**, which includes a downward swipe or drag gesture. In response to receiving user input **1910f**, photo **1908c** is moved downward in accordance with user input **1910f** and independent of the position of gaze **1906**, as shown in FIG. **19K**. According to this technique, user **200** can use gaze **1906** to quickly and roughly designate an initial placement position and then make fine adjustments to the position that do not depend on gaze. Once photo **1908c** is in the desired position (e.g., aligned with photo **1908f** and photo **1908g**), user **200** provides input **1910g**. In response to input **1910g**, the position of photo **1908c** in FIG. **19K** is selected as the final placement position and gaze **1906** is re-engaged. As shown in FIG. **19L**, in response to receiving user input **1910g**, focus is removed from photo **1908c** (photo **1908c** is de-selected) and photo **1908c** remains at the selected placement position as user **200** moves gaze **1906** to a different position.

(130) Turning now to FIG. **19M**, virtual environment **1902** is configured as shown in FIG. **19L**, with the addition of mug **1918**. In FIG. **19M**, while gaze **1906** is positioned between mug **1918** and stack of photos **1908**, device **1900** receives user input **1910h** (e.g., a touch on touch-sensitive surface **1904**, a press of a button, or a body gesture). In response to receiving user input **1910h**, a selection point represented by focus indicator **1920** is designated at a position corresponding to the position of gaze **1906**, as shown in FIG. **19N**. In some embodiments, focus indicator **1920** includes a pointer, cursor, dot, or sphere. In some embodiments, gaze **1906** is determined (e.g., measured or estimated) prior to the user input (e.g., the most recent measured or estimated position) or subsequent (e.g., in response) to the user input.

(131) In some embodiments, the response to user input **1910h** is contextual. In some embodiments, the response is based on what is located at the gaze position. For example, device **1900** can respond differently depending on whether an object, a plurality of unresolvable objects, a menu affordance, or no object is at the gaze position at the time of user input **1910h**. For example, if device **1900** determines with a predetermined amount of certainty that gaze **1906** corresponds to stack of photos **1908**, focus indicator **1914** is displayed as described with reference to FIGS. **19A-19C** instead of focus indicator **1920**. In some embodiments, a plurality of objects include menu options associated with an object (e.g., menu affordance **1924** described below).

(132) In some embodiments, the response is based on whether an object is currently selected. For example, if an object is not currently selected, device **1900** can operate in a selection mode and perform a selection action (e.g., select an object (FIG. **19B**), designate a selection point (FIG. **19N**), or display multiple objects to select (FIG. **19C**)); if an object is currently selected, device **1900** can operate in a placement mode and perform a placement action (e.g., place the object at the gaze position or display a ghost image of the selected object at a designated placement position; see, e.g., the description of FIGS. **19H-19J** above and FIGS. **19P-19Q** below).

(133) Returning to FIG. **19N**, focus indicator **1920** is displayed in accordance with a determination

that there are multiple selectable objects corresponding to the position of gaze **1906** at the time of user input **1910h**. For example, if device **1900** is unable to determine with sufficient certainty whether gaze **1906** corresponds to stack of photos **1908** or mug **1918**, focus indicator **1920** is displayed so that user **200** can clarify which object he desires to select. In the illustrated embodiment, user **200** desires to select mug **1918** and provides user input **1910i**, which includes a right-to-left swipe or drag gesture on touch-sensitive surface **1904** to move focus indicator **1920** to mug **1918**. In response to receiving user input **1910i**, the selection point is moved to a position corresponding to mug **1918**, as indicated by focus indicator **1920** in FIG. **19O**. While the selection point is positioned on mug **1918**, device **1900** receives user input **1910j** (e.g., a click). In response to receiving user input **1910j**, the selection point is confirmed and the object corresponding to the current position of the selection point is selected. As illustrated in FIG. **19P**, mug **1918** is selected, as indicated by focus indicator **1915** (e.g., highlighting) around mug **1918**, and gaze **1906** is re-engaged.

(134) As shown in FIG. **19P**, while mug **1918** remains selected, user **200** moves gaze **1906** to table **1922**. In the illustrated embodiment, mug **1918** remains displayed at the same position (e.g., it does not move with gaze **1906** even though gaze **1906** is engaged).

(135) While gaze **1906** is positioned as shown in FIG. **19P**, device **1900** receives user input **1910k**. In response to receiving user input **1910k**, a placement point is designated by focus indicator **1920** at the position corresponding to gaze **1906**, and gaze **1906** is disengaged, as shown in FIG. **19Q**. In some embodiments, focus indicator **1920** includes a pointer, cursor, dot, sphere, highlighting, outline, or ghost image of the selected object (e.g., mug **1918**).

(136) In some embodiments, the response to user input **1910k**, while mug **1918** is selected, depends on whether there is more than one placement position corresponding to the position of gaze **1906** at the time of user input **1910k**. In FIG. **19P**, the placement point is designated in accordance with a determination that the position of gaze **1906** corresponds to a plurality of possible selectable placement positions (e.g., device **1900** does not confirm the placement position for the selected object if there are various possible placement position at or near the gaze position). In some embodiments, in accordance with a determination that the position of gaze **1906** corresponds to only a single selectable placement position and in response to receiving user input **1910k**, device **1900** places the selected object at the gaze position, de-selects the object, and re-engages gaze **1906**.

(137) Turning to FIG. **19Q**, while the placement point is designated, device **1900** receives user input **1910l**, which includes a diagonal swipe or drag gesture upward and to the right on touch-sensitive surface **1904**. In response to receiving user input **1910l**, the placement point is moved in accordance with user input **1910l**, as indicated by focus indicator **1920** moving toward the center of table **1922**, as shown in FIG. **19R**. The placement point is confirmed in response to receiving user input **1910m**, and the selected object (e.g., mug **1918**) is placed at the confirmed placement point on table **1922**, as shown in FIG. **19S**. Gaze **1906** is also re-engaged in response to receiving user input **1910m**.

(138) Turning now to FIG. **19T**, virtual environment **1902** is configured as shown in FIG. **19M**, with the addition of menu affordance **1924**, which is associated with objects in the vicinity of menu affordance **1924** (e.g., table **1912**, photos **1908**, and mug **1918**). In FIG. **19T**, while gaze **1906** is positioned on menu affordance **1924**, device **1900** receives user input **1910n** (e.g., a touch). In response to receiving user input **1910n**, menu affordance **1924** is selected and gaze **1906** is disengaged from user input, as shown in FIG. **19U**.

(139) Selection of menu affordance **1924** causes display of menu options **1926a-1926d**, which can be cycled through and selected with input independent of gaze **1906**. As shown in FIG. **19U**, menu option **1926a** (SELECT TABLE) is initially designated with focus indicator **1928** (e.g., bold border) in response to selection of menu affordance **1924**.

(140) As shown in FIG. **19V**, device **1900** receives user input **1910o**, which includes a downward

swipe or drag gesture. In response to receiving user input **1910o**, focus indicator **1928** moves according to user input **1910o** from menu option **1926a** (SELECT TABLE) down to menu option **1926b** (SELECT PHOTOS), regardless of the position of gaze **1906**, as shown in FIG. **19W**.

(141) In FIG. **19W**, device **1900** receives user input **1910p**, which includes additional downward movement. In response to receiving user input **1910p**, focus indicator **1928** moves according to user input **1910p** from menu option **1926b** (SELECT PHOTOS) down to menu option **1926c** (SELECT MUG), again regardless of the position of gaze **1906**, as shown in FIG. **19X**.

(142) In FIG. **19X**, while menu option **1926C** is designated, device **1900** receives user input **1910q**. In response to receiving user input **1910q**, the object corresponding to menu option **1926c** is selected, as shown in FIG. **19Y**. In FIG. **19Y**, in response to receiving user input **1910r**, mug **1918** is selected and moved to the center of the field of view of user **200**.

(143) Furthermore, although the embodiments described above with reference to FIGS. **19A-19Y** refer to a virtual environment, similar techniques can be applied to other CGR environments, including mixed reality environments.

(144) Turning now to FIG. **20**, a flow chart of exemplary process **2000** for interacting with an electronic device using an eye gaze is depicted. Process **2000** can be performed using a user device (e.g., **100a**, **300**, **900**, or **1900**). The user device is, for example, a handheld mobile device, a head-mounted device, or a head-up device. In some embodiments, process **2000** is performed using two or more electronic devices, such as a user device that is communicatively coupled to another device, such as a base device. In these embodiments, the operations of process **2000** are distributed in any manner between the user device and the other device. Further, the display of the user device can be transparent or opaque. Process **2000** can be applied to CGR environments, including virtual reality and mixed reality environments, and to virtual objects, physical objects, and representations (e.g., affordances) corresponding to virtual and physical objects. Although the blocks of process **2000** are depicted in a particular order in FIG. **20**, these blocks can be performed in other orders. Further, one or more blocks of process **2000** can be partially performed, optionally performed, combined with another block(s), and/or additional blocks can be performed.

(145) At block **2002**, the device receives a first user input at a first time (e.g., a contact on a touch-sensitive surface, a press of a button, or a body gesture). At block **2004**, in response to receiving the first user input, the device designates a selection point at a first position based on the gaze position at the first time, where the first position corresponds to the gaze position at the first time. In some embodiments, the gaze position at the first time is determined (e.g., measured or estimated) prior to the first user input (e.g., the most recent measured or estimated position) or subsequent (e.g., in response) to the first user input.

(146) In some embodiments, a focus indicator is displayed at the gaze position. In some embodiments, the focus indicator includes a pointer, cursor, dot, sphere, highlighting, outline, or ghost image (e.g., of a designated or selected object(s)). In some embodiments, the focus indicator designates a selection point corresponding to an object at the gaze position. In some embodiments, the device disengages gaze from user input in response to the first user input.

(147) In some embodiments, the response to the first input is contextual (e.g., the response is based on what is located at the gaze position (e.g., an object, a plurality of unresolvable objects, a menu affordance, or no object) or whether an object is currently selected. For example, if an object is not currently selected, the device operates in selection mode and performs a selection action (e.g., multiple objects are displayed for selection), whereas if an object is currently selected, the device operates in placement mode and performs a placement action (e.g., a ghost image of the selected object is displayed at a tentative placement position).

(148) In some embodiments, the selection point is designated at the first position in accordance with a determination that the first position corresponds to a plurality of selectable objects. In some embodiments, a plurality of objects is a group of closely spaced objects that cannot be resolved based on the gaze of the user. In some embodiments, the plurality of objects are menu options

associated with an object (e.g., a menu affordance) at the gaze position. For example, the device tentatively designates a selection point rather than confirming selection of an object if it is determined that there is ambiguity or uncertainty about the object to be selected. In some such embodiments, in response to receiving the first user input, in accordance with a determination that the first position corresponds to only a single selectable object, the device selects the single selectable object (e.g., instead of designating the selection point at the first position).

(149) In some embodiments, the selection point is designated at the first position in accordance with a determination that the first user input is a first type of input (e.g., a touch on a touch-sensitive surface, a press of a button, or a body gesture). In some such embodiments, in response to receiving the first user input and in accordance with a determination that the first user input is a second type of input different than the first type of input (e.g., a click (in contrast to a touch) on the touch-sensitive surface, a press of a different button, or a different body gesture), the device confirms the selection point at the first position.

(150) While maintaining designation of the selection point, the device performs the operations of blocks **2006**, **2008**, **2010**, and **2012**. At block **2006**, the device receives a second user input (e.g., movement of a contact on a touch-sensitive surface or press of a directional button). At block **2008**, in response to receiving the second user input, the device moves the selection point to a second position different than the first position, where moving the selection point to the second position is not based on the gaze position. For example, the device moves a focus indicator to a different object, selection point, or placement point. In some embodiments, the selection point is moved based solely on characteristics (e.g., position, direction, speed, duration, etc.) of the second input. In some embodiments, the movement of the selection point is independent from (not based on) a gaze position. In some embodiments, the second position is different than a gaze position associated with the second user input.

(151) In some embodiments, the first user input is received while the device is in a first mode (e.g., a gaze-engaged mode in which a response to a user input is based on a gaze of a user), and the selection point is designated at the first position in accordance with the device being in the first mode. In some such embodiments, in response to receiving the first user input, the device switches from the first mode to a second mode (e.g., a gaze-disengaged mode in which a response to a user input is not based on a gaze of a user such that the gaze is disengaged from further input). In some such embodiments, the second input is received while the device is in the second mode, and the selection point is moved to the second position in accordance with the device being in the second mode.

(152) At block **2010**, while the selection point is at the second position, the device receives a third user input (e.g., click, double tap, or contact liftoff from a touch-sensitive surface). At block **2012**, in response to receiving the third user input, the device confirms the selection point at the second position. In some embodiments, the device re-engages input with gaze upon confirmation (e.g., switches from gaze-disengaged mode to gaze-engaged mode). In some embodiments, the third input is received while the device is in the second mode (gaze-disengaged mode), and the selection point is confirmed at the second position in accordance with the device being in the second mode.

(153) In some embodiments, confirming the selection point selects an object corresponding to the position of the selection point (e.g., the second position). For example, in response to receiving the third user input, the device selects an object corresponding to the second position.

(154) In some embodiments, confirming the selection point places an object at the position of the selection point. For example, before receiving the first user input, the device selects an object at a third position different than the second position, and in response to receiving the third user input, places the object at the second position. In some embodiments, before receiving the first user input, the device selects an object at a third position different than the second position, where the selection point is designated at the first position in accordance with a determination that the first position corresponds to a plurality of selectable placement positions (e.g., the device does not

confirm a placement position if there is ambiguity or uncertainty about the place to be selected). In some such embodiments, in response to receiving the first user input and in accordance with a determination that the first position corresponds to only a single selectable placement position, the device places the object at the single selectable placement position (e.g., the device bypasses tentatively designating a placement position if there is only one option).

(155) In some embodiments, the first user input is the same type of input as the second user input or the third user input. In some embodiments, a single tap or press of a button is used to designate a point or object(s), and another single tap or press of the same button is used to confirm a designated point or object(s). In some embodiments, device decides which action to take based on the mode (e.g., selection mode or placement mode) in which the device is operating.

(156) Turning now to FIG. 21, a flow chart of exemplary process **2100** for interacting with an electronic device using an eye gaze is depicted. Process **2100** can be performed using a user device (e.g., **100a**, **300**, **900**, or **1900**). The user device is, for example, a handheld mobile device, a head-mounted device, or a head-up device. In some embodiments, process **2100** is performed using two or more electronic devices, such as a user device that is communicatively coupled to another device, such as a base device. In these embodiments, the operations of process **2100** are distributed in any manner between the user device and the other device. Further, the display of the user device can be transparent or opaque. Process **2100** can be applied to CGR environments, including virtual reality and mixed reality environments, and to virtual objects, physical objects, and representations (e.g., affordances) corresponding to virtual and physical objects. Although the blocks of process **2100** are depicted in a particular order in FIG. 21, these blocks can be performed in other orders. Further, one or more blocks of process **2100** can be partially performed, optionally performed, combined with another block(s), and/or additional blocks can be performed.

(157) At block **2102**, the device receives a first user input at a first time. At block **2104**, in response to receiving the first user input, the device designates a first object of a plurality of objects based on a gaze position (e.g., the position of the plurality of objects corresponds to the gaze position at the first time). In some embodiments, a focus indicator designates the first object. In some embodiments, the plurality of objects are highlighted or enlarged or menu options corresponding to a menu affordance at the gaze position are displayed.

(158) In some embodiments, the first object is designated in accordance with a determination that the gaze position at the first time corresponds to a gaze at more than one object (e.g., the plurality of objects). For example, the device does not confirm selection if there is ambiguity or uncertainty about the object to be selected. In some such embodiments, in response to receiving the first user input and in accordance with a determination that the gaze position at the first time corresponds to a gaze at only a single selectable object, the device selects the single selectable object.

(159) In some embodiments, the first user input is received while the device is in a first mode (e.g., a gaze-engaged mode in which a response to a user input is based on a gaze of a user) and the first object is designated in accordance with the electronic device being in the first mode. In some such embodiments, in response to receiving the first user input, the device switches from the first mode to a second mode (e.g., switches to a gaze-disengaged mode in which a response to a user input is not based on a gaze of a user such that the gaze is disengaged from further input). In some such embodiments, the second input is received while the electronic device is in the second mode, and the second object is designated in accordance with the electronic device being in the second mode.

(160) In some embodiments, the first object is designated in accordance with a determination that the first user input is a first type of input (e.g., a touch on a touch-sensitive surface, a press of a button, or a body gesture). In some such embodiments, in response to receiving the first user input and in accordance with a determination that the first user input is a second type of input different than the first type of input (e.g., a click (in contrast to a touch) on the touch-sensitive surface, a press of a different button, or a different body gesture), the device selects the plurality of objects.

(161) While maintaining designation of the first object, the device performs the operations of

blocks **2106** and **2108**. At block **2106**, the device receives a second user input. At block **2108**, in response to receiving the second user input, the device ceases designation of the first object and designates a second object of the plurality of objects (e.g., moves a focus indicator to a different object), where designating the second object is not based on the gaze position. In some embodiments, the second object is selected based solely on characteristics of the second user input (e.g., position, direction, speed, duration, etc.). In some embodiments, the second user input is at a second time and a position of the second object at the second time is different than a gaze position at the second time.

(162) While maintaining designation of the second object, the device performs the operations of blocks **2110** and **2112**. At block **2110**, the device receives a third user input. At block **2112**, in response to receiving the third user input, the device selects the second object.

(163) In some embodiments, after selecting the second object, the device receives a fourth user input at a second time. In response to receiving the fourth user input and in accordance with a determination that the fourth user input is a first type of input, the device places the second object at a gaze position at the second time. In response to receiving the fourth user input and in accordance with a determination that the fourth user input is a second type of input different than the first type of input, the device designates a placement point corresponding to the gaze position at the second time. In some such embodiments while maintaining designation of the placement position, the device receives a fifth user input and, in response to receiving the fifth user input, places the second object at a current position of the placement point.

(164) In some embodiments, the first user input is the same type of input as the second user input or the third user input. In some embodiments, a single tap or press of a button is used to designate the first object, and another single tap or press of the same button is used to select the second object.

(165) Turning now to FIG. **22**, a flow chart of exemplary process **2200** for interacting with an electronic device using an eye gaze is depicted. Process **2200** can be performed using a user device (e.g., **100a**, **300**, **900**, or **1900**). The user device is, for example, a handheld mobile device, a head-mounted device, or a head-up device. In some embodiments, process **2200** is performed using two or more electronic devices, such as a user device that is communicatively coupled to another device, such as a base device. In these embodiments, the operations of process **2200** are distributed in any manner between the user device and the other device. Further, the display of the user device can be transparent or opaque. Process **2200** can be applied to CGR environments, including virtual reality and mixed reality environments, and to virtual objects, physical objects, and representations (e.g., affordances) corresponding to virtual and physical objects. Although the blocks of process **2200** are depicted in a particular order in FIG. **22**, these blocks can be performed in other orders. Further, one or more blocks of process **2200** can be partially performed, optionally performed, combined with another block(s), and/or additional blocks can be performed.

(166) At block **2202**, the device selects an object (e.g., as described in process **2100**). While maintaining selection of the object, the device performs the operations of blocks **2204**, **2206**, **2208**, **2210**, **2212**, and **2214**. At block **2204**, the device receives a first user input at a first time. At block **2206**, in response to receiving the first user input, the device designates a placement point at a first position based on a gaze position at the first time, where the first position corresponds to the gaze position at the first time.

(167) In some embodiments, the placement point is designated at the first position in accordance with a determination that the first user input is a first type of input (e.g., a touch on a touch-sensitive surface, a press of a button, or a body gesture). In some such embodiments, in response to receiving the first user input and in accordance with a determination that the first user input is a second type of input different than the first type of input (e.g., a click (in contrast to a touch) on the touch-sensitive surface, a press of a different button, or a different body gesture), the device places the selected object at the first position.

(168) In some embodiments, the placement point is designated at the first position in accordance with a determination that the first position corresponds to a plurality of selectable placement positions (e.g., the device does not confirm the placement position when there is ambiguity or uncertainty about the position to be selected for placement). In some such embodiments, in response to receiving the first user input and in accordance with a determination that the first position corresponds to only a single selectable placement position, the device places the selected object at the single selectable placement position.

(169) While maintaining designation of the placement point, the device performs the operations of blocks **2208**, **2210**, **2212**, and **2214**. At block **2208**, the device receives a second user input. At block **2210**, in response to receiving the second user input, the device moves the placement point to a second position different than the first position, where moving the placement point to the second position is not based on gaze position (e.g., a gaze position at the time of the second user input). In some embodiments, the second position is different than a gaze position associated with the second user input.

(170) In some embodiments, the first user input is received while the electronic device is in a first mode (e.g., a gaze-engaged mode in which a response to a user input is based on a gaze position) and the placement point is designated at the first position in accordance with the electronic device being in the first mode. In some such embodiments, in response to receiving the first user input, the device switches from the first mode to a second mode (e.g., switch to a gaze-disengaged mode in which a response to a user input is not based on a gaze of a user such that the gaze is disengaged from further input in response to the first input). In some such embodiments, the second user input is received while the electronic device is in the second mode, and the placement point is moved to the second position in accordance with the electronic device being in the second mode.

(171) At block **2212**, the device receives a third user input. At block **2214**, in response to receiving the third user input, the device places the selected object at the second position and, optionally, de-selects the object. In some embodiments, the first user input is the same type of input as the second user input or the third user input. In some embodiments, a single tap or press of a button is used to designate the placement point at the first position, and another single tap or press of the same button is used to place the selected object at the second position.

(172) Executable instructions for performing the features of processes **2000**, **2100**, and/or **2200** described above are, optionally, included in a transitory or non-transitory computer-readable storage medium (e.g., memory(ies) **106**) or other computer program product configured for execution by one or more processors (e.g., processor(s) **102**). Some operations in process **2000** are, optionally, included in process **2100** and/or process **2200** (e.g., block **2004** and/or block **2008** are included in block **2104** and/or block **2108**, respectively), some operations in process **2100** are, optionally, included in process **2000** and/or process **2200** (e.g., block **2202** includes block **2112**), and some operations in process **2200** are, optionally, included in process **2000** and/or process **2100** (e.g., block **2112** includes block **2202**). Further, some operations in processes **2000**, **2100**, and/or **2200** (e.g., blocks **2004**, **2008**, **2104**, **2108**, **2206**, and/or **2210**) are, optionally, included in processes **1600**, **1700**, and/or **1800**, and some operations in processes **1600**, **1700**, and/or **1800** (e.g., blocks **1604**, **1606**, **1704**, **1706**, **1804**, and/or **1806**) are, optionally, included in processes **2000**, **2100**, and/or **2200**.

(173) As described above, one aspect of the present technology involves the use of data about a user's gaze. Gaze information, in the present technology, can be used to the benefit of users. For example, a user's gaze can be used to infer a user's focus on a particular part of a computer generated reality environment and to allow the user to interact with particular objects in that part of the field of view. It is possible, however, that some users may consider gaze information to be sensitive or to be of a personal nature.

(174) Entities that collect, use, transfer, store, or otherwise affect gaze information detected by a CGR system should comply with well-established privacy policies and/or privacy practices. In

particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Gaze information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such information data and ensuring that others (if any) with access to the gaze information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of gaze information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations.

(175) The present disclosure also contemplates embodiments in which users selectively block the use of, or access to, gaze information. Entities implementing the present technology can determine whether certain features can be provided while allowing users to select to “opt in” or “opt out” of participation in the use of gaze information during registration for services or anytime thereafter. In addition to providing “opt in” and “opt out” options, the present disclosure contemplates providing notifications relating to the access or use of gaze information. For instance, a user may be notified upon downloading an app that their personal gaze data will be accessed. Users may also be transparently educated as to why some gaze information is being used to provide certain features. For example, in virtual reality systems where gaze information is used to determine where a user is looking, user may be informed that the their gaze information is being used to determine what field of view of the virtual environment the system should render, thereby enabling the user to make an informed decision as to when to allow the use of gaze information.

(176) Nonetheless, it is the intent of the present disclosure that gaze information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., user name, device name, etc.), controlling the amount or specificity of data stored (e.g., collect mathematical coordinates of where a user is looking in a coordinate system but avoid collecting information on what content is being viewed at the coordinates), controlling how data is stored (e.g., locally), and/or other methods.

(177) The foregoing descriptions of specific embodiments have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the scope of the claims to the precise forms disclosed, and it should be understood that many modifications and variations are possible in light of the above teaching.

Claims

1. An electronic device, comprising: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying an object at an initial position in a three-dimensional computer-generated reality environment; selecting the object; while maintaining selection of the object and display of the selected object at the initial position in the three-dimensional computer-generated reality environment: receiving a first user input at a first time; in response to receiving the first user input, designating a placement point at a first position in the three-dimensional computer-generated reality environment based on a gaze position at the first time, wherein the first position corresponds to the gaze position at the first time; while maintaining designation of the

placement point: receiving a second user input; in response to receiving the second user input, moving the placement point to a second position in the three-dimensional computer-generated reality environment different than the first position, wherein moving the placement point to the second position is not based on the gaze position; and receiving a third user input; and in response to receiving the third user input: ceasing to display the selected object at the initial position in the three-dimensional computer-generated reality environment; and placing the selected object at the second position in the three-dimensional computer-generated reality environment.

2. The electronic device of claim 1, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with a determination that the first position corresponds to a plurality of selectable placement positions in the three-dimensional computer-generated reality environment, and wherein the one or more programs further include instructions for: in response to receiving the first user input: in accordance with a determination that the first position corresponds to a single selectable placement position in the three-dimensional computer-generated reality environment, placing the selected object at the single selectable placement position.

3. The electronic device of claim 1, wherein the first user input is received while the electronic device is in a first mode, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with the electronic device being in the first mode, and wherein the one or more programs further include instructions for: in response to receiving the first user input, switching the electronic device from the first mode to a second mode, wherein the second user input is received while the electronic device is in the second mode, and wherein the placement point is moved to the second position in the three-dimensional computer-generated reality environment in accordance with the electronic device being in the second mode.

4. The electronic device of claim 1, wherein the first user input is the same type of input as the second user input or the third user input.

5. The electronic device of claim 1, wherein the second position in the three-dimensional computer-generated reality environment is different than a gaze position associated with the second user input.

6. The electronic device of claim 1, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with a determination that the first user input is a first type of input, and wherein the one or more programs further include instructions for: in response to receiving the first user input: in accordance with a determination that the first user input is a second type of input different than the first type of input, placing the selected object at the first position in the three-dimensional computer-generated reality environment.

7. A non-transitory computer-readable storage medium storing one or more programs configured to be executed by one or more processors of an electronic device, the one or more programs including instructions for: displaying an object at an initial position in a three-dimensional computer-generated reality environment; selecting the object; while maintaining selection of the object and display of the selected object at the initial position in the three-dimensional computer-generated reality environment: receiving a first user input at a first time; in response to receiving the first user input, designating a placement point at a first position in the three-dimensional computer-generated reality environment based on a gaze position at the first time, wherein the first position corresponds to the gaze position at the first time; while maintaining designation of the placement point: receiving a second user input; in response to receiving the second user input, moving the placement point to a second position in the three-dimensional computer-generated reality environment different than the first position, wherein moving the placement point to the second position is not based on the gaze position; and receiving a third user input; and in response to receiving the third user input: ceasing to display the selected object at the initial position in the three-dimensional

computer-generated reality environment; and placing the selected object at the second position.

8. The non-transitory computer-readable storage medium of claim 7, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with a determination that the first position corresponds to a plurality of selectable placement positions in the three-dimensional computer-generated reality environment, and wherein the one or more programs further include instructions for: in response to receiving the first user input: in accordance with a determination that the first position corresponds to a single selectable placement position in the three-dimensional computer-generated reality environment, placing the selected object at the single selectable placement position.

9. The non-transitory computer-readable storage medium of claim 7, wherein the first user input is received while the electronic device is in a first mode, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with the electronic device being in the first mode, and wherein the one or more programs further include instructions for: in response to receiving the first user input, switching the electronic device from the first mode to a second mode, wherein the second user input is received while the electronic device is in the second mode, and wherein the placement point is moved to the second position in the three-dimensional computer-generated reality environment in accordance with the electronic device being in the second mode.

10. The non-transitory computer-readable storage medium of claim 7, wherein the first user input is the same type of input as the second user input or the third user input.

11. The non-transitory computer-readable storage medium of claim 7, wherein the second position in the three-dimensional computer-generated reality environment is different than a gaze position associated with the second user input.

12. The non-transitory computer-readable storage medium of claim 7, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with a determination that the first user input is a first type of input, and wherein the one or more programs further include instructions for: in response to receiving the first user input: in accordance with a determination that the first user input is a second type of input different than the first type of input, placing the selected object at the first position in the three-dimensional computer-generated reality environment.

13. A method, comprising: at an electronic device: displaying an object at an initial position in a three-dimensional computer-generated reality environment; selecting the object; while maintaining selection of the object and display of the selected object at the initial position in the three-dimensional computer-generated reality environment: receiving a first user input at a first time; in response to receiving the first user input, designating a placement point at a first position in the three-dimensional computer-generated reality environment based on a gaze position at the first time, wherein the first position corresponds to the gaze position at the first time; while maintaining designation of the placement point: receiving a second user input; in response to receiving the second user input, moving the placement point to a second position in the three-dimensional computer-generated reality environment different than the first position, wherein moving the placement point to the second position is not based on the gaze position; and receiving a third user input; and in response to receiving the third user input: ceasing to display the selected object at the initial position in the three-dimensional computer-generated reality environment; and placing the selected object at the second position in the three-dimensional computer-generated reality environment.

14. The method of claim 13, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with a determination that the first position corresponds to a plurality of selectable placement positions in the three-dimensional computer-generated reality environment, and wherein the method further comprises: in response to receiving the first user input: in accordance with a determination that the first

position corresponds to a single selectable placement position in the three-dimensional computer-generated reality environment, placing the selected object at the single selectable placement position.

15. The method of claim 13, wherein the first user input is received while the electronic device is in a first mode, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with the electronic device being in the first mode, and wherein the method further comprises: in response to receiving the first user input, switching the electronic device from the first mode to a second mode, wherein the second user input is received while the electronic device is in the second mode, and wherein the placement point is moved to the second position in the three-dimensional computer-generated reality environment in accordance with the electronic device being in the second mode.

16. The method of claim 13, wherein the first user input is the same type of input as the second user input or the third user input.

17. The method of claim 13, wherein the second position in the three-dimensional computer-generated reality environment is different than a gaze position associated with the second user input.

18. The method of claim 13, wherein the placement point is designated at the first position in the three-dimensional computer-generated reality environment in accordance with a determination that the first user input is a first type of input, and wherein the method further comprises: in response to receiving the first user input: in accordance with a determination that the first user input is a second type of input different than the first type of input, placing the selected object at the first position in the three-dimensional computer-generated reality environment.
