

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407645
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Parappalliyalil; Jayakrishnan et al.

Systems and methods of database instance container deployment

Abstract

Systems and methods can include one or more processing modules and one or more non-transitory storage modules storing computing instructions configured to run on the one or more processing modules and perform acts. The acts can include providing a bonded network interface on a host server, where the host server can include a plurality of internet protocol (IP) addresses. The acts also can include binding a first database instance container to a first IP address of the plurality of IP addresses of the host server such that a first database deployed inside the first database instance container has direct access to the host server. Systems and methods also can include deploying a first database instance container of a first cluster at a first host server and deploying a second database instance container of a second cluster at the first host server. Other embodiments also are disclosed herein.

Inventors: Parappalliyalil; Jayakrishnan (Cupertino, CA), Yerolkar; Kavindra (Foster City, CA), Mondal; Aniruddha (San Francisco, CA), Tripathi; Preetish Kumar (Bengaluru, IN)

Applicant: Walmart Apollo, LLC (Bentonville, AR)

Family ID: 60418779

Assignee: Walmart Apollo, LLC (Bentonville, AR)

Appl. No.: 17/866902

Filed: July 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220353237 A1	Nov. 03, 2022

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04L61/5007** (20220101); **G06F16/21** (20190101); **G06F16/27** (20190101);
H04L61/5061 (20220101); **H04L67/1097** (20220101)

U.S. Cl.:

CPC **H04L61/5007** (20220501); **G06F16/21** (20190101); **G06F16/27** (20190101);
H04L61/5061 (20220501); **H04L67/1097** (20130101);

Field of Classification Search

CPC: H04L (61/5007); H04L (61/5061); H04L (67/1097); G06F (16/21); G06F (16/27)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9256467	12/2015	Singh	N/A	G06F 9/5077
2008/0056120	12/2007	Jha	370/216	H04L 12/4641
2013/0151680	12/2012	Salinas	709/223	G06F 16/211
2016/0205519	12/2015	Patel	455/518	H04W 4/10
2016/0299800	12/2015	Cleary et al.	N/A	N/A
2016/0330138	12/2015	Thomason	N/A	N/A
2017/0170990	12/2016	Gaddehosur et al.	N/A	N/A
2017/0317969	12/2016	Masurekar	N/A	H04L 61/5014

Primary Examiner: Shah; Sanjiv

Assistant Examiner: Forouharnejad; Faezeh

Attorney, Agent or Firm: DICKINSON WRIGHT RLLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 15/166,985 filed May 27, 2016, to be issued as U.S. Pat. No. 11,394,685. U.S. application Ser. No. 15/166,985 is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) This disclosure relates generally to container deployment, and relates more particularly to database instance container deployment.

BACKGROUND

(2) Conventional systems require a single hardware device for each application/database deployment. However, the nature of application workload is highly variable, resulting in an

impedance mismatch between application workloads and hardware. This mismatch causes suboptimal resource utilization and unused capacity within clusters.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) To facilitate further description of the embodiments, the following drawings are provided in which:
- (2) FIG. 1 illustrates a front elevational view of a computer system that is suitable for implementing various embodiments of the systems disclosed in FIGS. 3 and 5;
- (3) FIG. 2 illustrates a representative block diagram of an example of the elements included in the circuit boards inside a chassis of the computer system of FIG. 1,
- (4) FIG. 3 illustrates a representative block diagram of a system, according to an embodiment;
- (5) FIG. 4 is a flowchart of a method, according to an embodiment;
- (6) FIG. 5 illustrates a representative block diagram of a portion of the system of FIG. 3, according to an embodiment; and
- (7) FIG. 6 illustrates a representative block diagram of database instance containers deployed on two different host servers.
- (8) For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the present disclosure. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure. The same reference numerals in different figures denote the same elements.
- (9) The terms “first,” “second,” “third,” “fourth,” and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms “include,” and “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, system, article, device, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, system, article, device, or apparatus.
- (10) The terms “left,” “right,” “front,” “back,” “top,” “bottom,” “over,” “under,” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the apparatus, methods, and/or articles of manufacture described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein.
- (11) The terms “couple,” “coupled,” “couples,” “coupling,” and the like should be broadly understood and refer to connecting two or more elements mechanically and/or otherwise. Two or more electrical elements may be electrically coupled together, but not be mechanically or otherwise coupled together. Coupling may be for any length of time, e.g., permanent or semi-permanent or only for an instant. “Electrical coupling” and the like should be broadly understood and include electrical coupling of all types. The absence of the word “removably,” “removable,” and the like near the word “coupled,” and the like does not mean that the coupling, etc. in question is or is not removable.

(12) As defined herein, two or more elements are “integral” if they are comprised of the same piece of material. As defined herein, two or more elements are “non-integral” if each is comprised of a different piece of material.

(13) As defined herein, “approximately” can, in some embodiments, mean within plus or minus ten percent of the stated value. In other embodiments, “approximately” can mean within plus or minus five percent of the stated value. In further embodiments, “approximately” can mean within plus or minus three percent of the stated value. In yet other embodiments, “approximately” can mean within plus or minus one percent of the stated value.

DESCRIPTION OF EXAMPLES OF EMBODIMENTS

(14) A number of embodiments can include a system. The system can include one or more processing modules and one or more non-transitory storage modules storing computing instructions configured to run on the one or more processing modules and perform acts. The acts can include deploying a first database instance container at a first host server, the first database instance container belonging to a first cluster. The acts also can include deploying a second database instance container at a second host server, the second database instance container belonging to the first cluster. The acts can further include deploying a third database instance container at the first host server, the third database instance container belonging to the first cluster. The acts can additionally include deploying a fourth database instance container at the second host server, the fourth database instance container belonging to the second cluster.

(15) A number of embodiments can include a system. The system can include one or more processing modules and one or more non-transitory storage modules storing computing instructions configured to run on the one or more processing modules and perform acts. The acts can include creating a bonded network interface on a host server, the host server comprising a plurality of internet protocol (IP) addresses. The acts also can include binding a first database instance container to a first IP address of the plurality of IP addresses of the host server such that a first database deployed inside the first database instance container has direct access to the host server.

(16) Various embodiments include a method. The method can include allocating a first pool of a first plurality of internet protocol (IP) addresses to a first host server. The method also can include allocating a second pool of a second plurality of IP addresses to a second server, wherein the first plurality of IP addresses are different from and non-overlapping with the second plurality of IP addresses. The method can further include creating a first bonded network interface at the first host server. The method can additionally include creating a second bonded network interface at the second host server. Moreover, the method can include binding a first database instance container to the first bonded network interface and also to a first IP address of the first pool of the first plurality of IP addresses such that a first database deployed inside the first database instance container has direct access to the first host server. The method also can include binding a second database instance container to the second bonded network interface and also to a second IP address of the second pool of the second plurality of IP addresses such that a second database inside the second database instance container has direct access to the second host server.

(17) A number of embodiments include a system including one or more processors and one or more non-transitory computer-readable media storing computing instructions that, when executed on the one or more processors, cause the one or more processors to perform certain acts. The acts can include providing a bonded network interface on a host server, the host server comprising a plurality of internet protocol (IP) addresses. The acts also can include binding a first database instance container to a first IP address of the plurality of IP addresses of the host server. The first database instance container can belong to a first cluster. The acts further can include binding a second database instance container to a second IP address of the plurality of IP addresses of the host server. The second database instance container can belong to a second cluster that is different from and non-overlapping with the first cluster. The first cluster can include a different fault tolerance than the second cluster.

(18) Several embodiments can include a method being implemented via execution of computing instructions configured to run on one or more processors and stored at one or more non-transitory computer-readable media. The method can include providing a bonded network interface on a host server, the host server comprising a plurality of internet protocol (IP) addresses. The method also can include binding a first database instance container to a first IP address of the plurality of IP addresses of the host server. The first database instance container can belong to a first cluster. The method further can include binding a second database instance container to a second IP address of the plurality of IP addresses of the host server. The second database instance container can belong to a second cluster that is different from and non-overlapping with the first cluster. The first cluster can include a different fault tolerance than the second cluster.

(19) Turning to the drawings, FIG. 1 illustrates an exemplary embodiment of a computer system **100**, all of which or a portion of which can be suitable for implementing the techniques described herein. As an example, a different or separate one of a chassis **102** (and its internal components) can be suitable for implementing the techniques described herein. Furthermore, one or more elements of computer system **100** (e.g., a refreshing monitor **106**, a keyboard **104**, and/or a mouse **110**, etc.) also can be appropriate for implementing the techniques described herein. Computer system **100** comprises chassis **102** containing one or more circuit boards (not shown), a Universal Serial Bus (USB) port **112**, a Compact Disc Read-Only Memory (CD-ROM) and/or Digital Video Disc (DVD) drive **116**, and a hard drive **114**. A representative block diagram of the elements included on the circuit boards inside chassis **102** is shown in FIG. 2. A central processing unit (CPU) **210** in FIG. 2 is coupled to a system bus **214** in FIG. 2. In various embodiments, the architecture of CPU **210** can be compliant with any of a variety of commercially distributed architecture families.

(20) Continuing with FIG. 2, system bus **214** also is coupled to a memory storage unit **208**, where memory storage unit **208** comprises both read only memory (ROM) and random access memory (RAM). Non-volatile portions of memory storage unit **208** or the ROM can be encoded with a boot code sequence suitable for restoring computer system **100** (FIG. 1) to a functional state after a system reset. In addition, memory storage unit **208** can comprise microcode such as a Basic Input-Output System (BIOS). In some examples, the one or more memory storage units of the various embodiments disclosed herein can comprise memory storage unit **208**, a USB-equipped electronic device, such as, an external memory storage unit (not shown) coupled to universal serial bus (USB) port **112** (FIGS. 1-2), hard drive **114** (FIGS. 1-2), and/or CD-ROM or DVD drive **116** (FIGS. 1-2). In the same or different examples, the one or more memory storage units of the various embodiments disclosed herein can comprise an operating system, which can be a software program that manages the hardware and software resources of a computer and/or a computer network. The operating system can perform basic tasks such as, for example, controlling and allocating memory, prioritizing the processing of instructions, controlling input and output devices, facilitating networking, and managing files. Some examples of common operating systems can comprise Microsoft® Windows® operating system (OS), Mac® OS, UNIX® OS, and Linux® OS.

(21) As used herein, “processor” and/or “processing module” means any type of computational circuit, such as but not limited to a microprocessor, a microcontroller, a controller, a complex instruction set computing (CISC) microprocessor, a reduced instruction set computing (RISC) microprocessor, a very long instruction word (VLIW) microprocessor, a graphics processor, a digital signal processor, or any other type of processor or processing circuit capable of performing the desired functions. In some examples, the one or more processors of the various embodiments disclosed herein can comprise CPU **210**. In some examples, the systems and procedures described herein are implemented in hardware, or a combination of hardware, software, and/or firmware. For example, one or more application specific integrated circuits (ASICs) can be programmed to carry out one or more of the systems and methods described herein.

(22) In the depicted embodiment of FIG. 2, various I/O devices such as a disk controller **204**, a

graphics adapter **224**, a video controller **202**, a keyboard adapter **226**, a mouse adapter **206**, a network adapter **220**, and other I/O devices **222** can be coupled to system bus **214**. Keyboard adapter **226** and mouse adapter **206** are coupled to keyboard **104** (FIGS. **1-2**) and mouse **110** (FIGS. **1-2**), respectively, of computer system **100** (FIG. **1**). While graphics adapter **224** and video controller **202** are indicated as distinct units in FIG. **2**, video controller **202** can be integrated into graphics adapter **224**, or vice versa in other embodiments. Video controller **202** is suitable for refreshing monitor **106** (FIGS. **1-2**) to display images on a screen **108** (FIG. **1**) of computer system **100** (FIG. **1**). Disk controller **204** can control hard drive **114** (FIGS. **1-2**), USB port **112** (FIGS. **1-2**), and CD-ROM drive **116** (FIGS. **1-2**). In other embodiments, distinct units can be used to control each of these devices separately.

(23) In some embodiments, network adapter **220** can comprise and/or be implemented as a WNIC (wireless network interface controller) card (not shown) plugged or coupled to an expansion port (not shown) in computer system **100** (FIG. **1**). In other embodiments, the WNIC card can be a wireless network card built into computer system **100** (FIG. **1**). A wireless network adapter can be built into computer system **100** by having wireless communication capabilities integrated into the motherboard chipset (not shown), or implemented via one or more dedicated wireless communication chips (not shown), connected through a PCI (peripheral component interconnector) or a PCI express bus of computer system **100** (FIG. **1**) or USB port **112** (FIG. **1**). In other embodiments, network adapter **220** can comprise and/or be implemented as a wired network interface controller card (not shown).

(24) Although many other components of computer system **100** (FIG. **1**) are not shown, such components and their interconnection are well known to those of ordinary skill in the art. Accordingly, further details concerning the construction and composition of computer system **100** and the circuit boards inside chassis **102** (FIG. **1**) are not discussed herein.

(25) When computer system **100** in FIG. **1** is running, program instructions stored on a USB-equipped electronic device connected to USB port **112**, on a CD-ROM or DVD in CD-ROM and/or DVD drive **116**, on hard drive **114**, or in memory storage unit **208** (FIG. **2**) are executed by CPU **210** (FIG. **2**). A portion of the program instructions, stored on these devices, can be suitable for carrying out at least part of the techniques described herein.

(26) Although computer system **100** is illustrated as a desktop computer in FIG. **1**, there can be examples where computer system **100** may take a different form factor while still having functional elements similar to those described for computer system **100**. In some embodiments, computer system **100** may comprise a single computer, a single server, or a cluster or collection of computers or servers, or a cloud of computers or servers. Typically, a cluster or collection of servers can be used when the demand on computer system **100** exceeds the reasonable capability of a single server or computer. In certain embodiments, computer system **100** may comprise a portable computer, such as a laptop computer. In certain other embodiments, computer system **100** may comprise a mobile device, such as a smartphone. In certain additional embodiments, computer system **100** may comprise an embedded system.

(27) Turning ahead in the drawings, FIG. **3** illustrates a block diagram of a system **300** that can be employed for database instance container deployment. System **300** is merely exemplary and embodiments of the system are not limited to the embodiments presented herein. The system can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements or modules of system **300** can perform various procedures, processes, and/or activities. In other embodiments, the procedures, processes, and/or activities can be performed by other suitable elements or modules of system **300**.

(28) In some embodiments, system **300** can include a deployment system **310**, a web server **320**, a container level system **330**, an orchestration system **340**, and/or a display system **350**. Deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and display system **350** can each be a computer system, such as computer system **100** (FIG. **1**), as described

above, and can each be a single computer, a single server, or a cluster or collection of computers or servers, or a cloud of computers or servers. Additional details regarding deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and display system **350** are described herein.

(29) In some embodiments, web server **320** can be in data communication through Internet **330** with user computers (e.g., **340**, **341**). In certain embodiments, user computers **340-341** can be desktop computers, laptop computers, smart phones, tablet devices, and/or other endpoint devices. Web server **320** can host one or more websites. In other embodiments, user computers **340-341** can be administrator computers.

(30) In many embodiments, deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and/or display system **350** can each comprise one or more input devices (e.g., one or more keyboards, one or more keypads, one or more pointing devices such as a computer mouse or computer mice, one or more touchscreen displays, a microphone, etc.), and/or can each comprise one or more display devices (e.g., one or more monitors, one or more touch screen displays, projectors, etc.). In these or other embodiments, one or more of the input device(s) can be similar or identical to keyboard **104** (FIG. **1**) and/or a mouse **110** (FIG. **1**). Further, one or more of the display device(s) can be similar or identical to monitor **106** (FIG. **1**) and/or screen **108** (FIG. **1**). The input device(s) and the display device(s) can be coupled to the processing module(s) and/or the memory storage module(s) of deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and/or display system **350** in a wired manner and/or a wireless manner, and the coupling can be direct and/or indirect, as well as locally and/or remotely. As an example of an indirect manner (which also may or may not be a remote manner), a keyboard-video-mouse (KVM) switch can be used to couple the input device(s) and the display device(s) to the processing module(s) and/or the memory storage module(s). In some embodiments, the KVM switch also can be part of deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and/or display system **350**. In a similar manner, the processing module(s) and the memory storage module(s) can be local and/or remote to each other.

(31) In many embodiments, deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and display system **350** can be configured to communicate with one or more user computers **340** and **341**. In some embodiments, user computers **340** and **341** also can be referred to as customer computers and/or administrator computers. In some embodiments, deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and/or display system **350** can communicate or interface (e.g. interact) with one or more user computers (such as user computers **340** and **341**) through a network or internet **330**. Internet **330** can be an intranet that is not open to the public. Accordingly, in many embodiments, deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and display system **350** (and/or the software used by such systems) can represent at least a portion of a back end of system **300** operated by an operator and/or administrator of system **300**, and user computers **340** and **341** (and/or the software used by such systems) can refer to a front end of system **300** used by one or more customers **350** and **351**, respectively. In some embodiments, customers **350** and **351** also can be referred to as users. In these or other embodiments, the operator and/or administrator of system **300** can manage system **300**, the processing module(s) of system **300**, and/or the memory storage module(s) of system **300** using the input device(s) and/or display device(s) of system **300**.

(32) Meanwhile, in many embodiments, deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and display system **350** also can be configured to communicate with one or more databases and one or more host servers **601**, **602**. In some embodiments, host servers **601**, **602** also can be part of a back end of system **300**. The one or more databases can comprise a product database that contains information about products, items, or SKUs sold by a retailer. The one or more databases can be stored on one or more memory storage modules (e.g., non-transitory memory storage module(s)), which can be similar or identical to the

one or more memory storage module(s) (e.g., non-transitory memory storage module(s)) described above with respect to computer system **100** (FIG. **1**). Also, in some embodiments, for any particular database of the one or more databases, that particular database can be stored on a single memory storage module of the memory storage module(s), and/or the non-transitory memory storage module(s) storing the one or more databases or the contents of that particular database can be spread across multiple ones of the memory storage module(s) and/or non-transitory memory storage module(s) storing the one or more databases, depending on the size of the particular database and/or the storage capacity of the memory storage module(s) and/or non-transitory memory storage module(s).

(33) The one or more databases can each comprise a structured (e.g., indexed) collection of data and can be managed by any suitable database management systems configured to define, create, query, organize, update, and manage database(s). Exemplary database management systems can include MySQL (Structured Query Language) Database, PostgreSQL Database, Microsoft SQL Server Database, Oracle Database, SAP (Systems, Applications, & Products) Database, and IBM DB2 Database.

(34) Meanwhile, communication between deployment system **310**, web server **320**, container level system **330**, orchestration system **340**, and/or display system **350**, the one or more host servers **601**, **602**, and/or the one or more databases can be implemented using any suitable manner of wired and/or wireless communication. Accordingly, system **300** can comprise any software and/or hardware components configured to implement the wired and/or wireless communication. Further, the wired and/or wireless communication can be implemented using any one or any combination of wired and/or wireless communication network topologies (e.g., ring, line, tree, bus, mesh, star, daisy chain, hybrid, etc.) and/or protocols (e.g., personal area network (PAN) protocol(s), local area network (LAN) protocol(s), wide area network (WAN) protocol(s), cellular network protocol(s), powerline network protocol(s), etc.). Exemplary PAN protocol(s) can comprise Bluetooth, Zigbee, Wireless Universal Serial Bus (USB), Z-Wave, etc.; exemplary LAN and/or WAN protocol(s) can comprise Institute of Electrical and Electronic Engineers (IEEE) 802.3 (also known as Ethernet), IEEE 802.11 (also known as WiFi), etc.; and exemplary wireless cellular network protocol(s) can comprise Global System for Mobile Communications (GSM), General Packet Radio Service (GPRS), Code Division Multiple Access (CDMA), Evolution-Data Optimized (EV-DO), Enhanced Data Rates for GSM Evolution (EDGE), Universal Mobile Telecommunications System (UMTS), Digital Enhanced Cordless Telecommunications (DECT), Digital AMPS (IS-136/Time Division Multiple Access (TDMA)), Integrated Digital Enhanced Network (iDEN), Evolved High-Speed Packet Access (HSPA+), Long-Term Evolution (LTE), WiMAX, etc. The specific communication software and/or hardware implemented can depend on the network topologies and/or protocols implemented, and vice versa. In many embodiments, exemplary communication hardware can comprise wired communication hardware including, for example, one or more data buses, such as, for example, universal serial bus(es), one or more networking cables, such as, for example, coaxial cable(s), optical fiber cable(s), and/or twisted pair cable(s), any other suitable data cable, etc. Further exemplary communication hardware can comprise wireless communication hardware including, for example, one or more radio transceivers, one or more infrared transceivers, etc. Additional exemplary communication hardware can comprise one or more networking components (e.g., modulator-demodulator components, gateway components, etc.)

(35) Turning ahead in the drawings, FIG. **4** illustrates a flow chart for a method **400**, according to an embodiment. Method **400** is merely exemplary and is not limited to the embodiments presented herein. Method **400** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, the activities of method **400** can be performed in the order presented. In other embodiments, the activities of method **400** can be performed in any suitable order. In still other embodiments, one or more of the activities of method **400** can be combined or skipped. In many embodiments, system **300** (FIG. **3**) can be suitable to perform

method **400** and/or one or more of the activities of method **400**. In these or other embodiments, one or more of the activities of method **400** can be implemented as one or more computer instructions configured to run at one or more processing modules and configured to be stored at one or more non-transitory memory storage modules, such as modules **512**, **532**, **534**, **542**, **544**, **552** (FIG. 5). Such non-transitory memory storage modules can be part of a computer system such as deployment system **310** (FIGS. 3 & 5), container level system **330** (FIGS. 3 & 5), orchestration system **340** (FIGS. 3 & 5), and/or display system **350**. The processing module(s) can be similar or identical to the processing module(s) described above with respect to computer system **100** (FIG. 1).

(36) Method **400** can comprise an activity **405** of cabling a plurality of host servers for network aggregation. For example, host servers **601**, **602** (FIGS. 5 & 6) can be cabled for network aggregation. Other embodiments contemplated herein may comprise any number of a plurality of host servers or, alternatively, a single host server. In many embodiments, host servers can include the necessary specifications to support running multiple containers and application instances at the respective host server. In some embodiments, the plurality of host servers can comprise a server farm created from a plurality of racks. In some embodiments, the host network of the plurality of host servers is designed with leaf-spine network topology.

(37) Method **400** also can comprise an activity **410** of allocating a pool of internet protocol (IP) addresses to each host server. More particularly, using FIG. 6 as an example, a method can comprise allocating a first pool **611** of a first plurality of IP addresses to a first host server **601**, and allocating a second pool **612** of a second plurality of IP addresses to a second server **602**. For example, the non-limiting block diagram of FIG. 6 shows a system **600** having a first server **601**, which comprises a first pool **611** of IP addresses, and also having a second server **602**, which comprises a second pool **612** of IP addresses. In some embodiments, the first plurality of IP addresses in the first pool **611** at the first server **601** are different from and non-overlapping with the second plurality of IP addresses of the second pool **612** at the second server **602**. In some embodiments, each host server is allocated with at least two IP addresses in the pool of IP addresses. The pool of IP addresses can comprise a pool of physical IP addresses and/or a pool of routable IP addresses. In some embodiments comprising a pool of routable IP addresses, there is no virtual network layer on the host server that is responsible to direct server traffic. IP addresses can be assigned directly to the bonded network interface or to multiple aliases created on the server.

(38) Returning to FIG. 4, method **400** can further comprise an activity **415** of creating a bonded network interface at a host server. More particularly, using FIG. 6 as an example, a method can comprise activities of creating a first bonded network interface **621** at the first host server **601** and creating a second bonded network interface **622** at the second host server **602**. For example, the non-limiting block diagram of FIG. 6 shows a first bonded network interface **621** created at the first host server **601** and a second bonded network interface **622** created at the second host server **602**. Thus, in some embodiments, a first host server of a server network can comprise a bonded network interface and a first plurality of internet protocol (IP) addresses in a first pool of IP addresses, and a second host server of the server network can comprise a bonded network interface and a second plurality of IP addresses in a second pool of plurality of IP addresses.

(39) In some embodiments, creating the bonded network interface for the respective host server comprises aggregating a plurality of network interface controllers (NIC) available at the host server in active-active mode. For example, in active-active mode, all the network interfaces in a bonded network interface are actively servicing network traffic. Different embodiments can utilize different implementations of active mode, such as but not limited to a first active-active mode, a second active-active mode, a third active-active mode, a fourth active-active mode, a fifth active-active mode, a sixth active-active mode, and a seventh active-active mode. A first active-active mode can comprise a balanced round robin. For example, if there are three physical interfaces in the bonded network interface, the first frame will go out to the first interface of the bonded network interface, the second frame will go out to the second interface of the bonded network interface, and the third

frame will go out to the third interface of the bonded network interface. In a second active-active mode, when an active interface face fails, the next active interface in line in the bonded network interface can be used for transmitting. In a third active-active mode, or XOR mode, the same active interface always can be selected for the same destination media access control (MAC) address. In a fourth active-active mode, or broadcast mode, everything can be transmitted to all active interfaces. In a fifth active-active mode, or dynamic link aggregation, the active interface can have the same link speed and duplex settings. Active interface selection in a fifth active-active mode can be done based on the hash policy or the XOR policy of the third active-active mode. A sixth active-active mode can be adaptive transmit load balancing, and can be done based on the present load on the active interfaces of the bonded network interface. The active interfaces under a lesser outgoing queue can be chosen. A seventh active-active mode can be similar to the sixth active-active mode, with the possible addition of receiving load balance. It is noted that various embodiments contemplated herein can utilize any of the described active-active modes. Furthermore, network bonding can require certain conditions to be met at the switch level. Thus, the switch to which the bonded network interface is coupled can support the specific active-active mode being utilized in the system.

(40) In some embodiments, all of the available NICs at a host server may be aggregated to create the bonded network interface at that host server. More particularly, creating the first bonded network interface at the first host server can comprise creating the first bonded network interface by aggregating a plurality of network interface controllers available in the first host server when the first host server is in an active-active mode, and creating the second bonded network interface at the second host server can comprises creating the second bonded network interface by aggregating a plurality of network interface controllers available in the second host server when the second host server is in an active-active mode. By creating a bonded network interface with the host server in active-active mode, maximum network bandwidth for high throughput and availability on the host server is achieved. It is contemplated, however, that other modes also may be utilized in other embodiments, such as but not limited to aggregating a plurality of network interface controllers available in the host server when the host server is in an active-passive mode.

(41) Returning back to FIG. 4, method **400** also can comprise an activity **420** of receiving a request from an input device to deploy or otherwise create a database instance container at a host server. In more particular embodiments, a method can comprise receiving a request from an input device to deploy one or more database instance containers at a first host server, and a request from the input device to deploy one or more of database instance containers at a second host server. For example, a method can comprise receiving a request from an input device to deploy one or more of a first database instance container and a third database instance container at a first host server, and receiving a request from the input device to deploy one or more of a second database instance container and a fourth database instance container at a second host server. In some embodiments, the input device can determine whether the first host server and the second host server are in the same or separate fault zones. The input device can be one of the input devices of the system **300** (FIG. 3) or one of user computers **340**, **341** (FIG. 3). In some embodiments, using FIG. 5 as an example, deployment module **512** of deployment system **310** of system **300** receives a request from an input device to deploy or otherwise create a database instance container at a host server. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can receive a request from an input device to deploy or otherwise create a database instance container at a host server.

(42) Referring to FIG. 4, again, method **400** also can comprise an activity **425** of transmitting an instruction from an output device to deploy or otherwise create a database instance container at a host server. In more particular embodiments, a method can comprise transmitting an instruction from an output device to deploy one or more database instance containers at a first host server on a host server network responsive to the request from the input device, and transmitting an instruction from the output device to deploy one or more database instance containers at a second host server

network responsive to the request from the input device. For example, a method can comprise transmitting an instruction from an output device to deploy the one or more of the first database instance container and the third database instance container at the first host server responsive to the request from the input device, and transmitting an instruction from the output device to deploy the one or more of the second database instance container and the fourth database instance container at the second host server responsive to the request from the input device. The output device can be one of the output devices of the system **300** (FIG. 3) or user computers **340**, **341** (FIG. 3). In some embodiments, using FIG. 5 as an example, deployment module **512** of deployment system **310** of system **300** is configured to transmit instructions to the output device to deploy or otherwise create a database instance container at a host server of a host server network. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can transmit instructions to the output device to deploy or otherwise create a database instance container at a host server of a host server network.

(43) Referring back to FIG. 4, method **400** can further comprise an activity **430** of creating a database instance container at the host server. As used herein, a database instance container can comprise an application instance container. As such, a database instance container can comprise an application or database deployed within a container on a host server. In more particular embodiments, a method can comprise an activity of creating a plurality of database instance containers at a first host server of a host server network and a plurality of database instance containers at a second host server of the host server network. In some embodiments, creating the database instance container at a host server comprises installing a database on the first host server, and then creating a container at the first host server by using one IP address from the pool of IP addresses of the host server to create a network alias on the bonded network interface at the host server. A routable IP address from the pool of IP addresses can be assigned to the network alias. After the container is created, an installation path of the database can be mapped to a directory inside the container such that the database can then be started inside the container. In particular embodiments comprising a plurality of host servers, a method can comprise creating the first database instance container at the first host server by using one IP address from the first pool of the first plurality of IP addresses of the first host server to create a first virtual IP address on the first bonded network interface at the first host server, and creating the second database instance container at the second host server by using one IP address from the second pool of the second plurality of IP addresses of the second host server to create a second virtual IP address on the second bonded network interface at the second host server.

(44) Turning to FIG. 5, in some embodiments, deployment module **512** of deployment system **310** of system **300** creates a database instance container at the host server. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can create a database instance container at the host server. In some embodiments, database instance containers can be deployed using Dockers or other container services. In some embodiments, systems and methods can comprise virtual network interface on top of the bonded network interface for every database instance container. The virtual IP addresses can belong to the same virtual local area network (VLAN) or a different VLAN depending upon the desired security requirements. Each database instance container created can be created with predetermined required system resources, such as but not limited to CPU and memory.

(45) In some embodiments, creating a database instance container at a host server can comprise creating a database instance container belonging to a cluster at a host server. In more particular embodiments, multiple database instance containers created or otherwise deployed at a host server may belong to different and non-overlapping clusters. For example, a method can comprise deploying a first database instance container at a first host server, the first database instance container belonging to a first cluster, deploying a second database instance container at a second host server, the second database instance container belonging to the first cluster, deploying a third database instance container at the first host server, the third database instance container belonging to the first cluster, and deploying a fourth database instance container at the second host server, the

fourth database instance container belonging to the second cluster. The first cluster and the second cluster of such embodiments can be different from and non-overlapping with one another. The non-limiting block diagram of FIG. 6 shows, by way of example, a first database instance container (D.I.C.) **651** of a first cluster **641** at a first host server **601**, a second database instance container **652** of a second cluster **642** at the first host server **601**, a third database instance container **653** of the first cluster **641** at a second host server **602**, and a fourth database instance container **654** of the second cluster **642** at the second host server **602**.

(46) By distributing database instance containers of a cluster to different host servers, system performance is improved in case of a crash or other hardware malfunction of the host server. Some embodiments can be designed to be rack or fault domain aware. Thus, clusters can be created with nodes or database instance containers in different fault tolerant zones. If a host server or other hardware has a malfunction, then the malfunction results in only the loss of the database instance container running on the host server or hardware, and does not result in the loss of the entire cluster. Moreover, by deploying multiple database instance containers on a single host server, the capacity for database instances can be doubled (or more), thereby saving costs for the administrator.

(47) Returning to FIG. 4, method **400** can further comprise an activity **435** of binding the database instance container to the bonded network interface and also a first IP address from the pool of IP addresses of the host server. Thus, the database deployed inside the container has direct access to the host level system, storage, and network resources. In some embodiments, binding the database instance container to the IP address of the host server comprises binding the database instance container to a physical IP address of the host server. More particularly, a method can comprise binding the database instance container to a bonded network interface and also to a first IP address of the pool of IP addresses of the host server of the host server network such that a database deployed inside the database instance container has direct access to the host server. In embodiments comprising a plurality of host servers and database instance containers, a method can comprise the activities of binding a first database instance container to the first bonded network interface and also to a first IP address of the first pool of the first plurality of IP addresses of the first host server such that a first database deployed inside the first database instance container has direct access to the first host server, and binding a second database instance container to the second bonded network interface and also to a second IP address of the second pool of the second plurality of IP addresses of the second host server such that a second database inside the second database instance container has direct access to the second host server.

(48) Deployment of database instance container by binding the database instance container to a bonded network interface and also an IP address of the host server is advantageous because this deployment enables the database deployed within the database instance container to have direct access to the system resources and avoid any resource virtualization. Referring to FIG. 5, in some embodiments, deployment module **512** of deployment system **310** of system **300** binds the database instance container to the bonded network interface and also to a first IP address from the pool of IP addresses of the host server. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can bind the database instance container to the bonded network interface and also to a first IP address from the pool of IP addresses of the host server. In some embodiments, each IP address bound to a database instance container can be assigned with an addressable hostname and/or public name.

(49) In some embodiments, binding the database instance container to an IP address from the pool of IP addresses of the host server can comprise allocating the IP address from the pool of IP addresses of the host server to a database instance container. In more particular embodiments, allocation of the IP address from the pool of IP addresses of the host server can be automatic or otherwise automated. For example, a method can comprise automatically allocating a first IP address of the first host server to the first database instance container, automatically allocating a

second IP address of the second host server to the second database instance container, automatically allocating a third IP address of the first host server to the third database instance container, automatically allocating a fourth IP address of the second host server to the fourth database instance container, and automatically allocating an additional IP address of either one of the first host server or the second host server to an additional database instance container for binding to the respective host server. In some embodiments, allocation module **544** of orchestration system **340** is configured to automatically allocate an IP address of a host server to a database instance container. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can automatically allocate the IP address from the pool of IP addresses of the host server to a database instance container. In some embodiments, automatic allocation of an IP address of a pool of IP addresses can be based up on the availability of the IP addresses in the pool of the IP addresses of the particular host server. Orchestration tools developed using products such as Chef, Jenkins, Github, and Rundeck can be utilized to automate deployment of database instance containers.

(50) As referenced above, some embodiments can comprise a plurality of clusters, a plurality of database containers, and a plurality of host servers. In these and other embodiments, binding the database instance container to an IP address from the pool of IP addresses of the host server can comprise binding the first database instance container of the first cluster to a first IP address of the first plurality of IP addresses of the first host server such that a first database deployed inside the first database instance container has direct access to the first host server, binding the second database instance container of the first cluster to a second IP address of the second plurality of IP addresses of the second host server such that a second database deployed inside the second database instance container has direct access to the second host server, binding the third database instance container of the second cluster to a third IP address of the first plurality of IP addresses of the first host server such that a third database deployed inside the third database instance container has direct access to the first host server, and binding the fourth database instance container of the second cluster to a fourth IP address of the second plurality of IP addresses of the second host server such that a fourth database deployed inside the fourth database instance container has direct access to the second host server.

(51) Continuing with FIG. **4**, method **400** can further comprise an activity of limiting an amount of a central processing unit (CPU) allocated to each database instance container. For example, a method can comprise limiting one or more different or same amounts of a CPU of the system allocated to each of the first, second, third, and fourth database instance containers. When creating a container on the host server, the container instance is allocated a specific number of CPU cores. If the container malfunctions and consumes excessive amounts of CPU capacity, the container could never consume more than what is allocated to the container. Referring to FIG. **5**, in some embodiments, a CPU module **532** of the container level system **330** is configured to limit an amount of a CPU allocated to each database instance container. In other embodiments, any other modules **512**, **534**, **542**, **544**, **552** of system **300** can be configured to limit an amount of a CPU allocated to each database instance container.

(52) Method **400** of FIG. **4** can further comprise an activity of guaranteeing an amount of a CPU allocated to each database instance container. For example, a method can comprise an activity of guaranteeing one or more different or same amounts of the CPU of the system allocated to each of the first, second, third, and fourth database instance containers. Referring to FIG. **5**, in some embodiments, a CPU module **532** of the container level system **330** is configured to guarantee an amount of a CPU allocated to each database instance container. In other embodiments, any other modules **512**, **534**, **542**, **544**, **552** of system **300** can be configured to guarantee an amount of a CPU allocated to each database instance container.

(53) Method **400** of FIG. **4** can further comprise an activity of limiting an amount of memory of the system allocated to each database instance container. For example, a method can comprise an

activity of limiting one or more different or same amounts of memory of the system allocated to each of the first, second, third, and fourth database instance containers. Limiting the amount of memory allocated to each database instance container can be advantageous to the system. For example, a memory leak in the database running inside the container will not affect the other containers on the same host server by consuming all the system memory. Referring to FIG. 5, in some embodiments, a memory module **534** of the container level system **330** is configured to limit an amount of memory allocated to each database instance container. In other embodiments, any other modules **512, 532, 542, 544, 552** of system **300** can be configured to limit an amount of memory allocated to each database instance container.

(54) Method **400** of FIG. 4 can further comprise an activity of guaranteeing an amount of memory of the system allocated to each database instance container. For example, a method can comprise guaranteeing one or more different or same amounts of the memory of the system allocated to each of the first, second, third, fourth database instance containers. Referring to FIG. 5, in some embodiments, a memory module **534** of the container level system **330** is configured to guarantee an amount of a memory allocated to each database instance container. In other embodiments, any other modules **512, 532, 542, 544, 552** of system **300** can be configured to guarantee an amount of a memory allocated to each database instance container.

(55) Method **400** of FIG. 4 can further comprise an activity **440** of mapping a persistent file system. Mapping the persistent file system can comprise mapping a persistent file system for each host server to host level volumes. In some embodiments, each host server can comprise multiple file system partitions. In such embodiments, a full partition to a container can be mapped such that a container will be able to see all the files on the file system. Alternatively, different directories on a file system can be created, and a directory can be mapped to the container such that a container will be able to see all the files within that specific directory. In some embodiments, mapping a persistent file system for each host server to host level volumes can comprise mapping a directory structure inside the container such that a volume of the directory structure inside the container is mapped to a directory and/or partition outside the container. For example, a method can comprise an activity of mapping a first persistent file system of a first host server to a predetermined first host level volume, and mapping a second persistent file system of the second host server to a predetermined second host level volume. Referring to FIG. 5, in some embodiments, an orchestration module **542** of the orchestration system **340** is configured to map a persistent file system of each host server. In other embodiments, any other modules **512, 532, 534, 544, 552** of system **300** can be configured to map a persistent file system of each host server.

(56) Method **400** of FIG. 4 can further comprise an activity **445** of storing data of a database instance container outside the database instance container and in the persistent file system. For example, a method can comprise storing application data of a first database instance container in a first persistent file system of a first host and outside the first database instance container, storing application data of a second database instance container in a second persistent file system of a second host server and outside the second database instance container, storing application data of a third database instance container in the first persistent file system of the first host and outside the third database instance container, and storing application data of a fourth database instance container in the second persistent file system of the second host server and outside the fourth database instance container. The non-limiting block diagram of FIG. 6 illustrates, by way of example, a first persistent file system **631** at a first host server **601** outside the database instance containers of the first host server **601**, and a second persistent file system **632** at a second host server **602** outside the database instance containers of the second host server **602**. Referring to FIG. 5, in some embodiments, an orchestration module **542** of the orchestrations system **340** is configured to store data of a database instance container outside the database instance container and in the persistent file system. In other embodiments, any other modules **512, 532, 534, 544, 552** of system **300** can be configured to store data of a database instance container outside the database

instance container and in the persistent file system.

(57) In some embodiments, storing data of a database instance container outside the database instance container and in the persistent file system comprises storing all data of the database instance container outside the database instance container and in the persistent file system. As used herein, all data references components of a particular database instance container deployment, the data files, the log files, and any other data that needs to be persisted. Storing data of the database instance container outside the database instance container and in a persistent file system is advantageous to virtual machines, which use ephemeral storage that is susceptible to data loss. Moreover, storing components of a particular database container deployment outside the database instance container is advantageous because any change to the specific deployment configuration of the database instance container does not warrant rebuilding of the container images.

(58) Method **400** can further comprise an activity **450** of facilitating a display on a device of the host server at which the database instance container has been deployed. In some embodiments, a user interface communicates to an application programming interface (API) exposed on all the host servers to retrieve (a) information on the containers that each host server is running and (b) the specifications of the host server and the containers operating thereon. For example, a method can comprise activities of facilitating a display on a device of the first host server at which one or more of the first database instance container and the third database instance container has been deployed, and facilitating a display on a device of the second host server at which one or more of the second database instance container and the fourth database instance container has been deployed. In some embodiments, a display module **552** of the display system **550** is configured to facilitate a display on a device at the host server at which the database instance container has been deployed. In other embodiments, any other modules **512**, **532**, **534**, **542**, **544** of system **300** can be configured to facilitate a display on a device at the host server at which the database instance container has been deployed.

(59) In some embodiments, method **400** also can comprise an activity of facilitating a display on a device of a user interface configured to capture requirements of a database instance container, monitor host servers and clusters, and allow a user or administrator to configure clusters, host servers, and database instance containers. Examining FIG. 5, in some embodiments, a display module **552** of the display system **550** is configured to facilitate a display on a device of a user interface. In other embodiments, any other modules **512**, **532**, **534**, **542**, **544** of system **300** can be configured to facilitate a display on a device of a user interface.

(60) Returning to FIG. 4, method **400** also can comprise an activity **455** of eliminating or removing a database instance container from a host server. For example, a method can comprise eliminating at least one of the first database instance container or the second database instance container from a host server.

(61) Upon elimination of a database instance container, method **400** can comprise activities **460** of deallocating an IP address from a database instance container and returning the IP address to the pool of IP addresses of the host server. In more particular embodiments, a method can comprise the activities of automatically deallocating a first IP address of the first host server to the first database instance container, automatically deallocating a second IP address of the second host server to the second database instance container, automatically deallocating a third IP address of the first host server to the third database instance container, automatically deallocating a fourth IP address of the second host server to the fourth database instance container, and automatically deallocating an additional IP address of either one of the first host server or the second host server from an additional database instance container at the respective host server. Upon deallocation of an IP address to a database instance container, the IP address may be returned to the pool of IP addresses of the host server to which the database instance container had previously been bound. For example, if a first database instance container is eliminated, a method can comprise returning the first IP address of the first database instance container to the first pool of the first plurality of IP

addresses of the first host server, and if a second database instance container is eliminated, a method can comprise returning the second IP address of the second database instance container to the second pool of the second plurality of IP addresses of the second host server.

(62) Returning to FIG. 5, in some embodiments, allocation module **544** of orchestration system **340** is configured to automatically deallocate an IP address of a host server to a database instance container. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can automatically deallocate the IP address from the pool of IP addresses of the host server to a database instance container.

(63) Method **400** in FIG. 4 can further comprise an activity of selecting one host server of the first host server or the second host server for binding of at least one additional database instance container to an IP address of the one of the first host server or the second host server based upon at least one of the one or more of (a) resource availability of the first host server relative to the second host server or (b) a number of database instance containers already bound to the first host server relative to the second host server. In some embodiments, selecting a host server for binding of a database instance container is determined by a set of rules and/or an algorithm. Turning to FIG. 5, in some embodiments, orchestration module **542** of orchestration system **340** comprises information about all the switches in the network and is configured to obtain port number/mac address information of all of the switches in the network. In a container configuration, a particular IP address of the host server can be defined to be assigned or allocated to a database container instance. Before assigning or allocating the IP address to the database instance container, the orchestration system **340** can determine which host server has capacity to run that database instance container. The orchestration system **340** can then log into the switch where one of the physical NICs is coupled, configure the VLAN on that switch port, and start container binding the VLAN to the NIC with the IP provided. Thus, no virtual network layer is utilized.

(64) Returning to FIG. 4, method **400** can further comprise an activity **465** of determining if a host server has sufficient space to create a redundant array of independent discs (RAID). More particularly, a method can comprise specifying an amount of storage space required for an additional database instance container and determining which one host server of the first host server and the second host server has sufficient space to create a RAID volume.

(65) Method **400** can further comprise an activity **470** deploying an additional database container. For example, upon determining which host server has sufficient space to create a RAID volume, a method can comprise deploying an additional database instance container to the one host server of the first host server or the second host server determined to have sufficient space to create the RAID volume. In more particular embodiments, deploying an additional database container can comprise deploying an additional database instance container to a cluster if utilization of the cluster exceeds a defined threshold. For example, deploying an additional database cluster can comprise deploying a first additional database instance container to the first cluster if utilization of the first cluster exceeds a defined threshold, and deploying a second additional database instance container to the second cluster if utilization of the second cluster exceeds the defined threshold. Reviewing FIG. 5, in some embodiments, deployment module **512** of the deployment system **310** is configured to deploy an additional database container. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can be configured to deploy an additional database container. While these deployments of database instance containers are described with respect to additional database instance containers, it also is contemplated that similar activities can be performed for deployment of any database instance containers, including but not limited to a first database instance container deployed to or otherwise created at a first host server.

(66) Method **400** in FIG. 4 can further comprise an activity **470** of eliminating an additional database instance container. Eliminating an additional database instance container can comprise eliminating the additional database instance if utilization of the cluster to which the database instance container belongs falls below a defined threshold. For example, a method can comprise

eliminating a first additional database instance container from a first cluster if utilization of the first cluster falls below the defined threshold, and/or eliminating a second additional database instance container from a second cluster if utilization of the second cluster falls below the defined threshold. Returning to FIG. 5, in some embodiments, deployment module **512** of the deployment system **310** is configured to eliminate an additional database container. In other embodiments, any other modules **532**, **534**, **542**, **544**, **552** of system **300** can be configured to eliminate an additional database container. While these embodiments are described with respect to additional database instance containers, it also is contemplated that similar activities can be performed for deployment of any database instance containers, including but not limited to a first database instance container deployed to or otherwise created at a first host server.

(67) FIG. 5 illustrates a block diagram of a portion of system **300** comprising deployment **310**, container level system **330**, orchestration system **340**, and display system **350** according to the embodiment shown in FIG. 3. Each of deployment **310**, container level system **330**, orchestration system **340**, and/or display system **350** is merely exemplary and not limited to the embodiments presented herein. Each of deployment **310**, container level system **330**, orchestration system **340**, and/or display system **350** can be employed in many different embodiments or examples not specifically depicted or described herein. In some embodiments, certain elements or modules of deployment **310**, container level system **330**, orchestration system **340**, and/or display system **350** can perform various procedures, processes, and/or acts. In other embodiments, the procedures, processes, and/or acts can be performed by other suitable elements or modules.

(68) In many embodiments deployment system **310** can comprise a non-transitory storage module such as module **512**, container level system **330** can comprise non-transitory storage modules such as modules **532**, **534**, orchestration system **340** can comprise non-transitory storage modules such as modules **542**, **544**, and display system **350** can comprise a non-transitory storage module such as module **552**. Module **512** can be referred to as deployment module **512**, module **532** can be referred to as CPU module **532**, module **534** can be referred to as memory module **534**, module **542** can be referred to as orchestration module **542**, module **544** can be referred to as allocation module **544**, and module **552** can be referred to as display module **552**.

(69) In many embodiments, deployment module **512** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **400** (FIG. 4) (e.g. activity **420** of receiving a request from an input device to deploy a database instance container at the host server, activity **425** of transmitting an instruction from an output device to deploy the database instance container at the host server, activity **430** of creating a database instance container at the host server, and activity **435** of binding the database instance container to the bonded network interface and also an IP address from the pool of IP addresses of the host server). In some embodiments, CPU module **532** can store computing instructions configured to run on one or more processing modules and perform one or more acts of a method (e.g. an activity of guaranteeing and/or limiting an amount of CPU of the system allocated to each database instance container). In some embodiments, memory module **534** can store computing instructions configured to run on one or more processing modules and perform one or more acts of a method (e.g. an activity of guaranteeing and/or limiting an amount of memory of the system allocated to each database instance container). In some embodiments, orchestration module **542** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **400** (FIG. 4) (e.g. activity **440** of mapping a persistent file system and activity **445** storing data of the database instance container outside the database instance container and in the persistent file system). In some embodiments, allocation module **544** can store computing instructions configured to run on one or more processing modules and perform one or more acts of a method (e.g. allocating and deallocating an IP address of a host server to a database instance container). In some embodiments, display module **552** can store computing instructions configured to run on one or more processing modules and perform one or more acts of method **400** (FIG. 4)

(e.g. activity 450 of facilitating a display on a device of the host server at which the database instance container has been deployed).

(70) In some embodiments, orchestration system can comprise a VLAN orchestration module. The VLAN orchestration module, or any other modules 512, 532, 534, 542, 544, 552, can be configured to configure VLANs on the switch to which the host servers are coupled. The VLAN orchestration module can be configured to automatically detect a fleet of switches coupled to a cluster and, based on the requirement, configure switch ports of the VLAN depending upon which database instance container is going to run on the bare metal host coupled to that switch port.

(71) Various embodiments described herein allow a user to deploy multiple database instance containers to optimally leverage system resources, which results in reducing the overall hardware procurement costs, extending the available capacity of the system, and lowering of the effective license costs. Some embodiments provide the efficiency of a bare metal system while simultaneously avoiding the inefficiency of virtualized system caused by resource virtualization layers. For example, some embodiments described herein are devoid of a virtualization layers between the host server and the database instance container.

(72) To illustrate the efficiency of the contemplated embodiments, performance tests were completed. The performance test environment included a production cluster on bare metal and a database instance container cluster (using production hardware). The test was performed by an application “e-Receipts”. All clusters were created with four nodes in each of two datacenters for a total of eight nodes. Cassandra applications were utilized across the test environments, and the configurations/setup of the Cassandra applications was similar across the test environments. A test load was continuously executed from four application instances, two from each data center, accessing the local datacenter nodes. Each application instance wrote/read 1,000,000 rows. Table 1 provides a summary of a test environment configuration of the performance test.

(73) TABLE-US-00001 TABLE 1 Database Instance Hardware Resources Bare Metal Containers
CPU 32 Cores 16 Cores Memory 190 GB 80 GB Disk 6 TB 6 TB (single RAID0 (14 SSDs-JBOD) volume) Disk Throughput Test Write 1.2 GB/s 1.3 GB/s Read 4.3 GB/s 4.4 GB/s

(74) Table 2 provides a number comparison of the performance test of the e-Receipts application on the bare metal and database instance containers systems. The asterisk in Table 2 notes that a difference in I/O throughput was caused by the different storage RAID configurations. The results of the performance testing indicate that the database instance container solution performs similar to bare metal systems.

(75) TABLE-US-00002 TABLE 2 Comparison (+/-3% Bare Database Instance Margin of Error)
Metal Containers Reads Per Second 4615.72 6778.57 Average Latency (in 1.49 0.60 milliseconds (ms)) Writes Per Second 8332.02 8333.33 Average Latency (in ms) 0.72* 0.46*

(76) Although database instance container deployment has been described with reference to specific embodiments, it will be understood by those skilled in the art that various changes may be made without departing from the spirit or scope of the disclosure. Accordingly, the disclosure of embodiments is intended to be illustrative of the scope of the disclosure and is not intended to be limiting. It is intended that the scope of the disclosure shall be limited only to the extent required by the appended claims. For example, to one of ordinary skill in the art, it will be readily apparent that any element of FIGS. 1-6 may be modified, and that the foregoing discussion of certain of these embodiments does not necessarily represent a complete description of all possible embodiments. For example, one or more of the procedures, processes, or activities of FIG. 4 may include different procedures, processes, and/or activities and be performed by many different modules, in many different orders.

(77) All elements claimed in any particular claim are essential to the embodiment claimed in that particular claim. Consequently, replacement of one or more claimed elements constitutes reconstruction and not repair. Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to

problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be construed as critical, required, or essential features or elements of any or all of the claims, unless such benefits, advantages, solutions, or elements are stated in such claim.

(78) Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

Claims

1. A system comprising: one or more processors; and one or more non-transitory computer-readable media storing computing instructions that, when executed on the one or more processors, cause the one or more processors to perform operations comprising: providing a bonded network interface on a host server, the host server comprising a plurality of internet protocol (IP) addresses; binding a first database instance container to a first IP address of the plurality of IP addresses of the host server, wherein the first database instance container belongs to a first cluster, and wherein binding the first database instance container to the first IP address further comprises accessing a switch comprising a port coupled to a network interface controller of a first plurality of network interface controllers in the host server; and binding a second database instance container to a second IP address of the plurality of IP addresses of the host server, wherein: the second database instance container belongs to a second cluster that is different from and non-overlapping with the first cluster; the first cluster has a different fault tolerance than the second cluster; a first database deployed inside the first database instance container has direct access to the host server; a second database deployed inside the second database instance container has direct access to the host server; and binding the first database instance container to the first IP address further comprises binding the first database instance container to the first IP address without a virtual network layer.
2. The system of claim 1, wherein the operations further comprise: storing application data of the first database instance container in a first persistent file system and outside the first database instance container; storing application data of a third database instance container in the first persistent file system and outside the third database instance container; storing application data of the second database instance container in a second persistent file system and outside the second database instance container; and storing application data of a fourth database instance container in the second persistent file system and outside the fourth database instance container.
3. The system of claim 1, wherein the operations further comprise: automatically allocating and deallocating the first IP address to the first database instance container; automatically allocating and deallocating the second IP address to the second database instance container; automatically allocating and deallocating a third IP address of a first host server to a third database instance container; and automatically allocating and deallocating a fourth IP address of a second host server to a fourth database instance container.
4. The system of claim 1, wherein the operations further comprise: deploying an additional database instance container to the first cluster when utilization of the first cluster exceeds a defined threshold; deploying the additional database instance container to the second cluster when utilization of the second cluster exceeds the defined threshold; eliminating the additional database instance container from the first cluster when utilization of the first cluster falls below the defined threshold; and eliminating the additional database instance container from the second cluster when utilization of the second cluster falls below the defined threshold.
5. The system of claim 1, wherein the operations further comprise: aggregating the first plurality of network interface controllers available in a first host server to create a first bonded network interface in a first active-active mode; and aggregating a second plurality of network interface

controllers available in a second host server to create a second bonded network interface in a second active-active mode, wherein the host server comprises the first host server and the second host server; limiting one or more amounts of a central processing unit (CPU) of the system allocated to one or more of the first database instance container, the second database instance container, a third database instance container, or a fourth database instance container; guaranteeing one or more amounts of the CPU of the system allocated to one or more of the first database instance container, the second database instance container, the third database instance container, or the fourth database instance container; limiting one or more amounts of memory of the system allocated to one or more of the first database instance container, the second database instance container, the third database instance container, or the fourth database instance container; and guaranteeing one or more amounts of the memory of the system allocated to one or more of the first database instance container, the second database instance container, the third database instance container, or the fourth database instance container.

6. The system of claim 1, wherein the operations further comprise: receiving a first request from an input device to deploy one or more of the first database instance container or a third database instance container at a first host server; receiving a second request from the input device to deploy one or more of the second database instance container or a fourth database instance container at a second host server, wherein the host server comprises the first host server and the second host server; transmitting a first instruction from an output device to deploy the one or more of the first database instance container or the third database instance container at the first host server responsive to the first request from the input device to deploy the one or more of the first database instance container or the third database instance container at the first host server; transmitting a second instruction from the output device to deploy the one or more of the second database instance container or the fourth database instance container at the second host server responsive to the second request from the input device to deploy the one or more of the second database instance container or the fourth database instance container on the second host server; facilitating displaying on a device of the first host server at which the one or more of the first database instance container or the third database instance container has been deployed; and facilitating displaying on a device of the second host server at which the one or more of the second database instance container or the fourth database instance container has been deployed.

7. The system of claim 1, wherein: providing the bonded network interface on the host server further comprises: providing a first bonded network interface at a first host server to create a first bonded network interface in a first active-active mode by aggregating the first plurality of network interface controllers available in the first host server; and creating a second bonded network interface at a second host server to create the second bonded network interface in a second active-active mode by aggregating a second plurality of network interface controllers available in the second host server, wherein the host server comprises the first host server and the second host server; and the operations further comprise: creating the first database instance container at the first host server by using one IP address from a first pool of a first plurality of IP addresses of the first host server to create the first IP address on the first bonded network interface at the first host server; creating the second database instance container at the second host server by using one IP address from a second pool of a second plurality of IP addresses of the second host server to create the second IP address on the second bonded network interface at the second host server; eliminating at least one of the first database instance container or the second database instance container; when the first database instance container is eliminated, returning the first IP address of the first database instance container to the first pool of the first plurality of IP addresses of the first host server; and when the second database instance container is eliminated, returning the second IP address of the second database instance container to the second pool of the second plurality of IP addresses of the second host server.

8. The system of claim 1, wherein the operations further comprise: mapping a first persistent file

system of a first host server to a predetermined first host level volume; mapping a second persistent file system of a second host server to a predetermined second host level volume, wherein the host server comprises the first host server and the second host server; storing data for the first database instance container outside the first database instance container and in the first persistent file system; storing data for the second database instance container outside the second database instance container and in the second persistent file system; binding a third database instance container of the first cluster to a first bonded network interface and also to a third IP address of a first pool of a first plurality of IP addresses of the first host server such that a third database deployed inside the third database instance container has direct access to the first host server; and binding a fourth database instance container of the second cluster to a second bonded network interface and also to a fourth IP address of a second pool of a second plurality of IP addresses of the second host server such that a fourth database deployed inside the fourth database instance container has direct access to the second host server.

9. The system of claim 1, wherein the operations further comprise: selecting one of a first host server or a second host server for binding of at least one additional database instance container to (i) an IP address of the first host server or (ii) an IP address of the second host server based upon at least one of one or more of: resource availability of the first host server relative to the second host server; or a number of database instance containers already bound to the first host server relative to the second host server, wherein the host server comprises the first host server and the second host server; when utilization of the first cluster exceeds a defined threshold, deploying a first additional database instance container to the first cluster; when utilization of the second cluster exceeds the defined threshold, deploying a second additional database instance container to the second cluster; when utilization of the first cluster falls below the defined threshold, eliminating a database instance container from the first cluster; when utilization of the second cluster falls below the defined threshold, eliminating a database instance container from the second cluster; specifying an amount of storage space required for an additional database instance container; determining which one of the first host server or the second host server has sufficient space to create a redundant array of independent discs (RAID) volume; deploying the additional database instance container to the one of the first host server or the second host server determined to have sufficient space to create the RAID volume; and before binding the first database instance container and also before binding the second database instance container, receiving one or more requests from an electronic device to: bind the first database instance container; bind the second database instance container; or set the different fault tolerance for the first cluster and the second cluster.

10. A method being implemented via execution of computing instructions configured to run on one or more processors and stored at one or more non-transitory computer-readable media, the method comprising: providing a bonded network interface on a host server, the host server comprising a plurality of internet protocol (IP) addresses; binding a first database instance container to a first IP address of the plurality of IP addresses of the host server, wherein the first database instance container belongs to a first cluster, and wherein binding the first database instance container to the first IP address further comprises accessing a switch comprising a port coupled to a network interface controller of a first plurality of network interface controllers in the host server; and binding a second database instance container to a second IP address of the plurality of IP addresses of the host server, wherein: the second database instance container belongs to a second cluster that is different from and non-overlapping with the first cluster; the first cluster has a different fault tolerance than the second cluster; a first database deployed inside the first database instance container has direct access to the host server; a second database deployed inside the second database instance container has direct access to the host server; and binding the first database instance container to the first IP address further comprises binding the first database instance container to the first IP address without a virtual network layer.

11. The method of claim 10, further comprising: storing application data of the first database

instance container in a first persistent file system and outside the first database instance container; storing application data of a third database instance container in the first persistent file system and outside the third database instance container; storing application data of the second database instance container in a second persistent file system and outside the second database instance container; and storing application data of a fourth database instance container in the second persistent file system and outside the fourth database instance container.

12. The method of claim 10, further comprising: automatically allocating and deallocating the first IP address to the first database instance container; automatically allocating and deallocating the second IP address to the second database instance container; automatically allocating and deallocating a third IP address of a first host server to a third database instance container; and automatically allocating and deallocating a fourth IP address of a second host server to a fourth database instance container.

13. The method of claim 10, further comprising: deploying an additional database instance container to the first cluster when utilization of the first cluster exceeds a defined threshold; deploying the additional database instance container to the second cluster when utilization of the second cluster exceeds the defined threshold; eliminating the additional database instance container from the first cluster when utilization of the first cluster falls below the defined threshold; and eliminating the additional database instance container from the second cluster when utilization of the second cluster falls below the defined threshold.

14. The method of claim 10, further comprising: aggregating the first plurality of network interface controllers available in a first host server to create a first bonded network interface in a first active-active mode; and aggregating a second plurality of network interface controllers available in a second host server to create a second bonded network interface in a second active-active mode, wherein the host server comprises the first host server and the second host server; limiting one or more amounts of a central processing unit (CPU) of a system allocated to one or more of the first database instance container, the second database instance container, a third database instance container, or a fourth database instance container; guaranteeing one or more amounts of the CPU of the system allocated to one or more of the first database instance container, the second database instance container, the third database instance container, or the fourth database instance container; limiting one or more amounts of memory of the system allocated to one or more of the first database instance container, the second database instance container, the third database instance container, or the fourth database instance container; and guaranteeing one or more amounts of the memory of the system allocated to one or more of the first database instance container, the second database instance container, the third database instance container, or the fourth database instance container.

15. The method of claim 10, further comprising: receiving a first request from an input device to deploy one or more of the first database instance container or a third database instance container at a first host server; receiving a second request from the input device to deploy one or more of the second database instance container or a fourth database instance container at a second host server, wherein the host server comprises the first host server and the second host server; transmitting a first instruction from an output device to deploy the one or more of the first database instance container or the third database instance container at the first host server responsive to the first request from the input device to deploy the one or more of the first database instance container or the third database instance container at the first host server; transmitting a second instruction from the output device to deploy the one or more of the second database instance container or the fourth database instance container at the second host server responsive to the second request from the input device to deploy the one or more of the second database instance container or the fourth database instance container on the second host server; facilitating displaying on a device of the first host server at which the one or more of the first database instance container or the third database instance container has been deployed; and facilitating displaying on a device of the second host

server at which the one or more of the second database instance container or the fourth database instance container has been deployed.

16. The method of claim 10, wherein: providing the bonded network interface on the host server further comprises: providing a first bonded network interface at a first host server to create a first bonded network interface in a first active-active mode by aggregating the first plurality of network interface controllers available in the first host server; and creating a second bonded network interface at a second host server to create the second bonded network interface in a second active-active mode by aggregating a second plurality of network interface controllers available in the second host server, wherein the host server comprises the first host server and the second host server; and; further comprising: creating the first database instance container at the first host server by using one IP address from a first pool of a first plurality of IP addresses of the first host server to create the first IP address on the first bonded network interface at the first host server; creating the second database instance container at the second host server by using one IP address from a second pool of a second plurality of IP addresses of the second host server to create the second IP address on the second bonded network interface at the second host server; eliminating at least one of the first database instance container or the second database instance container; when the first database instance container is eliminated, returning the first IP address of the first database instance container to the first pool of the first plurality of IP addresses of the first host server; and when the second database instance container is eliminated, returning the second IP address of the second database instance container to the second pool of the second plurality of IP addresses of the second host server.

17. The method of claim 10, further comprising: mapping a first persistent file system of a first host server to a predetermined first host level volume; mapping a second persistent file system of a second host server to a predetermined second host level volume, wherein the host server comprises the first host server and the second host server; storing data for the first database instance container outside the first database instance container and in the first persistent file system; storing data for the second database instance container outside the second database instance container and in the second persistent file system; binding a third database instance container of the first cluster to a first bonded network interface and also to a third IP address of a first pool of a first plurality of IP addresses of the first host server such that a third database deployed inside the third database instance container has direct access to the first host server; and binding a fourth database instance container of the second cluster to a second bonded network interface and also to a fourth IP address of a second pool of a second plurality of IP addresses of the second host server such that a fourth database deployed inside the fourth database instance container has direct access to the second host server.

18. The method of claim 10, further comprising: selecting one of a first host server or a second host server for binding of at least one additional database instance container to (i) an IP address of the first host server or (ii) an IP address of the second host server based upon at least one of one or more of: resource availability of the first host server relative to the second host server, or a number of database instance containers already bound to the first host server relative to the second host server, wherein the host server comprises the first host server and the second host server; when utilization of the first cluster exceeds a defined threshold, deploying a first additional database instance container to the first cluster; when utilization of the second cluster exceeds the defined threshold, deploying a second additional database instance container to the second cluster; when utilization of the first cluster falls below the defined threshold, eliminating a database instance container from the first cluster; when utilization of the second cluster falls below the defined threshold, eliminating a database instance container from the second cluster; specifying an amount of storage space required for an additional database instance container; determining which one of the first host server or the second host server has sufficient space to create a redundant array of independent discs (RAID) volume; deploying the additional database instance container to the one

of the first host server or the second host server determined to have sufficient space to create the RAID volume; and before binding the first database instance container and also before binding the second database instance container, receiving one or more requests from an electronic device to: bind the first database instance container; bind the second database instance container; or set the different fault tolerance for the first cluster and the second cluster.

19. A non-transitory computer-readable medium storing instructions, wherein the instructions, upon execution by a processor, cause the processor to perform operations comprising: providing a bonded network interface on a host server, the host server comprising a plurality of internet protocol (IP) addresses; binding a first database instance container to a first IP address of the plurality of IP addresses of the host server, wherein the first database instance container belongs to a first cluster, and wherein binding the first database instance container to the first IP address further comprises accessing a switch comprising a port coupled to a network interface controller of a first plurality of network interface controllers in the host server; and binding a second database instance container to a second IP address of the plurality of IP addresses of the host server, wherein: the second database instance container belongs to a second cluster that is different from and non-overlapping with the first cluster; the first cluster has a different fault tolerance than the second cluster; a first database deployed inside the first database instance container has direct access to the host server; a second database deployed inside the second database instance container has direct access to the host server; and binding the first database instance container to the first IP address further comprises binding the first database instance container to the first IP address without a virtual network layer.

20. The non-transitory computer-readable medium of claim 19, wherein the operations further comprise: storing application data of the first database instance container in a first persistent file system and outside the first database instance container; storing application data of a third database instance container in the first persistent file system and outside the third database instance container; storing application data of the second database instance container in a second persistent file system and outside the second database instance container; and storing application data of a fourth database instance container in the second persistent file system and outside the fourth database instance container.
