

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282103

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

IMS; Matthew et al.

HEAT SEALING APPARATUSES AND METHODS OF USE THEREOF

Abstract

A heating block assembly including one or more configurable insulator segments and a heater block having a first surface configured to removably receive the one or more configurable insulator segments, in which each of the one or more configurable insulator segments covers only a portion of the first surface. A method for sealing at least one portion of a package using such a heating block assembly is also disclosed.

Inventors: IMS; Matthew (Cincinnati, OH), FRAILING; William R. (Cincinnati, OH), MELLIN; Gustav André (Amberley Village, OH)

Applicant: The Procter & Gamble Company (Cincinnati, OH)

Family ID: 86230188

Appl. No.: 19/220477

Filed: May 28, 2025

Related U.S. Application Data

parent US continuation 17523371 20211110 parent-grant-document US 12330379 child US 19220477

Publication Classification

Int. Cl.: B29C65/00 (20060101)

U.S. Cl.:

CPC B29C66/8122 (20130101); B29C66/1122 (20130101); B29C66/81821 (20130101); B29C66/81871 (20130101);

Background/Summary

FIELD OF THE INVENTION

[0001] The invention generally relates to a heat sealing apparatus, and more particularly to a heat sealing apparatus having a configurable heat sealing surface and methods of using the same.

BACKGROUND OF THE INVENTION

[0002] A heat sealing machine may be used to seal one or more end surfaces of a package, such as an overwrap for absorbent articles. The package may then be subjected to a further heat shrinking process to achieve a tight wrap around the contents of the package. In some cases, the seals created by conventional heat sealing machines result in nonuniform heat shrinking, which may cause visual defects in the package such as bunching, wrinkling, and/or stretching. These visual defects may be particularly evident when the package includes graphics printed or otherwise formed in or on the package. The graphics may, for example, become distorted and/or change color, resulting in an undesirable visual appearance that may detract from a customer's impression of the product and/or manufacturer.

SUMMARY OF THE INVENTION

[0003] In accordance with an aspect of the present disclosure, a heating block assembly is disclosed, the heating block assembly comprising: one or more configurable insulator segments; and a heater block comprising a first surface configured to removably receive the one or more configurable insulator segments, in which each of the one or more configurable insulator segments covers only a portion of the first surface.

[0004] Each of the one or more configurable insulator segments may comprise an inner surface positioned adjacent to the first surface of the heater block and an outer surface opposite the inner surface. Each of the one or more configurable insulator segments may comprise a thickness of between 2.9 and 3.1 mm, in which the thickness is defined between the inner and outer surfaces. A temperature of the outer surface of each of the one or more configurable insulator segments may be between 20% and 30% less than a temperature of the first surface of the heater block.

[0005] The first surface of the heater block may comprise a first extension and a second extension, in which each of the one or more configurable insulator segments may comprise a first corresponding channel and a second corresponding channel configured to receive the respective first and second extensions.

[0006] The heater block may comprise aluminum, and each of the one or more configurable insulator segments may comprise polyether ether ketone.

[0007] The heater block may be configured to receive a heating cartridge, and the heater block may comprise a thermally conductive material.

[0008] The heating block assembly may further comprise one or more configurable conductor segments each comprising a thermally conductive material. The one or more configurable insulator segments may comprise a first insulator segment and a second insulator segment, in which the first and second insulator segments may be spaced apart from each other along a longitudinal length of the heater block by at least one of the one or more configurable conductor segments to define at least one heating zone. The first insulator segment may comprise a first length, and the second insulator segment may comprise a second length that is the same as or different from the first length.

[0009] In accordance with another aspect of the present disclosure, a heat sealing apparatus is disclosed, the heat sealing apparatus comprising at least a first heating block assembly and a second heating block assembly, each of which comprise: one or more configurable insulator segments; and a heater block comprising a first surface configured to removably receive the one or more configurable insulator segments, in which each of the one or more configurable insulator segments

covers only a portion of the first surface.

[0010] The first heating block assembly may comprise a first insulator segment, and the second heating block assembly may comprise a second insulator segment, in which top edges and/or bottom edges of the first and second insulator segments may be horizontally aligned with each other when the first and second heating block assemblies are positioned side-by-side.

[0011] The heat sealing apparatus may further comprise a plurality of configurable conductor segments, in which the first heating block assembly may comprise first and second insulator segments spaced apart from each other along a longitudinal length of the heater block of the first heating block assembly by at least one of the plurality of configurable conductor segments and the second heating block assembly may comprise third and fourth insulator segments spaced apart from each other along a longitudinal length of the heater block of the second heating block assembly by at least one of the plurality of configurable conductor segments. The first and second heating block assemblies may be positioned side-by-side, in which top edges and/or bottom edges of the first and third insulator segments may be horizontally aligned with each other and/or top edges and/or bottom edges of the second and fourth insulator segments may be horizontally aligned with each other.

[0012] The first heating block assembly may be positioned to at least partially define a first heat sealing surface configured to seal a portion of a first end surface of a package, and the second heating block assembly may be positioned opposite the first heating block assembly to at least partially define a second heat sealing surface configured to seal a portion of a second end surface of the package.

[0013] In accordance with a further aspect of the present disclosure, a heat sealing apparatus is disclosed, the heat sealing apparatus comprising: a configurable heat sealing surface comprising one or more heating zones each defined by one or more configurable insulator segments and one or more configurable conductor segments, in which each of the one or more configurable insulator segments covers only a portion of the configurable heat sealing surface.

[0014] The configurable heat sealing surface may comprise a first configurable heat sealing surface, and the heat sealing apparatus may further comprise a second configurable heat sealing surface that may comprise one or more second heating zones each defined by one or more second configurable insulator segments and one or more second configurable conductor segments, in which each of the one or more second configurable insulator segments covers only a portion of the second configurable heat sealing surface. The first configurable heat sealing surface may comprise a first insulator segment configuration, and the second configurable heat sealing surface may comprise a second insulator segment configuration that is the same as or different from the first insulator segment configuration. The first configurable heat sealing surface may comprise one or more first heating block assemblies, each of which may comprise a first heater block with a first surface configured to removably receive the one or more configurable insulator and conductor segments, and the second configurable heat sealing surface may comprise one or more second heating block assemblies, each of which may comprise a second heater block with a first surface configured to removably receive the one or more second configurable insulator and conductor segments. The one or more configurable insulator segments may each cover only a portion of the first surface of the first heater block, and the one or more second configurable insulator segments may each cover only a portion of the first surface of the second heater block.

[0015] The one or more first heating block assemblies may comprise a first plurality of heating block assemblies, which may comprise a first pair of heating block assemblies and a second pair of heating block assemblies positioned side-by-side with the first pair of heating block assemblies, in which the heat sealing apparatus may further comprise a controller operatively coupled to each of the first plurality of heating block assemblies and configured to selectively operate the first and second pairs of heating block assemblies. The first pair of heating block assemblies may comprise a first insulator segment configuration, and the second pair of heating block assemblies may

comprise a second insulator segment configuration that is different from the first insulator segment configuration, in which the controller may be configured to selectively provide power to the first and second pair of heating block assemblies such that the one or more heating zones of the first pair of heating block assemblies may comprise a first temperature and the one or more second heating zones of the second pair of heating block assemblies may comprise a second temperature that is different from the first temperature.

[0016] In accordance with a further aspect of the present disclosure, a method for sealing at least one portion of a package is disclosed, the method comprising: providing a configurable heat sealing surface; selectively adjusting a configuration of the configurable heat sealing surface to define one or more heating zones; and advancing the package along the configurable heat sealing surface adjacent to the one or more heating zones to seal the at least one portion of the package.

[0017] Selectively adjusting the configuration of the configurable heat sealing surface may comprise adjusting (i) a number of heating zones, (ii) a vertical location of the one or more heating zones, (iii) a horizontal location of the one or more heating zones, and/or (iv) a dimension of the one or more heating zones.

[0018] The configurable heat sealing surface may comprise a plurality of heating block assemblies each comprising a heater block with one or more configurable insulator segments and one or more configurable conductor segments that define the one or more heating zones. Selectively adjusting the configuration of the configurable heat sealing surface may comprise, for each heating block assembly, selectively positioning the one or more configurable insulator and conductor segments along a longitudinal length of the heater block to define the one or more heating zones.

[0019] The plurality of heating block assemblies may comprise a first pair of heating block assemblies and a second pair of heating block assemblies, in which the method may further comprise selectively operating the first and second pairs of heating block assemblies to seal the at least one portion of the package. The first and second pair of heating block assemblies may be positioned side-by-side. The package may comprise a first package, in which the method may further comprise: selectively providing power to the first pair of heating block assemblies to seal the at least one portion of the first package; after sealing the at least one portion of the first package, advancing a second package along the configurable heat sealing surface; and selectively providing power to the second pair of heating block assemblies to seal at least one portion of the second package. The first pair of heating block assemblies may comprise a first insulator segment configuration, and the second pair of heating block assemblies may comprise a second insulator segment configuration different from the first insulator segment configuration.

[0020] The configuration of the configurable heat sealing surface may comprise a first configuration, in which the method may further comprise, after sealing the at least one portion of the package, selectively adjusting the configuration of the configurable heat sealing surface to comprise a second configuration defining one or more second heating zones, the second configuration being different from the first configuration. The method may further comprise advancing a second package along the configurable heat sealing surface adjacent to the one or more second zones to seal at least one portion of the second package.

[0021] The one or more heating zones may comprise a first heating zone and a second heating zone that is positioned above or below the first heating zone, in which the package may comprise a first package and the method may further comprise: positioning a second package above or below the first package; and advancing the second package along the configurable heat sealing surface with the first package, in which one of the first or the second heating zone seals the at least one portion of the first package and the other of the first or the second heating zone simultaneously seals at least one portion of the second package.

[0022] The configurable heat sealing surface may comprise a first configurable heat sealing surface, in which the method may further comprise: providing a second configurable heat sealing surface positioned opposite the first configurable heat sealing surface; and selectively adjusting a

configuration of the second configurable heat sealing surface to define one or more second heating zones. The at least one portion of the package may comprise a first end surface, and advancing the package along the first configurable heat sealing surface may seal at least a section of the first end surface of the package. The at least one portion of the package may further comprise a second end surface positioned opposite the first end surface, in which the method may further comprise advancing the package along the second configurable heat sealing surface adjacent to the one or more second heating zones to seal at least one section of the second end surface of the package. The package may be advanced along the first and second configurable heat sealing surfaces such that the at least one sections of the first and second end surfaces of the package are sealed simultaneously.

[0023] The method may further comprise, after advancing the package along the configurable heat sealing surface, subjecting the package to a heat shrinking process.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] While the specification concludes with claims particularly pointing out and distinctly claiming the subject matter which is regarded as forming the present invention, it is believed that the invention will be better understood from the following description which is taken in conjunction with the accompanying drawings in which like designations are used to designate substantially identical elements, and in which:

[0025] FIG. 1 is an exploded view of a heating block assembly, in accordance with the present disclosure;

[0026] FIG. 2 is a perspective view of one example of the heating block assembly of FIG. 1 following assembly;

[0027] FIG. 3 is an end view of the heating block assembly taken along view line 3-3 in FIG. 2;

[0028] FIG. 4 is a perspective view of another example of the heating block assembly of FIG. 1 following assembly;

[0029] FIG. 5 is a perspective view of an exemplary heat sealing apparatus, in accordance with the present disclosure.

[0030] FIG. 6 is a perspective view of another exemplary heat sealing apparatus, in accordance with the present disclosure;

[0031] FIG. 7 is a perspective view of a further exemplary heat sealing apparatus, in accordance with the present disclosure

[0032] FIG. 8 is a perspective view of a heat sealing apparatus comprising a plurality of heating block assemblies positioned opposite one another;

[0033] FIG. 9 is a partial cross-sectional view taken along line 9-9 in FIG. 8;

[0034] FIG. 10 is a partial cross-sectional view similar to FIG. 9 of another exemplary heat sealing surface;

[0035] FIG. 11 is an end view of a package sealed with a heat sealing apparatus, in accordance with the present disclosure;

[0036] FIGS. 12-15 are photographs of packages formed using conventional methods and methods in accordance with the present disclosure;

[0037] FIG. 16 is a flow diagram illustrating an exemplary method for sealing at least one portion of a package, in accordance with the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

[0038] The present disclosure relates to a heat sealing apparatus having a configurable heat sealing surface and methods of use thereof. The heat sealing surface comprises configurable insulator and conductor segments that permit greater control over sealing of packages by minimizing a size of a

heating zone to that necessary to form a minimally sufficient seal that serves to hold the package ends together long enough to undergo a subsequent heat shrinking process.

[0039] As described herein, a package may be formed by folding a plastic overwrap, e.g., polyethylene, over and around a matrix of one or more articles and closing one or more ends of the overwrap by folding end flaps in an overlapping relationship, e.g., an envelope folding pattern, and delivering the package to a heat sealing section where heat is applied to the end surface(s) of the package to fuse together the layers of material of the end flaps. The package then enters a heat shrink tunnel where heat, e.g., convective heat, is applied to all sides of the package, which causes the plastic overwrap to expand before shrinking to create a tight fit around the matrix of articles. Conventional heat sealing machines generally provide a single, large heating zone that extends across an entirety of the heat sealing surface, such that substantially an entirety of the end surface of the package is subjected to heating while in the heat sealing section. It was found that this large heat sealing surface causes the overwrap material to undergo heat shrinking at the heat sealing section and leads to complete sealing of the end prior to entering the heat shrink tunnel. This premature heat shrinking creates a boundary where the overwrap material is prevented from naturally flowing during the heat shrink process, which produces localized bunching of the overwrap material. The overwrap often contains ink from, for example, graphics printed on one or more display panels, and the bunching of the overwrap material on the ends causes undesirable collection of the ink and distortion of the graphics (referred to herein as “veining”).

[0040] A heat sealing apparatus with a configurable heat sealing surface in accordance with the present disclosure enables a size of the heating zone to be reduced and minimizes a heat affected area on the end surface of the package. The smaller heating zone reduces or eliminates premature heat shrinking, which allows the overwrap material to flow properly during heat shrinking and reduces veining on the display panel(s). The configurable heat sealing surface may be tailored to create a heating zone with the size needed for each specific matrix of articles and may be configured to provide two or more heating zones. As described herein, one or more properties of the heating zone(s) may be altered quickly and easily, without the need to disassemble portions of the heat sealing apparatus.

[0041] With reference to FIG. 1, a heating block assembly **10** is shown, which may include a heater plate or block **12**, one or more configurable insulator segments **30a-30e**, and one or more configurable conductor segments **32a-32c**. The heater block **12** may comprise a first surface **12-1** that is configured to removably receive the one or more configurable insulator segments **30a-30e** and conductor segments **32a-32c**, as described in more detail below. The first surface **12-1** of the heater block **12** may be substantially planar or smooth, as shown in in FIG. 1.

[0042] The heater block **12** comprises a first end **14** and a second end **16**. The first end **14** may comprise a threaded bore **14-3**, and the second end **16** may comprise a similar threaded bore (not visible), in which the threaded bore **14-3** at the first end **14** and the threaded bore at the second end **16** are configured to receive a fastener **50**, **54**, respectively, as described herein. The first end **14** comprises a first opening **14-1** and a second opening **14-2**, as shown in FIG. 1. In the example shown, the first opening **14-1** may be configured to receive a heating element **58** that extends along at least a portion of a longitudinal length $L_{sub.12}$ of the heater block **12** and provides heat to the heating block assembly **10**. In the example shown, the heating element **58** comprises a cartridge heater, which may include a single zone or a multi zone cartridge heater. The second opening **14-2** may be configured to receive a temperature sensor **70** such as a thermocouple or a resistance temperature detector. As described in more detail below, the heating element **58** and the temperature sensor **70** may be operatively coupled to a controller **72** that receives temperature data from the temperature sensor **70** and adjusts operation of the heating element **58** to achieve a desired temperature. Although the heater block **12** in FIG. 1 is depicted as being configured to receive a cartridge heater, it is understood that other types of heating elements **58** could be used, such as a tubular heater. With reference to the end view shown in FIG. 3, the second end **16** of the heater

block **12** may comprise a first opening **16-1**, which may be connected to the first opening **14-1** in the first end **14**.

[0043] As shown in FIGS. **1** and **3**, the first surface **12-1** of the heater block **12** includes a first extension **18** and a second extension **22** that extends in a direction opposite the first extension **18**. The first and second extensions **18**, **22** define respective first and second channels **20**, **24**, which may extend along an entirety of the longitudinal length $L_{sub.12}$ of the heater block **12**. The heater block **12** may include a first width $W_{sub.12-1}$ at or near a second surface **12-2**, a second width $W_{sub.12-2}$ defined by the channels **20**, **24**, and a third width $W_{sub.12-3}$ defined by the extensions **18**, **22**. The first width $W_{sub.12-1}$ may be a maximum width of the heater block **12**, and the second width $W_{sub.12-2}$ may be a minimum width of the heater block **12**. The third width $W_{sub.12-3}$ may fall between the first and second widths $W_{sub.12-1}$, $W_{sub.12-2}$ such that the extensions **18**, **22**, the channels **20**, **24**, and the first surface **12-1** of the heater block **12** may together define a capital “T” shape. The first surface **12-1** of the heater block **12**, specifically the extensions **18**, **22** and the channels **20**, **24**, may be configured to removably receive the one or more configurable insulator and conductor segments **30a-30e**, **32a-32c**.

[0044] With reference to the detailed view in FIG. **3**, the insulator segment **30b** may comprise an inner surface **30b-1** and an outer surface **30b-2** that is opposite the inner surface **30b-1**, in which the inner surface **30b-1** of the insulator segment **30b** is positioned adjacent to the first surface **12-1** of the heater block **12**. The insulator segment **30b** may further comprise a first sidewall **34** with a first lip **36** and a second sidewall **38** with a second lip **40**. The first and second lips **36**, **40** extend inward toward each other and may be substantially perpendicular to the first and second sidewalls **34**, **38** and substantially parallel to the inner and outer surfaces **30b-1**, **30b-2** of the insulator segment **30b**, such that the inner surface **30b-1**, the sidewalls **34**, **38**, and the lips **36**, **40** of the insulator segment **30** may together define a slot in the shape of a capital “T.” The first lip **36** is received in the first channel **20** of the heater block **12**, and the second lip **40** is received in the second channel **24** to secure the insulator segment **30b** to the heater block **12**. A width (not separately labeled) of an outer surface of the first and second sidewalls **34**, **38** may be substantially similar to the first width $W_{sub.12-1}$ of the heater block **12**, such that sides of the heating block assembly **10** are substantially smooth and seamless. A portion of the outer surface **30b-2** adjacent to the sidewalls **34**, **38** may comprise a chamfer or slope to minimize impacts along edges of the insulator segment **30b** and to ensure that packages and other objects move smoothly along the outer surface **30b-2**.

[0045] Although not labeled, it can be seen in FIG. **1** that all of the insulator and conductor segments **30a**, **30c-30e**, **32a-32c** comprise a structure that is substantially similar to the insulator segment **30b** shown in detail in FIG. **3**. As shown in FIG. **1**, the insulator and conductor segments **30a-30e**, **32a-32c** may be installed on the heater block **12** from the first or the second end **14**, **16** by sliding the insulator and conductor segments **30a-30e**, **32a-32c** onto the first surface **12-1** of the heater block **12** in a direction indicated by arrow A. With reference to FIG. **3**, it can be seen that engagement between the lips **36**, **40** of the insulator segment **30b** and the channels **20**, **24** of the heater block **12** prevents movement of the insulator segment **30b** in any direction other than the direction indicated by arrow A in FIG. **1**. The insulator and conductor segments **30a**, **30c-30e**, **32a-32c** shown in FIG. **1** may similarly be secured to the heater block **12**.

[0046] One or more of the insulator segments **30a-30c** and the conductor segments **32a-32c** may be installed on the heater block **12** of FIG. **1** to generate the heating block assemblies **10**, **10'** depicted in FIGS. **2-4**. Following installation of the insulator and conductor segment(s) **30a-30e**, **32a-32c** onto the heater block **12**, the fasteners **50**, **54** may be used to secure the insulator and conductor segments **30a-30e**, **32a-32c** and prevent movement of the insulator and conductor segments **30a-30e**, **32a-32c** in the direction indicated by arrow A. As shown in FIGS. **1**, **2**, and **4**, the fastener **50**, e.g., a screw, may extend through a washer **52** and be received in the threaded bore **14-3** formed in the first end **14** of the heater block **12**. The washer **52** extends above the first surface **12-1** of the

heater block **12** to prevent the insulator and conductor segments **30a-30e**, **32a-32c** from moving past the first end **14**. Similarly, as shown in FIGS. **1** and **3**, the fastener **54** may extend through a washer **56** and be received in the threaded bore (not shown) formed in the second end **16** of the heater block **12**, in which the washer **56** extends above the first surface **12-1** of the heater block **12** to prevent the insulator and conductor segments **30a-30e**, **32a-32c** from moving past the second end **16**.

[0047] The heating block assembly **10**, **10'** shown in FIGS. **1-4**, including the heater block **12** and the one or more insulator and conductor segments **30a-30e**, **32a-32c**, may define a respective configurable heat sealing surface **60**, **60'** or a portion thereof. A configuration of the configurable heat sealing surface **60**, **60'** may be altered by changing one or more of a number, dimension, and location of the one or more insulator and conductor segments **30a-30e**, **32a-32c**, as described herein.

[0048] With reference to the heating block assembly **10** shown in FIG. **2**, the heater block **12** comprises insulator segments **30a** and **30b** and conductor segment **32a**, which define one exemplary heat sealing surface **60** or portion thereof. The insulator segment **30a** is positioned adjacent to the first end **14** of the heater block **12**, the insulator segment **30b** is positioned adjacent to the second end **16** of the heater block **12**, and the conductor segment **32a** is positioned between the insulator segments **30a**, **30b** to space the insulator segments **30a**, **30b** apart from each other along the longitudinal length $L_{sub.12}$ of the heater block **12**.

[0049] The heating block assembly **10'** in FIG. **4** comprises insulator segments **30c-30e** and conductor segments **32b**, **32c**, in which the insulator segment **30c** is positioned adjacent to the first end **14** of the heater block **12**, the insulator segment **30e** is positioned adjacent to the second end **16** of the heater block **12**, and the insulator segment **30d** is positioned between the insulator segments **30c**, **30e**. The conductor segment **32b** is positioned between the insulator segments **30c**, **30d**, and the conductor segment **32c** is positioned between the insulator segments **30d**, **30e** to space the insulator segments **30c-30e** apart from each other along the longitudinal length $L_{sub.12}$ of the heater block **12** and to define another exemplary heat sealing surface **60'** or portion thereof.

[0050] The insulator segments **30a-30e** may comprise a material with low thermal conductivity, e.g., from about 0.15 to about 0.95 W/(m.Math.K)+0.02 W/(m.Math.K), such as polyetheretherketone (PEEK), which may have an average thermal conductivity of about 0.25 W/(m.Math.K). Another example of a material with low thermal conductivity may include polytetrafluoroethylene. The heater block **12** and the conductor segments **32a-32c** may comprise a material with a high thermal conductivity, e.g., greater than about 200 W/(m.Math.K), such as one or more metals (e.g., aluminum or copper), alloys (e.g., brass or bronze), or combinations thereof. The heater block **12** may be made from a single (monolithic) piece of material such as anodized aluminum that is a good thermal conductor, resists wear and oxidation, and provides a lower coefficient of friction to enable the insulator and conductor segments **30a-30e**, **32a-32c** to slide on and off more easily. The heater block **12** and the conductor segments **32a-32c** may comprise the same material, e.g., aluminum, or may comprise one or more different materials as compared to each other.

[0051] The one or more insulator segments **30a-30e** may cover only a portion of the first surface **12-1** of the heater block **12**. As shown in FIGS. **2** and **4**, in examples comprising two or more insulator segments **30a-30e**, the insulator segments **30a-30e** may be spaced apart from each other via one or more conductor segments **32a-32c**. The heat sealing surface **60**, **60'** may comprise one or more heating zones **62**, **62'**, **64'** that are defined by the conductor segments **32a-32c**, specifically by a position of the insulator segments **30a-30e** with respect to the conductor segments **32a-32c** along the longitudinal length $L_{sub.12}$ of the heater block **12**. When heat is applied to the heater block **12**, e.g., via the heating element **58** shown in FIG. **1**, the insulator segments **30a-30e** reduce the amount of heat transmitted to corresponding portions of the heat sealing surface **60**, **60'**, while the conductor segments **32a-32c** conduct the heat from the heater block **12** to corresponding portions

of the heat sealing surface **60**, **60'**. For example, with reference to FIG. 2, the heat sealing surface **60** comprises one large heating zone **62** that is located toward a longitudinal center of the heater block **12** and is defined by insulator segments **30a**, **30b** and conductor segment **32a**. In FIG. 4, the heat sealing surface **60'** comprises two smaller heating zones **62'**, **64'** that are defined by insulator segments **30c-30e** and conductor segments **32a**, **32b**.

[0052] The insulator and conductor segments **30a-30e**, **32a-32c** may be manufactured to have any desired longitudinal length. With reference to FIGS. 2 and 4, the insulator segments **30a-30e** may each comprise a respective length $L_{sub.30a-L_{sub.30e}}$, and the conductor segments **32a-32c** may each comprise a respective length $L_{sub.32a-L_{sub.32c}}$. The lengths $L_{sub.30a-L_{sub.30e}}$ of the insulator segments **30a-30e** within the heating block assembly **10**, **10'** may be the same as or different from each other. For example, as shown in FIG. 2, the length $L_{sub.30a}$ of the insulator segment **30a** is different from, i.e., less than, the length $L_{sub.30b}$ of the insulator segment **30b**. As shown in FIG. 4, the length $L_{sub.30d}$ of the insulator segment **30d** is the same as the length $L_{sub.30e}$ of the insulator segment **30e**, while the length $L_{sub.30c}$ of the insulator segment **30c** is different from, i.e., less than, the lengths $L_{sub.30d}$, $L_{sub.30e}$ of the insulator segments **30d**, **30e**. The lengths $L_{sub.32a-L_{sub.32c}}$ of the conductor segments **32a-32c** within the heating block assembly **10**, **10'** may likewise be the same as or different from each other. For example, as shown in FIG. 4, the length $L_{sub.32b}$ of the conductor segment **32b** is the same as the length $L_{sub.32c}$ of the conductor segment **32c**.

[0053] A configuration of the heat sealing surfaces **60**, **60'** may be selectively adjusted to define the one or more heating zones **62**, **62'**, **64'**. In particular, an insulator and/or conductor configuration of the heating block assemblies **10**, **10'** in FIGS. 2-4 may be altered to achieve a desired number of heating zones **62**, **62'**, **64'** with the desired dimension(s) and/or desired vertical location(s) along the longitudinal length $L_{sub.12}$ of the heater block **12**. One or more of the insulator and/or conductor segments **30a-30e**, **32a-32c** may be removed from the heater block **12** by sliding them off of the first or second end **14**, **16** of the heater block **12** in the direction indicated by arrow A in FIG. 1 and replacing them with one or more additional insulator and/or conductor segments having a different length that are selectively positioned along the longitudinal length $L_{sub.12}$ of the heater block **12** (e.g., by sliding the one or more additional insulator and/or conductor segments onto the first surface **12-1** of the heater block **12** in the direction indicated by arrow A).

[0054] Although the insulator segments **30a-30e** in FIGS. 2 and 4 are depicted as being separated by one conductor segment **32a-32c** each, it should be understood that the insulator segments **30a-30e** may be separated by two or more conductor segments **32a-32c** that are positioned adjacent to each other along the longitudinal length $L_{sub.12}$ of the heater block **12** without insulator segments **30a-30e** positioned therebetween. Likewise, two or more insulator segments **30a-30e** may be positioned adjacent to each other along the longitudinal length $L_{sub.12}$ of the heater block **12** without conductor segment(s) **32a-32c** positioned therebetween. In addition, although FIG. 4 depicts two heating zones **62'**, **64'**, it should be understood that any number of heating zones, including three or more, may be possible.

[0055] With reference to FIGS. 1 and 3, a temperature of the outer surface **30b-2** of the insulator segment **30b** may be between 20% and 30% less than a temperature of the first surface **12-1** of the heater block **12** due to the insulator segment **30b** being comprised of a material with low thermal conductivity. The insulator segment **30b** may comprise a thickness $T_{sub.30b}$ of between 2.9 and 3.1 mm, as measured between the inner and outer surfaces **30b-1**, **30b-2** shown in FIG. 3. A central portion of the inner surface **30b-1** of the insulator segment **30b** may be spaced apart from an adjacent portion of the first surface **12-1** of the heater block **12** to define an air gap **68** therebetween. The air gap **68** serves to further reduce conduction of heat from the heater block **12** to the outer surface **30b-2** of the insulator segment **30b**. The air gap **68** may be between 0.9 and 1.1 mm, such that the outer surface **30b-2** of the insulator segment **30b** is spaced apart from the first surface **12-1** of the heater block **12** by about 4 mm. The other insulator segments **30a**, **30c-30e**

shown in FIGS. 1, 2, and 4 may comprise substantially similar structures and thicknesses and may achieve similar temperature differences between their respective outer surfaces (not labeled) and the first surface 12-1 of the heater block 12. The conductor segments 32a-32c, which do not define an air gap, may comprise a corresponding thickness (not shown) of about 4 mm so that substantially an entirety of inner surfaces (not labeled) of the conductor segments 32a-32c contact the first surface 12-1 of the heater block 12 and outer surfaces (not labeled) of the conductor segments 32a-32c are flush with the outer surfaces of the insulator segments 30a-30e, as seen in FIGS. 2 and 4, to ensure that packages and other objects move smoothly along the heat sealing surface 60, 60' (see also FIGS. 9 and 10). A temperature of an outer surface (not labeled) of the conductor segments 32a-32c may be substantially similar to a temperature of the heater block 12 due to the conductor segments 32a-32c being comprised of a material with a high thermal conductivity.

[0056] FIGS. 5-7 illustrate exemplary heat sealing apparatuses 100, 200, 300 comprising a respective configurable heat sealing surface 160, 260, 360, in accordance with the present disclosure. As used herein, the term “vertical” may be used to refer to a location, position, or dimension in a direction parallel to the longitudinal length L.sub.12 of the heater block 12 shown in FIGS. 1, 2, and 4, while the terms “horizontal” or “lateral” may be used to refer to a location, position, or dimension in a direction parallel to the width W.sub.12 of the heater block 12 shown in FIG. 3. Only a portion of the elements in FIGS. 5-7 are labeled in order to illustrate other aspects of each heat sealing apparatus 100, 200, 300 in detail. It should be understood that unless indicated otherwise, the heating block assemblies 110, 210/210', 310/310' within each heat sealing apparatus 100, 200, 300 may all include components that are substantially similar to each other.

[0057] With reference to FIG. 5, the heat sealing apparatus 100 comprises a plurality of heating block assemblies 110 that each comprise insulator segments 130a-130c and conductor segments 132a, 132b. The insulator segment 130a may be positioned adjacent to a first end 114 of a heater block 112, the insulator segment 130c may be positioned adjacent to a second end 116 of the heater block, and the insulator segment 130b may be positioned between the insulator segments 130a, 130c. The conductor segment 132a may be positioned between insulator segments 130a, 130b, and the conductor segment 132b may be positioned between insulator segments 130b, 130c to space apart the respective insulator segments 130a-130c and define respective heating zones 162, 164 in each heating block assembly 110. The heating block assemblies 110 may be horizontally aligned, side-by-side, along their longitudinal lengths (not labeled; see FIG. 1) to define one exemplary configurable heat sealing surface 160. An insulator and/or conductor segment configuration may be the same across all of the heating block assemblies 110.

[0058] The heat sealing apparatus 200 of FIG. 6 comprises a plurality of heating block assemblies 210, 210' horizontally aligned, side-by-side, along their longitudinal lengths (not labeled; see FIG. 1) to define another exemplary configurable heat sealing surface 260, in which the heating block assemblies 210 comprise a different insulator and/or conductor segment configuration than the heating block assemblies 210'. The heating block assemblies 210 may each comprise two insulator segments 230a, 230b that are spaced apart by a conductor segment 232a to define a heating zone 262. The heating block assemblies 210' may each comprise two insulator segments 230a', 230b' that are spaced apart by a conductor segment 232a' to define a heating zone 262'. It can be seen that the insulator segments 230a' comprise a length (not labeled) that is much larger than a length (not labeled) of the insulator segments 230a and that the conductor segments 232a comprise a length (not labeled) that is much larger than a length (not labeled) of the conductor segments 232a'. The insulator segments 230b, 230b' may have a length that is substantially the same, such that the heating zone 262 of the heating block assemblies 210 is larger than the heating zone 262'.

[0059] FIG. 7 depicts a heat sealing apparatus 300 comprising a further exemplary configurable heat sealing surface 360. The heat sealing apparatus 300 may comprise a plurality of heating block assemblies 310, 310' horizontally aligned, side-by-side, along their longitudinal lengths (not

labeled; see FIG. 1), in which the heating block assemblies **310** comprise a different insulator and/or conductor segment configuration than the heating block assemblies **310'**. The heating block assemblies **310** may be substantially similar to the heating block assemblies **110** shown in FIG. 5 and may each comprise three insulator segments **330a-330c** that are spaced apart by conductor segment **332a**, **332b** to define two heating zones **362**, **364**. The heating block assemblies **310'** may be substantially similar to the heating block assemblies **210** shown in FIG. 6 and may each comprise two insulator segments **330a'**, **330b'** that are spaced apart by a conductor segment **332a'** to define a heating zone **362'**.

[0060] In some examples, top and/or bottom edges of one or more of the insulator segments within adjacent heating block assemblies may be horizontally aligned with each other. As shown in FIG. 5, because the heating block assemblies **110** all comprise the same insulator and conductor segment configuration, top edges **130a-1** and bottom edges **130a-2** of the insulator segments **130a** are horizontally aligned with each other across all of the heating block assemblies **110**. Top and bottom edges **130b-1**, **130b-2** of the insulator segments **130b** and top and bottom edges **130c-1**, **130c-2** of the insulator segments **130c** are likewise all horizontally aligned with each other.

[0061] In FIGS. 6 and 7, the heating block assemblies **210**, **210'** and **310**, **310'** comprise different insulator and/or conductor segment configurations, such that the top and/or bottom edges of one or more of the insulator segments may not be aligned with each other. For example, as shown in FIG. 6, top edges **230a-1** of the insulator segments **230a** in the heating block assemblies **210** are horizontally aligned with top edges **230a-1'** of the insulator segments **230a'** in the heating block assemblies **210'**, but bottom edges **230a-2** of the insulator segments **230a** are not aligned with bottom edges **230a-2'** of the insulator segments **230a'**. Top edges **230b-1**, **230b-1'** and bottom edges **230b-2**, **230b-2'** of the insulator segments **230b**, **230b'** are horizontally aligned with each other across all of the heating block assemblies **210**, **210'**.

[0062] In FIG. 7, top and bottom edges **330a-1**, **330a-2** of the insulator segments **330a** in the heating block assemblies **310** are horizontally aligned with top and bottom edges **330a-1'**, **330a-2'** of the insulator segments **330a'** in the heating block assemblies **310'**, and top and bottom edges **330c-1**, **330c-2** of the insulator segments **330c** are horizontally aligned with top and bottom edges **330b-1'**, **330b-2'** of the insulator segments **330b'**. However, top and bottom edges **330b-1**, **330b-2** of the insulator segments **330b** in the heating block assemblies **310** are not horizontally aligned with top and/or bottom edges of any of the insulator segments **330a'**, **330b'** in the heating block assemblies **310'**.

[0063] With continued reference to FIGS. 5-7, each heating block assembly **110**, **210/210'**, **310/310'** comprises a respective heating element **158**, **258**, **358**, while every other heating block assembly **110**, **210/210'**, **310/310'** comprises a respective temperature sensor **170**, **270**, **370**. The heating block assemblies **110**, **210/210'**, **310/310'** may be controlled in pairs. As shown in FIG. 5, the four heating block assemblies **110** may comprise two pairs **128a**, **128b**, in which each pair **128a**, **128b** comprises two heating elements **158** and one temperature sensor **170**. In FIG. 6, the four heating block assemblies **210**, **210'** may likewise comprise two pairs **228a**, **228b**, in which each pair **228a**, **228b** comprises two heating elements **258** and one temperature sensor **270**. In FIG. 7, 12 heating block assemblies **310**, **310'** are shown, which may comprise six pairs **328a**, **328b** (only two pairs are labeled), in which each pair **328a**, **328b** comprises two heating elements **358** and one temperature sensor **370**. As shown in FIG. 5, in some examples, the insulator and/or conductor configuration of one pair **128a** of the heating block assemblies **110** may be the same as the insulator and/or conductor configuration of an adjacent pair **128b** of the heating block assemblies **110**. As shown in FIGS. 6 and 7, the insulator and/or conductor configuration of one pair **228a**, **328a** of the heating block assemblies **210**, **310** may be different from the insulator and/or conductor configuration of an adjacent pair **228b**, **328b** of the heating block assemblies **210'**, **310'**.

[0064] A controller (not shown; see FIG. 1) may be operatively coupled to the heating elements **158**, **258**, **358** and temperature sensors **170**, **270**, **370**. The controller may receive temperature

sensor data from one heating block assembly **110**, **210/210'**, **310/310'** within each pair **128a**, **128b**, **228a**, **228b**, **328a**, **328b** and may control operation of both heating elements **158**, **258**, **358** within each pair **128a**, **128b**, **228a**, **228b**, **328a**, **328b** based on the temperature sensor data. In particular, in some instances as described herein, the controller may selectively control operation of the pairs **128a**, **128b**, **228a**, **228b**, **328a**, **328b** of heating block assemblies **110**, **210/210'**, **310/310'**, e.g., by selectively providing power to the heating block assemblies **110**, **210/210'**, **310/310'**, to achieve a desired configuration of the respective heat sealing surface **160**, **260**, **360**. Selectively providing power to the pairs **128a**, **128b**, **228a**, **228b**, **328a**, **328b** of heating block assemblies **110**, **210/210'**, **310/310'** may comprise adjusting a horizontal location of the one or more heating zones within the heat sealing surfaces **160**, **260**, **360**, as the heating block assemblies **110**, **210/210'**, **310/310'** and their respective heating zones are located at different horizontal locations within the respective heat sealing apparatus **100**, **200**, **300**.

[0065] FIG. **8** depicts an exemplary heat sealing section **401**, which may be positioned within a larger wrapping and sealing device (not shown). A heat sealing apparatus **400** within the heat sealing section **401** may comprise a first configurable heat sealing surface **460** and a second configurable heat sealing surface **460'** for sealing one or more portions of a package **1000**. The package **1000** comprises a folded plastic overwrap, e.g., polyethylene, and at least a portion of the package **1000** may comprise one or more graphics **1003**. For example, as shown panels **1001-1**, **1001-2** comprise one or more graphics **1003**, which are indicated with dashed lines.

[0066] The package **1000** may be delivered to a conveyer **403**, e.g., a conveyer belt, that advances the package **1000** through the heat sealing section **401** along the first and second configurable heat sealing surfaces **460**, **460'** in a direction indicated by arrow **B**. A sealing belt **405** may be positioned between the package **1000** and the first configurable heat sealing surface **460**. Although not shown, a sealing belt would similarly be positioned on the right side of the heat sealing apparatus **400** between the second configurable heat sealing surface **460'** and the package **1000**. After passing through the heat sealing section **401**, the package **1000** may then enter a heat shrink tunnel (not shown) where the package **1000** undergoes a heat shrinking process and the overwrap material shrinks to create a tight fit.

[0067] The first configurable heat sealing surface **460** may be positioned to seal one or more sections of a first end surface **1000-1** of the package **1000** and may comprise a plurality of heating block assemblies (not shown, obscured by the sealing belt **405**; see FIGS. **9** and **10**). The second configurable heat sealing surface **460'** may be positioned opposite the first configurable heat sealing surface **460** to seal one or more sections of a second end surface **1000-2** of the package **1000**, the second end surface **1000-2** of the package **1000** being opposite the first end surface **1000-1**. The second configurable heat sealing surface **460'** may similarly comprise a plurality of heating block assemblies **410'** (the sealing belt on the right side of the heat sealing apparatus **400** is removed to show the heating block assemblies **410'** and several components of the heating block assemblies **410'** are omitted to illustrate other aspects in detail). The one or more sections of the first and second end surfaces **1000-1**, **1000-2** may be sealed substantially simultaneously, e.g., by advancing the package **1000** through the heat sealing section **401** and applying heat to both end surfaces **1000-1**, **1000-2** simultaneously from the first and second configurable heat sealing surfaces **460**, **460'**.

[0068] The heating block assemblies **410'** of the first and second configurable heat sealing surfaces **460**, **460'** may comprise any insulator and/or conductor segment configuration described herein. As discussed in more detail with respect to FIGS. **9** and **10**, the insulator and/or conductor segment configuration of the heating block assemblies **410'** in the first and second configurable heat sealing surfaces **460**, **460'** may be selectively adjusted to achieve a desired a number of heating zones (not labeled; see FIGS. **9** and **10**), a vertical location of the one or more heating zones, a horizontal location of the one or more heating zones, and/or a dimension of the one or more heating zones. Heat from the heating block assemblies **410'** through the sealing belts **405** and into one or more

sections of the end surfaces **1000-1**, **1000-2** of the package **1000** as the package **1000** is advanced along the first and second configurable heat sealing surfaces **460**, **460'** adjacent to the one or more heating zones. The sealing belts **405** may also help to advance the package **1000** through the heat sealing section **401**.

[0069] The first and second configurable heat sealing surfaces **460**, **460'** may each comprise 24 heating block assemblies **410'** for a total of 48 heating block assemblies in the heat sealing apparatus **400**. The 24 heating block assemblies **410'** of the second configurable heat sealing surface **460'** are horizontally aligned, side-by-side, with each other along their longitudinal lengths (not labeled; see FIG. **1**) as shown, and the 24 heating block assemblies (not visible) of the first configurable heat sealing surface **460** are horizontally aligned, side-by-side, with each other along their longitudinal lengths. The heating block assemblies **410'** are also aligned with corresponding ones of the 24 heating block assemblies in the first configurable heat sealing surface **460**. The heating block assemblies **410'** may be controlled in pairs, as described herein in detail. In some examples, the heat sealing apparatus **400** may comprise 24 heating sections defined by one pair of heating block assemblies, with each of the first and second configurable heat sealing surfaces **460**, **460'** comprising 12 respective heating sections. In some instances, a pair of heating block assemblies in the first configurable heat sealing surface **460** and a pair of heating block assemblies **410'** in the second configurable heat sealing surface **460'** immediately opposite the pair of heating block assemblies in the first configurable heat sealing surface **460** may comprise the same insulator and/or conductor segment configuration. In other instances, the pairs of opposing heating block assemblies **410'** in the first and second configurable heat sealing surfaces **460**, **460'** may comprise different insulator and/or conductor segment configurations. In both instances, the pairs of opposing heating block assemblies **410'** may be operated at a same temperature or at a different temperature.

[0070] With reference to FIGS. **9** and **10**, exemplary heating block assemblies **510**, **610** are depicted with respect to one or more packages **2000**, **2000A**, **2000B**. The heating block assembly **510** may at least partially define a configurable heat sealing surface **560**. The heating block assembly **510** may comprise an insulator and/or conductor segment configuration that is substantially similar to the heating block assemblies **10**, **210**, **310'** depicted in FIGS. **2**, **6**, and **7** and may comprise insulator segments **530a**, **530b** spaced apart by a conductor segment **532a** to define one large heating zone **562**. Heat passes from the conductor segment **532a** through a sealing belt **505** and into a first end surface **2000-1** of the package **2000** to seal one or more sections of the first end surface **2000-1**. In particular, heat from the heating zone **562** seals one or more sections of an overwrap **2002** that is formed around a matrix of articles **2004** (depicted with dashed lines), e.g., absorbent articles such as boxes of facial tissue, packages of diapers, etc., by fusing together two or more layers of a material of the overwrap **2002** adjacent to the heating zone **562**.

[0071] The heating block assembly **610** in FIG. **10** may at least partially define a configurable heat sealing surface **660**. The heating block assembly **610** may comprise an insulator and/or conductor segment configuration that is substantially similar to the heating block assemblies **10'**, **110**, **310** depicted in FIGS. **4**, **5**, **7** and may comprise insulator segments **630a-630c** and conductor segments **632a**, **632b**, in which the insulator segments **630a**, **630b** are spaced apart by the conductor segment **632a** and the insulator segments **630b**, **630c** are spaced apart by the conductor segment **632b**. The conductor segments **632a**, **632b** define first and second heating zones **662**, **664**, respectively. The heating block assembly **610** may be used to seal one or more sections of a first package **2000A** and a second package **2000B**, in which the first package **2000A** is positioned above or stacked on top of the second package **2000B** and advances with the second package **2000B** through the heat sealing section (see FIG. **8**). Heat passes from the conductor segment **632a** through a sealing belt **605** and into a first end surface **2000A-1** of the first package **2000A** to seal one or more sections of the first end surface **2000A-1**. In particular, heat from the first heating zone **662** seals one or more sections of an overwrap **2002A** that is formed around a matrix of articles **2004A** (shown with dashes lines)

by fusing together two or more layers of a material of the overwrap **2002A** adjacent to the first heating zone **662**. Heat similarly passes from the conductor segment **632b** through the sealing belt **605** and into a first end surface **2000B-1** of the second package **2000B**, such that heat from the second heating zone **664** fuses together two or more layers of a material of an overwrap **2002B** to substantially simultaneously seal one or more sections of the first end surface **2000B-1**, e.g., one or more sections of the overwrap **2002B** that is formed around a matrix of articles **2004B** (shown with dashed lines).

[0072] Although two packages **2000A**, **2000B** are depicted in FIG. **10**, it may be understood that three or more packages may be stacked on top of each other. In addition, it should be understood that the heat sealing surface **660** depicted in FIG. **10** may also be used to seal two or more sections of an end surface of a single package, e.g., package **2000** as shown in FIG. **9**, in which the package comprises dimensions that place portions of the end surface adjacent to both the first and second heating zone **662**, **664**. It should further be understood that a heating block assembly in accordance with the present disclosure may comprise three or heating zones (not shown) that may be used to seal one or more sections of one or more packages.

[0073] A second configurable heat sealing surface (not shown; see FIG. **8**) may be positioned opposite the heat sealing surface **560** in FIG. **9** and may comprise an insulator and/or conductor segment configuration that is similar to the configuration of the heat sealing surface **560** in order to seal one or more sections of a second end surface (not shown; see FIG. **8**) of the package **2000**. A second configurable heat sealing surface (not shown; see FIG. **8**) may likewise be positioned opposite the heat sealing surface **660** in FIG. **10** and may comprise an insulator and/or conductor segment configuration that is similar to the configuration of the heat sealing surface **660** in order to seal one or more sections of a second end surface (not shown; see FIG. **8**) of the first and second package **2000A**, **2000B**. The one or more sections of the first and second end surfaces **2000-1**, **2000A-1**, **2000B-1** of the respective packages **2000**, **2000A**, **2000B** may be sealed substantially simultaneously, e.g., by advancing the packages **2000**, **2000A**, **2000B** through a heat sealing section similar to that shown in FIG. **8** in which heat is applied to both end surfaces of the package from a series of aligned heating block assemblies.

[0074] FIG. **11** depicts an envelope folding pattern and a heat-affected zone **2006** in the first end surface **2000-1**, **2000A-1**, **2000B-1** that may be generated after the packages **2000**, **2000A**, **2000B** are advanced along a respective one of the configurable heat sealing surfaces **560**, **660** in FIGS. **9** and **10**. For comparison, a conventional heat-affected zone **2008** is shown. The conventional heat-affected zone **2008** is generated using a conventional heat sealing apparatus as described herein, in which a single, large heating zone extending across an entirety of the heat sealing surface subjects substantially an entirety of the end surface of the package to heating. Portions of overwrap material in the large, conventional heat-affected zone **2008** undergo premature heat shrinking and generate a complete seal of the first end surface **2000-1**, **2000A-1**, **2000B-1** prior to entering the heat shrink tunnel, which leads to bunching and veining. A vertical dimension of the heat-affected zone **2006** produced by the heat sealing surfaces **560**, **660** in accordance with the present disclosure is much smaller, as compared to the conventional heat-affected zone **2008**. This smaller vertical dimension of the heat-affected zone **2006** minimizes or eliminates premature heat shrinking, which allows the overwrap material to flow properly during heat shrinking and reduces veining on the display panel(s) (not labeled), as shown below. In some instances, because the heat-affected zone **2006** produced in accordance with the present disclosure is smaller than the conventional heat-affected zone **2008**, additional heating time and/or higher temperatures may be needed to ensure that the seal between the layers of the overwrap material has enough strength to avoid separation during conveyance and/or during the heat shrinking process. Although only one heat affected zone **2006** is depicted in FIG. **11**, it is understood that the package **2000**, **2000A**, **2000B** may comprise two or more heat affected zones (not shown), in which the number of heat affected zones corresponds to the number of heating zones.

[0075] FIGS. **12** and **14** are photographs of packages formed using conventional processes, and FIGS. **13** and **15** are photographs of similar packages formed using processes in accordance with the present disclosure. With reference to FIG. **12**, a package **3000** containing six boxes of facial tissues comprises a display panel **3000-1** with graphics **3003** extending over substantially an entirety thereof. The package **3000** is made with a conventional heat sealing process. It can be seen that the display panel **3000-1** includes several defects **3005** where the overwrap material is bunched together and ink from the graphics **3003** is collected to form dark, visible lines. In addition, the display panel **3000-1** includes defects **3005** in the form of stretching, wrinkling, and distortion, which are believed to be due to uneven shrinking of the overwrap material. FIG. **13** is a photograph of a substantially similar package **4000** with substantially similar graphics **4003**, in which the package **4000** is formed in accordance with the present disclosure. It can be seen that a display panel **4000-1** of the package **4000** contains no visible defects and that the graphics **4003** are clear with no visible distortion or collection of ink.

[0076] FIGS. **14** and **15** are photographs of packages **5000**, **6000** containing ten boxes of facial tissue. A display panel **5000-1** of the package **5000** of FIG. **14**, which is formed using a conventional process, has multiple defects **5005**, including bunching of the overwrap material in some areas and overstretching of the overwrap material in other areas. The display panel **5000-1** also includes areas where ink from the graphics **5003** is collected, along with overall distortion and misalignment of the graphics **5003** and areas where the overwrap material is overstretched to the point that portions of the graphics **5003** are washed out. FIG. **15** is a photograph of a substantially similar package **6000** with substantially similar graphics **6003** that is formed in accordance with the present disclosure. It can be seen that a display panel **6000-1** of the package **6000** contains no visible defects and that the graphics **6003** are clear, properly aligned, and contain no visible distortion or collection of ink.

[0077] A configuration of a configurable heat sealing surface in accordance with the present disclosure may be quickly and easily changed to accommodate each package **2000** or stack of packages **2000A**, **2000B**. In a conventional heat sealing apparatus, altering any properties of the heat sealing surface generally requires removing and/or replacing entire heating block assemblies, which can be a difficult and lengthy process. Conducting maintenance likewise requires removing/replacing the entire heating block assembly. In contrast, a configuration of a heat sealing surface in accordance with the present disclosure may be quickly and easily adjusted by altering the insulator and/or conductor segment configuration of one or more heating block assemblies define a different number of heating zones, change a vertical and/or horizontal location of one or more of the heating zones, and/or change a dimension of the one or more heating zones.

[0078] For example, following sealing of the package **2000** in FIG. **9**, it may be desirable to change the insulator and/or conductor segment configuration of the heating block assembly **510** to a configuration that permits sealing of a double-stack package configuration as shown in FIG. **10**. One or more of the insulator and/or conductor segments **530a**, **530b**, **532a** of the heating block assembly **510** may be removed as described herein and replaced with one or more insulator and/or conductor segments of a different length (not labeled; see FIGS. **2** and **4**), e.g., the insulator and conductor segments **630a-c**, **632a**, **632b** of FIG. **10**, such that the configuration of the heat sealing surface **560** is altered without the need to remove the heating block assembly **510**. In addition, any damaged insulator and/or conductor segments can easily be removed and replaced without the need to remove the heating block assemblies **510**, **610**.

[0079] In other examples, the controller (not shown; see FIG. **1**) may selectively control operation of the heating block assemblies within a heat sealing surface, thereby allowing a single heat sealing surface to accommodate packages of differing dimensions and/or different numbers of packages without the need to change the insulator and/or conductor segment configuration between runs. For instance, the controller may selectively provide power to one or more of the heating block assemblies to achieve a desired configuration of the heat sealing surface, e.g., a desired number,

dimension, and/or location of heating zones in a vertical and/or horizontal direction. In particular, the controller may be configured to selectively provide power to pairs of heating block assemblies such that heating zone(s) of one pair of heating block assemblies are a first temperature and heating zone(s) of an adjacent pair of heating block assemblies are a second temperature that is different from the first temperature

[0080] With reference to FIG. 7, when a (single-stack) package, e.g., package **1000** in FIG. 8, is advanced along the heat sealing surface **360**, the controller (not shown; see FIG. 1) may selectively provide power only to the heating elements **358** of pairs **328b** of heating block assemblies **310'**, such that only the appropriate heating zone, e.g., heating zone **362'**, is active (i.e., at or above a temperature necessary to melt the material of the overwrap) and conducting heat to seal only the one or more sections of the first end surface **1000-1** of the package **1000**. The heat sealing surface **360** may then be adapted for two (double-stacked) packages, e.g., packages **2000A**, **2000B** in FIG. 10, by selectively providing power only to the heating elements **358** of pairs **328a** of heating block assemblies **310**, such that only the appropriate heating zone, e.g., heating zones **362**, **364**, are active and conducting heat to seal only the one or more sections of the first end surfaces **2000A-1**, **2000B-1** of the first and the second package **2000A**, **2000B**.

[0081] Alternatively, with continued reference to FIG. 7, the controller (not shown) may provide power to all of the heating block assemblies **310**, **310'** simultaneously such that the heating zones **362**, **364** or **362'** of only one of the pairs **328a** or **328b** of heating block assemblies **310**, **310'** are at or above the temperature necessary to melt the material of the overwrap and the heating zones **362**, **364** or **362'** of the other one of the pairs **328a** or **328b** of heating block assemblies **310**, **310'** are above room temperature but below the temperature necessary to melt the material of the overwrap. In the case of a polyethylene overwrap, when a (single-stack) package (not shown) is advanced along the heat sealing surface **360**, the controller may provide power to the pairs **328a** of heating block assemblies **310** such that the heating zones **362**, **364** are at a temperature necessary to melt polyethylene, e.g., 150° C. or higher. The controller may simultaneously provide power to the adjacent pairs **328b** of heating block assemblies **310'** such that the heating zone **362'** is at a lower temperature, e.g., 125° C., that does not melt polyethylene. This selective control of the heating block assemblies **310**, **310'** limits the dimensions of the heat-affected zone of the package (see FIG. 11). For double-stacked packages, the controller may provide power such that the heating zones **362**, **364**, **362'** of all of the heating block assemblies **310**, **310'** are at or above 150° C. Maintaining the inactive pair(s) of heating block assemblies at a minimum temperature that is above room temperature but below the temperature needed to melt the material of the overwrap may minimize the time needed to bring the heating zones of the inactive pairs to the required temperature and may increase the number of runs that may be performed using a single configurable heat sealing surface. [0082] FIG. 16 is a flow diagram illustrating an exemplary method **7000** for sealing at least one portion of a package in accordance with the present disclosure. The method **7000** begins providing a configurable heat sealing surface at Step **7002** and selectively adjusting a configuration of the configurable heat sealing surface to define one or more heating zones at Step **7004**. At Step, **7006**, the package is advanced along the configurable heat sealing surface adjacent to the one or more heating zones to seal the at least one portion of the package, after which the method **7000** may conclude.

[0083] Representative embodiments of the present disclosure described above can be described as follows: [0084] A. A heating block assembly comprising: [0085] one or more configurable insulator segments; and [0086] a heater block comprising a first surface configured to removably receive the one or more configurable insulator segments, [0087] wherein each of the one or more configurable insulator segments covers only a portion of the first surface. [0088] B. The heating block assembly according to paragraph A, wherein each of the one or more configurable insulator segments comprises an inner surface positioned adjacent to the first surface of the heater block and an outer surface opposite the inner surface. [0089] C. The heating block assembly according to

paragraph B, wherein each of the one or more configurable insulator segments comprises a thickness of between 2.9 and 3.1 mm, wherein the thickness is defined between the inner and outer surfaces. [0090] D. The heating block assembly according to paragraphs B or C, wherein a temperature of the outer surface of each of the one or more configurable insulator segments is between 20% and 30% less than a temperature of the first surface of the heater block. [0091] E. The heating block assembly according to any of paragraphs A to D, wherein the first surface of the heater block comprises a first extension and a second extension and wherein each of the one or more configurable insulator segments comprises a first corresponding channel and a second corresponding channel configured to receive the respective first and second extensions. [0092] F. The heating block assembly according to any of paragraphs A to E, wherein the heater block comprises aluminum and wherein each of the one or more configurable insulator segments comprises polyether ether ketone. [0093] G. The heating block assembly according to any of paragraphs A to F, wherein the heater block is configured to receive a heating cartridge and the heater block comprises a thermally conductive material. [0094] H. The heating block assembly according to any of paragraphs A to G, further comprising one or more configurable conductor segments each comprising a thermally conductive material. [0095] I. The heating block assembly according to paragraph H, wherein the one or more configurable insulator segments comprise a first insulator segment and a second insulator segment, and wherein the first and second insulator segments are spaced apart from each other along a longitudinal length of the heater block by at least one of the one or more configurable conductor segments to define at least one heating zone. [0096] J. The heating block assembly according to paragraph I, wherein the first insulator segment comprises a first length and the second insulator segment comprises a second length that is the same as or different from the first length. [0097] K. A heat sealing apparatus comprising at least a first heating block assembly and a second heating block assembly, each of which comprises: [0098] one or more configurable insulator segments; and [0099] a heater block comprising a first surface configured to removably receive the one or more configurable insulator segments, [0100] wherein each of the one or more configurable insulator segments covers only a portion of the first surface. [0101] L. The heat sealing apparatus according to paragraph K, wherein the first heating block assembly comprises a first insulator segment and the second heating block assembly comprises a second insulator segment, and wherein when the first and second heating block assemblies are positioned side-by-side, at least one of top edges or bottom edges of the first and second insulator segments are horizontally aligned with each other. [0102] M. The heat sealing apparatus according to paragraphs K or L, further comprising a plurality of configurable conductor segments, wherein the first heating block assembly comprises first and second insulator segments spaced apart from each other along a longitudinal length of the heater block of the first heating block assembly by at least one of the plurality of configurable conductor segments, and wherein the second heating block assembly comprises third and fourth insulator segments spaced apart from each other along a longitudinal length of the heater block of the second heating block assembly by at least one of the plurality of configurable conductor segments. [0103] N. The heat sealing apparatus according to paragraph M, wherein the first and second heating block assemblies are positioned side-by-side and wherein at least one of: at least one of top edges or bottom edges of the first and third insulator segments are horizontally aligned with each other; or at least one of top edges or bottom edges of the second and fourth insulator segments are horizontally aligned with each other. [0104] O. The heat sealing apparatus according to any of paragraphs K to N, wherein the first heating block assembly is positioned to at least partially define a first heat sealing surface configured to seal a portion of a first end surface of a package, and wherein the second heating block assembly is positioned opposite the first heating block assembly to at least partially define a second heat sealing surface configured to seal a portion of a second end surface of the package. [0105] P. A heat sealing apparatus comprising: a configurable heat sealing surface comprising one or more heating zones each defined by one or more configurable insulator segments and one or more configurable

conductor segments, wherein each of the one or more configurable insulator segments covers only a portion of the configurable heat sealing surface. [0106] Q. The heat sealing apparatus according to paragraph P, wherein the configurable heat sealing surface comprises a first configurable heat sealing surface, the heat sealing apparatus further comprising: a second configurable heat sealing surface comprising one or more second heating zones each defined by one or more second configurable insulator segments and one or more second configurable conductor segments, wherein each of the one or more second configurable insulator segments covers only a portion of the second configurable heat sealing surface. [0107] R. The heat sealing apparatus according to paragraph Q, wherein the first configurable heat sealing surface comprises a first insulator segment configuration and wherein the second configurable heat sealing surface comprises a second insulator segment configuration that is the same as or different from the first insulator segment configuration. [0108] S. The heat sealing apparatus according to paragraphs Q or R, wherein the first configurable heat sealing surface comprises one or more first heating block assemblies, each of the one or more first heating block assemblies comprising a first heater block with a first surface configured to removably receive the one or more configurable insulator and conductor segments, wherein the one or more configurable insulator segments each cover only a portion of the first surface of the first heater block; and the second configurable heat sealing surface comprises one or more second heating block assemblies, each of the one or more second heating block assemblies comprising a second heater block with a first surface configured to removably receive the one or more second configurable insulator and conductor segments, wherein the one or more second configurable insulator segments each cover only a portion of the first surface of the second heater block. [0109] T. The heat sealing apparatus according to paragraph S, wherein the one or more first heating block assemblies comprise a first plurality of heating block assemblies, the first plurality of heating block assemblies comprising a first pair of heating block assemblies and a second pair of heating block assemblies positioned side-by-side with the first pair of heating block assemblies, the heat sealing apparatus further comprising: a controller operatively coupled to each of the first plurality of heating block assemblies and configured to selectively operate the first and second pairs of heating block assemblies. [0110] U. The heat sealing apparatus according to paragraph T, wherein the first pair of heating block assemblies comprises a first insulator segment configuration and the second pair of heating block assemblies comprises a second insulator segment configuration that is different from the first insulator segment configuration, the controller being configured to selectively provide power to the first and second pair of heating block assemblies such that the one or more heating zones of the first pair of heating block assemblies comprise a first temperature and the one or more second heating zones of the second pair of heating block assemblies comprise a second temperature that is different from the first temperature. [0111] V. A method for sealing at least one portion of a package, the method comprising: [0112] providing a configurable heat sealing surface; [0113] selectively adjusting a configuration of the configurable heat sealing surface to define one or more heating zones; and [0114] advancing the package along the configurable heat sealing surface adjacent to the one or more heating zones to seal the at least one portion of the package. [0115] W. The method according to paragraph V, wherein selectively adjusting the configuration of the configurable heat sealing surface comprises adjusting at least one of (i) a number of heating zones, (ii) a vertical location of the one or more heating zones, (iii) a horizontal location of the one or more heating zones, or (iv) a dimension of the one or more heating zones. [0116] X. The method according to paragraphs V or W, wherein the configurable heat sealing surface comprises a plurality of heating block assemblies each comprising a heater block with one or more configurable insulator segments and one or more configurable conductor segments that define the one or more heating zones. [0117] Y. The method according to paragraph X, wherein selectively adjusting the configuration of the configurable heat sealing surface comprises, for each of the plurality of heating block assemblies, selectively positioning the one or more configurable insulator and conductor segments along a longitudinal length of the heater block to define the one

or more heating zones. [0118] Z. The method according to paragraphs X or Y, wherein the plurality of heating block assemblies comprise a first pair of heating block assemblies and a second pair of heating block assemblies, the method further comprising: selectively operating the first and second pairs of heating block assemblies to seal the at least one portion of the package. [0119] AA. The method according to paragraph Z, wherein the first and second pair of heating block assemblies are positioned side-by-side. [0120] BB. The method according to paragraphs Z or AA, wherein the package comprises a first package, the method further comprising: selectively providing power to the first pair of heating block assemblies to seal the at least one portion of the first package; after sealing the at least one portion of the first package, advancing a second package along the configurable heat sealing surface; and selectively providing power to the second pair of heating block assemblies to seal at least one portion of the second package. [0121] CC. The method according to paragraph BB, wherein the first pair of heating block assemblies comprises a first insulator segment configuration and the second pair of heating block assemblies comprises a second insulator segment configuration different from the first insulator segment configuration. [0122] DD. The method according to any of paragraphs V to CC, wherein the configuration of the configurable heat sealing surface comprises a first configuration, the method further comprising: after sealing the at least one portion of the package, selectively adjusting the configuration of the configurable heat sealing surface to comprise a second configuration defining one or more second heating zones, the second configuration being different from the first configuration. [0123] EE. The method according to paragraph DD, further comprising: advancing a second package along the configurable heat sealing surface adjacent to the one or more second zones to seal at least one portion of the second package. [0124] FF. The method according to any of paragraphs V to EE, wherein the one or more heating zones comprise a first heating zone and a second heating zone that is positioned above or below the first heating zone, and wherein the package comprises a first package, the method further comprising: positioning a second package above or below the first package; and advancing the second package along the configurable heat sealing surface with the first package, wherein one of the first or the second heating zone seals the at least one portion of the first package and the other of the first or the second heating zone simultaneously seals at least one portion of the second package. [0125] GG. The method according to any of paragraphs V to FF, wherein the configurable heat sealing surface comprises a first configurable heat sealing surface, the method further comprising: providing a second configurable heat sealing surface positioned opposite the first configurable heat sealing surface; and selectively adjusting a configuration of the second configurable heat sealing surface to define one or more second heating zones. [0126] HH. The method according to paragraph GG, wherein the at least one portion of the package comprises a first end surface and wherein advancing the package along the first configurable heat sealing surface seals at least a section of the first end surface of the package. [0127] II. The method according to paragraph HH, wherein the at least one portion of the package further comprises a second end surface positioned opposite the first end surface, the method further comprising: advancing the package along the second configurable heat sealing surface adjacent to the one or more second heating zones to seal at least one section of the second end surface of the package. [0128] JJ. The method according to paragraph II, wherein the package is advanced along the first and second configurable heat sealing surfaces such that the at least one sections of the first and second end surfaces of the package are sealed simultaneously. [0129] KK. The method according to any of paragraphs V to JJ, further comprising: after advancing the package along the configurable heat sealing surface, subjecting the package to a heat shrinking process. [0130] The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as “40 mm” is intended to mean “about 40 mm.”

[0131] Every document cited herein, including any cross referenced or related patent or application and any patent application or patent to which this application claims priority or benefit thereof, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any invention disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such invention. Further, to the extent that any meaning or definition of a term in this document conflicts with any meaning or definition of the same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

[0132] While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

Claims

1. A method for sealing at least one portion of a package, the method comprising: providing a configurable heat sealing surface that comprises a heater block, wherein the heater block defines a longitudinal axis and is configured to removably receive various configurable insulator segments, wherein the various configurable insulator segments each cover only a portion of the heater block; selectively adjusting a configuration of the configurable heat sealing surface to define one or more heating zones; and advancing the package along the configurable heat sealing surface adjacent to the one or more heating zones to seal the at least one portion of the package.
2. The method of claim 1, wherein selectively adjusting the configuration of the configurable heat sealing surface comprises adjusting at least one of (i) a number of heating zones, (ii) a vertical location of the one or more heating zones, (iii) a horizontal location of the one or more heating zones, or (iv) a dimension of the one or more heating zones.
3. The method of claim 1, wherein the configurable heat sealing surface comprises a plurality of heating block assemblies each comprising a respective heater block with one or more configurable insulator segments and one or more configurable conductor segments that define the one or more heating zones.
4. The method of claim 1, wherein selectively adjusting the configuration of the configurable heat sealing surface comprises selectively positioning the one or more configurable insulator and conductor segments along the longitudinal axis of the heater block to define the one or more heating zones.
5. The method of claim 3, wherein the plurality of heating block assemblies comprise a first pair of heating block assemblies and a second pair of heating block assemblies, the method further comprising: selectively operating the first and second pairs of heating block assemblies to seal the at least one portion of the package.
6. The method of claim 5, wherein the first and second pair of heating block assemblies are positioned side-by-side.
7. The method of claim 5, wherein the package comprises a first package, the method further comprising: selectively providing power to the first pair of heating block assemblies to seal the at least one portion of the first package; after sealing the at least one portion of the first package, advancing a second package along the configurable heat sealing surface; and selectively providing power to the second pair of heating block assemblies to seal at least one portion of the second package.
8. The method of claim 7, wherein the first pair of heating block assemblies comprises a first insulator segment configuration and the second pair of heating block assemblies comprises a

second insulator segment configuration different from the first insulator segment configuration.

9. The method of claim 1, wherein the configuration of the configurable heat sealing surface comprises a first configuration, the method further comprising: after sealing the at least one portion of the package, selectively adjusting the configuration of the configurable heat sealing surface to comprise a second configuration defining one or more second heating zones, the second configuration being different from the first configuration.

10. The method of claim 9, further comprising: advancing a second package along the configurable heat sealing surface adjacent to the one or more second zones to seal at least one portion of the second package.

11. The method of claim 1, wherein the one or more heating zones comprise a first heating zone and a second heating zone that is positioned above or below the first heating zone, and wherein the package comprises a first package, the method further comprising: positioning a second package above or below the first package; and advancing the second package along the configurable heat sealing surface with the first package, wherein one of the first or the second heating zone seals the at least one portion of the first package and the other of the first or the second heating zone simultaneously seals at least one portion of the second package.

12. The method of claim 1, wherein the configurable heat sealing surface comprises a first configurable heat sealing surface, the method further comprising: providing a second configurable heat sealing surface positioned opposite the first configurable heat sealing surface; and selectively adjusting a configuration of the second configurable heat sealing surface to define one or more second heating zones.

13. The method of claim 12, wherein the at least one portion of the package comprises a first end surface and wherein advancing the package along the first configurable heat sealing surface seals at least a section of the first end surface of the package.

14. The method of claim 13, wherein the at least one portion of the package further comprises a second end surface positioned opposite the first end surface, the method further comprising: advancing the package along the second configurable heat sealing surface adjacent to the one or more second heating zones to seal at least one section of the second end surface of the package.

15. The method of claim 14, wherein the package is advanced along the first and second configurable heat sealing surfaces such that the at least one sections of the first and second end surfaces of the package are sealed simultaneously.

16. The method of claim 1, further comprising: after advancing the package along the configurable heat sealing surface, subjecting the package to a heat shrinking process.
