

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284583

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Mehta; Chintan et al.

COMPLIANCE TRACKING AND REMEDIATION ACROSS A DATA SHARING PLATFORM

Abstract

A system, method, and computer-readable media include detecting a noncompliance event based on content accessed by one or more user devices and served by an experience provider that is noncompliant with a data sharing preference of the one or more user devices, providing an alert on a graphical user interface (GUI) of a client application, remediating the detected noncompliance event according to a remediation selection of one or more options based on executing an API call with the experience provider by: transmitting a warning to the experience provider regarding a penalty for the noncompliance, receiving, from the experience provider, a data structure comprising a tabulation of funds due to resolve the penalty, verifying the tabulation of funds due, and depositing the funds due into an account of a user of the one or more user devices to resolve the penalty.

Inventors: Mehta; Chintan (San Ramon, CA), Strle; Jason (San Francisco, CA)

Applicant: Wells Fargo Bank, N.A. (San Francisco, CA)

Family ID: 87882431

Assignee: Wells Fargo Bank, N.A. (San Francisco, CA)

Appl. No.: 19/220400

Filed: May 28, 2025

Related U.S. Application Data

parent US continuation 18234833 20230816 parent-grant-document US 12339735 child US 19220400

parent US continuation 17316524 20210510 parent-grant-document US 11748189 child US 18234833

Publication Classification

Int. Cl.: **G06F11/07** (20060101); **G06F11/32** (20060101); **G06F21/53** (20130101); **H04L9/40** (20220101); **H04L67/133** (20220101)

U.S. Cl.:

CPC **G06F11/0793** (20130101); **G06F11/327** (20130101); **G06F21/53** (20130101); **H04L63/0272** (20130101); **H04L67/133** (20220501);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS AND CLAIM OF PRIORITY [0001] This application is a continuation of U.S. patent application Ser. No. 18/234,833, filed Aug. 16, 2023, which is a continuation of U.S. patent application Ser. No. 17/316,524, filed May 10, 2021, each of which is incorporated herein by reference in its entirety and for all purposes.

TECHNICAL FIELD

[0002] The present application relates to data sharing. More particularly, the present application relates to configuring permission settings with a platform, which dictate how user data is shared with experience providers.

BACKGROUND

[0003] User data has become one of the most sought after resources in the modern digital world. From websites to IoT devices, a wide variety of computing-enabled components are constantly tracking and cataloging user data. Users may come to find their data in the hands of unintended actors, and contrarily, not in the hands of intended recipients. Furthermore, some intended recipients of a user's data may use the user's data contrary to the user's wishes. Furthermore, users typically do not receive any benefit when an entity shares the user's data with another entity.

SUMMARY

[0004] One embodiment relates to a method. The method includes receiving, by a computing system associated with a platform provider, an input of a user to enable a data security tool of the platform provider. The method includes enabling, by the computing system, the data security tool. The method includes cataloging, by the computing system and via the data security tool, content accessed by the user and associated with an experience provider. The method includes detecting, by the computing system, a noncompliance event, the noncompliance event based on content accessed by the user and served by the experience provider that is noncompliant with at least one data sharing preference of the user. The method includes remediating, by the computing system, the detected noncompliance event.

[0005] Another embodiment relates to a system. The system includes a processing circuit having at least one processor coupled to at least one memory storing instructions that, when executed by the at least one processor, cause the processing circuit to receive an input of a user to enable a data security tool of the system. The at least one memory storing instructions that, when executed by the at least one processor, cause the processing circuit to enable the data security tool. The at least one memory storing instructions that, when executed by the at least one processor, cause the processing circuit to catalog, via the data security tool, content accessed by the user and associated with an experience provider. The at least one memory storing instructions that, when executed by the at least one processor, cause the processing circuit to detect a noncompliance event, the noncompliance event based on content accessed by the user and served by the experience provider that is noncompliant with at least one data sharing preference of the user. The at least one memory

storing instructions that, when executed by the at least one processor, cause the processing circuit to remediate the detected noncompliance event.

[0006] Another embodiment relates to a non-transitory computer readable media having computer-executable instructions embodied therein that, when executed by a processor of a server system, cause the server system to perform operations. The operations include receiving an input of a user to enable a data security tool of the server system. The operations include enabling the data security tool. The operations include cataloging, via the data security tool, content accessed by the user and associated with an experience provider. The operations include detecting a noncompliance event, the noncompliance event based on content accessed by the user and served by the experience provider that is noncompliant with at least one data sharing preference of the user. The operations include remediating the detected noncompliance event.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1 is a schematic diagram of a data sharing and permissioning computing system I 00, according to an example embodiment;

[0008] FIG. 2 is a flow diagram of a method for processing a data sharing and permissioning request from an experience provider, according to an example embodiment;

[0009] FIG. 3 is a flow diagram of a method for processing a data sharing and permissioning request from an experience provider, according to another example embodiment;

[0010] FIG. 4 is a flow diagram of a method for a data sharing and permissioning interaction with an experience provider, according to an example embodiment;

[0011] FIG. 5 is a flow diagram of a method for a data sharing and permissioning interaction with an experience provider, according to another example embodiment;

[0012] FIG. 6 is a flow diagram of a method for a data sharing and permissioning interaction with an experience provider, according to yet another example embodiment;

[0013] FIG. 7 is an illustration of a dynamic graphical user interface displayed on a user device as part of a data sharing process, according to an example embodiment;

[0014] FIG. 8 is an illustration of a dynamic graphical user interface displayed on a user device while accessing experience provider content using a data sharing protocol, according to an example embodiment;

[0015] FIG. 9 is an illustration of a dynamic graphical user interface displayed on a user device while interacting with an experience provider computing system using the data sharing protocol, according to an example embodiment;

[0016] FIG. 10 is an illustration of a dynamic graphical user interface displayed on a user device during a registration process of a data sharing and permissioning service, according to an example embodiment; and

[0017] FIG. 11 is an illustration of a dynamic graphical user interface for a message center displayed on a user device, according to an example embodiment.

[0018] It will be recognized that some or all of the figures are schematic representations for purposes of illustration. The figures are provided for the purpose of illustrating one or more embodiments with the explicit understanding that they will not be used to limit the scope or the meaning of the claims.

DETAILED DESCRIPTION

[0019] According to example embodiments described herein, systems and methods are described that includes users, experience providers and a platform. The experience providers (which exist today) provide some sort of experience for the user, such as social networking (e.g., a social or professional networking website), shopping (e.g., an online retailer or auction website), news or

entertainment (e.g., a streaming service), and so on. Experience providers often desire to have information about the consumer so that they can customize the experience that is provided to meet the user's preferences. Typically, whenever the user interacts with the experience provider, the experience provider collects data about the user's preferences and, over time, builds up a corpus of data about the user. The more the user interacts with a particular experience provider, the greater the depth of data that the experience provider can gain about the user. Typically, while the user may have consented to a privacy policy or other agreement of the experience provider, the user may have little control over how that data is used. Various improvements to computer hardware and data security are described herein. Through the systems and methods provided, a user is able to choose who can see their data, use their data, and how experience providers monetize their viewership. Accordingly, by handing control of personal data back to the user, the systems and methods described herein improve data security by reducing the exposure of sensitive user data to both malicious actors and unintended experience providers. The unintended experience providers may include any variety of experience providers that access personal data of a user without the knowledge or consent of the user, such as an experience provider website accessing the personal data of the user in order to serve targeted advertisements that the user does not wish to be shown. [0020] As will be appreciated, some experience providers are larger than others. For example, a large social networking website may have a large number of users that interact with the experience provider, and many of those users may interact with the experience provider on a relatively frequent basis. Conversely, other experience providers may be relatively small, having far fewer users, and having users that tend to interact with the experience provider on a relatively infrequent basis.

[0021] According to example embodiments, a platform is provided that interconnects the users and the experience providers through a network of application programming interfaces (APIs) implemented by the platform and the experience providers. Users may sign up to use the platform as a service to help the user control their own data (user preferences, insights about the customer, and so on). Such control may include how the data is shared, who it is shared with, how it is monetized, and so on. Such control may be implemented on a real-time basis.

[0022] For the experience providers, according to example embodiments, the platform provides a mechanism to aggregate user data from the experience providers that participate in the service. In various embodiments, the experience providers may retain the data they have collected, and the APIs provide a mechanism for data sharing to effectively provide an aggregated data set. Hence, smaller experience providers may be given access to user data collected by other experience providers, potentially subject to the real-time approval of the user. In effect, this may help to level the playing field between large experience providers (which have a large corpus of user data) and small experience providers (which do not have a large internal corpus of data).

[0023] Additionally, for the experience providers, the platform may assist with implementing controls over access to the user data in a manner that comports with the user's preferences. For an experience provider, controlling how user data is utilized and shared (e.g., for purposes of complying with regulatory requirements) requires a layer of software development above and beyond that which is needed for purposes of providing the features and functionality that attract the user to the website in the first place. Such additional layer may comprise tools for maintaining audit trails, processes and procedures relating to data retention, and so on. In various embodiments, the platform provides a centralized system for implementing controls over access to the user data in a manner that comports with the user's preferences, thereby offloading some or all of this responsibility from experience providers that participate in the service to the platform. Hence, this allows the experience providers to focus on building out the particular features and functionality that attract users to their website. This benefit may be of interest to large and small experience providers alike.

[0024] In various embodiments, for a large experience provider, the platform may provide a

mechanism for users to specify the types of messages (e.g., advertisements) that they want to receive. For example, some users may not wish to receive any politically-oriented messages. Other users may only wish to receive certain types of political messages. To satisfy these preferences, in various embodiments, the experience providers may be tasked with classifying the content they provide according to a classification scheme. The classification scheme may be provided by the platform, by the experience provider, or by another entity (e.g., by a standards-setting organization). The classification scheme may be at various levels of granularity. For example, a high level classification may be political content, which may then be further broken down into further layers of sub-classifications (e.g., based on political issues, political orientation, branch of government, geographic region, and so on). When providing content to the user, the experience provider may then determine what types of political content the user is willing to view, if any. By participating in the platform, the experience provider may offload the duty of being the arbiter of what messages users receive and instead be a pure messaging website. To the extent an experience provider accurately classifies its content in accordance with an accepted classification scheme, and provides content to the user in accordance with the user's preferences, the risk associated with providing such content to the user is substantially reduced or eliminated.

[0025] In various embodiments, users that sign up for the service may create a digital identity proxy that the user may then use to interact with the experience providers in real time. For example, the digital identity proxy may have the general form “_____.xxx.” As a more specific example, the digital identity proxy for a particular user may be “johndoe437.i”. The digital identity proxy for another user may be “robertmulligan15.i”. In both cases, the digital identity proxy uniquely identifies those two particular users. When the user visits an experience provider website, the user uses their “i” digital identity proxy as a login credential and, on this basis, the experience provider recognizes the user as being someone that utilizes the services of the platform. With this in mind, the experience provider recognizes that it may send API calls to the platform to gain additional information about the user in real time (i.e., while the user is enjoying the features/functionality of the experience provider website, as opposed to in an offline manner). In various embodiments, the platform and the experience providers all provide various APIs that facilitate real-time interaction between the various entities. In that vein, for the experience providers, the APIs may be provided based on template APIs developed by the platform and reused by the experience provider, or the APIs may be custom-written according to an API documentation of the platform. In various embodiments, the user is able to control the access of the experience provider as part of the afore-mentioned real time process. Again, with the user in direct real time control of how the user's data is accessed, the privacy and other regulatory concerns of the experience provider around sharing of user data are substantially reduced or eliminated.

[0026] In various embodiments, the customer may access an application or website of the platform to set preferences as to how their data is to be shared. In various embodiments, the platform may be provided by an entity that already has a significant amount of information pertaining to a set of users, such as by a financial institution or consortium of financial institutions. Through the application, the user may then “turn on” or “turn off” various items of data that may be shared with experience providers.

[0027] In various embodiments, such preferences may also be received from the user in real time (e.g., while the user is visiting an experience provider website). In various embodiments, the platform is interconnected with various payment rails (e.g., Real Time Payments, ACH, Zelle,

[0028] Venmo, and so on) that may be used to make payments to the user as a result of decisions made by the user concerning the sharing of their data. Hence, an experience provider that wishes to access certain data of the user may offer to pay the user a modest sum to gain access to that data (e.g., in order to improve targeted advertising). For example, if the user's generic preferences state that certain data is not to be shared, an experience provider may send an offer to request access to the data. In response to the user approving such access, in real time, the experience provider may

make a payment of the modest sum to the user's bank account. In various embodiments, and in a related vein, the user may be offered higher payments to the extent that the user agrees to expose more of their data (whether the approval is in real time or not). In an example where a user has specified that they do not wish to receive any politically-oriented messages, an experience provider website may wish to offer the user payment for receiving such messages, on the assumption that the user is an "independent" (or when other user data suggests the user is an independent), and thus a highly desirable target for political messages. Hence, due to such features as the real time integration and API interconnections, the user is able to monetize the user's own data in a way not previously possible.

[0029] In various embodiments, the experience providers may also be brick and mortar establishments. For example, a user may make an online reservation at a restaurant using the user's digital identity proxy. The restaurant may then send API requests to the platform to learn more about the user's dining preferences. Hence, the platform may also provide merchant services to brick and mortar institutions in the same manner as other experience providers.

[0030] Accordingly, the systems and methods provided tangibly improve computer hardware. Typically, user data is stored in a plethora of locations, contained in pieces across a myriad of experience providers that a user interacts with over their lifetime. Furthermore, that data may be frequently distributed, incompletely, amongst the various experience providers. Through the innovations described herein, the user data may be aggregated, protected, and distributed by a single provider, thereby reducing the inefficient, incomplete distributions. These inefficient, incomplete distributions require power consumption, CPU clock cycles, memory allocation, and network bandwidth. Furthermore, these resource expenditures occur on both sides of the transmission. That is, the transmission issuing system must expend resources and the receiving system, likewise, must expend resources to receive, interpret, and act upon the transmission. Accordingly, by reducing the total amount of transmissions occurring on behalf of user data requests, the entire computational ecosystem is impacted and improved. These and other features and benefits are described more fully herein.

[0031] Furthermore, it will be appreciated that the digital identity proxy and secure-pop up login protocols described herein provide a specific technical improvement to the technological fields of data security and data distribution. Through the systems and methods of the present application, a user may associate their data with a specific experience provider, enforce a set of permissions for the experience provider (including what data may be used and what content may be served by the experience provider), and also dynamically adjust these associations and permissions in real-time such that data distribution may be halted with a single input of the user. The innovations described herein are directed towards safeguarding user data, distributing the user data according to a prerogative of the user, protecting and enforcing experience provider content served to the user, and other data sharing and permissioning tangential processes, such as the monetization of the user data. These concepts are inextricably tied to computer technology and distinct from the types of concepts found by the courts to be abstract.

[0032] Additionally, through the sharing and enforcing of the permission set associated with the user, the experience of the user while accessing experience provider content and devices is greatly improved. As an example, consider a user accessing a smart car and subsequently logging into the smart car computing system with a data sharing and permissioning protocol of a platform (e.g., as discussed herein). The smart car is then enabled to access a wide variety of data and preferences of the user, and formulate a custom experience based on the data and preferences. For example, the smart car may adjust a climate control system (e.g., to provide the ideal temperature of the user), establish a self-driving destination, and perform predictive operations (e.g., pre-order a favorite drink of the user at the self-driving destination). Accordingly, the experience of the user is greatly improved, as the smart car is enabled (e.g., by the systems and methods described herein) to integrate with the user in a harmonious and convenient manner (e.g., in order to provide custom

experiences). Furthermore, the performance of the smart car is improved by reducing the number of interactions with the user (e.g., destination prompts, climate preference prompts, entertainment selections and adjustments, etc.) such that tangible reductions in both clock cycles and memory are achieved (e.g., as each interactive operation with the user costs resources). Thus, by reducing the number of interactions required by the user, the user is enabled to focus on the automated driving experience and intercede when required (e.g., the user is able to more rapidly react to a traffic crisis rather than being distracted by an interface of the smart car).

[0033] Referring now to FIG. 1, a schematic diagram of a data sharing and permissioning computing system **100** is shown, according to an example embodiment. The data sharing and permissioning computing system **100** includes a user device **104**, a platform computing system **122**, and an experience provider computing system(s) **150**. The user device **104**, the platform computing system **122**, and the experience provider computing system(s) **150** are each communicably coupled and configured to exchange information over a network **118**, which may include one or more of the Internet, cellular network, Wi-Fi, Wi-Max, a proprietary banking network, a proprietary retail or service provider network, or other type of wired or wireless network.

[0034] The user device **104** may be a computing device associated with a user **102** (e.g., owned by, used by, etc.). The user device **104** may be or include a mobile phone, a tablet, a laptop, a desktop computer, an IoT-enabled device (e.g., an IoT-enabled smart car), a wearable device, a virtual/augmented reality (VR/AR) device, and/or other suitable user computing devices capable of accessing and communicating using local and/or global networks (e.g., the network **118**). Wearable computing devices refer to types of devices that an individual wears, including, but not limited to, a watch (e.g., a smart watch), glasses (e.g., eye glasses, sunglasses, smart glasses, etc.), bracelet (e.g., a smart bracelet), etc.

[0035] The user **102** may be a customer or client of the platform **120** associated with the platform computing system **122** (e.g., an account holder). In some embodiments, the user **102** may not have a previous relationship with the platform **120**, and therefore, may only be a user of the features recited herein (e.g., with regard to the data sharing and permissioning computing system **100**). Accordingly, the user **102** may be an individual, a representative(s) of a small or large business entity, any customer of the provider, and/or any user registered to utilize the data sharing and permissioning computing system **100**.

[0036] The user device **104** is shown to include a network interface circuit **106**, a processing circuit **108**, a client application **114**, and an input/output circuit **116**. The network interface circuit **106** is structured to establish connections with other computing systems (e.g., the platform computing system **122**, the experience provider computing system(s) **150**, etc.) via the network **118**. Accordingly, the network interface circuit **106** enables the user device **104** to transmit and/or receive information to and/or from the platform computing system **122** and the experience provider computing system(s) **150** over the network **118**. The network interface circuit **106** includes program logic that facilitates connection of the user device **104** to the network **118**. For example, the network interface circuit **106** may include a combination of wireless network transceivers (e.g., a cellular modem, a NFC transceiver, a Bluetooth transceiver, a Wi-Fi transceiver, etc.) and/or a wired network transceivers (e.g., an Ethernet transceiver). In some arrangements, the network interface circuit **106** includes the hardware and machine-readable media sufficient to support communication over multiple channels of data communication. Further, in some arrangements, the network interface circuit **106** includes cryptography capabilities to establish a secure or relatively secure communication session in which data communicated over the session is encrypted.

[0037] The processing circuit **108** includes a memory **110** and a processor **112**. The memory **110** may be one or more memory or storage devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing and/or facilitating the various processes described herein. Memory **110** may be or include non-transient volatile memory, non-

volatile memory, and non-transitory computer storage media. Memory **110** may include database components, object code components, script components, or other types of information structured for supporting the various activities and information structures described herein. The memory **110** may be coupled to the processor **112** and include computer code or instructions for executing one or more processes described herein. The processor **112** may be implemented as one or more processors, application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), a group of processing components, or other suitable electronic processing components. As such, the user device **104** is configured to run a variety of application programs and store associated data in the memory **110**. One such application may be the client application **114**.

[0038] The user device **104** includes a client application **114** (also referred to herein as the platform client application **114**) that is provided by and coupled to the platform computing system **122**. In some arrangements, the client application **114** may be a standalone application or be incorporated with an existing application of the user device **104** (e.g., integrated into a mobile banking application, a service provider application, etc.). The client application **114** may be downloaded by the user device **104** prior to its usage, hard coded into the memory **110** of the user device **104**, or be a network-based or web-based interface application such that the platform computing system **122** may provide a web browser to access the application, which may be executed remotely from the user device **104**. In the example shown, the client application **114** is downloaded to the user device **104** and provided by the platform computing system **122** via, for example, an app store for download. In the example shown, the client application **114** is structured as a data sharing and permission application (e.g., to assign and customize data sharing and permission preferences of the user **102**). The client application **114** may be developed and maintained (e.g., provided with software updates on a regular or semi-regular basis) by the platform **120** using the platform computing system **122**. Accordingly, the user device **104** may include software and/or hardware capable of implementing a network-based or web-based application. For example, in some instances, the client application **114** includes software such as HTML, XML, WML, SGML, PHP (Hypertext Preprocessor), CGI, and like languages.

[0039] In the latter web-based instance, the user **102** may have to log onto or access the web-based interface before usage of the application. Further, and in this regard, the client application **114** may be supported by the platform computing system **122** via one or more servers, processors, network interface circuits, etc. that transmit applications for use to the user device **104**. Furthermore, prior to use of the client application **114** and/or at various points throughout the use of the client application **114**, the user **102** may be required to provide various authentication information or login credentials (e.g., a password, a personal identification number (PIN), a fingerprint scan, a retinal scan, a voice sample, a face scan, any other type of biometric security scan) to ensure that the user **102** associated with the user device **104** is authorized to use the client application **114**.

[0040] The client application **114** is structured to provide displays (e.g., generated by the interface circuit **136** of the platform computing system **122** and transmitted over the network **118**) to the user **102** of the user device **104** in order to provide information pertaining to data sharing preferences (e.g., as described further herein). Accordingly, the user **102** may manage data sharing and permission settings that are maintained and distributed by the platform **120**, via the client application **114**.

[0041] The input/output circuit **116** is structured to receive communications from and provide communications to the user **102**. In this regard, the input/output circuit **116** is structured to exchange data, communications, instructions, etc. with an input/output component of the user device **104**. In one embodiment, the input/output circuit **116** includes an input/output device. In another embodiment, the input/output circuit **116** includes communication circuitry for facilitating the exchange of data, values, messages, and the like between an input/output device and the components of the user device **104**. In yet another embodiment, the input/output circuit **116** includes machine-readable media for facilitating the exchange of information between an

input/output device and the components of the user device **104**. In still another embodiment, the input/output circuit **116** includes a combination of hardware components, communication circuitry, and machine-readable media.

[0042] For example, in some embodiments, the input/output circuit **116** may include suitable input/output ports and/or uses an interconnect bus (not shown) for interconnection with a local display (e.g., a touchscreen display) and/or keyboard/mouse devices (when applicable), or the like, serving as a local user interface for programming and/or data entry, retrieval, or manipulation purposes. That is, the input/output circuit **116** provides an interface for the user **102** to interact with various applications (e.g., the client application **114**) accessed by the user device **104**.

[0043] Still referring to FIG. **1**, the platform computing system **122** is associated with (e.g., owned, managed, and/or operated by) the platform **120**. In the example depicted, the platform **120** is a financial institution capable of providing one or more products and services, such as the providing of various accounts, such as a demand deposit account, lending, money transfers, issuing credit and/or debit cards, wealth management, etc. Thus, the associated platform computing system **122** is structured to provide or otherwise facilitate providing the one or more products and services to customers. Additionally, the platform computing system **122** is structured to maintain, control access to, and provide data of the user **102** to experience provider computing systems **150** (e.g., as described further below, with reference to FIGS. **2** and **3**). As depicted, the platform computing system **122** is a backend computer system. The platform computing system **122** may be implemented using a computing system, such as a discrete server, a group of two or more computing devices/servers, a distributed computing network, a cloud computing network, and/or another type of computing system capable of accessing and communicating using local and/or global networks (e.g., the network **118**).

[0044] The platform computing system **122** includes a network interface circuit **124**, a processing circuit **126**, a token generator circuit **132**, a security circuit **134**, an interface circuit **136**, an access circuit **138**, a data management circuit **140**, and an input/output circuit **142**. The platform computing system **122** also includes a token repository **144**, a permissions repository **146**, and a user data repository **148**. In an alternate embodiment, the token repository **144**, and/or the permissions repository **146**, and/or the user data repository **148** may be a part of another computing system, accessed as needed by the platform computing system **122**.

[0045] The network interface circuit **124** is structured to establish communicable connections with other computing systems (e.g., the user device **104**, the experience provider computing system(s) **150**, other computing systems, etc.), by way of the network **118**. The network interface circuit **124** may include program logic that facilitates connection of the platform computing system **122** to the network **118**. For example, the network interface circuit **124** may include a combination of a wireless network transceivers (e.g., a NFC transceiver, a Bluetooth transceiver, a Wi-Fi transceiver, etc.) and/or a wired network transceiver (e.g., an Ethernet transceiver). In some arrangements, the network interface circuit **124** includes the hardware and machine-readable media sufficient to support communication over multiple channels of data communication. Further, in some arrangements, the network interface circuit **124** includes cryptography capabilities to establish a secure or relatively secure communication session in which data communicated over the session is encrypted.

[0046] The processing circuit **126** includes a memory **128** and a processor **130**. The memory **128** may be one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing and/or facilitating the various processes described herein. Memory **128** may be or include non-transient volatile memory, non-volatile memory, and non-transitory computer storage media. Memory **128** may include database components, object code components, script components, or other types of information structured for supporting the various activities and information structures described herein. The memory **128** may be coupled to the processor **130** and include computer code or instructions for executing one or more processes

described herein. The processor **130** may be implemented as one or more server processors, application specific integrated circuits (ASIC), field programmable gate arrays (FPGAs), digital signal processor (DSP), microprocessors, or other suitable electronic processing components. The server(s) or server computer may be geographically dispersed relative to other server(s) of the platform computing system **122**. Further, there may be a variety of different types of server(s) included in the computing system **122** (e.g., application server, database server, catalog sever, virtual private network (VPN) server, communications server, web server, and so on). The memory device may be included with the server(s). The platform computing system **122** is structured to run a variety of application programs and store associated data in a database of the memory **128**.

[0047] The platform computing system **122** further includes a token generator circuit **132**. The token generator circuit **132** is structured to generate and/or otherwise create access tokens for a user **102**. The access tokens are used in a token-based authentication to allow an experience provider computing system (e.g., experience provider computing system(s) **150**) to access an application programming interface (API) (e.g., via the access circuit **138**, as described further below) of the platform computing system **122**. Furthermore, the token generator circuit **132** is structured to generate access tokens which associatively map to both an expiration (e.g., a lifespan for the access token contained in the token repository **144**) and a set of user preferences and permissions (e.g., in the permissions repository **146** as further described below, with particular reference to FIGS. **2** and **3**). In an exemplary embodiment, the access tokens are opaque access tokens. That is, in such an embodiment, the access tokens are proprietarily formatted by the platform computing system **122** such that they contain no inherent identifying data of a user (e.g., the user **102**). Rather, such opaque tokens contain some identifier to information in a server's persistent storage (e.g., a persistent storage of the platform computing system **122**, such as the token and/or permissions repository **146**). The identifier may be a memory pointer, a database pointer, or any other identifier that may be modulated, or mapped to (e.g., associatively mapped via a data structure), by the platform computing system **122** in order to access data of the user **102**. In other embodiments, the access token may not be opaque, and may instead be an encrypted token directly containing the data of the user **102** (e.g., such as exemplified by a JSON Web Token (JWT)).

[0048] The security circuit **134** is structured to authenticate users (e.g., the user **102**) accessing the system in order to configure data sharing and permission preferences (e.g., via the interface circuit **136**, as described further below). The user **102** may authenticate with the platform computing system **122** via a variety of modalities input into the client application **114** (or a web-based version of the client application **114**, as described above), such as via a password, a fingerprint scan, a retinal scan, a voice sample, a face scan, and/or any other type of biometric security scan.

Furthermore, the security circuit **134** is structured to verify a supplemental authentication when applicable (e.g., a two-factor authentication (2FA) presented on the user device **104** via the client application **114**). The supplemental authentication may occur as part of a process to authorize an experience provider (e.g., the experience provider computing system(s) **150**) to access data of the user **102** (e.g., such as discussed below, with reference to FIGS. **2** and **3**). Additionally, the security circuit **134** is structured to authenticate experience provider computing system(s) **150** (e.g., subsequent to receiving an API call, via the access circuit **138**, as discussed below). The security circuit **134** may authenticate the experience provider computing system(s) **150** according to credentials contained in the JSON body of the API call, such as an API token that uniquely identifies the experience provider in the token repository **144** (e.g., provisioned by the platform computing system **122** to the experience provider computing system(s) **150**).

[0049] Still referring to FIG. **1**, the platform computing system **122** further includes an interface circuit **136**. The interface circuit **136** is structured to generate, compile, and otherwise create computer code executable on a processor of a user device (e.g., the user device **104**), which when executed, creates user-interactive user interfaces (e.g., as part of a data sharing and permission settings process, as described further herein). For example, the interface circuit **136** may generate a

user interface that enables a user (e.g., the user **102**) to: select experience providers for data sharing (e.g., via domain, internet protocol (IP) address, or a unique hardware device ID), configure permission sets (e.g., as described further below, with reference to FIGS. **2** and **4**), and configure security parameters (e.g., for a dependent account, as described further below with reference to FIGS. **2** and **3**). The user interface may then be provided to the user **102** via the client application **114** (e.g., over the network **118**).

[0050] The access circuit **138** is structured to initiate, receive, process, and respond to API calls (e.g., over the network **118**). That is, the access circuit **138** is the access point (e.g., such as a webserver) between the platform computing system **122** and the experience provider computing system(s) **150**. Accordingly, in order to process the various API calls, the access circuit **138** delegates specific tasks to the other circuits. For example, user logins are delegated to the security circuit **134** and access token creation is delegated to the token generator circuit **132**. Additionally, the access circuit **138** is structured to receive communication (e.g., API calls) from the interface circuit **136**, which captures inputs of the user **102**. That is, the interface circuit **136** may communicate selections of the user **102** to the platform computing system **122** via the access circuit **138**. Therefore, the access circuit **138** is communicatively coupled to the other circuits of the platform computing system **122**, either tangibly via hardware, or indirectly via software.

[0051] The data management circuit **140** is structured to handle a wide variety of tasks associated with the gathering, analysis, configuration, categorization, and permissioning of user data. The data management circuit **140** is structured to gather data about the user **102** from any accounts associated with the platform **120**, and also from experience provider computing system(s) **150**, such as social media websites. The data management circuit **140** may utilize web scraping algorithms and image recognition logic to pull and aggregate data of the user **102** into the user data repository **148**. Furthermore, the data management circuit **140** may then analyze and divide the user data into categories. For example, the data management circuit **140** may parse the user data (including the received updates, as further described in FIG. **2**) in order to identify applicable categories. That is, the data management circuit **140** may analyze (e.g., via any suitable data analysis or natural language processing technique) various data, such as search history, browsing history, image posting, file uploads/downloads (including metadata), transaction history, and location history (e.g., of the user **102**), and subsequently, associatively store them with categorical descriptors (e.g., in the user data repository **148**). The data management circuit **140** is further structured to process all permissioning and settings related tasks. That is, the data management circuit **140** is structured to: verify (e.g., via the permissions repository **146**) data sharing requests, apply rules to data of the user **102** (e.g., via the rules engine, as further discussed below) prior to providing the data of the user **102**, provide the applicable data of the user **102** (e.g., the data of the user **102** after rules have been applied), monitor the activity of the experience provider (e.g., as discussed further herein, with reference to FIG. **6**), calculate and process funds due to the user **102** (e.g., as discussed further herein, with reference to FIGS. **4**, **5**, and **6**), and generate messages (e.g., alerts and/or notifications) for the user **102** in response to identifying non-compliant content (e.g., as discussed further in FIG. **6**).

[0052] In some embodiments, the data management circuit **140** may be configured to assist experience providers with compliance of regulatory requirements such as data privacy requirements. Hence, in some embodiments, the data management circuit **140** may further be structured to implement a rules engine of the platform computing system **122**. The rules engine utilizes a set of logic (e.g., rules) to modulate, or truncate, data of the user **102** that is shared with experience providers based on the data sharing and permissioning settings of the user **102** (e.g., as discussed further herein), and all applicable regulatory and privacy requirements (also referred to herein as data privacy regulatory requirements). Furthermore, the rules utilized may be configured according to inputs of the user **102** (e.g., user inputs that pertain to data sharing and/or permissioning settings). The rules utilized may be further configured (e.g., through regular

maintenance and updates completed by an employee associated with the platform **120**) according to any applicable data privacy regulatory requirements. That is, the rules pertaining to data privacy regulatory requirements are regularly maintained (e.g., kept up-to-date) by the platform **120**. Accordingly, in response to a data sharing request from an experience provider, the rules engine may first access the permissions repository **146** and the user data repository **148** to gather data of the user **102** (e.g., as identified by the information contained in the permissions repository **146**), and subsequently modulate, or truncate, the gathered data to comport with any applicable data privacy regulatory requirements (e.g., such as may be applicable for medical data, financial data, etc.). The resulting data (e.g., the applicable data) of the user **102**, which is obtained after applying rules to modulate the data (e.g., as described above), may then be provided to the experience provider from which the data sharing request was received.

[0053] The data management circuit **140** is further structured to implement a payments engine of the platform computing system **122**. The payments engine utilizes a payment logic of the platform computing system **122** in order to determine, verify, and process any funds due to the user **102**, such as may occur as part of a shared-revenue request (e.g., as discussed herein, with reference to FIGS. **4**, **5**, and **6**). That is, the payments engine may determine, verify, and process an amount of funds due to the user **102** according to any applicable agreements in place between an experience provider and the user **102** (e.g., advertising and/or data access related). For example, the user **102** may have an agreement in place with an experience provider that dictates that the experience provider is to share revenue with the user **102** in the amount of \$0.03 for each advertisement displayed from a particular category (e.g., sports). Accordingly, in an example where the user **102** was shown ten (10) sports-related advertisements, the payments engine may calculate that the user **102** is due funds in the amount of 30 cents (e.g., **10** multiplied by the agreed-upon value of \$0.03 each). In examples where the experience provider provides a tabulation of funds due, the payments engine may verify the experience provider tabulation in a similar manner (e.g., prior to processing a payment for the user **102**). Furthermore, the payments engine is configured to process payments (e.g., by an API call, via the access circuit **138**) for the user **102**. That is, the payments engine may initiate an API call to deduct funds from an account of the experience provider and transfer funds to the user **102**. In embodiments where the user **102** has a financial account with the platform **120**, the payments engine may directly credit the account of the user **102** in the amount of the funds due.

[0054] The input/output circuit **142** of the platform computing system **122** is structured to exchange data, communications, instructions, etc. with an input/output component of the platform computing system **122** (e.g., a keyboard, a mouse, etc.) (e.g., with a platform **120** employee, non-employee, operator, etc.). In one embodiment, the input/output circuit **142** is incorporated into an input/output device. For example, a laptop, desktop, or tablet computer may include the input/output circuit **142** such that the laptop, desktop, or tablet computer is communicably coupled to the platform computing system **122**. The input/output circuit **142** is structured to receive communications from, and provide communications to, various platform **120** employees, agents, or operators associated with the platform computing system **122**.

[0055] The token repository **144** is configured to retrievably hold (e.g., in cache memory), store (e.g., in non-transitory memory), categorize, and/or otherwise serve as a repository for information pertaining to access tokens (e.g., generated access tokens as discussed further herein, with reference to FIGS. **2-6**), configuration option(s) associated with the access tokens (e.g., an expiration), users (e.g., associatively mapping the access tokens to a user), and API tokens provisioned to experience providers. Accordingly, the token repository **144** is configured to retrievably store and access information pertaining to access rights of an experience provider (e.g., access to the platform computing system **122** and access to data of the user **102**).

[0056] The permissions repository **146** is configured to retrievably hold (e.g., in cache memory), store (e.g., in non-transitory memory), categorize, and/or otherwise serve as a repository for information pertaining to permission settings of the user **102** (e.g., experience provider

designations for data sharing, the subsets of the data to share, advertising preferences and arrangements, and any such settings associated with a dependent of the user **102**).

[0057] The user data repository **148** is configured to retrievably hold (e.g., in cache memory), store (e.g., in non-transitory memory), categorize, and/or otherwise serve as a repository for information pertaining to the data of the user **102**. That is, the user data repository **148** serves as the central aggregation point for all of the categorized data of the user **102**, including pending alerts and notifications (e.g., as discussed further herein, with reference to FIG. **6**). Accordingly, the user data repository **148** may retrievably store data of the user **102** that has been collected from, among other sources, a plurality of experience providers (e.g., as discussed further herein, with reference to FIGS. **2** and **3**).

[0058] Still referring to FIG. **1**, the data sharing and permissioning computing system **100** further includes an experience provider computing system(s) **150**. As depicted, the experience provider computing system(s) **150** is a backend computer system. The experience provider computing system(s) **150** may be implemented using a computing system, such as a discrete server, a group of two or more computing devices/servers, a distributed computing network, a cloud computing network, and/or another type of computing system capable of accessing and communicating using local and/or global networks (e.g., the network **118**). For example, in some embodiments, the experience provider computing system(s) may be a webserver.

[0059] The experience provider computing system(s) **150** includes a network interface circuit **152**, a processing circuit **154**, and an input/output circuit **160**. The network interface circuit **152** is structured to establish communicable connections with other computing systems (e.g., the user device **104**, the platform computing system **122**, other computing systems, etc.), by way of the network **118**. The network interface circuit **152** may include program logic that facilitates connection of the experience provider computing system(s) **150** to the network **118**. For example, the network interface circuit **152** may include a combination of a wireless network transceivers (e.g., a NFC transceiver, a Bluetooth transceiver, a Wi-Fi transceiver, etc.) and/or a wired network transceiver (e.g., an Ethernet transceiver). In some arrangements, the network interface circuit **152** includes the hardware and machine-readable media sufficient to support communication over multiple channels of data communication. Further, in some arrangements, the network interface circuit **152** includes cryptography capabilities to establish a secure or relatively secure communication session in which data communicated over the session is encrypted.

[0060] The processing circuit **154** includes a memory **156** and a processor **158**. The memory **156** may be one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing and/or facilitating the various processes described herein. Memory **156** may be or include non-transient volatile memory, non-volatile memory, and non-transitory computer storage media. Memory **156** may include database components, object code components, script components, or other types of information structured for supporting the various activities and information structures described herein. The memory **156** may be coupled to the processor **158** and include computer code or instructions for executing one or more processes described herein. The processor **158** may be implemented as one or more server processors, application specific integrated circuits (ASIC), field programmable gate arrays (FPGAs), digital signal processor (DSP), microprocessors, or other suitable electronic processing components. Further, there may be a variety of different types of server(s) included in the experience provider computing system(s) **150** (e.g., application server, database server, communications server, web server, and so on). The memory device may be included with the server(s). The experience provider computing system(s) **150** is structured to run a variety of application programs and store associated data in a database of the memory **156**.

[0061] The input/output circuit **160** of the experience provider computing system(s) **150** is structured to exchange data, communications, instructions, etc. with an input/output component of the experience provider computing system(s) **150** (e.g., a keyboard, a mouse, etc.) (e.g., with an

experience provider employee, non-employee, operator, etc.). In one embodiment, the input/output circuit **160** is incorporated into an input/output device. For example, a laptop, desktop, or tablet computer may include the input/output circuit **160** such that the laptop, desktop, or tablet computer is communicably coupled to the experience provider computing system(s) **150**. The input/output circuit **160** is structured to receive communications from, and provide communications to, various experience provider employees, agents, or operators associated with the experience provider.

[0062] Referring now to FIG. **2**, a flow diagram of a method **200** for processing a data sharing and permissioning request from an experience provider is shown, according to an example embodiment. As a broad overview, method **200** includes a description of the data sharing and permissioning configuration process, in particular as it pertains to advertising. That is, method **200** describes the advertising negotiation process in detail (e.g., between the user **102** and the experience provider computing system **150**), including real-time negotiations, as it relates to the overall data sharing process. Hence, an experience provider that wishes to access certain data, or display certain advertisements, of/to the user **102** may offer to pay the user **102** a modest sum to gain access to that data (e.g., in order to improve targeted advertising), and/or to display advertisements from a particular category to the user **102**. As an example, method **200** may occur as part of a user (e.g., the user **102**) configuring settings for a website that they intend to visit, and then subsequently accessing the website (e.g., provided by the experience provider computing system **150**). Accordingly, a practical example of the user **102** configuring settings to access a sporting goods website is discussed throughout method **200**. Method **200** may be performed using the system of FIG. **1** such that reference is made to the components of FIG. **1** to aid the description of method **200**.

[0063] The method **200** begins at process **202** with the platform computing system **122** receiving an input from the user **102** that identifies an experience provider for data sharing (e.g., via an API call, by the client application **114**). It should be appreciated that process **202** presupposes an authenticated user-session in order to access the client application **114**. Any such required authentication may be completed via the security circuit **134** prior to accessing the client application **114** (e.g., via password, biometric scan, etc., as described above with reference to FIG. **1**). The input may be any variety of selections made by the user **102** via the user interface of the client application **114** (e.g., a drop-down box, a button, a highlighted row, etc.) and transmitted over the network **118**. Furthermore, the user **102** may identify the experience provider according to a variety of identifiers, such as a domain name, an IP address, and unique hardware identification numbers (e.g., a MAC address). In some embodiments, the user **102** may begin to type an identifier (e.g., “goog”) and an automatic predictive logic of the interface circuit **136** presents the user with auto-filled suggestions. For example, in the stated example, the interface circuit **136** may predict that the user **102** is starting to type “Google” and generate a selectable interaction point labeled accordingly (e.g., a pop-up row or button). Alternatively, the user **102** may enter an IP address, such as “8.8.8.8” (e.g., Google's public IPv4 DNS server, although it should be noted that any IP protocol version may be entered, such as IPv6). In that same vein, the automatic predictive logic of the interface circuit **136** may associate the IP address and provide a similar auto-filled suggestion. Alternatively, the user **102** may wish to share data and configure permissions for only the device identified by the IP address. In such a case, the user **102** may opt to not select the auto-filled suggestion. In some cases where the user **102** desires to share data and configure permissions for a specific device, particularly where there is concern for a pending change in the IP address, the user **102** may enter a unique hardware identification number, such as a MAC address. Furthermore, in some embodiments, the user **102** may also enter (e.g., via the client application **114**) an expiration (e.g., date and time) or a predetermined number of uses (e.g., data sharing events) during this process. For example, the user **102** may have access to an IoT-enabled vehicle for a day and wish to configure data sharing for the vehicle as a one-time event. In such a scenario, the user **102** may complete the method **200** while defining the data sharing and permissioning as granting a single-

use access.

[0064] Furthermore, it should be appreciated that the user **102** selection of an experience provider to share data with is a real-time updating processes and one that may occur at any point (e.g., in the methods **200**, **300**, **400**, **500**, and **600**). That is, at any point during use of the systems and methods described herein, the user **102** may access the graphical user interface (e.g., via the client application **114**) and disable data sharing with an experience provider (e.g., or with all experience providers, such as via a toggle generated by the interface circuit **136**). For example, the user **102** may access an experience provider (e.g., a website provided by the experience provider computing system **150**) and discover something alarming (e.g., the experience provider website is directed to different subject matter than originally expected by the user **102**). Accordingly, the user **102** may immediately access the client application **114** and disable data sharing with the experience provider. The platform computing system **122** may then automatically expire or delete the generated access token associated with the experience provider (e.g., via an API call, or a native query, to the token repository **144**), thus preventing any further sharing with the experience provider.

[0065] At process **204**, the platform computing system **122** provides (e.g., via the interface circuit **136** over the network **118**) selectable data categories that classify subsets of data of the user (e.g., according to a classification scheme). That is, the platform computing system **122** may first gather (e.g., as described further in FIG. 3) and aggregate all the data of the user **102** that it contains in the user data repository **148**. The platform computing system **122** then classifies the user data into data category subsets according to a classification scheme. The aggregated and classified (e.g., categorized) data of the user **102** is alternatively referred to herein as a corpus (e.g., a user data corpus). The classification scheme provides a set of rules or logical expression that enable various parties (e.g., the platform **120** and the experience providers) to assign data to categories in a consistent manner. Furthermore, the classification scheme may provide rules for classification at various levels of granularity. For example, a high level classification may be political content, which may then be further broken down into further layers of sub-classifications (e.g., based on political issues, political orientation, branch of government, geographic region, and so on). In some embodiments, the classification scheme may be provided by the platform **120**. In other embodiments, the classification scheme may be provided by an experience provider or a third party. Accordingly, the classification scheme utilized may be agreed upon by the platform **120** and an experience provider prior to use (e.g., such as during an initial contract negotiation). In other embodiments, the classification scheme may be subject to change (e.g., dynamically with regulation changes, user preference changes, etc.) and decided on a per-use basis (e.g., via an API call).

[0066] Therefore, as an example, the platform computing system **122** may create data subsets (e.g., according to the classification scheme) representing social activities, political affiliations, financial information, education information, and culinary preferences. It should be appreciated that the data categories are not limited by the examples provided herein, but rather, are subject to dynamic change at the discretion of the platform **120**. In some embodiments, the platform computing system **122** may generate data categories in response to current events. For example, during a weather emergency, the platform computing system **122** may generate and provide a category representing the weather emergency (e.g., a hurricane category). Moreover, in some embodiments, the platform computing system **122** may periodically communicate (e.g., an API call via the access circuit **138**) with an experience provider computing system **150** for current events and updates (in order to generate and provide up-to-date categories at all times). Furthermore, in yet another embodiment, the user **102** may create categories of their own and subsequently assign data to them (e.g., via the client application **114**). As an example, the platform computing system **122** may categorize a subset of data as pertaining to sports or hobbies; however, the user **102** may wish to further narrow such a subset and re-classify the data into a golf and a football category. In such a scenario, the user **102** may either manually assign data (e.g., via the client application **114**) into the new categories or rely

on the predictive logic of the interface circuit **136** to assign data into the respective categories (e.g., all data pertaining to golf or originating from a golf-oriented experience provider may be predictively assigned). Accordingly, the classification scheme employed by the various parties to assign data to such categories may be updated in response to any data category changes (e.g., where applicable). Additionally, in some embodiments, the platform computing system **122** may create data categories that represent data subsets that have been grouped based on the origin of the data contained therein (e.g., a data category representing all data of the user **102** contained by experience provider X). Accordingly, in such embodiments, the user **102** may select such a data category to create a data sharing relationship between the experience provider identified in process **202** and the experience provider represented by the selected data category (e.g., experience provider X). That is, in such an embodiment, the user **102** may grant an experience provider access to all applicable data of the user **102** contained by one or more other experience providers (e.g., instead of, or in addition to, designating topical categories to share).

[0067] At process **206**, the user **102** selects (e.g., via a selectable icon such as a checkbox, presented via the client application **114**) at least one data category from the provided data categories for sharing with the identified experience provider. That is, the user **102** makes a decision to share all the data contained in the selected categories with the identified experience provider. For example, the user **102** may decide to share all data categorized as football, hobbies, etc. with an experience provider (e.g., the sporting goods website). Additionally, in an exemplary embodiment, the user **102** may be presented with a checkbox or other selectable icon (e.g., via the client application **114**) that allows the user **102** to select all the potential categories with a single input. The client application **114** then transmits the selections of the user **102** to the platform computing system **122** (e.g., via an API call over the network **118**). Accordingly, at the conclusion of process **206**, the user **102** has identified an experience provider (e.g., a sporting goods website) and at least one data category from which the user **102** desires to share data with the experience provider (e.g., data represented by the data category to share with the website, such as hobbies and favorite sports of the user **102**).

[0068] At process **208**, the platform computing system **122** receives the selection of data categories from the user **102** and subsequently determines a set of advertising categories (e.g., according to the classification scheme) applicable to the identified experience provider. The applicable advertising categories correlate to advertising topics that are displayed by the experience provider (e.g., an experience provider domain, for example, as provided by the experience provider computing system **150**). The platform computing system **122** may determine the set of applicable advertising categories via a variety of modalities. In one embodiment, the platform computing system **122** may receive periodic (e.g., daily, weekly, monthly, etc.) updates from cooperating experience providers that identify the advertising categories currently utilized. In an exemplary embodiment, the platform computing system **122** may communicate in real-time with an experience provider computing system **150** associated with the identified experience provider. In such an embodiment, the platform computing system **122** may formulate a GET request, for example, and transmit it over the network **118**, via the access circuit **138** (e.g., communicating via application programming interfaces (APIs)). The GET request being structured to get a real-time list of the applicable advertising categories of the identified experience provider. In response, the platform computing system **122** receives a real-time list of the applicable experience provider advertising categories (e.g., formatted in JavaScript Object Notation (JSON)). The platform computing system **122** may then parse the JSON response and derive a text-based list of the applicable advertising categories (e.g., based on the rules defined in the classification scheme). Continuing the example of the user **102** accessing a sporting goods website, the platform computing system **122** may determine that the website serves advertisements relating to sports, travel, and finances.

[0069] At process **210**, the platform computing system **122** generates a selectable representation of

the applicable advertising categories received at process **208**. The selectable representation may be in the form of a list with checkboxes, buttons, or via an otherwise selectable graphic. The platform computing system **122** then transmits the generated selectable representation over the network **118** (e.g., via the interface circuit **136**, displayed on the client application **114**).

[0070] The client application **114** receives the generated selectable representation and displays it for the user **102** (e.g., via a display device of the user device **104**). At process **212**, the user **102** selects (e.g., via the client application **114**) zero or more advertising categories that the user **102** is willing to view. For example, continuing the sporting goods website discussion, the client application **114** may display selectable representations of sports, travel, and finances. The user **102** may decide that they are interested in sports, but not travel or finances. As another example, the experience provider may display advertisements that are categorized as political, footwear, and rental properties. The user **102** may then decide that they are interested in new shoes and a new apartment, but that they have no interest in viewing political campaign advertisements.

Accordingly, the user **102** selects footwear and rental properties (or just sports in the sporting goods website example), but leaves the political (or travel and finances in the sporting goods website example) selectable icon un-selected (e.g., an un-checked checkbox). The client application **114** then transmits these selections to the platform computing system **122** (e.g., via an API call over the network **118**).

[0071] The platform computing system **122** then receives the transmitted advertising category selections. At process **214**, the platform computing system **122** determines (e.g., via the data management circuit **140**) a divergence, or difference, between the set of advertising categories displayed by the identified experience provider and the user **102** selection of zero or more advertising categories that they are agreeable to viewing. The platform computing system **122** may determine such a divergence via any variety of algorithms or computational processes. For example, the platform computing system **122** may remove the intersection of the two sets and then parse any remaining advertising categories of the experience provider into a list or a new divergent set (e.g., creates a list or set). That is, in the sporting goods website example, the platform computing system **122** creates a divergent set containing categories of travel and finances (e.g., the un-selected options).

[0072] At process **216**, the platform computing system **122** determines (e.g., via the data management circuit **140**) a monetary value for each of the advertising categories displayed by the experience provider contained in the divergent set or list. For example, continuing the previous example, the divergent set contains only one entry correlating to political advertisements. The platform computing system **122** may then determine the monetary value for each political advertisement served on the experience provider computing systems **150** of the identified experience provider. In some embodiments, the platform computing system **122** may receive periodic updates from cooperating experience providers (e.g., similar to, or apart of, the periodic updates of process **208**), which associate a monetary value to the advertising categories. In an exemplary embodiment, the platform computing system **122** may formulate a GET request, for example, and transmit it over the network **118**, via the access circuit **138**. The GET request being structured to get a real-time list of the monetary values associated with each applicable advertising category of the identified experience provider. In response, the platform computing system **122** receives a real-time list, or dictionary, of the monetary values associated with the applicable experience provider advertising categories (e.g., formatted in JavaScript Object Notation (JSON)) contained in the divergent set. The platform computing system **122** may then parse the JSON response and derive, for example, an associative dictionary containing advertising categories and their associated monetary values. As an example result, the platform computing system **122** may then determine that political advertisements have a monetary value of 5 cents per view (to the experience provider). In some embodiments, the JSON response may also contain a minimum monetary value that the experience provider is willing to accept for displaying advertisements from

each advertising category. That is, the identified experience provider may dictate that it needs at least 3 cents per view from advertisements in the political category. Therefore, the identified experience provider enables the platform computing system **122** to negotiate with the user **102** on their behalf (e.g., by leaving 2 cents of disposable revenue from such advertisements).

[0073] Accordingly, at process **218**, the platform computing system **122** generates (e.g., via the interface circuit **136**) and provides (e.g., via the client application **114** and over the network **118**) a prompt that offers the user **102** a portion of the determined monetary value for each advertising category displayed by the experience provider and contained in the divergent set. For example, continuing the previous example, the platform computing system **122** may offer the user **102** 1.5 cents per political advertisement viewed (e.g., maintaining 0.5 cents as compensation for facilitating the process). In other embodiments, the platform computing system **122** may offer the entire example budget of 2 cents directly to the user **102** and derive compensation in another fashion, or not at all. In yet another embodiment, the platform computing system **122** may facilitate a real-time negotiation between the identified experience provider and the user **102** (e.g., via a collaborative effort between the data management circuit **140**, the access circuit **138**, the client application **114**, and the experience provider computing system **150**). In such an embodiment, the platform computing system **122** may query the experience provider computing system **150** with an API call identifying the un-selected advertising categories to the experience provider computing system **150**. In response, the experience provider computing system **150** may provide an initial monetary offer in order to view advertisements from each un-selected advertisement category. Continuing the example, the experience provider computing system **150** may respond with an offer of 0.5 cents per view of political advertisements. Subsequently, the platform computing system **122** may then present that offer to the user **102** (e.g., via the client application **114**). The user **102** may then decide to accept the offer, decline the offer, or make a counter offer (e.g., make a counter offer of 1.5 cents). Accordingly, the platform computing system **122** may communicate these offers back and forth between the parties (e.g., via API calls) until an agreement is reached or until either party declines.

[0074] Therefore, at process **220**, in all embodiments, the selections of the user **102** indicating an amenability (e.g., an agreement) to view advertisements from previously un-selected categories are captured by the client application **114** and transmitted back to the platform computing system **122** (e.g., via an API call over the network **118**). In some embodiments, the user **102** may decide not to change their advertisement viewing preference and select zero of the advertising categories from the offer prompt.

[0075] At process **222**, the platform computing system **122** receives the selections of the user **102** and creates a finalized set of allowable advertising categories for the identified experience provider. Furthermore, the finalized set of allowable advertising categories is then processed by the platform computing system **122** in order to generate a linked data structure (e.g., a tuple list, a dictionary, a hash-based map, etc.). The linked data structure is structured to associatively map the allowable advertising categories to the agreed upon monetary compensation for the user **102**, when applicable.

[0076] At process **224**, the identified experience provider, the user **102** selection of at least one data category, and the linked data structure of the finalized set of allowable advertising categories are retrievably stored in the permissions repository **146** of the platform **120**. In some embodiments, the platform computing system **122** may first convert the linked data structure of the finalized set of allowable advertising categories into a table (e.g., rows and columns) prior to retrievably storing it in the permissions repository **146**. The aforementioned items may be stored, for example, via an API call or a native query (e.g., MySQL query, PostgreSQL query, etc.). In some embodiments, the linked data structure may be simultaneously maintained in a memory **128** of the platform computing system **122** and also converted into a table (e.g., rows and columns) for storing in a repository (e.g., the permissions repository **146**).

[0077] Furthermore, in some embodiments, the processes **202-224** may also be completed for a dependent(s) of the user **102**. That is, the user **102** may indicate (e.g., via the client application **114**) a desire to establish data sharing and permissioning preferences for a dependent(s) (e.g., a child). In such embodiments, the user **102** may complete the processes **202-224** as described for an alternative account (e.g., “userChild.i”) and link it (e.g., via the client application **114**) to their own account (e.g., linked as a dependent account, maintaining administrative privileges). Therefore, it should be appreciated that any of the methods described herein as pertaining to a user (e.g., the user **102**) may be completed on behalf of a dependent and associatively stored with the account of the user **102** (e.g., as a dependent account, thus maintained administrative privileges for the user **102**).

[0078] At process **226**, the platform computing system **122** receives a request for data sharing (e.g., alternatively referred to as a request for access to data of the user **102**) from an experience provider (e.g., over the network **118**). The request may be communicated as an API call received and processed by the access circuit **138** of the platform computing system **122**. Furthermore, in an exemplary embodiment, the request is received in response to the user **102** interacting with a secure pop-up on an interactive asset of the experience provider (e.g., an encrypted pop-up that serves as a connection to the platform computing system **122** while on the interactive asset of the experience provider). In other embodiments, the request is received in response to the user **102** logging into an interactive asset of the experience provider with a digital identity proxy (e.g., “user.i”). In the exemplary embodiment, the request may be structured to contain an identifier of the experience provider and an API route (e.g., for passing an access token in the response, as further discussed below). In other embodiments, the request may be structured to contain an identifier of the experience provider and the gathered credentials of the user (e.g., as input into the experience provider computing system **150** during the login with the digital identity proxy). Both embodiments are discussed in further detail below and in the description of FIG. 3. That is, continuing the sporting goods website example, process **226** may occur as a result of the user **102** logging into the website (e.g., as described above, and further in FIG. 3). Accordingly, in response to the login of the user **102**, the sporting goods website initiates a data sharing request in order to customize the experience of the user **102** (e.g., via analysis of the data of the user **102** and a subsequent modification of the content served).

[0079] At process **228**, the platform computing system **122** authenticates the request for data sharing from the experience provider (e.g., the request for access to data of the user **102**), via the security circuit **134**. In the exemplary embodiment, the platform computing system **122** receives the credentials of the user **102** directly, via an encrypted connection (e.g., a Secure Sockets Layer (SSL) pop-up) that is initiated by a user interaction on an experience provider asset (e.g., a button, a hyper-link, etc.). In other embodiments, the platform computing system **122** may receive the credentials of the user **102** indirectly, such as via an API call from the experience provider computing system **150**. In such embodiments, the user **102** may have logged in directly to an experience provider computing system **150** with the digital identity proxy (e.g., “user.i”). In response, the experience provider computing system **150** recognizes the digital identity proxy (e.g., according to the format of the credential, such as “user.i”) as indicating that the user **102** wishes to utilize the data sharing and permissioning protocols described herein, and accordingly, passes the credentials of the user **102** to the platform computing system **122** in order to authenticate (e.g., over an SSL connection). In yet other embodiments, the platform computing system **122** may require a second, additional authentication (e.g., in addition to the credentials of the user **102**). In such embodiments, the platform computing system **122** may transmit (e.g., via the security circuit **134**, over the network **118**) a 2FA prompt. The 2FA prompt may be structured as a push notification (e.g., via the client application **114**), an SMS, an email, etc. Additionally, the 2FA prompt may also require a fingerprint scan, a retinal scan, or some other biometric to ensure that the user credentials were indeed entered by the user **102**. The security circuit **134** verifies that the received credentials of the user **102** are correct (e.g., by comparing the received credentials with those stored in the

permissions repository **146**).

[0080] At process **230**, the platform computing system **122** verifies, via the data management circuit **140**, that the experience provider associated with the experience provider computing system **150** is designated for data sharing by the user **102** in the permissions repository **146** (or that the experience provider computing system **150** is designated directly in the permissions repository **146**, via IP address, or a hardware identifier). For example, the platform computing system **122** may receive a data sharing request from a specific experience provider (e.g., the sporting goods website), and subsequently query the permissions repository **146** (e.g., via an API call, or directly, via a native query in MySQL, PostgreSQL, etc.) In such an example, the query is made in order to verify that the user **102**, identified by the received credentials of process **228**, has designated the specific experience provider (e.g., the sporting goods website) as an intended data sharing recipient.

[0081] At process **232**, the platform computing system **122** generates an access token for the experience provider to utilize in subsequent data sharing requests, and stores the generated access token in the token repository **144** (e.g., via an API call, or directly, via a native query in MySQL, PostgreSQL, etc.). That is, continuing the example, the platform computing system **122** generates an access token that the experience provider (e.g., the sporting goods website) may use to access data of the user **102**. In an exemplary embodiment, the access token is generated as an opaque access token (as described above, with reference to FIG. 1). That is, in such an embodiment, the access token is formatted by the platform computing system **122** such that it contains no inherent identifying data of a user (e.g., the user **102**). Rather, such opaque tokens contain some identifier of the user **102** data in the token repository **144** (as configured in processes **204-224**), such as a pointer or value that only has meaning in the context of the token repository **144**. In this way, security for the process is enhanced. Additionally, if the user **102** has not entered an expiration or a predetermined number of uses during process **202**, the platform computing system **122** may assign a predetermined expiration date (e.g., an amount of time applied as the default to all such access tokens at the time of generation). In other embodiments, the access token may be an encrypted token (e.g., a JWT token, or other encrypted format) that contains the data (as configured in processes **204-224**) directly. In embodiments that utilize such encrypted tokens, processes **234-242** may be ignored, as they pertain to accessing the data with the opaque token of the exemplary embodiment. For example, the encrypted token embodiments may utilize an asymmetric public-private key cryptosystem, such as RSA. Therefore, the experience provider computing system **150** may decrypt the access token at its discretion, according to the cryptosystem in place, in order to access the data of the user **102**.

[0082] At process **234**, the platform computing system **122** provides (e.g., via an API response, over the network **118**) the access token to the experience provider computing system **150**. At process **236** and **238**, the experience provider computing system **150** receives the access token and generates a subsequent data sharing request (e.g., now containing the access token received at process **236**).

[0083] At process **240**, the subsequent data sharing request (e.g., alternatively referred to as a request for data of the user **102**) containing the access token is received by the access circuit **138** (e.g., via an API call). That is, in the sporting goods website example, process **240** represents the website making an authorized (e.g., containing the access token) request to access data of the user **102**. Accordingly, at process **242**, the platform computing system **122** (e.g., the rules engine of the data management circuit **140**) provides the data of the user **102** as identified by the access token (e.g., as associatively mapped to in the permissions repository **146**). It will be appreciated that in some embodiments, the platform computing system **122** may not store the aggregated data of the user **102** (e.g., in order to provide to an experience provider in response to a data access request). Rather, in some embodiments, the platform computing system **122** may instead make an API call(s) to all eligible experience providers participating in the service of the platform **120**, which requests

the applicable data contained locally by each experience provider. Accordingly, in such embodiments, the platform computing system **122** may then aggregate the data of the user **102** on the fly (e.g., as the API call(s) return with responses), process it via the rules engine (e.g., of the data management circuit **140**, as discussed further herein), and ultimately provide the applicable data (e.g., the data after rules have been applied) of the user **102** without storing it or only temporarily storing it. In addition to providing any data selected by the user **102** (e.g., as identified in process **206**), the platform computing system **122** also includes the information identifying the advertising categories of the user that can only be displayed in exchange for currency (e.g., as discussed in processes **208-224**), and their associated currency value (e.g., 2 cents per view, as per the continued example). In some embodiments, the platform computing system **122** may generate and transmit an internal confirmation message (e.g., from one API to another) that confirms the data of the user **102** was provided to the experience provider.

[0084] At process **244**, the platform computing system **122** receives (e.g., via an API call) an update to the data of the user **102** based on the activity of the user **102** during their interactions with the experience provider computing system **150** (e.g., henceforth discussed as activity data). For example, continuing the sporting goods website discussion, the platform computing system **122** may receive updates (e.g., from the website) that identify activities of the user **102** on the website, which occurred after the data sharing (e.g., transactions, navigations, selections, etc.). In addition to the activity data, the platform computing system **122** may also receive a tabulation (e.g., a systematic count, record, or list) of any funds due according to the advertising categories that were monetized for the user **102** during processes **208-224**. Accordingly, the platform computing system **122** may then verify any received tabulation of funds due and initiate a payment for the user **102** in the amount due (e.g., via the payments engine of the data management circuit **140**). In some embodiments, the activity data is received directly from the experience provider computing system **150** as part of a financial arrangement, a contract (e.g., between the platform **120** and the experience provider), or as part of a cooperative regulatory arrangement. In other embodiments, the client application **114** may monitor (e.g., with consent from the user **102**) activities of the user directly (e.g., when the experience provider computing systems **150** are accessed by the user **102** via the user device **104**). In yet other embodiments, the platform computing system **122** may provide the user **102** with a browser extension or plugin that monitors (e.g., with consent from the user **102**) the activity of the user. In all embodiments, subsequent to receiving the activity data, the platform computing system **122** updates (e.g., via an API call, or directly, via a native query in MySQL, PostgreSQL, etc.) the user data held in the user data repository **148**.

[0085] Furthermore, while the method **200** describes revenue sharing between the experience provider and the user **102** as it pertains to advertising, it will be appreciated that in some embodiments the user **102** may receive a shared-revenue offer simply for authorizing access to data. That is, the user **102** may receive an offer (e.g., \$1, \$3, etc.) from the experience provider to access data of the user **102**. Such an offer may be in addition to, or separate from, any advertising agreements made. Accordingly, funds due for revenue sharing regarding access to data (e.g., of the user **102**) are included in the received tabulation.

[0086] In some embodiments, a plurality of APIs can be used to carry out the processes of method **200**. For example, a first API can be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **202-206**, **210-212**, **218-220**, **226-228**, and **244**), and a second API can be configured to facilitate communication of data between the platform computing system **122** and the experience provider computing system(s) **150** (e.g., processes **204**, **208**, **216-218**, **226-228**, **234**, and **240-244**). However, it will be appreciated that any number of APIs could be used to carry out the processes of method **200**. For example, more than one API could be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **202-206**, **210-212**, **218-220**, **226-228**, and **244**), and likewise more than one API could be substituted for the second API discussed above.

Furthermore, it will be appreciated that, for the experience providers, the APIs may be provided based on template APIs developed by the platform **120** and reused by the experience provider, or may be custom-written according to an API documentation (e.g., provided by the platform **120**, such that the experience provider may conveniently access the endpoint functions of the data sharing and permissioning service).

[0087] Referring now to FIG. **3**, a flow diagram of a method **300** for processing a data sharing and permissioning request from an experience provider is shown, according to an example embodiment. As a broad overview, method **300** includes a description of a registration process for the data sharing and permissioning protocol of the platform **120**, and the subsequent processing of a data sharing request. That is, method **300** discusses a user **102** signing up for the data sharing service of the platform **120**, including the establishment of a digital identity proxy. Thus, when the user **102** visits an experience provider website, the user **102** uses their “.i” digital identity proxy and, on this basis, the experience provider recognizes the user as being someone that utilizes the services of the platform **120**. With this in mind, the experience provider recognizes that it may send API calls to the platform computing system **122** in order to gain additional information about the user **102** in real time (i.e., while the user is enjoying the features/functionality of the experience provider website, as opposed to in an offline manner). Method **300** further describes user profiles that implement templates of the platform **120** in order to establish initial settings for a new user. As an example, method **300** may occur as part of a user (e.g., the user **102**) registering for the data sharing service of the platform **120**, configuring settings for a website that they intend to visit, and then subsequently accessing the website (e.g., provided by the experience provider computing system **150**). Accordingly, a practical example of the user **102** registering for the data sharing service, configuring settings, and subsequently accessing a social media website is discussed throughout method **300**. Method **300** may be performed using the system of FIG. **1**, and with similar implementation as the processes of method **200**, such that reference is made to the components of FIG. **1** and FIG. **2** in order to aid the description of method **300**.

[0088] The method **300** begins at process **302** with the platform computing system **122** receiving an indication (e.g., via the interface circuit **136**, and provided as an API call of the client application **114**) from a user **102** to register for a data sharing and permissioning account. It should be appreciated that process **302** presupposes (e.g., similar to process **202**) an authenticated user-session in order to access the client application **114**. Any such required authentication may be completed via the security circuit **134** prior to accessing the client application **114** (e.g., via password, biometric scan, etc., as described above with reference to FIG. **1**). The indication may be any variety of selections made by the user **102** via the user interface of the client application **114** (e.g., a drop-down box, a button, a voice command, etc.), and subsequently transmitted over the network **118**.

[0089] At process **304**, the platform computing system **122** provides the user **102** with a registration interface (e.g., generated by the interface circuit **136** and provided as an API call over the network **118**). The registration interface is structured to prompt the user **102** for registration information and account preferences. Accordingly, the registration interface provides the user **102** with a variety of selectable interaction points (e.g., drop-down box, text-entry area, buttons, checkboxes, etc.) to easily facilitate the gathering of the required user information and account preferences (e.g., as further discussed below, and illustrated in FIG. **10**).

[0090] At process **306**, the user device **104** receives the registration interface and displays it to the user **102** (e.g., via the client application **114**, and over the network **118**). At process **308**, the registration interface first prompts the user **102** to establish a user identifier (e.g., formatted as a digital identity proxy, such as “user.i”) and a user password. The digital identity proxy is an identifiable (e.g., identifiable to the experience provider computing system(s) **150**) sequence of characters (e.g., a string token) that identifies a username as participating in the data sharing and permissioning protocol of the platform **120**. In an exemplary embodiment, the digital identity proxy

is a string of characters that ends in “i”. For example, a user (e.g., the user **102**) named Tom may establish a user identifier that incorporates the name Tom, such as “tom.i” or “tomr.i”. In other examples, the user **102** may establish a user identifier that correlates to a passion, such as “baseballfanatic.i”. It should be appreciated that any variety of characters may be combined to create a string formatted as a digital identity proxy, as long as the user identifier complies with any predetermined rules (e.g., as implemented by the platform **120**) and is unique in the system (e.g., only one user may have the user identifier “tom.i”). That is, in alternative embodiments, the digital identity proxy may utilize a different sequence of characters (or string token). For example, in alternative embodiments, the user identifier may be “tom: i”, “i.tom”, or “tom*”. It should be appreciated that any sequence of characters may act as the string token, as long as it is consistent across the platform (e.g., the platform computing system **122**) and all the users (e.g., the user **102**). [0091] Continuing the example of the exemplary embodiment, the platform computing system **122** may first query the permissions repository **146**, via an API call or a native query (e.g., MySQL query, PostgreSQL query, etc.), and verify that no other accounts are already registered with the user identifier “tom.i”. In response to successfully verifying that the user identifier is available (e.g., unclaimed), the user **102** may continue by entering a password (e.g., for the “tom.i” account) and the remainder of the required user information. The remainder of the required user information may include a variety of record-keeping items, such as: a full legal name, a current address, a telephone number, an email address, a financial account information, etc.

[0092] At process **310**, the registration interface prompts (e.g., via the client application **114**) the user **102** to select and configure a variety of account profile options (also referred to as the profile configuration settings). The profile configuration settings include options that pertain to security and profile population (e.g., for the user **102**). The security-based settings may include confirming the items entered during process **308**, such as the telephone number (e.g., via a 2FA prompt), the email address (e.g., via an email containing a hyperlink or a code that must be entered into the client application **114**), and the financial account. The financial account may be confirmed via, for example, an undisclosed value, marginal deposit or withdrawal (e.g., 1 cent, 3 cents, etc.), made by the platform **120** to the user-entered financial account. The user **102** may then verify the financial account by entering the value of the marginal deposit or withdrawal into the client application **114**.

[0093] In some embodiments, the platform **120** may be, or may be associated with, a financial institution. Accordingly, in such embodiments, the registration interface prompts may include a selectable list (e.g., a drop-down menu) of any financial accounts held by the user **102** with the platform **120**. In other words, the platform computing system **122** may first determine if the user **102** holds any financial accounts with the platform **120** (e.g., by querying the user data repository **148** or an accounts database (not depicted)), and subsequently, provide (e.g., via the interface circuit **136**) the user **102** with a selectable list containing any determined accounts of the user **102**. Therefore, the user **102** may select a financial account from the prepopulated list rather than entering the financial account manually (e.g., typing in the account numbers). Furthermore, the verification of the financial account (e.g., as discussed above) may still be required by the financial institution (e.g., platform **120**) in order to increase security (e.g., prove ownership, or authorized access, to the prepopulated account).

[0094] The profile configuration settings pertain to populating the user profile (e.g., for data sharing) of the user **102** and to configure alerts (e.g., discussed further below). In some embodiments, the user **102** may select (e.g., via the user interface displayed on the client application **114**) to gather initial data from experience providers (e.g., social media accounts, financial accounts, shopping accounts, etc.). In such an embodiment, the user **102** may enter the credentials for each experience provider that they would like to centralize the data from (e.g., in the user data repository **148**). For example, the user **102** may make a selection identifying a particular social media website, enter credentials (e.g., existing credentials of the user **102** at the particular social media website), and subsequently, the platform computing system **122** may scrape the

particular social media website (e.g., via a web-scraping technique implemented by the data management circuit **140**). In other embodiments, the platform computing system **122** may transmit an API request for the corpus (e.g., a data set(s)) data of the user **102** (e.g., a current corpus of data relating to the user **102** held by the experience provider) to the identified experience provider (e.g., via the access circuit **138**). In some embodiments, the request for the corpus of the user **102** may contain authorization information, such as the credentials of the user **102** or a token identifying the platform computing system **122** to the experience provider (e.g., in order to verify the API call). Furthermore, in some embodiments, the platform computing system **122** may poll the experience provider members of the data sharing and permissioning service (e.g., via API calls) to retrieve all the initial corpus data relating to the user **102** at once (e.g., in addition to any specific designations, data submissions, questionnaires, etc., as described herein for data aggregation purposes). Accordingly, the platform computing system **122** may then receive an API response(s) from the experience provider(s) containing the corpus data of the user **102** (e.g., the aggregated and categorized data of the user **102**, as contained by the experience provider(s) computing system(s) **150**). The data garnered (e.g., via scraping, API call, etc.) may then be categorized according to the classification scheme (e.g., via the data management circuit **140**) and retrievably stored in the user data repository **148** (e.g., via an API call or a native query). In other examples, the user **102** may not identify an experience provider for data scraping. In such examples, the user profile may be built based on any accounts of the user **102** held by the platform **120** (e.g., bank accounts, lending data, etc.), when applicable. Furthermore, in such examples, the user **102** may respond to a questionnaire (e.g., generated by the data management circuit **140**, and provided by the interface circuit **136**), which enables the platform computing system **122** to create a user profile for the user **102** according to common data points of interest. For example, the questionnaire may ask the user **102** questions regarding: political affiliation, religious affiliation, employment status, education level, hobbies, opinions around current events, etc. It should be noted that the preceding is not an exhaustive list. The questions provided via the questionnaire may be based on any data category and furthermore determined to be a common point of interest at the discretion of the platform **120** (e.g., based on feedback from experience providers, advertising desires, etc.).

[0095] Still referring to the profile configuration settings, the platform computing system **122** may analyze (e.g., via the data management circuit **140**) the user **102** responses to the questionnaire, any data scraped from experience providers, and any data from accounts held by the user **102** and associated with the platform **120**. Subsequently, the platform computing system **122** may predict (e.g., via the data management circuit **140**) a data sharing and permissioning template to apply to the user profile of the user **102**. For example, the platform computing system **122** may predict (e.g., based on the gathered information) that the user **102** is an avid user of social media and a frequent attendee of concerts. Accordingly, in such an example, the platform computing system **122** may prompt the user (e.g., via the client application **114**) to confirm template settings that automatically share data with a variety of social media websites and any website pertaining to music or concert functions (e.g., scheduling, news, ticket vendors, etc.). In some examples, the user **102** may decide that the predicted template is too broad, or otherwise not the preferred default settings for the user **102**. In such an example, the user **102** may decide to select aspects of the template to adjust (e.g., perhaps the user **102** is happy to share data with the variety of social media sites, but not ticketing venues). Accordingly, the user **102** may alter (e.g., via the client application **114**) the aspects of the template that are undesired. Alternatively, the user **102** may decide to apply data sharing and permissioning settings manually for each experience provider. In such an example, the platform computing system **122** may disable all data sharing by default.

[0096] Furthermore, the profile configuration settings include options for the user **102** to configure alerts and notifications. The alerts and notifications may occur as part of security and login procedures (e.g., a 2FA prompt confirming a data sharing request) and as part of advertising offers (e.g., as explained in FIG. 2, and further discussed in FIG. 6). That is, the user **102** may configure

modalities of delivery (e.g., email, SMS, 2FA prompt, etc.) and triggers (e.g., security, advertising, etc., as discussed in FIG. 6) for alerts and notifications via the client application **114**.

[0097] At process **312**, the user **102** selects an experience provider for data sharing and permissioning. It should be noted that process **312** may not always occur during the initial registration process as described in processes **302-310** (e.g., it could happen at a later time, or not at all). The process of **312** may occur at the discretion of the user **102** (e.g., in addition to any template selections made in process **310**). Accordingly, should the user **102** decide to manually adjust the experience provider data sharing and permissioning settings during the initial registration, the process **312** may occur substantially similar to the processes **202-224** of the method **200**, as described in FIG. 2. At process **314**, the selections of the user **102** made via the registration interface (e.g., displayed via the client application **114**) are transmitted to the platform computing system **122**, over the network **118**. That is, at the conclusion of process **314**, the user **102** has successfully completed registration inputs for the data sharing service of the platform **120**. Although other processes remain, such as generating a user profile (e.g., as discussed below), the necessary information of the user **102** has been gathered and relayed (e.g., back to the platform computing system **122**) at the conclusion of process **314**.

[0098] At process **316**, the platform computing system **122** receives the selections of the user **102** made via the registration interface. At process **318**, the platform computing system **122** (e.g., via the data management circuit **140**) generates a user profile for the user **102** based on the received selections. The user profile contains the account preferences of the user **102**, the data sharing and permissioning settings of the user **102**, and the data of the user **102**. The aforementioned aspects of the user profile may be associatively linked and retrievably stored in both the permissions repository **146** (e.g., the account preferences and the data sharing and permissioning settings) and the user data repository **148** (e.g., the data of the user **102**). Therefore, by associatively linking the various components of the user profile, the user **102** may dynamically configure (e.g., via the client application **114**) any of the settings at any time, according to the relevant processes for the component (e.g., as described herein, with reference to FIGS. 2, 3, and 4). That is, for example, the user **102** may open the client application **114** at any point and adjust data sharing and permissioning settings to match a template (e.g., rather than having manually adjusted settings), as described in process **310**.

[0099] At process **320**, an experience provider computing system **150** receives a digital identity proxy login, thus identifying a current session as a data sharing and permissioning user (e.g., of the user **102**). For example, the experience provider computing system **150** may receive a digital identity proxy login through a text-entry login component (e.g., the user **102** enters “tom.i” into a username field of a login screen of the experience provider). In exemplary embodiments, the user **102** simply needs to enter the username (e.g., “tom.i”) in order to be identified by the experience provider computing system **150** (e.g., identified as utilizing the data sharing and permissioning protocol associated with the platform **120**). That is, the user **102** need not enter a password directly into any component associated with the experience provider computing system **150**. Additionally, the experience provider may display a selectable interaction point (e.g., a button or a link labelled “Login with your *.i identifier here”, etc.) that launches a login window of the platform computing system **122**. For example, in some embodiments, the selectable interaction point may be structured to execute a block of code that is structured (e.g., JavaScript) to create a secure pop-up (e.g., an SSL encrypted connection to the platform computing system **122**) that appears on the experience provider component (e.g., the website being served via the experience provider computing system **150**). Further, it will be appreciated that these interactions occur (e.g., as described above) as a substitution to a typical experience provider login processes. That is, the interactions described above occur rather than the experience provider receiving a username and a password (e.g., via a login component of the experience provider), and subsequently verifying the credentials against an internal experience provider database (e.g., an accounts database of the experience provider).

Accordingly, continuing the example of the user **102** accessing a social media website, process **320** may occur responsive to the user **102** logging into the social media website with a digital identity proxy login, or alternatively, to the user **102** interacting with the selectable interaction point. [0100] Therefore, and now referring to process **322**, the block of code may be structured to generate an API call (e.g., a data sharing request) to the platform computing system **122**. In some embodiments, the API call may contain a uniform resource locator (URL), thus creating the SSL encrypted window directly to an address to the platform computing system **122**, as well as an identifier of the experience provider (e.g., in a JSON body of the call). For example, the platform computing system **122** may provision API tokens (e.g., an access token that the access circuit **138** requires to validate a call) to the experience provider. Therefore, the experience provider computing system **150** may validate API calls by including the provisioned API token. In other embodiments, the experience provider computing system **150** may validate its calls by including an identifier string and a password. Furthermore, it should be noted that subsequent to receiving a digital identity proxy login through a text-entry component, the experience provider computing system **150** may initiate the rest of the process as though the selectable interaction point was selected instead (e.g., in order to protect the user **102** from entering the data sharing and permissioning password into an experience provider computing system **150**). Accordingly, security for the process is improved by isolating the exposure of password entry to only the platform computing system **122**.

[0101] At process **324** and **326**, the platform computing system **122** receives (e.g., via the access circuit **138**) the data sharing request (e.g., the API call containing the identifier of the experience provider) and authenticates it (e.g., via the security circuit **134**). Similar to method **200**, the data sharing request may be alternatively referred to as a request for access to data of the user **102**. That is, continuing the social media website example, process **324-326** may occur as a result of the user **102** logging into the website (e.g., as described above). Accordingly, in response to the login of the user **102**, the social media website initiates a data sharing request in order to customize the experience of the user **102** (e.g., via analysis of the data of the user **102** and a subsequent modification of the content served). The authentication process may be two-fold, such that it requires authenticating the call itself and the user credentials (e.g., entered into the SSL pop-up and received only by the platform computing system **122**). That is, the platform computing system **122** may first validate the API call by verifying the API token included in the call (e.g., by querying the token repository **144**). Next, the platform computing system **122** authenticates the login credentials of the user **102** (e.g., via the security circuit **134**, as described in the method **200**).

[0102] Processes **328-340** may be completed substantially similar to the processes **230-242** of method **200**. Accordingly, at process **328** the platform computing system **122** verifies, via the data management circuit, that the experience provider associated with the experience provider computing system **150** is designated for data sharing by the user **102** in the permissions repository **146** (or that the experience provider computing system **150** is designated directly in the permissions repository **146**, via IP address, or a hardware identifier).

[0103] At process **330**, the platform computing system **122** generates an access token for the experience provider to utilize in subsequent data sharing requests, and stores the generated access token in the token repository **144** (e.g., via an API call, or directly, via a native query in MySQL, PostgreSQL, etc.). In the exemplary embodiment, the access token is generated as an opaque access token.

[0104] At process **332**, the platform computing system **122** provides (e.g., via an API response, over the network **118**) the access token to the experience provider computing system **150**. Therefore, the access token may be provided as a string of characters (e.g., in a JSON body of the response to the API call), which uniquely identify the successful data sharing request of the experience provider (e.g., associatively mapped to in the permissions repository **146**).

[0105] At process **334** and **336**, the experience provider computing system **150** receives the access

token and generates a subsequent data sharing request (e.g., now containing the received access token of the user **102**).

[0106] At process **338**, the subsequent data sharing request (e.g., alternatively referred to as a request for data of the user **102**) containing the access token is received by the access circuit **138** (e.g., via an API call, such as described above during process **322**). Continuing the social media website example, process **338** represents the social media website making an authorized (e.g., containing the access token) request to access data of the user **102**. Accordingly, at process **340**, the platform computing system **122** provides (e.g., via the rules engine of the data management circuit **140**) the data of the user **102** as identified by the access token (e.g., as associatively mapped to in the permissions repository **146**). The data may be provided as a response to the API call, contained in the JSON body. It will be appreciated that in some embodiments, the platform computing system **122** may not store the aggregated data of the user **102** or only store the aggregated data of the user **102** temporarily (e.g., in order to provide to an experience provider in response to a data access request). Rather, in some embodiments, the platform computing system **122** may instead make an API call(s) to all eligible experience providers participating in the service of the platform **120**, which requests the applicable data contained locally by each experience provider. Accordingly, in such embodiments, the platform computing system **122** may then aggregate the data of the user **102** on the fly (e.g., as the API call(s) return with responses), process it via the rules engine (e.g., of the data management circuit **140**, as discussed further herein), and ultimately provide the applicable data (e.g., the data after rules have been applied) of the user **102** without storing it or after temporarily storing it. In some embodiments, the platform computing system **122** may generate and transmit an internal confirmation message (e.g., from one API to another) that confirms the data of the user **102** was provided to the experience provider. Therefore, at process **340**, the social media website receives the data of the user (e.g., as identified by the access token), and may subsequently utilize the data to customize the experience of the user **102** (e.g., the experience of the user **102** while accessing the social media website).

[0107] It should be appreciated that a variety of API endpoints may exist for data sharing requests (containing the access token), such that the experience provider computing system **150** may make targeted API calls to the platform computing system **122**. For example, the experience provider may have been granted access to a variety of data categories of the user **102**, but may only be interested in a select few. The experience provider may be, for example, a fishing lure manufacturer, and thus, only interested in data categories pertaining thereto. That is, the fishing lure manufacturer may be interested in data relating to hobbies or travel plans, but may not have any interest in data relating to politics or religion. Accordingly, the experience provider computing system **150** may make specific API calls for only the subsets of data that they care about (e.g., hobbies and travel plans). For example, the platform computing system **122** may provide categorical API endpoints (e.g., <https://api.provider.com/userdata/hobbies>) in addition to broad API endpoints (e.g., <https://api.provider.com/userdata/allavailable>). Therefore, the categorical API endpoint (/hobbies) may return user data relating to hobbies only, while the broad API endpoint (/allavailable) may return all the available data of the user **102** (e.g., from the categories selected by the user **102** for sharing). Furthermore, the platform computing system **122** may also provide permission only API endpoints for experience providers that are only interested in what content is allowable (e.g., an experience provider that doesn't customize a service based on the user data). For example, an experience provider that operates as an auction website (e.g., via the experience provider computing system **150**) may not be interested in the data of the user **102**. That is, it may be too presumptuous to predict what item the user **102** is looking for based on the data (e.g., the experience provider would rather rely on the navigable structure of the website); however, the experience provider may still be interested in complying with the advertising preferences of the user **102**. Accordingly, the experience provider may make an API call to, for example, an /allpermissions endpoint (e.g., structured as discussed above) and receive only the permission set of

the user **102** as a response.

[0108] At process **342**, the experience provider computing system **150** receives the data associated with the API call made (e.g., during the subsequent data sharing request of process **336**). The experience provider may then use that data to dynamically tailor their user experience (e.g., for the user **102**). Furthermore, the experience provider may also make additional API calls to access other information of the user **102** (e.g., as dictated by the permission settings), and to further refine the information they are receiving (e.g., as discussed above). Any additional API calls made by the experience provider computing system **150** may follow the same processes, beginning at process **336**.

[0109] In some embodiments, a plurality of APIs can be used to carry out the processes of method **300**. For example, a first API can be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **302-304**, **308-310**, **314-316**, and **320-326**), and a second API can be configured to facilitate communication of data between the platform computing system **122** and the experience provider computing system(s) **150** (e.g., processes **310**, **320-326**, **332**, and **338-340**). However, it will be appreciated that any number of APIs could be used to carry out the processes of method **300**. For example, more than one API could be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **302-304**, **308-310**, **314-316**, and **320-326**), and likewise more than one API could be substituted for the second API discussed above. Furthermore, it will be appreciated that, for the experience providers, the APIs may be provided based on template APIs developed by the platform **120** and reused by the experience provider, or may be custom-written according to an API documentation (e.g., provided by the platform **120**, such that the experience provider may conveniently access the endpoint functions of the data sharing and permissioning service).

[0110] As an illustrative example, consider a scenario where the user **102** rents a smart car for the day. Through the data sharing and permissioning service of the platform **120**, the user **102** may safely enable the smart car to access data regarding the user's interests and habits. The user **102** may safely enable the smart car to access the data simply by associating the data sharing account with the smart car (e.g., logging into an interface of the smart car via the digital identity proxy or the secure pop-up of process **320**). That is, even as part of a transient experience, the user **102** may conveniently, quickly, and securely enable data sharing with the smart car. Furthermore, the smart car, now empowered by the data of the user **102**, may process and interpret the data of the user **102** to provide a dynamically tailored experience. The smart car may analyze the data of the user **102** and determine, for example, that the user **102** enjoys flash mobs, dancing, and adult beverages. Therefore, the smart car may set a nearby tavern, where a flash mob is about to congregate for a conga dance, as a self-driving destination. Accordingly, the smart car may begin to drive the user **102** to the destination (e.g., a hands-free, automated driving experience). Furthermore, the smart car may also communicate with the destination (e.g., via an API call to computing systems associated with the destination, perhaps routed through a third-party that manages online commerce for the destination) in order to make a reservation and to pre-pay any applicable cover charge (e.g., using a financial account of the user **102**). Continuing the foregoing example, the smart car may also pre-order a favorite beverage of the user **102** (e.g., at a time that the smart car estimates the user will arrive). Thus, it should be appreciated that such seamless integration of user data with experience providers in a secure-manner facilitates a wide variety of direct and tangential improvements to user experiences in the digital world.

[0111] As another example, consider a scenario in which the user **102** enters a gym to exercise via an IoT-enabled exercise device (e.g., a bicycle, a rowing machine, a treadmill, etc.). Accordingly, subsequent to logging in to the exercise device with the data sharing and permissioning protocol, the exercise device may adjust a component(s) in order to provide a custom exercise experience. For example, the exercise device may analyze the data of the user **102** (e.g., either directly, or via a

cloud-based data processing associated with the manufacturer of the exercise device) and determine various workout preferences of the user **102**. That is, the exercise device may adjust: the brightness of a display component, the content of the display component (e.g., tune the display component to a favorite show of the user **102**), and adjust the volume on an audio component (e.g., speakers that output the audio of the favorite show, a music player, a radio, etc.).

[0112] As a further example, consider a scenario in which the user **102** accesses an experience provider lodging and accommodations website in order to book a hotel room for an upcoming trip. Accordingly, upon logging into the experience provider website with the data sharing and permissioning protocol (e.g., logging into the experience provider website via the digital identity proxy or the secure pop-up of process **320**), the lodging and accommodations website may receive the data of the user **102** and analyze it. That is, the experience provider website may analyze the data of the user **102** in order to provide a custom experience. For example, the experience provider website may notice (e.g., via analysis of the received data of the user **102**) that the user **102** previously purchased plane tickets to visit Houston, Texas, in a month. Furthermore, the experience provider website may also notice that the user data doesn't indicate that the user **102** has any accommodations booked for that month. Therefore, the experience provider website may initially present the user **102** with a screen that displays Houston, Texas, hotel listings for the following month.

[0113] Now referring to FIG. 4, a flow diagram of a method **400** for a data sharing and permissioning interaction with an experience provider is shown, according to an example embodiment. As a broad overview, method **400** describes a basic advertising shared-revenue process (relative to FIG. 2) between the user **102** and an experience provider. Hence, an experience provider that wishes to access certain data, or display certain advertisements, of/to the user **102** may offer to pay the user **102** a modest sum to gain access to that data (e.g., in order to improve targeted advertising), and/or to display advertisements from a particular category to the user **102**. As an example, method **400** may occur as part of a user (e.g., the user **102**) visiting a website and subsequently receiving a real-time revenue sharing offer from the experience provider (e.g., displayed on the website, such as via a secure pop-up). That is, method **400** further describes displaying a shared-revenue request on a component of the experience provider computing system **150**, in real-time and in response to the user **102** accessing the component, such as a website. Therefore, method **400** provides a practical example of simple advertisement revenue sharing between an experience provider (e.g., the social media website or the sporting goods website) and a user **102**. Method **400** may be performed using the system of FIG. 1, and with similar implementation as the processes of method **200** and method **300**, such that reference is made to the components of FIGS. 1, 2, and 3 in order to aid the description of method **400**.

[0114] The method **400** begins at process **402** with the experience provider computing system **150** receiving data of a user (e.g., the user **102**). Accordingly, in some embodiments, the method **400** may begin after process **242** or after process **342**. Therefore, the method **400** begins after a successful initial exchange between the platform computing system **122** and the experience provider computing system **150** (e.g., a subsequent data sharing request was received with an access token and successfully processed).

[0115] At process **404**, the experience provider computing system **150** analyzes the received user data and identifies an advertising category that the user **102** has opted out of viewing, but that is a category the experience provider would like to display (e.g., even at a reduced monetization rate). For example, referring back to the sporting goods website discussion, process **404** may include the experience provider computing system **150** (e.g., the sporting goods website computing system) analyzing the data of the user **102** and identifying that the user **102** has opted out of viewing advertisements relating to travel and finances.

[0116] Accordingly, at process **406**, the experience provider computing system **150** generates and transmits (e.g., to the platform computing system **122**) a shared-revenue request. The shared-

revenue request may be structured similarly to the other requests (e.g., API calls) described herein. In an exemplary embodiment, the shared-revenue request is structured in the same manner as the request of process **322**. That is, the shared-revenue request is an API call (e.g., received by the access circuit **138**) containing the access token of the user **102** and an identifier of the experience provider (e.g., an API token or credential contained in the JSON body of the request). Additionally, the shared-revenue request also contains an offer from the experience provider (e.g., contained in the JSON body). The offer represents a revenue amount that the experience provider would like to give the user **102** as compensation for viewing advertisements from the advertising category identified in process **404** (e.g., 1 cent per view of travel advertisements). Furthermore, in the exemplary embodiment, as similar to process **322**, the shared-revenue request may be structured to create a secure pop-up (e.g., an SSL encrypted connection to the platform computing system **122**) that appears on the experience provider component (e.g., the website being served via the experience provider computing system **150**).

[0117] At process **408**, the platform computing system **122** receives the shared-revenue request of the experience provider (e.g., via the access circuit **138**). Accordingly, at process **410**, the shared-revenue request is authenticated. The authentication process may be two-fold, such that it requires authenticating the call itself (e.g., via an API token or other identifier of the experience provider, as discussed in process **322**) and the user credentials (e.g., via the access token contained in the shared-revenue request). That is, the platform computing system **122** may first validate the API call by verifying the API token included in the call (e.g., by querying the token repository **144**). Next, the platform computing system **122** authenticates the credentials of the user **102** (e.g., via an API call to the token repository **144**, or directly, via a native query in MySQL, PostgreSQL, etc.). Reiteratively, the platform computing system **122** verifies that the access token is both contained, and not expired, in the token repository **144**.

[0118] In some embodiments, the platform computing system **122** may require a new login of the user **102** (e.g., such as described during processes **322-326**) in order to affect changes to the data sharing permissions. In other embodiments, the platform computing system **122** may track an active user-session of the user **102** (e.g., from an initial authentication process, as required for the access token generation). In such embodiments, the platform computing system **122** may track the active user-session based on the expiration of the access token (e.g., presuming the user **102** is active as long as the access token is active). In yet other embodiments, the platform computing system **122** may track the active user-session of the user **102** according to any variety of session tracking (e.g., cookies, a JWT token, etc.), occurring during the initial authentication via the secure pop-up, as exemplified in processes **322-326**. Furthermore, in some embodiments, the platform computing system **122** may require a secondary authentication, such as a 2FA prompt (e.g., via the client application **114**) or an email containing a selectable hyperlink.

[0119] At process **412**, subsequent to the authentication of the platform computing system **122**, the experience provider computing system **150** displays the secure pop-up (e.g., via a code block that initiates the secure connection to the platform computing system **122**, displayed on a component, such as a website being used by the user **102**). The secure pop-up may be structured by the platform computing system **122** to display a simple yes/no question to the user **102**. For example, the secure-pop up may inform the user that “Would you like to allow experience provider X to display travel advertisements to you in exchange for 1 cent per view of travel advertisements?” Furthermore, the user **102** may be provided with selectable interaction points (e.g., a yes button and a no button) to facilitate a quick and convenient response. In embodiments where the user **102** selects no, the platform computing system **122** responds with a decline response to the experience provider computing system **150** (e.g., an API response, via the access circuit **138**, that informs the experience provider computing system **150** that the user **102** is not interested in the offer). In such embodiments, no further action is taken beyond the API response. However, at process **414**, in embodiments where the user **102** accepts the offer (e.g., by selecting the “yes” button on the secure

pop-up) from the experience provider, the process may continue to **418**.

[0120] Accordingly, at process **416**, the platform computing system **122** receives the “yes” selection of the user (e.g., via the secure pop-up) and at process **418** automatically updates the data sharing and permissioning settings of the user **102**. That is, the platform computing system **122** queries the permissions repository **146** (e.g., via an API call, or directly, via a native query in MySQL, PostgreSQL, etc.) and adjusts the associated permissions (e.g., associated with the experience provider) to reflect that the user **102** may now view travel advertisements in exchange for 1 cent per view (e.g., to be paid by the experience provider, as discussed further in FIG. 6). In some embodiments, the revenue-sharing arrangement is maintained in the permissions repository **146** until changed by either party (e.g., the user **102** de-selects the category again via the client application **114**, or the experience provider makes a subsequent API call indicating a termination of the arrangement). In other embodiments, the revenue-sharing arrangement exists only for the lifespan of the access token (e.g., according to the expiration of the access token). In such embodiments, upon expiration of the access token, the platform computing system **122** automatically adjusts the associated permissions again (e.g., as described above) in order to reflect the termination of the arrangement. Thus, at a later time, when another data sharing request comes in from the experience provider, the access token generated will reflect the previous wishes of the user **102** (e.g., to not view political advertisements). At such a point, the experience provider computing system **150** may re-negotiate the arrangement (e.g., according to the applicable processes described in FIGS. 2, 4, and 5).

[0121] At process **420**, the platform computing system **122** transmits the acceptance response (e.g., via an API response of the access circuit **138**) to the experience provider computing system **150**. Furthermore, in some embodiments, the API response may include the expiration of the arrangement (e.g., the response indicates that the user **102** has accepted the offer, but only temporarily during the lifespan of the current access token). In other embodiments, when the arrangement is similarly temporary, the platform computing system **122** may not immediately identify the expiration of the arrangement, but rather, refresh the permission set during the generation of the next access token (e.g., the current permissions identified by the access token, as described in the method **200**). That is, continuing the sporting goods website example, at process **420** the platform computing system **122** informs (e.g., transmits) the sporting goods website that the user **102** has agreed to view travel-based advertisements in exchange for 1 cent per view.

[0122] At process **422**, the experience provider computing system **150** receives the acceptance response from the platform computing system **122**. Accordingly, the experience provider computing system **150** may then display advertisements from the advertising category identified in the arrangement (e.g., travel ads from the example). A tabulation of funds due (e.g., according to how many travel advertisements were displayed multiplied by the agreed upon revenue-sharing value) may then be provided by the experience provider computing system **150** (e.g., via an API call to the platform computing system **122**) at a predetermined interval. In some embodiments, the tabulation of funds may be provided (e.g., via the access circuit **138**) in real-time. That is, as each applicable advertisement is displayed, a tabulation of funds due is immediately transmitted. Furthermore, the platform computing system **122** may then verify the received tabulation of funds due (e.g., via the payments engine of the data management circuit **140**). The funds due may be paid out by either the experience provider or the platform **120** (e.g., via the payments engine of the data management circuit **140**). Accordingly, the platform computing system **122** may then verify the received tabulation of funds due and initiate a payment for the user **102** in the amount due (e.g., via the payments engine of the data management circuit **140**). Details of the tabulation (e.g., the systematic count, record, or list) of funds due and the subsequent payout are further discussed in FIG. 6.

[0123] Furthermore, while the method **400** describes revenue sharing between the experience provider and the user **102** as it pertains to advertising, it will be appreciated that in some

embodiments the user **102** may receive a shared-revenue offer simply for authorizing access to data. That is, the user **102** may receive an offer (e.g., \$1, \$3, etc.) from the experience provider to access data of the user **102**. Such an offer may be in addition to, or separate from, any advertising agreements made. Additionally, it will be appreciated that the offer may also be in the form of an incentive, such as a discount for goods and/or services provided by the experience provider (e.g., 5% off a next purchase in exchange for access to data or advertising categories). Accordingly, funds due for revenue sharing regarding access to data (e.g., of the user **102**) are included in the received tabulation. That is, in some embodiments, processes **402-404** may initially be directed to determining that the user **102** has not designated the experience provider for data sharing (e.g., after receiving a rejection response to a data access request from the platform computing system **122**), and subsequently in process **406**, generating a shared revenue request for access to data of the user **102**. In such an alternative embodiment, the method **400** may continue similarly with the exception of the nature of the shared revenue request (e.g., being for general data sharing and not advertising categories). For example, at process **422**, rather than display the advertising category in response to an acceptance from the user **102**, the experience provider may access the data of the user **102** and utilize it to customize the experience of the user **102** (e.g., and generate a tabulation of funds due based on accessing the data). It will be appreciated that such an embodiment is not mutually exclusive to the advertising embodiment, but rather, may be in addition to the embodiment of method **400** that pertains specifically to advertising (e.g., first access to the data of the user **102** is negotiated, and then the advertising is negotiated).

[0124] In some embodiments, a plurality of APIs can be used to carry out the processes of method **400**. For example, a first API can be configured to facilitate communication of data between the experience provider computing system **150** and the platform computing system **122** (e.g., processes **402**, **406-412**, and **422**), a second API can be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **406** and **410-416**), and a third API can be configured to facilitate communication of the shared-revenue request result between the platform computing system **122** and the experience provider computing system **150** (e.g., processes **420-422**). However, it will be appreciated that any number of APIs could be used to carry out the processes of method **400**. For example, more than one API could be configured to facilitate communication of data between the experience provider computing system **150** and the platform computing system **122** (e.g., processes **402**, **406-412**, and **422**), and likewise more than one API could be substituted for the second API and the third API discussed above. Furthermore, it will be appreciated that, for the experience providers, the APIs may be provided based on template APIs developed by the platform **120** and reused by the experience provider, or may be custom-written according to an API documentation (e.g., provided by the platform **120**, such that the experience provider may conveniently access the endpoint functions of the data sharing and permissioning service).

[0125] Now referring to FIG. 5, a flow diagram of a method **500** for a data sharing and permissioning interaction with an experience provider is shown, according to an example embodiment. As a broad overview, method **500** describes a basic advertising shared-revenue process (relative to FIG. 2) between the user **102** and an experience provider, according to a different example embodiment than method **400**. Hence, an experience provider that wishes to access certain data, or display certain advertisements, of/to the user **102** may offer to pay the user **102** a modest sum to gain access to that data (e.g., in order to improve targeted advertising), and/or to display advertisements from a particular category to the user **102**. As an example, method **500** may occur as part of a user (e.g., the user **102**) receiving a revenue sharing offer (e.g., in real-time and responsive to the user **102** visiting the website, in some embodiments) from the experience provider (e.g., displayed on the client application **114**). That is, method **500** further describes displaying a shared-revenue request on a component of the platform computing system **122** (rather than via the component of the experience provider, as described in FIG. 4). Therefore, method **500**

provides a practical example of simple advertisement revenue sharing between an experience provider (e.g., the social media website or the sporting goods website) and a user **102**. Method **500** may be performed using the system of FIG. **1**, and with similar implementation as the processes of method **200** and method **300**, such that reference is made to the components of FIGS. **1**, **2**, and **3** in order to aid the description of method **400**.

[0126] Method **500** further describes displaying a simplified shared-revenue request (e.g., similar to FIG. **4**) on a component of the platform computing system **122**, such as via a messaging center of the client application **114**. Therefore, method **500** provides a practical example of simple advertisement revenue sharing between an experience provider (e.g., the social media website or the sporting goods website) and a user **102**, which is displayed on a component of the platform computing system **122**. Method **500** may be performed using the system of FIG. **1**, and with similar implementation as the processes of method **200**, method **300**, and method **400**, such that reference is made to the components of FIGS. **1**, **2**, **3**, and **4** in order to aid the description of method **500**.

[0127] The method **500** begins at process **502** with the platform computing system **122** receiving a shared-revenue request (e.g., from an experience provider computing system **150**, regarding the user **102**). Accordingly, in some embodiments, the method **500** may begin after process **242** or after process **342**. Therefore, the method **500** begins after a successful initial exchange between the platform computing system **122** and the experience provider computing system **150** (e.g., a request for data of the user was received with an access token and successfully processed).

[0128] The received shared-revenue request may be structured substantially similar to the shared-revenue request of process **322** and processes **406-408**. That is, the shared-revenue request is an API call (e.g., received by the access circuit **138**) containing the access token of the user **102** and an identifier of the experience provider (e.g., an API token or credential contained in the JSON body of the request). Additionally, the shared-revenue request also contains an offer from the experience provider (e.g., contained in the JSON body) and a response-URL. The offer represents a revenue amount that the experience provider would like to give the user **102** as compensation for viewing advertisements from an advertising category that the user **102** has opted out of viewing (e.g., identified, for example, in process **404**). The response-URL is a URL designated by the experience provider computing system **150** for responses that exceed the timeout threshold (e.g., a maximum amount of time before a request expires-variably determined by each experience provider). Accordingly, should there be delay (e.g., such as awaiting a response to a pending message, as discussed in processes **508-510**), the platform computing system **122** may initiate an API call (e.g., via the access circuit **138**) to the response-URL defined in the request (e.g., contained in the JSON body). Furthermore, the shared-revenue request may be retrievably stored (e.g., in the user data repository **148**) for display at a later time (e.g., during an active user-session, as discussed below). In that same vein, the response-URL is also retrievably stored (e.g., as existing as part of the shared-revenue request) for initiating a response at a later time.

[0129] At process **504**, the platform computing system **122** authenticates the received shared-revenue request. Process **504** may be completed substantially similar to process **410**. That is, the authentication process may be two-fold, such that it requires authenticating the call itself (e.g., via an API token or other identifier of the experience provider, as discussed in process **322**) and the user credentials (e.g., via the access token contained in the shared-revenue request). That is, the platform computing system **122** may first validate the API call by verifying the API token included in the call (e.g., by querying the token repository **144**). Next, the platform computing system **122** authenticates that the identified user **102** (e.g., via an API call to the token repository **144**, or directly, via a native query in MySQL, PostgreSQL, etc.). Reiteratively, the platform computing system **122** verifies that the access token is both contained, and not expired, in the token repository [0130] At process **506**, the platform computing system **122** receives an indication of an active user-session (e.g., a session of the user **102**) in the client application **114** (e.g., via an API call). In some embodiments, the indication may be received in the form of the user **102** logging into the client

application **114** (e.g., logging into a mobile application or a website of the platform **120**). In other embodiments, the shared-revenue request may be received after the user **102** has already logged in to the client application **114**, and the indication may take the form of any current activity of the user **102** via the client application **114** (e.g., changing menus, adjusting settings, etc.).

[0131] At process **508**, the platform computing system **122** displays the shared-revenue request to the user **102**. In some embodiments, the platform computing system **122** may first retrieve the shared-revenue request from the user data repository **148** (e.g., when there is a delay between receiving the request and the next active user-session). Furthermore, in some embodiments, the platform computing system **122** may display the request as a pop-up on the generated graphical user interface of the client application **114** (e.g., via the interface circuit **136**). In other embodiments, the platform computing system **122** may alert the user **102** of a pending offer by dynamically marking an alert and notification area of the user interface (e.g., a messaging center). For example, the client application **114** may display (e.g., via the interface circuit **136**) an area on the user interface containing a selectable icon indicative of a messaging center (e.g., an envelope, a stack of documents, etc.). Upon receiving a shared-revenue request (or any other alert/notification, as further discussed in FIG. **6**), the interface circuit **136** may dynamically mark, or adjust, the selectable icon to indicate a new matter requiring attention from the user **102**. In some embodiments, the selectable icon may have the contrast dynamically adjusted (e.g., made darker or lighter). In other embodiments, the selectable icon may be adjoined to another icon (e.g., such as a numerical counter displayed, for example, over the top of the messaging icon).

[0132] At process **510**, the user **102** accepts the shared-revenue request (e.g., via the client application **114**) and transmits it to the platform computing system **122** (e.g., via an API call over the network **118**). For example, the user **102** may notice the dynamically marked aspect of the user interface (e.g., displayed via the client application **114**) and subsequently select (e.g., click) the area. In response, the user **102** is taken to a new page of the client application **114** (e.g., the messaging center). From there, the user **102** may select and read any messages (e.g., alerts and/or notifications) waiting for the user (e.g., contained in the user data repository **148**). Continuing the example, the user **102** may select a message correlating to the shared-revenue request and read the offer (e.g., the message opened as a new page, a new sub-area of the current page, or as a pop-up). The message may be structured similarly to the secure pop-up of process **412**. That is, it may contain a simple question (e.g., “Would you like to allow experience provider X to display political advertisements to you in exchange for 1 cent per view of political advertisements?”), and selectable interaction points for the response (e.g., a yes/no button). Therefore, at process **510**, the user **102** reads the message and selects the selectable interaction point to agree (e.g., the “yes” button). The platform computing system **122** then receives the selection (e.g., over the network **118**, via the client application **114**, received by the access circuit **138**). In embodiments where the user **102** selects the “no” button, the method **500** may conclude with a decline response to the experience provider computing system **150** (e.g., an API response, via the access circuit **138**, that informs the experience provider computing system **150** that the user **102** is not interested in the offer). In such embodiments, no further action is taken beyond the API response.

[0133] At process **512**, the platform computing system **122** receives and transmits the acceptance response (e.g., via an API response of the access circuit **138**) to the experience provider computing system **150**. Similar to process **418**, as part of receiving the “yes” selection of the user **102**, the platform computing system **122** automatically updates the data sharing and permissioning settings of the user **102**. That is, the platform computing system **122** queries the permissions repository **146** (e.g., via an API call, or directly, via a native query in MySQL, PostgreSQL, etc.) and adjusts the associated permissions (e.g., associated with the experience provider) to reflect that the user **102** may now view political advertisements in exchange for 1 cent per view (e.g., to be paid by the experience provider, as discussed further in FIG. **6**). In some embodiments, the revenue-sharing arrangement is maintained in the permissions repository **146** until changed by either party (e.g., the

user **102** de-selects the category again via the client application **114**, or the experience provider makes a subsequent API call indicating a termination of the arrangement). In other embodiments, the revenue-sharing arrangement exists only for the lifespan of the access token (e.g., according to the expiration of the access token). In such embodiments, upon expiration of the access token, the platform computing system **122** automatically adjusts the associated permissions again (e.g., as described above) in order to reflect the termination of the arrangement. Thus, at a later time, when another data sharing request comes in from the experience provider, the access token generated will reflect the previous wishes of the user **102** (e.g., to not view political advertisements). At such a point, the experience provider computing system **150** may re-negotiate the arrangement (e.g., according to the applicable processes described in FIGS. **2**, **4**, and **5**).

[0134] Furthermore, in embodiments where there is a delay between the shared-revenue request and the next active user-session of the user **102**, the platform computing system **122** response may be directed to the experience provider computing system **150** as a new API call. The new API call may utilize the response-URL contained in the shared-revenue request (e.g., the platform computing system **122** may initiate the API call by responding to the experience provider designated URL contained in the JSON body of the shared-revenue request). In some embodiments, the new API call (e.g., the delayed response) may include the expiration of the arrangement (e.g., the call indicates that the user **102** has accepted the offer, but only temporarily during the lifespan of the current access token). In other embodiments, when the arrangement is similarly temporary, the platform computing system **122** may not immediately identify the expiration of the arrangement, but rather, refresh the permission set during the generation of the next access token (e.g., the current permissions identified by the access token, as described in the method **200**).

[0135] At process **514**, the experience provider computing system **150** receives the acceptance response from the platform computing system **122** (e.g., in some embodiments, receives the acceptance response at a later time, in the form of the new API call as discussed above). Accordingly, the experience provider computing system **150** may then display advertisements from the advertising category identified in the arrangement (e.g., political ads from the example). A tabulation of funds due (e.g., according to how many political advertisements were displayed multiplied by the agreed upon revenue-sharing value) may then be provided by the experience provider computing system **150** (e.g., via an API call to the platform computing system **122**) at a predetermined interval. In some embodiments, the tabulation of funds may be provided (e.g., via the access circuit **138**) in real-time. That is, as each applicable advertisement is displayed, a tabulation of funds due is immediately transmitted. Furthermore, the platform computing system **122** may then verify the received tabulation of funds due (e.g., via the payments engine of the data management circuit **140**). Accordingly, the platform computing system **122** may then verify any received tabulation of funds due (e.g., via the payments engine of the data management circuit **140**). The funds due may be paid out by either the experience provider or the platform **120** (e.g., via the payments engine of the data management circuit **140**). Details of the tabulation of funds and the subsequent payout are further discussed in FIG. **6**.

[0136] Furthermore, while the method **500** describes revenue sharing between the experience provider and the user **102** as it pertains to advertising, it will be appreciated that in some embodiments the user **102** may receive a shared-revenue offer simply for authorizing access to data. That is, the user **102** may receive an offer (e.g., \$1, \$3, etc.) from the experience provider to access data of the user **102**. Such an offer may be in addition to, or separate from, any advertising agreements made. Accordingly, funds due for revenue sharing regarding access to data (e.g., of the user **102**) are included in the received tabulation.

[0137] In some embodiments, a plurality of APIs can be used to carry out the processes of method **500**. For example, a first API can be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **504-512**), and a second API can

be configured to facilitate communication of data between the platform computing system **122** and the experience provider computing system(s) **150** (e.g., processes **502-504** and **510-514**). However, it will be appreciated that any number of APIs could be used to carry out the processes of method **500**. For example, more than one API could be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **504-512**), and likewise more than one API could be substituted for the second API discussed above. Furthermore, it will be appreciated that, for the experience providers, the APIs may be provided based on template APIs developed by the platform **120** and reused by the experience provider, or may be custom-written according to an API documentation (e.g., provided by the platform **120**, such that the experience provider may conveniently access the endpoint functions of the data sharing and permissioning service).

[0138] Referring now to FIG. **6**, a flow diagram of a method **600** for a data sharing and permissioning interaction with an experience provider is shown, according to an example embodiment. As a broad overview, method **600** describes the regulatory, monitoring, remediation, and payment processing aspects of a data sharing event (e.g., data of the user **102** provided to an experience provider computing system **150**). Therefore, method **600** discusses data sharing and revenue sharing (e.g., similar to methods **200**, **300**, **400**, and **500**); however, method **600** further elaborates on the enforcement of the settings of the user **102** and any applicable payments associated with shared-revenue agreements. Accordingly, by participating in the service of the platform **120**, the experience provider may offload the duty of being the arbiter of what advertisements users receive. Furthermore, through the remediation protocols of the data sharing and permissioning service, the experience provider may be immediately notified of non-compliance, thus substantially reducing the risk associated with providing customized content to the user **102** (e.g., regulatory risk, reputation risk, etc.).

[0139] Method **600** may be performed using the system of FIG. **1**, and with similar implementation as the processes of method **200**, method **300**, method **400**, and method **500**, such that reference is made to the components of FIGS. **1**, **2**, **3**, **4**, and **5** in order to aid the description of method **600**.

[0140] The method **600** begins at process **602** with the user **102** selecting an option (e.g., provided via the graphical user interface of the client application **114**), which enables a data security monitoring tool of the platform computing system **122**. It should be appreciated that the process **602** may occur at any point in the various embodiments described here. That is, the data security monitoring tool may be enabled (e.g., via the client application **114**) at the discretion of the user **102**. For the sake of discussion, method **600** is described herein as occurring subsequent to a successful data sharing request (e.g., alternatively referred to as a request for data of the user **102**, such as after processes **242** and **340**).

[0141] In some embodiments, the data security monitoring tool may be provided as part of the client application **114**. For example, the data security monitoring tool may be included in the client application **114** and activated at the request of the user **102** (e.g., a user selection made via the graphical user interface). That is, in embodiments where the user device **104** is a mobile device (e.g., a cellphone, a tablet, smart glasses, etc.), the data security monitoring tool may be accessed via the graphical user interface of the client application **114**. In other embodiments, the client application **114** may prompt the user **102** to download an additional package in order to enable the data security monitoring tool (e.g., a mobile application downloaded via, for example, the Google Play Store or the iOS store, and associated with the platform **120**). In the same vein, in embodiments where the client application **114** is structured as a cloud-based asset (e.g., a webpage), the platform computing system **122** may prompt the user **102** (e.g., a pop-up, or notification, displayed on the webpage **114**) to download and install a web browser extension containing the data security monitoring tool (e.g., a browser extension maintained and provided by the platform **120**). Furthermore, in yet other embodiments, the data security monitoring tool may additionally utilize a virtual private network (VPN) provided by, or otherwise associated with, the

platform **120**. In such embodiments, the user **102** may connect the user device **104** to the VPN of the platform **120** (e.g., thus tunneling the internet traffic of the user **102** through the secure VPN of the platform **120**). In this way, the user **102** may route activity data directly through the platform computing system **122**, and therefore, enable the platform computing system **122** to have a comprehensive view of the activity occurring between the user **102** and the experience provider computing system **150** (e.g., the modalities of operation for the data security monitoring tool are discussed further below, with reference to process **606** and **608**).

[0142] At process **604**, the user **102** proceeds to access content of the experience provider (e.g., via the experience provider computing system **150**) with the data security monitoring tool enabled. For example, the user **102** may access content of the experience provider via a website, an application associated with the experience provider, a smart-device that communicates with the experience provider computing system **150**, etc. That is, the user **102** accesses content of the experience provider with the data security monitoring tool enabled as one of a component (or as an additional package) of the client application **114** or a browser extension, and optionally while connected to the VPN of the platform **120**.

[0143] At process **606**, the platform computing system **122** monitors and catalogs (e.g., monitored via the data security monitoring tool, communicated via an API call or directly-inspected such as via the VPN) the experience provider content, accessed by the user **102** in process **604**. For example, the platform computing system **122** may utilize the data security tool (e.g., via the client application **114**, or via the browser extension) to inspect and analyze the content shown to the user **102**. In some embodiments, the data security monitoring tool may inspect the source code for the experience provider content (e.g., a website), including executable scripts and metadata associated with the content (e.g., a set of data that describes and provides information about other data). Accordingly, the platform computing system **122** may then compare the inspected source code with a list of data aggregated from advertising servers in order to ascertain categorical information about the content. In some embodiments, the list of data from advertising servers is aggregated and maintained by the platform **120**. In other embodiments, the list of data from advertising servers is provided and maintained by an experience provider. In yet other embodiments, the list of data from advertising servers is a collaborative effort between an experience provider and the platform **120**.

[0144] Furthermore, in some embodiments, the data security monitoring tool may run the source code in a sandbox environment in order to ascertain the categorical information about the content. The sandbox environment is an isolated virtual machine, associated with the platform computing system **122**, in which potentially unsafe software code can execute without affecting network resources or local applications. Thus, the platform computing system **122** may run the source code of the experience provider content in a safe environment, and subsequently inspect and analyze the results directly (e.g., via code analysis and interpretation of the results, including the use of image recognition logic). In some embodiments, the platform computing system **122** may also utilize the VPN connection, where applicable, to further analyze the content of the experience provider by directly inspecting the data packets exchanged by the user device **104** and the experience provider computing system **150**. In this manner, the platform computing system **122** may directly inspect all unencrypted traffic (e.g., via a Deep Packet Inspection (DPI) algorithm). It should be appreciated that the exemplary embodiment encompasses the user **102** utilizing the data security monitoring tool in conjunction with the VPN service of the platform **120**. In this manner, the experience provider content may be thoroughly inspected and analyzed, while simultaneously capturing the activity data of the user **102** (e.g., for retrievable storage in the user data repository **148**).

Accordingly, the platform computing system **122** may then catalog the activity data of the user **102** and store it in the user data repository **148**.

[0145] At process **608**, the platform computing system **122** identifies (e.g., via the data security monitoring tool) non-compliant content being served to the user **102**, via the experience provider computing system **150**. For example, the platform computing system **122** may identify (e.g.,

subsequent to the analysis of process **606**) a script, or other component of the experience provider content, that generates advertisements from a category (e.g., according to the classification scheme) opted out of by the user **102** (e.g., as identified in the permissions repository **146**).

[0146] At process **610**, the platform computing system **122** generates an alert for the user **102**, and provides it via the client application **114** (e.g., over the network **118**). In some embodiments, the platform computing system **122** may display the alert as a secure pop-up (e.g., similar to processes **226-228** and **320**) on the generated graphical user interface of the client application **114** (e.g., via the interface circuit **136**). In other embodiments, the platform computing system **122** may notify the user **102** of the pending alert by dynamically marking an alert and notification area of the user interface (e.g., a messaging center displayed via the client application **114**). For example, the client application **114** may display (e.g., via the interface circuit **136**) an area on the user interface containing a selectable icon indicative of a messaging center (e.g., an envelope, a stack of documents, etc.). Upon receiving the non-compliant content alert, the interface circuit **136** may dynamically mark, or adjust, the selectable icon to indicate a new matter requiring attention from the user **102**. In some embodiments, the selectable icon may have the contrast dynamically adjusted (e.g., made darker or lighter). In other embodiments, the selectable icon may be adjoined to another icon (e.g., such as a numerical counter displayed, for example, over the top of the messaging icon).

[0147] The alert may be structured to inquire of the user **102** about the identified non-compliant content and to offer a remediation protocol. For example, the alert may state that “We noticed that Experience provider X is showing advertisements from a category you opted out of: Sports. Would you like to transmit a cease and desist warning or disconnect from Experience provider X's services?” The alert may be further structured such that the user **102** may be provided with selectable interaction points (e.g., a “Warn” button and a “Disconnect” button) to facilitate a quick and convenient response.

[0148] At processes **612** and **614**, the user **102** receives the alert (e.g., via the client application **114**), views the alert (e.g., selects a selectable icon that displays the alert), and selects a remediation protocol (e.g., warn or disconnect). In embodiments where the user **102** selects the option to disconnect, the client application **114** may temporarily block all data exchange between the user device **104** and the experience provider computing system **150** (e.g., for an hour, a day, a week, etc., as predetermined by the platform **120**). In such embodiments, the method **600** continues at process **624**. However, in embodiments where the user **102** selects the option corresponding to warning the experience provider, the method **600** continues at process **616** (e.g., after communicating the remediation protocol selection of the user **102** to the platform computing system **122** via an API call).

[0149] At process **616**, the platform computing system **122** receives the remediation selection of the user **102** (e.g., a selection to warn the experience provider, via the client application **114**). At process **618**, the platform computing system **122** generates and transmits a cease and desist warning to the experience provider computing system **150**. The cease and desist warning may be transmitted as an API call (e.g., via the access circuit **138**) to the experience provider computing system **150**. Furthermore, the cease and desist warning may include (e.g., in the JSON body of the call) the access token of the user **102** (e.g., to identify the non-compliant user experience), the non-compliant advertising category, and in some embodiments, a punitive measure. That is, in some embodiments, the platform computing system **122** may impose a punitive measure on the experience provider for the non-compliant advertising. The punitive measure may be in the form of a financial penalty, a service penalty (e.g., a temporary lockout from data sharing requests), or a regulatory penalty (e.g., reporting the non-compliance to an applicable regulatory oversight department).

[0150] At process **620**, the experience provider computing system **150** receives the cease and desist warning (e.g., the API call, over the network **118**). Accordingly, at process **622**, the experience provider computing system **150** adjusts the content being served to the user **102**. Thus, continuing

the example, the experience provider computing system **150** may make the corrections necessary (e.g., based on the infrastructure and implementation of the experience provider computing system **150**) in order to prevent any further non-compliant advertisements from reaching the user **102**. [0151] At process **624**, the experience provider computing system **150** tabulates the funds due to the user **102** (e.g., based on any shared-revenue agreements, as discussed previously, with reference to FIGS. **2**, **3**, **4**, and **5**). The experience provider computing system **150** may tabulate the funds due in real-time, as particular advertisements are served and viewed, or at predetermined intervals. For example, the experience provider computing system may generate a data structure (e.g., a JSON-formatted dictionary/list, for an API call) containing associative entries, which identify the shared-revenue advertisements that were served to the user **102**, and the corresponding financial compensation due. In some embodiments, the generated data structure may contain additional data, such as a timestamp identifying the date and time that the advertisement was served, a portion of funds due to the platform **120** (e.g., where applicable, as discussed in FIG. **2**), and a currency type for the funds due (e.g., United States Dollar). Furthermore, in embodiments where the user **102** selected to disconnect from the experience provider service (e.g., as discussed in process **614**), the experience provider computing system **150** is required to tabulate the funds due at the time of disconnection.

[0152] At process **626**, the experience provider computing system **150** transmits the data structure containing the tabulation of funds due to the platform computing system **122** (e.g., via an API call structured as discussed above, over the network **118**). At process **628**, the platform computing system **122** receives the tabulation of funds (e.g., via the access circuit **138**). The platform computing system **122** may then verify the tabulation of funds due (e.g., via the payments engine of the data management circuit **140**). That is, the platform computing system **122** may traverse the received data structure and verify the calculations (e.g., advertisements served multiplied by the agreed-upon price per view).

[0153] Therefore, at process **630**, the platform computing system **122** deposits the funds due (e.g., as identified by the tabulation of funds due) into an account of the user **102** (e.g., via the payments engine of the data management circuit **140**). In some embodiments, the experience provider computing system **150** may first transfer the funds due to an account associated with the platform computing system **122** (e.g., a distribution account established for paying shared-revenue agreements). In other embodiments, the platform **120** may settle funds due with the experience provider associated with the experience provider computing system **150** at a predetermined interval (e.g., as dictated by a contract or agreement between the platform **120** and the experience provider). The account of the user **102** may be a financial account (e.g., entered during registration, as discussed in FIG. **3**), or any other account of the user **102** that may receive funds (e.g., entered via the client application **114**). For example, the account may be a gift card, a prepaid card, a rewards account, etc. Furthermore, in embodiments where the platform **120** is a financial institution, or associated with a financial institution, the account may be an account held by the user **102** with the platform **120** (e.g., an account held with the platform **120** and selected from the prepopulated list during registration, as described in process **310**).

[0154] Furthermore, while the method **600** describes revenue sharing between the experience provider and the user **102** as it pertains to advertising, it will be appreciated that in some embodiments the user **102** may receive a shared-revenue offer simply for authorizing access to data. That is, the user **102** may receive an offer (e.g., \$1, \$3, etc.) from the experience provider to access data of the user **102**. Such an offer may be in addition to, or separate from, any advertising agreements made. Accordingly, funds due for revenue sharing regarding access to data (e.g., of the user **102**) are included in the received tabulation.

[0155] In some embodiments, a plurality of APIs can be used to carry out the processes of method **600**. For example, a first API can be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **606** and **610-616**), and a second

API can be configured to facilitate communication of data between the platform computing system **122** and the experience provider computing system(s) **150** (e.g., processes **618-620** and **626-628**). However, it will be appreciated that any number of APIs could be used to carry out the processes of method **600**. For example, more than one API could be configured to facilitate communication of data between the user **102** and the platform computing system **122** (e.g., processes **606** and **610-616**), and likewise more than one API could be substituted for the second API discussed above. Furthermore, it will be appreciated that, for the experience providers, the APIs may be provided based on template APIs developed by the platform **120** and reused by the experience provider, or may be custom-written according to an API documentation (e.g., provided by the platform **120**, such that the experience provider may conveniently access the endpoint functions of the data sharing and permissioning service).

[0156] Additionally, at the conclusion of methods **200**, **300**, **400**, **500**, and **600**, the user **102** may be presented with a voting interface (e.g., generated via the interface circuit **136** and displayed on the client application **114**), which prompts the user **102** to provide a rating for the experience provider based on how well the experience provider complied with the preferences and settings of the user **102** (e.g., during the activity session). The rating may be based on a scale of the platform **120** (e.g., 5 stars, 1-10, etc.) and subjectively determined according to the experience of the user **102**.

Furthermore, the ratings may be aggregated and averaged by the platform computing system **122**, and subsequently provided to other users (e.g., during registration, configuration processes, and via a centralized location, such as a ratings website maintained by the platform **120**). Accordingly, through such experience transparency, experience providers are incentivized both to adhere to the preferences of the user **102** and to provide updated activity data to the platform computing system **122** (e.g., in order to avoid social backlash or ill will).

[0157] While methods **200**, **300**, **400**, **500**, and **600** are described as being separate and distinct from one another, it will be appreciated that some processes of methods **200**, **300**, **400**, **500**, and **600** are the same or similar to one another, that some methods may include all of the processes of another method, some methods may not include any processes of another method, and some methods may include some processes but not all processes of another method.

[0158] Furthermore, in some embodiments, it will be appreciated that the platform computing system **122** applies (e.g., via the rules engine of the data management circuit **140**) all applicable regulatory and privacy requirements to the methods of **200**, **300**, **400**, **500**, and **600**. The applicable regulatory and privacy requirements may be determined according to the rules utilized by the rules engine (e.g., the rules being regularly configured and updated, as discussed in FIG. **1**). That is, the platform computing system **122** may adjust (e.g., by the data management circuit **140**, via the interface circuit **136**) the data sharing and permissioning interfaces to prevent the user **102** from attempting to share, for example, health and/or financial information protected by law (e.g., Health Insurance Portability and Accountability Act (HIPAA)). For example, in some embodiments, the platform computing system **122** may not display data categories for data associated with such regulations (e.g., preventing the user **102** from making a selection to share the associated data). In other embodiments, the platform computing system **122** may only display such data categories after receiving (e.g., a document upload via the graphical user interface of the client application **114**) the required authorization documents (e.g., to share medical data with a new doctor). Furthermore, the platform computing system **122** may actively analyze (e.g., via the data management circuit **140**) the data of the user **102** (e.g., in real-time during updates or at predetermined intervals) and move all such data protected by regulatory law to protected categories (e.g., in the user data repository **148**) in order to prevent accidental distribution of the protected data.

[0159] Referring now to FIG. **7**, an illustrative example of a dynamic graphical user interface **700**, displayed on the user device **104** as part of a data sharing process is shown, according to an example embodiment. In the depicted embodiment, the user device **104** includes a display showing

the graphical user interface **700** (e.g., provided by the client application **114**, via the interface circuit **136**), which is structured to facilitate a user (e.g., the user **102**) to configure data sharing for an identified experience provider, as described in the method **200**.

[0160] The user interface of **700** includes a title bar **702**; section columns **704**, **706**, and **708**; section rows **710**, **712**, and **714**; a “BACK” button **716**; and a “SUBMIT” button **718**. The title bar **702** is depicted as a textual (e.g., string) display title, which informs the user as to the purpose of the display. The title bar **702** is structured to dynamically update (e.g., via the interface circuit **136**, displayed by the client application **114**) as the user **102** navigates around the client application **114**. Accordingly, the title bar **702** informs the user **102** that the purpose of the graphical user interface **700** is to configure data sharing for the experience provider domain “XYZ.COM”.

[0161] The section columns **704**, **706**, and **708** are depicted as textual (e.g., string) column titles that identify the data held in the rows below them. For example, section column **704**, “DATA CATEGORY”, identifies the contents of the rows below as data category labels. Continuing, section column **706**, “ENABLED”, identifies the contents of the rows below as a selectable Boolean attribute (e.g., to enable/disable data sharing from the associated data category, with the experience provider identified in the display title). Section column **708**, “MANAGE DATA SHARING AND PREFERENCE SETTINGS” identifies the contents of the rows below as a selectable interaction point, which when selected brings the user **102** to a display (not depicted) that enables the user **102** to create more narrow subsets of the correlated data category (e.g., such as described in processes **204** and **206**).

[0162] Therefore, the section rows **710**, **712**, and **714** represent an operative view of each data category, as it pertains to its enablement and structure. That is, in the depicted example, each row contains a data category label (e.g., string), a Boolean selectable toggle (e.g., a button as depicted), and a selectable interaction point (e.g., a button as depicted), which enables the user **102** to further narrow the data category. For example, section row **710** defines an operative view of a data category for sports (e.g., for the method **200**). Accordingly, section row **710** indicates that data categorized as relating to sports will be shared with XYZ.COM (e.g., with an optional button to further narrow sports into other subsets, such as golf and football). Similarly, section row **712** indicates that data categorized as relating to Food will not be shared with XYZ.com (e.g., with an optional button to further narrow food into other subsets, such as food types or food distinctions-cooking recipes and favorite restaurants). Section row **714** indicates that data categorized as relating to travel will not be shared with XYZ.COM (e.g., with an optional button to further narrow travel into other subsets, such as destinations and activities).

[0163] The generated graphical user interface **700** further depicts a “BACK” button **716**. The button **716** is depicted as a selectable (e.g., clickable) button of the generated graphical user-interface that transitions the user **102** back to a previous display (not depicted), without initiating process **208** of method **200**.

[0164] The “SUBMIT” button **718** is depicted as a selectable (e.g., clickable) button of the generated graphical user interface, which in response to being selected, initiates process **208** of method **200**. Accordingly, the data category selections represented by the operative view of section rows **710**, **712**, and **714** may subsequently be utilized in the process of data sharing and permissioning (e.g., as discussed above, with reference to FIG. 2).

[0165] Now referring to FIG. 8, an illustrative example of a user device **104** display **800** accessing experience provider content while using a data sharing protocol is shown, according to an example embodiment. In the depicted embodiment, the display **800** includes a web browser **802** accessing experience provider content (e.g., a website).

[0166] The display **800** further includes an account notification **804**; content columns **806**, **808**, and **810**; a secure pop-up **812**; a “NO” button **814**; and a “YES” button **816**. The account notification **804** is depicted as text (e.g., string) that informs the user **102** of the currently logged in account (e.g., logged into the experience provider website). Therefore, as depicted, the account notification

804 informs the user **102** that the experience provider content is currently being accessed under the data sharing and permissioning settings of “TOM.I”.

[0167] The content columns **806**, **808**, and **810** include a textual (e.g., string) and categorical title with correlating content (abstracted as vertical ellipses in the depiction). Accordingly, content column **806** contains news content, content column **808** contains weather content, and content column **810** contains featured products (e.g., advertisements).

[0168] The secure pop-up **812** is depicted as showing an example offer from the experience provider to view an advertising category, such as is described in process **412** of the method **400**. That is, the secure pop-up is depicted as an SSL encrypted connection to the platform computing system **122**, appearing on an experience provider component (e.g., the experience provider website). As depicted, the secure pop-up **812** prompts the user **102** with an offer of the experience provider to share revenue (e.g., 1 cent per view) for advertisements relating to cleaning products. Accordingly, the display **800** further includes buttons associated with the secure pop-up **812**. The associated buttons are shown as a “NO” button **814** and a “YES” button **816**. The “NO” button **814** is depicted as a selectable (e.g., clickable) button, which may be selected by the user **102** in order to decline the offer. The “YES” button **816** is depicted as a selectable (e.g., clickable) button, which may be selected by the user **102** in order to accept the offer. Accordingly, the “YES” button **816** may initiate, for example, process **416** of the method **400**.

[0169] Now referring to FIG. **9**, an illustrative example of a user device **104** display **900** interacting with an experience provider computing system **150** while using the data sharing protocol is shown, according to an example embodiment. In the depicted embodiment, the user device **104** is a smart car, and the display **900** is an interface of the smart car (e.g., a touchscreen).

[0170] The display **900** includes an account notification **902**, a welcome message **904**, an itinerary **906** generated based on the data sharing and permissioning protocol of the platform **120**, a “MAKE CHANGES” button **908**, and a “SOUNDS GREAT!” button **910**. The account notification **902** is depicted a text (e.g., string) that informs the user **102** of the currently logged in account (e.g., logged into the smart car interface). Therefore, as depicted, the account notification **902** informs the user **102** that the smart car is currently utilizing the data sharing and permissioning settings of “TOMR.I”.

[0171] The generated itinerary **906** (e.g., generated based on data shared from the TOMR.I account) is depicted as a series of textual (e.g., string) proposals for the user **102**. Namely, the generated itinerary **906** informs the user **102** that the smart car has deduced (e.g., based on the shared data of the user **102**) that the user **102** may enjoy an impromptu trip to the local tavern, where a flash dance conga meet-up is about to occur. The smart car may deduce these items based on the data shared from the TOMR.I account, such as through analysis of the user's **102**: social media posts (e.g., gathered via web scraping as discussed in FIG. **3**), data the user **102** manually entered during registration (e.g., as discussed in FIG. **3**), internet history (e.g., activity data of the user **102**, including updated activity data such as is discussed in FIG. **2**), and transaction history (e.g., as discussed in FIG. **3**). For example, the smart car may identify that the user **102** has many social media posts relating to dancing, an internet search history that indicates many recent searches about flash mobs, and a transaction history indicating that the user **102** often orders the same drink at various locations (e.g., a favorite drink). Accordingly, the smart car proposes to set the local tavern (e.g., the Thirsty Tavern) as a self-driving destination, pre-pay a cover charge for the user **102**, and order ahead so that the favorite drink of the user **102** is ready upon arrival.

[0172] The display **900** further depicts a “MAKE CHANGES” button **908** and a “SOUNDS GREAT!” button **910**. The “MAKE CHANGES” button **908** is depicted as a selectable (e.g., clickable) button, which may be selected by the user **102** in order to make changes to the proposed itinerary (e.g., cancel, add, or alter aspects of the itinerary). The “SOUNDS GREAT!” button is depicted as a selectable (e.g., clickable) button, which may be selected by the user **102** in order to accept the proposed itinerary (and commence according to the protocol of the experience provider

smart car).

[0173] Referring now to FIG. **10**, an illustrative example of a dynamic graphical user interface **1000**, displayed on the user device **104** during a registration process of the data sharing and permissioning service (e.g., of the platform **120**) is shown, according to an example embodiment. In the depicted embodiment, the user device **104** includes a display showing the graphical user interface **1000** (e.g., provided by the client application **114**, via the interface circuit **136**), which is structured to facilitate a user (e.g., the user **102**) to register for the data sharing and permissioning service of the platform **120**.

[0174] As shown, the graphical user interface **1000** includes a registration interface title **1002**; a dynamically adjusted messaging center icon **1004**; registration input prompts **1006**, **1012**, **1016**, **1020**, and **1024**; registration input fields **1008**, **1014**, **1018**, **1022**, and **1026**; a dynamically generated input validator **1010**; and a “NEXT” button **1028**.

[0175] The registration interface title **1002** is depicted as a textual (e.g., string) title that identifies (e.g., to the user **102**) the contents of the interface as pertaining to a *.i (e.g., the data sharing and permissioning service of the platform **120**, as described herein) account registration. The dynamically adjusted messaging center icon **1004** is depicted as a selectable icon containing a dynamically adjusted (e.g., contrast, increment, decrement) numerical counter. As shown, the dynamically adjusted messaging center icon **1004** includes a grayed-out (e.g., contrasted) zero, thus indicating to the user **102** that the messaging center is currently not-applicable (e.g., as the user **102** is still in the registration phase).

[0176] The registration input prompts **1006**, **1012**, **1016**, **1020**, and **1024** are depicted as textual (e.g., string) statements that inform the user **102** what to input in the correlated registration input fields **1008**, **1014**, **1018**, **1022**, and **1026**. Accordingly, registration input prompt **1006** informs the user **102** that the registration input field **1008** is for entering a username (e.g., “TOMR” as shown). Furthermore, registration input prompt **1006** and the correlated registration input field **1008** are depicted as being associated with the dynamically generated input validator **1010**. The dynamically generated input validator **1010** is depicted as a checkmark, which indicates to the user **102** that the username entered in the registration input field **1008** is available for registration (e.g., “TOMR”). However, it should be appreciated that prior to entering a username or after entering a username that has already been claimed, the dynamically generated input validator **1010** is not shown to the user **102** (e.g., dynamically generated).

[0177] Continuing on, registration input prompt **1012** informs the user **102** that the registration input field **1014** is for entering a first name and a last name (e.g., of the user **102**). Similarly, registration input prompt **1016** informs the user **102** that the registration input field **1018** is for entering a current address (e.g., of the user **102**).

[0178] Registration input prompt **1020** informs the user **102** that the registration input field **1022** is for selecting a payment account type (e.g., depicted as selectable buttons, labeled “CHECKING”, “GIFT CARD”, and “OTHER”). Lastly, registration input prompt **1024** informs the user **102** that the registration input field **1026** is for entering the account number of the payment account selected at **1022**. The graphical user interface **1000** also depicts a “NEXT” button **1028**. The “NEXT” button **1028** is depicted as a selectable (e.g., clickable) button, which may be selected by the user **102** in order to submit the inputs and proceed to the next step of the registration process (e.g., such as is described in the method **300**).

[0179] Referring now to FIG. **11**, an illustrative example of a dynamic graphical user interface **1100** for a message center, displayed on the user device **104** is shown, according to an example embodiment. In the depicted embodiment, the user device **104** includes a display showing a graphical user interface **1100** (e.g., provided by the client application **114**, via the interface circuit **136**), which is structured to facilitate a user (e.g., the user **102**) to view and respond to alerts and notifications (e.g., messages).

[0180] As shown, the graphical user interface **1100** includes an interface title **1102**; a dynamically

adjusted messaging center icon **1104**; message selection checkboxes **1106**, **1108**, and **1110**; selectable message subject lines **1112**, **1114**, and **1116**; a “DELETE” button **1118**; and a “HOME” button **1120**.

[0181] The interface title **1102** is a textual (e.g., string) title that identifies the contents of the display. Accordingly, the interface title **1102**, “MESSAGE CENTER”, identifies the contents of the display as pertaining to alerts and notifications (e.g., for the user **102**). The dynamically adjusted messaging center icon **1104** is depicted as a selectable icon containing a dynamically adjusted (e.g., contrast, increment, decrement) numerical counter. As shown, the dynamically adjusted messaging center icon **1104** includes a darkly-contrasted (e.g., not grayed-out as in FIG. **10**) numerical three, thus indicating that the messaging center has 3 unviewed messages for the user **102**. Furthermore, it should be appreciated that the user **102** may select (e.g., click) the dynamically adjusted messaging center icon **1104** on any interface of the client application **114** that displays it, and subsequently be shown the graphical user interface of **1100** (e.g., display the message center).

[0182] The message selection checkboxes **1106**, **1108**, and **1110** correlate to the selectable message subject lines **1112**, **1114**, and **1116**. That is, the message selection checkboxes are depicted as selectable (e.g., clickable) checkboxes, which when selected by the user **102**, identify a message associated with the correlated selectable message subject line for an operation (e.g., as further discussed below). For example, the user **102** may select the checkbox **1106** in order to identify the message associated with the selectable message subject line **1112** for a future operation.

[0183] The selectable message subject lines **1112**, **1114**, and **1116** are depicted as selectable rows containing a textual (e.g., string) subject (e.g., the subject of the associated message). For example, the selectable message subject line **1112** “WELCOME TO THE *.I DATA SHARING FAMILY!” may be selected (e.g., clicked) by the user **102**, thus causing the client application **114** to display a welcome message associated with the subject line **1112** (e.g., via a pop-up or an interface transition to another page). Accordingly, the selectable message subject line **1114**, “TIPS FOR MAKING YOUR FINANCIAL ACCOUNTS MORE SECURE WITH THE *.I PROTOCOL” may be selected (e.g., clicked) by the user **102**, thus causing the client application **114** to display a tips article associated with the subject line **1114**. Similarly, the selectable message subject line **1116**, “OFFER TO SHARE ADVERTISING REVENUE FROM EXPERIENCE PROVIDER.COM.” may be selected (e.g., clicked) by the user **102**, thus causing the client application **114** to display a revenue sharing offer associated with the subject line **1116** (e.g., as described herein, with reference to FIG. **5**).

[0184] The “DELETE” button **1118** is depicted as a selectable (e.g., clickable) button, which may be selected by the user **102** in order to delete any messages identified by user selections of the message selection checkboxes **1106**, **1108**, and **1110**. For example, subsequent to viewing the welcome message associated with the selectable message subject line **1112**, the user **102** may decide to delete the welcome message via the checkbox **1106** and the “DELETE” button **1118**. It should be appreciated that the “DELETE” button **1118** may be used in batch operations, such that any number of message selection checkboxes may be selected by the user **102** and subsequently deleted in one click.

[0185] The “HOME” button **1120** is depicted as a selectable (e.g., clickable) button, which may be selected by the user **102** in order to return to a home screen of the client application **114** (not shown).

[0186] While this specification contains many specific implementation details and/or arrangement details, these should not be construed as limitations on the scope of any inventions or of what may be claimed, but rather as descriptions of features specific to particular implementations and/or arrangements of the systems and methods described herein. Certain features that are described in this specification in the context of separate implementations and/or arrangements can also be implemented and/or arranged in combination in a single implementation and/or arrangement. Conversely, various features that are described in the context of a single implementation and/or

arrangement can also be implemented and arranged in multiple implementations and/or arrangements separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

[0187] Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In some cases, the actions recited in the claims can be performed in a different order and still achieve desirable results. In addition, the processes depicted in the accompanying figures do not necessarily require the particular order shown, or sequential order, to achieve desirable results.

[0188] It should be understood that no claim element herein is to be construed under the provisions of 35 U.S.C. § 112 (f), unless the element is expressly recited using the phrase “means for.”

[0189] The embodiments described herein have been described with reference to drawings. The drawings illustrate certain details of specific embodiments that implement the systems, methods and programs described herein. However, describing the embodiments with drawings should not be construed as imposing on the disclosure any limitations that may be present in the drawings.

[0190] As used herein, the term “circuit” may include hardware structured to execute the functions described herein. In some embodiments, each respective “circuit” may include machine-readable media for configuring the hardware to execute the functions described herein. The circuit may be embodied as one or more circuitry components including, but not limited to, processing circuitry, network interfaces, peripheral devices, input devices, output devices, sensors, etc. In some embodiments, a circuit may take the form of one or more analog circuits, electronic circuits (e.g., integrated circuits (IC), discrete circuits, system on a chip (SOC) circuits), telecommunication circuits, hybrid circuits, and any other type of “circuit.” In this regard, the “circuit” may include any type of component for accomplishing or facilitating achievement of the operations described herein. For example, a circuit as described herein may include one or more transistors, logic gates (e.g., NAND, AND, NOR, OR, XOR, NOT, XNOR), resistors, multiplexers, registers, capacitors, inductors, diodes, wiring, and so on.

[0191] The “circuit” may also include one or more processors communicatively coupled to one or more memory or memory devices. In this regard, the one or more processors may execute instructions stored in the memory or may execute instructions otherwise accessible to the one or more processors. In some embodiments, the one or more processors may be embodied in various ways. The one or more processors may be constructed in a manner sufficient to perform at least the operations described herein. In some embodiments, the one or more processors may be shared by multiple circuits (e.g., circuit A and circuit B may comprise or otherwise share the same processor which, in some example embodiments, may execute instructions stored, or otherwise accessed, via different areas of memory). Alternatively or additionally, the one or more processors may be structured to perform or otherwise execute certain operations independent of one or more co-processors. In other example embodiments, two or more processors may be coupled via a bus to enable independent, parallel, pipelined, or multi-threaded instruction execution. Each processor may be implemented as one or more processors, application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), digital signal processors (DSPs), or other suitable electronic data processing components structured to execute instructions provided by memory. The one or more processors may take the form of a single core processor, multi-core processor (e.g., a dual core processor, triple core processor, quad core processor), microprocessor, etc. In some embodiments, the one or more processors may be external to the apparatus, for example the one or more processors may be a remote processor (e.g., a cloud based processor). Alternatively or additionally, the one or more processors may be internal and/or local to the apparatus. In this regard, a given circuit or components thereof may be disposed locally (e.g., as part of a local

server, a local computing system) or remotely (e.g., as part of a remote server such as a cloud based server). To that end, a “circuit” as described herein may include components that are distributed across one or more locations.

[0192] An exemplary system for implementing the overall system or portions of the embodiments might include a general purpose computing devices in the form of computers, including a processing unit, a system memory, and a system bus that couples various system components including the system memory to the processing unit. Each memory device may include non-transient volatile storage media, non-volatile storage media, non-transitory storage media (e.g., one or more volatile and/or non-volatile memories), etc. In some embodiments, the non-volatile media may take the form of ROM, flash memory (e.g., flash memory such as NAND, 3D NAND, NOR, 3D NOR), EEPROM, MRAM, magnetic storage, hard discs, optical discs, etc. In other embodiments, the volatile storage media may take the form of RAM, TRAM, ZRAM), etc. Combinations of the above are also included within the scope of machine-readable media. In this regard, machine-executable instructions comprise, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions. Each respective memory device may be operable to maintain or otherwise store information relating to the operations performed by one or more associated circuits, including processor instructions and related data (e.g., database components, object code components, script components), in accordance with the example embodiments described herein.

[0193] It should also be noted that the term “input devices,” as described herein, may include any type of input device including, but not limited to, a keyboard, a keypad, a mouse, joystick or other input devices performing a similar function. Comparatively, the term “output device,” as described herein, may include any type of output device including, but not limited to, a computer monitor, printer, facsimile machine, or other output devices performing a similar function.

[0194] Any foregoing references to currency or funds are intended to include fiat currencies, non-fiat currencies (e.g., precious metals), and math-based currencies (often referred to as cryptocurrencies). Examples of math-based currencies include Bitcoin, Litecoin, Dogecoin, and the like.

[0195] It should be noted that although the diagrams herein may show a specific order and composition of method steps, it is understood that the order of these steps may differ from what is depicted. For example, two or more steps may be performed concurrently or with partial concurrence. Also, some method steps that are performed as discrete steps may be combined, steps being performed as a combined step may be separated into discrete steps, the sequence of certain processes may be reversed or otherwise varied, and the nature or number of discrete processes may be altered or varied. The order or sequence of any element or apparatus may be varied or substituted according to alternative embodiments. Accordingly, all such modifications are intended to be included within the scope of the present disclosure as defined in the appended claims. Such variations will depend on the machine-readable media and hardware systems chosen and on designer choice. It is understood that all such variations are within the scope of the disclosure. Likewise, software and web implementations of the present disclosure could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various database searching steps, correlation steps, comparison steps and decision steps.

[0196] The foregoing description of embodiments has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure to the precise form disclosed, and modifications and variations are possible in light of the above teachings or may be acquired from this disclosure. The embodiments were chosen and described in order to explain the principals of the disclosure and its practical application to enable one skilled in the art to utilize the various embodiments and with various modifications as are suited to the particular use contemplated. Other substitutions, modifications, changes and omissions may be made in the

design, operating conditions and embodiment of the embodiments without departing from the scope of the present disclosure as expressed in the appended claims

Claims

1. A method comprising: detecting, by a computing system and via a security tool, a noncompliance event based on content accessed by one or more user devices and served by an experience provider that is noncompliant with a data sharing preference of the one or more user devices; providing, by the computing system using one or more APIs based on detecting the noncompliance event, an alert on a graphical user interface (GUI) of a client application, wherein the alert comprises one or more options associated with the detected noncompliance event; and remediating, by the computing system and via the security tool using the one or more APIs, the detected noncompliance event according to a remediation selection of the one or more options based on executing an API call with the experience provider by: transmitting a warning to the experience provider regarding a penalty for the noncompliance; receiving, from the experience provider, a data structure comprising a tabulation of funds due to resolve the penalty; verifying the tabulation of funds due; and depositing the funds due into an account of a user of the one or more user devices to resolve the penalty.
2. The method of claim 1, wherein detecting the noncompliance event comprises: identifying one or more advertisement categories opted out of by the user of the one or more user devices; and determining that the experience provider has generated one or more advertisements corresponding to at least one of the one or more advertisement categories opted out of by the user.
3. The method of claim 1, wherein the alert is provided as a pop-up notification or an area on the GUI comprising a selectable icon.
4. The method of claim 3, wherein the alert is provided as the area on the GUI comprising the selectable icon, and wherein, responsive to detecting the noncompliance event, the method comprises dynamically adjusting the selectable icon to indicate the alert to the user.
5. The method of claim 1, wherein the one or more options associated with the detected noncompliance event comprise warning the experience provider or disconnecting from the experience provider.
6. The method of claim 5, wherein the method further comprises: receiving a selection of disconnecting from the experience provider; and temporarily blocking data exchanges between the one or more user devices and the experience provider for a predetermined length of time.
7. The method of claim 1, wherein the warning comprises at least one of: an access token of the one or more user devices, a category associated with the noncompliance event, or the penalty.
8. The method of claim 1, wherein the penalty for the noncompliance is at least one of: a financial penalty, a service penalty, or a regulatory penalty.
9. The method of claim 1, further comprising transferring, prior to depositing the funds due into the account of the user, the funds due from the experience provider to an account associated with the computing system, wherein the funds due are deposited into the account of the user from a distribution account of the computing system.
10. A computing system comprising one or more processors configured to: detect, by the one or more processors and via a security tool, a noncompliance event based on content accessed by one or more user devices and served by an experience provider that is noncompliant with a data sharing preference of the one or more user devices; provide, by the one or more processors using one or more APIs based on detecting the noncompliance event, an alert on a graphical user interface (GUI) of a client application, wherein the alert comprises one or more options associated with the detected noncompliance event; and remediate, by the one or more processors and via the security tool using the one or more APIs, the detected noncompliance event according to a remediation selection of the one or more options based on executing an API call with the experience provider by: transmitting a

warning to the experience provider regarding a penalty for the noncompliance; receiving, from the experience provider, a data structure comprising a tabulation of funds due to resolve the penalty; verifying the tabulation of funds due; and depositing the funds due into an account of a user of the one or more user devices to resolve the penalty.

11. The computing system of claim 10, wherein detecting the noncompliance event comprises: identifying one or more advertisement categories opted out of by the user of the one or more user devices; and determining that the experience provider has generated one or more advertisements corresponding to at least one of the one or more advertisement categories opted out of by the user.

12. The computing system of claim 10, wherein the alert is provided as a pop-up notification or an area on the GUI comprising a selectable icon.

13. The computing system of claim 12, wherein the alert is provided as the area on the GUI comprising the selectable icon, and wherein, responsive to detecting the noncompliance event, the one or more processors are further configured to dynamically adjust the selectable icon to indicate the alert to the user.

14. The computing system of claim 10, wherein the one or more options associated with the detected noncompliance event comprises warning the experience provider or disconnecting from the experience provider.

15. The computing system of claim 14, wherein the one or more processors are further configured to: receive a selection of disconnecting from the experience provider; and temporarily block data exchanges between the one or more user devices and the experience provider for a predetermined length of time.

16. The computing system of claim 10, wherein the warning comprises at least one of: an access token of the one or more user devices, a category associated with the noncompliance event, or the penalty.

17. The computing system of claim 10, wherein the penalty for the noncompliance is at least one of: a financial penalty, a service penalty, or a regulatory penalty.

18. The computing system of claim 10, wherein the one or more processors are further configured to: prior to depositing the funds due into the account of the user, transfer the funds due from the experience provider to an account associated with the computing system, wherein the funds due are deposited into the account of the user from a distribution account of the computing system.

19. One or more non-transitory computer-readable media storing instructions thereon that, when executed by one or more processors, cause the one or more processors to: detect, via a security tool, a noncompliance event based on content accessed by one or more user devices and served by an experience provider that is noncompliant with a data sharing preference of the one or more user devices; provide, using one or more APIs based on detecting the noncompliance event, an alert on a graphical user interface (GUI) of a client application, wherein the alert comprises one or more options associated with the detected noncompliance event; and remediate, via the security tool using the one or more APIs, the detected noncompliance event according to a remediation selection of the one or more options based on executing an API call with the experience provider by: transmitting a warning to the experience provider regarding a penalty for the noncompliance; receiving, from the experience provider, a data structure comprising a tabulation of funds due to resolve the penalty; verifying the tabulation of funds due; and depositing the funds due into an account of a user of the one or more user devices to resolve the penalty.

20. The non-transitory computer-readable media of claim 19, wherein the instructions further cause the one or more processors to: prior to depositing the funds due into the account of the user, transfer the funds due from the experience provider to an account associated with the computing system, wherein the funds due are deposited into the account of the user from a distribution account of the computing system.
