

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285565

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

LEE; Jaesung et al.

HEAD MOUNTED DEVICE INCLUDING MULTIPLE DISPLAY PANELS AND OPERATING METHOD THEREOF

Abstract

A head mounted device may include: a first display panel having a fixed location; a second display panel having a fixed location; a first display driving circuit configured to drive the first display panel; a second display driving circuit configured to drive the second display panel; and at least one processor comprising processing circuitry. At least one processor may be configured to: provide screen input data to the first display driving circuit and the second display driving circuit; acquire a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel, on the basis of the provided screen input data; correct at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit, on the basis of the acquired deviation; and modify an emission timing of at least one of the first display panel or the second display panel, based on the modification of at least a portion of the screen input data.

Inventors: LEE; Jaesung (Suwon-si, KR), KIM; Seungryeol (Suwon-si, KR), BAE; Jongkon (Suwon-si, KR), KIM; Kwangtai (Suwon-si, KR), YEOM; Donghyun (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 91195967

Appl. No.: 19/217468

Filed: May 23, 2025

Foreign Application Priority Data

KR 10-2022-0158723

Nov. 23, 2022

KR 10-2022-0183033

Dec. 23, 2022

Related U.S. Application Data

Publication Classification

Int. Cl.: G09G3/00 (20060101)

U.S. Cl.:

CPC G09G3/001 (20130101); G09G2310/08 (20130101); G09G2340/045 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of International Application No. PCT/KR2023/016412 designating the United States, filed on Oct. 20, 2023, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application Nos. 10-2022-0158723, filed on Nov. 23, 2022, and 10-2022-0183033, filed on Dec. 23, 2022, in the Korean Intellectual Property Office, the disclosures of each of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

[0002] The disclosure relates to a technology related to a head mounted device including a plurality of display panels and a method of operating the same.

Description of Related Art

[0003] With the advancement of electronic device technology, various types of electronic devices such as mobile communication terminals, personal digital assistants (PDAs), electronic notebooks, smart phones, tablet personal computers (PCs), and wearable devices are widely used. For example, an electronic device may provide virtual reality (VR) allowing users to have a realistic experience in a computer-generated virtual world, augmented reality (AR) adding virtual information (or objects) to the real world, and mixed reality (MR) combining VR and AR.

[0004] The above information is presented as related art only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

[0005] A head mounted device according to an example embodiment may include: a first display panel having a fixed position, a second display panel having a fixed position, a first display driving circuit configured to drive the first display panel, a second display driving circuit configured to drive the second display panel, and at least one processor comprising processing circuitry. At least one processor, individually and/or collectively, may be configured to cause the head mounted device to: provide screen input data to the first display driving circuit and the second display driving circuit; based on the provided screen input data, obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, change a light emitting timing of at least one of the first display panel or the second display panel.

[0006] A method of operating a head mounted device according to an example embodiment of the disclosure may include: providing screen input data to a first display driving circuit configured to drive a first display panel and a second display driving circuit configured to drive a second display

panel; obtaining a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modifying at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, changing a light emitting timing of at least one of the first display panel or the second display panel.

[0007] A non-transitory computer-readable storage medium storing at least one program according to an example embodiment of the disclosure may include, instructions, that when executed by at least one processor, comprising processing circuitry, individually and/or collectively, of an electronic device, may cause the electronic device to: based on execution of an application, provide screen input data to a first display driving circuit configured to drive a first display panel and a second display driving circuit configured to drive a second display panel; obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, change a light emitting timing of at least one of the first display panel or the second display panel.

[0008] A head mounted device according to an example embodiment may include: a first display panel having a fixed position, a second display panel having a fixed position, a first display driving circuit configured to drive the first display panel, a second display driving circuit configured to drive the second display panel, and at least one processor comprising processing circuitry. At least one processor, individually and/or collectively, may be configured to cause the head mounted device to: provide screen input data to the first display driving circuit and the second display driving circuit; based on the provided screen input data, obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, change a driving timing of at least one of the first display driving circuit or the second display driving circuit.

[0009] A method of operating a head mounted device according to an example embodiment of the disclosure may include: providing screen input data to a first display driving circuit configured to drive a first display panel and a second display driving circuit configured to drive a second display panel; obtaining a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modifying at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, changing a driving timing of at least one of the first display driving circuit or the second display driving circuit.

[0010] A non-transitory computer-readable storage medium storing at least one program according to an example embodiment of the disclosure may include instructions, that when executed by at least one processor, comprising processing circuitry, individually and/or collectively, of an electronic device, cause the electronic device to: based on execution of an application, provide screen input data to a first display driving circuit configured to drive a first display panel and a second display driving circuit configured to drive a second display panel; obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, change a driving timing of at least one of the first display driving circuit or the second display driving circuit.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

[0012] FIG. 1 is a block diagram illustrating an example electronic device in a network environment according to various embodiments;

[0013] FIG. 2 is a perspective view illustrating internal components of an example wearable electronic device according to various embodiments;

[0014] FIGS. 3A and 3B are perspective views illustrating the front and rear surfaces of an example wearable electronic device according to various embodiments;

[0015] FIG. 4 is a block diagram illustrating an example configuration of a display module according to various embodiments;

[0016] FIG. 5 is a block diagram illustrating an example configuration of a head mounted device according to various embodiments;

[0017] FIGS. 6A, 6B, and 6C are block diagrams illustrating an example configuration of a head mounted device according to various embodiments;

[0018] FIGS. 7A, 7B, and 7C are block diagrams illustrating an example configuration of a head mounted device according to various embodiments;

[0019] FIG. 8 is a diagram illustrating an example head mounted device displaying a screen according to various embodiments;

[0020] FIG. 9A is a diagram illustrating binocular disparities between the left and right eyes according to depths according to various embodiments;

[0021] FIG. 9B is a diagram illustrating depth perception according to image acquisition of the left and right eyes according to various embodiments;

[0022] FIG. 10A is a diagram illustrating a positional deviation on a plane between a screen displayed on a first display panel and a screen displayed on a second display panel according to various embodiments;

[0023] FIG. 10B is a diagram illustrating an example screen displayed on a second display panel, which is moved in parallel on a plane according to various embodiments;

[0024] FIG. 10C is a diagram illustrating an example tearing screen based on parallel movement of a screen displayed on a second display panel according to various embodiments;

[0025] FIG. 11A is a timing diagram illustrating a timing of a vertical synchronization signal or screen input data for at least one of a first display driving circuit or a second display driving circuit based on parallel movement of a screen according to various embodiments;

[0026] FIG. 11B is a timing diagram illustrating a timing of a display period for at least one of a first display driving circuit or a second display driving circuit based on parallel movement of a screen according to various embodiments;

[0027] FIG. 11C is a timing diagram illustrating an example of changing light emitting timings of a first display panel and a second display panel based on parallel movement of a screen according to various embodiments;

[0028] FIG. 12A is a diagram illustrating a size deviation between a screen displayed on a first display panel and a screen displayed on a second display panel according to various embodiments;

[0029] FIG. 12B is a diagram illustrating enlargement or reduction of a screen displayed on a second display panel according to various embodiments;

[0030] FIG. 12C is a diagram illustrating an example tearing screen based on enlargement or reduction of a screen displayed on a second display panel according to various embodiments;

[0031] FIG. 13A is a timing diagram illustrating a timing of a vertical synchronization signal or

screen input data for at least one of a first display driving circuit or a second display driving circuit based on enlargement or reduction of a screen according to various embodiments;

[0032] FIG. **13B** is a timing diagram illustrating an example of changing a light emitting timing of a first display panel or a second display panel based on enlargement or reduction of a screen according to various embodiments;

[0033] FIG. **14A** is a diagram illustrating a rotational deviation between a screen displayed on a first display panel and a screen displayed on a second display panel according to various embodiments;

[0034] FIG. **14B** is a diagram illustrating rotation of a screen displayed on a second display panel according to various embodiments;

[0035] FIG. **15A** is a diagram illustrating a rotational deviation between a screen displayed on a first display panel and a screen displayed on a second display panel according to various embodiments;

[0036] FIG. **15B** is a diagram illustrating an example of perspective transformation according to various embodiments;

[0037] FIG. **16** is a diagram illustrating a positional deviation, a size deviation, and a rotational deviation between a screen displayed on a first display panel and a screen displayed on a second display panel according to various embodiments;

[0038] FIG. **17** is a diagram illustrating sub-pixel rendering based on arrangement of sub-pixels according to various embodiments; and

[0039] FIG. **18** is a flowchart illustrating an example method of operating a head mounted device according to various embodiments.

DETAILED DESCRIPTION

[0040] FIG. **1** is a block diagram illustrating an example electronic device **101** in a network environment **100** according to various embodiments.

[0041] Referring to FIG. **1**, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In various embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In various embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

[0042] The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in

conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**. Thus, the processor **120** may include various processing circuitry and/or multiple processors. For example, as used herein, including the claims, the term “processor” may include various processing circuitry, including at least one processor, wherein one or more of at least one processor, individually and/or collectively in a distributed manner, may be configured to perform various functions described herein. As used herein, when “a processor”, “at least one processor”, and “one or more processors” are described as being configured to perform numerous functions, these terms cover situations, for example and without limitation, in which one processor performs some of recited functions and another processor(s) performs other of recited functions, and also situations in which a single processor may perform all recited functions. Additionally, the at least one processor may include a combination of processors performing various of the recited/disclosed functions, e.g., in a distributed manner. At least one processor may execute program instructions to achieve or perform various functions.

[0043] The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

[0044] The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

[0045] The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

[0046] The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

[0047] The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may

be implemented as separate from, or as part of the speaker.

[0048] The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the strength of force incurred by the touch.

[0049] The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

[0050] The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

[0051] The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

[0052] A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

[0053] The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

[0054] The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

[0055] The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

[0056] The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

[0057] The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular

communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

[0058] The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

[0059] The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

[0060] According to an embodiment, the antenna module **197** may form an mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

[0061] At least some of the above-described components may be coupled mutually and

communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

[0062] According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In an embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

[0063] FIG. **2** is a perspective view illustrating internal components of an example wearable electronic device **200** according to various embodiments.

[0064] Referring to FIG. **2**, the wearable electronic device **200** according to an embodiment of the disclosure may include at least one of a light output module (e.g., including a lens) **211**, a display member (e.g., including a waveguide) **201**, and a camera module (e.g., including a camera) **250**.

[0065] According to an embodiment of the disclosure, the light output module **211** may include a light source capable of outputting an image, and a lens that guides the image to the display member **201**. According to an embodiment of the disclosure, the light output module **211** may include at least one of a liquid crystal display (LCD), a digital mirror device (DMD), a liquid crystal on silicon (LCoS), a light emitting diode (LED) on silicon (LEDoS), an organic light emitting diode (OLED), or a micro LED.

[0066] According to an embodiment of the disclosure, the display member **201** may include an optical waveguide (e.g., a waveguide). According to an embodiment of the disclosure, an output image of the light output module **211** incident on one end of the optical waveguide may be propagated through the optical waveguide and provided to a user. According to an embodiment of the disclosure, the optical waveguide may include at least one of a diffractive element (e.g., a diffractive optical element (DOE) or a holographic optical element (HOE)) or a reflective element (e.g., a reflective mirror). For example, the optical waveguide may guide the output image of the light output module **211** to the user's eye using at least one diffractive element or reflective element.

[0067] According to an embodiment of the disclosure, the camera module **250** may capture a still image and/or a video. According to an embodiment, the camera module **250** may be disposed within a lens frame and disposed around the display member **201**.

[0068] According to an embodiment of the disclosure, a first camera module **251** may capture and/or recognize the trajectory of the user's eye (e.g., pupil or iris) or gaze. According to an

embodiment of the disclosure, the first camera module **251** may periodically or aperiodically transmit information (e.g., trajectory information) related to the trajectory of the user's eye or gaze to a processor (e.g., the processor **120** of FIG. **1**).

[0069] According to an embodiment of the disclosure, a second camera module **253** may capture an external image.

[0070] According to an embodiment of the disclosure, a third camera module **255** may be used for hand detection and tracking, and user gesture (e.g., hand movement) recognition. The third camera module **255** according to an embodiment of the disclosure may be used for 3 degrees of freedom (3DoF) or 6DoF head tracking, location (space or environment) recognition, and/or movement recognition. The second camera module **253** may also be used for hand detection and tracking, and user gesture recognition according to an embodiment of the disclosure. According to an embodiment of the disclosure, at least one of the first camera module **251** to the third camera module **255** may be replaced with a sensor module (e.g., a LiDAR sensor). For example, the sensor module may include at least one of a vertical cavity surface emitting laser (VCSEL), an IR sensor, and/or a photodiode.

[0071] FIGS. **3A** and **3B** are perspective views illustrating the front and rear surfaces of an example wearable electronic device **300** according to various embodiments.

[0072] Referring to FIGS. **3A** and **3B**, in an embodiment, camera modules **311**, **312**, **313**, **314**, **315**, and **316** and/or a depth sensor **317** may be disposed on a first surface **310** of a housing to obtain information related to a surrounding environment of the wearable electronic device **300**.

[0073] In an embodiment, the camera modules **311** and **312** may obtain an image related to the surrounding environment of the wearable electronic device **300**.

[0074] In an embodiment, the camera modules **313**, **314**, **315**, and **316** may obtain an image, while the wearable electronic device **300** is worn by the user. The camera modules **313**, **314**, **315**, and **316** may be used for hand detection and tracking, and user gesture (e.g., hand movement) recognition. The camera modules **313**, **314**, **315**, and **316** may be used for 3DoF or 6DoF head tracking, location (space or environment) recognition, and/or movement recognition. In an embodiment, the camera modules **311** and **312** may also be used for hand detection and tracking, and user gesture recognition.

[0075] In an embodiment, the depth sensor **317** may be configured to transmit a signal and receive a signal reflected from an object, and used for the purpose of identifying a distance to an object, such as time of flight (TOF). Alternatively or additionally to the depth sensor **217**, the camera modules **313**, **314**, **315**, and **316** may identify a distance to an object.

[0076] According to an embodiment, face recognition camera modules **325** and **326** and/or a display **321** (and/or a lens) may be disposed on a second surface **320** of the housing.

[0077] In an embodiment, the face recognition camera modules **325** and **326** adjacent to the display **321** may be used for the purpose of recognizing the user's face or may recognize and/or track both eyes of the user.

[0078] In an embodiment, the display **321** (and/or the lens) may be disposed on the second surface **320** of the wearable electronic device **300**. In an embodiment, the wearable electronic device **300** may not include the camera modules **315** and **316** among a plurality of camera modules **313**, **314**, **315**, and **316**. Although not shown in FIGS. **3A** and **3B**, the wearable electronic device **300** may further include at least one of the components illustrated in FIG. **2**.

[0079] As described above, according to an embodiment, the wearable electronic device **300** may have a form factor for being worn on the user's head. The wearable electronic device **300** may further include a strap and/or wearing member to be secured on a body part of the user. The wearable electronic device **300** may provide a user experience based on augmented reality, virtual reality, and/or mixed reality, while worn on the user's head.

[0080] FIG. **4** is a block diagram **400** illustrating an example configuration of the display module **160** according to various embodiments.

[0081] Referring to FIG. 4, the display module **160** may include a display **410** and a display driver IC (DDI) **430** for controlling the display. The DDI **430** may include an interface module (e.g., including circuitry) **431**, memory **433** (e.g., buffer memory), an image processing module (e.g., including circuitry) **435**, and/or a mapping module (e.g., including various circuitry and/or executable program instructions) **437**. The DDI **430** may receive image information including, for example, screen input data or an image control signal corresponding to a command for controlling the screen input data, from another component of the electronic device **101** through the interface module **431**. For example, according to an embodiment, the image information may be received from the processor **120** (e.g., the main processor **121** (e.g., an AP) or the auxiliary processor **123** (e.g., a graphic processing unit) that operates independently of the function of the main processor **121**). The DDI **430** may communicate with a touch circuit **450** or the sensor module **176** through the interface module **431**. In addition, the DDI **430** may store at least a portion of the received image information in the memory **433**, for example, in units of frames. The image processing module **435** may perform preprocessing or postprocessing (e.g., resolution, brightness, or size adjustment) on at least a portion of the screen input data based on at least the characteristics of the screen input data or the characteristics of the display **410**, for example. The mapping module **437** may generate a voltage value or current value corresponding to the screen input data that has been preprocessed or postprocessed through the image processing module **435**. According to an embodiment, the generation of the voltage value or current value may be performed based at least in part on the properties (e.g., arrangement (RGB stripe or pentile structure) of the pixels, or the size of each of sub-pixels) of pixels of the display **410**. At least some of the pixels of the display **410** may be driven based at least in part on the voltage value or current value, so that visual information (e.g., text, an image, or an icon) corresponding to the screen input data may be displayed through the display **410**.

[0082] According to an embodiment, the display module **160** may further include the touch circuit **450**. The touch circuit **450** may include a touch sensor **451** and a touch sensor IC **453** for controlling the same. The touch sensor IC **453** may control the touch sensor **451** to detect, for example, a touch input or hovering input at a specific position of the display **410**. For example, the touch sensor IC **453** may detect the touch input or hovering input by measuring a change in a signal (e.g., voltage, light intensity, resistance, or charge) at the specific position of the display **410**. The touch sensor IC **453** may provide information (e.g., position, area, pressure, or time) about the detected touch input or hovering input to the processor **120**. According to an embodiment, at least a portion (e.g., the touch sensor IC **453**) of the touch circuit **450** may be included as a portion of the DDI **430** or the display **410**, or as a portion of another component (e.g., the auxiliary processor **123**) disposed outside the display module **160**.

[0083] According to an embodiment, the display module **160** may further include at least one sensor (e.g., a fingerprint sensor, an iris sensor, a pressure sensor, or an illuminance sensor) of the sensor module **476**, or a control circuit for the at least one sensor. In this case, the at least one sensor or the control circuit for it may be embedded in a portion (e.g., the display **410** or the DDI **430**) of the display module **160** or a portion of the touch circuit **450**. For example, when the sensor module **476** embedded in the display module **160** includes a biometric sensor (e.g., a fingerprint sensor), the biometric sensor may obtain biometric information (e.g., a fingerprint image) associated with a touch input through a partial area of the display **410**. In another example, when the sensor module **476** embedded in the display module **160** includes a pressure sensor, the pressure sensor may obtain pressure information associated with a touch input through a partial area or the entire area of the display **410**. According to an embodiment, the touch sensor **451** or the sensor module **476** may be disposed between pixels of a pixel layer of the display **410**, or above or below the pixel layer. According to an embodiment, the sensor module **176** may also be disposed in the display **410** (e.g., a mechanism/structure supporting the display **410**).

[0084] FIG. 5 is a block diagram illustrating an example configuration of a head mounted device

500 according to various embodiments.

[0085] Referring to FIG. 5, the head mounted device **500**, (e.g., the electronic device **101** of FIG. 1, the wearable electronic device **200** of FIG. 2, or the wearable electronic device **300** of FIG. 3A) according to an embodiment may include a processor (e.g., including processing circuitry) **510**, a first display driving circuit **520**, (e.g., the DDI **430** of FIG. 4), a second display driving circuit **530**, (e.g., the DDI **430** of FIG. 4), a first display panel **540**, (e.g., the display **321** of FIG. 3B or the display **410** of FIG. 4), and/or a second display panel **550** (e.g., the display **321** of FIG. 3B or the display **410** of FIG. 4).

[0086] In an embodiment, the head mounted device **500** may be a binocular stereo vision type that individually drives the first display panel **540** and the second display panel **550**.

[0087] In an embodiment, the processor **510** may include various processing circuitry, including a graphics processing unit that generates image data. Screen input data may define a screen output to the first display panel **540** and/or the second display panel **550**. In an embodiment, the graphics processing unit included in the processor **510** may provide the screen input data to an AP included in the processor **510**. The description of the processor **120** above applies equally to the processor **510**.

[0088] In an embodiment, the processor **510** may transmit screen input data for setting a data voltage to the first display driving circuit **520** and/or the second display driving circuit **530**. In an embodiment, two processors **510** may be configured to transmit the screen input data to the first display driving circuit **520** and the second display driving circuit **530**, respectively, or a single processor **510** may be configured to transmit the screen input data to each of the first display driving circuit **520** and the second display driving circuit **530**.

[0089] In an embodiment, the processor **510** may transmit the screen input data to the first display driving circuit **520** and the second display driving circuit **530** with the same horizontal synchronization signal Hsync, the same vertical synchronization signal Vsync, and/or the same data reception timing (e.g., a vertical back porch VBP, a vertical front porch VFP, a horizontal back porch HBP, or a horizontal front porch HFP).

[0090] In an embodiment, the processor **510** may transmit commands related to data display timings (e.g., vertical back porches VBP, vertical front porches VFP, horizontal back porches HBP, or horizontal front porches HFP) of the first display driving circuit **520** and the second display driving circuit **530** to the first display driving circuit **520** and the second display driving circuit **530**, respectively.

[0091] In an embodiment, the first display driving circuit **520** and the second display driving circuit **530** may output images to the first display panel **540** and the second display panel **550** based on the commands related to the data display timings received from the processor. In an embodiment, when data reception timings are different from the data display timings, the first display driving circuit **520** and the second display driving circuit **530** may store the screen input data in an internal buffer (e.g., the memory **433** of FIG. 4), and output images to the first display panel **540** and the second display panel **550** based on the data display timings.

[0092] In an embodiment, the processor **510** may provide screen input data in each frame to the first display driving circuit **520** and/or the second display driving circuit **530** through an interface. The length of one frame may be determined according to a driving frequency of the first display driving circuit **520** and/or the second display driving circuit **530**. The driving frequency may be a scan rate of the first display driving circuit **520** and/or the second display driving circuit **530**. The driving frequency and the length of one frame may be inversely proportional. For example, when the first display driving circuit **520** and/or the second display driving circuit **530** operates at a driving frequency of about 60 Hz, the length of one frame may be about 16.67 ms. In another example, when the first display driving circuit **520** and/or the second display driving circuit **530** operates at a driving frequency of about 120 Hz, the length of one frame may be about 8.33 ms.

[0093] In an embodiment, the first display driving circuit **520** and the second display driving circuit

530 may drive the first display panel **540** and the second display panel **550**, respectively, and may be implemented as a DDI or a timing controller (TCON). In an embodiment, the first display driving circuit **520** and the second display driving circuit **530** control the overall operation of the first display panel **540** or the second display panel **550**, and control input/output of data packets having display data (e.g., data displayed through the display) according to a clock CLK. The data packets may include display data, a horizontal synchronization signal Hsync, a vertical synchronization signal Vsync, and/or a data enable signal DE. For example, the horizontal synchronization signal Hsync is a signal indicating a time taken to display one horizontal line of a screen, and the vertical synchronization signal Vsync is a signal indicating a time taken to display one frame of the screen. In addition, the data enable signal is a signal indicating a period during which a voltage (data voltage) is supplied to pixels defined on the first display panel **540** or the second display panel **550**.

[0094] In an embodiment, the first display driving circuit **520** and the second display driving circuit **530** may set data voltages to be scanned on the first display panel **540** and the second display panel **550**, respectively, based on the screen input data. In an embodiment, the first display panel **540** and/or the second display panel **550** may display a screen according to the scanned data voltage.

[0095] In an embodiment, the processor **510** may modify at least a portion of the screen input data input to the first display driving circuit **520** and the second display driving circuit **530**, and change a driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** based on the modification of the screen input data. In an embodiment, the processor **510** may change the driving timing based on an effective display area of the first display panel **540** and/or the second display panel **550**, which is changed based on the modification of the screen input data.

[0096] In an embodiment, the processor **510** may change a light emitting timing of at least one of the first display panel **540** or the second display panel **550**, based on the modification of the screen input data input to the first display driving circuit **520** and the second display driving circuit **530**. In an embodiment, when an OLED or OLEDoS is applied to the first display panel **540** or the second display panel **550**, the processor **510** may change a light emitting timing included in a light emission signal (e.g., an EM signal) based on the effective display area of the first display panel **540** and/or the second display panel **550**, which is changed based on the modification of the screen input data.

[0097] In an embodiment, the first display panel **540** and the second display panel **550** may have fixed positions on one side and the other side of the head mounted device **500**, respectively. In an embodiment, the first display panel **540** may be located to correspond to the left eye of the user wearing the head mounted device **500**, and the second display panel **550** may be located to correspond to the right eye of the user wearing the head mounted device **500**.

[0098] The head mounted device **500** according to an embodiment may obtain a positional deviation, size deviation, and/or rotational deviation between a screen displayed through the first display panel **540** and a screen displayed through the second display panel **550**.

[0099] In an embodiment, the head mounted device **500** may receive the deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** from an external device (e.g., a detection device), while displaying the screens on the first display panel **540** and the second display panel **550**.

[0100] In an embodiment, the head mounted device **500** may capture images of the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**, or images reflected from the respective screens through a camera (e.g., the first camera module **251** of FIG. 2), and identify the deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** from the captured images. In an embodiment, the head mounted device **500** may store the identified deviation between the screen displayed through the first display panel **540** and the screen displayed through

the second display panel **550** in memory (e.g., memory (not shown) connected to the processor **510** or memory (not shown) connected to the first display driving circuit **520** or the second display driving circuit **530**), for use.

[0101] In an embodiment, the head mounted device **500** may adjust (e.g., move, enlarge/reduce, or rotate) the screen displayed through the first display panel **540** and/or the screen displayed through the second display panel **550**, based on a user input. In an embodiment, the head mounted device **500** may obtain the deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**, based on a user input for adjusting the screen displayed through the first display panel **540** and/or the screen displayed through the second display panel **550**.

[0102] In an embodiment, the head mounted device **500** may obtain the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**, or images reflected from the screens, through a separate sensor (not shown), and obtain the deviation in real time based on the obtained screens or images.

[0103] FIGS. **6A**, **6B**, and **6C** are block diagrams illustrating example configurations of the head mounted device **500** according to various embodiments.

[0104] Referring to FIGS. **6A**, **6B**, and **6C**, the first display driving circuit **520** and/or the second display driving circuit **530** according to an embodiment may operate in a first mode (e.g., command mode) in which it receives screen input data Data I/F and a command from the outside and drives the first display panel **540** and/or the second display panel **550**.

[0105] In an embodiment, the first display driving circuit **520** and/or the second display driving circuit **530** may include a frame buffer (not shown). The frame buffer (not shown) may store the screen input data Data I/F during one frame. The first display driving circuit **520** and/or the second display driving circuit **530** according to an embodiment may store the screen input data Data I/F transmitted by the processor **510** in the frame buffer (not shown). The first display driving circuit **520** and/or the second display driving circuit **530** according to an embodiment may output a screen to the first display panel **540** and/or the second display panel **550** by scanning the screen input data Data I/F stored in the frame buffer (not shown) during one frame.

[0106] In an embodiment, the first display driving circuit **520** and/or the second display driving circuit **530** may generate a tearing effect (TE) signal that reduces a TE. In an embodiment, the TE signal may be a signal that controls the timing of supplying a data voltage to the first display panel **540** and/or the second display panel **550**. For example, the TE may be a phenomenon in which an image of a current frame is scanned while an image of a previous frame remains.

[0107] In an embodiment, the first display driving circuit **520** and/or the second display driving circuit **530** may transmit the generated TE signal to the processor **510**, and the processor **510** may set a timing of the screen input data Data I/F based on the received TE signal and transmit the screen input data Data I/F to the first display driving circuit **520** and/or the second display driving circuit **530** based on the set timing, thereby reducing the TE.

[0108] In an embodiment, the processor **510** and the first display driving circuit **520** and/or the second display driving circuit **530** may be connected through an interface. For example, the processor **510** and the first display driving circuit **520** and/or the second display driving circuit **530** may be connected through a designated interface (e.g., mobile industry processor interface (MIPI)). The interface may transmit a command. The processor **510** may transmit the screen input data Data I/F to the first display driving circuit **520** and/or the second display driving circuit **530** through the interface. The interface is not limited to the above example, and various interfaces may be formed, such as a mobile display digital interface (MDDI), a serial peripheral interface (SPI), an inter-integrated circuit (I2C), an improved inter-integrated circuit (I3C), or a compact display port (CDP).

[0109] In an embodiment, as illustrated in FIG. **6A**, a single processor **510** may be configured and receive TE signals from the first display driving circuit **520** and the second display driving circuit

530, respectively. The processor **510** may set timings of screen input data Data I/F based on the TE signals received from the first display driving circuit **520** and the second display driving circuit **530**, respectively, and transmit the screen input data Data I/F to the first display driving circuit **520** and the second display driving circuit **530**, respectively, based on the set timings. In an embodiment, when driving timings of the first display driving circuit **520** and the second display driving circuit **530** are changed, the first display driving circuit **520** and the second display driving circuit **530** may separate the timings of their generated TE signals, and the processor **510** may separate timings of the screen input data Data I/F input to the first display driving circuit **520** and the second display driving circuit **530** based on the TE signals generated by the first display driving circuit **520** and the second display driving circuit **530**, respectively.

[0110] In an embodiment, as illustrated in FIG. **6B**, a single processor **510** may be configured and receive a TE signal from either the first display driving circuit **520** or the second display driving circuit **530**. The processor **510** may set timings of screen input data Data I/F based on the received TE signal, and transmit the screen input data Data I/F to the first display driving circuit **520** and the second display driving circuit **530**, respectively, based on the set timings. In an embodiment, the first display driving circuit **520** and the second display driving circuit **530** may synchronize the driving timings of the first display driving circuit **520** and the second display driving circuit **530** based on a synchronization signal sync. In an embodiment, when the driving timings of the first display driving circuit **520** and the second display driving circuit **530** are changed, the timing of a display period may be changed using the internal frame buffer of the first display driving circuit **520** and/or the second display driving circuit **530**.

[0111] In an embodiment, as illustrated in FIG. **6C**, the processor **510** may be divided into a first processor **513** and a second processor **515**, the first processor **513** may receive a TE signal from the first display driving circuit **520**, and the second processor **515** may receive a TE signal from the second display driving circuit **530**. In an embodiment, the first processor **513** and the second processor **515** may set timings of screen input data Data I/F based on the received TE signals, and transmit the screen input data Data I/F to the first display driving circuit **520** and the second display driving circuit **530**, respectively, based on the set timings. In an embodiment, the first display driving circuit **520** and the second display driving circuit **530** may synchronize the driving timings of the first display driving circuit **520** and the second display driving circuit **530** based on a synchronization signal sync. In an embodiment, when the driving timings of the first display driving circuit **520** and the second display driving circuit **530** are changed, the first display driving circuit **520** and the second display driving circuit **530** may separate the timings of their generated TE signals, and the processor **510** may separate the timings of the screen input data Data I/F input to the first display driving circuit **520** and the second display driving circuit **530**, based on the TE signals generated by the first display driving circuit **520** and the second display driving circuit **530**, respectively. In an embodiment, the first display driving circuit **520** and/or the second display driving circuit **530** may change the timing of a display period using the internal frame buffer.

[0112] FIGS. **7A**, **7B**, and **7C** are block diagrams illustrating an example configuration of the head mounted device **500** according to various embodiments.

[0113] Referring to FIGS. **7A**, **7B**, and **7C**, the first display driving circuit **520** and/or the second display driving circuit **530** according to an embodiment may not be provided with the frame buffer, and operate in a second mode (e.g., video mode) in which it drives the first display panel **540** and/or the second display panel **550** based on an operation timing set by the processor **510**.

[0114] In an embodiment, the processor **510** may transmit screen input data Data I/F and a vertical synchronization signal Vsync to the first display driving circuit **520** and/or the second display driving circuit **530** through the interface. The first display driving circuit **520** and the second display driving circuit **530** may output horizontal synchronization signals, vertical synchronization signals, data enable signals, display data, and/or clocks CLK to the first display panel **540** and the second display panel **550**, respectively.

[0123] For example, screens displayed at 6000 ppi on the first display panel **540** and the second display panel **550** may be magnified to 58 to 97 ppi and input to the user's eyes depending on the viewing distance. Accordingly, a mechanical deviation or assembly deviation of the first display panel **540** and the second display panel **550** fixed to the head mounted device **500** may be magnified 60 to 100 times on a screen input to the user as perceived by the user.

[0124] Referring to FIGS. **9A** and **9B**, the user may recognize the depth of an object based on the positions of the object input to the left and right eyes. For example, the user may recognize the depth (disparity distance) of an object based on the difference between an image of the object input to the left eye and an image of the object input to the right eye. For example, when the difference between the positions of the object input to the left and right eyes is relatively small (e.g., Far in (a) and (b) of FIG. **9A**), the user may recognize the object as relatively far away, and when the difference between the positions of the object is relatively large (e.g., Near in (a) and (b) of FIG. **9A**), the user may recognize the object as relatively close.

[0125] In an embodiment, when there is a deviation between the positions of an object input to the left and right eyes of the user, a sense of depth different from that intended by the head mounted device **500** may be perceived. In an embodiment, as illustrated in FIG. **9B**, when there is a deviation between the positions of an object input to the left and right eyes, a sense of depth different from that intended for the object may be perceived. For example, when the deviation between the positions of the object input to the left or right eye occurs in a direction in which they are close to each other (-2 or -1), the object may be perceived as having a relatively small depth. On the contrary, when the deviation between the positions of the object input to the left or right eye occurs in a direction in which they are away from each other (1 or 2), the object may be perceived as having a relatively large depth.

[0126] Further, this may cause fatigue and operational errors due to a continued error between a displayed image of the head mounted device **500** and an image recognized by the user.

[0127] Therefore, when a mechanical deviation occurs in the head mounted device **500** in which the first display panel **540** and the second display panel **550** are completely assembled, a deviation in an image recognized by the user may be resolved by changing a screen displayed on the first display panel **540** and/or the second display panel **550** without reassembly. Further, service cost may be reduced by compensating for a deviation caused by mechanical deformation that occurs during use of the head mounted device **500**.

[0128] FIG. **10A** is a diagram illustrating example positional deviation on a plane between a screen displayed on the first display panel **540** and a screen displayed on the second display panel **550** according to various embodiments. FIG. **10B** is a diagram illustrating a screen displayed on the second display panel **550**, which is moved in parallel on a plane according to various embodiments. FIG. **10C** is a diagram illustrating an example tearing screen based on parallel movement of a screen displayed on the second display panel **550** according to various embodiments.

[0129] Referring to FIGS. **10A** and **10B**, the head mounted device **500** according to an embodiment may obtain a positional deviation on a plane between a screen displayed through the first display panel **540** and a screen displayed through the second display panel **550**. In an embodiment, the head mounted device **500** may obtain a positional deviation along the Y axis (e.g., the Y axis of FIG. **6A**) or the Z axis (e.g., the Z axis of FIG. **6A**) between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**.

[0130] In an embodiment, the head mounted device **500** may modify at least a portion of screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**. In an embodiment, the head mounted device **500** may modify the screen input data input to the at least one of the first display driving circuit **520** or the second display driving circuit **530** to move the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550** in parallel, as illustrated in FIG. **10B**. Accordingly, images of an object displayed on the user's eyes may be displayed at the same position. For example, the head

mounted device **500** may modify the screen input data to move a screen displayed through the second display panel **550** located relatively downward (in the Z-axis direction (e.g., the Z-axis direction of FIG. **6A**)) in parallel upward (in the Z-axis direction (e.g., the Z-axis direction of FIG. **6A**)) by k lines.

[0131] In an embodiment, the head mounted device **500** may change the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** based on the modification of the at least portion of the screen input data.

[0132] In an embodiment, the first display driving circuit **520** and the second display driving circuit **530** may scan screens on the first display panel **540** and the second display panel **550** in a specified scanning direction. For example, the specified scanning direction on the first display panel **540** and the second display panel **550** may be from the top to the bottom along the Z axis (e.g., the Z axis of FIG. **6A**), and the first display panel **540** and the second display panel **550** may gradually display (scan) a plurality of scan lines extending in the Y-axis direction (e.g., the Y-axis direction of FIG. **6A**) in the scanning direction.

[0133] For example, since parallel movement of the first display panel **540** or the second display panel **550** in a direction (e.g., the Y-axis direction (e.g., the Y-axis direction of FIG. **6A**)) perpendicular to the scanning direction is movement in the same scan line, there is almost no time difference caused by the scanning operation on the first display panel **540** or the second display panel **550**. However, since k-line parallel movement of the first display panel **540** or the second display panel **550** in a direction (e.g., the Z-axis direction (e.g., the Z-axis direction of FIG. **6A**)) parallel to the scanning direction results in movement of scan lines as illustrated in FIG. **10B**, images of an object may be scanned at different scanning time points to be displayed through the first display panel **540** and the second display panel **550**. In an embodiment, as illustrated in FIG. **10C**, instantaneously different screens may be displayed through the first display panel **540** and the screen displayed through the second display panel **550**, thereby causing a tearing phenomenon in which an image is torn in a kl line.

[0134] FIG. **11A** is a timing diagram illustrating a timing of a vertical synchronization signal V-sync(L) or V-sync(R) or screen input data of at least one of the first display driving circuit **520** or the second display driving circuit **530**, based on parallel movement of a screen according to various embodiments. FIG. **11B** is a timing diagram illustrating a timing of a display period V-act(L) or V-act(R) of at least one of the first display driving circuit **520** or the second display driving circuit **530**, based on parallel movement of a screen according to various embodiments.

[0135] Referring to FIGS. **11A** and **11B**, the head mounted device **500** according to an embodiment may change the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530**, based on parallel movement of the first display panel **540** or the second display panel **550** in the scanning direction.

[0136] In an embodiment, the head mounted device **500** may change the timing of the vertical synchronization signal V-sync(L) or V-sync(R) or screen input data transmitted to at least one of the first display driving circuit **520** or the second display driving circuit **530**, as illustrated in FIG. **11A**. In an embodiment, since the screen input data is output based on a TE signal received from the first display driving circuit **520** or the second display driving circuit **530**, the timing of the screen input data may be changed by changing the timing of the TE signal.

[0137] In an embodiment, the head mounted device **500** may change the timing of the vertical synchronization signal V-sync(L) or V-sync(R) or the timing of the screen input data, based on the number of scan lines moved in the scanning direction on the first display panel **540** or the second display panel **550**. For example, when the screen displayed on the second display panel **550** is moved upward by k lines in the scanning direction, the timing of the vertical synchronization signal Vsync or the timing of the screen input data transmitted to the second display driving circuit **530** may be delayed by a scanning time of k lines.

[0138] In an embodiment, the head mounted device **500** may change the timing of the display

period V-act(L) or V-act(R) of at least one of the first display driving circuit 520 or the second display driving circuit 530 driving the first display panel 540 or the second display panel 550, while maintaining the timing of the vertical synchronization signal V-sync(L) or V-sync(R) or the screen input data, as illustrated in FIG. 11B.

[0139] In an embodiment, the head mounted device 500 may modify a vertical back porch VBP, which is a period in which buffering occurs in the first display driving circuit 520 or the second display driving circuit 530, before the display periods V-act(L) and V-act(R) start within one frame. In an embodiment, the head mounted device 500 may modify a vertical front porch VFP, which is a period in which the processor 510 starts transmitting image data to the first display driving circuit 520 or the second display driving circuit 530 after the display periods V-act(L) and V-act(R) proceed within one frame. The display period V-act(L) or V-act(R) may be a period in which the first display driving circuit 520 or the second display driving circuit 530 scans a data voltage on the first display panel 540 or the second display panel 550 within one frame, and thus a period in which a screen is output.

[0140] In an embodiment, the head mounted device 500 may change the vertical front porch VFP or the vertical back porch VBP based on the number of scan lines moved in the scanning direction on the first display panel 540 or the second display panel 550. For example, when the screen displayed on the second display panel 550 is moved upward by k lines in the scanning direction, the second display driving circuit 530 may change the timing of the display period V-act(L) or V-act(R) of the second display driving circuit 530 so as to increase the vertical back porch VBP by k lines and decrease the vertical front porch VFP by k lines.

[0141] FIG. 11C is a timing diagram illustrating an example of changing light emitting timings of the first display panel 540 and the second display panel 550 based on parallel movement of a screen according to various embodiments.

[0142] Referring to FIG. 11C, the head mounted device 500 (e.g., the processor 510, the first display driving circuit 520, or the second display driving circuit 530 of FIG. 5) according to an embodiment may change the light emitting timings of the first display panel 540 and the second display panel 550, based on modification of at least a portion of screen input data. In an embodiment, the head mounted device 500 may change the light emitting timing of the first display panel 540 or the second display panel 550, while maintaining the timing of a vertical synchronization signal V-sync(L) or V-sync(R) or the screen input data. In an embodiment, the head mounted device 500 may control light emission of the first display panel 540 or the second display panel 550 based on light emission-related signals EM(L) and EM(R). In an embodiment, the head mounted device 500 may control the timings of the light emission-related signals (e.g., EM(L) and EM(R)).

[0143] In an embodiment, the head mounted device 500 may change the timings of the light emission-related signals EM(L) and EM(R) based on the number of scan lines moved in the scanning direction on the first display panel 540 or the second display panel 550. For example, when the screen displayed through the second display panel 550 is moved upward by k lines in the scanning direction, the light emitting timing of the second display driving circuit 530 may be changed such that the second display driving circuit 530 delays the timing of EM(R) by k lines (k line time increase) and advances the timing of EM(R) by k lines (k line time decrease).

[0144] FIG. 12A is a diagram illustrating example size deviation between a screen displayed on the first display panel 540 and a screen displayed on the second display panel 550 according to various embodiments. FIG. 12B is a diagram illustrating example enlarged or reduced screen displayed on the second display panel 550 according to various embodiments. FIG. 12C is a diagram illustrating an example tearing screen caused by enlargement or reduction of a screen displayed on the second display panel 550 according to various embodiments.

[0145] Referring to FIGS. 12A and 12B, the head mounted device 500 according to an embodiment may obtain a size deviation based on a positional deviation in a depth direction between a screen

displayed through the first display panel **540** and a screen displayed through the second display panel **550**.

[0146] In an embodiment, when a depth difference occurs in the X-axis direction (e.g., the X-axis direction of FIG. 6A) between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**, the sizes of the screens may be different. Since the human eye is not capable of performing an image enlargement/reduction operation unlike a positional deviation in a plane direction, it may not correct the image size deviation. Therefore, when a size deviation occurs in an image, a problem may occur in which images input to the left and right eyes do not overlap.

[0147] In an embodiment, the head mounted device **500** may modify at least a portion of screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**. In an embodiment, the head mounted device **500** may modify screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530** so that a screen displayed through the first display panel **540** or the screen displayed through the second display panel **550** is enlarged or reduced, as illustrated in FIG. 12B. Accordingly, images of an object displayed on the user's eyes may be displayed in substantially the same size.

[0148] In an embodiment, when the sizes of the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** are different from each other, the head mounted device **500** may reduce a relatively large screen to correspond to a relatively small screen.

[0149] In an embodiment, when the sizes of the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** are different from each other, the head mounted device **500** may enlarge the relatively small screen to correspond to the relatively large screen. In an embodiment, when the screen displayed through the first display panel **540** or the second display panel **550** may not be enlarged any further due to the limit of a physical display range, the relatively large screen may be reduced to correspond to the relatively small screen.

[0150] For example, the head mounted device **500** may modify the screen input data to enlarge the screen displayed through the second display panel **550** by k lines upward (in the Z-axis direction (e.g., the Z-axis direction of FIG. 6A)) and by n lines downward (in the Z-axis direction (e.g., the Z-axis direction of FIG. 6A)).

[0151] In an embodiment, the head mounted device **500** may change the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** based on the modification of at least a portion of the screen input data.

[0152] For example, since enlargement or reduction of the first display panel **540** or the second display panel **550** in a direction (e.g., the Y-axis direction (e.g., the Y-axis direction of FIG. 6A)) perpendicular to the scanning direction is movement in the same scan line, there is almost no time difference caused by the scanning operation on the first display panel **540** or the second display panel **550**. However, enlargement or reduction of the first display panel **540** or the second display panel **550** in a direction (e.g., the Z-axis direction (e.g., the Z-axis direction of FIG. 6A)) parallel to the scanning direction as illustrated in FIG. 12B may increase or decrease the number of scan lines, thereby resulting in different scanning time points for images of an object displayed through the first display panel **540** and the second display panel **550**.

[0153] In an embodiment, for an image of the same object, a scanning time of T lines may be taken for the second display panel **550**, while a scanning time of $T-(k+n)$ lines may be taken for the first display panel **540**. In an embodiment, as illustrated in FIG. 12C, as the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** may be instantaneously different due to the difference in scanning time, a tearing phenomenon may occur in which an image is torn in a k.sup.th line and an n.sup.th line.

[0154] FIG. 13A is a timing diagram illustrating a timing of a vertical synchronization signal V-sync(L) or V-sync(R) or screen input data of at least one of the first display driving circuit **520** or

the second display driving circuit **530** based on enlargement or reduction of a screen according to various embodiments.

[0155] Referring to FIG. **13A**, the head mounted device **500** according to an embodiment may change a driving period of at least one of the first display driving circuit **520** or the second display driving circuit **530** based on enlargement or reduction of the first display panel **540** or the second display panel **550** in the scanning direction.

[0156] In an embodiment, the head mounted device **500** may change the driving period of at least one of the first display driving circuit **520** or the second display driving circuit **530** so that a time $T-(k+n)$ for scanning $T-(k+n)$ scan lines in the first display panel **540** matches a time T' for scanning T scan lines in the second display panel **550**. For example, the head mounted device **500** may reduce the driving period of the first display driving circuit **520** to $(T-(k+n))/T$ times the driving period of the second display driving circuit **530**. In an embodiment, the head mounted device **500** may increase the driving period of the second display driving circuit **530** to $(T/(T-(k+n)))$ times the driving period of the first display driving circuit **520**.

[0157] In an embodiment, the head mounted device **500** may change a scanning speed or clock speed of at least one of the first display driving circuit **520** or the second display driving circuit **530**. For example, the head mounted device **500** may increase the scanning speed of the first display driving circuit **520** by reducing the period of the horizontal synchronization signal H-sync of the first display driving circuit **520**, or may decrease the scanning speed of the second display driving circuit **530** by increasing the period of the horizontal synchronization signal H-sync of the second display driving circuit **530**. The vertical synchronization signals V-sync(L) and V-sync(R) may be maintained constant. The head mounted device **500** may increase the clock speed of the first display driving circuit **520** or decrease the clock speed of the second display driving circuit **530**.

[0158] In an embodiment, the head mounted device **500** may change the timing of the display period V-act(L) or V-act(R) of at least one of the first display driving circuit **520** or the second display driving circuit **530**. In an embodiment, the head mounted device **500** may match scanning times for scanning images of an object and match the start and end times of the scanning times of the first display driving circuit **520** and the second display driving circuit **530** by changing the driving period of at least one of the first display driving circuit **520** or the second display driving circuit **530**. In an embodiment, the head mounted device **500** may change the timing of the display period V-act(L) or V-act(R) in which an image is scanned on the first display panel **540** or the second display panel **550** by changing the vertical front porch VFP and/or vertical back porch VBF of the first display driving circuit **520** or the second display driving circuit **530**.

[0159] FIG. **13B** is a timing diagram illustrating an example of changing the light emitting timing of the first display panel **540** or the second display panel **550** based on enlargement or reduction of a screen according to various embodiments.

[0160] Referring to FIG. **13B**, the head mounted device **500** (e.g., the processor **510**, the first display driving circuit **520**, or the second display driving circuit **530** of FIG. **5**) according to an embodiment may change the light emitting timings of the first display panel **540** and the second display panel **550**, based on modification of at least a portion of screen input data. In an embodiment, the head mounted device **500** may change the light emitting timing of the first display panel **540** or the second display panel **550**, while maintaining the timing of the vertical synchronization signal V-sync(L) or V-sync(R) or the screen input data. In an embodiment, the head mounted device **500** may control the light emission of the first display panel **540** or the second display panel **550** based on light emission-related signals.

[0161] In an embodiment, the head mounted device **500** may control the timings of the light emission-related signals (e.g., EM(L) and EM(R)). In an embodiment, the head mounted device **500** may control the light emission of the first display panel **540** or the second display panel **550** so that a light emitting timing at which the image of the object is displayed through the first display

panel **540** coincides with a light emitting timing at which the image of the object is displayed through the second display panel **550**.

[0162] In an embodiment, the head mounted device **500** may change a light emitting period of at least one of the first display driving circuit **520** or the second display driving circuit **530**, so that the time $T-(k+n)$ for scanning $T-(k+n)$ scan lines on the first display panel **540** is equal to the time T' for scanning T scan lines on the second display panel **550**.

[0163] For example, the head mounted device **500** may reduce the light emitting period of the first display driving circuit **520** to $(T-(k+n))/T$ times the light emitting period of the second display driving circuit **530**. In an embodiment, the head mounted device **500** may increase the light emitting period of the second display driving circuit **530** by $(T/(T-(k+n)))$ times the light emitting period of the first display driving circuit **520**.

[0164] FIG. **14A** is a diagram illustrating example rotational deviation between a screen displayed on the first display panel **540** and a screen displayed on the second display panel **550** according to various embodiments. FIG. **14B** is a diagram illustrating example rotation of a screen displayed on the second display panel **550** according to various embodiments.

[0165] Referring to FIGS. **14A** and **14B**, the head mounted device **500** according to an embodiment may obtain a rotational deviation in a roll direction with respect to the X axis (e.g., the X axis of FIG. **6A**) between a screen displayed through the first display panel **540** and a screen displayed through the second display panel **550**.

[0166] The head mounted device **500** according to an embodiment may modify at least a portion of screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, based on the rotational deviation between the screen displayed through the acquired first display panel **540** and the screen displayed through the second display panel **550**. In an embodiment, the head mounted device **500** may modify the screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530** so as to rotate the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550**, as illustrated in FIG. **14A**.

[0167] In an embodiment, as illustrated in FIG. **14B**, based on the rotation of the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550**, an effective display area of the first display panel **540** and an effective display area of the second display panel **550** may be different from each other.

[0168] In an embodiment, the head mounted device **500** may change the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** based on the effective display area L of the first display panel **540** and the effective display area R of the second display panel **550**. In an embodiment, the head mounted device **500** may change the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** based on the heights of the effective display area L of the first display panel **540** and the effective display area R of the second display panel **550** in the scanning direction.

[0169] For example, as illustrated in FIG. **14B**, as the screen displayed through the second display panel **550** is rotated, the height of the effective display area R of the second display panel **550** in the scanning direction may be changed, relative to the height of the effective display area L of the first display panel **540** in the scanning direction. In an embodiment, the head mounted device **500** may match a scanning time T_2 and time point between the top and bottom of the effective display area R of the second display panel **550** in the scanning direction with the a scanning time T_1 and time point of the effective display area L of the first display panel **540**.

[0170] FIG. **15A** is a diagram illustrating example rotational deviation between a screen displayed on the first display panel **540** and a screen displayed on the second display panel **550** according to various embodiments. FIG. **15B** is a diagram illustrating an example of perspective transformation according to various embodiments.

[0171] Referring to FIGS. **15A** and **15B**, the head mounted device **500** according to an embodiment

may obtain a rotational deviation between a screen displayed through the first display panel **540** and a screen displayed through the second display panel **550**, in a pitch direction or a yaw direction with respect to the Y axis (e.g., the Y axis of FIG. **6A**) or the Z axis (e.g., the Z axis of FIG. **6A**). [0172] The head mounted device **500** according to an embodiment may modify at least a portion of screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, based on the obtained rotational deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**. In an embodiment, the head mounted device **500** may modify screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, so that the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550** is perspective-transformed in an opposite direction of the rotational deviation, as illustrated in FIG. **15A**.

[0173] In an embodiment, the head mounted device **500** may modify a source image into a destination image by applying perspective transformation to the source image, as illustrated in FIG. **15B**. The head mounted device **500** may apply perspective transformation in the opposite direction of the rotational deviation based on a rule regarding how an image changes depending on an angle. For example, the perspective transformation may correct the rotational deviation by moving the coordinates of an image on the plane of the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550**, such as specifying a distance (perspective) from an observation point in a three-dimensional space.

[0174] FIG. **16** is a diagram illustrating example positional deviation, size deviation, and rotational deviation between a screen displayed on the first display panel **540** and a screen displayed on the second display panel **550** according to various embodiments.

[0175] Referring to FIG. **16**, the head mounted device **500** may obtain a composite deviation in which at least two of a positional deviation, a size deviation, or a rotational deviation occur in combination between a screen displayed on the first display panel **540** and a screen displayed on the second display panel **550**.

[0176] In an embodiment, when the head mounted device **500** obtains a composite deviation in which at least two of a positional deviation, a size deviation, or a rotational deviation are combined, the head mounted device **500** may modify at least a portion of screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, based on the composite deviation. For example, the head mounted device **500** may modify the screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, so that the screen displayed through the first display panel **540** or the second display panel **550** is moved in parallel, enlarged or reduced, and/or rotated.

[0177] In an embodiment, the head mounted device **500** may change the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530**, based on the modification of the at least portion of the screen input data. In an embodiment, the head mounted device **500** may identify an effective display area displayed through at least one of the first display panel **540** or the second display panel **550**, based on the modification of the at least portion of the screen input data, and change a driving timing based on the identified effective display area.

[0178] In an embodiment, the head mounted device **500** may identify the scanning-direction height of the effective display area of the first display panel **540** or the second display panel **550**, and change the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** based on the identified height.

[0179] For example, an effective display area R displayed through the second display panel **550** may have a height of T2 in the scanning direction, and an effective display area L displayed through the first display panel **540** may have a height of T1 in the scanning direction. The head mounted device **500** may change the driving period of the first display driving circuit **520** or the second display driving circuit **530** based on the height of the effective display area in the scanning

direction (e.g., at a ratio of $T2/T1$ ratio or $T1/T2$). The head mounted device **500** may change the driving timing of the first display driving circuit **520** or the second display driving circuit **530** based on the position of the effective display area in the scanning direction, so as to match the scanning start time and end time of the first display panel **540** or the second display panel **550**. [0180] In an embodiment, the head mounted device **500** may change the luminance and/or sharpness of the first display panel **540** or the second display panel **550** based on the identified effective display area.

[0181] In an embodiment, when the effective display areas L and R of the first display panel **540** and the second display panel **550** are different due to enlargement or reduction of the screen displayed through the first display panel **540** or the second display panel **550** for correction of a size deviation, the head mounted device **500** may change the luminance and/or sharpness of the first display panel **540** or the second display panel **550** based on the effective display areas L and R of the first display panel **540** and the second display panel **550**.

[0182] For example, when the effective display area R of the second display panel **550** is 90% of the effective display area L of the first display panel **540**, the PPD (e.g., 27 ppd) of the second display panel **550** may be reduced to 90% of the PPD (e.g., 27 ppd) of the first display panel **540**. Accordingly, the second display panel **550** may display an image in a smaller number of pixels, which may reduce a luminous intensity per unit solid angle [lm/sr] and cause blurring of an image. In an embodiment, the head mounted device **500** may increase the luminance and/or sharpness of the second display panel **550** to the reciprocal of a ratio between the effective display areas (e.g., a ratio of 100/90), relative to the luminance and/or sharpness of the first display panel **540**.

[0183] FIG. **17** is a diagram illustrating sub-pixel rendering based on arrangement of sub-pixels according to various embodiments.

[0184] Referring to FIG. **17**, the first display driving circuit **520** and/or the second display driving circuit **530** may change screen input data received from the processor **510** into a form transmittable to the first display panel **540** and/or the second display panel **550**, and transmit the changed data (e.g., screen output data) to the display. In an embodiment, the changed data (e.g., output screen data) may be supplied in units of pixels or sub-pixels.

[0185] In an embodiment, the first display panel **540** and the second display panel **550** may include a plurality of pixels including sub-pixels. In an embodiment, a pixel is a structure in which red, green, and blue sub-pixels are arranged adjacent to each other in relation to display of specified colors, and one pixel may include RGB sub-pixels (an RGB stripe layout structure) or RGBG sub-pixels (a pentile layout structure). In an embodiment, the RGBG sub-pixel arrangement structure may be replaced with an RRGB sub-pixel arrangement structure. In an embodiment, a pixel may be replaced with an RGBW sub-pixel arrangement structure.

[0186] In an embodiment, the head mounted device **500** may change the effective display area L of the first display panel **540** or the effective display area R of the second display panel **550** on a pixel basis. In this case, since the same sub-pixel is included in each pixel, sub-pixel rendering may not be required.

[0187] In an embodiment, the head mounted device **500** may change the effective display area L of the first display panel **540** or the effective display area R of the second display panel **550** in units of sub-pixels. In this case, the arrangement of sub-pixels may be different between the effective display area L of the first display panel **540** and the effective display area R of the second display panel **550**, and accordingly, a color representation scheme for an image at the same position from a reference point may be different. In an embodiment, the head mounted device **500** may perform sub-pixel rendering on screen input data based on the arrangement of sub-pixels included in an identified effective display area.

[0188] For example, as illustrated in FIG. **17**, the effective display area L of the first display panel **540** may have a sub-pixel arrangement of RG/BG from the reference point, and the effective display area R of the second display panel **550** may have a sub-pixel arrangement of GR/GB from

the reference point. In an embodiment, the head mounted device **500** may perform sub-pixel rendering on the screen input data, so that the effective display area **L** of the first display panel **540** may have a sub-pixel arrangement of BG/RG from the reference point, and the effective display area **R** of the second display panel **550** may have a sub-pixel arrangement of GB/GR from the reference point.

[0189] FIG. **18** is a flowchart illustrating an example method **1800** of operating a head mounted device according to various embodiments.

[0190] Referring to FIG. **18**, the head mounted device (e.g., the head mounted device **500** or the processor **510** of FIG. **5**) according to an embodiment may provide screen input data to a first display driving circuit (e.g., the first display driving circuit **520** of FIG. **5**) that drives a first display panel (e.g., the first display panel **540** of FIG. **5**) and a second display driving circuit (e.g., the second display driving circuit **530** of FIG. **5**) that drives a second display panel (e.g., the second display panel **550** of FIG. **5**) in operation **1810**. In an embodiment, the first display panel **540** and the second display panel **550** may display their respective screens based on screen output data provided by the first display driving circuit **520** and the second display driving circuit **530** based on the screen input data provided by the processor **510**.

[0191] In an embodiment, the head mounted device **500** may obtain a deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** in operation **1820**. In an embodiment, the head mounted device **500** may execute operation **1820** of obtaining the deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**, based on a specific situation such as an update or booting of the head mounted device **500**, or periodically according to a specified periodicity.

[0192] In an embodiment, as the first display driving circuit **520** and the second display driving circuit **530** may receive the same input data, the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** may be the same, or a positional deviation, a size deviation, and/or a rotational deviation may occur between the screens. According to an embodiment, the head mounted device **500** may obtain a positional deviation, size deviation, and/or rotational deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**.

[0193] In an embodiment, the head mounted device **500** may receive, from an external device (e.g., a detection device), a deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**, while displaying the screens on the first display panel **540** and the second display panel **550**. In an embodiment, the head mounted device **500** may capture the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550**, or an image reflected from each screen, through a camera (e.g., the first camera module **251** of FIG. **2**), and identify the deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** from the captured image or video.

[0194] According to an embodiment, the head mounted device **500** may modify at least a portion of the screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530** based on the obtained deviation in operation **1830**.

[0195] The head mounted device **500** according to an embodiment may identify an effective display area displayed on at least one of the first display panel **540** or the second display panel **550** based on the modification of the at least portion of the screen input data in operation **1840**.

[0196] The head mounted device **500** according to an embodiment may change the luminance and/or sharpness of the first display panel **540** or the second display panel **550** based on the identified effective display area in operation **1850**.

[0197] The head mounted device **500** according to an embodiment may perform sub-pixel rendering on the screen input data based on arrangement of sub-pixels included in the identified

effective display areas of the first display panel **540** and the second display panel **550** in operation **1860**.

[0198] In an embodiment, in operation **1870**, the head mounted device **500** may change at least one of the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** or the light emitting timing of at least one of the first display panel **540** or the second display panel **550**, based on the modification of the at least portion of the screen input data. In an embodiment, the head mounted device **500** may change the driving timing of the first display driving circuit **520** or the second display driving circuit **530**, based on the identified effective display areas of the first display panel **540** and the second display panel **550**.

[0199] In an embodiment, the head mounted device **500** may change the driving timing of the first display driving circuit **520** or the second display driving circuit **530** based on the identified effective display areas of the first display panel **540** and the second display panel **550** in operation **1820**. In operation **1830**, the head mounted device **500** may modify the screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, so that the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550** is moved in parallel. In operation **1870**, the head mounted device **500** may change at least one of the driving timing of at least one of the first display driving circuit **520** or the second display driving circuit **530** or the light emitting timing of at least one of the first display panel **540** or the second display panel **550**, based on the parallel movement of the first display panel **540** or the second display panel **550** in the scanning direction.

[0200] In an embodiment, the head mounted device **500** may obtain a size deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** in operation **1820**. The head mounted device **500** may modify the screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, so that the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550** is enlarged or reduced in operation **1830**. The head mounted device **500** may change at least one of the driving period of at least one of the first display driving circuit **520** or the second display driving circuit **530**, or the light emitting period of at least one of the first display panel **540** or the second display panel **550**, based on the enlargement or reduction of the first display panel **540** or the second display panel **550** in the scanning direction in operation **1870**.

[0201] In an embodiment, the head mounted device **500** may obtain a rotational deviation between the screen displayed through the first display panel **540** and the screen displayed through the second display panel **550** in operation **1820**. The head mounted device **500** may modify the screen input data input to at least one of the first display driving circuit **520** or the second display driving circuit **530**, so that the screen displayed through the first display panel **540** or the screen displayed through the second display panel **550** is tilted or perspective-transformed in operation **1830**.

[0202] The head mounted device according to an example embodiment may include: a first display panel having a fixed position, a second display panel having a fixed position, a first display driving circuit configured to drive the first display panel, a second display driving circuit configured to drive the second display panel, and at least one processor comprising processing circuitry. At least one processor, individually and/or collectively, may be configured to cause the head mounted device to: provide screen input data to the first display driving circuit and the second display driving circuit; based on the provided screen input data, obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, change a light emitting timing of at least one of the first display panel or the second display panel.

[0203] In the head mounted device according to an example embodiment, the first display panel may be configured to display a screen to a user's left eye through the first optical system; and the

second display panel may be configured to display a screen to the user's right eye through the second optical system.

[0204] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to: obtain a positional deviation on a plane between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel; and modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to move the screen displayed through the first display panel or the screen displayed through the second display panel in parallel, as at least part of modifying the at least portion of the screen input data.

[0205] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to change the light emitting timing of the at least one of the first display panel or the second display panel based on parallel movement of the first display panel or the second display panel in a scanning direction, as at least part of changing the light emitting timing.

[0206] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to: obtain a size deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel; and modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to enlarge or reduce the screen displayed through the first display panel or the screen displayed through the second display panel, as at least part of modifying the at least portion of the screen input data.

[0207] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to: change the light emitting period of the at least one of the first display panel or the second display panel, based on enlargement or reduction of the first display panel or the second display panel in the scanning direction, as at least part of changing the light emitting timing; obtain a rotational deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel; and modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to tilt or perspective-transform the screen displayed through the first display panel or the screen displayed through the second display panel, as at least part of modifying the at least portion of the screen input data.

[0208] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to: identify an effective display area displayed on at least one of the first display panel or the second display panel based on the modification of the at least portion of the screen input data; and change the light emitting timing based on the identified effective display area, as at least part of changing the light emitting timing.

[0209] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to: change the light emitting timing of the at least one of the first display panel or the second display panel based on a height of the identified effective display area of the first display panel or the second display panel in the scanning direction, as at least part of changing the light emitting timing of the at least one of the first display panel or the second display panel.

[0210] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to change luminance or sharpness of the first

display panel or the second display panel based on the identified effective display area.

[0211] In the head mounted device according to an example embodiment, the first display panel and the second display panel may include a plurality of pixels including sub-pixels. At least one processor, individually and/or collectively, may be configured to: identify effective display areas displayed on the first display panel and the second display panel, respectively, based on the modification of the at least portion of the screen input data; and perform sub-pixel rendering on the screen input data, based on arrangement of sub-pixels included in the identified effective display areas of the first display panel and the second display panel.

[0212] A method of operating the head mounted device according to an example embodiment may include: providing screen input data to a first display driving circuit configured to drive a first display panel and a second display driving circuit configured to drive a second display panel; obtaining a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modifying at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, changing a light emitting timing of at least one of the first display panel or the second display panel.

[0213] In the method of operating the head mounted device according to an example embodiment, obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel may include: obtaining a positional deviation on a plane between the screen displayed through the first display panel and the screen displayed through the second display panel; modifying the at least portion of the screen input data may include modifying the screen input data input to the at least one of the first display driving circuit or the second display driving circuit **530** to move the screen displayed through the first display panel or the screen displayed through the second display panel in parallel; and changing **1870** the light emitting timing may include changing the light emitting timing of the at least one of the first display panel or the second display panel based on parallel movement of the first display panel or the second display panel in a scanning direction.

[0214] In the method of operating the head mounted device according to an example embodiment, obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel may include obtaining a size deviation between the screen displayed through the first display panel and the screen displayed through the second display panel. In the method of operating the head mounted device according to an example embodiment, modifying the at least portion of the screen input data may include modifying the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to enlarge or reduce the screen displayed through the first display panel or the screen displayed through the second display panel. In the method of operating the head mounted device according to an example embodiment, changing the light emitting timing may include changing the light emitting period of the at least one of the first display panel or the second display panel, based on enlargement or reduction of the first display panel or the second display panel in the scanning direction.

[0215] In the method of operating the head mounted device according to an example embodiment, obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel may include obtaining a rotational deviation between the screen displayed through the first display panel and the screen displayed through the second display panel. In the method of operating the head mounted device according to an example embodiment, modifying the at least portion of the screen input data may include modifying the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to tilt or perspective-transform the screen displayed through the first display panel or the screen displayed through the second display panel.

[0216] The method of operating the head mounted device according to an example embodiment may further include identifying an effective display area displayed on at least one of the first display panel or the second display panel based on the modification of the at least portion of the screen input data. In the method of operating the head mounted device according to an example embodiment, changing the light emitting timing may include changing the light emitting timing of the at least one of the first display panel or the second display panel based on a height of the identified effective display area of the first display panel or the second display panel in the scanning direction. The method of operating the head mounted device according to an example embodiment may further include changing luminance or sharpness of the first display panel **540** or the second display panel based on the identified effective display area.

[0217] The method of operating the head mounted device according to an example embodiment may further include identifying effective display areas displayed on the first display panel and the second display panel, respectively, based on the modification of the at least portion of the screen input data. The method of operating the head mounted device according to an example embodiment may further include performing sub-pixel rendering on the screen input data, based on arrangement of sub-pixels included in the identified effective display areas of the first display panel and the second display panel.

[0218] A non-transitory computer-readable storage medium storing at least one program according to an example embodiment may include instructions, that when executed by at least one processor, comprising processing circuitry, individually and/or collectively, of an electronic device, cause the electronic device to: based on execution of an application, providing screen input data to the first display driving circuit driving the first display panel and the second display driving circuit driving the second display panel; obtaining a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modifying at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, changing **1870** a light emitting timing of at least one of the first display panel **540** or the second display panel **550**.

[0219] The head mounted device according to an example embodiment, may include: a first display panel having a fixed position, a second display panel having a fixed position, a first display driving circuit configured to drive the first display panel, a second display driving circuit configured to drive the second display panel, and at least one processor comprising processing circuitry. At least one processor, individually and/or collectively, may be configured to cause the head mounted device to: provide screen input data to the first display driving circuit and the second display driving circuit; based on the provided screen input data, obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, change a driving timing of at least one of the first display driving circuit or the second display driving circuit.

[0220] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to: obtain a positional deviation on a plane between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel; modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to move the screen displayed through the first display panel or the screen displayed through the second display panel in parallel, as at least part of modifying the at least portion of the screen input data; and change a timing of a vertical synchronization signal or the screen input data input to at least one of the first display driving circuit or the second display

driving circuit or change a timing of a display period of at least one of the first display driving circuit or the second display driving **530**, based on parallel movement of the first display panel or the second display panel in a scanning direction, as at least part of changing the driving timing. [0221] In the head mounted device according to an example embodiment, at least one processor, individually and/or collectively, may be configured to: obtain a size deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel; modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to enlarge or reduce the screen displayed through the first display panel or the screen displayed through the second display panel, as at least part of modifying the at least portion of the screen input data; and change a scanning speed or a clock speed of at least one of the display driving circuit or the second display driving circuit or change a period of the display period of at least one of the display driving circuit or the second display driving circuit, based on enlargement or reduction of the first display panel or the second display panel in the scanning direction, as at least part of changing the driving timing.

[0222] A method of operating the head mounted device according to an example embodiment may include: providing screen input data to the first display driving circuit configured to drive the first display panel and the second display driving circuit configured to drive the second display panel; obtaining a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modifying at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, changing a driving timing of at least one of the first display driving circuit or the second display driving circuit.

[0223] A non-transitory computer-readable storage medium storing at least one program according to an example embodiment may include instructions that when executed by at least one processor, comprising processing circuitry, individually and/or collectively, of an electronic device, cause the electronic device to: provide screen input data to the first display driving circuit configured to drive the first display panel and the second display driving circuit configured to drive the second display panel; obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; based on the modification of the at least portion of the screen input data, change a driving timing of at least one of the first display driving circuit or the second display driving circuit.

[0224] The electronic device according to embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, a home appliance, or the like. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

[0225] It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B, or C”, “at least one of A, B, and C”, and “at least one of A, B, or C”, may include any one of, or all possible combinations of the items enumerated together in a

corresponding one of the phrases. As used herein, such terms as “1.sup.st” and “2.sup.nd”, or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with”, “coupled to”, “connected with”, or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

[0226] As used in connection with embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, or any combination thereof, and may interchangeably be used with other terms, for example, logic, logic block, part, or circuitry. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

[0227] Embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the “non-transitory” storage medium is a tangible device, and may not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

[0228] According to an embodiment, a method according to embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

[0229] According to embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to an embodiment, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to an embodiment, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

[0230] While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various

modifications, alternatives and/or variations of the various example embodiments may be made without departing from the true technical spirit and full technical scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. A head mounted device comprising: a first display panel having a fixed position; a second display panel having a fixed position; a first display driving circuit configured to drive the first display panel; a second display driving circuit configured to drive the second display panel; and at least one processor comprising processing circuitry, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to: provide screen input data to the first display driving circuit and the second display driving circuit, based on the provided screen input data, obtain a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel, based on the obtained deviation, modify at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit, and based on the modification of the at least portion of the screen input data, change a light emitting timing of at least one of the first display panel or the second display panel.
2. The head mounted device of claim 1, wherein the first display panel is configured to display a screen to a user's left eye through a first optical system, and wherein the second display panel is configured to display a screen to the user's right eye through a second optical system.
3. The head mounted device of claim 1, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to: obtain a positional deviation on a plane between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, and modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to move the screen displayed through the first display panel or the screen displayed through the second display panel in parallel, as at least part of modifying the at least portion of the screen input data.
4. The head mounted device of claim 3, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to change the light emitting timing of the at least one of the first display panel or the second display panel based on parallel movement of a first screen provided by the first display panel or a second screen provided by the second display panel in a scanning direction, as at least part of changing the light emitting timing.
5. The head mounted device of claim 1, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to: obtain a size deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, and modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to enlarge or reduce the screen displayed through the first display panel or the screen displayed through the second display panel, as at least part of modifying the at least portion of the screen input data.
6. The head mounted device of claim 5, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to change the light emitting period of the at least one of the first display panel or the second display panel, based on enlargement or reduction of a third screen provided by the first display panel or a fourth screen provided by the second display panel in the scanning direction, as at least part of changing the light emitting timing.

7. The head mounted device of claim 1, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to: obtain a rotational deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, as at least part of obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, and modify the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to tilt or perspective-transform the screen displayed through the first display panel or the screen displayed through the second display panel, as at least part of modifying the at least portion of the screen input data.

8. The head mounted device of claim 1, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to: identify a first effective display area of at least one of the first display panel or a second effective display area of the second display panel based on the modification of the at least portion of the screen input data, and change the light emitting timing based on the identified effective display area, as at least part of changing the light emitting timing.

9. The head mounted device of claim 8, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to change the light emitting timing of the at least one of the first display panel or the second display panel based on a height of the first effective display area of the first display panel and a height of the second effective display area of the second display panel in the scanning direction, as at least part of changing the light emitting timing of the at least one of the first display panel or the second display panel.

10. The head mounted device of claim 8, wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to change luminance and/or sharpness of the first display panel or the second display panel based on the identified effective display area.

11. The head mounted device of claim 1, wherein the first display panel and the second display panel include a plurality of pixels including sub-pixels, and wherein at least one processor, individually and/or collectively, is configured to cause the head mounted device to: identify effective display areas of the first display panel and the second display panel, respectively, based on the modification of the at least portion of the screen input data, and perform sub-pixel rendering on the screen input data, based on arrangement of sub-pixels included in the identified effective display areas of the first display panel and the second display panel.

12. A method of operating a head mounted device, comprising: providing screen input data to a first display driving circuit configured to drive a first display panel and a second display driving circuit configured to drive a second display panel; obtaining a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modifying at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, changing a light emitting timing of at least one of the first display panel or the second display panel.

13. The method of claim 12, wherein obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel includes obtaining a positional deviation on a plane between the screen displayed through the first display panel and the screen displayed through the second display panel, wherein the modifying of the at least portion of the screen input data includes modifying the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to move the screen displayed through the first display panel or the screen displayed through the second display panel in parallel, and wherein the changing of the light emitting timing includes changing the light emitting timing of the at least one of the first display panel or the second display panel based on parallel movement of a first screen provided by the first display panel or a second screen provided by the second display panel in a scanning direction.

14. The method of claim 12, wherein obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel includes obtaining a size deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, wherein the modifying of the at least portion of the screen input data includes modifying the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to enlarge or reduce the screen displayed through the first display panel or the screen displayed through the second display panel, and wherein the changing of the light emitting timing includes changing the light emitting period of the at least one of the first display panel or the second display panel, based on enlargement or reduction of a third screen provided by the first display panel or a fourth screen provided by the second display panel in the scanning direction.

15. The method of claim 12, wherein obtaining the deviation between the screen displayed through the first display panel and the screen displayed through the second display panel includes obtaining a rotational deviation between the screen displayed through the first display panel and the screen displayed through the second display panel, and wherein the modifying of the at least portion of the screen input data includes modifying the screen input data input to the at least one of the first display driving circuit or the second display driving circuit to tilt or perspective-transform the screen displayed through the first display panel or the screen displayed through the second display panel.

16. The method of claim 12, further comprising: identifying a first effective display area of at least one of the first display panel or a second effective display area of the second display panel based on the modification of the at least portion of the screen input data, and changing the light emitting timing based on the identified effective display area.

17. The method of claim 16, further comprising: changing the light emitting timing of the at least one of the first display panel or the second display panel based on a height of the first effective display area of the first display panel and a height of the second effective display area of the second display panel in the scanning direction.

18. The method of claim 16, further comprising: changing luminance and/or sharpness of the first display panel or the second display panel based on the identified effective display area.

19. The method of claim 12, wherein the first display panel and the second display panel include a plurality of pixels including sub-pixels, and further comprising: identifying effective display areas of the first display panel and the second display panel, respectively, based on the modification of the at least portion of the screen input data, and performing sub-pixel rendering on the screen input data, based on arrangement of sub-pixels included in the identified effective display areas of the first display panel and the second display panel.

20. One or more non-transitory computer-readable storage media storing one or more computer programs including computer-executable instructions that, when executed by one or more processors of a head mounted device individually or collectively, cause the head mounted device to perform operations, the operations comprising: providing screen input data to a first display driving circuit configured to drive a first display panel and a second display driving circuit configured to drive a second display panel; obtaining a deviation between a screen displayed through the first display panel and a screen displayed through the second display panel; based on the obtained deviation, modifying at least a portion of the screen input data input to at least one of the first display driving circuit or the second display driving circuit; and based on the modification of the at least portion of the screen input data, changing a light emitting timing of at least one of the first display panel or the second display panel.
