

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250269801

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Jeon; Minseok et al.

VECHICLE STORAGE COMPARTMENT ALONG A TOP SURFACE OF A DOOR INTERIOR PANEL

Abstract

Disclosed is a product that may include a vehicle door interior panel having lower portion having a front surface, opposite rear surface, bottom surface and a top surface, a storage compartment having a lid hinged to the at least one wall, wherein the lid forms a portion of the top surface of the bottom portion of the interior panel.

Inventors: Jeon; Minseok (Gimpo-si, KR), Lim; Hyunsoo (Bucheon-si, KR), Hwang; Jinki (Incheon, KR)

Applicant: GM GLOBAL TECHNOLOGY OPERATIONS LLC (Detroit, MI)

Family ID: 1000007723363

Assignee: GM GLOBAL TECHNOLOGY OPERATIONS LLC (Detroit, MI)

Appl. No.: 18/587891

Filed: February 26, 2024

Publication Classification

Int. Cl.: B60R7/04 (20060101)

U.S. Cl.:

CPC B60R7/046 (20130101);

Background/Summary

INTRODUCTION

[0001] The technical field generally relates to vehicle storage compartments and components and method of using the same.

BACKGROUND

[0002] Cars traditionally have had storage compartments in the glove box, center console, and door pockets. However, these compartments are often small and inconveniently located. For example, the glove box is often difficult to reach while driving, and the center console can become cluttered with other items. Door pockets are also small and can be awkward to use, especially in the back seat. The front door upper trim is usually a nonfunctional decorative piece of plastic or other material. Storage space in your car is always important, especially in small cars where every cubic inch of space counts.

[0003] Accordingly, it is desirable to provide a product including a vehicle storage compartment, which in a number of variations may include non-traditional materials for a vehicle storage compartment and may be located in a non-traditional place in a vehicle. Furthermore, other desirable features and characteristics of the variations disclosed herein will become apparent from the subsequent detailed description and the appended claims, taken in conjunction with the accompanying drawings and the foregoing.

SUMMARY

[0004] A number of variations may include a product including a vehicle door interior panel having lower portion having a front surface, opposite rear surface, bottom surface and a top surface, a storage compartment having a lid hinged to the at least one wall, wherein the lid forms a portion of the top surface of the lower portion of the interior panel.

[0005] A number of variations may include a product wherein the at least one wall includes a bottom wall.

[0006] A number of variations may include a product wherein the at least one wall further includes at least one connecting wall extending from the bottom wall.

[0007] A number of variations may include a product wherein the at least one connecting wall includes a front wall and an opposite rear wall, and an outer side wall and an inner side wall each connected to the front wall and rear wall.

[0008] A number of variations may include a product wherein the lid is hinged to the at least one connecting wall.

[0009] A number of variations may include a product wherein the lid is hinged to the at least one connecting wall by a metal hinge or a flexible hinge comprising a polymeric material or fabric.

[0010] A number of variations may include a product further including a zipper having a first row of teeth connected to the lid and a second row of teeth connected to the at least one connecting wall, and a slide for drawing the first row of teeth and the second row of teeth together to close the storage compartment or to separate the first row of teeth and the second row of teeth to open the storage compartment and allow the lid to be moved to an open position.

[0011] A number of variations may include a product wherein the lid, bottom wall, and at least one connecting wall each includes an inflexible material.

[0012] A number of variations may include a product wherein the inflexible material includes a polymeric material, composite, or metal.

[0013] A number of variations may include a product further including a fabric, natural leather, synthetic leather, or polymeric material covering an outer surface of the lid.

[0014] A number of variations may include a product wherein the storage compartment is located along the top surface closer to the front surface than the rear surface of the interior panel.

[0015] A number of variations may include a product further including a vehicle having a dashboard and wherein the storage compartment is located along the top surface near the dashboard.

[0016] A number of variations may include a product wherein interior panel includes an interior face facing a driver seat or passenger seat, and wherein the interior face includes a portion curved toward the dashboard, and wherein at least a portion of the storage compartment is located behind the curved portion of the interior face of the interior panel.

[0017] A number of variations may include a product further including a vehicle having an A-pillar and wherein the storage compartment is located along the top surface on the door interior panel near the A-pillar.

[0018] A number of variations may include a product including a vehicle having a pair of spaced a part A-pillars and a dashboard extending therebetween; a vehicle door interior panel having lower portion having a front surface, opposite rear surface, bottom surface and a top surface, a storage compartment having a lid hinged to the at least one wall, wherein the lid forms a portion of the top surface of the bottom portion of the interior panel; wherein the storage compartment is located along the top surface of the interior panel closest to the dashboard and one of the spaced a part A-pillars.

[0019] A number of variations may include a product wherein the at least one wall includes a front wall and an opposite rear wall, and an outer side wall and an inner side wall each connected to the front wall and rear wall.

[0020] A number of variations may include a product wherein the lid is hinged to the at least one wall by a metal hinge or a flexible hinge including a polymeric material or fabric.

[0021] A number of variations may include a product further comprising a zipper having a first row of teeth connected to the lid and a second row of teeth connected to the at least one connecting wall, and a slide for drawing the first row of teeth and the second row of teeth together to close the storage compartment or to separate the first row of teeth and the second row of teeth to open the storage compartment and allow the lid to be moved to an open position.

[0022] A number of variations may include a product wherein interior panel includes an interior face facing a driver seat or passenger seat, and wherein the interior face includes a portion curved toward the dashboard, and wherein at least a portion of the storage compartment is located behind the covered portion of the interior face of the interior panel.

[0023] A number of variations may include a method including assembling a vehicle door interior panel having lower portion having a front surface, opposite rear surface, bottom surface and a top surface, a storage compartment having a lid hinged to the at least one wall, wherein the lid forms a portion of the top surface of the bottom portion of the interior panel.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The variations will hereinafter be described in conjunction with the following drawing figures, wherein like numerals denote like elements, and wherein:

[0025] FIG. 1 illustrates a vehicle door including a door frame, and a door interior panel according to a number of variations;

[0026] FIG. 2 is a perspective view of a lower portion of a vehicle door interior panel having a storage compartment along a top surface of the lower portion of the vehicle door interior panel according to a number of variations;

[0027] FIG. 3 is a sectional view taken along lines 3-3 of FIG. 2 according to a number of variations;

[0028] FIG. 4 is a perspective, partial view of the vehicle door interior panel having a storage compartment along the top surface of the lower portion of the vehicle door interior panel with a lid of the storage compartment and an open position according to a number of variations;

[0029] FIG. 5 illustrates to variations of a hinge for use with a lid of a storage compartment

according to a number of variations;

[0030] FIG. **6** illustrates a zipper for use in closing and/or locking the lid of a storage compartment according to a number of variations;

[0031] FIG. **7** is a partial view illustrating a vehicle interior having a vehicle door interior panel having a curve portion engaging a dashboard wherein the curved portion provides a space there behind is suitable receiving at least a portion of a storage compartment for according to a number of variations.

DETAILED DESCRIPTION

[0032] The following detailed description is merely illustrative in nature and is not intended to limit the application and uses. Furthermore, there is no intention to be bound by any expressed or implied theory presented in the preceding technical field, background, brief summary or the following detailed description.

[0033] A number of variations are illustrated in FIG. **1**, which may include a product which may be a vehicle door interior panel **30** having a lower portion **32** and an upper portion **42**. The lower portion **32** may include a forward surface **34**, a rear surface **36**, a bottom surface **38**, and a top surface **40**. The upper portion **42** may include an A-pillar engagement portion **44**, a top portion **46**, a B pillar engagement portion **4**, which along with the top surface **40** of the lower portion **32** define a window opening **50**. The vehicle door interior panel **30** may be mounted to a door frame **52** typically made of stamped metal. The door frame **52** may include a roof engaging edge **54**, an A-pillar engaging edge **56**, a front edge **58**, a bottom edge **60**, a rear edge **62**, and a B-pillar engaging edge **64**. The lower portion **32** of the vehicle door interior panel **30** may be configured to accommodate a storage compartment area **66** near the upper front portion of the lower portion **32** of the vehicle door interior panel **30**.

[0034] A number of variations are illustrated in FIGS. **2-3**, which may include a lower portion **32** of the vehicle door interior panel **30** having a storage compartment **68** therein. The storage compartment **68** may include a lid **70**, at least one hinge **72** connected to the lid **70**, and outer wall **74** connected to a bottom wall **76**, and a front wall **78** and rear wall **80** each connected to the bottom wall **76**. The vehicle door interior panel **30** may include an interior face **84** joining the top surface **40**. The lid **70** of the storage compartment **68** may form a portion of the top surface **40** of the lower portion **32** of the vehicle door interior panel **30**.

[0035] A number of variations are illustrated in FIG. **4** wherein the lid **70**, outer wall **74**, bottom wall **76**, front wall **78**, rear wall **80**, and an inner wall **82** (not shown in FIG. **4**) define a space for luggage and other objects. At least one hinge **72** may be operatively connected to the lid **70** and one of the outer wall **74**, front wall **78**, rear wall **80**, an inner wall **82** so that the lid **70** may be swung to an open position or close position wherein the lid **70** engages at least one of the outer wall **74**, front wall **78**, rear wall **80**, an inner wall **82**. The lid **70** may include a lower edge **71**, a first end edge **136** and an opposite second end edge **134** joining the lower edge **71** and a top edge **132**. The outer wall **74** may have first upper edge **75**, rear wall **80** may have second upper edge **138**, the inner wall **82** may have third upper edge **140**, and the front wall **78** may have fourth upper edge **142**.

[0036] A number of variations are illustrated in FIG. **5** which may include a hinge **72** made of a metal or a polymeric material including a first hinge piece **88** having a first finger **90** and spaced apart a second finger **92**. The hinge **72** may include a second piece **94** having a third finger **96** and spaced apart a fourth finger **98**. The first finger **90** and the second finger **92** may be interdigitated with the third finger **96** and the fourth finger **98**. The hinge **72** may be made from a relatively flexible material which may be a metal, a polymeric material, or a fabric and may extend along at least a portion of a lower edge **71** of the lid **70** and long an upper edge **75**, **142**, **138**, **140** of one of the outer wall **74**, front wall **78**, rear wall **80**, an inner wall **82**, respectively.

[0037] A number of variations are illustrated in FIG. **6** which may include a zipper **100** having first strip of fabric **102** having a first row of spaced a part teeth **104** attached thereto, and second strip of fabric **106** having a second row of spaced a part teeth **108** attached thereto, and a slide **110** for

drawing the first row of spaced a part teeth **104** and the second row of spaced a part teeth **108** together to close the storage compartment **68** or to separate the first row of spaced a part teeth **104** and the second row of spaced a part teeth **108** to open the storage compartment **68** and allow the lid **70** to be moved to an open position. The first strip of fabric **102** and first row of spaced a part teeth **104** may be provided along at least one of the lower edge **71**, the first end edge **136**, the opposite second end edge **134** or a top edge **132** of the lid **70**. In a number of variations, the first strip of fabric **102** and first row of spaced a part teeth **104** may be provided along three of the lower edge **71**, the first end edge **136**, the opposite second end edge **134** or a top edge **132** of the lid **70**. The second strip of fabric **106** and second row of spaced a part teeth **108** may be provided along at least one of the first upper edge **75** of the outer wall **74**, the second upper edge **138** rear wall **80**, the third upper edge **140** the inner wall **82**, or fourth upper edge **142** the front wall **78**. In a number of variations, the second strip of fabric **106** and second row of spaced a part teeth **108** may be provided along three of the first upper edge **75** of the outer wall **74**, the second upper edge **138** of rear wall **80**, the third upper edge **140** the inner wall **82**, or fourth upper edge **142** the front wall **78**. In a number of variations, the storage compartment **68** and the lid **70** there of may have a variety of shapes.

[0038] FIG. 7 is a partial view illustrating a vehicle interior wherein the vehicle may include a pair of spaced apart a-pillars **120**, **2120** and a dashboard **128** extending therebetween. A driver side door interior panel **112** and a front passenger side door interior panel **114** may be provided. A steering **116** will may be connected to a shaft (not shown) extending through the dashboard **128**. A driver seat **118** may be provided next to the driver side door interior panel **112** and a front passenger seat **124** may be provided next to the front passenger side door interior panel **114**. The driver side door interior panel **112** may include a top surface **40** and an interior face **84** facing the driver seat **118**. The interior face **84** may have a curved portion **122** providing a space there behind which may receive at least a portion of a storage compartment according to a number of variations. Similarly, the front passenger side door interior panel **114** may include a top surface **2040** and an interior face **2084** which may have a curved portion **2122** providing a space there behind for receiving at least a portion of a storage compartment according to a number of variations. A center counsel **126** may be provided between the driver seat **118** and the front passenger seat **124**.

[0039] While at least one illustrative variation has been presented in the foregoing detailed description, it should be appreciated that a vast number of variations exist. It should also be appreciated that the exemplary embodiment or exemplary embodiments are only examples, and are not intended to limit the scope, applicability, or configuration of the disclosure in any way. Rather, the foregoing detailed description will provide those skilled in the art with a convenient road map for implementing the exemplary embodiment or exemplary embodiments. It should be understood that various changes can be made in the function and arrangement of elements without departing from the scope of the disclosure as set forth in the appended claims and the legal equivalents thereof.

Claims

1. A product comprising: a vehicle door interior panel having lower portion having a front surface, opposite rear surface, bottom surface and a top surface, a storage compartment having a lid hinged to the at least one wall, wherein the lid forms a portion of the top surface of the lower portion of the interior panel.
2. The product as set forth in claim 1 wherein the at least one wall comprises a bottom wall.
3. The product as set forth in claim 2 wherein the at least one wall further comprising at least one connecting wall extending from the bottom wall.
4. The product as set forth in claim 3 wherein the at least one connecting wall comprises a front wall and an opposite rear wall, and an outer side wall and an inner side wall each connected to the

front wall and rear wall.

5. The product as set forth in claim 3 wherein the lid is hinged to the at least one connecting wall.

6. The product as set forth in claim 5 wherein the lid is hinged to the at least one connecting wall by a metal hinge or a flexible hinge comprising a polymeric material or fabric.

7. The product as set forth in claim 6 further comprising a zipper having a first row of teeth connected to the lid and a second row of teeth connected to the at least one connecting wall, and a slide for drawing the first row of teeth and the second row of teeth together to close the storage compartment or to separate the first row of teeth and the second row of teeth to open the storage compartment and allow the lid to be moved to an open position.

8. The product as set forth in claim 3 wherein the lid, bottom wall, and at least one connecting wall each comprises an inflexible material.

9. The product as set forth in claim 8 wherein the inflexible material comprises a polymeric material, composite, or metal.

10. The product as set forth in claim 1 further comprising a fabric, natural leather, synthetic leather, or polymeric material covering an outer surface of the lid.

11. The product as set forth in claim 1 wherein the storage compartment is located along the top surface closer to the front surface than the rear surface of the interior panel.

12. The product as set forth in claim 1 further comprising a vehicle having a dashboard and wherein the storage compartment is located along the top surface near the dashboard.

13. The product as set forth in claim 12 wherein interior panel includes an interior face facing a driver seat or passenger seat, and wherein the interior face includes a portion curved toward the dashboard, and wherein at least a portion of the storage compartment is located behind the curved portion of the interior face of the interior panel.

14. The product is set forth in claim 1 further comprising a vehicle having an A-pillar and wherein the storage compartment is located along the top surface on the door interior panel near the A-pillar.

15. A product comprising: a vehicle having a pair of spaced a part A-pillars and a dashboard extending therebetween; a vehicle door interior panel having lower portion having a front surface, opposite rear surface, bottom surface and a top surface, a storage compartment having a lid hinged to the at least one wall, wherein the lid forms a portion of the top surface of the bottom portion of the interior panel; wherein the storage compartment is located along the top surface of the interior panel closest to the dashboard and one of the spaced a part A-pillars.

16. The product as set forth in claim 15 wherein the at least one wall comprises a front wall and an opposite rear wall, and an outer side wall and an inner side wall each connected to the front wall and rear wall.

17. The product as set forth in claim 16 wherein the lid is hinged to the at least one wall by a metal hinge or a flexible hinge comprising a polymeric material or fabric.

18. The product is set forth in claim 17 further comprising a zipper having a first row of teeth connected to the lid and a second row of teeth connected to the at least one connecting wall, and a slide for drawing the first row of teeth and the second row of teeth together to close the storage compartment or to separate the first row of teeth and the second row of teeth to open the storage compartment and allow the lid to be moved to an open position.

19. A product as set forth in claim 18 wherein interior panel includes an interior face facing a driver seat or passenger seat, and wherein the interior face includes a portion curved toward the dashboard, and wherein at least a portion of the storage compartment is located behind the curved portion of the interior face of the interior panel.

20. A method comprising: assembling a vehicle door interior panel having lower portion having a front surface, opposite rear surface, bottom surface and a top surface, a storage compartment having a lid hinged to the at least one wall, wherein the lid forms a portion of the top surface of the bottom portion of the interior panel.

