

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250271747

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

SHEN; Guoqiang

Multifunctional Image Mapping Device

Abstract

The present invention discloses a multifunctional image mapping device, which comprises a main body shell, an image mapping apparatus, a control apparatus and a sound apparatus, wherein an inner bracket, a mapping bracket and a lens bracket are arranged in the main body shell; the image mapping apparatus comprises a mapping disc, a light source and a lens assembly; a mapping port is arranged on the mapping disc; mapping sheets are arranged in the mapping port; the mapping disc is provided with coding information corresponding to each mapping sheet; the mapping disc is arranged on the mapping bracket; the light source is arranged in the mapping bracket; the mapping port is aligned with the lens assembly and the light source through the rotation of the mapping disc, and a control apparatus and a sound apparatus are also arranged in the main body shell.

Inventors: SHEN; Guoqiang (Zhejiang, CN)

Applicant: SHEN; Guoqiang (Zhejiang, CN)

Family ID: 1000007842811

Appl. No.: 18/587046

Filed: February 26, 2024

Publication Classification

Int. Cl.: G03B23/10 (20060101); G03B21/14 (20060101); G03B21/20 (20060101); G03B21/64 (20060101); G03B29/00 (20210101)

U.S. Cl.:

CPC G03B23/105 (20130101); G03B21/145 (20130101); G03B21/208 (20130101); G03B21/64 (20130101); G03B29/00 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to the field of projection device, in particular to a multifunctional image mapping device.

BACKGROUND

[0002] At present, there are many similar products of projection music box on the market, and all of them are manually operated to realize the music playback of each picture, so the detailed information of the currently displayed picture cannot be accurately reflected. Therefore, it can't have a correct understanding and counseling effect on children. Due to the defects in the overall design of the product, the picture information of the product is not rich enough, and the picture and the built-in music of the host can not be replaced casually, so the product is single and not rich.

[0003] For example, a projection toy is disclosed in the patent document "Projection Toy" with US application number of U.S. Pat. No. 1,176,842, which includes a top shell. By arranging one side of the convex end of the first convex lens close to one side of the convex end of the second convex lens, the present invention can effectively improve the intensity of photography, increase the projection distance, and provide a clear visual field for children in use. The film turntable is rotatably installed in the shell, and the film can rotate around the rotating shaft under the action of two clamps. So that users can directly change the patterns, thus improving the playability, and solving the problem of single product pictures; however, the present invention only realizes the projection by rotating and changing the pictures, can not provide the sound matching with the current projection content, and only provides the pictures, which is rather boring.

[0004] However, the patent document "Toy Projector" with a US patent number of 20150147932 discloses a toy projector with animal or peculiar appearance. Although it is suitable for playing all kinds of images, audio and video content, it includes a microcomputer, which processes what is played in the data file. There is a plush toy package outside the device, which cannot be grasped, and its operation steps are complicated, and the preparation time before projection is long, and thus it cannot be projected quickly.

[0005] Based on the above problems, it is necessary to provide a brand-new mapping device, which has the advantages of high synchronization, strong playability, convenient use and not easy to damage.

SUMMARY

[0006] The present invention provides a multifunctional image mapping device, which includes a main body shell, an image mapping apparatus, a control apparatus and a sound apparatus; [0007] wherein, an inner bracket, a mapping bracket and a lens bracket are arranged inside said main body shell; and [0008] wherein, said image mapping apparatus comprises a mapping disc, a light source and a lens assembly, wherein said mapping disc is provided with a plurality of mapping ports, mapping sheets are arranged in the plurality of mapping ports, and said mapping disc is also provided with coding information corresponding to each mapping sheet, wherein said mapping disc is rotatably coupled to said mapping bracket, said lens assembly is arranged in said lens bracket, and said light source is arranged in said mapping bracket, wherein said mapping port can be aligned with the lens assembly and the light source through the rotation of said mapping disc; [0009] wherein, said control apparatus and said sound apparatus are arranged on said inner bracket, and said control apparatus comprises a circuit board which is electrically connected with said image mapping apparatus and said sound apparatus; and [0010] wherein when a user rotates said mapping disc, said circuit board recognizes the coding information of said mapping sheet aligned with said lens assembly, and controls said light source and said sound apparatus to work according to a preset program.

[0011] The present invention provides another multifunctional image mapping device, which includes a main body shell, an image mapping apparatus, a control apparatus and a sound apparatus; [0012] wherein, an inner bracket, a mapping bracket, a lens bracket and a knob are

arranged inside said main body shell; and [0013] wherein, said image mapping apparatus comprises a mapping disc, a light source and a lens assembly, wherein said mapping disc is provided with a plurality of mapping ports, mapping sheets are arranged in said mapping ports, and said mapping disc is also provided with coding information corresponding to each mapping sheet, wherein said mapping disc is rotatably coupled to said mapping bracket, said lens assembly is arranged in said lens bracket, and said light source is arranged in said mapping bracket, wherein said mapping port can be aligned with said lens assembly and said light source through the rotation of said mapping disc; [0014] wherein said knob is operatively connected to said lens assembly to adjust a focal length of said lens assembly; and [0015] wherein, said control apparatus and said sound apparatus are arranged on said inner bracket, and said control apparatus comprises a circuit board, wherein said circuit board is provided with an identification probe which is in contact with said mapping disc, and when said mapping disc rotates, said identification probe can read the coding information of said mapping sheet aligned with said lens assembly; and [0016] wherein when said control apparatus receives an input instruction from a user, said control apparatus controls said light source and said sound apparatus to work according to a preset program.

[0017] The present invention further provides an image mapping method, which includes providing a multifunctional image mapping device including a main body shell, an image mapping apparatus, a control apparatus and a sound apparatus; [0018] wherein, an inner bracket, a mapping bracket, a lens bracket and a knob are arranged inside said main body shell; and [0019] wherein, said image mapping apparatus comprises a mapping disc, a light source and a lens assembly, wherein said mapping disc is provided with a plurality of mapping ports, mapping sheets are arranged in said mapping ports, and said mapping disc is also provided with coding information corresponding to each mapping sheet, wherein said mapping disc is rotatably coupled to said mapping bracket, said lens assembly is arranged in said lens bracket, and said light source is arranged in said mapping bracket, wherein said mapping port can be aligned with said lens assembly and said light source through the rotation of said mapping disc; [0020] wherein said knob is operatively connected to said lens assembly to adjust a focal length of said lens assembly; and [0021] wherein, said control apparatus and said sound apparatus are arranged on said inner bracket, and said control apparatus comprises a circuit board, wherein said circuit board is provided with an identification probe which is in contact with said mapping disc, and when said mapping disc rotates, said identification probe can read the coding information of said mapping sheet aligned with said lens assembly; and [0022] wherein when said control apparatus receives an input instruction from a user, said control apparatus controls said light source and said sound apparatus to work according to a preset program; and [0023] the method comprises the following steps: [0024] turning on said multifunctional image mapping device through said control apparatus; [0025] rotating said mapping disc and selecting a mapping sheet to be mapped; [0026] rotating said knob to select an appropriate focal length; and [0027] mapping by said control apparatus.

[0028] The terms “invention,” “the invention,” “this invention” and “the present invention” used in this patent are intended to refer broadly to all of the subject matter of this patent and the patent claims below. Statements containing these terms should be understood not to limit the subject matter described herein or to limit the meaning or scope of the patent claims below. Embodiments of the invention covered by this patent are defined by the claims below, not this summary. This summary is a high-level overview of various embodiments of the invention and introduces some of the concepts that are further described in the Detailed Description section below. This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended to be used in isolation to determine the scope of the claimed subject matter. The subject matter should be understood by reference to appropriate portions of the entire specification of this patent, any or all drawings and each claim.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0029] In order to explain the technical scheme of this application more clearly, the drawings needed in the implementation will be briefly introduced below. Obviously, the drawings described below are only some implementations of this application. For those skilled in the art, other drawings can be obtained according to these drawings without creative work.

[0030] FIG. 1 is an overall view of a multifunctional image mapping device;

[0031] FIG. 2 is an exploded view of a multifunctional image mapping device;

[0032] FIG. 3 is a sectional view of a multifunctional image mapping device;

[0033] FIG. 4 is a partial view of a mapping bracket and a lens bracket in a multifunctional image mapping device;

[0034] FIG. 5 is a front view of a mapping disc in a multifunctional image mapping device;

[0035] FIG. 6 is an exploded view of a mapping disc in a multifunctional image mapping device;

[0036] FIG. 7 is a front view of a main body of the mapping disc in a multifunctional image mapping device;

[0037] FIG. 8 is a partial view of a mapping disc and an identification apparatus in a multifunctional image mapping device;

[0038] FIG. 9 is an internal structural view of a multifunctional image mapping device;

[0039] FIG. 10 is a partial view of a knob and a mapping disc in a multifunctional image mapping device;

[0040] FIG. 11 is an internal view of the lower end of the main body shell in a multifunctional image mapping device;

[0041] FIG. 12 is a view of a cover plate in a multifunctional image mapping device.

[0042] In the drawings: Main body shell (1000); Inner bracket (1100); Battery assembly (1110); Mapping bracket (1200); Condenser lens (1210); Identification apparatus (1230); Spring probe (1231); Base point probe (1232); Resistance identification probe (1233); Gear position identification probe (1234); Lens bracket (1300); First lens (1310); Second lens (1320); Adjusting thread (1330); Upper end (1400); Lower end (1500); Battery cover plate (1600); Cover plate (1700); Fixing block (1710); Image mapping apparatus (2000); Mapping disc (2100); Mapping port (2110); Rotating shaft (2160); Mapping sheet (2120); Mapping disc main body (2101); Port disc (2130); Base point area (2131); Resistance value identification area (2132); Gear recognition area (2133); Mapping sheet placement area (2150); Coding disc (2140); Mapping disc upper cover (2102); Light source (2200); Lens assembly (2300); Knob (2310); Control apparatus (3000); Circuit board (3100); Control button (3200); Mapping switch (3210); Start switch (3220); Sound apparatus (4000); Speaker hole (4100).

DESCRIPTION OF EMBODIMENTS

[0043] In describing the preferred embodiments, specific terminology will be resorted to for the sake of clarity. It is to be understood that each specific term includes all technical equivalents which operate in a similar manner to accomplish a similar purpose.

[0044] While various aspects and features of certain embodiments have been summarized above, the following detailed description illustrates a few exemplary embodiments in further detail to enable one skilled in the art to practice such embodiments. Reference will now be made in detail to embodiments of the inventive concept, examples of which are illustrated in the accompanying drawings. The accompanying drawings are not necessarily drawn to scale. The described examples are provided for illustrative purposes and are not intended to limit the scope of the invention. It should be understood, however, that persons having ordinary skill in the art may practice the inventive concept without these specific details.

[0045] It will be understood that, although the terms first, second, etc. may be used herein to

describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first attachment could be termed a second attachment, and, similarly, a second attachment could be termed a first attachment, without departing from the scope of the inventive concept.

[0046] It will be understood that when an element or layer is referred to as being “on,” “coupled to,” or “connected to” another element or layer, it can be directly on, directly coupled to or directly connected to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly coupled to,” or “directly connected to” another element or layer, there are no intervening elements or layers present. Like numbers refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0047] As used in the description of the inventive concept and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates other.

[0048] As a preferred embodiment of the present invention, in order to solve the problem that the current projected toy product picture is single and audio content corresponding to the projected picture cannot be provided, the present invention provides a multifunctional image mapping device.

[0049] Referring to FIGS. 1 to 3, the multifunctional image mapping device includes a main body shell **1000**, an image mapping apparatus **2000**, a control apparatus **3000** and a sound apparatus **4000**. Inside the main body shell **1000**, there are an inner bracket **1100**, a mapping bracket **1200** and a lens bracket **1300**. The whole main body shell **1000** is divided into an upper end **1400** and a lower end **1500**, both of which have a maximum diameter. The upper end **1400** is fixedly connected to the lower end **1500** through arc transition, and the maximum diameter of the upper end **1400** is greater than that of the lower end **1500**. The inner bracket **1100** is arranged at the lower end **1500** of the main body shell **1000**, and the mapping and lens bracket **1300** are arranged at the upper end **1400** of the main body shell **1000**. From top to bottom, there are a lens bracket **1300**, a mapping bracket **1200** and an inner bracket **1100** in turn.

[0050] Referring to FIGS. 1 to 3, the image mapping apparatus **2000** includes a mapping disc **2100**, a light source **2200** and a lens assembly **2300**. In this embodiment, the mapping disc **2100** is provided with eight mapping ports **2110**, and each mapping port **2110** is internally provided with a mapping sheet **2120**. The mapping disc **2100** has coding information corresponding to each mapping sheet **2120**, and the mapping disc **2100** is rotatably coupled to the mapping bracket **1200**; the lens assembly **2300** is arranged in the lens bracket **1300**, and the light source **2200** is arranged in the mapping bracket **1200**. By rotating the mapping disc **2100**, different mapping ports **2110** can be selected to align the lens assembly **2300** and the light source **2200**.

[0051] Referring to FIGS. 1 to 3, the control apparatus **3000** and the sound apparatus **4000** are arranged on the inner bracket **1100**. The control apparatus **3000** includes a circuit board **3100**, which is electrically connected with the image mapping apparatus **2000** and the sound apparatus **4000**. When the user rotates the mapping disc **2100**, the circuit board **3100** recognizes the coding information of the mapping sheet **2120** in the corresponding mapping port **2110** at present, and controls the light source **2200** and the sound apparatus **4000** to work according to the preset program, so as to map and play sound.

[0052] Referring to FIGS. 2 and 3, the lens assembly **2300** includes a first lens **1310** and a second lens **1320**, and a condenser lens **1210** is also arranged above the light source **2200**. The mapping sheet **2120** on the mapping disc **2100** is located between the second lens **1320** and the condenser lens **1210**. The light source **2200** is turned on by the mapping switch **3210** in the control apparatus **3000** for mapping, and the light beam generated by the light source **2200** passes through the condenser lens **1210**, the mapping sheet **2120**, the second lens **1320** and the first lens **1310** for mapping.

[0053] Referring to FIG. 4, the condenser lens **1210**, the mapping port **2110**, the mapping sheet

1210 (not shown in the figure) in the mapping port **2110**, the second lens **1320** and the first lens **1310** are all in the same straight line direction, and the condenser lens **1210** can focus the light beam generated by the light source **2200** on the mapping sheet **2120** to obtain the best mapping effect, provide illumination with sufficient degree and uniformity, and ensure the mapping.

[0054] Referring to FIGS. 5 to 7, the mapping disc **2100** is composed of a mapping disc main body **2101** and a mapping disc upper cover **2102**. The mapping disc main body **2101** is divided into a port disc **2130**, a coding disc **2140** and a mapping sheet placement area **2150**. The port disc **2130** includes a resistance value identification area **2132**, a base point area **2131** and a gear recognition area **2133**. Eight resistance values with different gears are set in the base point area **2131** and the resistance value identification area **2132**, and eight different gear values are uniformly set in the gear recognition area **2133**, and each gear value corresponds to the resistance value of each gear one-to-one, respectively representing the contents of different mapping sheets **2120**. The port disc **2130** is electrically connected with the circuit board **3100**, and a coding disc **2140** is arranged on the back of the port disc **2130**, and the coding disc **2140** is provided with pre-stored coding information. Mapping sheets **2120** are placed on the mapping sheet placement area **2150**, and each mapping sheet **2120** corresponds to the code on the coding disc **2140**; the mapping disc **2100** is also provided with a rotating shaft **2160**, which is located in the center of the mapping disc **2100**, and the mapping ports **2110** are distributed on the mapping disc **2100** at the same angle with the rotating shaft **2160** as a center.

[0055] In other embodiments, the resistance values of eight different gears set in the base point area **2131** and the resistance value identification area **2132** can be changed to four different gears or six different gears or any other desired number of gears.

[0056] Referring to FIG. 10, a knob **2310** is arranged outside the lens assembly **2300**, and an adjusting thread **1330** is arranged on the lens bracket **1300**. Rotating the knob **2310** can drive the lens bracket **1300** to adjust the height of the lens bracket **1300**, thereby adjusting the distance h between the lens bracket **1300** and the mapping disc **2100**, thereby adjusting the focal length. The design of the knob **2310** and the adjusting thread **1330** enables the height of the lens bracket **1300** to be accurately adjusted, so as to realize the precise control of the focal length. By rotating the knob **2310**, the distance between the lens bracket **1300** and the mapping disc **2100** can be flexibly adjusted to meet the different use requirements of users.

[0057] Referring to FIG. 11, the main body shell **1000** is provided with a plurality of speaker holes **4100**, the positions of which correspond to and are above the sound apparatus **4000**, and the setting of the speaker holes **4100** can provide a sound propagation path, making the sound clearer and louder; the position of the speaker hole **4100** corresponding to the sound apparatus **4000** can increase the volume of the sound, so that the sound is louder, and the position of the speaker hole **4100** is above the sound apparatus **4000**, so that the sound propagation direction can be optimized, and the sound propagation can be more uniform. The arrangement of a plurality of speaker holes **4100** can improve the sound effect and enrich the sound quality.

[0058] Referring to FIGS. 2 to 8, the mapping bracket **1200** is also provided with an identification apparatus **1230**. In this embodiment, the identification apparatus **1230** is composed of three spring probes **1231** with different purposes, including a base point probe **1232**, a resistance identification probe **1233** and a gear position identification probe **1234**, wherein the base point probe **1232** is in contact with the base point area **2131**, the resistance identification probe **1233** is in contact with the resistance value identification area **2132**, and the gear position identification probe **1234** is in contact with the gear recognition area **2133**. When the multifunctional image mapping device works, the current resistance value is identified and read by the base point probe **1232** and the resistance identification probe **1233**, and the current gear position is identified by the base point probe **1232** and the gear position identification probe **1234**. The base point probe **1232** is electrically connected with the circuit board **3100**, and can be used for communicating and transmitting electrical signals, and transmitting the currently identified information to the circuit

board **3100**. The circuit board **3100** performs calculation processing, controls the image mapping apparatus **2000** to map the contents of the currently corresponding mapping sheet **2120**, and controls the sound apparatus **4000** to play out the preset audio information of the currently corresponding mapping sheet **2120**.

[0059] Referring to FIG. 2 to FIG. 8, the inner bracket **1100** is provided with a battery assembly **1110**, which can provide working energy for the whole multifunctional image mapping device. The main body shell **1000** includes a battery cover plate **1600** detachably connected with the main body shell **1000**, and the battery cover plate **1600** is detachably connected with the main body shell **1000** through bolts. If the battery assembly **1110** has problems or needs to be replaced, the user can easily replace the battery assembly by disassembling the battery cover plate **1600**, and the battery assembly is located on the inner bracket **1100**, which can protect the battery assembly from the external environment, thereby improving the reliability of the device.

[0060] Referring to FIG. 2 to FIG. 8, the control apparatus **3000** includes a control button **3200**, which is arranged on the main body shell **1000** in a penetrating way and consists of a mapping switch **3210** and a start switch **3220**, both of which are electrically connected to the circuit board **3100**. The start switch **3220** is used to turn on the device, and the mapping switch **3210** controls the switch of the light source **2200**. The mapping switch **3210** and the start switch **3220** have clear functions, and they are used to control the switch of the light source **2200** and turn on the device, respectively, and the user can operate as required.

[0061] As shown in FIG. 12, the main body shell **1000** further includes a cover plate **1700**, and two sides of the top end face of the cover plate **1700** are respectively provided with fixing blocks **1710**, which can be used for fixing the mapping disc **2100**, so as to ensure the stability of the device during use, protect the probe from being damaged, and improve the durability of the device.

[0062] In this embodiment, the inner bracket **1100** is provided with two bolt holes for connecting the circuit board **3100**, and the circuit board **3100** is fixed on the inner bracket **1100** through the bolt holes, so as to ensure the stability and reliability of the circuit board **3100** during the use of device; the maximum diameter of the lower end **1500** of the main body shell **1000** is smaller than that of the upper end **1400** of the main body shell, so that the lower end **1500** is more suitable for users to hold, and the use comfort of the device is improved; there are three lithium batteries in the battery assembly **1110**, which can provide lasting power for the device and keep the normal operation of the device.

[0063] In this embodiment, when the multifunctional image mapping device is used, the battery assembly **1110** prevents the battery from providing power, and the device is powered and turned on by pressing the start switch **3220**. The mapping disc **2100** is rotated to select the content of the mapping sheet **2120** to be mapped, and the mapping switch **3210** is pressed to turn on the light source **2200**, so that the light emitted by the light source **2200** passes through the mapping sheet **2120** by being condensed by the condenser lens **1210**. Then it passes through the second lens **1320** and the first lens **1310** in turn, so that the projection distance is increased and the projected pattern is enlarged. At the same time, the identification apparatus **1230** recognizes the information on the coding disc **2140** on the mapping disc **2100** and communicates with the circuit board **3100** through the resistance value identification area **2132** and the base point area **2131**. The circuit board **3100** is provided with a circuit to process the currently recognized content and map it to the corresponding content, and the sound apparatus **400** plays the audio file. When the current mapping content needs to be changed, the current content can be changed only by rotating the mapping disc **2100**. The first lens **1310** and the second lens **1320** form a lens group, and the distance between the first lens **1310** and the second lens **1320** is fixed. The user can change the distance between the lens group and the mapping disc **2100** by turning the knob **2310** to change the focal length. The circuit board **3100** belongs to the prior art and can be easily implemented by technicians in the basic field, and therefore the structure and working principle of the circuit board **3100** are not described here.

[0064] In this embodiment, the circuit board **3100** can match a large amount of picture content

information, and it is easy to expand, and the product information is rich and diverse, and it is easy to operate. The design of the circuit board **3100** makes data processing more efficient and can quickly match the content information. Users do not need complicated operation procedures, and just needs to turn on the device, rotate the mapping disc **2100** and turn on the mapping switch **3210**, therefore users can choose a plurality of mapping discs **2100** independently, thus having more and richer mapping contents, and playing corresponding audio according to the current mapping contents, thus enhancing the user's experience.

[0065] In other embodiments, the encoding information in the coding disc can be encoded in three-bit binary codes (the three-bit binary code is a coding method that uses three binary bits (0 or 1) to represent information; each binary bit can have two possible states (0 or 1), and thus the three-bit binary code can represent $2^3=8$ different states, including 000; 001; 010; 011; 100; 101; 110; 111, and two state of “0” and “1” in the codes are realized by using the point where the resistance identification probe **1233** and the gear recognition area **2133** contact with the power supply). The three-digit binary code can represent 1-8 pictures; the mapping disc **2100** can also be provided with four mapping sheets **2120**, and the coding information adopts two-bit binary codes, which can represent 1-4 pictures.

[0066] In other embodiments, in addition to the above-mentioned identifying method by different gear resistance values and the method of digital coding (binary coding), the coding information can also adopt analog coding or any other desired coding types.

[0067] In another embodiment, the battery assembly **1110** can adopt different types of batteries such as lithium battery, nickel-metal hydride battery and alkaline battery, or change to various charging methods such as wired charging, wireless charging or solar energy, or a power adapter, so that the device can be directly powered through a power socket; if the device needs to be used in the vehicle, the car charger may be considered for charging the device.

[0068] In other embodiments, the port positions on the main body of the mapping disc **2100** can be randomly combined, for example, the resistance value identification area **2132**, the gear recognition area **2133** and the base point area **2131** are sequentially arranged from the inside to the outside, or in other desired orders.

[0069] In other embodiments, the control apparatus **3000** includes a replacement button (not shown in the figure), which can rotate the mapping disc **2100** to replace the currently projected content.

[0070] In other embodiments, the lower end **1500** of the main body shell **1000** can be provided with anti-slip lines, which can increase the friction between the user's palm and the main body shell **1000**, reduce the sliding of the multifunctional image mapping device caused by unexpected factors, and reduce the risk of damage.

[0071] The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. The use of “adapted to” or “configured to” herein is meant as open and inclusive language that does not foreclose devices adapted to or configured to perform additional tasks or steps. Additionally, the use of “based on” is meant to be open and inclusive, in that a process, step, calculation, or other action “based on” one or more recited conditions or values may, in practice, be based on additional conditions or values beyond those recited. Similarly, the use of “based at least in part on” is meant to be open and inclusive, in that a process, step, calculation, or other action “based at least in part on” one or more recited conditions or values may, in practice, be based on additional conditions or values beyond those recited. Headings, lists, and numbering included herein are for ease of explanation only and are not meant to be limiting.

[0072] The various features and processes described above may be used independently of one another, or may be combined in various ways. All possible combinations and sub-combinations are intended to fall within the scope of the present disclosure. In addition, certain method or process

blocks may be omitted in some implementations. The methods and processes described herein are also not limited to any particular sequence, and the blocks or states relating thereto can be performed in other sequences that are appropriate. For example, described blocks or states may be performed in an order other than that specifically disclosed, or multiple blocks or states may be combined in a single block or state. The example blocks or states may be performed in serial, in parallel, or in some other manner. Blocks or states may be added to or removed from the disclosed examples. Similarly, the example systems and components described herein may be configured differently than described. For example, elements may be added to, removed from, or rearranged compared to the disclosed examples.

[0073] The invention has now been described in detail for the purposes of clarity and understanding. However, those skilled in the art will appreciate that certain changes and modifications may be practiced within the scope of the appended claims.

[0074] Conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain examples include, while other examples do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more examples or that one or more examples necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular example.

Claims

1. A multifunctional image mapping device, comprising a main body shell, an image mapping apparatus, a control apparatus and a sound apparatus; wherein, an inner bracket, a mapping bracket and a lens bracket are arranged inside said main body shell; and wherein, said image mapping apparatus comprises a mapping disc, a light source and a lens assembly, wherein said mapping disc is provided with a plurality of mapping ports, mapping sheets are arranged in the plurality of mapping ports, and said mapping disc is also provided with coding information corresponding to each mapping sheet, wherein said mapping disc is rotatably coupled to said mapping bracket, said lens assembly is arranged in said lens bracket, and said light source is arranged in said mapping bracket, wherein said mapping port can be aligned with the lens assembly and the light source through the rotation of said mapping disc; wherein, said control apparatus and said sound apparatus are arranged on said inner bracket, and said control apparatus comprises a circuit board which is electrically connected with said image mapping apparatus and said sound apparatus; and wherein when a user rotates said mapping disc, said circuit board recognizes the coding information of said mapping sheet aligned with said lens assembly, and controls said light source and said sound apparatus to work according to a preset program.
2. The multifunctional image mapping device according to claim 1, wherein said mapping disc further comprises a mapping disc main body and a mapping disc upper cover, and said mapping port is arranged on said mapping disc upper cover; and said mapping disc main body is divided into a port disc, a coding disc and a mapping sheet placement area, wherein said port disc comprises a base point area, a resistance value identification area and a gear position identification area; said port disc is electrically connected with said circuit board, said coding disc is arranged at a rear side of said port disc, and said coding disc is provided with pre-stored coding information, and said mapping sheets are placed in the mapping sheet placement area, and each mapping sheet corresponds to the coding information on said coding disc.
3. The multifunctional image mapping device according to claim 2, wherein said mapping disc is further provided with a rotating shaft, a center of said mapping disc passes through said rotating shaft, and said mapping ports are distributed on said mapping disc at a same angle with said

rotating shaft as a center.

4. The multifunctional image mapping device according to claim 3, wherein said main body shell is provided with a plurality of speaker holes, and a sound propagation path is provided above said speaker holes and said sound apparatus.

5. The multifunctional image mapping device according to claim 4, wherein said mapping bracket is further provided with a condenser lens, and said condenser lens is arranged above said light source.

6. The multifunctional image mapping device according to claim 5, wherein said mapping bracket comprises an identification probe, and said identification probe is composed of a plurality of spring probes with different functions, and said spring probes comprise a base point probe, a resistance identification probe and a gear position identification probe.

7. The multifunctional image mapping device according to claim 6, wherein said base point probe is in contact with said base point area, said resistance identification probe is in contact with said resistance value identification area, and said gear position identification probe is in contact with said gear position identification area.

8. The multifunctional image mapping device according to claim 7, wherein said base point probe is electrically connected with said circuit board, said base point probe recognizes said coding information and transmits said coding information to said circuit board, and said circuit board controls said image mapping apparatus and said sound apparatus to work.

9. The multifunctional image mapping device according to claim 8, wherein said lens bracket comprises a first lens and a second lens, and said second lens is arranged below said first lens.

10. The multifunctional image mapping device according to claim 9, wherein a battery assembly is arranged inside said inner bracket, and said battery assembly provides working energy for said multifunctional image mapping device to operate.

11. The multifunctional image mapping device according to claim 10, wherein said main body shell has an upper end and a lower end, said inner bracket is arranged at said lower end, and said mapping bracket and said lens bracket are arranged at said upper end.

12. The multifunctional image mapping device according to claim 11, wherein said upper end is fixedly connected to said lower end through arc transition, and both said upper end and said lower end have maximum diameters, and the maximum diameter of said upper end is greater than that of said lower end.

13. The multifunctional image mapping device according to claim 12, wherein said main body shell further comprises a cover plate, and two sides of a top end face of said cover plate are respectively provided with fixing blocks for fixing said mapping disc.

14. The multifunctional image mapping device according to claim 13, wherein said main body shell comprises a battery cover plate detachably connected with said main body shell, and said battery cover plate is detachably connected with said main body shell by bolts.

15. The multifunctional image mapping device according to claim 14, wherein said control apparatus comprises a control button, which is arranged on said main body shell in a penetrating way, and comprises a mapping switch and a start switch, both of which are electrically connected with said circuit board.

16. A multifunctional image mapping device, comprising a main body shell, an image mapping apparatus, a control apparatus and a sound apparatus; wherein, an inner bracket, a mapping bracket, a lens bracket and a knob are arranged inside said main body shell; and wherein, said image mapping apparatus comprises a mapping disc, a light source and a lens assembly, wherein said mapping disc is provided with a plurality of mapping ports, mapping sheets are arranged in said mapping ports, and said mapping disc is also provided with coding information corresponding to each mapping sheet, wherein said mapping disc is rotatably coupled to said mapping bracket, said lens assembly is arranged in said lens bracket, and said light source is arranged in said mapping bracket, wherein said mapping port can be aligned with said lens assembly and said light source

through the rotation of said mapping disc; wherein said knob is operatively connected to said lens assembly to adjust a focal length of said lens assembly; and wherein, said control apparatus and said sound apparatus are arranged on said inner bracket, and said control apparatus comprises a circuit board, wherein said circuit board is provided with an identification probe which is in contact with said mapping disc, and when said mapping disc rotates, said identification probe can read the coding information of said mapping sheet aligned with said lens assembly; and wherein when said control apparatus receives an input instruction from a user, said control apparatus controls said light source and said sound apparatus to work according to a preset program.

17. The multifunctional image mapping device according to claim 16, wherein said knob is arranged at an outer side of said lens bracket, and said lens bracket is provided with an adjusting thread, and said knob is rotationally matched with a rotating adjusting thread, and a distance H between said lens bracket and said mapping disc can be adjusted by rotating said knob, thereby adjusting the focal length.

18. A method for mapping an image, said method comprising providing a multifunctional image mapping device comprising a main body shell, an image mapping apparatus, a control apparatus and a sound apparatus; wherein, an inner bracket, a mapping bracket, a lens bracket and a knob are arranged inside said main body shell; and wherein, said image mapping apparatus comprises a mapping disc, a light source and a lens assembly, wherein said mapping disc is provided with a plurality of mapping ports, mapping sheets are arranged in said mapping ports, and said mapping disc is also provided with coding information corresponding to each mapping sheet, wherein said mapping disc is rotatably coupled to said mapping bracket, said lens assembly is arranged in said lens bracket, and said light source is arranged in said mapping bracket, wherein said mapping port can be aligned with said lens assembly and said light source through the rotation of said mapping disc; wherein said knob is operatively connected to said lens assembly to adjust a focal length of said lens assembly; and wherein, said control apparatus and said sound apparatus are arranged on said inner bracket, and said control apparatus comprises a circuit board, wherein said circuit board is provided with an identification probe which is in contact with said mapping disc, and when said mapping disc rotates, said identification probe can read the coding information of said mapping sheet aligned with said lens assembly; and wherein when said control apparatus receives an input instruction from a user, said control apparatus controls said light source and said sound apparatus to work according to a preset program; and the method comprises the following steps: turning on said multifunctional image mapping device through said control apparatus; rotating said mapping disc and selecting a mapping sheet to be mapped; rotating said knob to select an appropriate focal length; and mapping by said control apparatus.

19. The method according to claim 18, wherein before turning on said multifunctional image mapping device through said control apparatus, a user can choose to place different mapping discs.

20. The method according to claim 19, wherein when the user uses said multifunctional image mapping device, said mapping disc can be manually rotated to select different mapping sheets, thereby mapping contents of different mapping sheets.
