

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12403010
B2
September 02, 2025
Green, II; John M. et al.

Knee replacement implant having stackable spacers

Abstract

A knee replacement prosthesis includes a distal femoral implant, including a femoral head portion, including an outer arcuate surface, and interior posterior surface, an interior distal surface disposed at a first angle with respect to the interior posterior surface, and a first interior intermediate surface joining the interior posterior surface and the interior distal surface and being disposed at a second angle with respect to the interior posterior surface and at a third angle with respect to the interior distal surface. The distal femoral implant includes stackable femoral spacers secured to at least one of the interior posterior surface and the interior distal surface, thereby adjusting an aggregate spacing between the interior posterior surface and/or the interior distal surface and a resected surface of a distal femur of the patient. A tibial implant is also provided. Related methods of use of either implant or both are also provided.

Inventors: Green, II; John M. (Leander, TX), Small; Laura (Austin, TX)
Applicant: Encore Medical, LP (Austin, TX)
Family ID: 79021639
Assignee: Encore Medical, LP (Austin, TX)
Appl. No.: 17/537256
Filed: November 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220168111 A1	Jun. 02, 2022

Related U.S. Application Data

us-provisional-application US 63119802 20201201

Publication Classification

Int. Cl.: A61F2/38 (20060101); A61F2/30 (20060101)

U.S. Cl.:

CPC A61F2/3859 (20130101); A61F2/385 (20130101); A61F2002/30599 (20130101); A61F2/389 (20130101)

Field of Classification Search

CPC: A61F (2/3859); A61F (2002/30599); A61F (2002/30151); A61F (2002/30158); A61F (2/38); A61F (2/40); A61F (2/4081)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5609645	12/1996	Vinciguerra	N/A	N/A
5702464	12/1996	Lackey et al.	N/A	N/A
5755800	12/1997	O'Neil	623/20.16	A61F 2/30734
5984969	12/1998	Matthews et al.	N/A	N/A
6074424	12/1999	Perrone, Jr. et al.	N/A	N/A
7892288	12/2010	Blaylock et al.	N/A	N/A
8167888	12/2011	Steffensmeier	N/A	N/A
8506645	12/2012	Blaylock et al.	N/A	N/A
8603101	12/2012	Claypool et al.	N/A	N/A
8632599	12/2013	Bonitati et al.	N/A	N/A
8968413	12/2014	Cook et al.	N/A	N/A
9011459	12/2014	Claypool et al.	N/A	N/A
9044326	12/2014	Blaylock et al.	N/A	N/A
9144495	12/2014	Lin et al.	N/A	N/A
9149206	12/2014	Claypool et al.	N/A	N/A
9265614	12/2015	Blaylock et al.	N/A	N/A
9427337	12/2015	Claypool et al.	N/A	N/A
9468531	12/2015	Cook et al.	N/A	N/A
9532879	12/2016	Lieberman et al.	N/A	N/A
9592133	12/2016	Toler et al.	N/A	N/A
9597090	12/2016	Claypool et al.	N/A	N/A
9763807	12/2016	Claypool et al.	N/A	N/A
9901331	12/2017	Toler et al.	N/A	N/A
9907664	12/2017	Blaylock et al.	N/A	N/A
9918845	12/2017	Roby et al.	N/A	N/A
10010330	12/2017	Claypool et al.	N/A	N/A
10052207	12/2017	Chernosky et al.	N/A	N/A
10085841	12/2017	Blaylock et al.	N/A	N/A
10188530	12/2018	Claypool et al.	N/A	N/A
2004/0122521	12/2003	Lee et al.	N/A	N/A
2008/0051908	12/2007	Angibaud et al.	N/A	N/A

2008/0167722	12/2007	Metzger et al.	N/A	N/A
2012/0185053	12/2011	Berger	N/A	N/A
2012/0209391	12/2011	Cipolletti et al.	N/A	N/A
2013/0013077	12/2012	Metzger	623/20.35	A61F 2/3859
2013/0079671	12/2012	Stein et al.	N/A	N/A
2014/0222155	12/2013	Metzger et al.	N/A	N/A
2016/0278925	12/2015	Roby et al.	N/A	N/A
2017/0333194	12/2016	Pierce et al.	N/A	N/A
2018/0098856	12/2017	Blaylock et al.	N/A	N/A
2019/0000632	12/2018	Blaylock et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2651343	12/2012	EP	N/A
2822508	12/2014	EP	N/A
2830543	12/2014	EP	N/A
2682073	12/2014	EP	N/A
2710980	12/2014	EP	N/A
2918235	12/2014	EP	N/A
2921141	12/2014	EP	N/A
2953583	12/2014	EP	N/A
2777619	12/2015	EP	N/A
3071152	12/2015	EP	N/A
3335674	12/2019	EP	N/A
3057760	12/2017	FR	N/A
2014180559	12/2013	JP	N/A
9730661	12/1996	WO	N/A
2020093100	12/2019	WO	N/A

OTHER PUBLICATIONS

Examination Report mailed on Apr. 22, 2024 in AU 2021391408. cited by applicant
International Preliminary Report on Patentability received for WO Patent Application Serial No. PCT/US21/061017 dated Jun. 15, 2023, 10 pages. cited by applicant
Office Action mailed on Mar. 26, 2024 in JP 2023-533220. cited by applicant
Examination report No. 2 mailed on Jul. 9, 2024 in AU 2021391408. cited by applicant
Office Action mailed on Jul. 2, 2024 in JP 2023-533220. cited by applicant
Office Action mailed on Sep. 9, 2024 in CA 3198140. cited by applicant

Primary Examiner: Aleman; Sarah W

Attorney, Agent or Firm: Eversheds Sutherland (US) LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of U.S. Provisional Application No. 63/119,802, which was filed on Dec. 1, 2020, and the contents of which are incorporated by reference herein in its entirety.

BACKGROUND

(1) Partial and/or total knee arthroplasty are commonly used to relieve pain and to correct mobility

issues related to, and/or resulting from, degradation of one or more portions of one or both of a tibia and a distal femur within a patient's knee. However, as cost constraints become more prevalent, implant solutions that minimize inventory are becoming more important factors in the design and selection for use of such implant solutions. Accordingly, there is a need for providing implant solutions that minimize inventory and cost in both manufacture and use, while expanding the ability to accommodate more variability in the knees of prospective patients.

(2) It should be noted that this Background is not intended to be an aid in determining the scope of the claimed subject matter nor be viewed as limiting the claimed subject matter to implementations that solve any or all of the disadvantages or problems presented above. The discussion of any technology, documents, or references in this Background section should not be interpreted as an admission that the material described is prior art to any of the subject matter claimed herein.

SUMMARY

(3) In one implementation, a knee replacement prosthesis for a patient is provided. The prosthesis includes a tibial baseplate implant. The tibial baseplate implant includes a tibial baseplate including an upper surface and an underside. The tibial baseplate implant includes a plurality of stackable tibial spacers configured to be stacked directly on top of one another and secured directly to the underside of the tibial baseplate, thereby adjusting an aggregate spacing between the underside of the tibial base plate and a resected surface of a proximal tibia of the patient.

(4) In another implementation, another knee replacement prosthesis for a patient is provided. The prosthesis includes a distal femoral implant. The distal femoral implant includes a femoral head portion. The femoral head portion includes an outer arcuate surface configured to mate with one of a tibial baseplate or a proximal surface of a tibia of the patient. The femoral head portion includes an interior posterior surface. The femoral head portion includes an interior distal surface disposed at a first angle with respect to the interior posterior surface. The femoral head portion includes a first interior intermediate surface joining the interior posterior surface and the interior distal surface such that the first interior intermediate surface is disposed at a second angle with respect to the interior posterior surface and at a third angle with respect to the interior distal surface. The distal femoral implant includes a plurality of stackable femoral spacers configured to be secured to at least one of the interior posterior surface and the interior distal surface, thereby adjusting an aggregate spacing between the at least one of the interior posterior surface or the interior distal surface and a resected surface of a distal femur of the patient.

(5) In yet another implementation, a method of using a knee replacement prosthesis for replacing at least a portion of a knee of a patient is provided. The method includes resecting a proximal portion of a tibia of the patient to form a resected surface of the tibia. The method includes stacking a plurality of stackable tibial spacers directly on top of one another. The method includes securing the plurality of stackable tibial spacers directly to an underside of a tibial baseplate of a tibial baseplate implant. The method includes securing the tibial baseplate implant to the resected portion of the tibia, thereby providing a desired aggregate spacing between the underside of the tibial baseplate and the resected surface of the tibia.

(6) In yet another implementation, another method of using a knee replacement prosthesis for replacing at least a portion of a knee of a patient is provided. The method includes resecting a distal portion of a femur of the patient to form a resected surface of the femur. The method includes stacking a plurality of stackable femoral spacers. The method includes securing the plurality of stackable femoral spacers to at least one of an interior posterior surface and an interior distal surface of a femoral head portion of a distal femoral implant. The interior distal surface is disposed at a first angle with respect to the interior posterior surface. The femoral head portion further includes an outer arcuate surface configured to mate with one of a tibial baseplate or a proximal surface of a tibia of the patient, and a first interior intermediate surface joining the interior posterior surface and the interior distal surface such that the first interior intermediate surface is disposed at a second angle with respect to the interior posterior surface and at a third angle with respect to the

interior distal surface. The method includes securing the distal femoral implant to the resected surface of the femur, thereby providing a desired aggregate spacing between the at least one of the interior posterior surface or the interior distal surface of the femoral head portion and the resected surface of the femur.

(7) It is understood that various configurations of the subject technology will become apparent to those skilled in the art from the disclosure, wherein various configurations of the subject technology are shown and described by way of illustration. As will be realized, the subject technology is capable of other and different configurations and its several details are capable of modification in various other respects, all without departing from the scope of the subject technology. Accordingly, the summary, drawings and detailed description are to be regarded as illustrative in nature and not as restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Various embodiments are discussed in detail in conjunction with the Figures described below, with an emphasis on highlighting the advantageous features. These embodiments are for illustrative purposes only and any scale that may be illustrated therein does not limit the scope of the technology disclosed. These drawings include the following figures, in which like numerals indicate like parts.

(2) FIG. 1 shows a side view of tibial baseplate implant, in accordance with some embodiments;

(3) FIG. 2 shows a partial cutaway view of a distal femoral implant, in accordance with some embodiments;

(4) FIG. 3A shows a partial cutaway view of the distal femoral implant of FIG. 2 including one or more spacers disposed therein, in accordance with some embodiments;

(5) FIG. 3B shows the partial cutaway view of FIG. 3A further including additional spacers, each stacked on one of the spacers illustrated in FIG. 3A, in accordance with some embodiments;

(6) FIG. 3C shows a partial cutaway view of the distal femoral implant of FIG. 2 further including additional pairs of stacked spacers, as viewed from an opposite side of the distal femoral implant as FIGS. 2-3B, in accordance with some embodiments;

(7) FIG. 3D shows the partial cutaway view of FIG. 3A and further including the additional pairs of stacked spacers of FIG. 3C, in accordance with some embodiments;

(8) FIG. 4 shows a cutaway view of the distal femoral implant of FIG. 3D as viewed along the cutline 4 and in the direction of the cutline arrows illustrated in FIG. 3D, in accordance with some embodiments;

(9) FIG. 5 shows a top view of the distal femoral implant of any of FIGS. 2-4 as viewed in the direction of arrow B illustrated in FIG. 3D, in accordance with some embodiments;

(10) FIG. 6 shows a flowchart relating to a method for using a tibial baseplate implant, in accordance with some embodiments; and

(11) FIG. 7 shows another flowchart relating to a method for using a distal femoral implant, in accordance with some embodiments.

DETAILED DESCRIPTION

(12) The following description and examples illustrate some exemplary implementations, embodiments, and arrangements of the disclosed invention in detail. Those of skill in the art will recognize that there are numerous variations and modifications of this invention that are encompassed by its scope. Accordingly, the description of a certain example embodiments should not be deemed to limit the scope of the present invention.

(13) Implementations of the technology described herein are directed generally to implants for use in partial or total knee arthroplasty. The apparatuses, systems and/or methods described herein

simultaneously solve multiple problems, at least in part, by reducing a number of components of an implant or implant system while, counterintuitive, accommodating increased variability in anatomical characteristics of one or both knees of a wide range of candidate patients for partial or total knee arthroplasty.

(14) Several embodiments of a knee replacement implant having one or more stackable spacers according to this disclosure will now be described in connection with FIGS. 1-6. Within this disclosure, such stackable spacers may also be known as, or called “augments.” Discussion will first turn to embodiments of a tibial baseplate implant **100**, as described in connection with at least FIG. 1 below.

(15) FIG. 1 shows a side view of a tibial baseplate implant **100**, in accordance with some embodiments. Tibial baseplate implant **100** can include a tibial baseplate **110** having an upper surface **112** configured to be disposed against at least one of a distal femur implant (as will be described in more detail below) or a distal femur within a patient's knee, and an underside **114** configured to receive one or more stackable tibial spacers **140a-140c**. Tibial baseplate **110** further comprises a distal transitional portion **120** coupled to, couplable to, or monolithically integrated with underside **114** of tibial baseplate **110** at a proximal portion of distal transitional portion **120**, and a stem **130** coupled to, couplable to, or monolithically integrated with a distal portion of distal transitional portion **120**.

(16) Stem **130** is configured to be disposed longitudinally into and secured within a cavity of a tibia of a patient. In some embodiments, stem **130** has a substantially cylindrical shape and a distal end that tapers to a point or substantially rounded point. However, stem **130** can have any suitable shape. In some embodiments, stem **130** comprises one or more longitudinal grooves or fluted or recessed portions **132a**, **132b**, **132c**. In some embodiments, such grooves or fluted or recessed portions **132a**, **132b**, **132c** may increase adhesion of stem **130** to inner surfaces of the tibia of the patient.

(17) As illustrated, in some embodiments, distal transitional portion **120** may have a shape that generally tapers from its proximal end nearest underside **114** of tibial baseplate **110** toward its distal end nearest stem **130**. In some embodiments, distal transitional portion **120** can comprise one or more fins, protrusions or protrusive portions that extend laterally away from distal transitional portion **120**. Such fins, protrusions or protrusive portions may aid adhesion of distal transitional portion **120** to a surface of the tibia of the patient. In some embodiments, such fins, protrusions or protrusive portions may additionally or alternatively aid in the securing and/or aligning of one or more stackable tibial spacers **140a**, **140b**, **140c** to underside **114** of tibial baseplate **110**, as will be described below.

(18) Tibial baseplate implant **100** may further comprise one or more stackable spacers **140a-140c**. In some embodiments, one or more of stackable spacers **140a-140c** (e.g., spacers **140a** and **140b** as illustrated) are configured to be secured directly to underside **114** of tibial baseplate **110** by one or more screws **250**. In some embodiments, one or more of stackable spacers **140a-140c** (e.g., spacers **140b** and **140c** as illustrated) are configured to be stacked directly on top of one another and secured to underside **114** of tibial baseplate **110** by one or more screws **250**.

(19) In some embodiments, spacers **140a-140c** all have a same form factor, size or radius along their perimeters. In some embodiments, one or more of spacers **140a-140c** have a different form factor, size or radius along its perimeter compared to one or more other of spacers **140a-140c**. In some embodiments, spacers **140a-140c** have a substantially circular, doughnut-shaped (e.g., substantially circular and having an aperture or opening configured to receive a portion of distal transition portion **120**), or semicircular form factor such that they fit around and/or adjacent to at least a portion of distal transitional portion **120** and/or of stem **130**. However, spacers **140a-140c** may have any suitable form factor or shape.

(20) In some embodiments, opposing stackable surfaces of each of spacers **140a-140c** are substantially planar and parallel to one another such that, when stacked, negligible or no open

space is present between mating stackable surfaces of adjacently stacked spacers.

(21) In some embodiments, spacers **140a-140c** all have a same thickness (e.g., 5 mm, although any suitable thickness is also contemplated). In some embodiments, one or more of spacers **140a-140c** have a different thickness (e.g., 7 mm, 8 mm or 10 mm, although any other suitable thickness is also contemplated) from one or more other of spacers **140a-140c**. By stacking one or more spacers **140a-140c** having the same or different thicknesses, a greater variety of aggregate spacings between underside **114** of tibial baseplate **110** and a resected surface of a tibia of the patient can be obtained compared to systems in which spacers having same or different thicknesses are not specifically designed or configured to be so stacked. Moreover, stacking spacers **140a-140c** allows for a smaller number of spacers to be utilized or inventoried while still providing an increased number of possible aggregate spacings at a lower cost of manufacture, use and/or inventory than is possible with other implant systems in which spacers are not specifically designed or configured to be so stacked.

(22) Knee replacement prostheses according to the present disclosure can further or alternatively include a distal femoral implant **200** and one or more stackable femoral spacers **242a**, **242b**, **244a**, **244b**, **248a**, **248b**, **249a**, **249b** as will be described in more detail below. Discussion now turns to embodiments of distal femoral implant **200**, as described in connection with at least FIGS. 2-5 below.

(23) FIG. 2 shows a partial cutaway view of distal femoral implant **200**, in accordance with some embodiments. Distal femoral implant **200** comprises a femoral head portion **210** and a stem **230** coupled to, couplable to, or monolithically integrated with femoral head portion **210**.

(24) Stem **230** is configured to be disposed longitudinally into and secured within a cavity of a femur of a patient. In some embodiments, stem **230** has a substantially cylindrical shape. However, stem **230** can have any suitable shape. In some embodiments, stem **230** comprises one or more longitudinal grooves or fluted or recessed portions **232a**, **232b**. In some embodiments, such grooves or fluted or recessed portions **232a**, **232b** may increase adhesion of stem **230** to the inner surfaces of the femur of the patient. A longitudinal direction of extension of stem **230** is illustrated by dotted line **250** in FIG. 2.

(25) Femoral head portion **210** comprises an outer arcuate surface **212** configured to mate with at least one of upper surface **112** of tibial baseplate **110** (see, e.g., FIG. 1) or a proximal surface of a tibia of the patient. Distal femoral implant **200** further comprises an interior posterior surface **214**, an interior distal surface **218** disposed at a first angle ($\theta_{\text{sub.1}}$) with respect to interior posterior surface **214**, and an interior intermediate surface **216** joining interior posterior surface **214** and interior distal surface **218**. The interior intermediate surface is disposed at a second angle ($\theta_{\text{sub.2}}$) with respect to interior posterior surface **214** and at a third angle ($\theta_{\text{sub.3}}$) with respect to interior distal surface **218**. In some embodiments, the first angle ($\theta_{\text{sub.1}}$) is substantially 90°. In some but not necessarily all such embodiments, interior posterior surface **214** may be substantially parallel to longitudinal direction of extension **250** of stem **230** and interior distal surface **218** may be substantially perpendicular to longitudinal direction of extension **250** of stem **230**. However, any suitable first angle ($\theta_{\text{sub.1}}$) and relative orientation(s) of interior posterior surface **214** and interior distal surface **218** are also contemplated.

(26) In some embodiments, the second angle ($\theta_{\text{sub.2}}$) between interior posterior surface **214** and interior intermediate surface **216** is substantially 45°. In such embodiments, where the first angle ($\theta_{\text{sub.1}}$) is also 90°, the third angle ($\theta_{\text{sub.3}}$) between interior intermediate surface **216** and interior distal surface **218** is also substantially 45° (i.e., second and third angles $\theta_{\text{sub.2}}$, $\theta_{\text{sub.3}}$ are substantially equal). Such 90°, 45°, 45° embodiments provide a unique advantage, as will be described in more detail below in connection with FIGS. 3A-3D and 4, in that spacers **242a**, **242b**, **244a**, **244b** and/or spacers **248a**, **248b**, **249a**, **249b** having beveled edges with a similar 45° angle can be stacked maximally close to one another, with negligible or no spacing between adjacent mating edges of the spacers, and in completely interchangeable, flipped (e.g., mirrored)

orientations against each of interior posterior, intermediate and distal surfaces **214**, **216**, **218**. However, any suitable second and third angles ($\theta_{\text{sub.2}}$ and $\theta_{\text{sub.3}}$) are also contemplated. Though, since first, second and third angles ($\theta_{\text{sub.1}}$, $\theta_{\text{sub.2}}$, $\theta_{\text{sub.3}}$) form a triangle, their sum will add to 180° .

(27) In some embodiments, distal femoral implant **200** further comprises an interior anterior surface **219** and a second interior intermediate surface **217** joining interior distal surface **218** and interior anterior surface **219**. In some embodiments, interior anterior surface **219** is disposed at a fourth angle ($\theta_{\text{sub.4}}$) with respect to interior distal surface **218**. Second interior intermediate surface **217** is disposed at a fifth angle ($\theta_{\text{sub.5}}$) with respect to interior anterior surface **219** and at a sixth angle ($\theta_{\text{sub.6}}$) with respect to interior distal surface **218**. In some embodiments, as illustrated in FIG. 2, the fourth angle ($\theta_{\text{sub.4}}$) is slightly greater than 90° . Accordingly, in some but not necessarily all such embodiments, interior anterior surface **219** may extend slightly laterally and away from longitudinal direction of extension **250** of stem **230** when followed from distal to proximal edge. Fourth angle ($\theta_{\text{sub.4}}$) being slightly greater than 90° has a benefit of increasing a size of a distal opening of an interior cavity of distal femoral implant **200** in which all above-mentioned interior surfaces **214**, **216** and **217-219** are at least partly disposed, for more easily receiving a resected portion of a femur of the patient. However, any suitable fourth angle ($\theta_{\text{sub.4}}$) is also contemplated.

(28) In some embodiments, the fifth angle ($\theta_{\text{sub.5}}$) between second interior intermediate surface **217** and interior anterior surface **219** is less than 45° and the sixth angle ($\theta_{\text{sub.6}}$) between interior distal surface **218** and second interior intermediate surface **217** is substantially 45° (i.e., second, third and sixth angles $\theta_{\text{sub.2}}$, $\theta_{\text{sub.3}}$, $\theta_{\text{sub.6}}$ are substantially equal). Embodiments where the sixth angle ($\theta_{\text{sub.6}}$) is also 45° further supports the unique advantage that spacers **242a**, **242b**, **244a**, **244b** and/or **248a**, **248b**, **249a**, **249b** having beveled edges with a similar 45° angle, can be stacked maximally close to one another, with negligible or no spacing between adjacent mating edges of the spacers, and in completely interchangeable, flipped (e.g., mirrored) orientations against each of interior posterior, first and second intermediate and distal surfaces **214**, **216-218**. However, any suitable fifth and sixth angles ($\theta_{\text{sub.5}}$ and $\theta_{\text{sub.6}}$) are also contemplated. Though, since fourth, fifth and sixth angles ($\theta_{\text{sub.4}}$, $\theta_{\text{sub.5}}$, $\theta_{\text{sub.6}}$) form a triangle, their sum will also add to 180° .

(29) In some embodiments, one, some or all of interior posterior surface **214**, interior intermediate surface **216**, interior distal surface **218**, second interior intermediate surface **217** and interior anterior surface **219** are substantially planar.

(30) In some embodiments, distal femoral implant **200** comprises a median (or central dividing portion) **260** disposed substantially centrally therein. In some embodiments, stem **230** couples to, is coupleable to, or is monolithically integrated with femoral head portion **210** at median **260**. In some embodiments, a first portion of one or more of interior posterior surface **214**, interior intermediate surface **216**, interior distal surface **218**, second interior intermediate surface **217** and interior anterior surface **219** are disposed to a first side of median **260** and a second portion of one or more of interior posterior surface **214**, interior intermediate surface **216**, interior distal surface **218**, second interior intermediate surface **217** and interior anterior surface **219** are disposed to a second side of median **260** opposite the first side. Accordingly, all previously described angles between meeting surfaces of distal femoral head portion **210** (e.g., $\theta_{\text{sub.1}}$, $\theta_{\text{sub.2}}$, $\theta_{\text{sub.3}}$, $\theta_{\text{sub.4}}$, $\theta_{\text{sub.5}}$, $\theta_{\text{sub.6}}$) may have the same characteristics at each of the first and second portions of each of those meeting surfaces to either side of median **260**.

(31) As illustrated in FIG. 2, distal femoral implant **200** may further comprise at least one threaded aperture **292** configured to secure one or more stackable spacers to interior distal surface **218** utilizing a fastener **250**, which in some embodiments may be a threaded screw. FIG. 2 also illustrates distal femoral implant **200** to further comprise at least one threaded aperture **296** configured to secure one or more stackable spacers to interior posterior surface **214** utilizing a

fastener **250**, which in some embodiments may be a threaded screw.

(32) As illustrated in at least FIG. 3C, distal femoral implant **200** may further comprise at least one additional threaded aperture **294** configured to secure one or more stackable spacers to the portion of interior distal surface **218** disposed to an opposite side of median **260** from the portion in which threaded aperture **292** is disposed, utilizing a similar or same fastener **250**. Likewise, distal femoral implant **200** may further comprise at least one additional threaded aperture **298** configured to secure one or more stackable spacers to the portion of interior posterior surface **214** disposed to an opposite side of median **260** from the portion in which threaded aperture **296** is disposed, utilizing a similar or same fastener **250**.

(33) Distal femoral implant **200** may further comprise one or more stackable spacers **242a**, **242b**, **244a**, **244b**, **248a**, **248b**, **249a**, **249b**. FIGS. 3A-3D show different partial cutaway views of distal femoral implant **200** of FIG. 2 including different configurations of such spacers **242a**, **242b**, **244a**, **244b**, **248a**, **248b**, **249a**, **249b**.

(34) For example, a first posterior spacer **242a** is configured to be secured directly to interior posterior surface **214** utilizing one or more screws **250** and a first distal spacer **244a** is configured to be secured directly to interior distal surface **218** utilizing one or more screws **250**, in accordance with some embodiments. First posterior spacer **242a** and first distal spacer **244a** are illustrated as being disposed on portions of interior posterior surface **214** and on portions of interior distal surface **218** that are each disposed to a first side of median **260**.

(35) FIG. 3B shows the partial cutaway view of distal femoral implant **200** of FIGS. 2 and 3A, further including a second posterior spacer **242b** stacked in a flipped (e.g., mirrored) orientation and secured directly on first posterior spacer **242a** utilizing one or more screws and a second distal spacer **244b** stacked in a flipped (e.g., mirrored) orientation and secured directly on first distal spacer **244a** utilizing one or more screws **250**, in accordance with some embodiments.

(36) In some embodiments, each of first and second posterior spacers **242a**, **242b** have a same shape, size and form factor. In some embodiments, each of first and second distal spacers **244a**, **244b** have a same shape, size and form factor. In yet other embodiments, all of first and second posterior spacers **242a**, **242b** and first and second distal spacers **244a**, **244b** have a same shape, size and form factor, for example as shown for first and second posterior spacers **242a**, **242b** or, for example as shown for first and second distal spacers **244a**, **244b**.

(37) In some embodiments, opposing stackable surfaces of each of spacers **242a**, **242b**, **244a**, **244b** are substantially planar and parallel to one another such that, when stacked, negligible or no open space is present between mating stackable surfaces of adjacently stacked spacers.

(38) In some embodiments, spacers **242a**, **242b**, **244a**, **244b** all have a same thickness (e.g., 5 mm, although any suitable thickness is also contemplated). In some embodiments, first and second posterior spacers **242a**, **242b** have a same first thickness, while first and second distal spacers **244a**, **244b** have a same second thickness. In yet other embodiments, one or more of spacers **242a**, **242b**, **244a**, **244b** have a different thickness (e.g., 7 mm, 8 mm or 10 mm, although any other suitable thickness is also contemplated) from one or more other of spacers **242a**, **242b**, **244a**, **244b**. By stacking one or more of posterior spacers **242a**, **242b**, having the same or different thicknesses, a greater variety of aggregate spacings between interior posterior surface **214** and a resected surface of a femur of the patient can be obtained compared to systems in which spacers are not specifically designed or configured to be so stacked. Similarly, by stacking one or more of distal spacers **244a**, **244b**, having the same or different thicknesses, a greater variety of aggregate spacings between interior distal surface **218** and a resected surface of a femur of the patient can be obtained compared to systems in which spacers are not specifically designed or configured to be so stacked. Moreover, stacking posterior spacers **242a**, **242b** or distal spacers **244a**, **244b** allows for a smaller total number of spacers to be utilized or inventoried while still providing an increased number of possible aggregate spacings at a lower cost of manufacture, use and/or inventory than is possible with other implant systems in which spacers are not specifically designed or configured to be so

stacked.

(39) As illustrated in FIGS. 3A and 3B, first and second posterior spacers **242a**, **242b** each include at least one respective beveled edge **241a**, **241b** having a bevel angle ($\theta_{\text{sub.7}}$). In some embodiments, this bevel angle ($\theta_{\text{sub.7}}$) is substantially equal to the second angle ($\theta_{\text{sub.2}}$) between interior posterior surface **214** and interior intermediate surface **216**, thereby allowing at least first posterior spacer **242a** to simultaneously abut interior posterior surface **214** along its long surface and interior intermediate surface **216** along beveled edge **241a**. However, any suitable bevel angle ($\theta_{\text{sub.7}}$) is also contemplated. In some embodiments, first and second posterior spacers **242a**, **242b** each include an edge **243a**, **243b** opposite beveled edge **241a**, **241b** disposed perpendicular to the direction of extension of their long surfaces.

(40) As illustrated in FIGS. 3A and 3B, first and second distal spacers **244a**, **244b** each include respective opposing beveled edges **245a**, **245b** having respective bevel angle ($\theta_{\text{sub.9}}$) and **246a**, **246b** having respective bevel angle ($\theta_{\text{sub.10}}$). In some embodiments, bevel angle ($\theta_{\text{sub.9}}$) is substantially equal to the third angle ($\theta_{\text{sub.3}}$) between interior intermediate surface **216** and interior distal surface **218**, thereby allowing at least first distal spacer **244a** to simultaneously abut interior distal surface **218** along its long surface and interior intermediate surface **216** along beveled edge **245a**. However, any suitable bevel angle ($\theta_{\text{sub.9}}$) is also contemplated. In some embodiments, bevel angle ($\theta_{\text{sub.10}}$) is substantially equal to the sixth angle ($\theta_{\text{sub.6}}$) between interior distal surface **218** and second interior intermediate surface **217**, thereby allowing at least first distal spacer **244a** to simultaneously abut interior distal surface **218** along its long surface and interior intermediate surface **216** along beveled edge **246a**. However, any suitable bevel angle ($\theta_{\text{sub.10}}$) is also contemplated.

(41) As illustrated in FIG. 3B, second posterior spacer **242b** is configured to be stacked directly on and in a flipped (e.g., mirrored) orientation compared to first posterior spacer **242a** such that respective beveled edges **241a**, **241b** of first and second posterior spacers **242a**, **242b** meet at a common point. Similarly, second distal spacer **244b** is configured to be stacked directly on and in a flipped (e.g., mirrored) orientation compared to first distal spacer **244a** such that respective beveled edges **245a**, **245b** meet at a first common point and respective beveled edges **246a**, **246b** meet at a second common point.

(42) Embodiments where all of angles ($\theta_{\text{sub.2}}$, $\theta_{\text{sub.3}}$, $\theta_{\text{sub.6}}$, $\theta_{\text{sub.7}}$, $\theta_{\text{sub.9}}$, and $\theta_{\text{sub.10}}$) are substantially 45° also allow for simultaneous stacking of at least 2 posterior spacers on interior posterior surface **214** and at least 2 distal spacers on interior distal surface **218**, in some but not necessarily all such embodiments, with negligible or substantially no space between adjacent mating surfaces of the spacers, since beveled edge **241b** of second posterior spacer **242b** and beveled edge **245b** of second distal spacer **244b** align substantially parallel and adjacent to one another (see FIG. 3B).

(43) FIG. 3C illustrates a partial cutaway view of distal femoral implant **200** of FIG. 2 as viewed from the opposite side of median **260** from the view of FIGS. 2-3B. Threaded apertures **294** and **298** are substantially identical to respective threaded apertures **292** and **296**, being configured to receive similar or identical fasteners **250** but disposed within portions of their respective surfaces disposed to an opposite side of median **260**. FIG. 3C similarly illustrates spacers **248a** and **248b**, which are substantially identical to respective spacers **244a**, **244b** except being disposed or disposable an opposite side of median **260**. FIG. 3C similarly illustrates spacers **249a** and **249b**, which are substantially identical to respective spacers **242a**, **242b** except being disposed or disposable an opposite side of median **260**.

(44) For ease of visualization and understanding, FIG. 3D illustrates the partial cutaway view of distal femoral implant **200** shown in FIGS. 2 and 3A, however, further comprising spacers **248a**, **248b**, **249a**, **249b**. Of course, in FIG. 3D the view of spacer **249a** is obstructed by spacer **242a** and median **260**, the view of spacer **249b** is partially obstructed by median **260**, and the view of spacers **248a**, **248b** is entirely obstructed by median **260**.

(45) FIG. 4 illustrates a cutaway view of distal femoral implant **200** as shown in FIG. 3D but viewed along the cut line **4** and in the direction of the cut-line arrows, in accordance with some embodiments. As illustrated, one or more (e.g., each) of spacers **242a** (and **242b**), **244a** (and **244b**), **248a**, **248b**, **249a**, **249b** comprises a slot **570** having a substantially larger lateral dimension than an anterior-posterior dimension. Slot **570** is configured to receive a respective fastener **250**. The larger lateral dimension of slot **570** compared to its anterior-posterior dimension allows a user and/or surgeon to adjust the medial/lateral position of the spacer(s) with respect to fasteners **250** and, so also, with respect to distal femoral implant **200**, any of its features, and/or any bone deficiencies. This allows the surgeon to optimize the placement of the spacers depending on those bone deficiencies to maximize coverage.

(46) FIG. 5 illustrates a top view of distal femoral implant **200** as viewed in the direction of arrow B, for example, in FIG. 3D, in accordance with some embodiments. FIG. 5 provides another view of slots **570** of each of the spacers, of median **260**, and of various features of distal femoral implant **200**.

(47) Discussion will now turn to example methods for using one or both of tibial baseplate implant **100**, for example as described in connection with at least FIG. 1, and distal femoral implant **200**, for example as described in connection with at least any one or more of FIGS. 2-5 above.

(48) FIG. 6 shows a flowchart **600** relating to a method for using at least a tibial baseplate implant, in accordance with some embodiments. Such methods comprise one or more steps or actions for achieving the described method. The method steps and/or actions may be interchanged with one another without departing from the scope of the claims. In other words, unless a specific order of steps or actions is specified, the order and/or use of specific steps and/or actions may be modified without departing from the scope of the claims.

(49) Turning to flowchart **600**, block **602** includes resecting a proximal portion of a tibia of the patient to form a resected surface of the tibia.

(50) Block **604** includes stacking a plurality of stackable tibial spacers directly on top of one another. For example, as previously described in connection with at least FIG. 1, plurality of spacers, e.g., **140b**, **140c**, can be stacked directly against, or on top of, one another. In some embodiments, plurality of stackable tibial spacers **140a-140c** are one of substantially circular shaped and substantially semi-circular shaped. In some embodiments, each of stackable tibial spacers **140a-140c** have a same thickness (e.g., 6 mm). In some other embodiments, at least one of stackable tibial spacers **140a-140c** has a first thickness and at least one other of the plurality of stackable tibial spacers **140a-140c** has a second thickness different from the first thickness.

(51) Block **606** includes securing the plurality of stackable tibial spacers directly to an underside of a tibial baseplate of a tibial baseplate implant. For example, as previously described in connection with at least FIG. 1, plurality of spacers, e.g., **140b**, **140c** and in some cases **140a**, can be secured directly to underside **114** of tibial baseplate **110** of a tibial baseplate implant **100**. In some embodiments, plurality of stackable tibial spacers **140a-140c** are configured to be secured to underside **114** of tibial base plate **110** utilizing one or more screws **250**.

(52) Block **608** includes securing the tibial baseplate implant to the resected portion of the tibia, thereby providing a desired aggregate spacing between the underside of the tibial baseplate and the resected surface of the tibia. For example, as previously described in connection with at least FIG. 1, tibial baseplate implant **100** can be secured to the resected portion of the tibia of the patient, thereby providing a desired aggregate spacing between underside **114** of tibial baseplate **110** and the resected surface of the tibia.

(53) In some embodiments, tibial baseplate implant **100** further includes distal transitional portion **120** coupled to underside **114** of tibial baseplate **110**, and stem **130** coupled to distal transitional portion **120**. Stem **130** is configured to be disposed within a cavity of the tibia of the patient. In some embodiments, stem **130** has a substantially cylindrical shape, a distal end that tapers to a point, and one or more longitudinal grooves **132a-132c** configured to aid adhesion of stem **130** to a

surface of the tibia of the patient.

(54) In some embodiments, distal transitional portion **120** tapers from a proximal end toward a distal end and includes one or more protrusions that extend laterally away from distal transitional portion **120**. Such one or more protrusions are configured to aid in at least one of adhesion of distal transition portion **120** to a surface of the tibia of the patient and/or aligning plurality of stackable tibial spacers, e.g., **140b**, **140c** and in some cases **140a**, on underside **114** of tibial baseplate **110**.

(55) FIG. 7 shows another flowchart **700** relating to a method for using at least a distal femoral implant, in accordance with some embodiments. Such methods comprise one or more steps or actions for achieving the described method. The method steps and/or actions may be interchanged with one another without departing from the scope of the claims. In other words, unless a specific order of steps or actions is specified, the order and/or use of specific steps and/or actions may be modified without departing from the scope of the claims.

(56) Turning to flowchart **700**, block **702** includes resecting a distal portion of a femur of the patient to form a resected surface of the femur.

(57) Block **704** includes stacking a plurality of stackable femoral spacers into one or more stacked pairs of femoral spacers. For example, as previously described in connection with one or more of FIGS. 3B-5, posterior spacers **242a**, **242b** can be stacked directly on one another, distal spacers **244a**, **244b** can be stacked directly on one another, posterior spacers **249a**, **249b** can be stacked directly on one another, and/or distal spacers **248a**, **248b** can be stacked directly on one another.

(58) In some embodiments, stacking the plurality of stackable femoral spacers comprises disposing first posterior spacer **242a** directly against interior posterior surface **214** and disposing second posterior spacer **242b** directly against, and in a mirrored orientation with respect to, first posterior spacer **242a** such that the respective first beveled edges **241a**, **241b** of first and second posterior spacers **242a**, **242b** meet at a first common point.

(59) In some embodiments, stacking the plurality of stackable femoral spacers further and/or alternatively includes disposing first distal spacer **244a** directly against interior distal surface **218**, and disposing second distal spacer **244b** directly against, and in a mirrored orientation with respect to, first distal spacer **244a** such that the respective first beveled edges **245a**, **245b** of first and second distal spacers **244a**, **244b** meet at a second common point.

(60) In some embodiments, stacking the plurality of stackable femoral spacers comprises disposing third posterior spacer **249a** directly against a portion of interior posterior surface **214** to a side of median **260** opposite a portion of interior posterior surface **214** against which first posterior spacer **242a** may be disposed, and disposing fourth posterior spacer **249b** directly against, and in a mirrored orientation with respect to, third posterior spacer **249a** such that the respective first beveled edges **241a**, **241b** of third and fourth posterior spacers **249a**, **249b** meet at a third common point.

(61) In some embodiments, stacking the plurality of stackable femoral spacers further and/or alternatively includes disposing third distal spacer **248a** directly against a portion of interior distal surface **218** to a side of median **260** opposite a portion of interior distal surface **218** against which first distal spacer **244a** may be disposed, and disposing fourth distal spacer **248b** directly against, and in a mirrored orientation with respect to, third distal spacer **248a** such that the respective first beveled edges **245a**, **245b** of third and fourth distal spacers **244a**, **244b** meet at a fourth common point.

(62) In some embodiments, each of femoral spacers **242a**, **242b**, **244a**, **244b**, **248a**, **248b**, **249a**, **249b** have a same thickness (e.g., 5 mm). In some other embodiments, at least one of spacers **242a**, **242b**, **244a**, **244b**, **248a**, **248b**, **249a**, **249b** has a first thickness and at least one other of spacers **242a**, **242b**, **244a**, **244b**, **248a**, **248b**, **249a**, **249b** has a second thickness different from the first thickness.

(63) Block **706** includes securing the one or more stacked pairs of femoral spacers to at least one of an interior posterior surface and an interior distal surface of a femoral head portion of a distal

femoral implant, wherein the interior distal surface is disposed at a first angle with respect to the interior posterior surface. For example, as previously described in connection with at least FIG. 4, posterior spacers **242a**, **242b** and/or **249a**, **249b** can be secured to respective portions of interior posterior surface **214** utilizing one or more screws **250** and/or distal spacers **244a**, **244b** and/or **248a**, **248b** can be secured to interior distal surface **218** of femoral head portion **210** of distal femoral implant **200** utilizing one or more screws **250**.

(64) In some embodiments, securing the plurality of stackable femoral spacers to least one of an interior posterior surface and an interior distal surface of a femoral head portion of a distal femoral implant comprises securing a screw through respective slots in stacked pairs of the stackable femoral spacers, each of the respective slots having a substantially larger lateral dimension than an anterior-posterior dimension that allows for adjustment of a medial/lateral position of each of the spacer with respect to distal femoral implant **200**.

(65) As described in connection with FIGS. 2-5, interior distal surface **218** is disposed at a first angle ($\theta_{\text{sub.1}}$) with respect to interior posterior surface **214**. Femoral head portion **210** further includes outer arcuate surface **212**, which is configured to mate with one of tibial baseplate **110** or a proximal surface of a tibia of the patient. Femoral head portion **210** further includes first interior intermediate surface **2116** joining interior posterior surface **214** and interior distal surface **218**. First interior intermediate surface **216** is disposed at a second angle ($\theta_{\text{sub.2}}$) with respect to interior posterior surface **214** and at a third angle ($\theta_{\text{sub.3}}$) with respect to interior distal surface **218**. In some embodiments, the second angle ($\theta_{\text{sub.2}}$) is substantially equal to the third angle ($\theta_{\text{sub.3}}$). And in some such embodiments, that angle is 45° .

(66) In some embodiments, femoral head portion **210** further includes interior anterior surface **219** disposed at a fourth angle ($\theta_{\text{sub.4}}$) with respect to interior distal surface **218** and second interior intermediate surface **217** joining interior anterior surface **219** and interior distal surface **218**. Second interior intermediate surface **170** is disposed at a fifth angle ($\theta_{\text{sub.5}}$) with respect to interior anterior surface **219** and at a sixth angle ($\theta_{\text{sub.6}}$) with respect to interior distal surface **218**. In some embodiments, the sixth angle ($\theta_{\text{sub.6}}$) between interior distal surface **218** and second interior intermediate surface **217** is substantially equal to the third angle ($\theta_{\text{sub.3}}$) between interior distal surface **218** and first interior intermediate surface **216**.

(67) In some embodiments, interior posterior surface **214**, interior distal surface **218** and first interior intermediate surface **216** are each substantially planar. In some embodiments, each of plurality of stackable femoral spacers **242a**, **242b**, **244a**, **244b**, **248a**, **248b**, **249a**, **249b** include at least a respective first beveled edge (e.g., **241a** for spacers **242a** and/or **249a**; **241b** for spacers **242b** and/or **249b**; **245a** for spacers **244a** and/or **248a**; **245b** for spacers **244b** and/or **248b**). In some embodiments, this first respective beveled edge has a bevel angle of substantially 45° . In some embodiments, each of first through fourth distal spacers **244a**, **244b**, **248a**, **248b** include a respective second beveled edge (e.g., **246a** for spacers **244a** and/or **248a** and **246b** for spacers **244b** and/or **248b**) such that, when stacked, the respective second beveled edges **246a**, **246b** of first and second distal spacers **244a**, **244b** meet at a third common point and/or such that, when stacked, the respective second beveled edges **246a**, **246b** of third and fourth distal spacers **248a**, **248b** meet at a fourth common point. In some embodiments, this second respective beveled edge has a bevel angle of substantially 45° .

(68) In some embodiments, for example as illustrated in FIGS. 3B-5, when secured, first beveled edge **245b** of second posterior spacer **244b** is substantially parallel to, and disposed immediately adjacent to, first beveled edge **241b** of second distal spacer **242b**. In some similar or same embodiments, when secured, first beveled edge **245b** of fourth posterior spacer **249b** is substantially parallel to, and disposed immediately adjacent to, first beveled edge **241b** of fourth distal spacer **248b**.

(69) Block **708** includes securing the distal femoral implant to the resected surface of the femur, thereby providing a desired aggregate spacing between the at least one of the interior posterior

surface or the interior distal surface of the femoral head portion and the resected surface of the femur. For example, as previously described in connection with at least FIG. 2-5, distal femoral implant **200** can be secured to the resected surface of the femur, thereby providing a desired aggregate spacing between at least one of interior posterior surface **214** or interior distal surface **218** of femoral head portion **210** and the resected surface of the femur.

(70) Various aspects of the novel systems, apparatuses, and methods are described more fully hereinafter with reference to the accompanying drawings. The teachings disclosure may, however, be embodied in many different forms and should not be construed as limited to any specific structure or function presented throughout this disclosure. Rather, these aspects are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. Based on the teachings herein one skilled in the art should appreciate that the scope of the disclosure is intended to cover any aspect of the novel systems, apparatuses, and methods disclosed herein, whether implemented independently of or combined with any other aspect of the disclosure. For example, a system or an apparatus may be implemented, or a method may be practiced using any one or more of the aspects set forth herein. In addition, the scope of the disclosure is intended to cover such a system, apparatus or method which is practiced using other structure, functionality, or structure and functionality in addition to or other than the various aspects of the disclosure set forth herein. It should be understood that any aspect disclosed herein may be set forth in one or more elements of a claim. Although some benefits and advantages of the preferred aspects are mentioned, the scope of the disclosure is not intended to be limited to particular benefits, uses, or objectives. The detailed description and drawings are merely illustrative of the disclosure rather than limiting, the scope of the disclosure being defined by the appended claims and equivalents thereof.

General Interpretive Principles for the Present Disclosure

(71) Various aspects of the novel systems, apparatuses, and methods are described more fully hereinafter with reference to the accompanying drawings. The teachings disclosure may, however, be embodied in many different forms and should not be construed as limited to any specific structure or function presented throughout this disclosure. Rather, these aspects are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. Based on the teachings herein one skilled in the art should appreciate that the scope of the disclosure is intended to cover any aspect of the novel systems, apparatuses, and methods disclosed herein, whether implemented independently of or combined with any other aspect of the disclosure. For example, a system or an apparatus may be implemented, or a method may be practiced using any one or more of the aspects set forth herein. In addition, the scope of the disclosure is intended to cover such a system, apparatus or method which is practiced using other structure, functionality, or structure and functionality in addition to or other than the various aspects of the disclosure set forth herein. It should be understood that any aspect disclosed herein may be set forth in one or more elements of a claim. Although some benefits and advantages of the preferred aspects are mentioned, the scope of the disclosure is not intended to be limited to particular benefits, uses, or objectives. The detailed description and drawings are merely illustrative of the disclosure rather than limiting, the scope of the disclosure being defined by the appended claims and equivalents thereof.

(72) The use of the anatomical term “distal” is understood by those having skill in the art and can be understood to describe a location with respect to a center of a patient's body. For example, a distal femur would be located substantially at or near the distant or far end of the femur from its connection to the hip.

(73) The use of the anatomical term “proximal” is understood by those having skill in the art and can be understood to describe a location with respect to a center of a patient's body. For example, a proximal tibia would be located substantially at or near the proximate or closest end of the tibia to the femur.

- (74) The use of the anatomical term “posterior” is understood by those having skill in the art and can be understood to describe a location toward the back side of the feature being descriptively modified with respect to a plane, for example, running from head to toe of a patient. For example, a posterior surface would be understood to be located toward a back side of the feature with respect to a plane, for example, running from head to toe of a patient.
- (75) The use of the anatomical term “anterior” is understood by those having skill in the art and can be understood to be substantially opposite of “posterior,” describing a location toward the front side of the feature being descriptively modified with respect to a plane, for example, running from head to toe of a patient. For example, an anterior surface would be understood to be located toward a front side of the feature with respect to a plane, for example, running from head to toe of a patient.
- (76) With respect to the use of plural vs. singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.
- (77) When describing an absolute value of a characteristic or property of a thing or act described herein, the terms “substantial,” “substantially,” “essentially,” “approximately,” and/or other terms or phrases of degree may be used without the specific recitation of a numerical range. When applied to a characteristic or property of a thing or act described herein, these terms refer to a range of the characteristic or property that is consistent with providing a desired function associated with that characteristic or property. For example, the terms “approximately,” “about” and “substantially” may refer to an amount that is within less than 10% of, within less than 5% of, within less than 1% of, within less than 0.1% of, and within less than 0.01% of the stated amount.
- (78) In those cases where a single numerical value is given for a characteristic or property, it is intended to be interpreted as at least covering deviations of that value within one significant digit of the numerical value given.
- (79) If a numerical value or range of numerical values is provided to define a characteristic or property of a thing or act described herein, whether or not the value or range is qualified with a term of degree, a specific method of measuring the characteristic or property may be defined herein as well. In the event no specific method of measuring the characteristic or property is defined herein, and there are different generally accepted methods of measurement for the characteristic or property, then the measurement method should be interpreted as the method of measurement that would most likely be adopted by one of ordinary skill in the art given the description and context of the characteristic or property. In the further event there is more than one method of measurement that is equally likely to be adopted by one of ordinary skill in the art to measure the characteristic or property, the value or range of values should be interpreted as being met regardless of which method of measurement is chosen.
- (80) It will be understood by those within the art that terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are intended as “open” terms unless specifically indicated otherwise (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.).
- (81) It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to embodiments containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted

to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations).

(82) In those instances where a convention analogous to “at least one of A, B, and C” is used, such a construction would include systems that have A alone, B alone, C alone, A and B together without C, A and C together without B, B and C together without A, as well as A, B, and C together. It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include A without B, B without A, as well as A and B together.”

(83) Various modifications to the implementations described in this disclosure can be readily apparent to those skilled in the art, and generic principles defined herein can be applied to other implementations without departing from the spirit or scope of this disclosure. Thus, the disclosure is not intended to be limited to the implementations shown herein but is to be accorded the widest scope consistent with the claims, the principles and the novel features disclosed herein. The word “exemplary” is used exclusively herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations.

(84) Certain features that are described in this specification in the context of separate implementations also can be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation also can be implemented in multiple implementations separately or in any suitable sub-combination. Moreover, although features can be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination can be directed to a sub-combination or variation of a sub-combination.

Claims

1. A knee replacement prosthesis for a patient, comprising: a distal femoral implant comprising: a femoral head portion comprising: an outer arcuate surface configured to mate with one of a tibial baseplate or a proximal surface of a tibia of the patient; an interior posterior surface; an interior distal surface disposed at a first angle with respect to the interior posterior surface; and a first interior intermediate surface joining the interior posterior surface and the interior distal surface, the first interior intermediate surface disposed at a second angle with respect to the interior posterior surface and at a third angle with respect to the interior distal surface; and a plurality of stackable femoral spacers, each comprising a respective first beveled edge, wherein: a first posterior spacer of the plurality of stackable femoral spacers is disposed directly against the interior posterior surface; and a second posterior spacer of the plurality of stackable femoral spacers is disposed directly against, and in a mirrored orientation with respect to, the first posterior spacer such that the respective first beveled edges of the first and second posterior spacers meet at a first common point.
2. The prosthesis of claim 1, wherein each of the plurality of stackable femoral spacers comprises a slot configured to receive a fastener to, thereby, secure the respective femoral spacer to at least one of: another of the stackable femoral spacers, the interior posterior surface and the interior distal surface of the distal femoral implant, the slot comprising a substantially larger lateral dimension than an anterior-posterior dimension, thereby allowing lateral adjustment of a secured position of

the respective femoral spacer with respect to the distal femoral implant.

3. The prosthesis of claim 1, wherein the interior posterior surface, the interior distal surface and the first interior intermediate surface are each substantially planar.

4. The prosthesis of claim 1, wherein the second angle is substantially equal to the third angle.

5. The prosthesis of claim 4, wherein the second angle and the third angle are each substantially equal to 45° .

6. The prosthesis of claim 1, wherein the respective first beveled edges each have an angle of substantially 45° .

7. The prosthesis of claim 1, wherein the distal femoral implant comprises a median and the plurality of stackable femoral spacers further comprises: a third posterior spacer disposed directly against a portion of the interior posterior surface disposed to an opposite side of the median from the first posterior spacer; and a fourth posterior spacer disposed directly against, and in a mirrored orientation with respect to, the third posterior spacer such that the respective first beveled edges of the third and fourth posterior spacers meet at a third common point.

8. The prosthesis of claim 1, wherein the plurality of stackable femoral spacers further comprises: a first distal spacer disposed directly against the interior distal surface; and a second distal spacer disposed directly against, and in a mirrored orientation with respect to, the first distal spacer such that the respective first beveled edges of the first and second distal spacers meet at a second common point.

9. The prosthesis of claim 8, wherein the distal femoral implant comprises a median and the plurality of stackable femoral spacers further comprises: a third distal spacer disposed directly against a portion of the interior distal surface disposed to an opposite side of the median from the first distal spacer; and a fourth distal spacer disposed directly against, and in a mirrored orientation with respect to, the third distal spacer such that the respective first beveled edges of the third and fourth distal spacers meet at a third common point.

10. The prosthesis of claim 8, wherein the first beveled edge of the second posterior spacer is substantially parallel to, and disposed immediately adjacent to, the first beveled edge of the second distal spacer.

11. The prosthesis of claim 10, wherein the respective second beveled edges have an angle of substantially 45° .

12. The prosthesis of claim 8, wherein each of the first and second distal spacers comprise a respective second beveled edge such that the respective second beveled edges of the first and second distal spacers meet at a third common point.

13. The prosthesis of claim 1, wherein each of the plurality of stackable femoral spacers has a same thickness.

14. The prosthesis of claim 1, wherein at least one of the plurality of stackable femoral spacers has a first thickness and at least one other of the plurality of stackable femoral spacers has a second thickness different from the first thickness.

15. The prosthesis of claim 14, wherein the sixth angle between the interior distal surface and the second interior intermediate surface is substantially equal to the third angle between the interior distal surface and the first interior intermediate surface.

16. The prosthesis of claim 1, wherein the femoral head portion further comprises: an interior anterior surface disposed at a fourth angle with respect to the interior distal surface; and a second interior intermediate surface joining the interior anterior surface and the interior distal surface, the second interior intermediate surface disposed at a fifth angle with respect to the interior anterior surface and at a sixth angle with respect to the interior distal surface.
