

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent

12404222

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Alshehri; Ahmad Mahdi et al.

### Systems and methods for enhancing the extractive section operability and modifying solvent heat recovery cycle in the separation of C4 mixtures

#### Abstract

A system and a method for separating C.sub.4 and recovering 1,3-butadiene are disclosed. The system includes a main washer column, a rectifier column for separating a bottom stream from the main washer column, an after washer column for purifying 1,3-butadiene from a side stream of the rectifier column comprising acetylenes and butadienes, a degasser column for separating a bottom stream from the rectifier column to produce a lean solvent stream. The lean solvent stream comprises primarily the solvent and about 8.3% water used in the main washer column and after washer column. A reboiler for the rectifier column includes one or more heat exchange units. At least one of the heat exchange units of the reboiler for the rectifier column uses steam as heating medium.

**Inventors:** Alshehri; Ahmad Mahdi (Riyadh, SA), Abdelghani; Mohammed Sabri (Riyadh, SA), Alzenaidi; Ahmed (Riyadh, SA)

**Applicant:** SABIC Global Technologies B.V. (Bergen op Zoom, NL)

**Family ID:** 74494963

**Assignee:** SABIC Global Technologies B.V. (Bergen op Zoom, NL)

**Appl. No.:** 17/760103

**Filed (or PCT Filed):** January 26, 2021

**PCT No.:** PCT/IB2021/050591

**PCT Pub. No.:** WO2021/156707

**PCT Pub. Date:** August 12, 2021

#### Prior Publication Data

## Related U.S. Application Data

us-provisional-application US 62971163 20200206

---

## Publication Classification

**Int. Cl.:** **B01D3/40** (20060101); **B01D3/14** (20060101); **B01D3/32** (20060101); **C07C7/00** (20060101); **C07C7/08** (20060101); C07C9/10 (20060101); C07C11/08 (20060101); C07C11/167 (20060101); C07C11/22 (20060101); C07C11/24 (20060101)

### U.S. Cl.:

**CPC** **C07C7/08** (20130101); **B01D3/143** (20130101); **B01D3/322** (20130101); **B01D3/40** (20130101); **C07C7/005** (20130101); C07C9/10 (20130101); C07C11/08 (20130101); C07C11/167 (20130101); C07C11/22 (20130101); C07C11/24 (20130101)

## Field of Classification Search

**CPC:** C07C (7/04); C07C (7/05); C07C (7/06); C07C (7/08); C07C (9/10); C07C (9/12); C07C (11/08); C07C (11/09); C07C (11/16); C07C (11/167); C07C (11/22); C07C (11/24); B01D (3/141); B01D (3/143); B01D (3/322); B01D (3/40)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name  | U.S. Cl. | CPC          |
|--------------|-------------|----------------|----------|--------------|
| 2744394      | 12/1955     | Newton         | 62/635   | C07C 7/05    |
| 3338799      | 12/1966     | Brandt         | 203/84   | B01D 3/40    |
| 6337429      | 12/2001     | Kindler et al. | N/A      | N/A          |
| 9296667      | 12/2015     | Schwint        | N/A      | B01D 19/0068 |
| 9409838      | 12/2015     | Schwint        | N/A      | C07C 7/005   |
| 9611195      | 12/2016     | Brummer        | N/A      | C07C 7/10    |
| 9656929      | 12/2016     | Abdelghani     | N/A      | C07C 7/005   |
| 9744475      | 12/2016     | Schwint et al. | N/A      | N/A          |
| 10569192     | 12/2019     | Asprion        | N/A      | B01D 3/326   |
| 11780789     | 12/2022     | Abdelghani     | 585/809  | C07C 7/005   |
| 2014/0100405 | 12/2013     | Brummer        | 202/168  | C07C 7/005   |
| 2014/0121437 | 12/2013     | Schwint        | 202/168  | B01D 19/0068 |
| 2014/0124358 | 12/2013     | Schwint        | 202/168  | C07C 7/08    |
| 2016/0122265 | 12/2015     | Abdelghani     | 585/810  | B01D 3/143   |
| 2018/0327337 | 12/2017     | Senetar et al. | N/A      | N/A          |
| 2019/0031581 | 12/2018     | Asprion        | N/A      | N/A          |

### FOREIGN PATENT DOCUMENTS

| Patent No. | Application Date | Country | CPC |
|------------|------------------|---------|-----|
| 1298375    | 12/2000          | CN      | N/A |

|              |         |    |     |
|--------------|---------|----|-----|
| 103304359    | 12/2012 | CN | N/A |
| 104812725    | 12/2014 | CN | N/A |
| 104837796    | 12/2014 | CN | N/A |
| 3194349      | 12/2016 | EP | N/A |
| 3390330      | 12/2017 | EP | N/A |
| 101789892    | 12/2016 | KR | N/A |
| 20180104640  | 12/2017 | KR | N/A |
| 99200254     | 12/2005 | SA | N/A |
| WO2014058585 | 12/2013 | WO | N/A |
| WO2017103776 | 12/2016 | WO | N/A |

## OTHER PUBLICATIONS

Norbert Asprion, Gerd Kaibel, Dividing wall columns: Fundamentals and recent advances, Chemical Engineering and Processing: Process Intensification, vol. 49, Issue 2, 2010, pp. 139-146, ISSN 0255-2701, <https://doi.org/10.1016/j.cep.2010.01.013>. cited by examiner  
International Search Report and Written Opinion from PCT/IB2021/050591 dated Apr. 26, 2021, 11 pages. cited by applicant

---

*Primary Examiner:* Pilcher; Jonathan Luke

*Attorney, Agent or Firm:* Norton Rose Fulbright US LLP

---

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a national phase application under 35 U.S.C. § 371 of International Application No. PCT/IB2021/050591 filed Jan. 26, 2021, which claims priority to U.S. Provisional Patent Application No. 62/971,163 filed Feb. 6, 2020. The entire contents of each of the above-referenced disclosures is specifically incorporated by reference herein without disclaimer.

## FIELD OF INVENTION

(1) The present invention generally relates to systems and methods for separating C.sub.4 hydrocarbons. More specifically, the present invention relates to systems and methods for separating 1,3-butadiene from a C.sub.4 mixture with an optimized heat recovery cycle.

## BACKGROUND OF THE INVENTION

(2) 1,3-butadiene is a valuable chemical that can be used as a raw material in many chemical production processes. For instance, 1,3-butadiene can be used to produce polybutadiene, which is the main component of synthetic rubber. Furthermore, butadiene can be used for making adiponitrile, a nylon intermediate, via a hydrocyanation process.

(3) Conventionally, 1,3-butadiene is produced via various processes including extraction from C.sub.4 raffinate of steam crackers, dehydrogenation of n-butane, and dehydrogenation of butenes. In the process of extractive distillation of C.sub.4 raffinate from steam crackers, a 1,3-butadiene containing stream from an extractive distillation column is separated in a rectifier column to further separate the solvent and 1,3-butadiene. The solvent is further purified in a degasser column to produce purified solvent. The solvent from the degasser column is used as the heating medium for a reboiler for the rectifier column, which includes multiple heat exchangers in series, for sufficient heat recovery. However, the reliability and stability of the conventional system can be an issue that affects the 1,3-butadiene production due to high sensitivity of the heat exchanger performance to changes in the purified solvent stream. Furthermore, the heat exchangers of the reboiler are highly

susceptible to fouling, which can cause system instabilities for 1,3-butadiene production.

(4) Overall, while systems and methods for separating 1,3-butadiene from a C.sub.4 mixture exist, the need for improvements in this field persists in light of at least the aforementioned drawbacks for the conventional systems and methods.

#### BRIEF SUMMARY OF THE INVENTION

(5) A solution to at least the above-mentioned problem associated with the systems and methods for separating 1,3-butadiene from a C.sub.4 hydrocarbon mixture has been discovered. The solution resides in a system and a method for separating a C.sub.4 hydrocarbon mixture and recovering 1,3-butadiene. The method includes subjecting the C.sub.4 hydrocarbon mixture to extractive distillation, separating a bottom stream from the extractive distillation column in a rectifier column, and purifying solvent in a degasser unit. Notably, the reboiler for the rectifier column can include two or more heat exchangers in series with the last of the heat exchangers in series using steam as heating medium. This can be beneficial for at least enabling the heating performance of the reboiler to be manipulated independently from any process streams of the system, therefore increasing the stability and reliability for the system. Additionally, the first one or more exchangers of the rectifier column reboiler can use purified solvent stream from the degasser column as heating medium, resulting in optimized heat integration of the system. Moreover, the extra heat provided to the system by the steam can be further recovered in the downstream operation units, further optimizing the heat recovery and maintaining heat balance for the system. Therefore, the system and methods of the present invention provide a technical solution to at least some of the problems associated with the conventional systems and methods mentioned above.

(6) Embodiments of the invention include a method of separating a mixture of C.sub.4 hydrocarbons and a solvent. The method comprises separating the mixture in a rectifier column to produce a top stream comprising at least some C.sub.4 hydrocarbons and a bottom stream comprising (a) primarily the solvent and (b) some C.sub.4 hydrocarbons. The method comprises separating the bottom stream in a degasser column to produce a lean solvent stream comprising primarily the solvent. A reboiler for the rectifier column comprises one or more heat exchange units in series and at least one of the heat exchange units uses steam as a heating medium.

(7) Embodiments of the invention include a method of separating a mixture of C.sub.4 hydrocarbons and a solvent. The method comprises separating the mixture in a rectifier column to produce a top stream comprising at least some C.sub.4 hydrocarbons and a bottom stream comprising (a) primarily the solvent and (b) some C.sub.4 hydrocarbons. The method comprises separating the bottom stream in a degasser column to produce a lean solvent stream comprising primarily the solvent. A reboiler for the rectifier column comprises two or more heat exchange units in series. The last heat exchange unit in series uses steam as a heating medium, and the heat exchange units upstream of the last heat exchange unit use the lean solvent stream as a heating medium.

(8) Embodiments of the invention include a method of separating 1,3-butadiene from a C.sub.4 hydrocarbon feed stream. The method comprises separating, in a main washer column, the C.sub.4 hydrocarbon feed stream via extractive distillation to produce (i) a first overhead stream comprising 1-butene, 2-butene, isobutylene, isobutane, n-butane, or combinations thereof, and (ii) a first bottom stream comprising a C.sub.4 hydrocarbon mixture comprising primarily 1,3-butadiene, a solvent, and C.sub.4 hydrocarbons other than 1,3-butadiene, collectively. The method comprises separating the first bottom stream in a rectifier column to produce (a) a top stream comprising at least some of the C.sub.4 hydrocarbons other than 1,3-butadiene, (b) a first side stream comprising 1,3-butadiene and the solvent, and (c) a bottom stream comprising primarily the solvent and at least some C.sub.4 hydrocarbons. A reboiler for the rectifier column comprises two or more heat exchange units in series configured to heat the reboiler. The method comprises separating the first side stream in an after washer column to produce a crude 1,3-butadiene stream comprising primarily 1,3-butadiene. The method comprises separating the bottom stream in a degasser column

to produce a lean solvent stream comprising primarily the solvent. The method comprises flowing the lean solvent stream to at least one of the heat exchange units as a heating medium for the reboiler for the rectifier column to produce a first cooled lean solvent stream. The method further comprises flowing a low pressure steam to the last heat exchange unit in series as a heating medium to heat fluid in the reboiler for the rectifier column to a pre-determined final temperature. (9) The following includes definitions of various terms and phrases used throughout this specification.

(10) The terms “about” or “approximately” are defined as being close to as understood by one of ordinary skill in the art. In one non-limiting embodiment the terms are defined to be within 10%, preferably, within 5%, more preferably, within 1%, and most preferably, within 0.5%.

(11) The terms “wt. %”, “vol. %” or “mol. %” refer to a weight, volume, or molar percentage of a component, respectively, based on the total weight, the total volume, or the total moles of material that includes the component. In a non-limiting example, 10 moles of component in 100 moles of the material is 10 mol. % of component.

(12) The term “substantially” and its variations are defined to include ranges within 10%, within 5%, within 1%, or within 0.5%.

(13) The terms “inhibiting” or “reducing” or “preventing” or “avoiding” or any variation of these terms, when used in the claims and/or the specification, include any measurable decrease or complete inhibition to achieve a desired result.

(14) The term “effective,” as that term is used in the specification and/or claims, means adequate to accomplish a desired, expected, or intended result.

(15) The use of the words “a” or “an” when used in conjunction with the term “comprising,” “including,” “containing,” or “having” in the claims or the specification may mean “one,” but it is also consistent with the meaning of “one or more,” “at least one,” and “one or more than one.”

(16) The words “comprising” (and any form of comprising, such as “comprise” and “comprises”), “having” (and any form of having, such as “have” and “has”), “including” (and any form of including, such as “includes” and “include”) or “containing” (and any form of containing, such as “contains” and “contain”) are inclusive or open-ended and do not exclude additional, unrecited elements or method steps.

(17) The term “lean solvent stream” as that term is used in the specification and/or claims, means a stream comprising no less than 91.7 wt. % a solvent, or no more than 8.7 wt. % hydrocarbons.

(18) The process of the present invention can “comprise,” “consist essentially of,” or “consist of” particular ingredients, components, compositions, etc., disclosed throughout the specification.

(19) The term “primarily,” as that term is used in the specification and/or claims, means greater than any of 50 wt. %, 50 mol. %, and 50 vol. %. For example, “primarily” may include 50.1 wt. % to 100 wt. % and all values and ranges there between, 50.1 mol. % to 100 mol. % and all values and ranges there between, or 50.1 vol. % to 100 vol. % and all values and ranges there between.

(20) Other objects, features and advantages of the present invention will become apparent from the following figures, detailed description, and examples. It should be understood, however, that the figures, detailed description, and examples, while indicating specific embodiments of the invention, are given by way of illustration only and are not meant to be limiting. Additionally, it is contemplated that changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description. In further embodiments, features from specific embodiments may be combined with features from other embodiments. For example, features from one embodiment may be combined with features from any of the other embodiments. In further embodiments, additional features may be added to the specific embodiments described herein.

---

## Description

## BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a more complete understanding, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1A shows a schematic diagram of a system for separating a C.sub.4 hydrocarbon mixture, according to embodiments of the invention;
- (3) FIG. 1B shows a schematic diagram of a configuration of a rectifier column and a degasser column of a system for separating a C.sub.4 hydrocarbon mixture, according to embodiments of the invention;
- (4) FIG. 2 shows a schematic flowchart of a method of for separating a C.sub.4 hydrocarbon mixture, according to embodiments of the invention; and
- (5) FIG. 3 shows a temperature profile for heat exchangers of a reboiler for a rectifier column in a system for separating a C.sub.4 hydrocarbon mixture obtained by simulation.

## DETAILED DESCRIPTION OF THE INVENTION

(6) Currently, 1,3-butadiene is separated in a system that includes an extractive distillation column, a rectifier column, and a degasser column where the purified solvent stream from the degasser column is used as heating medium for the reboiler for the rectifier column. The performance of the reboiler for the rectifier column is highly sensitive to any changes in the purified solvent stream, and the reboiler for the rectifier column is susceptible to fouling. Thus, maintaining stability and reliability of the separation performance in the rectifier column and the entire system is challenging. The present invention provides a solution to this problem. The solution is premised on a method of separating 1,3-butadiene from a C.sub.4 hydrocarbon mixture that utilizes steam as heating medium of the last heat exchanger in series of the rectifier column reboiler. The parameters (e.g., temperature, and pressure) of the steam can be adjusted independently from any process streams in the system, and controlled based on the amount of heat needed to keep the reboiler in a desired temperature range and/or mitigating heat loss caused by fouling in heat exchangers that uses purified solvent as heating medium. Thus, the disclosed method is capable of increasing the stability and reliability of the 1,3-butadiene production system. Additionally, the extra heat provided by the steam used in the last heat exchanger can be further utilized in a downstream operation unit, for instance a propyne separation column, thus further enhancing the optimization of the heat cycle for the system. These and other non-limiting aspects of the present invention are discussed in further detail in the following sections.

### (7) A. System for Separating C.sub.4 Hydrocarbons

(8) In embodiments of the invention, the system for separating C.sub.4 hydrocarbons comprises a main washer column (e.g., extractive distillation column), a rectifier column, and a degasser column. The system is capable of increasing the reliability and stability for producing 1,3-butadiene. With reference to FIG. 1A, a schematic diagram is shown for system **100**, which is used for separating C.sub.4 hydrocarbons and producing 1,3-butadiene with improved system stability and reliability compared to conventional systems.

(9) According to embodiments of the invention, system **100** comprises main washer column **101** configured to separate C.sub.4 hydrocarbon feed stream **11** to produce first overhead stream **12** comprising 1-butene, 2-butene, isobutylene, isobutane, n-butane, or combinations thereof and first bottom stream **13** comprising a mixture of C.sub.4 hydrocarbons and a solvent. In embodiments of the invention, main washer column **101** includes an extractive distillation column. In embodiments of the invention, the mixture of C.sub.4 hydrocarbons of first bottom stream **13** comprises 1,3-butadiene. The mixture of C.sub.4 hydrocarbons can further comprise C.sub.4 hydrocarbons. The solvent comprises N-methyl-2-pyrrolidone (NMP). The solvent may further comprise 8-10 wt. % water, preferably about 8.3 wt. % water. The C.sub.4 hydrocarbons may include 1-butene, 2-butene, n-butane, isobutane, isobutylene, or combinations thereof.

(10) According to embodiments of the invention, a bottom outlet of main washer column **101** is in

fluid communication with rectifier column **102** such that first bottom stream flows from main washer column **101** to rectifier column **102**. In embodiments of the invention, rectifier column **102** is configured to separate first bottom stream **13** to form top stream **14** comprising at least some C.sub.4 hydrocarbons and bottom stream **15** comprising primarily the solvent and some C.sub.4 hydrocarbons. C.sub.4 hydrocarbons in both top stream **14** and bottom stream **15** include C.sub.4 hydrocarbons. In embodiments of the invention, rectifier column **102** can be configured to use 1,3-butadiene to strip butenes from the solvent into top stream **14**. At least a portion of top stream **14** is recycled back to main washer column **101**. Reboiler **105** for rectifier column **102** may include one or more heat exchange units configured to heat and boil bottom liquid stream **35** from rectifier column **102** to form bottom stream **15**. In embodiments of the invention, rectifier column **102** is further configured to produce first side stream **16** comprising primarily 1,3-butadiene and acetylenes, collectively.

(11) According to embodiments of the invention, a side outlet of rectifier column **102** is in fluid communication with after washer column **103** such that first side stream **16** flows from rectifier column **102** to after washer column **103**. After washer column **103** may be configured to separate first side stream **16** to form crude butadiene stream **17** comprising primarily 1,3-butadiene and after washer bottom stream **18** comprising primarily the solvent and acetylenes. In embodiments of the invention, after washer column **103** includes a distillation column or an extractive distillation column. In embodiments of the invention, after washer column **103** is an extractive distillation column, which uses the lean solvent of solvent feed stream **31** to dissolve the acetylenes in stream **16** which is sent back to the rectifier column again via after washer bottom stream **18**.

(12) According to embodiments of the invention, a bottom outlet of rectifier column **102** is in fluid communication with degasser column **104** such that bottom stream **15** flows from rectifier column **102** to degasser column **104**. In embodiments of the invention, degasser column **104** is configured to separate bottom stream **15** to form lean solvent stream **19** comprising the solvent, and second side stream **20** comprising acetylene. In embodiments of the invention, degasser column **104** is configured to further produce third overhead stream **21** comprising C.sub.4 hydrocarbons. In embodiments of the invention, degasser column **104** may include a distillation column.

(13) According to embodiments of the invention, a top outlet of degasser column **104** is in fluid communication with rectifier column **102** such that third overhead stream **21** flows from degasser column **104** to rectifier column **102**. In embodiments of the invention, a bottom outlet of degasser column **104** is in fluid communication with reboiler **105** for rectifier column **102** such that lean solvent stream **19** flows through reboiler **105** as a heating medium to form first cooled lean solvent stream **22**. As shown in FIG. 1B, reboiler **105** comprises two or more heat exchange units in series. The two or more heat exchange units can include heat exchangers in shell and tube configuration for counter-current heat exchange. At least the last one of the heat exchange units in series uses steam as a heating medium. The heat exchange units upstream of the last heat exchange unit may use lean solvent stream **19** as a heating medium to heat and boil bottom liquid stream **35** to form bottom stream **15** and first cooled lean solvent stream **22**. In embodiments of the invention, reboiler **105** comprises four heat exchangers in series. The first three heat exchangers in series are configured to use lean solvent stream **19** as heating medium. The last heat exchanger in series, which is downstream to the first three heat exchangers, is configured to use steam as a heating medium. The steam used as heating medium for the last heat exchanger in series of reboiler **105** may be low pressure steam. The low pressure steam may be at a pressure of 3 to 4 bar. In embodiments of the invention, downstream of low pressure steam can be flowed to a condensate system of system **100**. The condensate system can be configured to adjust temperature of the low pressure steam and/or redistribute the low pressure steam to one or more units that utilize the low pressure steam. According to embodiments of the invention, the condensate system of system **100** includes two drums comprising a medium pressure condensate drum for medium pressure steam and a low pressure condensate drum for low pressure steam.

(14) According to embodiments of the invention, an outlet of reboiler **105** is in fluid communication with refining column **106** such that at least a portion of first cooled lean solvent stream **22**, which forms downstream heating medium stream **23**, flows from reboiler **105** to a reboiler of refining column **106** as a heating medium and forms a cooled downstream heating medium stream **24**. In embodiments of the invention, refining column **106** is configured to purify 1,3-butadiene in crude butadiene stream **17**. In embodiments of the invention, an outlet of the reboiler of refining column **106** is in fluid communication with a reboiler of propyne column **107** such that cooled downstream heating medium stream **24** flows through the reboiler of propyne column **107** as a heating medium to form second cooled heating medium stream **25**. Propyne column **107** may be configured to separate purify 1,3-butadiene from the crude butadiene stream **17** by removing propyne as an overhead product.

(15) According to embodiments of the invention, an outlet of the reboiler of propyne column **107** is in fluid communication with feed evaporator **108** such that second cooled heating medium stream **25** flows from the reboiler of propyne column **107** to feed evaporator **108** as a heating medium to form third cooled heating medium stream **26**.

(16) According to embodiments of the invention, an outlet of reboiler **105** for rectifier **102** is in fluid communication with solvent regenerator **109** such that at least a portion of first cooled lean solvent stream **22**, which forms solvent regenerator feed stream **27**, flows from reboiler **105** to solvent regenerator **109**. Solvent regenerator **109** may be configured to regenerate the solvent of solvent regenerator feed stream **27** by physical separation under vacuum conditions to form regenerated solvent stream **28**. In embodiments of the invention, system **100** may further comprise condenser **110** configured to condense regenerator solvent stream to form condensed solvent stream **29**.

(17) In embodiments of the invention, third cooled heating medium stream **26** is combined with condensed solvent stream **29** to form combined solvent stream **30**. According to embodiments of the invention, system **100** includes solvent cooler **111** configured to cool combined solvent stream **30** to produce solvent feed stream **31**. Solvent cooler **111** may include a shell and tube heat exchanger. At least a portion of solvent feed stream **31** may be fed into main washer column **101** and/or after washer column **103**.

(18) B. Method of Separating C.sub.4 Hydrocarbons

(19) Methods for separating C.sub.4 hydrocarbons and recovering 1,3-butadiene have been discovered. As shown in FIG. 2, embodiments of the invention include method **200** for separating C.sub.4 hydrocarbons. Method **200** may be implemented by system **100**, as shown in FIG. 1A and described above.

(20) According to embodiments of the invention, as shown in block **201**, method **200** comprises separating, in main washer column **101**, C.sub.4 hydrocarbon feed stream **11** to produce (i) first overhead stream **12** comprising 1-butene, 2-butene, isobutylene, isobutane, n-butane, or combinations thereof, and (ii) first bottom stream **13** comprising primarily a C.sub.4 hydrocarbon mixture, and a solvent, collectively. In embodiments of the invention, the separating at block **201** is conducted via extractive distillation. The C.sub.4 hydrocarbon mixture comprises 1,3-butadiene and other C.sub.4 hydrocarbons including n-butane, isobutane, 1-butene, 2-butene, isobutylene, or combinations thereof. The C.sub.4 hydrocarbon mixture may further include C.sub.4 acetylenes and/or propyne. In embodiments of the invention, main washer column **101** is operated at an overhead temperature range of 40 to 45° C. In embodiments of the invention, main washer column **101** may not include a reboiler and the bottom product of first bottom stream **13** is diverted to the main washer rectifier column directly. Main washer column **101** may be operated at an operating pressure in a range of 4 to 5 bar and all ranges and values there between including 4 to 4.1 bar, 4.1 to 4.2 bar, 4.2 to 4.3 bar, 4.3 to 4.4 bar, 4.4 to 4.5 bar, 4.5 to 4.6 bar, 4.6 to 4.7 bar, 4.7 to 4.8 bar, 4.8 to 4.9 bar, and 4.9 to 5.0 bar. The C.sub.4 hydrocarbons other than 1,3-butadiene comprise 1-butene, 2-butene, n-butane, isobutane, isobutylene, or combinations thereof. First overhead stream



12, in embodiments of the invention, can include 0.2 wt. % to 1.0 wt. %, 1,3-butadiene and all ranges and values there between including ranges of 0.2 to 0.3 wt. %, 0.3 to 0.4 wt. %, 0.4 to 0.5 wt. %, 0.5 to 0.6 wt. %, 0.6 to 0.7 wt. %, 0.7 to 0.8 wt. %, 0.8 to 0.9 wt. %, and 0.9 to 1.0 wt. %.

(21) According to embodiments of the invention, as shown in block **202**, method **200** comprises separating first bottom stream **13** comprising the C.sub.4 hydrocarbon mixture by rectifier column **102** to produce top stream **14** comprising at least some of the C.sub.4 hydrocarbons, first side stream **16** comprising 1,3-butadiene and acetylenes, and bottom stream **15** comprising primarily the solvent and at least some C.sub.4 hydrocarbons. Bottom stream **15** may include 5 to 10 wt. % hydrocarbons. In embodiments of the invention, rectifier column **102** is operated at an overhead boiling temperature range of 55 to 75° C., and a reboiler temperature range of 100 to 125° C. Rectifier column **102** may be operated at an operating pressure of 4.5 to 5.5 bara and all ranges and values there between including ranges of 4.5 to 4.6 bara, 4.6 to 4.7 bara, 4.7 to 4.8 bara, 4.8 to 4.9 bara, 4.9 to 5.0 bara, 5.0 to 5.1 bara, 5.1 to 5.2 bara, 5.2 to 5.3 bara, 5.3 to 5.4 bara, and 5.4 to 5.5 bara. In embodiments of the invention, first side stream **16** comprises 96 to 99 wt. % 1,3-butadiene. First side stream **16** may be withdrawn from a first bottom quarter of rectifier column **102**.

(22) According to embodiments of the invention, as shown in block **203**, method **200** includes separating first side stream **16** in after washer column **103** to produce crude butadiene stream **17** comprising primarily 1,3-butadiene. The separating at block **203** may be conducted via extractive distillation. In embodiments of the invention, crude butadiene stream **17** comprises 97 to 99 wt. % 1,3-butadiene. In embodiments of the invention, after washer column **103** is operated at an overhead boiling temperature range of 40 to 48° C. After washer column **103** maybe operated without a reboiler. In embodiments of the invention, after washer column **103** may be operated at an operating pressure of 4.5 to 5.5 bara. In embodiments of the invention, separating at block **203** further produces after washer bottom stream **18** comprising the solvent, and about 15 to 20 wt. % hydrocarbons. After washer bottom stream **18** may be flowed back to rectifier column **102**. Crude butadiene stream **17** may be processed to propyne column **107** to remove propyne, and then flowed into refining column **106** for purifying 1,3-butadiene by removing heavies and 1,2-butadiene.

(23) According to embodiments of the invention, as shown in block **204**, method **200** includes separating bottom stream **15** in degasser column **104** to produce lean solvent stream **19** comprising primarily the solvent. Lean solvent stream **19** may comprise less than 1 wt. % hydrocarbons. In embodiments of the invention, separating at block **204** further produces third overhead stream **21** comprising C.sub.4 hydrocarbons and/or second side stream **20** comprising acetylene. In embodiments of the invention, degasser column **104** is operated at an overhead boiling temperature range of 85 to 100° C., a reboiler temperature range of 145 to 155° C. In embodiments of the invention, lean solvent stream **19** comprises 91 to 93 wt. % of the solvent. Third overhead stream **21** may be flowed back to rectifier column **102**. Second side stream **20** may be flowed to an acetylene column for recovering acetylene.

(24) According to embodiments of the invention, as shown in block **205**, method **200** includes flowing lean solvent stream **19** to at least one of the heat exchange units of reboiler **105** for rectifier column **102** as a heating medium to produce first cooled lean solvent stream **22**. In embodiments of the invention, reboiler **105** comprises four heat exchange units in series and lean solvent stream **19** flows through the first three heat exchange units sequentially as the heating medium. In embodiments of the invention, the first cooled lean solvent stream **22** is at a temperature of 110 to 120° C. and all ranges and values there between including 110 to 111° C., 111 to 112° C., 112 to 113° C., 113 to 114° C., 114 to 115° C., 115 to 116° C., 116 to 117° C., 117 to 118° C., 118 to 119° C., 119 to 120° C. In embodiments of the invention, a volumetric flow rate ratio of lean solvent stream **19** to fluid being heated in reboiler **105** may be in a range of 0.5 to 2 and all ranges and values there between including ranges of 0.5 to 0.7, 0.7 to 0.8, 0.8 to 1.0, 1.0 to 1.2, 1.2 to 1.4, 1.4 to 1.6, 1.6 to 1.8, and 1.8 to 2.0.

(25) According to embodiments of the invention, as shown in block **206**, method **200** includes

flowing steam to the last heat exchange unit in series of reboiler **105** as a heating medium to heat the fluid in reboiler **105** of rectifier column **102** to a pre-determined final temperature. In embodiments of the invention, the steam used in block **206** is low pressure steam at a pressure of 3 to 4 bara. The pre-determined final temperature may be in a range of 100 to 125° C. In embodiments of the invention, the steam used at block **206** is at a temperature of 130 to 135° C. The parameters including temperature, flow rate, and/or pressure of the steam used at block **206** can be adjusted to facilitate heating the fluid in reboiler **105** to the final pre-determined temperature. The flowing steps at blocks **205** and **206** may be capable of lowering shell side temperature of reboiler **105**, thereby reducing fouling tendency in heat exchange units of reboiler **105**.

(26) According to embodiments of the invention, as shown in block **207**, method **200** includes flowing at least a portion of first cooled lean solvent stream **22** as heating medium for one or more downstream units, including a reboiler of refining column **106**, a reboiler of propyne column **107**, and feed evaporator **108** of main washer column **101**. to produce third cooled heating medium stream **26**. In embodiments of the invention, at least a portion of first cooled lean solvent stream **22** is flowed as heating medium sequentially through a reboiler of refining column **106**, a reboiler of propyne column **107**, and feed evaporator **108** of main washer column **101**. Third cooled heating medium stream **26** may be at a temperature of 70 to 75° C. Flowing at block **207** may be capable of reducing or eliminating an amount of hot condensate needed for heating the reboiler of propyne column **107**.

(27) According to embodiments of the invention, as shown in block **208**, method **200** includes regenerating at least a portion of first cooled lean solvent stream **22** and condensing the regenerated solvent stream **28** to form condensed solvent stream **29**. Condensed solvent stream **29** may be at a temperature of 45 to 55° C. According to embodiments of the invention, as shown in block **209**, method **200** includes cooling third cooled heating medium stream **26** and/or condensed solvent stream **29** in solvent cooler **111** to produce solvent feed stream **31**. Solvent feed stream **31** may be at a temperature of 36 to 44° C. and all ranges and values there between. At least a portion of solvent feed stream **31** may be fed into main washer column **101** and/or after washer column **103**.

(28) Although embodiments of the present invention have been described with reference to blocks of FIG. 2 should be appreciated that operation of the present invention is not limited to the particular blocks and/or the particular order of the blocks illustrated in FIG. 2. Accordingly, embodiments of the invention may provide functionality as described herein using various blocks in a sequence different than that of FIG. 2

(29) The systems and processes described herein can also include various equipment that is not shown and is known to one of skill in the art of chemical processing. For example, some controllers, piping, computers, valves, pumps, heaters, thermocouples, pressure indicators, mixers, heat exchangers, and the like may not be shown.

(30) As part of the disclosure of the present invention, specific examples are included below. The examples are for illustrative purposes only and are not intended to limit the invention. Those of ordinary skill in the art will readily recognize parameters that can be changed or modified to yield essentially the same results.

#### Example

##### Comparison of Methods for Separating C.SUB.4 .Hydrocarbons Via Simulation

(31) Simulations based on a conventional process and the disclosed process for separating C.sub.4 hydrocarbons and producing 1,3-butadiene were run in PRO II platform. The NMP cycle duty, which is the energy exchanged within the NMP cycle in the system, and utility consumption for both the conventional method (based case) and the disclosed method (post modification) were calculated. The results are shown in Table 1 and Table 2, respectively. The temperature profile of shell side and tube side of the three heat exchangers, which used lean solvent stream as heating medium, are plotted in FIG. 3.

(32) TABLE-US-00001 TABLE 1 Comparison of NMP cycle duty NMP Cycle Duty ( Base case 197 KTA) Duty[MM kcal/hr] Exchanger Base Case Post modification NMP/NMP-HC 12.70 [4 exchangers] 9.37 [3 exchangers] Refining reboiler 7.50 7.50 Feed evaporator 3.70 3.97 Propyne reboiler N/A 2.27 Solvent cooler 2.78 3.78 T .sub.i, NMP ° C. 151.4 T .sup.f, NMP ° C. 38 Total NMP duty 26.68 26.86 \* Ti .sub.NMP means the solvent temperature at the beginning of the solvent cycle. In FIG. 1A, it is stream 19. Tf .sub.NMP means the inlet solvent temperature at the end of the solvent cycle. In FIG. 1A, it is stream 31.

(33) TABLE-US-00002 TABLE 2 Comparison of utility consumptions Consumption [ton/ton BD] Type Base Case Post modification MP steam 1.40 1.40 LP steam 0.14 0.46 Cond. 3.63 0.08\* CW 25.49 25.49 \*MP means medium pressure steam (10-11 bara and 258-268° C.), LP means low pressure steam (3-4 bara and 142-147° C.), CW means cooling water (25-30° C.).

(34) The results show that the disclosed method was capable of maintaining a comparable heat cycle duty as the conventional method. The disclosed method was capable of substantially eliminating the use of hot condensate, which is condensed low pressure steam at a temperature of 90 to 95° C., for heating the reboiler of propyne column.

(35) In the context of the present invention, at the least the following 18 embodiments are described. Embodiment 1 is a method of separating a mixture of C.sub.4 hydrocarbons and a solvent. The method includes separating the mixture of C.sub.4 hydrocarbons in a rectifier column to produce a top stream containing at least some C.sub.4 hydrocarbons and a bottom stream containing (a) primarily the solvent and (b) some C.sub.4 hydrocarbons. The method further includes separating the bottom stream in a degasser column to produce a lean solvent stream containing primarily the solvent, wherein a reboiler for the rectifier column includes one or more heat exchange units in series and at least one of the heat exchange units uses steam as a heating medium. Embodiment 2 is the method of embodiment 1, wherein the reboiler for the rectifier column includes two or more heat exchange units in series, wherein a last heat exchange unit in series uses steam as a heating medium, and the heat exchange units upstream of the last heat exchange unit use the lean solvent stream as a heating medium. Embodiment 3 is the method of either of embodiments 1 or 2, wherein the mixture of C.sub.4 hydrocarbons and the solvent is produced by a step of separating, in a main washer column, a C.sub.4 hydrocarbon feed stream via extractive distillation to produce (i) a first overhead stream containing 1-butene, 2-butene, isobutylene, isobutane, n-butane, or combinations thereof, and (ii) the mixture of C.sub.4 hydrocarbons and the solvent containing primarily 1,3-butadiene, the solvent, C.sub.4 hydrocarbons other than 1,3-butadiene, collectively. Embodiment 4 is the method of any of embodiments 1 to 3, wherein the separating of the mixture of C.sub.4 hydrocarbons and the solvent further produces a first side stream containing 1,3-butadiene and the acetylenes. Embodiment 5 is the method of embodiment 4, further including separating the first side stream in an after washer column to produce a crude butadiene stream containing primarily 1,3-butadiene. Embodiment 6 is the method of any of embodiments 1 to 5, further including flowing the lean solvent stream to at least one of the heat exchange units as a heating medium for the reboiler for the rectifier column to produce a first cooled lean solvent stream. The method further includes flowing a low pressure steam to the last heat exchange unit in series as a heating medium to heat the reboiler for the rectifier column to a pre-determined final temperature. Embodiment 7 is the method of embodiment 6, wherein the separating of the bottom stream in the degasser column further produces a second side stream containing acetylene. Embodiment 8 is the method of embodiment 7, further including purifying the acetylene in an acetylene column. Embodiment 9 is the method of embodiment 8, wherein the first cooled lean solvent stream is further flowed as the heating medium to provide heat for one or more reboilers of the propyne column for purifying propyne from the crude butadiene stream, a refining column for purifying 1,3-butadiene from crude butadiene stream, and a feed evaporator for the main washer column. Embodiment 10 is the method of embodiment 9, wherein the first cooled lean solvent stream is sequentially flowed through the

reboilers of the propyne column, the refining column, and a feed evaporator for vaporizing a hydrocarbons feed stream for the main washer column as the heating medium. Embodiment 11 is the method of any of embodiments 6 to 10, wherein the pre-determined final temperature of the reboiler for the rectifier column is in a range of 100 to 125° C. Embodiment 12 is the method of any of embodiments 1 to 11, wherein the separating of the bottom stream in the degasser column further produces a second overhead stream containing C.sub.4 hydrocarbons. Embodiment 13 is the method of embodiment 12, wherein the second overhead stream is flowed back to the rectifier column. Embodiment 14 is the method of any of embodiments 1 to 13, wherein the C.sub.4 hydrocarbons contain 1-butene, 2-butene, n-butane, isobutane, isobutylene, 1,3-butadiene, or combinations thereof. Embodiment 15 is the method of any of embodiments 1 to 14, wherein the solvent contains N-methyl-2-pyrrolidone and 8.3 wt. % water. Embodiment 16 is the method of any of embodiments 1 to 15, wherein the rectifier column is operated at an overhead boiling temperature range of 55 to 75° C., a reboiler temperature range of 100 to 125° C., and an operating pressure of 4.5 to 5.5 bara. Embodiment 17 is the method of any of embodiments 1 to 16, wherein the degasser column is operated at an overhead boiling temperature range of 85 to 100° C., a reboiler temperature range of 145 to 155° C. Embodiment 18 is the method of any of embodiments 1 to 17, wherein the rectifier column includes four heat exchangers in series, wherein the first three of the heat exchangers is operated with the lean solvent stream as the heating medium, and the last heat exchanger is operated with a low pressure steam as the heating medium.

(36) Although embodiments of the present application and their advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the embodiments as defined by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the above disclosure, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

## Claims

1. A method of separating a mixture of C.sub.4 hydrocarbons and a solvent, the method comprising: separating the mixture of C.sub.4 hydrocarbons and the solvent in a rectifier column to produce a top stream comprising at least some C.sub.4 hydrocarbons and a bottom stream comprising (a) primarily the solvent and (b) some C.sub.4 hydrocarbons; separating the bottom stream in a degasser column to produce a lean solvent stream comprising primarily the solvent; wherein a reboiler for the rectifier column comprises four or more heat exchangers in series, wherein at least three of the heat exchangers are operated using the lean solvent stream as a heating medium, and wherein a last heat exchanger of the four or more heat exchangers in series is operated using low pressure steam as a heating medium; wherein the degasser column is operated at an overhead boiling temperature range of 85 to 100° C.; and wherein the method further comprises steps of: flowing the lean solvent stream to at least one of the four or more heat exchangers as a heating medium for the reboiler to heat a rectifier feed stream to produce a first cooled lean solvent stream and a heated rectifier feed stream; and flowing the low pressure steam to the last heat exchanger of the four or more heat exchangers as a heating medium to heat the reboiler to heat the heated rectifier feed stream and produce a further heated rectifier feed stream.
2. The method of claim 1, wherein the mixture of C.sub.4 hydrocarbons and the solvent is produced by a step of separating, in a main washer column, a C.sub.4 hydrocarbon feed stream via extractive

distillation to produce (i) a first overhead stream comprising 1-butene, 2-butene, isobutylene, isobutane, n-butane, or combinations thereof, and (ii) the mixture of C.sub.4 hydrocarbons and the solvent comprising primarily a mixture of 1,3-butadiene, the solvent, and C.sub.4 hydrocarbons other than 1,3-butadiene.

3. The method of claim 1, wherein the separating of the mixture of C.sub.4 hydrocarbons and the solvent in the rectifier column further produces a first side stream comprising 1,3-butadiene and acetylenes.

4. The method of claim 3, further comprising separating the first side stream in an after washer column to produce a crude butadiene stream comprising primarily 1,3-butadiene.

5. The method of claim 1, wherein the separating of the bottom stream in the degasser column further produces a second side stream comprising acetylene.

6. The method of claim 5, further comprising separating the second side stream in an acetylene column to produce a purified acetylene stream.

7. The method claim 1, wherein the first cooled lean solvent stream is provided as a heating medium to one or more of: i) a reboiler of a propyne column for purifying propyne from the crude butadiene stream, ii) a reboiler of a refining column for purifying 1,3-butadiene from the crude butadiene stream, and/or iii) a feed evaporator for the main washer column.

8. The method of claim 7, wherein the first cooled lean solvent stream is provided as a heating medium to all of the reboiler of the propyne column, the reboiler of the refining column, and the feed evaporator for the main washer column, such the first cooled lean solvent stream flows through the reboiler of the propyne column, the reboiler of the refining column, and the feed evaporator for the main washer column in series.

9. The method of claim 1, wherein the temperature of the reboiler for the rectifier column is in a range of 100 to 125° C.

10. The method of claim 1, wherein the separating of the bottom stream in the degasser column further produces a second overhead stream comprising C.sub.4 hydrocarbons.

11. The method of claim 10, wherein the second overhead stream is flowed to the rectifier column.

12. The method of claim 1, wherein the C.sub.4 hydrocarbons in the mixture of C.sub.4 hydrocarbons and the solvent comprise 1-butene, 2-butene, n-butane, isobutane, isobutylene, 1,3-butadiene, or combinations thereof.

13. The method of claim 1, wherein the solvent comprises N-methyl-2-pyrrolidone and 8.3 wt. % water.

14. The method of claim 1, wherein the rectifier column is operated at an overhead boiling temperature range of 55 to 75° C., a reboiler temperature range of 100 to 125° C., and an operating pressure of 4.5 to 5.5 bara.

15. The method of claim 1, wherein the degasser column is operated at a reboiler temperature range of 145 to 155° C.

16. The method of claim 2, wherein the degasser column is operated at a reboiler temperature range of 145 to 155° C.

17. A method of separating a mixture of C.sub.4 hydrocarbons and a solvent, the method comprising: separating the mixture of C.sub.4 hydrocarbons and the solvent in a rectifier column to produce a top stream comprising at least some C.sub.4 hydrocarbons and a bottom stream comprising (a) primarily the solvent and (b) some C.sub.4 hydrocarbons; separating the bottom stream in a degasser column to produce a lean solvent stream comprising primarily the solvent; wherein a reboiler for the rectifier column comprises four or more heat exchangers, wherein at least three of the heat exchangers are operated using the lean solvent stream as a heating medium, and wherein a last heat exchanger of the four or more heat exchangers in series is operated using low pressure steam as a heating medium; wherein the rectifier column is operated at an overhead boiling temperature range of 55 to 75° C.; and wherein the method further comprises steps of: flowing the lean solvent stream to at least one of the four or more heat exchangers as a heating

medium for the reboiler to heat a rectifier feed stream to produce a first cooled lean solvent stream and a heated rectifier feed stream; and flowing the low pressure steam to the last heat exchanger of the four or more heat exchangers as a heating medium to heat the reboiler to heat the heated rectifier feed stream and produce a further heated rectifier feed stream.

---