

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                         |
|----------------------|-------------------------|
| United States Patent | 12405529                |
| Kind Code            | B2                      |
| Date of Patent       | September 02, 2025      |
| Inventor(s)          | Tsai; Cheng Hung et al. |

---

### Lithography system and methods

---

#### Abstract

A method includes: depositing a mask layer over a substrate; directing first radiation reflected from a central collector section of a sectional collector of a lithography system toward the mask layer according to a pattern; directing second radiation reflected from a peripheral collector section of the sectional collector toward the mask layer according to the pattern, wherein the peripheral collector section is vertically separated from the central collector section by a gap; forming openings in the mask layer by removing first regions of the mask layer exposed to the first radiation and second regions of the mask layer exposed to the second radiation; and removing material of a layer underlying the mask layer exposed by the openings.

---

**Inventors:** Tsai; Cheng Hung (Hsinchu, TW), Yu; Sheng-Kang (Hsinchu, TW), Chien; Shang-Chieh (Hsinchu, TW), Liu; Heng-Hsin (Hsinchu, TW), Chen; Li-Jui (Hsinchu, TW)

**Applicant:** Taiwan Semiconductor Manufacturing Co., Ltd. (Hsinchu, TW)

**Family ID:** 82762140

**Assignee:** Taiwan Semiconductor Manufacturing Co., Ltd. (Hsinchu, TW)

**Appl. No.:** 18/446400

**Filed:** August 08, 2023

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20230400763 A1   | Dec. 14, 2023    |

#### Related U.S. Application Data

division parent-doc US 17232483 20210416 US 12287572 child-doc US 18446400

---

## Publication Classification

**Int. Cl.:** G03F7/00 (20060101); G03F7/20 (20060101); G03F7/22 (20060101); G03F7/36 (20060101)

**U.S. Cl.:**

**CPC** G03F7/0035 (20130101); G03F7/2004 (20130101); G03F7/2026 (20130101); G03F7/22 (20130101); G03F7/36 (20130101);

## Field of Classification Search

**CPC:** G03F (7/0035); G03F (7/2004); G03F (7/2026); G03F (7/22); G03F (7/36); G03F (7/70033); G03F (7/70175); G03F (7/70916); G03F (7/70975); G03F (7/203); G03F (7/70058); G21K (2201/067)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl.  | CPC             |
|--------------|-------------|---------------|-----------|-----------------|
| 9465208      | 12/2015     | Vogt et al.   | N/A       | N/A             |
| 9541840      | 12/2016     | Brandt et al. | N/A       | N/A             |
| 10635002     | 12/2019     | Brandt et al. | N/A       | N/A             |
| 2006/0000985 | 12/2005     | Chandhok      | 250/492.2 | G03F<br>7/70175 |
| 2008/0273235 | 12/2007     | Cho           | 359/226.1 | G02B<br>27/0025 |
| 2010/0051827 | 12/2009     | Derra         | 250/492.1 | G03F<br>7/70916 |
| 2013/0088697 | 12/2012     | Labetski      | 359/838   | G03F<br>7/70933 |
| 2013/0176614 | 12/2012     | Anderl et al. | N/A       | N/A             |
| 2015/0261094 | 12/2014     | Huang et al.  | N/A       | N/A             |
| 2017/0097572 | 12/2016     | Brandt        | N/A       | G21K 1/062      |
| 2017/0315453 | 12/2016     | Bauer et al.  | N/A       | N/A             |
| 2019/0166680 | 12/2018     | Hsu et al.    | N/A       | N/A             |
| 2020/0057393 | 12/2019     | Yang et al.   | N/A       | N/A             |
| 2020/0073250 | 12/2019     | Zi et al.     | N/A       | N/A             |

### FOREIGN PATENT DOCUMENTS

| Patent No.    | Application Date | Country | CPC |
|---------------|------------------|---------|-----|
| 20070032230   | 12/2006          | KR      | N/A |
| WO 2014170093 | 12/2013          | WO      | N/A |

### OTHER PUBLICATIONS

Anthony, Frank M. "High heat load optics: an historical overview." Optical Engineering 34(2) (Feb. 1995): 313-320. cited by applicant

---

*Primary Examiner:* Huff; Mark F.

*Assistant Examiner:* Smoot; Moriah S.

*Attorney, Agent or Firm:* Seed Intellectual Property Law Group LLP

---

## **Background/Summary**

### **BACKGROUND**

(1) The semiconductor integrated circuit (IC) industry has experienced exponential growth. Technological advances in IC materials and design have produced generations of ICs where each generation has smaller and more complex circuits than the previous generation. In the course of IC evolution, functional density (i.e., the number of interconnected devices per chip area) has generally increased while geometry size (i.e., the smallest component (or line) that can be created using a fabrication process) has decreased. This scaling down process generally provides benefits by increasing production efficiency and lowering associated costs. Such scaling down has also increased the complexity of processing and manufacturing ICs.

---

## **Description**

### **BRIEF DESCRIPTION OF THE DRAWINGS**

- (1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.
- (2) FIGS. 1A-16 are views of portions of a lithography scanner according to embodiments of the present disclosure.
- (3) FIGS. 2A-2H are views of various embodiments of a sectional collector of the lithography scanner according to various aspects of the present disclosure.
- (4) FIGS. 3A-3E are views illustrating air flow in the sectional collector in accordance with various embodiments.
- (5) FIGS. 4-5 are views illustrating methods of fabricating a device according to various aspects of the present disclosure.

### **DETAILED DESCRIPTION**

(6) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(7) Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are

intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(8) Terms such as “about,” “roughly,” “substantially,” and the like may be used herein for ease of description. A person having ordinary skill in the art will be able to understand and derive meanings for such terms. For example, “about” may indicate variation in a dimension of 20%, 10%, 5% or the like, but other values may be used when appropriate. “Substantially” is generally more stringent than “about,” such that variation of 10%, 5% or less may be appropriate, without limit thereto. A feature that is “substantially planar” may have variation from a straight line that is within 10% or less. A material with a “substantially constant concentration” may have variation of concentration along one or more dimensions that is within 5% or less. Again, a person having ordinary skill in the art will be able to understand and derive appropriate meanings for such terms based on knowledge of the industry, current fabrication techniques, and the like.

(9) The present disclosure is generally related to lithography equipment for fabricating semiconductor devices, and more particularly to a sectional collector that is part of a light source. Dimension scaling (down) is increasingly difficult in advanced technology nodes. Lithography techniques employ ever shorter exposure wavelengths, including deep ultraviolet (DUV; about 193-248 nanometers), extreme ultraviolet (EUV; about 10-100 nanometers; particularly 13.5 nanometers), and X-ray (about 0.01-10 nanometers) to ensure accurate patterning at the scaled-down dimensions. EUV light is generated by a light source, and reflected toward a wafer by multiple mirrors and a reflective mask. Only a fraction of the EUV light reaches the wafer, such that increasing intensity of EUV light generated by the light source is a topic of much interest.

(10) A typical EUV scanner includes a collector for focusing light scattered from a laser pulse incident on a droplet of material, such as tin. The collector includes a highly-polished mirror surface that is concave with a generally circular cross-section. In most configurations, the collector has an opening located at its center, and a light source, such as a laser, emits one or more laser pulses from behind the collector through the opening to strike the droplet as it traverses space in front of the collector. As EUV lithography advances, it becomes desirable for the collector to have increasingly large size to raise EUV conversion efficiency, which boosts wafer per day (WPD) throughput. Deformation of the collector as size increases due to collector weight impinges on ability to focus the EUV light. Tin contamination or buildup on the mirror surface of the collector is related to air flow over the collector surface, which can be difficult to maintain and control when the collector surface is large. Cost to manufacture a monolithic collector of very large dimensions with precise convex surface also increases significantly.

(11) In the embodiments of this disclosure, a sectional collector with hierarchical structure is disclosed that enables enlargement of the collector size. The flow coverage is improved by gaps between collector sections to prevent tin buildup on the sectional collector. The modular design of the sectional collector with hierarchical structure is easier to maintain and lowers manufacturing cost.

(12) FIG. 1A is a schematic and diagrammatic view of a lithography exposure system **10**, in accordance with some embodiments. In some embodiments, the lithography exposure system **10** is an extreme ultraviolet (EUV) lithography system designed to expose a resist layer by EUV radiation, and may also be referred to as the EUV system **10**. The lithography exposure system **10** includes a light source **120**, an illuminator **140**, a mask stage **16**, a projection optics module (or projection optics box (POB)) **130** and a substrate stage **24**, in accordance with some embodiments. The elements of the lithography exposure system **10** can be added to or omitted, and the disclosure should not be limited by the embodiment.

(13) The light source **120** is configured to generate light radiation having a wavelength ranging between about 1 nm and about 100 nm in certain embodiments. In one particular example, the light

source **120** generates an EUV radiation with a wavelength centered at about 13.5 nm. Accordingly, the light source **120** is also referred to as an EUV radiation source. However, it should be appreciated that the light source **120** should not be limited to emitting EUV radiation. The light source **120** can be utilized to perform any high-intensity photon emission from excited target fuel.

(14) In various embodiments, the illuminator **140** includes various refractive optic components, such as a single lens or a lens system having multiple reflectors **100**, for example lenses (zone plates) or alternatively reflective optics (for EUV lithography exposure system), such as a single mirror or a mirror system having multiple mirrors in order to direct light from the light source **120** onto the mask stage **16**, particularly to a mask **18** secured on the mask stage **16**. In the present embodiment where the light source **120** generates light in the EUV wavelength range, reflective optics are employed. In some embodiments, the illuminator **140** includes at least three lenses.

(15) The mask stage **16** is configured to secure the mask **18**. In some embodiments, the mask stage **16** includes an electrostatic chuck (e-chuck) to secure the mask **18**. This is because gas molecules absorb EUV radiation and the lithography exposure system for the EUV lithography patterning is maintained in a vacuum environment to avoid EUV intensity loss. In the present disclosure, the terms mask, photomask, and reticle are used interchangeably. In the present embodiment, the mask **18** is a reflective mask. One exemplary structure of the mask **18** includes a substrate with a suitable material, such as a low thermal expansion material (LTEM) or fused quartz. In various examples, the LTEM includes TiO.sub.2 doped SiO.sub.2, or other suitable materials with low thermal expansion. The mask **18** includes a reflective multilayer deposited on the substrate.

(16) The projection optics module (or projection optics box (POB)) **130** is configured for imaging the pattern of the mask **18** on to a semiconductor wafer **22** secured on the substrate stage **24** of the lithography exposure system **10**. In some embodiments, the POB **130** has refractive optics (such as for a UV lithography exposure system) or alternatively reflective optics (such as for an EUV lithography exposure system) in various embodiments. The light directed from the mask **18**, carrying the image of the pattern defined on the mask, is collected by the POB **130**. The illuminator **140** and the POB **130** are collectively referred to as an optical module of the lithography exposure system **10**. In some embodiments, the POB **130** includes at least six reflective optics.

(17) In the present embodiment, the semiconductor wafer **22** may be made of silicon or other semiconductor materials. Alternatively or additionally, the semiconductor wafer **22** may include other elementary semiconductor materials such as germanium (Ge). In some embodiments, the semiconductor wafer **22** is made of a compound semiconductor such as silicon carbide (SiC), gallium arsenic (GaAs), indium arsenide (InAs), or indium phosphide (InP). In some embodiments, the semiconductor wafer **22** is made of an alloy semiconductor such as silicon germanium (SiGe), silicon germanium carbide (SiGeC), gallium arsenic phosphide (GaAsP), or gallium indium phosphide (GaInP). In some other embodiments, the semiconductor wafer **22** may be a silicon-on-insulator (SOI) or a germanium-on-insulator (GOI) substrate.

(18) In addition, the semiconductor wafer **22** may have various device elements. Examples of device elements that are formed in the semiconductor wafer **22** include transistors (e.g., metal oxide semiconductor field effect transistors (MOSFET), complementary metal oxide semiconductor (CMOS) transistors, bipolar junction transistors (BJT), high voltage transistors, high-frequency transistors, p-channel and/or n-channel field-effect transistors (PFETs/NFETs), etc.), diodes, and/or other applicable elements. Various processes are performed to form the device elements, such as deposition, etching, implantation, photolithography, annealing, and/or other suitable processes. In some embodiments, the semiconductor wafer **22** is coated with a resist layer sensitive to the EUV radiation in the present embodiment. Various components including those described above are integrated together and are operable to perform lithography processes.

(19) The lithography exposure system **10** may further include other modules or be integrated with (or be coupled with) other modules, such as a cleaning module designed to provide hydrogen gas to the light source **120**. The hydrogen gas helps reduce contamination in the light source **120**. Further

description of the light source **120** is provided with reference to FIG. **1B**.

(20) In FIG. **1B**, the light source **120** is shown in a diagrammatical view, in accordance with some embodiments. In some embodiments, the light source **120** employs a dual-pulse laser produced plasma (LPP) mechanism to generate plasma **88** and further generate EUV radiation from the plasma. The light source **120** includes a droplet generator **30**, a droplet receptacle **35**, a laser generator **50**, a laser produced plasma (LPP) collector **60** (also referred to as “sectional collector **60**”), a monitoring device **70** and a controller **90**. Some or all of the above-mentioned elements of the light source **120** may be held under vacuum. It should be appreciated that the elements of the light source **120** can be added to or omitted, and should not be limited by the embodiment.

(21) The droplet generator **30** is configured to generate a plurality of droplets **82**, which may be elongated, of a target fuel **80** to a zone of excitation at which at least one laser pulse **51** from the laser generator **50** hits the droplets **82** along an x-axis, as shown in FIG. **1B**. In an embodiment, the target fuel **80** includes tin (Sn). In an embodiment, the droplets **82** may be formed with an elliptical shape. In an embodiment, the droplets **82** are generated at a rate of about 50 kilohertz (kHz) and are introduced into the zone of excitation in the light source **120** at a speed of about 70 meters per second (m/s). Other material can also be used for the target fuel **80**, for example, a tin containing liquid material such as eutectic alloy containing tin, lithium (Li), and xenon (Xe). The target fuel **80** in the droplet generator **30** may be in a liquid phase.

(22) The laser generator **50** is configured to generate at least one laser pulse to allow the conversion of the droplets **82** into plasma **88**. In some embodiments, the laser generator **50** is configured to produce a laser pulse **51** to the lighting point **52** to convert the droplets **82** to plasma **88** which generates EUV radiation **84**. The laser pulse **51** is directed through window (or lens) **55**, and irradiates droplets **82** at the lighting point **52**. The window **55** is formed in the sectional collector **60** and adopts a suitable material substantially transparent to the laser pulse **51**. The droplet receptacle **35** catches and collects unused droplets **82** and/or scattered material of the droplets **82** resulting from the laser pulse **51** striking the droplets **82**.

(23) The plasma emits EUV radiation **84**, which is collected by the sectional collector **60**. The sectional collector **60** further reflects and focuses the EUV radiation **84** for the lithography processes performed through an exposure tool. In some embodiments, the sectional collector **60** has an optical axis **61** which is parallel to the z-axis and perpendicular to the x-axis. The sectional collector **60** includes at least two collector sections, such as collector sections **60A-60C** illustrated in FIG. **1B**, and described in detail with reference to FIGS. **2A-2G**. The sectional collector **60** may further include a vessel wall **65** having first and second pumps **66, 68** attached thereto. In some embodiments, the first and second pumps **66, 68** include scrubbers configured to remove particulates and/or gases from the sectional collector **60**. The first and second pumps **66, 68** may be collectively referred to as “the pumps **66, 68**” herein.

(24) In an embodiment, the laser generator **50** is a carbon dioxide (CO<sub>2</sub>) laser source. In some embodiments, the laser generator **50** is used to generate the laser pulse **51** with single wavelength. The laser pulse **51** is transmitted through an optic assembly for focusing and determining incident angle of the laser pulse **51**. In some embodiments, the laser pulse **51** has a spot size of about 200-300 μm, such as 225 μm. The laser pulse **51** is generated to have certain driving power to meet wafer production targets, such as a throughput of 125 wafers per hour (WPH), though greater WPH may be achieved by use of the sectional collector **60** which increases throughput by its larger surface area. For example, the laser pulse **51** is equipped with about 23 kW driving power. In various embodiments, the driving power of the laser pulse **51** is at least 20 kW, such as 27 kW.

(25) The monitoring device **70** is configured to monitor one or more conditions in the light source **70** so as to produce data for controlling configurable parameters of the light source **120**. In some embodiments, the monitoring device **70** includes a metrology tool **71** and an analyzer **73**. In cases where the metrology tool **71** is configured to monitor condition of the droplets **82** supplied by the droplet generator **30**, the metrology tool may include an image sensor, such as a charge coupled

device (CCD), complementary metal oxide semiconductor sensor (CMOS) sensor or the like. The metrology tool **71** produces a monitoring image including image or video of the droplets **82** and transmits the monitoring image to the analyzer **73**. In cases where the metrology tool **71** is configured to detect energy or intensity of the EUV light **84** produced by the droplet **82** in the light source **120**, the metrology tool **71** may include a number of energy sensors. The energy sensors may be any suitable sensors that are able to observe and measure energy of electromagnetic radiation in the ultraviolet region.

(26) The analyzer **73** is configured to analyze signals produced by the metrology tool **71** and outputs a detection signal to the controller **90** according to an analyzing result. For example, the analyzer **73** includes an image analyzer. The analyzer **73** receives the data associated with the images transmitted from the metrology tool **71** and performs an image analysis process on the images of the droplets **82** in the excitation zone. Afterwards, the analyzer **73** sends data related to the analysis to the controller **90**. The analysis may include a flow path error or a position error.

(27) In some embodiments, two or more metrology tools **71** are used to monitor different conditions of the light source **120**. One is configured to monitor condition of the droplets **82** supplied by the droplet generator **30**, and the other is configured to detect energy or intensity of the EUV light **84** produced by the droplet **82** in the light source **120**. In some embodiments, the metrology tool **71** is a final focus module (FFM) and positioned in the laser source **50** to detect light reflected from the droplet **82**.

(28) The controller **90** is configured to control one or more elements of the light source **120**. In some embodiments, the controller **90** is configured to drive the droplet generator **30** to generate the droplets **82**. In addition, the controller **90** is configured to drive the laser generator **50** to fire the laser pulse **51**. The generation of the laser pulse **51** may be controlled to be associated with the generation of droplets **82** by the controller **90** so as to make the laser pulse **51** hit each target **82** in sequence.

(29) In some embodiments, the droplet generator **30** includes a reservoir **31** and a nozzle assembly **32**. The reservoir **31** is configured for holding the target material **80**. In some embodiments, one gas line **41** is connected to the reservoir **31** for introducing pumping gas, such as argon, from a gas source **40** into the reservoir **31**. By controlling the gas flow in the gas line **41**, the pressure in the reservoir **31** can be manipulated. For example, when gas is continuously supplied into the reservoir **31** via the gas line **41**, the pressure in the reservoir **31** increases. As a result, the target material **80** in the reservoir **31** can be forced out of the reservoir **31** in the form of droplets **82**.

(30) FIGS. 2A-2H are various views of the sectional collector **60** in accordance with various embodiments. FIG. 2A is a top view of the sectional collector **60**. FIGS. 2B and 2E are cross-sectional views of the sectional collector **60** along the line B-B shown in FIG. 2A. FIGS. 2C and 2D are detailed views of a collector section **60C** in accordance with various embodiments. FIGS. 2F and 2G are detailed views of overlap regions **62**, **63** of the sectional collector **60** depicted in FIG. 2B. FIG. 2H is a top view of the sectional collector **60** including ring segments, in accordance with various embodiments.

(31) In FIG. 2A, the sectional collector **60** is shown including three collector sections **60A**, **60B**, **60C**. The collector section **60A** is substantially mirror-polished, includes an upper portion **600** facing the droplets **82**, a support portion **610** configured to support the upper portion **600**, and is positioned in a central region of the sectional collector **60**. In some embodiments, the upper portion **600** and the support portion **610** are monolithically formed. In some embodiments, the support portion **610** encloses and/or secures the upper portion **600**, for example by clamps or other securing structure holding the outer edge of the upper portion **600**.

(32) In some embodiments, the collector section **60A** includes material such as stainless steel, or the like, and may further include one or more coatings of another material, such as Ru, ZrN/ZrO<sub>2</sub> multilayers, or other suitable material for providing a mirror surface. In some embodiments, the material has Young's Modulus greater than about 200 GPa. The collector section

**60A** has diameter  $D_{\text{sub.60A}}$ , which may be uniform for the entire collector section **60A**, in some embodiments. In some other embodiments, the diameter  $D_{\text{sub.60A}}$  may be one of at least two diameters of the collector section **60A**. For example, for the collector section **60A** that has elliptical cross-section normal to the Z-axis, the diameter  $D_{\text{sub.60A}}$  may be a major diameter (or “major axis”) or a minor diameter (or “minor axis”). In some embodiments, the diameter  $D_{\text{sub.60A}}$  is in a range of about 100 mm to about 600 mm (e.g., about 400 mm), though larger or smaller diameters may be desirable in other embodiments. The collector section **60A** includes the window **55**, which is substantially positioned at the center of the collector section **60A**, in some embodiments. As shown in FIG. 2B, the collector section **60A** further has width  $W_{\text{sub.60A}}$ , which is a distance between the outer edge of the collector section **60A** and the outer edge of the window **55** at the surface of the collector section **60A** facing the laser generator **50**. In some embodiments, the width  $W_{\text{sub.60A}}$  is substantially uniform over the entire collector section **60A**. The collector section **60A** is configured to reflect a first set of photons corresponding to the central region of the sectional collector which is described in further detail with reference to FIG. 2E. The collector section **60A** further has thickness  $t_{\text{sub.60A}}$ , which is illustrated in FIG. 2F. In some embodiments, the thickness  $t_{\text{sub.60A}}$  of the collector section **60A** is substantially uniform (e.g., having variation of less than about 10%, about 5% or about 1%) across the entirety of the collector section **60A**.

(33) In some embodiments, the collector section **60A** is positioned nearest the laser generator **50**, and furthest the droplet **82**, along the Z-axis, of the three collector sections **60A-60C**. In some embodiments, the Z-axis, which is parallel to the central (or “optical”) axis **61** (see FIG. 1B) of the sectional collector **60**, is parallel to Earth's gravity, or perpendicular to Earth's gravity, though other orientations may also be desirable depending on, for example, position of the sectional collector **60** in the lithography system **10**. Configuring the optical axis **61** of the sectional collector **60** to be perpendicular to Earth's gravity may simplify calculation of path of motion of the droplets **82**, as the droplets **82** may travel in a direction generally parallel to the Earth's gravity.

(34) The collector section **60B** is substantially mirror-polished, and is positioned offset from the collector section **60A**, as shown in FIG. 2B. In the orientation shown in FIG. 2B, the collector section is offset from the collector section **60A** along the Z direction. The collector section **60B** is positioned in a first peripheral region of the sectional collector **60**. In some embodiments, the collector section **60B** includes material such as stainless steel, or the like. In some embodiments, the material has Young's Modulus greater than about 200 GPa. The collector section **60B** may further include one or more coatings of another material, such as Ru, ZrN/ZrO<sub>2</sub> multilayers, or other suitable material for providing a mirror surface. The collector section **60B** has diameter  $D_{\text{sub.60B}}$ , which may be uniform for the entire collector section **60B**, in some embodiments. In some other embodiments, the diameter  $D_{\text{sub.60B}}$  may be one of at least two diameters of the collector section **60B**. For example, for the collector section **60B** that has elliptical cross-section normal to the Z-axis, the diameter  $D_{\text{sub.60B}}$  may be a major diameter (or “major axis”) or a minor diameter (or “minor axis”). In some embodiments, the diameter  $D_{\text{sub.60B}}$  is in a range of about 200 mm to about 800 mm, though larger or smaller diameters may be desirable in other embodiments. The collector section **60B** is generally ring-shaped, having an inner edge and an outer edge (outer edge is depicted in phantom in FIG. 2A), and may be substantially aligned with the center of the collector section **60A**, in some embodiments. As shown in FIG. 2B, the collector section **60B** further has width  $W_{\text{sub.60B}}$ , which is a distance between the outer edge of the collector section **60B** and the inner edge of the collector section **60B**. The inner edge of the collector section **60B** overlaps the outer edge of the collector section **60A** in an overlap region **62** depicted in FIG. 2B, and described in detail with reference to FIG. 2F. The overlap region **62** is configured to allow flow of air or a gas into and/or from a gap between surfaces of the collector section **60B** and the collector section **60A**, which is described in detail with reference to FIGS. 3A-3B. In some embodiments, the width  $W_{\text{sub.60B}}$  is substantially uniform over the entire collector section **60B**. The collector section **60B** is configured to reflect a second set of photons

corresponding to the first peripheral region of the sectional collector **60**, which is described in further detail with reference to FIG. 2E. The collector section **60B** further has thickness  $t_{\text{sub.60B}}$ , which is illustrated in FIG. 2F and FIG. 2G. In some embodiments, the thickness  $t_{\text{sub.60B}}$  of the collector section **60B** is substantially uniform (e.g., having variation of less than about 10%, about 5% or about 1%) across the entirety of the collector section **60B**.

(35) The collector section **60C** is substantially mirror-polished, and is positioned offset from the collector section **60B**, as shown in FIG. 2B. In the orientation shown in FIG. 2B, the collector section **60C** is offset from the collector section **60B** along the Z direction. The collector section **60C** is positioned in a second peripheral region of the sectional collector **60**. The first peripheral region is generally between the central region and the second peripheral region. In some embodiments, the collector section **60C** includes material such as stainless steel, or the like. In some embodiments, the material has Young's Modulus greater than about 200 GPa. The collector section may further include one or more coatings of another material, such as Ru, ZrN/ZrO<sub>2</sub> multilayers, or other suitable material for providing a mirror surface. The collector section **60C** has diameter  $D_{\text{sub.60C}}$ , which may be uniform for the entire collector section **60C**, in some embodiments. In some other embodiments, the diameter  $D_{\text{sub.60C}}$  may be one of at least two diameters of the collector section **60C**. For example, for the collector section **60C** that has elliptical cross-section normal to the Z-axis, the diameter  $D_{\text{sub.60C}}$  may be a major diameter (or “major axis”) or a minor diameter (or “minor axis”). In some embodiments, the diameter  $D_{\text{sub.60C}}$  is in a range of about 300 mm to about 1000 mm, though larger or smaller diameters may be desirable in other embodiments. The collector section **60C** is generally ring-shaped, having an inner edge and an outer edge (outer edge is depicted in phantom in FIG. 2A), and may be substantially aligned with the center of the collector section **60A**, in some embodiments. As shown in FIG. 2B, the collector section **60C** further has width  $W_{\text{sub.60C}}$ , which is a distance between the outer edge of the collector section **60C** and the inner edge of the collector section **60C**. The inner edge of the collector section **60C** overlaps the outer edge of the collector section **60B** in an overlap region **63** depicted in FIG. 2B, and described in detail with reference to FIG. 2G. The overlap region **63** is configured to allow flow of air or a gas into and/or from a gap between surfaces of the collector section **60C** and the collector section **60B**, which is described in detail with reference to FIGS. 3A-3B. In some embodiments, the width  $W_{\text{sub.60C}}$  is substantially uniform over the entire collector section **60C**. The collector section **60C** is configured to reflect a third set of photons corresponding to the second peripheral region of the sectional collector **60**, which is described in further detail with reference to FIG. 2E. The collector section **60C** further has thickness  $t_{\text{sub.60C}}$ , which is illustrated in FIG. 2G. In some embodiments, the thickness  $t_{\text{sub.60C}}$  of the collector section **60C** is substantially uniform (e.g., having variation of less than about 10%, 5% or 1%) across the entirety of the collector section **60C**.

(36) In some embodiments, the width  $W_{\text{sub.60A}}$  of the collector section **60A** corresponding to the central region is substantially equal to the widths  $W_{\text{sub.60B}}$ ,  $W_{\text{sub.60C}}$  of the collector sections **60B**, **60C** corresponding to the first and second peripheral regions, respectively. In some embodiments, the width  $W_{\text{sub.60A}}$  is in a range of about 50 mm to about 300 mm. In some embodiments, the widths  $W_{\text{sub.60B}}$ ,  $W_{\text{sub.60C}}$  are each in a range of about 50 mm to about 300 mm. In some embodiments, the widths  $W_{\text{sub.60B}}$ ,  $W_{\text{sub.60C}}$  are about 100 mm. In some embodiments, at least one of the widths  $W_{\text{sub.60A}}$ - $W_{\text{sub.60C}}$  is different from the other of the widths  $W_{\text{sub.60A}}$ - $W_{\text{sub.60C}}$ . For example, to avoid deformation due to self-weight, it may be desirable for peripherally-located collector sections, such as the collector sections **60B**, **60C**, to have similar width to, or lower width than, the centrally-located collector section(s), such as the collector section **60A**. In such embodiments, the width  $W_{\text{sub.60C}}$  may be less than the width  $W_{\text{sub.60B}}$ , which may be less than the width  $W_{\text{sub.60A}}$ . In some embodiments, either of the widths  $W_{\text{sub.60B}}$ ,  $W_{\text{sub.60C}}$  is less than the width  $W_{\text{sub.60A}}$  by an amount in a range from about 20 mm to about 300 mm. In some embodiments, variance among the widths  $W_{\text{sub.60A}}$ - $W_{\text{sub.60C}}$

may be less than about 50%, less than about 30% or less than about 10%. Generally, if variance exists among the widths  $W_{\text{sub.60A}}$ - $W_{\text{sub.60C}}$ , the width  $W_{\text{sub.60A}}$  is greater than either or both of the widths  $W_{\text{sub.60B}}$ ,  $W_{\text{sub.60C}}$  to avoid deformation of the collector sections **60B**, **60C** located more peripherally in the sectional collector **60**. For example, a ratio of width  $W_{\text{sub.60A}}$  over width  $W_{\text{sub.60B}}$  or width  $W_{\text{sub.60C}}$  may be in a range of about 1 to about 1.5. A ratio of width  $W_{\text{sub.60B}}$  over width  $W_{\text{sub.60C}}$  may be in a range of about 0.7 to about 1.5, in some embodiments. In some embodiments, widths  $W_{\text{sub.60A}}$ ,  $W_{\text{sub.60B}}$ ,  $W_{\text{sub.60C}}$  may be in a ratio of about 1:0.8:0.8.

(37) In FIG. 2C and FIG. 2D, the collector section **60C** is shown as an example to illustrate cross-sectional dimensions in two configurations in accordance with various embodiments. Although the collector section **60C** is shown in FIGS. 2C and 2D, the collector sections **60A** and **60B** may also be configured similarly. In some embodiments, at least one of the collector sections **60A-60C** is configured as shown in FIG. 2C, and at least one of the collector sections **60A-60C** is configured as shown in FIG. 2D.

(38) In FIG. 2C, the collector section **60C** is curved and has substantially uniform thickness  $t_{\text{sub.60C}}$  over its entire volume. In some embodiments, the thickness  $t_{\text{sub.60C}}$  is in a range of about 1 mm to about 20 mm. A first surface **600** of the collector section **60C** faces the droplet **82**/plasma **88**, and has a curved mirror surface for reflecting the EUV radiation **84** toward the focal point **87**. A second surface **615** of the collector section **60C** is opposite the first surface **600**, and may have substantially the same curvature as, and be parallel to, the first surface **600**. A third surface **620** of the collector section **60C** may be the outer edge of the collector section **60C**. In some embodiments, the third surface **620** is substantially perpendicular to the first surface **600** and/or the second surface **615**. A fourth surface **630** of the collector section **60C** may be the inner edge of the collector section **60C**. In some embodiments, the fourth surface **630** is substantially perpendicular to the first surface **600** and/or the second surface **615**. In some embodiments, the third surface **620** and/or the fourth surface **630** may make an obtuse or acute angle with the first surface **600**. In some embodiments, the third and fourth surfaces **620**, **630** are configured to be angled corresponding to the first surface **600** in such a way as to prevent reflection of the EUV radiation **84** from the third and fourth surfaces **620**, **630**.

(39) In FIG. 2D, thickness of the collector section **60C** is not uniform. In the configuration shown, the collector section **60C** has a substantially planar lateral second surface **615L** and a substantially planar vertical second surface **615V**. The lateral second surface **615** is substantially perpendicular to the vertical second surface **615V**. In some embodiments, the collector section **60C** of FIG. 2D includes the third and fourth surfaces **620**, **630**. In some other embodiments, the third and/or fourth surface **620**, **630** does not exist, such that the vertical second surface **615V** and/or the lateral second surface **615L** makes a substantially sharp junction with the first surface **600**. Increasing the thickness of the collector section **60C** as shown in FIG. 2D can reduce self-weight deformation of the collector section **60C**, which is generally inversely proportional to thickness of the collector section **60C**. In some embodiments, the thickness  $t_{\text{sub.60C}}$  shown in FIG. 2D is maximum thickness of the collector section and may be in a range of about 1 mm to about 30 mm.

(40) In FIG. 2B, each of the collector sections **60B-60C** is adjustable in position and/or orientation by a corresponding actuator system **95B-95C**, which may be referred to collectively as “actuator systems **95**.” The actuator system **95B** contacts the collector section **60B**, and the actuator system **95C** contacts the collector section **60C**. In some embodiments, each of the actuator systems **95B-95C** may include at least three actuator modules (illustrated in phantom in FIG. 2A) to provide alignment of each collector section **60A-60C**. In some embodiments, the actuator modules are ball screws or the like, for providing fine control of position of each of the collector sections **60B-60C** along the z-axis. In some embodiments, the actuator systems **95** further include rotational actuators, such as tilt stages or the like, for providing fine control of angular orientation of each of the collector sections **60A-60C**. Taking the collector section **60B** as an example, in some embodiments,

number of actuator modules attached to the collector section **60B** may be determined to prevent self-deformation of the collector section **60B** between actuator modules based on parameters of the collector section **60B**, such as diameter  $D_{\text{sub.60B}}$ , width  $W_{\text{sub.60B}}$ , thickness  $t_{\text{sub.60B}}$ , and material of the collector section **60B**.

(41) In some embodiments, the collector section **60A** has substantially fixed position and orientation, and the collector sections **60B**, **60C** have adjustable position and orientation, such that no actuator system is attached to the collector section **60A**. In such a configuration, the number of actuator systems **95** may be equal to one less than the number of collector sections. For example, the sectional collector **60** may include four collector sections and three actuator systems **95**. Having too few actuator systems **95** may increase difficulty of aligning each collector section to focus the EUV radiation on the IF point **87**. Each of the actuator modules and/or rotational actuators of the actuator systems **95B-95C** may be electrically connected to and controlled by the controller **90**.

(42) Referring to FIG. 2E, the plasma **88** formed from the droplet **82** emits the EUV radiation in a non-unidirectional pattern, which may be omnidirectional in some embodiments. In some embodiments, the EUV radiation is emitted generally in a hemisphere toward the sectional collector **60**, and very little EUV radiation is emitted in a hemisphere facing away from the sectional collector **60**. Each of the collector sections **60A-60C** of the sectional collector **60** is configured with a position and elliptical orientation to reflect a portion of the EUV radiation toward the focal point **87**. In some embodiments, a number of conical regions **900A-900C** corresponding to the number of collector sections **60A-60C** exist, as shown in FIG. 2E. In some embodiments, the conical regions **900A-900C** are non-overlapping. A central conical region **900A** corresponds to the collector section **60A**, and extends from a sidewall of the opening **55** to the inner edge of the collector section **60B**. The central conical region **900A** includes an angular region of size  $\theta_{\text{sub.A}}$  as depicted in FIG. 2E. A first peripheral conical region **900B** corresponds to the collector section **60B**, and extends from the inner edge of the collector section **60B** to the inner edge of the collector section **60C**. The first peripheral conical region **900B** includes an angular region of size  $\theta_{\text{sub.B}}$ . A second peripheral conical region **900C** corresponds to the collector section **60C**, and extends from the inner edge of the collector section **60C** to the outer edge of the collector section **60C**. The second peripheral conical region **900C** includes an angular region of size  $\theta_{\text{sub.C}}$ . In some embodiments, the sizes  $\theta_{\text{sub.A}}-\theta_{\text{sub.C}}$  are substantially equal. In some embodiments, the size  $\theta_{\text{sub.A}}$  is larger than the size  $\theta_{\text{sub.B}}$ , which is in turn larger than the size  $\theta_{\text{sub.C}}$ . This may be advantageous in configurations in which the EUV radiation is concentrated more in the central conical region **900A** than in the first and/or second peripheral conical region **900B**, **900C**.

(43) Based on the arrangement just described and illustrated in FIG. 2E, the collector section reflects photons from the plasma **88** in the central conical region **900A**, the collector section **60B** reflects photons from the plasma **88** in the first peripheral conical region **900B**, and the collector section reflects photons from the plasma **88** in the second peripheral conical region **900C**, each substantially to the focal point **87** (see FIG. 1B).

(44) FIGS. 2F, 2G are detailed views of the overlap regions **62**, **63** of FIG. 2B, respectively. As described above with reference to FIG. 2B, the sectional collector **60** has a hierarchical structure, in which the collector section **60A** underlies the collector section **60B**, which underlies the collector section **60C**. The overlap regions **62**, **63** provide full optical coverage, which avoids loss of photons and/or dead zones (e.g., ring-shaped zones with substantially no reflected photons) in the EUV radiation **84** collected by and emitted from the sectional collector **60**.

(45) In FIG. 2F, the overlap region **62** is a region in which the collector section **60B** overlaps the collector section **60A**. The overlap region **62** may have a width  $O_{\text{sub.62}}$  equal to distance between the inner edge of the collector section **60B** and the outer edge of the collector section **60A**. The distance may be measured as substantially tangential to the mirror surface of either/both of the collector sections **60A**, **60B** near the inner edge of the collector section **60B** and the outer edge of the collector section **60A**. The overlap region **62** may further have a gap of dimension  $S_{\text{sub.62}}$

between the collector sections **60A**, **60B**. The dimension  $S_{.62}$  may be in a range of about 1 mm to about 3 mm, in some embodiments. The dimension  $S_{.62}$  may be measured normal to either/both of the mirror surfaces of the collector sections **60A**, **60B** within the overlap region **62**. The dimension  $S_{.62}$  being less than about 1 mm may leave insufficient space between the collector sections **60A**, **60B** for adjusting orientation of the collector section **60B**. The dimension  $S_{.62}$  being greater than about 3 mm may degrade uniformity between the EUV radiation **84** impinging upon the focal point **87** from the collector section **60A** and from the collector section **60B**. In some embodiments, the width  $O_{.62}$  is in a range of about 1 mm to about 20 mm. In some embodiments, a ratio between the width  $O_{.62}$  and the dimension  $S_{.62}$  is in a range of about 0.1 to about 20.

(46) In FIG. 2G, the overlap region **63** is a region in which the collector section **60C** overlaps the collector section **60B**. The overlap region **63** may have a width  $O_{.63}$  equal to distance between the inner edge of the collector section **60C** and the outer edge of the collector section **60B**. The overlap region **63** further has a gap of dimension  $S_{.63}$  between the collector sections **60B**, **60C**. Details of the width  $O_{.63}$  and the dimension  $S_{.63}$  are similar to those described with reference to width  $O_{.62}$  and dimension  $S_{.62}$  corresponding to FIG. 2F. In some embodiments, the width  $O_{.63}$  may be less than the width  $O_{.62}$ , for example, due to differences in curvature between the collector sections **60A-60C**. In some other embodiments, the width  $O_{.63}$  is substantially the same as the width  $O_{.62}$ , or may be greater than the width  $O_{.62}$ .

(47) FIG. 2H is a top view of the sectional collector **60** in accordance with various embodiments. In the configuration shown in FIG. 2H, the sectional collector **60** includes two sectional dimensions, such as the vertical dimension described with reference to FIGS. 2A-2B, and a further radial dimension, as shown. In some embodiments, the collector section **60B** and/or the collector section **60C** each includes at least two collector segments, such as the collector segments **60131**, **6062** and the collector segments **60C1**, **60C2**, respectively. The collector section **60B** is described as an example for illustrative purposes, and the description is equally applicable for the collector section **60C**. By further dividing each collector section **60B**, **60C** into collector segments **6061**, **6062**, **60C1**, **60C2**, increased modularity may be achieved, which may improve manufacturability and repairability. Reduced dimensions of the collector segments **6061**, **6062**, **60C1**, **60C2** relative to dimensions of the collector sections **60B**, **60C** may also reduce self-deformation as strain undergone by each collector segment **6061**, **6062**, **60C1**, **60C2** is reduced by having reduced dimensions.

(48) In the collector section **60B** shown in FIG. 2H, the collector section **60B** includes two semicircular, semielliptical, or otherwise shaped collector segments **6061**, **6062**. In some embodiments, the collector section **60B** includes three, four or more collector segments. In some embodiments, the collector segments are each of equal dimensions (e.g., diameter, width, thickness, curvature) and mass, though other configurations wherein the collector segments include different dimensions and/or mass may be desirable, as well. Each collector segment **6061**, **6062** may have position and orientation determined by the actuator system **95B** connected thereto. Generally, the collector segments **6061**, **6062** are arranged to minimize gaps between ends of the collector segments **6061**, **6062**. For example, a gap **650** between an edge of the collector segment **60131** and an edge of the collector segment **6062** may be less than about 1 mm. The gap **650** being larger than about 1 mm may adversely impact uniformity of the EUV radiation **84** leaving the collector **60**.

(49) In FIGS. 2A-2H, the sectional collector **60** including collector sections **60A-60C** employs a hierarchical structure to reduce surface deformation under self-weight, allowing for larger collector surface area and higher EUV radiation intensity, which improves WPD throughput due to both increased EUV radiation intensity and reduced downtime for repair. In addition to these benefits, the gaps between collector sections **60A-60C** in the overlap regions **62**, **63** improve air flow over the surface of the sectional collector **60**, which prevents contamination of the collector sections

**60A-60C**, and further reduces downtime for repair, which further improves WPD throughput. Description of air flow in the sectional collector **60** is provided with reference to FIGS. **3A-3D**. (50) FIGS. **3A, 3B** illustrate air flow in the sectional collector **60** in accordance with various embodiments. FIG. **3A** illustrates air flow when a positive pressure differential causes air to blow through the gaps in the overlap regions **62, 63**, and FIG. **3B** illustrates air flow when a negative pressure differential causes air to vent through the gaps in the overlap regions **62, 63**.

(51) In FIG. **3A**, a positive pressure differential established by at least the pumps **66, 68** (FIG. **1B**) causes various air flows indicated by arrows in the figure. A cone flow **310** is an air flow in generally the z-direction from the window **55** toward the focal point **87** (FIG. **1B**). A perimeter flow **320** is a radial flow inward from the outer edge of the collector section **60C** toward the center of the collector section e.g., toward the window **55**. An umbrella flow **330** is a radial flow outward from the window **55** toward the outer edge of the collector section **60C**. Due to the gaps between the collector sections **60A, 60C** in the overlap regions **62, 63** and the positive pressure differential, an inward gap flow **340** is present which is a radial flow inward and upward from behind the collector sections **60A-60C** toward the cone flow **310**. The inward gap flow **340** increases air flow across the surfaces of the collector sections **60B**, which aids in preventing contaminants (e.g., tin debris) from settling on the mirror surfaces of the collector sections **60A, 60B**. In some embodiments, the air flow at the surfaces of the collector sections **60A-60C** is in a range of about 50 slm to about 200 slm, such as about 90 slm. As such, downtime may be reduced due to a longer period before contaminant buildup affects yield.

(52) In FIG. **3B**, a negative pressure differential established by at least the pumps **66, 68** causes an outward gap flow **340** for taking particles (e.g., tin debris) away from the sectional collector **60** through the gaps at the overlap regions **62, 63**. Other air flows are similar to those described with reference to FIG. **3A**. In some embodiments, the positive and negative pressure differentials are established alternately in a repeating sequence to remove the particles effectively from the sectional collector **60** while minimizing contaminant buildup on the mirror surfaces of the collector sections **60A-60C**.

(53) FIG. **3C** and FIG. **3D** are views of a collector section (e.g., the collector section **60C**) or a collector segment (e.g., the collector segment **60C1**, as shown) in accordance with various embodiments. FIG. **3C** and FIG. **3D** are described with reference to the collector segment **60C1** for purposes of illustration. FIG. **3C** is a perspective view of the collector segment **60C1**, and FIG. **3D** is a cross-sectional view of the collector segment **60C1** along the line D-D' of FIG. **3C**. FIG. **3E** is a view of the sectional collector **60** illustrating air flow in accordance with various embodiments.

(54) In some embodiments, one or more of the collector segments of at least one of the collector sections **60B, 60C**, such as the collector segment **60C1**, is hollow (e.g., includes a cavity) and has a first opening **640** and a second opening **660**, as shown in FIG. **3C** and FIG. **3D**. The first opening **640** may be located in the second surface **615** (described with reference to FIG. **2C**), and the second opening **660** may be located in, or replace, the fourth surface **630** (see FIG. **2C**). The first opening **640** is in fluid communication with the second opening **660**. Flow of air through the collector segment **60C1** is shown as first, second, and third air flows **370, 380, 390**. The first air flow **370** is shown in FIG. **3D**, which enters the first opening **640**. The second air flow **380** exits the second opening **660** toward the center of the sectional collector **60**. The third air flow **390** flows through the collector segment **60C1** from the first opening **640** toward the second opening **660**. The second air flow **380** increases air flow across the surfaces of the sectional collector **60**, as shown in FIG. **3E**, which aids in preventing buildup of contaminants (e.g., tin debris) on the surfaces of the sectional collector **60**.

(55) FIG. **4** is a flowchart of a process **401** for forming a device in accordance with various embodiments. In some embodiments, the process **401** for forming the device includes a number of operations (**400, 410, 420** and **430**). The process **401** for forming the device will be further described according to one or more embodiments. It should be noted that the operations of the

process **401** may be rearranged or otherwise modified within the scope of the various aspects. It should further be noted that additional processes may be provided before, during, and after the process **401**, and that some other processes may be only briefly described herein. In some embodiments, the process **401** is performed by the lithography exposure system **10** described in FIGS. **1A-3E**.

(56) In operation **400**, a mask layer is deposited over a substrate. In some embodiments, the mask layer includes a photoresist layer that is sensitive to the EUV radiation **84**. In some embodiments, the substrate is a semiconductor substrate, such as the semiconductor wafer **22** (see FIG. **1A**). In some embodiments, the substrate is a layer overlying the semiconductor substrate, such as a dielectric layer, a metal layer, a hard mask layer, or other suitable layer. In some embodiments, the mask layer is deposited by spin coating or other suitable process.

(57) In operation **410**, first radiation is reflected from a central collector section (e.g., the collector section **60A**), and second radiation is reflected from a first peripheral collector section (e.g., the collector section **60B**). The first and second radiation are reflected along an optical path between the sectional collector **60** and the mask layer, which may be on the semiconductor wafer **22**. In some embodiments, the first and second radiation are reflected according to a pattern, such as exists on the mask **18**, which may be a reflective mask. In some embodiments, third radiation is further reflected from a second peripheral collector section (e.g., the collector section **60C**), may be reflected along the optical path, and may be reflected according to the pattern. The first, second, and third radiation may be EUV radiation, and may correspond to the regions **900A-900C** shown in FIG. **2E**. In some embodiments, the first peripheral collector section overlaps the central collector section, and is separated from the central collector section by a first gap (e.g., as shown in FIG. **2F**). In some embodiments, the second peripheral collector section overlaps the first peripheral collector section, and is separated from the first peripheral collector section by a second gap (e.g., as shown in FIG. **2G**).

(58) In operation **420**, openings are formed in the mask layer by removing first regions of the mask layer exposed to the first radiation and second regions of the mask layer exposed to the second radiation. In some other embodiments, the openings are formed by removing regions of the mask layer not exposed to the first radiation or the second radiation. In some embodiments, operation **420** further includes removing third regions of the mask layer exposed to the third radiation, or removing regions of the mask layer not exposed to the first, second or third radiation.

(59) In operation **430**, material of a layer underlying the mask layer is removed. The material removed is in regions of the layer exposed by the openings in the mask layer. In some embodiments, the layer is a dielectric layer, a semiconductor layer, or other layer.

(60) FIG. **5** is a flowchart of a process **501** for forming a device in accordance with various embodiments. In some embodiments, the process **501** for forming the device includes a number of operations (**500**, **510** and **520**). The process **501** for forming the device will be further described according to one or more embodiments. It should be noted that the operations of the process **501** may be rearranged or otherwise modified within the scope of the various aspects. It should further be noted that additional processes may be provided before, during, and after the process **501**, and that some other processes may be only briefly described herein. In some embodiments, the process **501** is performed by the lithography exposure system **10** described in FIGS. **1A-3E**.

(61) In operation **500**, a first layer of a first wafer is patterned by radiation from a first sectional collector. In some embodiments, the first sectional collector is any of the sectional collectors **60** shown in FIGS. **1A-3E**. In some embodiments, the first wafer is the semiconductor wafer **22** shown in FIG. **1A**, and the first layer is a photoresist layer on the semiconductor wafer **22**. In some embodiments, the radiation is the EUV radiation **84** reflected by the sectional collector **60**. In some embodiments, the patterning includes reflecting the EUV radiation **84** by a mask, such as the mask **18** (FIG. **1A**), and projecting the reflected EUV radiation onto the first layer by the POB **130**.

(62) In operation **510**, a second sectional collector is formed by replacing at least one first collector

segment of the first sectional collector with an equal number of corresponding second collector segments. In some embodiments, the first collector segment is a collector section, such as the collector section **60B** or the collector section **60C** of FIG. 2A. In some embodiments, the first collector segment is a collector segment, such as any of the collector segments **60131**, **6062**, **60C1**, **60C2** shown in FIG. 2H.

(63) In some embodiments, the replacement includes removing a collector section or segment based on a threshold condition. For example, the threshold condition may include a deformation threshold based on an unacceptable level of self-weight deformation of the collector section or segment, such that the first collector segment is replaced after exceeding the deformation threshold. In some embodiments, the deformation threshold is a numerical deformation condition, such as greater than about 0.5 mm, greater than about 1 mm, or the like. In some embodiments, the deformation threshold is a percentage deformation condition, such as greater than about 1%, greater than about 5%, or the like.

(64) The threshold condition may include a cleanliness condition based on an unacceptable level of contamination, such as tin debris buildup, on the collector section or segment. In some embodiments, the cleanliness condition is a contamination condition. In some embodiments, the contamination condition includes a percentage contamination condition, such as surface area of the mirror-surface of the first collector segment including contamination greater than about 1%, greater than about 5%, or another suitable percentage condition. In some embodiments, the contamination condition includes a reflectivity condition, such as reflectivity of the first collector segment being less than about 95% of original reflectivity, less than about 90% of the original reflectivity, or another suitable reflectivity condition. In some embodiments, the original reflectivity is reflectivity of the first collector segment immediately preceding or following installation into the sectional collector **60**.

(65) The threshold condition may include a scheduling threshold. For example, the scheduling threshold may include a period of time since installation of the collector section or segment, such as greater than about 14 days, greater than about one month, or another suitable period of time. The scheduling threshold may include total runtime since installation of the collector section or segment, such as greater than about 12 days, greater than about 3 weeks, or another suitable total runtime. The scheduling threshold may include a number of wafers processed since installation of the collector section or segment, such as greater than about 10,000 wafers, greater than about 100,000 wafers, or another suitable number of wafers.

(66) The second collector segment(s) may have substantially identical physical characteristics (shape, mass, material, surface roughness) as the first collector segment in its original form (e.g., prior to warpage or contamination). The second collector segment(s) may be installed by first removing the first collector segment(s), then attaching the second collector segments(s) in place of the removed first collector segment(s). In some embodiments, a calibration operation is performed following replacement of the first collector segment(s) with the second collector segment(s). The calibration operation may include adjusting position and/or orientation of the second collector segment(s) by the actuator systems **95**.

(67) In operation **520**, a second layer on a second wafer is patterned by radiation from the second sectional collector. In some embodiments, the second wafer is a semiconductor wafer similar to the semiconductor wafer **22** shown in FIG. 1A, and the second layer is a photoresist layer on the second wafer. In some embodiments, the radiation is EUV radiation similar to the EUV radiation **84** reflected by the sectional collector **60** following replacement of the collector section(s) or collector segment(s). In some embodiments, the patterning includes reflecting the EUV radiation by a mask, either the mask **18** (FIG. 1A) or a second mask including a pattern different from the mask **18**, and projecting the reflected EUV radiation onto the second layer by the POB **130**.

(68) Embodiments may provide advantages. Each of the sectional collectors **60A-60C** may have a different elliptical surface to focus the EUV light on the same focal point **87** (also referred to as the

“intermediate focal (IF) point;” see FIG. 1B). Use of the hierarchical structure reduces surface deformation under self-weight, as each of the collector sections **60A-60C** may have significantly lower mass and smaller dimensions than a monolithic collector of similar dimensions (e.g., the diameter D.sub.60C) would have. The hierarchical structure further provides the advantage of modularity. If any one of the collector sections **60A-60C** is defective, deformed or overly contaminated, the defective, deformed or contaminated collector sections may be replaced without replacing the entire collector, which is an advantage over the monolithic collector of similar dimensions. The sectional collector **60** is also protected from contamination by the target material (e.g., Sn) by the additional flow of air/gas through the gaps in the overlap regions **62, 63**, which decreases downtime that would be associated with repair of the collector, as described with reference to FIGS. **3A-3B**.

(69) In accordance with at least one embodiment, a method includes: depositing a mask layer over a substrate; directing first radiation reflected from a central collector section of a sectional collector of a lithography system toward the mask layer according to a pattern; directing second radiation reflected from a peripheral collector section of the sectional collector toward the mask layer according to the pattern, wherein the peripheral collector section is vertically separated from the central collector section by a gap; forming openings in the mask layer by removing first regions of the mask layer exposed to the first radiation and second regions of the mask layer exposed to the second radiation; and removing material of a layer underlying the mask layer exposed by the openings.

(70) In accordance with at least one embodiment, a method includes: patterning a first layer on a first wafer by first radiation from a first sectional collector; forming a second sectional collector by replacing a first collector segment of the first sectional collector with a second collector segment; and patterning a second layer on a second wafer by second radiation from the second sectional collector.

(71) In accordance with at least one embodiment, a lithography system includes a wafer stage, projection optics, a mask stage, illumination optics, and a light source. The wafer stage is configured to support a wafer. The projection optics are configured to direct patterned radiation onto a region of the wafer. The mask stage is configured to form and direct the patterned radiation to the projection optics. The illumination optics are configured to direct unpatterned radiation to the mask stage. The light source includes a droplet generator configured to generate a droplet, a laser source configured to emit at least one laser pulse toward the droplet, and a sectional collector configured to reflect radiation generated by the droplet toward the illumination optics. The sectional collector includes a central collector section configured to reflect a first portion of the radiation, and a first peripheral collector section configured to reflect a second portion of the radiation. The first peripheral collector section overlaps the central collector section in an overlap region. The overlap region includes a vertical gap between the first peripheral collector section and the central collector section.

(72) The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

## Claims

1. A lithography system, comprising: projection optics configured to direct patterned radiation onto a region of the wafer; a mask stage configured to form and direct the patterned radiation to the projection optics; illumination optics configured to direct unpatterned radiation to the mask stage; and a light source comprising: a sectional collector configured to reflect radiation generated by a droplet toward the illumination optics, the sectional collector including: a central collector section configured to reflect a first portion of the radiation; and a first peripheral collector section configured to reflect a second portion of the radiation, the first peripheral collector section is vertically separated from the central collector section by a vertical gap, the first peripheral collector section further comprising: a first surface configured to reflect radiation toward a focal point, the first surface being free of openings; a second surface opposite the first surface and having substantially the same curvature as the first surface; a third surface forming an outer edge of the first peripheral collector section and being substantially perpendicular to the first and second surfaces; a hollow cavity formed within the first peripheral collector section; a first opening located in the second surface; and a second opening located opposite the third surface and adjacent to an inner edge of the first peripheral collector section, wherein the first opening, the hollow cavity, and the second opening are in fluid communication to define an airflow path through the first peripheral collector section.
2. The lithography system of claim 1, wherein the first peripheral collector section overlaps the central collector section in first overlap region, the first overlap region including the vertical gap, the sectional collector further includes a second peripheral collector section overlapping the first peripheral collector section in a second overlap region.
3. The lithography system of claim 1, wherein the vertical gap is in a range of about 1 millimeter to about 3 millimeters.
4. The lithography system of claim 1, wherein the first peripheral collector section is substantially ring-shaped with a width in a range of about 50 millimeters to about 300 millimeters.
5. The lithography system of claim 1, wherein the first peripheral collector section includes a first collector segment and a second collector segment separated by at least one lateral gap.
6. The lithography system of claim 1, wherein the sectional collector further includes a second peripheral collector section overlapping the first peripheral collector section in a second overlap region, the second overlap region including a second vertical gap between the second peripheral collector section and the first peripheral collector section.
7. The lithography system of claim 1 wherein the second opening faces toward the center of the sectional collector.
8. A lithography system, comprising: a wafer stage configured to support a wafer; projection optics configured to direct patterned radiation onto a region of the wafer; a mask stage configured to form and direct the patterned radiation to the projection optics; illumination optics configured to direct unpatterned radiation to the mask stage; and a light source comprising: a droplet generator configured to generate a droplet; a laser source configured to emit at least one laser pulse toward the droplet; and a sectional collector configured to reflect radiation generated by the droplet toward the illumination optics, the sectional collector including: a central collector section configured to reflect a first portion of the radiation; and a first peripheral collector section configured to reflect a second portion of the radiation, the first peripheral collector section overlapping the central collector section in an overlap region, the overlap region including a vertical gap between the first peripheral collector section and the central collector section, and the first peripheral collector section further comprising: a first surface configured to reflect radiation toward a focal point, the first surface being free of openings; a second surface opposite the first surface and having substantially the same curvature as the first surface; a third surface forming an outer edge of the first peripheral collector section and being substantially perpendicular to the first and second surfaces; a hollow cavity formed within the first peripheral collector section; a first opening located

in the second surface; and a second opening located opposite the third surface and adjacent to an inner edge of the first peripheral collector section, wherein the first opening, the hollow cavity, and the second opening are in fluid communication to define an airflow path through the first peripheral collector section.

9. The lithography system of claim 8, wherein the sectional collector further includes a second peripheral collector section overlapping the first peripheral collector section in a second overlap region, the second overlap region including a second vertical gap between the second peripheral collector section and the first peripheral collector section.

10. The lithography system of claim 8, wherein the vertical gap is in a range of about 1 millimeter to about 3 millimeters.

11. The lithography system of claim 8, wherein the first peripheral collector section is substantially ring-shaped with a width in a range of about 50 millimeters to about 300 millimeters.

12. The lithography system of claim 8, wherein the first peripheral collector section includes a first collector segment and a second collector segment separated by at least one lateral gap.

13. The lithography system of claim 8, wherein the second opening of the first peripheral collector section faces toward the center of the sectional collector.

14. A lithography system, comprising: a light source comprising: a droplet generator configured to generate a droplet; a laser source configured to emit at least one laser pulse toward the droplet; and a sectional collector configured to reflect radiation generated by the droplet toward illumination optics, the sectional collector including: a central collector section configured to reflect a first portion of the radiation; and a first peripheral collector section configured to reflect a second portion of the radiation, the first peripheral collector section overlapping the central collector section in an overlap region, the overlap region including a vertical gap between the first peripheral collector section and the central collector section, the first peripheral collector section further comprising: a first surface configured to reflect radiation toward a focal point, the first surface being free of openings; a second surface opposite the first surface and having substantially the same curvature as the first surface; a third surface forming an outer edge of the first peripheral collector section and being substantially perpendicular to the first and second surfaces; a hollow cavity formed within the first peripheral collector section; a first opening located in the second surface; and a second opening located opposite the third surface and adjacent to an inner edge of the first peripheral collector section, wherein the first opening, the hollow cavity, and the second opening are in fluid communication to define an airflow path through the first peripheral collector section.

15. The lithography system of claim 14, wherein the sectional collector further includes a second peripheral collector section overlapping the first peripheral collector section in a second overlap region, the second overlap region including a second vertical gap between the second peripheral collector section and the first peripheral collector section.

16. The lithography system of claim 14, wherein the vertical gap is in a range of about 1 millimeter to about 3 millimeters.

17. The lithography system of claim 14, wherein the first peripheral collector section is substantially ring-shaped with a width in a range of about 50 millimeters to about 300 millimeters.

18. The lithography system of claim 14, wherein the first peripheral collector section includes a first collector segment and a second collector segment separated by at least one lateral gap.

19. The lithography system of claim 14, wherein the sectional collector further includes a second peripheral collector section overlapping the first peripheral collector section in a second overlap region.

20. The lithography system of claim 14, wherein the second opening faces toward the center of the sectional collector.

---