

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406404
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Zhang; Xiang et al.

Coding of multiple-component attributes for point cloud coding

Abstract

A method, computer program, and computer system is provided for point cloud coding. The method includes receiving, from a bitstream, data corresponding to a point cloud; obtaining from the data a first prediction residual of a first component from among a plurality of components of an attribute associated with the point cloud; reconstructing the first prediction residual; determining a predicted second prediction residual based on the reconstructed first prediction residual and at least one model parameter; obtaining a second prediction residual of a second component from among the plurality of components based on the predicted second prediction residual; reconstructing the second prediction residual; and decoding the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual.

Inventors: Zhang; Xiang (Palo Alto, CA), Gao; Wen (Palo Alto, CA), Liu; Shan (Palo Alto, CA)

Applicant: TENCENT AMERICA LLC (Palo Alto, CA)

Family ID: 80224271

Assignee: TENCENT AMERICA LLC (Palo Alto, CA)

Appl. No.: 18/368821

Filed: September 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240013445 A1	Jan. 11, 2024

Related U.S. Application Data

continuation parent-doc US 17332213 20210527 US 11816868 child-doc US 18368821
us-provisional-application US 63066121 20200814

Publication Classification

Int. Cl.: G06T9/00 (20060101); G06N20/00 (20190101)

U.S. Cl.:

CPC G06T9/001 (20130101); G06N20/00 (20190101);

Field of Classification Search

CPC: G06T (9/001); G06N (20/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10015485	12/2017	Xu et al.	N/A	N/A
10075709	12/2017	Xu et al.	N/A	N/A
10853973	12/2019	Tourapis	N/A	G06T 9/00
10909726	12/2020	Mammou	N/A	G06T 9/001
10909727	12/2020	Mammou et al.	N/A	N/A
11166048	12/2020	Yea et al.	N/A	N/A
11202054	12/2020	Yea et al.	N/A	N/A
11206426	12/2020	Sugio	N/A	N/A
11395005	12/2021	Sugio et al.	N/A	N/A
11417029	12/2021	Zhang et al.	N/A	N/A
11451802	12/2021	Yea	N/A	H04N 19/172
11483560	12/2021	Zhang et al.	N/A	N/A
11631158	12/2022	Lee et al.	N/A	N/A
11671576	12/2022	Yea et al.	N/A	N/A
11683524	12/2022	Zhang et al.	N/A	N/A
11816868	12/2022	Zhang	N/A	G06N 20/00
2011/0010400	12/2010	Hayes	N/A	N/A
2012/0014438	12/2011	Segall et al.	N/A	N/A
2014/0023139	12/2013	Xu et al.	N/A	N/A
2017/0347100	12/2016	Chou et al.	N/A	N/A
2019/0081638	12/2018	Mammou et al.	N/A	N/A
2020/0302655	12/2019	Oh	N/A	N/A
2020/0314435	12/2019	Tourapis et al.	N/A	N/A
2021/0112278	12/2020	Wang	N/A	N/A
2021/0400308	12/2020	Ray et al.	N/A	N/A
2022/0067981	12/2021	Zhang et al.	N/A	N/A
2022/0232261	12/2021	Zakharchenko	N/A	H04N 19/597
2023/0196663	12/2022	Tian et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111385555	12/2019	CN	N/A
2015/055832	12/2014	WO	N/A

2019/240215	12/2018	WO	N/A
2020/055865	12/2019	WO	N/A
2020123686	12/2019	WO	N/A

OTHER PUBLICATIONS

Graziosi et al., “An overview of ongoing point cloud compression standardization activities: video-based (V-PCC) and geometry-based (G-PCC)” (pp. 1-17) (Year: 2020). cited by examiner
Chinese Office Action dated Jan. 17, 2024 in Chinese Application No. 202180002868.3. cited by applicant

3DG “G-PCC codec description v7”, International Organisation for Standardisation Organisation Internationale De Normalisation ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, ISO/IEC JTC1/SC29/WG11, N19331, Apr. 2020, Online, (9 pages total). cited by applicant
Khaled Mammou et al., “G-PCC codec description v2”, International Organisation for Standardisation Organisation Internationale De Normalisation ISO/IEC JTC1/SC29/WG11. cited by applicant

Rufael Mekuria et al., “Requirements for Point Cloud Compression”, International Organisation for Standardisation Organisation Internationale De Normalisation ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, ISO/IEC JTC1/SC29/WG11 MPEG2016/n16330, Feb. 2016, Geneva, CH. cited by applicant

Christian Tulvan et al., “Use Cases for Point Cloud Compression (PCC)”, International Organisation for Standardisation. cited by applicant

Wei Pu et al., “Non-RCEI: Inter Color Component Residual Prediction”, Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG 16 WP 3 and ISO/IEC JTC 1/SC 29/WG 11, JCTVC-N0266, Jul. 25-Aug. 2, 2013, 14th Meeting, Vienna, AT (10 pages total). cited by applicant

“G-PCC codec description v8”, International Organisation for Standardisation Organisation Internationale De Normalisation ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, ISO/IEC JTC1/SC29/WG11, N19525, Jul. 2020, Online (140 pages total). cited by applicant

Written Opinion dated Apr. 21, 2023 issued by the Intellectual Property Office of Singapore in Application No. 11202111936V. cited by applicant

International Search Report dated Sep. 27, 2021 in International Application No. PCT/US21/37638. cited by applicant

Written Opinion of the International Searching Authority dated Sep. 27, 2021 in International Application No. PCT/US21/37638. cited by applicant

3DG, “G-PCC codec description v7”, International Organisation for Standardisation Organisation Internationale De Normalisation ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, ISO/IEC JTC1/SC29/WG11, N19331, Apr. 2020 (119 pages total). cited by applicant

Extended European Search Report issued Dec. 2022 in European Application No. 21786317.4. cited by applicant

“G-PCC codec description v2”, International Organisation for Standardisation Organisation Internationale De Normalisation ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, ISO/IEC JTC1/SC29/WG11 N18189, Jan. 2019, 39 pages, Marrakech, MA. cited by applicant

“Information technology—MPEG-I (Coded Representation of Immersive Media)—Part 9: Geometrybased Point Cloud Compression”, ISO/IEC 23090-9:2019(E), ISO/IEC JTC 1/SC 29/WG 11, Secretariat: JISC, 104 pages. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This is a Continuation of U.S. application Ser. No. 17/332,213, filed on May 27, 2021, which claims priority based on U.S. Provisional Application No. 63/066,121, filed Aug. 14, 2020, in the U.S. Patent & Trademark Office, the contents of which are incorporated herein by reference in their entireties.

FIELD

(1) This disclosure relates generally to field of data processing, and more particularly to point cloud coding.

BACKGROUND

(2) Point Cloud has been widely used in recent years. For example, it is used in autonomous driving vehicles for object detection and localization; it is also used in geographic information systems (GIS) for mapping, and used in cultural heritage to visualize and archive cultural heritage objects and collections, etc. Point clouds contain a set of high dimensional points, typically of three dimensional (3D), each including 3D position information and additional attributes such as color, reflectance, etc. They can be captured using multiple cameras and depth sensors, or Lidar in various setups, and may be made up of thousands up to billions of points to realistically represent the original scenes. Compression technologies are needed to reduce the amount of data required to represent a point cloud for faster transmission or reduction of storage.

SUMMARY

(3) Embodiments relate to a method, system, and computer readable medium for point cloud coding. According to one aspect, a method for point cloud coding is provided. The method may include receiving, from a bitstream, data corresponding to a point cloud; obtaining from the data a first prediction residual of a first component from among a plurality of components of an attribute associated with the point cloud; reconstructing the first prediction residual; determining a predicted second prediction residual based on the reconstructed first prediction residual and at least one model parameter; obtaining a second prediction residual of a second component from among the plurality of components based on the predicted second prediction residual; reconstructing the second prediction residual; and decoding the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual.

(4) According to another aspect, a computer system for point cloud coding is provided. The computer system may include one or more processors, one or more computer-readable memories, one or more computer-readable tangible storage devices, and program instructions stored on at least one of the one or more storage devices for execution by at least one of the one or more processors via at least one of the one or more memories, whereby the computer system is capable of performing a method. The method may include receiving, from a bitstream, data corresponding to a point cloud; obtaining from the data a first prediction residual of a first component from among a plurality of components of an attribute associated with the point cloud; reconstructing the first prediction residual; determining a predicted second prediction residual based on the reconstructed first prediction residual and at least one model parameter; obtaining a second prediction residual of a second component from among the plurality of components based on the predicted second prediction residual; reconstructing the second prediction residual; and decoding the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual.

(5) According to yet another aspect, a computer readable medium for point cloud coding is provided. The computer readable medium may include one or more computer-readable storage

devices and program instructions stored on at least one of the one or more tangible storage devices, the program instructions executable by a processor. The program instructions are executable by a processor for performing a method that may accordingly include receiving, from a bitstream, data corresponding to a point cloud; obtaining from the data a first prediction residual of a first component from among a plurality of components of an attribute associated with the point cloud; reconstructing the first prediction residual; determining a predicted second prediction residual based on the reconstructed first prediction residual and at least one model parameter; obtaining a second prediction residual of a second component from among the plurality of components based on the predicted second prediction residual; reconstructing the second prediction residual; and decoding the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These and other objects, features and advantages will become apparent from the following detailed description of illustrative embodiments, which is to be read in connection with the accompanying drawings. The various features of the drawings are not to scale as the illustrations are for clarity in facilitating the understanding of one skilled in the art in conjunction with the detailed description. In the drawings:
- (2) FIG. 1 illustrates a networked computer environment according to at least one embodiment;
- (3) FIGS. 2A-2B are block diagrams of point cloud update systems, according to at least one embodiment;
- (4) FIG. 2C is a diagram of a region adaptive hierarchical transform (RAHT), according to at least one embodiment;
- (5) FIG. 2D is a table of syntax elements for prediction residuals, according to at least one embodiment
- (6) FIGS. 3A-3B are operational flowcharts illustrating the steps carried out by programs for point cloud coding, according to at least one embodiment;
- (7) FIG. 4 is a block diagram of internal and external components of computers and servers depicted in FIG. 1 according to at least one embodiment;
- (8) FIG. 5 is a block diagram of an illustrative cloud computing environment including the computer system depicted in FIG. 1, according to at least one embodiment; and
- (9) FIG. 6 is a block diagram of functional layers of the illustrative cloud computing environment of FIG. 5, according to at least one embodiment.

DETAILED DESCRIPTION

(10) Detailed embodiments of the claimed structures and methods are disclosed herein; however, it can be understood that the disclosed embodiments are merely illustrative of the claimed structures and methods that may be embodied in various forms. Those structures and methods may, however, be embodied in many different forms and should not be construed as limited to the exemplary embodiments set forth herein. Rather, these exemplary embodiments are provided so that this disclosure will be thorough and complete and will fully convey the scope to those skilled in the art. In the description, details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the presented embodiments.

(11) Embodiments relate generally to the field of data processing, and more particularly to point cloud coding. The following described exemplary embodiments provide a system, method and computer program to, among other things, use inter-component correlation methods for coding point cloud attribute data. Therefore, some embodiments have the capacity to improve the field of computing by allowing for increased efficiency of point cloud coding by not requiring finding

nearest neighbors of the point cloud data.

(12) As previously described, Point Cloud has been widely used in recent years. For example, it is used in autonomous driving vehicles for object detection and localization; it is also used in geographic information systems (GIS) for mapping, and used in cultural heritage to visualize and archive cultural heritage objects and collections, etc. Point clouds contain a set of high dimensional points, typically of three dimensional (3D), each including 3D position information and additional attributes such as color, reflectance, etc. They can be captured using multiple cameras and depth sensors, or Lidar in various setups, and may be made up of thousands up to billions of points to realistically represent the original scenes. Compression technologies are needed to reduce the amount of data required to represent a point cloud for faster transmission or reduction of storage. In the prediction based attribute coding, the attribute of current point is predicted from the already coded points that are close to current point.

(13) In the TMC13 model, the geometry information and the associated attributes, such as color or reflectance, are separately compressed. The geometry information, which is the 3D coordinates of the point clouds, is coded by octree-partition with its occupancy information. The attributes are then compressed based on reconstructed geometry using prediction, lifting and region adaptive hierarchical transform techniques. However, to find the nearest points in 3D space for each point may be expensive. Additionally, for lossless and near-lossless coding of multiple channel attributes, e.g., RGB colors, the multiple channels are processed directly without color space conversion and coded independently. However, there is usually a strong correlation among different color channels especially in RGB domain. Without utilizing such correlation may result in performance loss in terms of coding efficiency. It may be advantageous, therefore, to use inter-component correlations.

(14) Aspects are described herein with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems), and computer readable media according to the various embodiments. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer readable program instructions.

(15) Referring now to FIG. 1, a functional block diagram of a networked computer environment illustrating a point cloud coding system **100** (hereinafter “system”) for coding point cloud data. It should be appreciated that FIG. 1 provides only an illustration of one implementation and does not imply any limitations with regard to the environments in which different embodiments may be implemented. Many modifications to the depicted environments may be made based on design and implementation requirements.

(16) The system **100** may include a computer **102** and a server computer **114**. The computer **102** may communicate with the server computer **114** via a communication network **110** (hereinafter “network”). The computer **102** may include a processor **104** and a software program **108** that is stored on a data storage device **106** and is enabled to interface with a user and communicate with the server computer **114**. As will be discussed below with reference to FIG. 4 the computer **102** may include internal components **800A** and external components **900A**, respectively, and the server computer **114** may include internal components **800B** and external components **900B**, respectively. The computer **102** may be, for example, a mobile device, a telephone, a personal digital assistant, a netbook, a laptop computer, a tablet computer, a desktop computer, or any type of computing devices capable of running a program, accessing a network, and accessing a database.

(17) The server computer **114** may also operate in a cloud computing service model, such as Software as a Service (SaaS), Platform as a Service (PaaS), or Infrastructure as a Service (IaaS), as discussed below with respect to FIGS. 5 and 6. The server computer **114** may also be located in a cloud computing deployment model, such as a private cloud, community cloud, public cloud, or hybrid cloud.

(18) The server computer **114**, which may be used for point cloud coding is enabled to run a Point Cloud Coding Program **116** (hereinafter “program”) that may interact with a database **112**. The

Point Cloud Coding Program method is explained in more detail below with respect to FIGS. 3A-3B. In one embodiment, the computer **102** may operate as an input device including a user interface while the program **116** may run primarily on server computer **114**. In an alternative embodiment, the program **116** may run primarily on one or more computers **102** while the server computer **114** may be used for processing and storage of data used by the program **116**. It should be noted that the program **116** may be a standalone program or may be integrated into a larger point cloud coding program.

(19) It should be noted, however, that processing for the program **116** may, in some instances be shared amongst the computers **102** and the server computers **114** in any ratio. In another embodiment, the program **116** may operate on more than one computer, server computer, or some combination of computers and server computers, for example, a plurality of computers **102** communicating across the network **110** with a single server computer **114**. In another embodiment, for example, the program **116** may operate on a plurality of server computers **114** communicating across the network **110** with a plurality of client computers. Alternatively, the program may operate on a network server communicating across the network with a server and a plurality of client computers.

(20) The network **110** may include wired connections, wireless connections, fiber optic connections, or some combination thereof. In general, the network **110** can be any combination of connections and protocols that will support communications between the computer **102** and the server computer **114**. The network **110** may include various types of networks, such as, for example, a local area network (LAN), a wide area network (WAN) such as the Internet, a telecommunication network such as the Public Switched Telephone Network (PSTN), a wireless network, a public switched network, a satellite network, a cellular network (e.g., a fifth generation (5G) network, a long-term evolution (LTE) network, a third generation (3G) network, a code division multiple access (CDMA) network, etc.), a public land mobile network (PLMN), a metropolitan area network (MAN), a private network, an ad hoc network, an intranet, a fiber optic-based network, or the like, and/or a combination of these or other types of networks.

(21) The number and arrangement of devices and networks shown in FIG. **1** are provided as an example. In practice, there may be additional devices and/or networks, fewer devices and/or networks, different devices and/or networks, or differently arranged devices and/or networks than those shown in FIG. **1**. Furthermore, two or more devices shown in FIG. **1** may be implemented within a single device, or a single device shown in FIG. **1** may be implemented as multiple, distributed devices. Additionally, or alternatively, a set of devices (e.g., one or more devices) of system **100** may perform one or more functions described as being performed by another set of devices of system **100**.

(22) Referring now to FIGS. **2A** and **2B**, block diagrams **200A** and **200B** of point cloud update systems are depicted. Block diagram **200A** may depict a direct or forward transform in the lifting scheme. Block diagram **200B** may depict an inverse transform in the lifting scheme.

(23) For prediction based attribute coding, let $(P_{\text{sub}.i})_{\text{sub}.i=1 \dots N}$ be the set of positions associated

(24) with the point cloud points and let $(M_{\text{sub}.i})_{\text{sub}.i=1 \dots N}$ be the Morton codes associated with $(P_{\text{sub}.i})_{\text{sub}.i=1 \dots N}$.

(25) First, the points are sorted according to their associated Morton codes in an ascending order. Let I be the array of point indexes ordered according to this process. The encoder/decoder compresses/decompresses respectively the points according to the order defined by I . At each iteration i , a point P_i is selected. The distances of $P_{\text{sub}.i}$ to the s (e.g., $s=64$) previous points are analyzed and the k (e.g., $k=3$) nearest neighbors of $P_{\text{sub}.i}$ are selected to be used for prediction. More precisely, the attribute values $(a_{\text{sub}.i})_{\text{sub}.i \in 0 \dots k-1}$ are predicted by using a linear interpolation process based on the distances of the nearest neighbours of point i . Let $N_{\text{sub}.i}$ be the set of the k -nearest neighbours of the current point i , and let $(a_{\text{sub}.i})_{\text{sub}.i \in N_{\text{sub}.i}}$ custom character be their

decoded/reconstructed attribute values and $(\delta_{\text{sub}.j})$ custom character their distances to the current point. The predicted attribute value $\hat{a}_{\text{sub}.i}$ is given by:

$$(26) \hat{a}_i = \text{Round}\left(\frac{1}{K} \cdot \text{Math.} \frac{\frac{1}{j}}{\text{Math.} \frac{1}{j}} \tilde{a}_j\right)$$

(27) Lifting based attribute coding is built upon the prediction-based coding. The main difference compared with prediction-based scheme is that two addition steps are introduced. The first is introduction of an update operator. The second is use of an adaptive quantization strategy.

(28) Referring now to FIG. 2C, a diagram **200C** of a region adaptive hierarchical transform (RAHT) is depicted. The block diagram **200C** may depict a forward transform **202A** and a reverse transform **202B**. For RAHT coding,

$$(29) a^2 = \frac{w_0}{w_0 + w_1} \text{ and } b^2 = \frac{w_1}{w_0 + w_1},$$

and $w_{\text{sub}.0}$ is the notation of the weight of the input coefficient $F_{\text{sub}.l+1,2n}$ while $w_{\text{sub}.1}$ is the same for $F_{\text{sub}.l+1,2n+1}$.

(30) To utilize the correlations among different components, one can apply prediction schemes in different attribute coding methods, such as prediction based attribute coding, lifting based attribute coding and RAHT based attribute coding. The cross component prediction can be applied to original signals or predictive residuals or transformation coefficients (if any transformation technique is applied such as RAHT). In the following embodiments, the prediction based attribute coding is used as examples, and the cross-component-prediction scheme is applied to prediction residuals of different channels (or components).

(31) One can build different models to predict signals cross components, such as linear model, quadratic model and other polynomial models. In the following embodiments, the linear models are used as examples.

(32) The cross-component prediction is not limited to RGB color attributes only, but also it can be utilized for any other attributes as long as there are more than one types of attribute to be coded and there is correlation between them. In the following embodiment, the RGB color attributes will be used as examples.

(33) Suppose the prediction residuals for R, G and B components are $r_{\text{sub}.0}$, $r_{\text{sub}.1}$, $r_{\text{sub}.2}$, respectively, and it is assumed that these signals are linearly correlated. These components can be coded in any order. The coding order can be either fixed for all cases, or can be configured differently case by case and specified in the bitstream as part of high-level syntax, such as sequence parameter set, geometry parameter set or slice header, etc. In the following embodiment, it is assumed that the coding order is R first followed by G and B. Therefore, when coding the prediction residuals of G, one can use the reconstructed prediction residual of R as prediction; when coding the prediction residuals of B, one can use the reconstructed prediction residuals of R and G for prediction.

(34) More specifically, suppose the prediction residual of R component, i.e., $r_{\text{sub}.0}$, is coded first, and its reconstructed value after quantization/dequantization is $R_{\text{sub}.0}$. Then, the prediction residual of G component, i.e., $r_{\text{sub}.1}$, can be predicted by $R_{\text{sub}.0}$ as follows:

$$P_{\text{sub}.1} = \alpha_{\text{sub}.0} R_{\text{sub}.0} + \beta_{\text{sub}.0}$$

where $\alpha_{\text{sub}.0}$ and $\beta_{\text{sub}.0}$ are linear model parameters, and $p_{\text{sub}.1}$ is the predicted prediction residual of G. Therefore, instead of coding the prediction residual, i.e., $r_{\text{sub}.1}$, directly, one can code the second-order residual between $r_{\text{sub}.1}$ and $p_{\text{sub}.1}$, i.e., $r_{\text{sub}.1}' = r_{\text{sub}.1} - p_{\text{sub}.1}$. Then, the second-order residual of G, i.e., $r_{\text{sub}.1}'$ is coded and its reconstructed value after quantization/dequantization is $R_{\text{sub}.1}'$, and the reconstructed prediction residual of G component is $R_{\text{sub}.1} = R_{\text{sub}.1}' + p_{\text{sub}.1}$. Lastly, the prediction residual of B component, i.e., $r_{\text{sub}.2}$, can be predicted by both $R_{\text{sub}.0}$ and $R_{\text{sub}.1}$ as follows,

$$P_{\text{sub}.2} = \alpha_{\text{sub}.1} R_{\text{sub}.0} + \beta_{\text{sub}.1} R_{\text{sub}.1} + \gamma_{\text{sub}.1}$$

where $\alpha_{\text{sub}.1}$, $\beta_{\text{sub}.1}$, $\gamma_{\text{sub}.1}$, and $\gamma_{\text{sub}.1}$ are linear model parameters, and $p_{\text{sub}.2}$ is the predicted prediction residual of B. Therefore, instead of coding the prediction residual, i.e., $r_{\text{sub}.2}$,

directly, one can code the second-order residual between $r_{sub.2}$ and $p_{sub.2}$, i.e., $r_{sub.2}' = r_{sub.2} + p_{sub.2}$. Then, the second-order residual of B, i.e., $r_{sub.2}'$ is coded and its reconstructed value after quantization/dequantization is $R_{sub.2}'$, and the reconstructed prediction residual of B component is $R_{sub.2} = R_{sub.2}' + p_{sub.2}$.

(35) The linear models in can be simplified in many ways, as suggested as follows. But note that the simplification method can be in any other similar forms. In one embodiment, the linear models are simplified as follows:

$$p_{sub.1} = a_{sub.0} R_{sub.0}, p_{sub.2} = a_{sub.1} R_{sub.0} + \beta_{sub.1} R_{sub.1}$$

where $\beta_{sub.0}$ and $\gamma_{sub.1}$ are fixed as zeros. In another embodiment, the linear models can be simplified as follows,

$$p_{sub.1} = \alpha_{sub.0} R_{sub.0}, p_{sub.2} = \alpha_{sub.1} R_{sub.0} + \beta_{sub.1} R_{sub.1}$$

where $\beta_{sub.0}$ and $\gamma_{sub.1}$ and $\beta_{sub.1}$ are fixed as zeros. In another embodiment, the linear models can be simplified as follows,

$$P_{sub.1} = \alpha_{sub.0} R_{sub.0}, P_{sub.2} = \beta_{sub.1} R_{sub.1}$$

where $\beta_{sub.0}$ and $\gamma_{sub.1}$ and $\alpha_{sub.1}$ are fixed as zeros. In another embodiment, the linear models can be simplified as follows,

$$p_{sub.1} = a_{sub.0} R_{sub.0}, p_{sub.2} = a_{sub.0} R_{sub.0}$$

where $\beta_{sub.0}$ and $\gamma_{sub.1}$ and $\beta_{sub.1}$ are fixed as zeros, and $\alpha_{sub.1} = \alpha_{sub.0}$. In another embodiment, the linear models can be simplified as follows,

$$p_{sub.1} = a_{sub.0} R_{sub.0}, p_{sub.2} = a_{sub.0} R_{sub.1}$$

where $\beta_{sub.0}$ and $\gamma_{sub.1}$ and $\alpha_{sub.1}$ are fixed as zeros, and $\beta_{sub.1} = \alpha_{sub.0}$.

(36) In the above-mentioned linear models, the model parameters can be fixed for both encoder and decoder and for all cases. In one embodiment, one can derive the prediction as:

$$(37) p_1 = R_0, p_2 = R_0; p_1 = R_0, p_2 = R_1; \text{ or } p_1 = R_0, p_2 = \frac{(R_0 + R_1)}{2}$$

(38) However, the model parameters can be different for different point clouds, and the parameters can be signaled in high-level syntax such as in sequence parameter set, attribute parameter set or slice header etc.

(39) In other embodiments, the model parameters can be also signaled as a “low-level syntax”, meaning each coding unit (node) may have different sets of parameters.

(40) In another embodiment, to avoid explicitly signaling the model parameters, one can adaptively learn the parameters on-the-fly from the reconstructed prediction residuals. The encoder and decoder may proceed a same training stage while coding, by minimizing the mean squared error.

(41) Referring now to FIG. 2D, a table 200D of syntax elements for prediction residuals is depicted. To code the prediction residuals more efficiently, different attribute components may use separate contexts. In one embodiment, both R, G and B components use different context models. $\text{prediction_residual_is_zero}[i]$ specifies if the prediction residual of the i .sup.th component equals to 0. $\text{prediction_residual_is_one}[i]$ specifies if the prediction residual of the i .sup.th component equals to 1. $\text{prediction_residual_is_two}[i]$ specifies if the prediction residual of the i .sup.th component equals to 2. $\text{prediction_residual_minus_three}[i]$ specifies the prediction residual of the i .sup.th component as $\text{prediction_residual_minus_three}[i] + 3$. In another embodiment, R component uses a separate context model, and G and B components use the same context models.

(42) FIGS. 3A and 3B are flowcharts illustrating example processes 300A and 300B for point cloud coding. FIGS. 3A-3B may be described with the aid of FIGS. 1 and 2A-2D. In embodiments, one or more blocks of process 300A and process 300B may be combined in any order. For example, in embodiments, the blocks of process 300B may be performed after the blocks of process 300A using results from process 300A.

(43) As shown in FIG. 3A, process 300A may include receiving, from a bitstream, data corresponding to a point cloud (block 311).

(44) As further shown in FIG. 3A, process 300A may include obtaining from the data a first prediction residual of a first component from among a plurality of components of an attribute

associated with the point cloud (block **312**).

(45) As further shown in FIG. 3A, process **300A** may include reconstructing the first prediction residual (block **313**).

(46) As further shown in FIG. 3A, process **300A** may include determining a predicted second prediction residual based on the reconstructed first prediction residual and at least one model parameter (block **314**).

(47) As further shown in FIG. 3A, process **300A** may include obtaining a second prediction residual of a second component from among the plurality of components based on the predicted second prediction residual (block **315**).

(48) As further shown in FIG. 3A, process **300A** may include reconstructing the second prediction residual (block **316**).

(49) As further shown in FIG. 3A, process **300A** may include decoding the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual (block **317**).

(50) As shown in FIG. 3B, process **300B** may include determining a predicted third prediction residual based on the reconstructed first prediction residual, the reconstructed second prediction residual, and the at least one model parameter (block **321**).

(51) As further shown in FIG. 3B, process **300B** may include obtaining a third prediction residual of a third component from among the plurality of components based on the predicted third prediction residual (block **322**).

(52) As further shown in FIG. 3B, process **300B** may include reconstructing the third prediction residual (block **323**).

(53) As further shown in FIG. 3B, process **300B** may include decoding the data corresponding to the point cloud based on the reconstructed first prediction residual, the reconstructed second prediction residual, and the reconstructed third prediction residual (block **324**).

(54) In embodiments, the first, second, and third components may correspond to the components discussed above with respect to FIGS. 1 and 2A-2C. For example, the first, second, and third components may variously correspond to the R, G, and B components discussed above, or to any other components or channels as desired.

(55) In embodiments, the blocks of process **300A** and process **300B** may be performed using any of the equations discussed above. For example, in embodiments, $R_{sub.0}$ may represent the reconstructed first prediction residual, $p_{sub.1}$ may represent the predicted second prediction residual, $R_{sub.1}$ may represent the reconstructed second prediction residual, $p_{sub.2}$ may represent the predicted third prediction residual, and $\alpha_{sub.0}$, $\alpha_{sub.1}$, $\beta_{sub.1}$, and $\gamma_{sub.1}$ may represent model parameters of the at least one model parameter.

(56) In embodiments, a model corresponding to the at least one model parameter may include at least one of a linear model, a quadratic model, and a polynomial model.

(57) In embodiments, the at least one model parameter may be signaled in the data.

(58) In embodiments, the at least one model parameter may be a predetermined model parameter.

(59) In embodiments, the at least one model parameter may be adaptively learned based on at least one of the reconstructed first prediction residual and the reconstructed second prediction residual.

(60) In embodiments, the first component may be associated with a first context model, and the second component may be associated with a second context model different from the first context model.

(61) It may be appreciated that FIGS. 3A-3B provide only illustrations of implementations, and do not imply any limitations with regard to how different embodiments may be implemented. Many modifications to the depicted environments may be made based on design and implementation requirements.

(62) FIG. 4 is a block diagram **400** of internal and external components of computers depicted in FIG. 1 in accordance with an illustrative embodiment. It should be appreciated that FIG. 4 provides

only an illustration of one implementation and does not imply any limitations with regard to the environments in which different embodiments may be implemented. Many modifications to the depicted environments may be made based on design and implementation requirements.

(63) Computer **102** (FIG. **1**) and server computer **114** (FIG. **1**) may include respective sets of internal components **800A,B** and external components **900A,B** illustrated in FIG. **5**. Each of the sets of internal components **800** include one or more processors **820**, one or more computer-readable RAMS **822** and one or more computer-readable ROMs **824** on one or more buses **826**, one or more operating systems **828**, and one or more computer-readable tangible storage devices **830**.

(64) Processor **820** is implemented in hardware, firmware, or a combination of hardware and software. Processor **820** is a central processing unit (CPU), a graphics processing unit (GPU), an accelerated processing unit (APU), a microprocessor, a microcontroller, a digital signal processor (DSP), a field-programmable gate array (FPGA), an application-specific integrated circuit (ASIC), or another type of processing component. In some implementations, processor **820** includes one or more processors capable of being programmed to perform a function. Bus **826** includes a component that permits communication among the internal components **800A,B**.

(65) The one or more operating systems **828**, the software program **108** (FIG. **1**) and the Point Cloud Coding Program **116** (FIG. **1**) on server computer **114** (FIG. **1**) are stored on one or more of the respective computer-readable tangible storage devices **830** for execution by one or more of the respective processors **820** via one or more of the respective RAMS **822** (which typically include cache memory). In the embodiment illustrated in FIG. **4**, each of the computer-readable tangible storage devices **830** is a magnetic disk storage device of an internal hard drive. Alternatively, each of the computer-readable tangible storage devices **830** is a semiconductor storage device such as ROM **824**, EPROM, flash memory, an optical disk, a magneto-optic disk, a solid state disk, a compact disc (CD), a digital versatile disc (DVD), a floppy disk, a cartridge, a magnetic tape, and/or another type of non-transitory computer-readable tangible storage device that can store a computer program and digital information.

(66) Each set of internal components **800A,B** also includes a R/W drive or interface **832** to read from and write to one or more portable computer-readable tangible storage devices **936** such as a CD-ROM, DVD, memory stick, magnetic tape, magnetic disk, optical disk or semiconductor storage device. A software program, such as the software program **108** (FIG. **1**) and the Point Cloud Coding Program **116** (FIG. **1**) can be stored on one or more of the respective portable computer-readable tangible storage devices **936**, read via the respective R/W drive or interface **832** and loaded into the respective hard drive **830**.

(67) Each set of internal components **800A,B** also includes network adapters or interfaces **836** such as a TCP/IP adapter cards; wireless Wi-Fi interface cards; or 3G, 4G, or 5G wireless interface cards or other wired or wireless communication links. The software program **108** (FIG. **1**) and the Point Cloud Coding Program **116** (FIG. **1**) on the server computer **114** (FIG. **1**) can be downloaded to the computer **102** (FIG. **1**) and server computer **114** from an external computer via a network (for example, the Internet, a local area network or other, wide area network) and respective network adapters or interfaces **836**. From the network adapters or interfaces **836**, the software program **108** and the Point Cloud Coding Program **116** on the server computer **114** are loaded into the respective hard drive **830**. The network may comprise copper wires, optical fibers, wireless transmission, routers, firewalls, switches, gateway computers and/or edge servers.

(68) Each of the sets of external components **900A,B** can include a computer display monitor **920**, a keyboard **930**, and a computer mouse **934**. External components **900A,B** can also include touch screens, virtual keyboards, touch pads, pointing devices, and other human interface devices. Each of the sets of internal components **800A,B** also includes device drivers **840** to interface to computer display monitor **920**, keyboard **930** and computer mouse **934**. The device drivers **840**, R/W drive or interface **832** and network adapter or interface **836** comprise hardware and software (stored in storage device **830** and/or ROM **824**).

(69) It is understood in advance that although this disclosure includes a detailed description on cloud computing, implementation of the teachings recited herein are not limited to a cloud computing environment. Rather, some embodiments are capable of being implemented in conjunction with any other type of computing environment now known or later developed.

(70) Cloud computing is a model of service delivery for enabling convenient, on-demand network access to a shared pool of configurable computing resources (e.g. networks, network bandwidth, servers, processing, memory, storage, applications, virtual machines, and services) that can be rapidly provisioned and released with minimal management effort or interaction with a provider of the service. This cloud model may include at least five characteristics, at least three service models, and at least four deployment models.

(71) Characteristics are as follows: On-demand self-service: a cloud consumer can unilaterally provision computing capabilities, such as server time and network storage, as needed automatically without requiring human interaction with the service's provider. Broad network access: capabilities are available over a network and accessed through standard mechanisms that promote use by heterogeneous thin or thick client platforms (e.g., mobile phones, laptops, and PDAs). Resource pooling: the provider's computing resources are pooled to serve multiple consumers using a multi-tenant model, with different physical and virtual resources dynamically assigned and reassigned according to demand. There is a sense of location independence in that the consumer generally has no control or knowledge over the exact location of the provided resources but may be able to specify location at a higher level of abstraction (e.g., country, state, or datacenter). Rapid elasticity: capabilities can be rapidly and elastically provisioned, in some cases automatically, to quickly scale out and rapidly released to quickly scale in. To the consumer, the capabilities available for provisioning often appear to be unlimited and can be purchased in any quantity at any time.

Measured service: cloud systems automatically control and optimize resource use by leveraging a metering capability at some level of abstraction appropriate to the type of service (e.g., storage, processing, bandwidth, and active user accounts). Resource usage can be monitored, controlled, and reported providing transparency for both the provider and consumer of the utilized service.

(72) Service Models are as follows: Software as a Service (SaaS): the capability provided to the consumer is to use the provider's applications running on a cloud infrastructure. The applications are accessible from various client devices through a thin client interface such as a web browser (e.g., web-based e-mail). The consumer does not manage or control the underlying cloud infrastructure including network, servers, operating systems, storage, or even individual application capabilities, with the possible exception of limited user-specific application configuration settings. Platform as a Service (PaaS): the capability provided to the consumer is to deploy onto the cloud infrastructure consumer-created or acquired applications created using programming languages and tools supported by the provider. The consumer does not manage or control the underlying cloud infrastructure including networks, servers, operating systems, or storage, but has control over the deployed applications and possibly application hosting environment configurations. Infrastructure as a Service (IaaS): the capability provided to the consumer is to provision processing, storage, networks, and other fundamental computing resources where the consumer is able to deploy and run arbitrary software, which can include operating systems and applications. The consumer does not manage or control the underlying cloud infrastructure but has control over operating systems, storage, deployed applications, and possibly limited control of select networking components (e.g., host firewalls).

(73) Deployment Models are as follows: Private cloud: the cloud infrastructure is operated solely for an organization. It may be managed by the organization or a third party and may exist on-premises or off-premises. Community cloud: the cloud infrastructure is shared by several organizations and supports a specific community that has shared concerns (e.g., mission, security requirements, policy, and compliance considerations). It may be managed by the organizations or a third party and may exist on-premises or off-premises. Public cloud: the cloud infrastructure is

made available to the general public or a large industry group and is owned by an organization selling cloud services. Hybrid cloud: the cloud infrastructure is a composition of two or more clouds (private, community, or public) that remain unique entities but are bound together by standardized or proprietary technology that enables data and application portability (e.g., cloud bursting for load-balancing between clouds).

(74) A cloud computing environment is service oriented with a focus on statelessness, low coupling, modularity, and semantic interoperability. At the heart of cloud computing is an infrastructure comprising a network of interconnected nodes.

(75) Referring to FIG. 5, illustrative cloud computing environment **500** is depicted. As shown, cloud computing environment **500** comprises one or more cloud computing nodes **10** with which local computing devices used by cloud consumers, such as, for example, personal digital assistant (PDA) or cellular telephone **54A**, desktop computer **54B**, laptop computer **54C**, and/or automobile computer system **54N** may communicate. Cloud computing nodes **10** may communicate with one another. They may be grouped (not shown) physically or virtually, in one or more networks, such as Private, Community, Public, or Hybrid clouds as described hereinabove, or a combination thereof. This allows cloud computing environment **500** to offer infrastructure, platforms and/or software as services for which a cloud consumer does not need to maintain resources on a local computing device. It is understood that the types of computing devices **54A-N** shown in FIG. 5 are intended to be illustrative only and that cloud computing nodes **10** and cloud computing environment **500** can communicate with any type of computerized device over any type of network and/or network addressable connection (e.g., using a web browser).

(76) Referring to FIG. 6, a set of functional abstraction layers **600** provided by cloud computing environment **500** (FIG. 5) is shown. It should be understood in advance that the components, layers, and functions shown in FIG. 6 are intended to be illustrative only and embodiments are not limited thereto. As depicted, the following layers and corresponding functions are provided:

(77) Hardware and software layer **60** includes hardware and software components. Examples of hardware components include: mainframes **61**; RISC (Reduced Instruction Set Computer) architecture based servers **62**; servers **63**; blade servers **64**; storage devices **65**; and networks and networking components **66**. In some embodiments, software components include network application server software **67** and database software **68**.

(78) Virtualization layer **70** provides an abstraction layer from which the following examples of virtual entities may be provided: virtual servers **71**; virtual storage **72**; virtual networks **73**, including virtual private networks; virtual applications and operating systems **74**; and virtual clients **75**.

(79) In one example, management layer **80** may provide the functions described below. Resource provisioning **81** provides dynamic procurement of computing resources and other resources that are utilized to perform tasks within the cloud computing environment. Metering and Pricing **82** provide cost tracking as resources are utilized within the cloud computing environment, and billing or invoicing for consumption of these resources. In one example, these resources may comprise application software licenses. Security provides identity verification for cloud consumers and tasks, as well as protection for data and other resources. User portal **83** provides access to the cloud computing environment for consumers and system administrators. Service level management **84** provides cloud computing resource allocation and management such that required service levels are met. Service Level Agreement (SLA) planning and fulfillment **85** provide pre-arrangement for, and procurement of, cloud computing resources for which a future requirement is anticipated in accordance with an SLA.

(80) Workloads layer **90** provides examples of functionality for which the cloud computing environment may be utilized. Examples of workloads and functions which may be provided from this layer include: mapping and navigation **91**; software development and lifecycle management **92**; virtual classroom education delivery **93**; data analytics processing **94**; transaction processing

95; and Point Cloud Coding 96. Point Cloud Coding 96 may decode point cloud data based on inter-component correlations.

(81) Some embodiments may relate to a system, a method, and/or a computer readable medium at any possible technical detail level of integration. The computer readable medium may include a computer-readable non-transitory storage medium (or media) having computer readable program instructions thereon for causing a processor to carry out operations.

(82) The computer readable storage medium can be a tangible device that can retain and store instructions for use by an instruction execution device. The computer readable storage medium may be, for example, but is not limited to, an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination of the foregoing. A non-exhaustive list of more specific examples of the computer readable storage medium includes the following: a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), a static random access memory (SRAM), a portable compact disc read-only memory (CD-ROM), a digital versatile disk (DVD), a memory stick, a floppy disk, a mechanically encoded device such as punch-cards or raised structures in a groove having instructions recorded thereon, and any suitable combination of the foregoing. A computer readable storage medium, as used herein, is not to be construed as being transitory signals per se, such as radio waves or other freely propagating electromagnetic waves, electromagnetic waves propagating through a waveguide or other transmission media (e.g., light pulses passing through a fiber-optic cable), or electrical signals transmitted through a wire.

(83) Computer readable program instructions described herein can be downloaded to respective computing/processing devices from a computer readable storage medium or to an external computer or external storage device via a network, for example, the Internet, a local area network, a wide area network and/or a wireless network. The network may comprise copper transmission cables, optical transmission fibers, wireless transmission, routers, firewalls, switches, gateway computers and/or edge servers. A network adapter card or network interface in each computing/processing device receives computer readable program instructions from the network and forwards the computer readable program instructions for storage in a computer readable storage medium within the respective computing/processing device.

(84) Computer readable program code/instructions for carrying out operations may be assembler instructions, instruction-set-architecture (ISA) instructions, machine instructions, machine dependent instructions, microcode, firmware instructions, state-setting data, configuration data for integrated circuitry, or either source code or object code written in any combination of one or more programming languages, including an object oriented programming language such as Smalltalk, C++, or the like, and procedural programming languages, such as the “C” programming language or similar programming languages. The computer readable program instructions may execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer may be connected to the user's computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider). In some embodiments, electronic circuitry including, for example, programmable logic circuitry, field-programmable gate arrays (FPGA), or programmable logic arrays (PLA) may execute the computer readable program instructions by utilizing state information of the computer readable program instructions to personalize the electronic circuitry, in order to perform aspects or operations.

(85) These computer readable program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or

other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks. These computer readable program instructions may also be stored in a computer readable storage medium that can direct a computer, a programmable data processing apparatus, and/or other devices to function in a particular manner, such that the computer readable storage medium having instructions stored therein comprises an article of manufacture including instructions which implement aspects of the function/act specified in the flowchart and/or block diagram block or blocks.

(86) The computer readable program instructions may also be loaded onto a computer, other programmable data processing apparatus, or other device to cause a series of operational steps to be performed on the computer, other programmable apparatus or other device to produce a computer implemented process, such that the instructions which execute on the computer, other programmable apparatus, or other device implement the functions/acts specified in the flowchart and/or block diagram block or blocks.

(87) The flowchart and block diagrams in the Figures illustrate the architecture, functionality, and operation of possible implementations of systems, methods, and computer readable media according to various embodiments. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of instructions, which comprises one or more executable instructions for implementing the specified logical function(s). The method, computer system, and computer readable medium may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in the Figures. In some alternative implementations, the functions noted in the blocks may occur out of the order noted in the Figures. For example, two blocks shown in succession may, in fact, be executed concurrently or substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts or carry out combinations of special purpose hardware and computer instructions.

(88) It will be apparent that systems and/or methods, described herein, may be implemented in different forms of hardware, firmware, or a combination of hardware and software. The actual specialized control hardware or software code used to implement these systems and/or methods is not limiting of the implementations. Thus, the operation and behavior of the systems and/or methods were described herein without reference to specific software code—it being understood that software and hardware may be designed to implement the systems and/or methods based on the description herein.

(89) No element, act, or instruction used herein should be construed as critical or essential unless explicitly described as such. Also, as used herein, the articles “a” and “an” are intended to include one or more items, and may be used interchangeably with “one or more.” Furthermore, as used herein, the term “set” is intended to include one or more items (e.g., related items, unrelated items, a combination of related and unrelated items, etc.), and may be used interchangeably with “one or more.” Where only one item is intended, the term “one” or similar language is used. Also, as used herein, the terms “has,” “have,” “having,” or the like are intended to be open-ended terms. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

(90) The descriptions of the various aspects and embodiments have been presented for purposes of illustration, but are not intended to be exhaustive or limited to the embodiments disclosed. Even though combinations of features are recited in the claims and/or disclosed in the specification, these combinations are not intended to limit the disclosure of possible implementations. In fact, many of these features may be combined in ways not specifically recited in the claims and/or disclosed in the specification. Although each dependent claim listed below may directly depend on only one

claim, the disclosure of possible implementations includes each dependent claim in combination with every other claim in the claim set. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope of the described embodiments. The terminology used herein was chosen to best explain the principles of the embodiments, the practical application or technical improvement over technologies found in the marketplace, or to enable others of ordinary skill in the art to understand the embodiments disclosed herein.

Claims

1. A method of point cloud video decoding, executable by a processor, comprising: receiving, from a bitstream, data of a video corresponding to a point cloud; obtaining from the data a first prediction residual of a first component from among a plurality of components of an attribute associated with the point cloud; reconstructing the first prediction residual; determining a predicted second prediction residual based on the reconstructed first prediction residual and at least one model parameter; obtaining a second prediction residual of a second component from among the plurality of components based on the predicted second prediction residual; reconstructing the second prediction residual based on the predicted second prediction residual; and decoding the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual, and decoding the data comprises decoding and causing a video of the point cloud, which is represented by the data, to be played, the point cloud representing any of color, reflectance, and positions of one or more objects in the video of the point cloud.
2. The method of claim 1, wherein the at least one model parameter is of at least one of a linear model, a quadratic model, and a polynomial model.
3. The method of claim 1, further comprising: determining a predicted third prediction residual based on the reconstructed first prediction residual, the reconstructed second prediction residual, and the at least one model parameter; reconstructing a third prediction residual based on the predicted third prediction residual; and decoding the data corresponding to the point cloud based on the reconstructed first prediction residual, the reconstructed second prediction residual, and the reconstructed third prediction residual.
4. The method of claim 3, wherein the predicted second prediction residual is determined based on: $p_{sub.1} = \alpha_{sub.0} R_{sub.0}$, wherein the predicted third prediction residual is determined based on: $p_{sub.2} = \alpha_{sub.1} R_{sub.0} + \beta_{sub.1} R_{sub.1}$, and wherein $R_{sub.0}$ represents the reconstructed first prediction residual, $p_{sub.1}$ represents the predicted second prediction residual, $R_{sub.1}$ represents the reconstructed second prediction residual, $p_{sub.2}$ represents the predicted third prediction residual, and wherein $\alpha_{sub.0}$, $\alpha_{sub.1}$, and $\beta_{sub.1}$ represent model parameters of the at least one model parameter.
5. The method of claim 3, wherein the predicted second prediction residual is determined based on: $p_{sub.1} = \alpha_{sub.0} R_{sub.0}$, wherein the predicted third prediction residual is determined based on: $\beta_{sub.2} = \alpha_{sub.1} R_{sub.0}$, and wherein $R_{sub.0}$ represents the reconstructed first prediction residual, $p_{sub.1}$ represents the predicted second prediction residual, $p_{sub.2}$ represents the predicted third prediction residual, and wherein $\alpha_{sub.0}$ and $\alpha_{sub.1}$ represent model parameters of the at least one model parameter.
6. The method of claim 3, wherein the predicted second prediction residual is determined based on: $p_{sub.1} = \alpha_{sub.0} R_{sub.0}$, wherein the predicted third prediction residual is determined based on: $p_{sub.2} = \beta_{sub.1} R_{sub.1}$, and wherein $R_{sub.0}$ represents the reconstructed first prediction residual, $p_{sub.1}$ represents the predicted second prediction residual, $R_{sub.1}$ represents the reconstructed second prediction residual, $p_{sub.2}$ represents the predicted third prediction residual, and wherein $\alpha_{sub.0}$ and $\beta_{sub.1}$ represent model parameters of the at least one model parameter.
7. The method of claim 3, wherein the predicted second prediction residual is determined based on:

$p_{sub.1} = \alpha_{sub.0} R_{sub.0}$, wherein the predicted third prediction residual is determined based on: $p_{sub.2} = \alpha_{sub.0} R_{sub.0}$, wherein $R_{sub.0}$ represents the reconstructed first prediction residual, $p_{sub.1}$ represents the predicted second prediction residual, and $p_{sub.2}$ represents the predicted third prediction residual, and wherein $\alpha_{sub.0}$ represents a model parameter of the at least one model parameter.

8. The method of claim 3, wherein the predicted second prediction residual is determined based on: $p_{sub.1} = \alpha_{sub.0} R_{sub.0}$, wherein the predicted third prediction residual is determined based on: $p_{sub.2} = \alpha_{sub.0} R_{sub.1}$, and wherein $R_{sub.0}$ represents the reconstructed first prediction residual, $p_{sub.1}$ represents the predicted second prediction residual, $R_{sub.1}$ represents the reconstructed second prediction residual, $p_{sub.2}$ represents the predicted third prediction residual, and wherein $\alpha_{sub.0}$ represents a model parameter of the at least one model parameter.

9. The method of claim 1, wherein the at least one model parameter is signaled in the data.

10. The method of claim 1, wherein the at least one model parameter is a predetermined model parameter.

11. The method of claim 1, wherein the at least one model parameter is adaptively learned based on at least one of the reconstructed first prediction residual and the reconstructed second prediction residual.

12. The method of claim 1, wherein the first component is associated with a first context model, and wherein the second component is associated with a second context model different from the first context model.

13. A computer system for point cloud video decoding, the computer system comprising: one or more computer-readable non-transitory storage media configured to store computer program code; and one or more processors configured to access the computer program code and operate as instructed by the computer program code, said computer program code including: receiving code configured to cause the one or more processors to receive, from a bitstream, data of a video corresponding to a point cloud; first obtaining code configured to cause the one or more processors to obtain, from the data a first prediction residual of a first component from among a plurality of components of an attribute associated with the point cloud; first reconstructing code configured to cause the one or more processors to reconstruct the first prediction residual; determining code configured to cause the one or more processors to determine a predicted second prediction residual based on a reconstructed first prediction residual and at least one model parameter; reconstructing code configured to cause the one or more processors to reconstruct the second prediction residual based on the predicted second prediction residual based on the predicted second prediction residual; and decoding code configured to cause the one or more processors to decode the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual, and decoding the data comprises decoding and causing a video of the point cloud, which is represented by the data, to be played, the point cloud representing any of color, reflectance, and positions of one or more objects in the video of the point cloud.

14. The computer system of claim 13, wherein the at least one model parameter is of at least one of a linear model, a quadratic model, and a polynomial model.

15. The computer system of claim 13, wherein the computer program code further includes: further determining code configured to cause the one or more processors to determine a predicted third prediction residual based on the reconstructed first prediction residual, the reconstructed second prediction residual, and the at least one model parameter; third obtaining code configured to cause the one or more processors to obtain a third prediction residual of a third component from among the plurality of components based on the predicted third prediction residual; further reconstructing code configured to cause the one or more processors to reconstruct a third prediction residual based on the predicted third prediction residual; and further decoding code configured to cause the one or more processors to decode the data corresponding to the point cloud based on the reconstructed

first prediction residual, the reconstructed second prediction residual, and the reconstructed third prediction residual.

16. The computer system of claim 13, wherein the at least one model parameter is signaled in the data.

17. The computer system of claim 13, wherein the at least one model parameter is a predetermined model parameter.

18. The computer system of claim 13, wherein the at least one model parameter is adaptively learned based on at least one of the reconstructed first prediction residual and the reconstructed second prediction residual.

19. The computer system of claim 13, wherein the first component is associated with a first context model, and wherein the second component is associated with a second context model different from the first context model.

20. A non-transitory computer readable medium having stored thereon a computer program for point cloud video coding, the computer program configured to cause one or more computer processors to: receive, from a bitstream, data of a video corresponding to a point cloud; obtain, from the data a first prediction residual of a first component from among a plurality of components of an attribute associated with the point cloud; reconstruct the first prediction residual; determine a predicted second prediction residual based on the reconstructed first prediction residual and at least one model parameter; obtain a second prediction residual of a second component from among the plurality of components based on the predicted second prediction residual; reconstruct the second prediction residual based on the predicted second prediction residual; and decode the data corresponding to the point cloud based on the reconstructed first prediction residual and the reconstructed second prediction residual, and decoding the data comprises decoding and causing a video of the point cloud, which is represented by the data, to be played, the point cloud representing any of color, reflectance, and positions of one or more objects in the video of the point cloud.
