

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407128
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Masuda; Satoki et al.

Connector with improved insulating capabilities

Abstract

A connector includes a housing having a fitting part that is inserted and fitted into a counterpart fitting part, a shield shell having a shell flange part disposed opposite a wall surface of a counterpart wall body with an interval therebetween, a first watertight member between the fitting part and the counterpart fitting part, and a second watertight member that is crushed between the shell flange part and a wall surface of the counterpart wall body. The housing has a housing flange part with an outer peripheral surface thereof disposed inside an outer peripheral edge of the shell flange part and outside an inner edge of the shell flange part, and with a contact surface with an annular shape in contact with the wall surface of the counterpart wall body.

Inventors: Masuda; Satoki (Shizuoka, JP), Oi; Hikaru (Shizuoka, JP), Jintoku; Tomohiro (Tokyo, JP), Kimura; Kanato (Tokyo, JP), Yamagishi; Masaharu (Aichi, JP), Okamura; Kazuhiro (Aichi, JP)

Applicant: Yazaki Corporation (Tokyo, JP); Mitsubishi Jidosha Kogyo Kabushiki Kaisha (Tokyo, JP)

Family ID: 79555427

Assignee: YAZAKI CORPORATION (Tokyo, JP); MITSUBISHI JIDOSHA KOGYO KABUSHIKI KAISHA (Tokyo, JP)

Appl. No.: 18/081785

Filed: December 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230124316 A1	Apr. 20, 2023

Foreign Application Priority Data

JP	2020-121258	Jul. 15, 2020
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/JP2021/025804 20210708 PENDING child-doc US 18081785

Publication Classification

Int. Cl.: H01R13/52 (20060101); H01R13/658 (20110101)

U.S. Cl.:

CPC H01R13/5202 (20130101); H01R13/5216 (20130101); H01R13/658 (20130101);

Field of Classification Search

CPC: H01R (13/5202); H01R (13/5205); H01R (13/5219); H01R (13/5221); H01R (13/74-748); H01R (33/965); H01R (13/6596)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0288090	12/2014	Shigeta	439/587	H01R 13/5202
2015/0364856	12/2014	Nakai	174/152G	H01B 17/583
2016/0172784	12/2015	Kataoka	439/271	H01R 13/5219
2016/0329651	12/2015	Yamaguchi	N/A	H01R 13/44
2017/0302019	12/2016	Horiuchi et al.	N/A	N/A
2018/0019544	12/2017	Ishibashi	N/A	H02K 11/30
2018/0358748	12/2017	Yamanashi	N/A	H01R 24/62
2018/0366851	12/2017	Garcia et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2016-071982	12/2015	JP	N/A
2015/108201	12/2014	WO	N/A

Primary Examiner: Patel; Tulsidas C

Assistant Examiner: Lopez-Pagan; Carlos E

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation application of International Application No. PCT/JP2021/025804 filed on Jul. 8, 2021 which claims the benefit of priority from Japanese Patent Application No. 2020-128258 filed on Jul. 15, 2020 and designating the U.S., the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to a connector.

2. Description of the Related Art

(2) Conventionally, shielded connectors are known that include a housing in which a fitting part is inserted and fitted into a counterpart fitting part with a bore shape provided on a counterpart wall body, and a shield shell that covers a protruding portion protruding from the counterpart fitting part in the housing from an outside. In this connector, the shield shell is fixed to the counterpart wall body. For example, the shield shell is known that has a cylindrical part that covers the protruding part of the housing from the outside, a flange part that is disposed opposite a wall surface of the counterpart wall body, and a fixed part that is bent from an end of the flange part and fixed to an end surface of the counterpart wall body. This type of connector is disclosed, for example, in Japanese Patent Application Laid-open No. 2016-71982.

(3) By the way, in such conventional connectors, if liquid such as water enters between the flange part of the shield shell and the wall surface of the counterpart wall body, the liquid may be transmitted through therebetween, to a gap between the fitting part and the counterpart fitting part, and the liquid may reach a terminal metal fitting. To avoid this possibility, conventional connectors are provided with a watertight member with an annular shape that seals a cylindrical gap between the fitting part and the counterpart fitting part. In conventional connectors, the watertight member prevents liquid that has entered between the fitting part and the counterpart fitting part from flowing out to a terminal metal fitting side. However, in connectors, if liquid tightness between the fitting part and the counterpart fitting part is to be considered, it is desirable to reduce an amount of liquid flowing into the gap therebetween.

SUMMARY OF THE INVENTION

(4) It is an object of the present invention to provide a connector capable of reducing the amount of liquid flowing between fitting parts.

(5) In order to achieve the above mentioned object, a connector according to one aspect of the present invention includes a terminal metal fitting attached to an end of a wire; a housing having a fitting part that accommodates the terminal metal fitting inside thereof and that is inserted and fitted into a counterpart fitting part with a bore shape of a counterpart wall body; a shield shell including a cylindrical part that covers, from outside, a protruding portion of the housing that protrudes from the counterpart fitting part on an opposite side of an insertion direction of the fitting part to the counterpart fitting part, and a shell flange part that protrudes outward beyond an outer peripheral surface of the cylindrical part and is disposed opposite a wall surface of the counterpart wall body with an interval therebetween; a first watertight member with an annular shape that is attached to an outer peripheral wall surface of the fitting part and covers a cylindrical gap between the fitting part and the counterpart fitting part in a fitting state where the fitting part is inserted and fitted into the counterpart fitting part; and a second watertight member with an annular shape that is crushed between the shell flange part and the wall surface of the counterpart wall body when in the fitting state, wherein the housing has a housing flange part that is interposed between the shell flange part and the wall surface of the counterpart wall body when in the fitting state, and an outer peripheral surface is disposed inside an outer edge of the shell flange part and outside an inner edge of the shell flange part, the housing flange part has a contact surface with an annular shape that contacts the wall surface of the counterpart wall body when in the fitting state, and the second watertight member is disposed outside of the housing flange part and has an inner peripheral surface disposed opposite the outer peripheral surface of the housing flange part and a pressurized surface with an annular shape that protrudes to the insertion direction side beyond the contact surface of the housing flange part and is subjected to a pressing force from the wall surface of the counterpart wall body when in the fitting state.

(6) According to another aspect of the present invention, in the connector, it is desirable that an amount of protrusion from the contact surface of the housing flange part in the second watertight member is greater than a sum of a maximum value of relative movement amount in the insertion direction between the shield shell and the counterpart wall body and a cumulative tolerance of a gap in the insertion direction between the shell flange part and the wall surface of the counterpart wall body.

(7) According to still another aspect of the present invention, in the connector, it is desirable that the shield shell has a fixed part that is bent from an end of the outer peripheral edge of the shell flange part and fixed to an end surface of the counterpart wall body.

(8) According to still another aspect of the present invention, in the connector, it is desirable that the second watertight member is attached to the shell flange part.

(9) According to still another aspect of the present invention, in the connector, it is desirable that the second watertight member is made of an ethylene propylene diene rubber.

(10) The above and other objects, features, advantages and technical and industrial significance of this invention will be better understood by reading the following detailed description of presently preferred embodiments of the invention, when considered in connection with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective diagram before fitting illustrating a connector of an embodiment;

(2) FIG. 2 is a perspective diagram after fitting illustrating the connector of the embodiment;

(3) FIG. 3 is an X-X cross-sectional view of FIG. 1;

(4) FIG. 4 is an X-X cross-sectional view of FIG. 2;

(5) FIG. 5 is an exploded view illustrating the connector of the embodiment;

(6) FIG. 6 is a perspective diagram illustrating a housing; and

(7) FIG. 7 is a perspective diagram illustrating a shield shell having a second watertight member installed thereon.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(8) The following is a detailed description of an embodiment of a connector according to the present invention with reference to the drawings. The invention is not limited to this embodiment. Embodiment

(9) One embodiment of the connector according to the present invention is described with reference to FIGS. 1 to 7.

(10) A reference sign **1** in FIGS. 1 to 5 indicates a connector of the present embodiment. This connector **1** is inserted and fitted into a counterpart fitting part **521** with a bore shape having an inner peripheral wall surface **521a**, so as to be electrically connected to a counterpart terminal metal fitting **510** (FIGS. 1 and 2). The connector **1** is inserted into and extracted from the counterpart fitting part **521** with a bore shape along a bore axis direction of the counterpart fitting part **521**. The counterpart fitting part **521** is formed as a portion that has, for example, a cross section orthogonal to the bore axis direction formed in a circular or elliptical shape.

(11) For example, the connector **1** is electrically connected to the counterpart terminal metal fitting **510** of an counterpart device **500**, thereby making an electrical connection between the counterpart device **500** and the device (not illustrated) at the end of the wire **We** (FIGS. 1 and 2). The counterpart device **500** includes a housing **501** made of metal, and uses a through hole formed in a wall body **502** of the housing **501** (hereinafter referred to as a “counterpart wall body”) as the counterpart fitting part **521**. The counterpart fitting part **521** has a perpendicular direction to a planar wall surface **502a** of the counterpart wall body **502** (FIGS. 1 to 4) as a hole axis direction,

and has the connector **1** inserted thereto and removed therefrom along the hole axis direction. The counterpart device **500** includes a terminal block or a counterpart connector (not illustrated) inside its housing **501**. The counterpart terminal metal fitting **510** is included in its terminal block or counterpart connector. Therefore, the connector **1** is inserted and fitted into the counterpart fitting part **521** and makes an electrical connection to the terminal block or the counterpart terminal metal fitting **510** of the counterpart connector inside the housing **501**.

(12) In the following, when we simply refer to an insertion direction without any special mention, the insertion direction refers to an insertion direction of the connector **1** into the counterpart fitting part **521**. In addition, when we simply refer to an extraction direction without any special mention, the extraction direction refers to an extraction direction of the connector **1** with respect to the counterpart fitting part **521**. In addition, when we simply refer to an insertion and extraction direction without any special mention, the insertion and extraction direction refers to an insertion and extraction direction of the connector **1** with respect to the counterpart fitting part **521**.

(13) This connector **1** includes a terminal metal fitting **10**, a housing **20**, and a shield shell **30** (FIG. **1** to FIG. **5**).

(14) The terminal metal fitting **10** is molded from metal or other conductive material. For example, this terminal metal fitting **10** is molded into a predetermined shape by press forming, such as bending or cutting, on a metal sheet that serves as a base material. The terminal metal fitting **10** is attached to an end of the wire **We** so as to make an electrical connection to the wire **We**. The terminal metal fitting **10** will also be electrically connected to the counterpart terminal metal fitting **510**. Therefore, the terminal metal fitting **10** has a terminal connecting part **11** that is physically and electrically connected to the counterpart terminal metal fitting **510**, and a wire connection part **12** that is physically and electrically connected to the end of the wire **We** (FIG. **5**).

(15) The terminal connecting part **11** illustrated here is shaped in a chip (FIG. **1** to FIG. **5**). The terminal connecting part **11** has a through hole **11a** (FIG. **1**, FIG. **2** and FIG. **5**). This terminal connecting part **11** is physically and electrically connected to the counterpart terminal metal fitting **510** by being fixed to the counterpart terminal metal fitting **510** through its through-hole **11a** using a screw or the like. A connection form between the terminal metal fitting **10** and the counterpart terminal metal fitting **510** does not necessarily have to be of such screwing structure. For example, the terminal metal fitting **10** and the counterpart terminal metal fitting **510** are molded so as to be able to fit and connect with each other, one of which may be molded in a shape of a female terminal and the other of which may be molded in a shape of a male terminal.

(16) The wire connection part **12** is physically and electrically connected to the wire **We** by being, for example, crimped or welded to a core of the end of the wire **We**. The wire connection part **12** illustrated here has two barrel pieces crimped to a bare core wire by being pressurized and connected to the core wire.

(17) The terminal metal fitting **10** in this example is molded as a straight shaped terminal metal fitting with the terminal connecting part **11** and the wire connection part **12** thereof arranged in a straight line. Therefore, the wire **We** is pulled out of the wire connection part **12** in a direction of extension of the terminal metal fitting **10** along its straight line. However, this terminal metal fitting **10** may be a terminal metal fitting having the terminal connecting part **11** and a wire connection part **12** arranged by being crossed one another, for example, by being arranged orthogonally.

(18) The connector **1** illustrated here has two sets of the terminal metal fitting **10** and the wire **We** in its pair.

(19) The housing **20** is molded from insulating material such as synthetic resin. This housing **20** accommodates inside thereof the terminal metal fitting **10** and the wire **We**. In this housing **20**, the terminal metal fitting **10** is held in an accommodation state as it is, and the wire **We** is pulled out outward from the inside to the outside thereof.

(20) The housing **20** has a fitting part **21** that accommodates inside thereof the terminal metal fitting **10** and is inserted and fitted into the counterpart fitting part **521** with a bore shape of the

counterpart wall body **502** (FIGS. **1** to **6**). The fitting part **21** is inserted and fitted into the inside of the counterpart fitting part **521** along the insertion direction, and is pulled out outward from the inside of the counterpart fitting part **521** along an extraction direction that is opposite to the insertion direction. This fitting part **21** is formed in a cylindrical shape with the insertion and extraction direction (insertion direction, and insertion and extraction direction) relative to the counterpart fitting part **521** as a cylinder axis direction. Therefore, the following may refer to the cylinder axis direction instead of the insertion and extraction direction. The fitting part **21** illustrated here is formed in a cylindrical shape such that a cross section orthogonal to the cylinder axis has a shape of an ellipse, and has two terminal metal fittings **10** placed in parallel along the longitudinal direction of the ellipse. The fitting part **21** illustrated here holds the terminal connecting part **11** inside thereof, and the end of the through hole **11a** side in this terminal connecting part **11** protrudes from the inside to the outside thereof. And the fitting part **21** illustrated here accommodates inside thereof the wire connection part **12** side in the terminal connecting part **11** and the terminal connecting part **11** side in the wire connection part **12**. This fitting part **21** has, inside thereof, a partition wall (not illustrated) provided between adjacent terminal metal fittings **10**.

(21) The housing **20** has, in a state where the fitting part **21** is inserted and fitted into the counterpart fitting part **521** (hereinafter referred to as a “fitting state”), a portion closer to an extraction direction side relative to the fitting part **21** protruding from the counterpart fitting part **521**. The housing **20** has a wire housing section **22** of a cylindrical shape that accommodates, inside thereof, the wire **We** as a protruding portion from the counterpart fitting part **521** on the extraction direction side (FIGS. **1**, **2**, **5** and **6**). The wire housing section **22** illustrated here is formed in a cylindrical shape and is provided for a corresponding wire **We**. Wire housing sections **22** are aligned in an array direction of the two terminal metal fittings. The housing **20** has a cylindrical part **23**, between the fitting part **21** and the corresponding wire housing section **22**, which is coaxial with the cylinder axis of the fitting part **21** and is provided outside an outer peripheral wall surface **21a** of the fitting part **21** (FIGS. **1** and **3** to **6**). The cylindrical part **23** illustrated here is formed in a cylindrical shape such that a cross section orthogonal to the cylinder axis has a shape of an ellipse, and is arranged with an annular gap against the outer peripheral wall surface **21a** of the fitting part **21**.

(22) In this housing **20**, the wire **We** with the terminal metal fitting **10** is inserted through an opening **22a** of the wire housing section **22** (FIG. **5**). Therefore, the wire **We** is pulled out outward from the opening **22a**. Here, an annular gap is formed between the wire housing section **22** and the wire **We**. Therefore, in this connector **1**, a watertight member with an annular shape (hereinafter referred to as an “inner watertight member”) **41** (FIG. **5**) has the wire **We** inserted thereto in advance, and the inner watertight member **41** is inserted into the wire housing section **22** together with the wire **We**, thereby sealing the annular gap between the wire housing section **22** and the wire **We**. That inner watertight member **41** is a so-called rubber plug.

(23) The housing **20** has a flange part **24** with an annular shape that is coaxial with the cylinder axis of the fitting part **21** (hereinafter referred to as a “housing flange part”) between the cylindrical part **23** and the corresponding wire housing section **22** as a protruding portion from the counterpart fitting part **521** on the extraction direction side (FIGS. **1** and FIGS. **3** to **6**). The housing flange part **24** has an outer peripheral surface **24a** outside the outer peripheral wall surface **21a** of the fitting part **21** and outside an outer wall **22b** of the corresponding wire housing section **22** (FIGS. **3**, **4** and **6**). The outer peripheral surface **24a** of the housing flange part **24**, illustrated here, is outside the cylindrical part **23**. Furthermore, the housing flange part **24** has a contact surface **24b** with an annular shape that contacts the wall surface **502a** of the counterpart wall body **502** when in the fitting state (FIGS. **1**, **3**, **4** and **6**). The contact surface **24b** is a wall surface on an insertion direction side in the housing flange part **24**, and contacts a peripheral portion of the counterpart fitting part **521** in the wall surface **502a** of the counterpart wall body **502**.

(24) The connector **1** includes a front holder **51** into which the tip of the fitting part **21** of the housing **20** (the end on the insertion direction side) is inserted inward (FIGS. **1** to **5**). The front holder **51** maintains a holding state of the terminal metal fitting **10** housed together with its fitting part **21** and the like in the housing **20**. The front holder **51** has a cylindrical part **51a** the insertion and extraction direction of which is the cylindrical direction, and the tip of the fitting part **21** is inserted into the inside of the cylindrical part **51a** (FIGS. **3** and **4**). The cylindrical part **51a** illustrated here is formed in a cylindrical shape such that a cross section orthogonal to the cylinder axis has a shape of an ellipse.

(25) In this connector **1**, an annular end surface on the extraction direction side in the cylindrical part **51a** of the front holder **51** and an end surface on the insertion direction side in the cylindrical part **23** of the housing **20** are disposed opposite with each other with an interval therebetween in the insertion and extraction direction. Therefore, in the connector **1**, an annular groove is formed between the respective end surfaces of the cylindrical parts **23** and **51a**, with the outer peripheral wall surface **21a** of the fitting part **21** as a groove bottom. The connector **1** has a first watertight member with an annular shape (hereinafter referred to as a “first outer watertight member”) **42** in the annular groove thereof (FIG. **1** and FIGS. **3** to **5**). The first outer watertight member **42** is attached to the outer peripheral wall surface **21a** of the fitting part **21**, and seals the cylindrical gap between the fitting part **21** and the counterpart fitting part **521** when in the fitting state. The first outer watertight member **42** illustrated here is molded as a member to seal a portion in the axial direction in the cylindrical gap.

(26) The first outer watertight member **42** allows the inner peripheral side to adhere to the groove bottom of the annular groove and the outer peripheral side to adhere to the inner peripheral wall surface **521a** of the counterpart fitting part **521**, so as to seal the annular gap between the groove bottom of the annular groove and the inner peripheral wall surface **521a** of the counterpart fitting part **521**, thereby preventing liquid such as water from entering to the inside of the housing **501** from between the fitting part **21** and the counterpart fitting part **521**. Therefore, the first outer watertight member **42** is molded from an elastically deformable synthetic resin material such as rubber.

(27) The first outer watertight member **42** has a base **42a** of a cylindrical shape, a lip **42b** with an annular shape that is coaxial and protrudes from the inner peripheral surface of the base **42a** (hereinafter referred to as an “inner peripheral lip”), and a lip **42c** with an annular shape that protrudes from the outer peripheral surface of the base **42a** (hereinafter referred to as an “outer peripheral lip”) (FIG. **5**). In the first outer watertight member **42**, a plurality of the inner peripheral lips **42b** and the outer peripheral lips **42c** are lined up in the cylinder axis direction of the base **42a**. The first outer watertight member **42** illustrated here has two inner peripheral lips **42b** and two outer peripheral lips **42c**. The base **42a** illustrated here is formed in a cylindrical shape such that a cross section orthogonal to the cylinder axis has a shape of an ellipse. The inner peripheral lip **42b** and outer peripheral lip **42c** illustrated here are each formed in a cylindrical shape such that a cross section orthogonal to the cylinder axis of the base **42a** is an ellipse.

(28) In addition, the connector **1** has a rear holder **52** assembled thereto between the opening **22a** of the wire housing section **22** and the inner watertight member **41**, so as to hold the wire **We** while suppressing bending of the wire **We** (FIG. **5**). The rear holder **52** in this example has a two-part structure including a first holder member **52A** and a second holder member **52B**, and allows the first holder member **52A** and the second holder member **52B** to clamp and hold the respective wires **We**. Each wire **We** is pulled out outward from the opening **22a** through the rear holder **52**. The rear holder **52** is held in the corresponding wire housing section **22** by hooking mooring parts respectively provided in the first holder member **52A** and the second holder member **52B** on claw parts provided in the wire housing section **22**, although not described in detail. The first holder member **52A** and the second holder member **52B** are molded from insulating materials such as synthetic resin, for example.

(29) The shield shell **30** covers the protruding portions of the housing **20** from the counterpart fitting part **521** on the extraction direction side (the corresponding wire housing section **22** and the corresponding housing flange part **24**) from the outside, thereby suppressing intrusion of noise to the wire **We** inside from the outside. Therefore, the shield shell **30** is molded from a metallic material (e.g., aluminum or aluminum alloy). The shield shell **30** illustrated here is press-formed using a metal plate as a base material.

(30) The shield shell **30** has a cylindrical part **31** that covers the corresponding wire housing section **22** from the outside (FIGS. **1** to **5** and **7**). The cylindrical part **31** is formed in a cylindrical shape such that a cross section orthogonal to the cylinder axis is an ellipse, and has two wire housing sections **22** arranged in parallel along a longitudinal direction of the ellipse.

(31) The shield shell **30** has a flange part **32** (hereinafter referred to as a “shell flange part”) that protrudes outward beyond the outer peripheral surface of the cylindrical part **31** thereof and is disposed counterpart the wall surface **502a** of the counterpart wall body **502** with an interval therebetween when in the fitting state (FIGS. **1** to **5** and **7**). The shell flange part **32** is molded to have an annular and flat shape that is coaxial with the cylinder axis of the cylindrical part **31**, and that protrudes outward beyond the outer peripheral surface of the cylindrical part **31**. The shell flange part **32**, when in the fitting state, has one plane **32a** disposed opposite the wall surface **502a** of the counterpart wall body **502** with an interval therebetween (FIG. **4**).

(32) Here, the housing flange part **24** is interposed between the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502** when in the fitting state (FIGS. **3** and **4**). The outer peripheral surface **24a** of the housing flange part **24** is disposed inside an outer peripheral edge of the shell flange part **32** and outside an inner edge of the shell flange part **32**. This allows the housing flange part **24** to have, as described earlier, the contact surface **24b** on the insertion direction side contact a peripheral portion of the counterpart fitting part **521** in the wall surface **502a** of the counterpart wall body **502** when in the fitting state. In the housing flange part **24**, a wall surface **24c** with an annular shape on the extraction direction side is disposed opposite the inner edge side in one plane **32a** of the shell flange part **32** (FIGS. **3** and **4**). The inner peripheral side in the one plane **32a** and the wall surface **24c** of the housing flange part **24** may be disposed opposite with each other with an interval or without interval therebetween.

(33) The shield shell **30** has a fixed part **33** that is bent from an end of the outer peripheral edge of the shell flange part **32**, and is, when in the fitting state, fixed to an end surface **502b** of the counterpart wall body **502** (FIGS. **1** to **5** and **7**).

(34) Here, the end surface **502b** of the counterpart wall body **502** is a plane that is orthogonally connected to the wall surface **502a**, and has one plane **33a** of the fixed part **33** of a flat shape disposed opposite thereto when in the fitting state (FIG. **4**). The fixed part **33** illustrated here is bent 90 degrees from the end of the shell flange part **32** so as to be orthogonal to the shell flange part **32**. The fixed part **33** illustrated here is fixed to the end surface **502b** of the counterpart wall body **502** by screwing and fixing. Therefore, the end surface **502b** of the counterpart wall body **502** has a fixing part **502c** as a female screw part to fix the fixed part **33** (FIG. **1**). The fixing part **502c** illustrated here has a spacer part **502d** with an annular shape protruding from the end surface **502b** of the counterpart wall body **502**. The one plane **33a** in the fixed part **33** is offset from the end surface **502b** of the counterpart wall body **502** by a thickness of the spacer part **502d**. The fixed part **33** has a through hole **33b** formed thereon into which a male screw (not illustrated) is inserted, the male screw being disposed opposite the fixing part **502c** and screwed into the fixing part **502c** when the fitting part **21** is inserted and fitted into the counterpart fitting part **521** (FIGS. **1** and **2**). Here, two sets of the through hole **33b** and the fixing part **502c** in its pair are provided.

(35) The connector **1** includes a braid (not illustrated) that covers the outer peripheral surface of the cylindrical part **31** of the shield shell **30** and the wires **We** pulled out outward from the openings **22a** of the respective wire housing sections **22**. The braid is a cylindrical and mesh-like braided material made of metallic material, which suppresses the intrusion of noise to the wires **We** pulled

out outward from the respective openings **22a**. The braid is pressed against the outer peripheral surface of the cylindrical part **31** using a cylindrical connection member **35** (FIGS. **1**, **2** and **5**).

(36) By the way, in the connector **1**, the first outer watertight member **42** described earlier prevents a liquid such as water from entering to the inside of the housing **501** from between the fitting part **21** and the counterpart fitting part **521**. And in this connector **1**, it is desirable to reduce the amount of liquid flowing into between the fitting part **21** and the counterpart fitting part **521** if liquid tightness therebetween is to be considered. Therefore, the connector **1** has a second watertight member **43** with an annular shape (hereinafter referred to as a “second outer watertight member”) that is crushed between the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502** when in the fitting state (FIGS. **1**, **3** to **5**, and **7**).

(37) That second outer watertight member **43** is disposed outside the housing flange part **24**. For example, the second outer watertight member **43** is disposed on the outer peripheral surface **24a** side of the housing flange part **24** so as to cover the outer peripheral surface **24a**. The second outer watertight member **43** is disposed on the shell flange part **32** side in the housing flange part **24** so as to be clamped between the housing flange part **24** and the shell flange part **32**. The second outer watertight member **43**, regardless of a manner of being disposed outside the housing flange part **24**, has an inner peripheral surface **43a** disposed opposite the outer peripheral surface **24a** of the housing flange part **24**, and a pressurized surface **43b** with an annular shape that protrudes to the insertion direction side beyond the contact surface **24b** of the housing flange part **24** and that is subjected to a pressing force from the wall surface **502a** of the counterpart wall body **502** when in the fitting state (FIGS. **1**, **3**, **4**, and **7**).

(38) The second outer watertight member **43** described here is an annular body that covers the outer peripheral surface **24a** of the housing flange part **24** on the outer peripheral surface **24a** side and is attached to the shell flange part **32** of the shield shell **30**. The second outer watertight member **43** is molded from an elastically deformable synthetic resin material such as rubber. More specifically, the second outer watertight member **43** is molded using a sponge-like sheet member. The second outer watertight member **43** described here is made of EPDM (ethylene propylene diene rubber) and is molded to have an annular shape that is coaxial with the cylindrical part **31** of the shield shell **30** and that has a cross section orthogonal to the cylinder axis, the cross section being an ellipse (FIG. **7**). In the second outer watertight member **43**, the inner surface of its elliptical annulus is the above-described inner peripheral surface **43a**, and the annular wall surface on the insertion direction side in the annulus is the above-described pressurized surface **43b**. In the second outer watertight member **43**, a wall surface **43c** with an annular shape on the extraction direction side is attached to the one plane **32a** of the shell flange part **32** using an adhesive or a double-sided tape (FIGS. **3** and **4**).

(39) In the connector **1**, by inserting and fitting the fitting part **21** into the counterpart fitting part **521**, the pressurized surface **43b** of the second outer watertight member **43** contacts the wall surface **502a** of the counterpart wall body **502**, and by continuing the inserting and fitting, the second outer watertight member **43** is crushed while the pressurized surface **43b** is subjected to a pressing force from the wall surface **502a** of the counterpart wall body **502**. In the connector **1**, by further continuing the inserting and fitting, the contact surface **24b** of the housing flange part **24** contacts the wall surface **502a** of the counterpart wall body **502**. In this connector **1**, when its contact surface **24b** contacts the wall surface **502a** of the counterpart wall body **502**, the fitting part **21** enters the fitting state where the inserting and fitting thereof is completed, and crushing of the second outer watertight member **43** stops there. As a result, in the connector **1**, the second outer watertight member **43** is sandwiched between the one plane **32a** of the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502** while being pressurized in the insertion and extraction direction, thereby preventing liquid from entering therebetween from the outside.

(40) Here, the amount of protrusion of the second outer watertight member **43** from the contact surface **24b** of the housing flange part **24** is, when the shield shell **30** may move relative to the

counterpart wall body **502** in the fitting state, desirably greater than, for example, a sum of a maximum value of relative movement amount in the insertion and extraction direction (insertion direction and extraction direction) between the shield shell **30** and the counterpart wall body **502** and a cumulative tolerance of a gap in the insertion and extraction direction (insertion direction and extraction direction) between the one plane **32a** of the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502**. The cumulative tolerance is a well-known cumulative tolerance that is calculated based on dimensional tolerances of respective components involved in the gap. As a result, in the connector **1**, even in a case of, for example, a largest relative movement between the shield shell **30** and the counterpart wall body **502** in the insertion and extraction direction due to an external input during vehicle driving when in the fitting state therebetween, a pressing force can be applied to the pressurized surface **43b** from the wall surface **502a** of the counterpart wall body **502**, and the second outer watertight member **43** remains crushed, thereby preventing liquid from entering between the one plane **32a** of the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502** from the outside. It should be noted that, in the connector **1**, instead of the cumulative tolerance, an accumulated tolerance may be used in which the dimensional tolerances of the respective components involved in the gap have been accumulated, so as to determine an amount of protrusion of the second outer watertight member **43**.

(41) Furthermore, in the connector **1**, the fixed part **33** of the shield shell **30** is fixed to the end surface **502b** of the counterpart wall body **502** when the connector **1** is in the fitting state. Therefore, when no relative movement occurs between the shield shell **30** and the counterpart wall body **502**, the amount of protrusion of the second outer watertight member **43** from the contact surface **24b** of the housing flange part **24** is larger than the cumulative tolerance of the gap in the insertion and extraction direction (insertion and extraction direction) between the one plane **32a** of the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502**. As a result, in the connector **1**, even if there is a variation in the dimensions of the respective components within a range of the tolerance, a pressing force can be applied from the wall surface **502a** of the counterpart wall body **502** to the pressurized surface **43b** when the connector **1** is in the fitting state, and the second outer watertight member **43** remains crushed, thereby preventing liquid from entering between the one plane **32a** of the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502** from the outside.

(42) As described above, the connector **1** of the present embodiment includes the second outer watertight member **43** between the shell flange part **32** and the wall surface **502a** of the counterpart wall body **502**, thereby reducing the amount of liquid flowing through a gap therebetween, into a gap between the fitting part **21** and the counterpart fitting part **521**. In particular, the connector **1** includes a first outer watertight member **42** between the fitting part **21** and the counterpart fitting part **521**, so as to suppress the amount of liquid flowing therebetween, so that the liquid tightness between the fitting part **21** and the counterpart fitting part **521** can be maintained by the first outer watertight member **42**.

(43) In the connector according to the present embodiment, by inserting and fitting the fitting part into the counterpart fitting part, a pressurized surface of a second watertight member contacts the wall surface of the counterpart wall body, and by continuing the inserting and fitting, the second watertight member is crushed while the pressurized surface is subjected to a pressing force from the wall surface of the counterpart wall body. In this connector, the inserting and fitting are continued, so that a contact surface of a housing flange part contacts the wall surface of the counterpart wall body. In this connector, when the contact surface of the connector contacts the wall surface of the counterpart wall body, the connector enters a fitting state where the inserting and fitting of the fitting part is completed, and crushing of the second watertight member stops there. As a result, in this connector, the second watertight member is sandwiched between the shell flange part and the wall surface of the counterpart wall body while the second watertight member is pressurized in an insertion and extraction direction, thereby preventing liquid from the outside from

entering therebetween. Therefore, the connector according to the present invention includes the second watertight member between the shell flange part and the wall surface of the counterpart wall body, thereby reducing the amount of liquid flowing through a gap therebetween, into a gap between the fitting part and the counterpart fitting part.

(44) Although the invention has been described with respect to specific embodiments for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art that fairly fall within the basic teaching herein set forth.

Claims

1. A connector comprising: a terminal metal fitting attached to an end of a wire; a housing having a fitting part that accommodates the terminal metal fitting inside thereof and that is inserted and fitted into a counterpart fitting part with a bore shape of a counterpart wall body; a shield shell including a cylindrical part that covers, from outside, a protruding portion of the housing that protrudes from the counterpart fitting part on an opposite side of an insertion direction of the fitting part to the counterpart fitting part, and a shell flange part that protrudes outward beyond a first outer peripheral surface of the cylindrical part and is disposed opposite a wall surface of the counterpart wall body with an interval therebetween; a first watertight member with an annular shape that is attached to an outer peripheral wall surface of the fitting part and covers a cylindrical gap between the fitting part and the counterpart fitting part in a fitting state where the fitting part is inserted and fitted into the counterpart fitting part; and a second watertight member with an annular shape that is crushed between the shell flange part and the wall surface of the counterpart wall body when in the fitting state, wherein the housing has a housing flange part that is interposed between the shell flange part and the wall surface of the counterpart wall body when in the fitting state, and a second outer peripheral surface is disposed inside an outer edge of the shell flange part and outside an inner edge of the shell flange part, the housing flange part has a contact surface with an annular shape that contacts the wall surface of the counterpart wall body when in the fitting state, the second watertight member is disposed outside of the housing flange part and has an inner peripheral surface disposed opposite the second outer peripheral surface of the housing flange part and a pressurized surface with an annular shape that protrudes to the insertion direction side beyond the contact surface of the housing flange part and is subjected to a pressing force from the wall surface of the counterpart wall body when in the fitting state, and the second watertight member is attached to the shell flange part.
 2. The connector according to claim 1, wherein an amount of protrusion from the contact surface of the housing flange part in the second watertight member is greater than a sum of a maximum value of relative movement amount in the insertion direction between the shield shell and the counterpart wall body and a cumulative tolerance of a gap in the insertion direction between the shell flange part and the wall surface of the counterpart wall body.
 3. The connector according to claim 1, wherein the shield shell has a fixed part that is bent from an end of the outer peripheral edge of the shell flange part and fixed to an end surface of the counterpart wall body.
 4. The connector according to claim 1, wherein the second watertight member is made of an ethylene propylene diene rubber.
 5. The connector according to claim 2, wherein the second watertight member is made of an ethylene propylene diene rubber.
 6. The connector according to claim 3, wherein the second watertight member is made of an ethylene propylene diene rubber.
-