

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282503

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Roizin; Yakov et al.

APPARATUS, SYSTEM, AND METHOD OF CHARGING A BATTERY OF AN AERIAL VEHICLE

Abstract

For example, an apparatus may include a processor configured to process photodiode signal information, which corresponds to a plurality of photodiodes of an aerial vehicle, for example, to identify a plurality of electric currents, which may be generated by the plurality of photodiodes based on energy of a light beam to charge a battery of the aerial vehicle. For example, the processor may be configured to determine a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents. For example, the vehicle-position displacement may be configured to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam. For example, the apparatus may include an output to provide position displacement information based on the vehicle-position displacement.

Inventors: Roizin; Yakov (Afula, IL), Pikhay; Evgeny (Haifa, IL), Mizrahi; Niv (Kiryat Bialik, IL)

Applicant: TOWER SEMICONDUCTOR LTD. (Migdal Haemek, IL)

Family ID: 96948506

Assignee: TOWER SEMICONDUCTOR LTD. (Migdal Haemek, IL)

Appl. No.: 18/598797

Filed: March 07, 2024

Publication Classification

Int. Cl.: B64U50/31 (20230101); B64U101/00 (20230101); H02J7/35 (20060101)

U.S. Cl.:

CPC B64U50/31 (20230101); H02J7/35 (20130101); B64U2101/00 (20230101)

Background/Summary

TECHNICAL FIELD

[0001] Aspects described herein generally relate to charging a battery of an aerial vehicle.

BACKGROUND

[0002] An aerial vehicle, e.g., a drone, may include a battery, which may be configured to provide electric power to the aerial vehicle.

[0003] Battery resources of the battery may be limited and, accordingly, it may be required to charge the battery of the aerial vehicle.

[0004] In some implementations, the battery of the aerial vehicle may be charged, for example, by connecting the aerial vehicle to a battery charger on the ground. However, this implementation may not be efficient, as it may require the aerial vehicle to land on the ground.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] For simplicity and clarity of illustration, elements shown in the figures have not necessarily been drawn to scale. For example, the dimensions of some of the elements may be exaggerated relative to other elements for clarity of presentation. Furthermore, reference numerals may be repeated among the figures to indicate corresponding or analogous elements. The figures are listed below.

[0006] FIG. 1 is a schematic block diagram illustration of an aerial device, in accordance with some demonstrative aspects.

[0007] FIG. 2 is a schematic illustration of components of an aerial device, in accordance with some demonstrative aspects.

[0008] FIG. 3 is a schematic flow-chart illustration of a method of determining a vehicle position displacement to displace an aerial vehicle, in accordance with some demonstrative aspects.

[0009] FIG. 4 is a schematic illustration of a graph depicting output currents of a photodiode, in accordance with some demonstrative aspects.

[0010] FIG. 5 is a schematic illustration of an aerial device, in accordance with some demonstrative aspects.

[0011] FIG. 6 is a schematic flow-chart illustration of a method of charging a battery of an aerial vehicle, in accordance with some demonstrative aspects.

[0012] FIG. 7 is a schematic illustration of a product of manufacture, in accordance with some demonstrative aspects.

DETAILED DESCRIPTION

[0013] In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of some aspects. However, it will be understood by persons of ordinary skill in the art that some aspects may be practiced without these specific details. In other instances, well-known methods, procedures, components, units and/or circuits have not been described in detail so as not to obscure the discussion.

[0014] Discussions herein utilizing terms such as, for example, “processing”, “computing”, “calculating”, “determining”, “establishing”, “analyzing”, “checking”, or the like, may refer to operation(s) and/or process(es) of a computer, a computing platform, a computing system, or other electronic computing device, that manipulate and/or transform data represented as physical (e.g., electronic) quantities within the computer's registers and/or memories into other data similarly represented as physical quantities within the computer's registers and/or memories or other information storage medium that may store instructions to perform operations and/or processes.

[0015] The terms “plurality” and “a plurality”, as used herein, include, for example, “multiple” or “two or more”. For example, “a plurality of items” includes two or more items.

[0016] References to “one aspect”, “an aspect”, “demonstrative aspect”, “various aspects” etc., indicate that the aspect(s) so described may include a particular feature, structure, or characteristic, but not every aspect necessarily includes the particular feature, structure, or characteristic. Further, repeated use of the phrase “in one aspect” does not necessarily refer to the same aspect, although it may.

[0017] As used herein, unless otherwise specified the use of the ordinal adjectives “first”, “second”, “third” etc., to describe a common object, merely indicate that different instances of like objects are being referred to, and are not intended to imply that the objects so described must be in a given sequence, either temporally, spatially, in ranking, or in any other manner.

[0018] The phrases “at least one” and “one or more” may be understood to include a numerical quantity greater than or equal to one, e.g., one, two, three, four, [. . .], etc. The phrase “at least one of” with regard to a group of elements may be used herein to mean at least one element from the group consisting of the elements. For example, the phrase “at least one of” with regard to a group of elements may be used herein to mean one of the listed elements, a plurality of one of the listed elements, a plurality of individual listed elements, or a plurality of a multiple of individual listed elements.

[0019] The terms “substrate” and/or “wafer”, as used herein, may relate to a thin slice of semiconductor material, for example, a silicon crystal, which may be used in fabrication of integrated circuits and/or any other microelectronic devices. For example, the wafer may serve as the substrate for the microelectronic devices, which may be built in and over the wafer.

[0020] The term “Integrated Circuit” (IC), as used herein, may relate to a set of one or more electronic circuits on a semiconductor material. For example, an electronic circuit may include electronic components and their interconnectors.

[0021] The term “data” as used herein may be understood to include information in any suitable analog or digital form, e.g., provided as a file, a portion of a file, a set of files, a signal or stream, a portion of a signal or stream, a set of signals or streams, and the like. Further, the term “data” may also be used to mean a reference to information, e.g., in form of a pointer. The term “data”, however, is not limited to the aforementioned examples and may take various forms and/or may represent any information as understood in the art.

[0022] The terms “processor” or “controller” may be understood to include any kind of technological entity that allows handling of any suitable type of data and/or information. The data and/or information may be handled according to one or more specific functions executed by the processor or controller. Further, a processor or a controller may be understood as any kind of circuit, e.g., any kind of analog or digital circuit. A processor or a controller may thus be or include an analog circuit, digital circuit, mixed-signal circuit, logic circuit, processor, microprocessor, Central Processing Unit (CPU), Graphics Processing Unit (GPU), Digital Signal Processor (DSP), Field Programmable Gate Array (FPGA), integrated circuit, Application Specific Integrated Circuit (ASIC), and the like, or any combination thereof. Any other kind of implementation of the respective functions, which will be described below in further detail, may also be understood as a processor, controller, or logic circuit. It is understood that any two (or more) processors, controllers, or logic circuits detailed herein may be realized as a single entity with equivalent functionality or the like, and conversely that any single processor, controller, or logic circuit detailed herein may be realized as two (or more) separate entities with equivalent functionality or the like.

[0023] The term “memory” is understood as a computer-readable medium (e.g., a non-transitory computer-readable medium) in which data or information can be stored for retrieval. References to “memory” may thus be understood as referring to volatile or non-volatile memory, including random access memory (RAM), read-only memory (ROM), flash memory, solid-state storage,

magnetic tape, hard disk drive, optical drive, among others, or any combination thereof. Registers, shift registers, processor registers, data buffers, among others, are also embraced herein by the term memory. The term “software” may be used to refer to any type of executable instruction and/or logic, including firmware.

[0024] The term “circuitry”, as used herein, may refer to, be part of, or include, an Application Specific Integrated Circuit (ASIC), an integrated circuit, an electronic circuit, a processor (shared, dedicated, or group), and/or memory (shared, dedicated, or group), that execute one or more software or firmware programs, a combinational logic circuit, and/or other suitable hardware components that provide the described functionality. In some aspects, some functions associated with the circuitry may be implemented by one or more software or firmware modules. In some aspects, circuitry may include logic, at least partially operable in hardware.

[0025] The term “logic” may refer, for example, to computing logic embedded in circuitry of a computing apparatus and/or computing logic stored in a memory of a computing apparatus. For example, the logic may be accessible by a processor of the computing apparatus to execute the computing logic to perform computing functions and/or operations. In one example, logic may be embedded in various types of memory and/or firmware, e.g., silicon blocks of various chips and/or processors. Logic may be included in, and/or implemented as part of, various circuitry, e.g., radio circuitry, receiver circuitry, control circuitry, transmitter circuitry, transceiver circuitry, processor circuitry, and/or the like. In one example, logic may be embedded in volatile memory and/or non-volatile memory, including random access memory, read only memory, programmable memory, magnetic memory, flash memory, persistent memory, and/or the like. Logic may be executed by one or more processors using memory, e.g., registers, buffers, stacks, and the like, coupled to the one or more processors, e.g., as necessary to execute the logic.

[0026] A “vehicle” may be understood to include any type of driven object. By way of example, a vehicle may be a driven object with a combustion engine, an electric engine, a reaction engine, an electrically driven object, a hybrid driven object, or a combination thereof.

[0027] An “aerial vehicle” may be understood to include any type of vehicle, which is configured to traverse within the air.

[0028] An “autonomous vehicle” may describe a vehicle capable of implementing at least one navigational change without a remote operator or a driver input. A navigational change may describe or include a change in one or more of an attitude, direction, orientation, steering, braking, acceleration/deceleration, or any other operation relating to movement, of the vehicle. A vehicle may be described as autonomous even in case the vehicle is not fully autonomous, for example, fully operational with or without a remote operator and/or a driver input. Autonomous vehicles may include those vehicles that can operate under remote operator control during certain time periods, and without remote operator control during other time periods. Additionally or alternatively, autonomous vehicles may include vehicles that control only some aspects of vehicle navigation, such as steering, e.g., to maintain a vehicle course, or some steering operations under certain circumstances, e.g., not under all circumstances, but may leave other aspects of vehicle navigation to the remote operator.

[0029] Reference is made to FIG. 1, which schematically illustrates a block diagram of an aerial vehicle **102**, in accordance with some demonstrative aspects.

[0030] In some demonstrative aspects, aerial vehicle **102** may include a drone, a quadcopter, an Unmanned Aerial Vehicle (UAV), or any other type of aerial vehicle.

[0031] In some demonstrative aspects, the aerial vehicle **102** may be configured to perform one or more operations, for example, while traversing the air, e.g., including flying, hovering, image capturing functionalities, photography functionalities, security functionalities, surveillance functionalities, communication functionalities, military functionalities, and/or the like.

[0032] In some demonstrative aspects, aerial vehicle **102** may be configured to carry at least one payload **199**, which may be configured to carry out one or more functionalities.

[0033] In one example, payload **199** may include an image-capturing device, e.g., a camera.

[0034] In another example, payload **199** may include one or more sensors, e.g., image sensors, heat sensors, and/or any other type of sensors.

[0035] In another example, payload **199** may include one or more communication devices, for example, transmitters, receivers, transceivers, routers, communication processors, or the like.

[0036] In another example, payload **199** may include one or more memories and/or storage devices, e.g., to store information processed by one or more other payloads.

[0037] In other aspects, payload **199** may include any other additional or alternative devices or systems.

[0038] In some demonstrative aspects, the aerial vehicle **102** may be configured to fly autonomously and/or to be piloted remotely, e.g., by a remote operator.

[0039] In some demonstrative aspects, the aerial vehicle may include a movement controller **140**, which may be configured to control movement of the aerial vehicle **102**.

[0040] In some demonstrative aspects, movement controller **140** may be configured to control one or more flight-control components and/or elements **142** of aerial vehicle **102**, for example, to control the movement of the aerial vehicle **102**.

[0041] In some demonstrative aspects, the one or more flight-control components **142** may include, for example, one or more motors, one or more engines, one or more wings, one or more rotors, one or more propellers, and/or any other suitable component and/or element, which may be utilized to control the movement of the aerial vehicle **102**.

[0042] In some demonstrative aspects, aerial vehicle **102** may include a battery **105**, which may be configured to provide electric power to components of the aerial vehicle **102**, e.g., to an engine of the aerial vehicle **102**, for example, to move the aerial vehicle **102**.

[0043] In some demonstrative aspects, a capacity of the battery **105** may be limited, and charging the battery **102** may be required, for example, before resources of the battery **105** are exhausted.

[0044] In some demonstrative aspects, the battery **105** may be charged, for example, to allow the aerial vehicle **102** to continue to perform one or more activities.

[0045] In one example, in many use cases and/or implementations it may not be efficient to configure an aerial vehicle to be charged on the ground, e.g., by a battery charger. For example, an aerial vehicle configured for charging on the ground may have a limited operation time, and/or limited operation distance, which may result in limited utilization of the aerial vehicle.

[0046] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support wireless charging of the remote aerial vehicle **102**, e.g., as described below.

[0047] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support wireless charging of the aerial vehicle **102**, for example, while the aerial vehicle **102** is in the air, e.g., as described below.

[0048] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support wireless charging of the aerial vehicle **102**, for example, based on energy of a light beam **103**, e.g., as described below.

[0049] In some demonstrative aspects, light beam **103** may be emitted, for example, from a light transmitter **106**.

[0050] For example, light transmitter **106** may include a light source, e.g., a laser source, an Infra-Red (IR) light source, a Light Emitting Diode (LED), a power LED, a power IR LED, an array of LEDs, or the like.

[0051] For example, the light transmitter **106** may be located at a light transmission station (not shown in FIG. 1). For example, the light transmission station may be located on the ground, or at

any other suitable location.

[0052] In some demonstrative aspects, aerial vehicle **102** may include a light receiver **130**, which may be configured to harvest the energy of the light beam **103**, which may be used, for example, to charge the battery **105**, e.g., as described below.

[0053] In some demonstrative aspects, light receiver **130** may include one or more light-receiving and/or energy-collecting components, which may be configured to “harvest” energy from light beam **103**, e.g., as described below.

[0054] In some demonstrative aspects, light receiver **130** may include an energy harvesting silicon chip, which may be configured to include energy collecting resources, e.g., a high-efficiency photovoltaic cell, which may be configured to collect energy from the light beam **103**, e.g., as described below.

[0055] In some demonstrative aspects, light receiver **130** may be configured to implement an energy harvesting silicon chip including a plurality of photodiodes, e.g., in the form of silicon photovoltaic devices, to harvest energy from light beam **103**, e.g., as described below.

[0056] For example, light receiver **130** may implement the silicon photovoltaic devices to provide a technical solution to support implementation of light receiver **130** with reduced cost, for example, compared to implementations using AIIIbV (A3B5) devices.

[0057] In some demonstrative aspects, as shown in FIG. 1, light receiver **130** may include a plurality of photodiodes **132** to harvest energy from the light beam **103**, e.g., as described below.

[0058] In other aspects, light receiver **130** may be configured to include any other additional or alternative energy harvesting components and/or mechanisms, which may be configured to collect energy from the light beam **103**.

[0059] In some demonstrative aspects, light receiver **130** may generate an electrical current to charge the battery **105**, for example, based on the light beam **103**.

[0060] In some demonstrative aspects, the level of the electrical current, which may be provided by the light receiver to charge the battery **105**, may depend on a relative position between the light receiver **130** and the light beam **103**, e.g., as described below.

[0061] For example, the level of the electrical current, which may be provided by the light receiver to charge the battery **105**, may be affected by the flux of light from light beam **103** incident on the light receiver **130**, e.g., as described below.

[0062] For example, the level of the electrical current, which may be provided by the light receiver to charge the battery **105**, may be increased, for example, with an increase in the flux of light from light beam **103** incident on the light receiver **130**, e.g., as described below.

[0063] For example, light receiver **130** may not be able to generate sufficient electrical current to properly charge the battery **105**, for example, in case the flux of light from light beam **103** incident on the light receiver **130** is too low.

[0064] For example, the level of the electrical current, which may be provided by the light receiver to charge the battery **105**, may be affected by an alignment between the light receiver **130** and the light beam **103**, e.g., as described below.

[0065] For example, the level of the electrical current, which may be provided by the light receiver to charge the battery **105**, may increase, for example, with the alignment between the light receiver **130** and the light beam **103**, e.g., as described below.

[0066] For example, light receiver **130** may not be able to generate sufficient electrical current to properly charge the battery **105**, for example, in case the light receiver **130** is not properly aligned with the light beam **103**.

[0067] In some demonstrative aspects, in some use cases, scenarios, and/or implementations, there may be one or more technical inefficiencies, disadvantages and/or problems in implementing one or more techniques (“beam-direction adjusting techniques”), which may be configured to adjust a direction of a light beam for an aerial vehicle, e.g., at the light transmitter, for example, in order to align the light beam with a light receiver of the aerial vehicle.

[0068] For example, the beam-direction adjusting techniques may be complicated, may be affected by environmental conditions, e.g., weather conditions, may be inefficient, and/or may be hard to implement.

[0069] In one example, a ground tracking system may be configured to adjust a direction of the light beam to track the position of the aerial vehicle. For example, a camera may be implemented at a ground station to track the position of the aerial vehicle, for example, based on images of the aerial vehicle and/or reflections of the light beam, which may be captured by the camera. For example, the images captured by the camera may be used to track the aerial vehicle, and to adjust the direction of the light beam, e.g., to aim the light beam towards the aerial vehicle. For example, performance of such ground tracking system may be affected by environment conditions, e.g., weather conditions.

[0070] In another example, a ground tracking system may be configured to adjust the direction of the light beam, for example, based on feedback, e.g., a laser feedback or any other feedback, which may be communicated from the aerial vehicle to a station operating the light transmitter. For example, the feedback from the aerial vehicle may be configured to indicate a direction in which the light beam is to be directed from the station towards the aerial vehicle. For example, implementation of the feedback from the aerial vehicle to the station may require the use of a communication interface, e.g., a dedicated communication payload, which may add complexity and cost.

[0071] For example, implementation of the laser feedback may be subject to atmospheric turbulence, which may cause fluctuations of the laser feedback and, accordingly, may affect an accuracy of the laser feedback, which may lead to a degradation in the accuracy of the adjustment of the direction of the light beam.

[0072] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support an alignment, e.g., an improved alignment, between light receiver **130** and light beam **103**, for example, even without using a camera, a tracking device, a feedback, and/or any other beam-direction adjusting techniques, e.g., as described below.

[0073] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support an alignment, e.g., an improved alignment, between light receiver **130** and light beam **103**, for example, even without adjusting the direction of the light beam **103**, e.g., as described below.

[0074] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support an alignment, e.g., an improved alignment, between light receiver **130** and light beam **103**, for example, by adjusting a position of the light receiver **130** relative to the light beam **103**, e.g., as described below.

[0075] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support an alignment, e.g., an improved alignment, between light receiver **130** and light beam **103**, for example, by controlling a position of the aerial vehicle **102** relative to the light beam **103**, e.g., as described below.

[0076] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support an alignment, e.g., an improved alignment, between light receiver **130** and light beam **103**, for example, by adjusting a position of the aerial vehicle **102** relative to the light beam **103**, e.g., as described below.

[0077] In some demonstrative aspects, the wireless charging mechanism may be configured to provide a technical solution to substantially maintain alignment of one or more light-receiving

and/or energy-collecting components of light receiver **130**, e.g., energy collecting resources of an energy harvesting silicon chip of light receiver **130**, with the light beam **103**, e.g., as described below.

[0078] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support the light-receiving and/or energy-collecting components of light receiver **130** in absorbing an increased quanta, e.g., a significant quanta, of the energy of light beam **103**, e.g., as described below.

[0079] In some demonstrative aspects, aerial vehicle **102** may be configured to implement one or more operations and/or functionalities of a wireless charging mechanism, which may be configured to provide a technical solution to support the alignment between the light receiver **130** and the light beam **130**, for example, by utilizing one or more high mobility attributes of the aerial vehicle **102**.

[0080] For example, the wireless charging mechanism may be configured to utilize high mobility attributes of modern aerial vehicles, e.g., modern drones, for example, to move and/or displace the aerial vehicle **102**, for example, in order to adjust a relative position of the light receiver **130** relative to the light beam **103**, e.g., as described below.

[0081] In some demonstrative aspects, aerial vehicle **102** may include a data processor **120**, which may be configured to control and/or adjust a relative position of the light receiver **130** relative to the light beam **103**, for example, based on photodiode signal information **133** corresponding to the plurality of photodiodes **132** of light receiver **130**, e.g., as described below.

[0082] In some demonstrative aspects, one or more components and/or functionalities of data processor **120** may be implemented as a dedicated and/or separate element of aerial device **102**.

[0083] In other aspects, one or more components and/or functionalities of data processor **120** may be implemented as part of controller **140** and/or as part of any other suitable component and/or element of aerial device **102**.

[0084] In some demonstrative aspects, data processor **120** may include a processor **122**, which may be configured to process the photodiode signal information **133**, e.g., as described below.

[0085] In some demonstrative aspects, processor **122** may include, or may be implemented, partially or entirely, by circuitry and/or logic, e.g., one or more processors including circuitry and/or logic, and/or memory circuitry and/or logic. For example, data processor **120** may include at least one memory (not shown in FIG. 1), e.g., coupled to the processor **122**, for example, to store data processed by processor **122**. For example, the memory may store, e.g., at least temporarily, at least some of the information processed by the processor **122**, and/or logic to be utilized by the processor **122**. Additionally or alternatively, one or more functionalities of processor **122** may be implemented by logic, which may be executed by a machine and/or one or more processors, e.g., as described below.

[0086] In other aspects, processor **122** may be implemented as part of any other, dedicated, or non-dedicated, element of aerial vehicle **102**.

[0087] In some demonstrative aspects, processor **122** may be configured to process the photodiode signal information **133**, for example, to identify a plurality of electric currents **134**, which may be generated by the plurality of photodiodes **132**, e.g., as described below.

[0088] In some demonstrative aspects, the plurality of electric currents **134** may be generated by the plurality of photodiodes **132**, for example, based on energy of the light beam **103** to charge the battery **105** of the aerial vehicle **102**, e.g., as described below.

[0089] In some demonstrative aspects, processor **122** may be configured to determine a vehicle-position displacement **123** to displace the aerial vehicle **102**, for example, based on the plurality of electric currents **134**, e.g., as described below.

[0090] In some demonstrative aspects, the vehicle-position displacement **123** may be configured to adjust a photodiode-beam relative position of the plurality of photodiodes **132** relative to the light beam **103**, e.g., as described below.

[0091] In one example, the vehicle-position displacement **123** may be configured, for example, relative to a current position of the aerial vehicle **102**.

[0092] In another example, the vehicle-position displacement **123** may be configured, for example, relative to a predefined position, e.g., a reference position, of the aerial vehicle **102**.

[0093] In another example, the vehicle-position displacement **123** may be configured, for example, relative to a predefined location, e.g., a reference location.

[0094] In other aspects, the vehicle-position displacement **123** may be configured relative to any other position, location, and/or orientation.

[0095] In one example, the vehicle-position displacement **123** may include, for example, a linear displacement, e.g., a vertical displacement, and/or a horizontal displacement, for example, according to a linear coordinate system.

[0096] In another example, the vehicle-position displacement **123** may include, for example, an angular displacement, e.g., a yaw rotation, a pitch rotation, and/or a roll rotation, for example, according to an angular coordinate system.

[0097] In another example, the vehicle-position displacement **123** may include, for example, a combination of an angular displacement and a linear displacement.

[0098] In other aspects, the vehicle-position displacement **123** may include any other suitable displacement according to any other suitable coordinate system.

[0099] In some demonstrative aspects, data processor **120** may include an output **126**, which may be configured to provide position displacement information **125**, for example, based on the vehicle-position displacement **123**, e.g., as described below.

[0100] In some demonstrative aspects, the position displacement information **125** may be provided to the controller **140**, for example, to control displacement of the aerial vehicle **102**, e.g., as described below.

[0101] In some demonstrative aspects, movement controller **140** may be configured to control movement of the aerial vehicle **102**, for example, based on the position displacement information **125**, e.g., as described below.

[0102] In some demonstrative aspects, the position displacement information **125** may be configured to include information suitable to indicate to controller that the aerial vehicle **102** is to be displaced according to the vehicle-position displacement **123**, e.g., as described below.

[0103] In some demonstrative aspects, the position displacement information **125** may be configured according to a suitable format to request, instruct, trigger, cause, and/or control controller **140** to displace the aerial vehicle **102** according to the vehicle-position displacement **123**, e.g., as described below.

[0104] In some demonstrative aspects, the position displacement information **125** may include, for example, the vehicle-position displacement **123**, e.g., as described below.

[0105] In other aspects, the position displacement information **125** may include any other additional and/or alternative information, which may be based, partially or entirely, on the vehicle-position displacement **123**.

[0106] In some demonstrative aspects, the photodiode signal information **133** may include a plurality of current magnitudes of the plurality of electric currents **134**, e.g., as described below.

[0107] In other aspects, the photodiode signal information **133** may include any other additional and/or alternative information based on the plurality of electric currents **134**.

[0108] In some demonstrative aspects, processor **122** may be configured to receive the plurality of electric currents **134**, and to determine the photodiode signal information **133**, for example, based on the plurality of electric currents **134**.

[0109] For example, processor **122** may be configured to process the plurality of electric currents **134**, for example, to determine the plurality of current magnitudes of the plurality of electric currents **134**.

[0110] In some demonstrative aspects, processor **122** may be configured to receive the photodiode

signal information **133**, for example, from a photodiode signal information provider **107**, which may be implemented by any other suitable element, device, and/or component of aerial device **102**.
[0111] In some demonstrative aspects, the signal information provider **107** may be configured to determine the photodiode signal information **133**, for example, based on the plurality of electric currents **134**, and to provide the photodiode signal information **133**, for example, to processor **122**.
[0112] In some demonstrative aspects, the signal information provider **107** may be configured to determine the plurality of current magnitudes of the plurality of electric currents **134**, for example, based on the plurality of electric currents **134**, and to provide the photodiode signal information **133** including the current magnitudes of the plurality of electric currents **134**, for example, to processor **122**.

[0113] In some demonstrative aspects, the signal information provider **107** may include a current meter, which may be configured to measure the plurality of current magnitudes of the plurality of electric currents **134**.

[0114] For example, the current meter may include current measurement circuitry, a current detector, a current sensor, and/or the like.

[0115] In some demonstrative aspects, the signal information provider **107** may include a processor, which may be configured to generate the photodiode signal information **133**, for example, including the plurality of current magnitudes of the plurality of electric currents **134**.

[0116] For example, the processor of signal information provider **107** may be configured to determine the plurality of current magnitudes of the plurality of electric currents **134**, and to provide the photodiode signal information **133** including the plurality of current magnitudes, e.g., to processor **122**.

[0117] In one example, the processor of signal information provider **107** may be configured to determine the photodiode signal information **133**, for example, based directly on the plurality of electric currents **134**.

[0118] In another example, the processor signal information provider **107** may be configured to determine the photodiode signal information **133**, for example, based on information from another device, e.g., from the current meter.

[0119] In some demonstrative aspects, processor **122** may be configured to determine the photodiode signal information **133**, for example, based on information from signal information provider **107**, which may be based on the plurality of electric currents **134**. For example, the information from signal information provider **107** may include voltage information, power information, and/or any other information, which may be used to determine the photodiode signal information **133**.

[0120] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a real-time levels of, and/or real-time changes in, the levels the electric currents **134** corresponding to the plurality of photodiodes **132**, e.g., as described below.

[0121] In some demonstrative aspects, processor **122** may be configured to determine a first vehicle-position displacement **123**, for example, based on a first plurality of electric currents **134** corresponding to the plurality of photodiodes **132**, e.g., as described below.

[0122] In some demonstrative aspects, processor **122** may be configured to determine a second vehicle-position displacement **123**, for example, based on a second plurality of electric currents **134** corresponding to the plurality of photodiodes **132**, e.g., as described below.

[0123] In some demonstrative aspects, the second plurality of electric currents **134** may be different from the first plurality of electric currents **134**, e.g., as described below.

[0124] In some demonstrative aspects, the second vehicle-position displacement **123** may be different from the first vehicle-position displacement **123**, e.g., as described below.

[0125] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a mapping between the plurality of electric

currents **134** and a plurality of photodiode positions of the plurality of photodiodes **132**, e.g., as described below.

[0126] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a geometrical arrangement of the plurality of photodiode positions, e.g., as described below.

[0127] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a distribution of magnitudes of the plurality of electric currents **134**, e.g., as described below.

[0128] In other aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on any other additional or alternative parameter or attribute of the plurality of electric currents **134**.

[0129] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a comparison between magnitudes of two or more of the plurality of electric currents **134**, e.g., as described below.

[0130] In other aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a comparison between any other attribute and/or parameter corresponding to the plurality of electric currents **134**, e.g., as described below.

[0131] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a difference between a first electric current magnitude mapped to a first photodiode position, e.g., of a first photodiode **132**, and a second electric current magnitude mapped to a second photodiode position, e.g., of a second photodiode **132**, e.g., as described below.

[0132] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a displacement between the first photodiode position and the second photodiode position, e.g., as described below.

[0133] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on the difference between the first electric current magnitude and the second electric current magnitude, and based on a displacement between the first photodiode position and the second photodiode position, e.g., as described below.

[0134] In some demonstrative aspects, processor **122** may be configured to determine a magnitude of the vehicle-position displacement **123**, for example, based on the difference between the first electric current magnitude and the second electric current magnitude, e.g., as described below.

[0135] In other aspects, processor **122** may be configured to determine the magnitude of the vehicle-position displacement **123** based on any other additional and/or alternative function and/or calculation applied to the first electric current magnitude and/or the second electric current magnitude.

[0136] In some demonstrative aspects, processor **122** may be configured to determine a direction of the vehicle-position displacement **123**, for example, based on the displacement between the first photodiode position and the second photodiode position, e.g., as described below.

[0137] In some demonstrative aspects, processor **122** may be configured to determine the direction of the vehicle-position displacement **123**, for example, based on sign of the difference between the first electric current magnitude and the second electric current magnitude, e.g., as described below.

[0138] In other aspects, processor **122** may be configured to determine the direction of the vehicle-position displacement **123** based on any other additional and/or alternative calculation and/or function applied to the first electric current magnitude and/or the second electric current magnitude.

[0139] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a real-time values of, and/or real-time changes in, the difference between the first electric current magnitude mapped to the first photodiode position and the second electric current magnitude mapped to the photodiode position, e.g., as described below.

[0140] In some demonstrative aspects, processor **122** may be configured to determine a first vehicle-position displacement **123**, for example, based on a first difference between the first electric current magnitude mapped to the first photodiode position and the second electric current magnitude mapped to the photodiode position, e.g., as described below.

[0141] In some demonstrative aspects, processor **122** may be configured to determine a second vehicle-position displacement **123**, for example, based on a second difference between the first electric current magnitude mapped to the first photodiode position and the second electric current magnitude mapped to the photodiode position, e.g., as described below.

[0142] In some demonstrative aspects, the first difference between the electric current magnitudes may be different from the second difference between the electric current magnitudes, e.g., as described below.

[0143] In some demonstrative aspects, the second vehicle-position displacement **123**, which is based on the second difference between the electric current magnitudes, may be different from the first vehicle-position displacement **123**, which is based on the first difference between the electric current magnitudes, e.g., as described below.

[0144] In some demonstrative aspects, processor **122** may be configured to determine a photodiode-beam relative position adjustment to adjust the photodiode-beam relative position of the plurality of photodiodes **132** relative to the light beam **103**, e.g., as described below.

[0145] In some demonstrative aspects, processor **122** may be configured to determine the photodiode-beam relative position adjustment, for example, to adjust the photodiode-beam relative position of the plurality of photodiodes **132** relative to the light beam **103**, for example, based on the mapping between the plurality of electric currents **134** and the plurality of photodiode positions, e.g., as described below.

[0146] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on the photodiode-beam relative position adjustment, e.g., as described below.

[0147] In other aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on any other additional or alternative criteria relating to the plurality of electric currents **134**, the plurality of photodiode positions of the plurality of photodiodes **132**, and/or any other suitable additional or alternative information.

[0148] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a target charging current of the battery **105**, e.g., as described below.

[0149] In some demonstrative aspects, processor **122** may be configured to determine a first vehicle-position displacement **123**, for example, based on a first target charging current, e.g., as described below.

[0150] In some demonstrative aspects, processor **122** may be configured to determine a second vehicle-position displacement **123**, for example, based on a second target charging current, e.g., as described below.

[0151] In some demonstrative aspects, the second target charging current may be different from the first target charging current, e.g., as described below.

[0152] In some demonstrative aspects, the second vehicle-position displacement **123** may be different from the first vehicle-position displacement **123**, e.g., as described below.

[0153] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on the target charging current of the battery **105** and a total current of the plurality of electric currents **134**, e.g., as described below.

[0154] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, based on a comparison between the total current of the plurality of electric currents **134** and the target charging current of the battery **105**, e.g., as described below.

[0155] In other aspects, processor **122** may be configured to determine the vehicle-position displacement **123** based on any other additional and/or alternative function and/or calculation applied to the plurality of electric currents **134** and/or the target charging current of the battery **105**.

[0156] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, to increase the total current of the plurality of electric currents **134**, for example, based on a determination that the total current is lower than the target charging current, e.g., as described below.

[0157] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123**, for example, to reduce the total current of the plurality of electric currents **134**, for example, based on a determination that the total current is higher than the target charging current, e.g., as described below.

[0158] In some demonstrative aspects, processor **122** may be configured to determine the target charging current according to a charging profile to charge the battery **105**, for example, based on a State Of Charge (SOC) of the battery **105**, e.g., as described below.

[0159] In other aspects, processor **122** may be configured to determine the target charging current according to the charging profile to charge the battery **105** based on any other additional or alternative criteria.

[0160] In some demonstrative aspects, the target charging current may include a maximal current, e.g., as described below.

[0161] In other aspects, the target charging current may include any other suitable current.

[0162] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123** to adjust the photodiode-beam relative position such that the light beam **103** substantially equally illuminates the plurality of photodiodes **132**, e.g., as described below.

[0163] In some demonstrative aspects, processor **122** may be configured to determine the vehicle-position displacement **123** to adjust the photodiode-beam relative position such that the light beam **103** substantially equally illuminates the plurality of photodiodes **132**, for example, based on a determination that the target charging current includes the maximal current, e.g., as described below.

[0164] In some demonstrative aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** including a Near Infra-Red (NIR) light beam **103**, e.g., as described below.

[0165] In some demonstrative aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** including a Neodymium-Doped Yttrium Aluminum Garnet (ND:YAG) light beam **103**, e.g., as described below.

[0166] In other aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** including any other type of light beam.

[0167] In some demonstrative aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** having a wavelength of, for example, between 0.9 micrometer (um) and 1.1 (um), e.g., as described below.

[0168] In some demonstrative aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** having a wavelength of, for example, between 1 um and 1.08 um, e.g., as described below.

[0169] In some demonstrative aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** having a wavelength of, for example, between 1.05 um and 1.07 um, e.g., as described below.

[0170] In some demonstrative aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** having a wavelength of, for example, substantially about 1.06 um, e.g., as described below.

[0171] In other aspects, the light receiver **130** may be configured to harvest the energy of the light beam **103** having any other suitable wavelength.

[0172] In one example, the light receiver **130** may be configured to harvest the energy of the light beam **103** including an ND:YAG light beam **103** having a wavelength of about 1.06 micrometer.

[0173] In some demonstrative aspects, the plurality of photodiodes **132** may include at least three photodiodes, e.g., as described below.

[0174] In some demonstrative aspects, the plurality of photodiodes **132** may include at least four photodiodes, e.g., as described below.

[0175] In other aspects, the plurality of photodiodes **132** may include any other count of photodiodes.

[0176] In some demonstrative aspects, the light receiver **130** may include a light receiver Silicon Integrated Circuit (SIC) **130**, which may be configured to harvest the energy of the light beam **103**, e.g., as described below.

[0177] In some demonstrative aspects, the light receiver SIC **130** may include the plurality of photodiodes **132**, e.g., as described below.

[0178] In some demonstrative aspects, the plurality of photodiodes **132** may be implemented on a same silicon chip, e.g., on the light receiver SIC **130**.

[0179] In some demonstrative aspects, the plurality of photodiodes **132** may be configured, for example, to have substantially a similar or same design and/or functionality of photovoltaic diodes.

[0180] In some demonstrative aspects, a width of the light receiver SIC **130** may be based, for example, on a two-sigma intensity distribution of the light beam **103**, e.g., as described below.

[0181] In other aspects, light receiver SIC **130** may have any other dimensions, which may be based on any other additional and/or alternative, parameter, criterion, and/or attribute of the light beam **103**.

[0182] In some demonstrative aspects, light receiver SIC **130** may include a quadrant light receiver SIC, for example, including four photodiodes **132**, e.g., as described below.

[0183] In some demonstrative aspects, the four photodiodes **132** may be arranged in a 2×2 matrix, e.g., as described below.

[0184] In other aspects, light receiver SIC **130** may include any other count of photodiodes **132**, which may be arranged in any other geometrical arrangement.

[0185] In some demonstrative aspects, aerial vehicle **102** may include a radiator **136**, which may be attached to the plurality of photodiodes **132**, e.g., as described below.

[0186] In one example, radiator **136** may be attached to the plurality of photodiodes **132**, for example, to provide a technical solution to cool the light receiver SIC **130**, e.g., as described below.

[0187] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be coated with an Anti-Reflective Coating (ARC), e.g., as described below.

[0188] In other aspects, at least one photodiode **132**, e.g., one, some, or all, of the plurality of photo diodes **132**, may be coated with any other additional and/or alternative type of coating.

[0189] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may include a Float Zone Silicon photodiode, e.g., as described below.

[0190] In one example, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132** may include a Float Zone Silicon photodiode coated with ARC.

[0191] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may include a black-silicon patterned surface photodiode, e.g., as described below.

[0192] In one example, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132** may include a Float Zone Silicon photodiode including a black-silicon patterned surface, for example, to provide a technical solution to reduce, e.g., minimize, light reflections from the photodiode **132**.

[0193] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the

plurality of photo diodes **132**, may include a P-type plus (P+)–N-type minus (N—) (P+–N–) photodiode, e.g., as described below.

[0194] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may include an N-type plus (N+) P-type minus (P–) (N+–P–) photodiode, e.g., as described below.

[0195] In other aspects, at least one photodiode **132**, e.g., one, some, or all, of the plurality of photo diodes **132**, may include any other type of photodiode.

[0196] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be configured to provide a Quantum Efficiency (QE) of at least 45 percent, e.g., as described below.

[0197] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be configured to provide a QE of at least 60 percent, e.g., as described below.

[0198] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be configured to provide a QE of at least 70 percent, e.g., as described below.

[0199] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be configured to provide a QE of at least 73 percent, e.g., as described below.

[0200] In some demonstrative aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be configured to provide a QE of at least 75 percent, e.g., as described below.

[0201] In other aspects, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be configured to provide any other QE.

[0202] In some demonstrative aspects, the plurality of photodiodes **132** may be fabricated, for example, on a high resistivity silicon, e.g., having a resistivity of about 10 kilo ohms per centimeter ($k\Omega \cdot \text{cm}$).

[0203] For example, the plurality of photodiodes **132** may be configured to provide a relatively high QE, for example, a QE of about 48%, e.g., based on testing of the plurality of photodiodes **132** with IR light.

[0204] In some demonstrative aspects, one or more silicon interface modifications may be implemented, for example, to enhance the QE of one or more of the plurality of photodiodes **132**, e.g., to a QE of about 75% or more.

[0205] In some demonstrative aspects, the plurality of photodiodes **132** may be configured to provide a technical solution to support efficient energy harvesting of the energy of the light beam **103**, for example, to charge the battery **105**.

[0206] In one example, at least one photodiode **132**, e.g., one, some or all, of the plurality of photo diodes **132**, may be configured to provide a QE of at least 45 percent, for example, for light of at least a wavelength, denoted λ , of about 1.06 μm , e.g., $\lambda=1060$ nanometer [nm].

[0207] In one example, the at least one photodiode **132** may be configured to provide the QE of at least 45 percent, for example, for light transmitted by a light transmitter, e.g., light transmitter **106**, with at least a power density, denoted P, of about 763 Watt (W) per square meter (m^2), e.g.,

$$[00001] P_{\text{LED, measured}} = 763.9 \left[\frac{\text{W}}{\text{m}^2} \right].$$

[0208] In one example, the at least one photodiode **132** may be configured to provide the QE of at least 45 percent, for example, based on a photodiode effective area, denoted A.sub.eff, of about 6 square millimeters, e.g., A.sub.eff=6 [mm^2].

[0209] In one example, the effective area A.sub.eff of a photodiode, e.g., a photodiode **132**, may be defined, for example, based on an area of the photodiode, which is not covered by metal. For example, the effective area A.sub.eff may include an open area, e.g., of light receiver **130**, which enables incident light of light beam **130** to reach to the silicon of light receiver **130**.

[0210] In one example, the at least one photodiode **132** may be configured to provide the QE of at least 45 percent, for example, with a photocurrent, denoted I, of about 1.88 milli-Ampere (mA) at a zero voltage, e.g., $I (@ V_p=0 [V])=1.88 \text{ mA}$.

[0211] In one example, the at least one photodiode **132** may be configured to provide the QE of at least 45 percent, for example, with a current density, denoted J, of about 312 ampere per meter squared, e.g.,

$$[00002] J = 312 \left[\frac{A}{m^2} \right].$$

[0212] For example, the current density J may be based on a quotient of division of the photocurrent I of the photodiode **132** at the zero voltage, divided by the effective area A.sub.eff of the photodiode **132**.

[0213] For example, the QE, denoted QE.sub.λ, of the photodiode **132** for the light beam having the wavelength λ of about 1.06 micrometer may be determined, e.g., as follows:

$$[00003] QE = \frac{R}{\text{Math. } \frac{hc}{e}} \cong \frac{R}{([W \cdot \text{Math. } \frac{nm}{A}])} = 47.7\%$$

wherein

$$[00004] R = \frac{J \left[\frac{A}{m^2} \right]}{P \left[\frac{W}{m^2} \right]} = 0.408 \left[\frac{A}{W} \right],$$

h denotes the Planck constant, c denotes the speed of light in vacuum, and e denotes the elementary charge.

[0214] In some demonstrative aspects, processor **122** may be configured to utilize signal information of current signals from the energy harvesting chip of aerial vehicle **102**, e.g., the photodiode signal information **133** corresponding to the plurality of currents **134**, for example, to determine the vehicle-position displacement **123** of the aerial vehicle **102**, e.g., as described above.

[0215] In some demonstrative aspects, processor **122** may be configured to utilize the signal information of current signals from the energy harvesting chip of aerial vehicle **102**, for example, to determine the vehicle-position displacement **123** of the aerial vehicle **102**, for example, with respect to an actual position of the aerial vehicle **102**, and/or an intensity of the light beam **103**, e.g., as described above.

[0216] In some demonstrative aspects, aerial vehicle **102** may be configured to provide a technical solution to support efficient charging of battery **105**, for example, by taking advantage of efficient photo conversion properties of light receiver **130**. For example, light receiver **130** may be configured to provide efficient photo conversion, for example, at least with respect to light beam **103** having a wavelength of about 1.06 μm, and the plurality of photodiodes **132**, which may be built on a Float Zone silicon having a high resistivity silicon, e.g., of 10 kΩ*cm, as described above.

[0217] For example, a photodiode **132**, e.g., each photodiode **132**, of the plurality of photo diodes **132**, may be configured to provide a QE, which may exceed about ~75%, e.g., with ARC, and/or a QE, which may exceed about 49%, e.g., without ARC.

[0218] In some demonstrative aspects, aerial vehicle **102** may be configured to provide a technical solution to support dual-utilization of the plurality of electric currents **134** from the plurality of photodiodes **132**, e.g., as described above.

[0219] In some demonstrative aspects, aerial vehicle **102** may be configured to utilize the plurality of electric currents **134** from the plurality of photodiodes **132**, for example, for energy harvesting, e.g., to charge the battery **105**.

[0220] In some demonstrative aspects, aerial vehicle **102** may be configured to utilize the plurality of electric currents **134** from the plurality of photodiodes **132**, for example, to position and/or displace the aerial device **102**, e.g., for adjusting the photodiode-beam relative position, for example, while utilizing the plurality of electric currents for energy harvesting, e.g., to charge the battery **105**.

[0221] In some demonstrative aspects, processor **122** may be configured to analyze the photodiode signal information **133** corresponding to the plurality of photodiodes **132**, for example, in order to

generate the position displacement information **125**, which may be configured, for example, to include movement commands to for controller **140** to control the one or more flight-control components **142**, e.g., drone motors and/or the like, as described above.

[0222] In some demonstrative aspects, processor **122** may be configured to generate the position displacement information **125** to include movement commands to the controller **140**, for example, to cause the one or more flight-control components **142** to adjust the photodiode-beam relative position of the plurality of photodiodes **132** relative to the light beam **132**, for example, based on one or more considerations, e.g., as described above.

[0223] In some demonstrative aspects, processor **122** may be configured to generate the position displacement information **125** to include the movement commands to adjust the photodiode-beam relative position of the plurality of photodiodes **132** relative to the light beam **132**, for example, according to a target charging current, e.g., as described above.

[0224] In one example, the target charging current may be configured, for example, to support a fast charging of the battery **105**, e.g., as described above.

[0225] In another example, the target charging current may be configured, for example, to support an adapted charging profile. In one example, the adapted charging profile may be configured to focus on battery life saving, and/or on any other additional or alternative criteria and/or target.

[0226] In some demonstrative aspects, processor **122** may be configured to generate the position displacement information **125** to include the movement commands to position aerial device **102** at a predefined charging location to charge the battery **105**, for example, based on a determination that a battery level of battery **105** is below a predefined threshold.

[0227] In one example, the predefined charging location may be associated with a light transmitter, for example, from a plurality of light transmitters in a plurality of light transmission stations.

[0228] In one example, aerial vehicle **102** may be configured to communicate, for example, with one or more light transmission stations, for example, to determine a predefined charging location corresponding to a selected light transmission station.

[0229] In one example, aerial vehicle **102** may be configured to navigate to the predefined charging location, for example, using a navigation system of the aerial vehicle **10**.

[0230] In some demonstrative aspects, light transmitter **106** may be configured, for example, to start emitting the light beam **103** for use by aerial device **102**, for example, based on an indication from aerial vehicle **102** and/or based on any other indication and/or determination, that the aerial vehicle **102** is at the predefined charging location corresponding to the light transmitter **106**.

[0231] In some demonstrative aspects, light transmitter **106** may be configured, for example, to stop emitting the light beam **103** for use by aerial device **102**, for example, based on an indication from aerial vehicle **102** and/or based on any other indication and/or determination, that the aerial vehicle **102** is charged and/or has left the predefined charging location.

[0232] Reference is made to FIG. 2, which schematically illustrates components of an aerial vehicle **202**, in accordance with some demonstrative aspects. For example, aerial vehicle **102** (FIG. 1) may include one or more of the components of aerial vehicle **202**, and/or may perform one or more operations and/or functionalities of the components of aerial vehicle **202**.

[0233] In some demonstrative aspects, as shown in FIG. 2, aerial vehicle **202** may include a controller (“Drone Processor”) **240**, which may be configured to control movement of the aerial vehicle **202**.

[0234] In some demonstrative aspects, as shown in FIG. 2, aerial vehicle **202** may include a battery **205**.

[0235] In some demonstrative aspects, as shown in FIG. 2, aerial vehicle **202** may include a light receiver **230**, which may be configured to harvest energy of a light beam **203**, for example, to charge the battery **205**, e.g., as described below.

[0236] In some demonstrative aspects, as shown in FIG. 2, light receiver **230** may include a quadrant light receiver **230** including four photodiodes **232**, which may be arranged in a 2×2

matrix, e.g., as a quadrant array.

[0237] In other aspects, light receiver **230** may include any other number of photodiodes **232**, which may be arranged in any other suitable geometrical arrangement.

[0238] In some demonstrative aspects, as shown in FIG. 2, the four photodiodes **232** may include a first photodiode, denoted Upper Left (UL), a second first photodiode, denoted Lower Left (LL), a third photodiode, denoted Upper Right (UR), and/or a fourth photodiode, denoted Lower Right (LR).

[0239] In some demonstrative aspects, as shown in FIG. 2, the four photodiodes **232** may generate a plurality of electric currents **234**, for example, by harvesting the energy of the light beam **203**.

[0240] In some demonstrative aspects, as shown in FIG. 2, light receiver **230** may be configured to charge the battery **205**, for example, based on the plurality of electric currents **234**.

[0241] In some demonstrative aspects, as shown in FIG. 2, aerial vehicle **202** may include a processor **222**, which may be configured to process photodiode signal information corresponding to the plurality of electric currents **234**.

[0242] In one example, the photodiode signal information may include a plurality of current magnitudes of the plurality of electric currents **234**.

[0243] In other aspects, the photodiode signal information may include any other additional or alternative information corresponding to the plurality of electric currents **234**.

[0244] In some demonstrative aspects, processor **222** may be configured to determine a vehicle-position displacement, e.g., vehicle-position displacement **123** (FIG. 1), for example, to displace the aerial vehicle **202**, for example, based on the plurality of electric currents **234**, e.g., as described below.

[0245] In some demonstrative aspects, the vehicle-position displacement may be configured to adjust a photodiode-beam relative position of the plurality of photodiodes **232** relative to the light beam **203**.

[0246] In one example, the photodiode-beam relative position of the plurality of photodiodes **232** relative to the light beam **203** may be determined, for example, according to a relative position **235** between a center of the light beam **203** and a center **231** of light receiver **230**.

[0247] In other aspects, the photodiode-beam relative position may be determined according to any other definition of the relative position of the plurality of photodiodes **232** relative to the light beam **203**.

[0248] In some demonstrative aspects, processor **222** may be configured to provide to the drone processor **240** movement information (signal) **266**, which may be based on the vehicle-position displacement. For example, movement information (signal) **266** may include position displacement information **125** (FIG. 1), e.g., as described above.

[0249] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on a mapping between the plurality of electric currents **234** and a plurality of photodiode positions of the plurality of photodiodes **232** in the 2×2 matrix, e.g., as described below.

[0250] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on a comparison between magnitudes of the plurality of electric currents **234**, e.g., as described below.

[0251] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on the arrangement of the plurality of photodiodes **232** in the 2×2 matrix, e.g., as described below.

[0252] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on a distribution of the magnitudes of the plurality of electric currents **234**, for example, with respect to the arrangement of the plurality of photodiodes **232** in the 2×2 matrix.

[0253] In one example, processor **222** may be configured to determine the vehicle-position

displacement to displace the aerial vehicle **202** towards a left direction **212**, for example, based on a determination that the distribution of the magnitudes of the plurality of electric currents **234** indicates that the light beam **203** is located left to the center **231** of the light receiver **230**.

[0254] In another example, processor **222** may be configured to determine the vehicle-position displacement to displace the aerial vehicle **202** towards a right direction **214**, for example, based on a determination that the distribution of the magnitudes of the plurality of electric currents **234** indicates that the light beam is located right to the center **231** of the light receiver **230**.

[0255] In one example, processor **222** may be configured to determine the vehicle-position displacement to displace the aerial vehicle **202** towards an up direction **262**, for example, based on a determination that the distribution of the magnitudes of the plurality of electric currents **234** indicates that the light beam **203** is located above the center **231** of the light receiver **230**.

[0256] In one example, processor **222** may be configured to determine the vehicle-position displacement to displace the aerial vehicle **202** towards a down direction **264**, for example, based on a determination that the distribution of the magnitudes of the plurality of electric currents **234** indicates that the light beam **203** is located below the center **231** of the light receiver **230**.

[0257] In another example, processor **222** may be configured to determine that the aerial vehicle **202** is not to be displaced, for example, based on a determination that the distribution of the magnitudes of the plurality of electric currents **234** includes a substantially equal distribution. For example, the distribution of the magnitudes of the plurality of electric currents **234** may indicate that the light beam substantially equally illuminates the plurality of photodiodes **232**, and accordingly, a total current from the plurality of photodiodes **232** may be maximized.

[0258] In another example, in some use cases and/or scenarios, processor **222** may be configured to determine that the aerial vehicle **202** is to be displaced, for example, based on the determination that the distribution of the magnitudes of the plurality of electric currents **234** includes a substantially equal distribution.

[0259] For example, processor **222** may be configured to determine that the aerial vehicle **202** is to be displaced by a displacement, which may include a vertical displacement and may substantially maintain the equal distribution of the magnitudes of the plurality of electric currents **234**.

[0260] In one example, processor **222** may be configured to determine that the aerial vehicle **202** is to be displaced by a displacement, which may include a vertical displacement downward and may substantially maintain the equal distribution of the magnitudes of the plurality of electric currents **234**, for example, based on a determination that the total current from the plurality of photodiodes **232** is to be increased, e.g., when the total current from the plurality of photodiodes **232** is determined to be less than a target current.

[0261] In one example, processor **222** may be configured to determine that the aerial vehicle **202** is to be displaced by a displacement, which may include a vertical displacement upward and may substantially maintain the equal distribution of the magnitudes of the plurality of electric currents **234**, for example, based on a determination that the total current from the plurality of photodiodes **232** is to be reduced, e.g., when the total current from the plurality of photodiodes **232** is determined to be higher than a target current.

[0262] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on a comparison between magnitudes of two or more of the plurality of electric currents **234**, e.g., as described below.

[0263] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on a difference between a first electric current magnitude mapped to a first photodiode position, e.g., of the first photodiode UL, and a second electric current magnitude mapped to a second photodiode location, e.g., of the second photodiode UR.

[0264] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on the difference between the first and second electric

current magnitudes, and, for example, based on a displacement between the first photodiode position and the second photodiode position in the 2×2 matrix, e.g., as described below.

[0265] In some demonstrative aspects, processor **222** may be configured to determine a direction of the vehicle-position displacement **223**, for example, based on the displacement between the first photodiode position and the second photodiode position in the 2×2 matrix, e.g., as described below.

[0266] In some demonstrative aspects, processor **222** may be configured to determine the direction of the vehicle-position displacement, for example, based on sign of the difference between the first electric current magnitude of the first photodiode UL and the second electric current magnitude of the second photodiode UR, e.g., as described below.

[0267] In one example, processor **222** may be configured to determine that the vehicle-position displacement is to be in the left direction **212**, for example, based on a determination that the sign of the difference between the first electric current magnitude of the first photodiode UL and the second electric current magnitude of the second photodiode UR is positive. For example, processor **222** may determine that the sign of the difference between the first and second electric current magnitudes is positive, for example, when the first electric current magnitude of the first photodiode UL is greater than the second electric current magnitude of the second photodiode UR.

[0268] In another one example, processor **222** may be configured to determine that the vehicle-position displacement is to in right direction **214**, for example, based on a determination that the sign of the difference between the first electric current magnitude of the first photodiode UL and the second electric current magnitude of the second photodiode UR is negative. For example, processor **222** may determine that the sign of the difference between the first and second electric current magnitudes is negative, for example, when the first electric current magnitude of the first photodiode UL is less than the second electric current magnitude of the second photodiode UR.

[0269] In some demonstrative aspects, processor **222** may be configured to determine a magnitude of the vehicle-position displacement, for example, based on the difference between the first electric current magnitude of the first photodiode UL and the second electric current magnitude of the second photodiode UR, e.g., as described below.

[0270] For example, processor **222** may be configured to determine a first magnitude of the vehicle-position displacement in the left direction **212**, for example, based on a determination of a first difference between the first electric current magnitude of the first photodiode UL and the second electric current magnitude of the second photodiode UR.

[0271] For example, processor **222** may be configured to determine a second magnitude of the vehicle-position displacement in the left direction **212**, for example, based on a determination of a second difference between the first electric current magnitude of the first photodiode UL and the second electric current magnitude of the second photodiode UR.

[0272] For example, processor **222** may be configured to determine the first magnitude of the vehicle-position displacement in the left direction **212**, which may be greater, for example, than the second magnitude of the vehicle-position displacement in the left direction **212**, for example, in case when the first difference between the first and second electric current magnitudes is greater than the second difference between the first and second electric current magnitudes.

[0273] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, based on a comparison between a target charging current of the battery **205** and a total current of the plurality of electric currents **234**, e.g., as described below.

[0274] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement to adjust the photodiode-beam relative position, for example, such that the light beam **203** may be substantially aligned to the center **231** of light receiver **230**.

[0275] For example, processor **222** may be configured to determine the vehicle-position displacement to adjust the photodiode-beam relative position such that the position of the light beam **203** may be substantially at the center **231**, for example, to equally illuminate the plurality of photodiodes **232**.

[0276] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement to substantially align the light beam **203** to the center **231** of light receiver **230**, for example, based on a determination that the target charging current includes a maximal current.

[0277] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement, for example, to increase or to reduce the total current of the plurality of electric currents **234**, for example, based on a target charging current according to a charging profile to charge the battery **205**. For example, the target charging current may be based on an SOC of battery **205**, e.g., as described below.

[0278] In some demonstrative aspects, processor **222** may be configured to determine the vehicle-position displacement to adjust the relative position **235**, for example, such that the light beam **203** may not be at the center **231** of the light receiver **230**, for example, based on a determination that the target current is lower than the total current of the plurality of electric currents **234**.

[0279] For example, the charging profile of battery **205** may define that at a high SoC of the battery **205**, e.g., above 90 percent, the target current may be less than the maximal current, e.g., 50 percent below the maximal current, or any other percentage of the maximal current.

[0280] Reference is made to FIG. **3**, which schematically illustrates a method of determining a vehicle position displacement to displace an aerial vehicle, in accordance with some demonstrative aspects. For example, one or more of the operations of the method of FIG. **3** may be performed by an aerial vehicle, e.g., aerial vehicle **102** (FIG. **1**), and/or aerial vehicle **202** (FIG. **1**); and/or a processor, e.g., data processor **120** (FIG. **1**), processor **122** (FIG. **11**), and/or processor **222** (FIG. **2**).

[0281] As indicated at block **302**, the method may include comparing between current magnitudes of two or more electric currents of two or more photodiodes of the aerial vehicle. For example, processor **222** (FIG. **2**) may be configured to compare between current magnitudes of the UL, UR, LR and LL photodiodes, e.g., as described above.

[0282] As indicated at block **304**, comparing between the current magnitudes of the two or more electric currents of the two or more photodiodes may include determining whether the current magnitudes, e.g., the total current magnitude, of electric current from the UL and UR photodiodes, are lower than the current magnitudes, e.g., the total current magnitude, of electric current from the LL and LR photodiodes. For example, processor **222** (FIG. **2**) may be configured to determine whether the total current magnitude of electric current from the UL and UR photodiodes **232** (FIG. **2**) is lower than the total current magnitude of electric current from the LL and LR photodiodes **232** (FIG. **2**), e.g., as described above.

[0283] As indicated at block **306**, comparing between the current magnitudes of the two or more electric currents of the two or more photodiodes may include determining whether the current magnitudes, e.g., the total current magnitude, of electric current from the LL and LR photodiodes, are lower than the current magnitudes, e.g., the total current magnitude, of electric current from the UL and UR photodiodes. For example, processor **222** (FIG. **2**) may be configured to determine whether the total current magnitude of electric current from the LL and LR photodiodes **232** (FIG. **2**) is lower than the total current magnitude of electric current from the UL and UR photodiodes **232** (FIG. **2**), e.g., as described above.

[0284] As indicated at block **308**, the method may include determining a vehicle position displacement to displace the aerial vehicle based on a comparison between the current magnitudes of the two or more electric currents of the two or more photodiodes. For example, processor **222** (FIG. **2**) may be configured to determine the vehicle position displacement to displace the aerial vehicle **202** (FIG. **2**), for example, based on the comparison between the current magnitudes of the two or more electric currents **234** (FIG. **2**) of the two or more photodiodes **232** (FIG. **2**), e.g., as described above.

[0285] As indicated at block **310**, determining the vehicle position displacement to displace the

aerial vehicle may include determining the vehicle position displacement to move the aerial vehicle in a direction towards positions of the UL and UR photodiodes, for example, based on a determination that the current magnitudes of electric current from the UL and UR photodiodes are lower than the current magnitudes of electric current from the LL and LR photodiodes. For example, processor **222** (FIG. **2**) may be configured to determine the vehicle position displacement to move the aerial vehicle **202** (FIG. **2**) in a direction towards positions of the UL and UR photodiodes **232** (FIG. **2**), for example, based on a determination that the total current magnitude of electric current from the UL and UR photodiodes **232** (FIG. **2**) is lower than the current magnitudes of electric current from the LL and LR photodiodes **232** (FIG. **2**), e.g., as described above.

[0286] As indicated at block **312**, determining the vehicle position displacement to displace the aerial vehicle may include determining the vehicle position displacement to move the aerial vehicle in a direction towards positions of the LL and LR photodiodes based on a determination that the current magnitudes of electric current from the LL and LR photodiodes are lower than the current magnitudes of electric current from the UL and UR photodiodes. For example, processor **222** (FIG. **2**) may be configured to determine the vehicle position displacement to move the aerial vehicle **202** (FIG. **2**) in a direction towards positions of the LL and LR photodiodes **232** (FIG. **2**), for example, based on a determination that the total current magnitudes of electric current from the LL and LR photodiodes **232** (FIG. **2**) is lower than the total current magnitudes of electric current from the UL and UR photodiodes **232** (FIG. **2**), e.g., as described above.

[0287] As indicated at block **314**, the method may include determining a vehicle position displacement to displace an aerial vehicle based on a distribution of the current magnitudes of the two or more electric currents of the two or more photodiodes. For example, processor **222** (FIG. **2**) may be configured to determine the vehicle position displacement to displace the aerial vehicle **202** (FIG. **2**), for example, based the distribution of the current magnitudes of the two or more electric currents **234** (FIG. **2**) of the two or more photodiodes **232** (FIG. **2**), e.g., as described above.

[0288] As indicated at block **316**, determining the vehicle position displacement to displace an aerial vehicle based the distribution of the current magnitudes may include determining whether or not the plurality of electric currents of the plurality of photodiodes are equally distributed. For example, processor **222** (FIG. **2**) may be configured to determine whether or not the current magnitudes of the plurality of electric currents **234** (FIG. **2**) of the plurality of photodiodes **232** (FIG. **2**) are equally distributed between the plurality of photodiodes **232** (FIG. **2**), e.g., as described above.

[0289] As indicated at block **318**, determining the vehicle position displacement to displace an aerial vehicle based the distribution of the current magnitudes may include maintaining a position of the aerial vehicle, for example, based on a determination that the plurality of electric currents of the plurality of photodiodes are substantially equally distributed. For example, processor **222** (FIG. **2**) may be configured to maintain a position of the aerial vehicle **202** (FIG. **2**), for example, based on the determination that the current magnitudes of the plurality of electric currents **234** (FIG. **2**) of the plurality of photodiodes **232** (FIG. **2**) are substantially equally distributed between the plurality of photodiodes **232** (FIG. **2**). For example, the current magnitudes of the plurality of electric currents **234** (FIG. **2**) of the plurality of photodiodes **232** (FIG. **2**) may be equally distributed between the plurality of photodiodes **232** (FIG. **2**), for example, when the beam **203** (FIG. **2**) is substantially at the center **231** (FIG. **2**) of the light receiver **230** (FIG. **2**), e.g., as described above.

[0290] For example, processor **222** (FIG. **2**) may be configured to maintain the position of the aerial vehicle **202** (FIG. **2**), for example, based on the determination that the current magnitudes of the plurality of electric currents **234** (FIG. **2**) of the plurality of photodiodes **232** (FIG. **2**) are substantially equally distributed between the plurality of photodiodes **232** (FIG. **2**), and based, for example, on a determination that the target charging current of the battery **205** (FIG. **2**) is the maximum current, e.g., as described above.

[0291] Reference is made to FIG. **4**, which schematically illustrates a graph **400** depicting output

currents of a photodiode, in accordance with some demonstrative aspects.

[0292] For example, graph **400** may represent output currents of a photodiode **232** (FIG. 2).

[0293] In some demonstrative aspects, as shown in FIG. 4, a first curve **402** may represent a first output current of the photodiode, which may be generated, for example, when the photodiode is not subject to emission from a light beam, e.g., in a dark scenario.

[0294] In some demonstrative aspects, as shown in FIG. 4, a second curve **404** may represent a second output current of the photodiode, for example, which may be generated based on a light beam, e.g., light beam **103** (FIG. 1), having a wavelength of 1.06 μm .

[0295] In some demonstrative aspects, as shown in FIG. 4, the photodiode subject to the light beam having the wavelength of 1.06 micrometer may provide an output current in the order of milliwatts.

[0296] Reference is made to FIG. 5, which schematically illustrates an aerial vehicle **502**, in accordance with some demonstrative aspects. For example, aerial vehicle **102** (FIG. 1) may include one or more elements of aerial vehicle **502**, and/or may perform one or more operations of aerial vehicle **502**.

[0297] In some demonstrative aspects, as shown in FIG. 5, aerial vehicle **502** may include a quadcopter, or a drone.

[0298] In some demonstrative aspects, aerial vehicle **502** may include a controller (“Drone Processor”), which may be configured to control movement of the aerial vehicle **502**.

[0299] In some demonstrative aspects, as shown in FIG. 5, aerial vehicle **502** may include a battery **505**.

[0300] In some demonstrative aspects, (FIG. 1) aerial vehicle **502** may include a light receiver **530**, which may be configured to harvest energy of a light beam **503**, for example, to charge the battery **505**.

[0301] In some demonstrative aspects, as shown in FIG. 5, aerial vehicle **502** may include a processor **522**. For example, processor **522** may include one or more elements of processor **120** (FIG. 1) and/or may perform one or more operations of processor **120** (FIG. 1).

[0302] In some demonstrative aspects, processor **522** may be configured to determine a vehicle-position displacement, for example, to displace the aerial vehicle **502**, for example, based on a plurality of electric currents from light receiver **530**, e.g., as described above.

[0303] In some demonstrative aspects, processor **522** may be configured to provide position displacement information, which may be configured to request, instruct, trigger, cause, and/or control the drone processor to displace the aerial vehicle **502** according to the vehicle-position displacement, e.g., as described above.

[0304] Reference is made to FIG. 6, which schematically illustrates a method of charging a battery of an aerial vehicle, in accordance with some demonstrative aspects. For example, one or more of the operations of the method of FIG. 6 may be performed by an aerial vehicle, e.g., aerial vehicle **102** (FIG. 1), aerial vehicle **202** (FIG. 2), and/or aerial vehicle **502** (FIG. 5); and/or a processor, e.g., data processor **120** (FIG. 1), processor **122** (FIG. 11), and/or processor **222** (FIG. 2).

[0305] As indicated at block **602**, the method may include processing photodiode signal information, which corresponds to a plurality of photodiodes of an aerial vehicle, to identify a plurality of electric currents, which are generated by the plurality of photodiodes based on energy of a light beam to charge a battery of the aerial vehicle. For example, processor **122** (FIG. 1) may be configured to process the photodiode signal information **133** (FIG. 1), which may correspond to the plurality of photodiodes **132** (FIG. 1) of aerial vehicle **102** (FIG. 1), for example, to identify the plurality of electric currents **134** (FIG. 1), which may be generated by the plurality of photodiodes **132** (FIG. 1), for example, based on the energy of the light beam **103** (FIG. 1) to charge the battery **105** (FIG. 1) of the aerial vehicle **102** (FIG. 2), e.g., as described above.

[0306] As indicated at block **604**, the method may include determining a vehicle-position displacement to displace the aerial vehicle, for example, based on the plurality of electric currents. For example, the vehicle-position displacement may be configured to adjust a photodiode-beam

relative position of the plurality of photodiodes relative to the light beam. For example, processor **122** (FIG. **1**) may be configured to determine the vehicle-position displacement **123** (FIG. **1**) to displace the aerial vehicle **102** (FIG. **1**), for example, based on the plurality of electric currents **134** (FIG. **1**), e.g., as described above.

[0307] As indicated at block **606**, the method may include providing position displacement information based on the vehicle-position displacement. For example, processor **122** (FIG. **1**) may be configured to cause output **126** (FIG. **1**) to provide the position displacement information **125** (FIG. **1**), e.g., to controller **140** (FIG. **1**), for example, based on the vehicle-position displacement **123** (FIG. **1**), e.g., as described above.

[0308] Reference is made to FIG. **7**, which schematically illustrates a product of manufacture **700**, in accordance with some demonstrative aspects. Product **700** may include one or more tangible computer-readable (“machine-readable”) non-transitory storage media **702**, which may include computer-executable instructions, e.g., implemented by logic **704**, operable to, when executed by at least one computer processor, enable the at least one computer processor to implement one or more operations and/or functionalities described with reference to any of the FIGS. **1-6**, and/or one or more operations described herein. The phrases “non-transitory machine-readable medium” and “computer-readable non-transitory storage media” may be directed to include all machine and/or computer readable media, with the sole exception being a transitory propagating signal.

[0309] In some demonstrative aspects, product **700** and/or machine-readable storage media **702** may include one or more types of computer-readable storage media capable of storing data, including volatile memory, non-volatile memory, removable or non-removable memory, erasable or non-erasable memory, writeable or re-writeable memory, and the like. For example, machine-readable storage media **702** may include, RAM, DRAM, Double-Data-Rate DRAM (DDR-DRAM), SDRAM, static RAM (SRAM), ROM, programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), flash memory (e.g., NOR or NAND flash memory), content addressable memory (CAM), polymer memory, phase-change memory, ferroelectric memory, silicon-oxide-nitride-oxide-silicon (SONOS) memory, a disk, a hard drive, and the like. The computer-readable storage media may include any suitable media involved with downloading or transferring a computer program from a remote computer to a requesting computer carried by data signals embodied in a carrier wave or other propagation medium through a communication link, e.g., a modem, radio, or network connection.

[0310] In some demonstrative aspects, logic **704** may include instructions, data, and/or code, which, if executed by a machine, may cause the machine to perform a method, process and/or operations as described herein. The machine may include, for example, any suitable processing platform, computing platform, computing device, processing device, computing system, processing system, computer, processor, or the like, and may be implemented using any suitable combination of hardware, software, firmware, and the like.

[0311] In some demonstrative aspects, logic **704** may include, or may be implemented as, software, a software module, an application, a program, a subroutine, instructions, an instruction set, computing code, words, values, symbols, and the like. The instructions may include any suitable type of code, such as source code, compiled code, interpreted code, executable code, static code, dynamic code, and the like. The instructions may be implemented according to a predefined computer language, manner, or syntax, for instructing a processor to perform a certain function. The instructions may be implemented using any suitable high-level, low-level, object-oriented, visual, compiled and/or interpreted programming language, machine code, and the like.

EXAMPLES

[0312] The following examples pertain to further aspects.

[0313] Example 1 includes an apparatus comprising a processor configured to process photodiode signal information, which corresponds to a plurality of photodiodes of an aerial vehicle, to identify

a plurality of electric currents, which are generated by the plurality of photodiodes based on energy of a light beam to charge a battery of the aerial vehicle; and determine a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents, the vehicle-position displacement to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam; and an output to provide position displacement information based on the vehicle-position displacement.

[0314] Example 2 includes the subject matter of Example 1, and optionally, wherein the processor is configured to determine the vehicle-position displacement based on a mapping between the plurality of electric currents and a plurality of photodiode positions of the plurality of photodiodes.

[0315] Example 3 includes the subject matter of Example 2, and optionally, wherein the processor is configured to determine the vehicle-position displacement based on a difference between a first electric current magnitude mapped to a first photodiode position and a second electric current magnitude mapped to a second photodiode location, and based on a displacement between the first photodiode position and the second photodiode position.

[0316] Example 4 includes the subject matter of Example 3, and optionally, wherein the processor is configured to determine a magnitude of the vehicle-position displacement based on the difference between the first electric current magnitude and the second electric current magnitude.

[0317] Example 5 includes the subject matter of Example 3 or 4, and optionally, wherein the processor is configured to determine a direction of the vehicle-position displacement based on the displacement between the first photodiode position and the second photodiode position.

[0318] Example 6 includes the subject matter of any one of Examples 3-5, and optionally, wherein the processor is configured to determine a direction of the vehicle-position displacement based on sign of the difference between the first electric current magnitude and the second electric current magnitude.

[0319] Example 7 includes the subject matter of any one of Examples 3-6, and optionally, wherein the processor is configured to determine a first vehicle-position displacement based on a first difference between the first electric current magnitude and the second electric current magnitude, and to determine a second vehicle-position displacement based on a second difference between the first electric current magnitude and the second electric current magnitude, wherein the first difference is different from the second difference, the second vehicle-position displacement is different from the first vehicle-position displacement.

[0320] Example 8 includes the subject matter of any one of Examples 2-7, and optionally, wherein the processor is configured to determine a photodiode-beam relative position adjustment to adjust the photodiode-beam relative position based on the mapping between the plurality of electric currents and the plurality of photodiode positions, and to determine the vehicle-position displacement based on the photodiode-beam relative position adjustment.

[0321] Example 9 includes the subject matter of any one of Examples 2-8, and optionally, wherein the processor is configured to determine the vehicle-position displacement based on a geometrical arrangement of the plurality of photodiode positions.

[0322] Example 10 includes the subject matter of any one of Examples 2-9, and optionally, wherein the processor is configured to determine the vehicle-position displacement based on a comparison between magnitudes of two or more of the plurality of electric currents.

[0323] Example 11 includes the subject matter of any one of Examples 2-10, and optionally, wherein the processor is configured to determine the vehicle-position displacement based on a distribution of magnitudes of the plurality of electric currents.

[0324] Example 12 includes the subject matter of any one of Examples 1-11, and optionally, wherein the processor is configured to determine a first vehicle-position displacement based on a first plurality of electric currents, and to determine a second vehicle-position displacement based on a second plurality of electric currents, wherein the second vehicle-position displacement is different from the first vehicle-position displacement, and the second plurality of electric currents is different

from the first plurality of electric currents.

[0325] Example 13 includes the subject matter of any one of Examples 1-12, and optionally, wherein the processor is configured to determine the vehicle-position displacement based on a comparison between a total current of the plurality of electric currents and a target charging current of the battery.

[0326] Example 14 includes the subject matter of Example 13, and optionally, wherein the processor is configured to determine the vehicle-position displacement to increase the total current of the plurality of electric currents based on a determination that the total current is lower than the target charging current.

[0327] Example 15 includes the subject matter of Example 13 or 14, and optionally, wherein the processor is configured to determine the vehicle-position displacement to reduce the total current of the plurality of electric currents based on a determination that the total current is higher than the target charging current.

[0328] Example 16 includes the subject matter of any one of Examples 13-15, and optionally, wherein the processor is configured to determine a first vehicle-position displacement based on a first target charging current, and to determine a second vehicle-position displacement based on a second target charging current, wherein the second vehicle-position displacement is different from the first vehicle-position displacement, and the second target charging current is different from the first target charging current.

[0329] Example 17 includes the subject matter of any one of Example 13-16, and optionally, wherein the processor is configured to determine the target charging current according to a charging profile to charge the battery based on a State Of Charge (SOC) of the battery.

[0330] Example 18 includes the subject matter of any one of Example 13-16, and optionally, wherein the target charging current comprises a maximal current.

[0331] Example 19 includes the subject matter of any one of Example 13-18, and optionally, wherein the processor is configured to, based on a determination that the target charging current comprises a maximal current, determine the vehicle-position displacement to adjust the photodiode-beam relative position such that the light beam substantially equally illuminates the plurality of photodiodes, based on a determination that the target charging current comprises a maximal current.

[0332] Example 20 includes the subject matter of any one of Examples 1-19, and optionally, wherein the photodiode signal information comprises a plurality of current magnitudes of the plurality of electric currents.

[0333] Example 21 includes the subject matter of any one of Examples 1-20, and optionally, wherein the position displacement information comprises the vehicle-position displacement.

[0334] Example 22 includes the subject matter of any one of Examples 1-21, and optionally, wherein the plurality of photodiodes comprises at least three photodiodes.

[0335] Example 23 includes the subject matter of any one of Examples 1-22, and optionally, wherein the plurality of photodiodes comprises at least four photodiodes.

[0336] Example 24 includes the subject matter of any one of Examples 1-23, and optionally, comprising the plurality of photodiodes.

[0337] Example 25 includes the subject matter of Example 24, and optionally, comprising a light receiver Silicon Integrated Circuit (SIC) configured to harvest the energy of the light beam, wherein the light receiver SIC comprises the plurality of photodiodes.

[0338] Example 26 includes the subject matter of Example 25, and optionally, wherein a width of the light receiver SIC is based on a two-sigma intensity distribution of the light beam.

[0339] Example 27 includes the subject matter of Example 25 or 26, and optionally, wherein the light receiver SIC comprises a quadrant light receiver SIC comprising four photodiodes arranged in a 2×2 matrix.

[0340] Example 28 includes the subject matter of any one of Examples 24-27, and optionally,

comprising a radiator attached to the plurality of photodiodes.

[0341] Example 29 includes the subject matter of any one of Examples 24-28, and optionally, wherein at least one photodiode of the plurality of photodiodes is configured to provide a Quantum Efficiency (QE) of at least 45 percent.

[0342] Example 30 includes the subject matter of any one of Examples 24-29, and optionally, wherein at least one photodiode of the plurality of photodiodes is configured to provide a Quantum Efficiency (QE) of at least 70 percent.

[0343] Example 31 includes the subject matter of any one of Examples 24-30, and optionally, wherein at least one photodiode of the plurality of photodiodes comprises a P-type plus (P+)–N-type minus (N–) (P+–N–) photodiode, or an N-type plus (N+) P-type minus (P–) (N+–P–) photodiode.

[0344] Example 32 includes the subject matter of any one of Examples 24-31, and optionally, wherein at least one photodiode of the plurality of photodiodes comprises a black-silicon patterned surface photodiode.

[0345] Example 33 includes the subject matter of any one of Examples 24-32, and optionally, wherein at least one photodiode of the plurality of photo diodes is coated with an Anti-Reflective Coating (ARC).

[0346] Example 34 includes the subject matter of any one of Examples 24-33, and optionally, wherein at least one photodiode of the plurality of photo diodes comprises a Float Zone Silicon photodiode.

[0347] Example 35 includes the subject matter of any one of Examples 1-34, and optionally, wherein the light beam comprises a Neodymium-Doped Yttrium Aluminum Garnet (ND:YAG) light beam.

[0348] Example 36 includes the subject matter of any one of Examples 1-35, and optionally, wherein a wavelength of the light beam is between 0.9 and 1.1 micrometer.

[0349] Example 37 includes the subject matter of any one of Examples 1-36, and optionally, wherein the light beam comprises a Near Infra-Red (NIR) light beam.

[0350] Example 38 includes the subject matter of any one of Examples 1-37, and optionally, comprising the aerial vehicle, the aerial vehicle comprising the battery, a movement controller, and a light receiver comprising the plurality of diodes, wherein the movement controller is configured to control movement of the aerial vehicle based on the position displacement information.

[0351] Example 39 includes the subject matter of any one of Examples 1-38, and optionally, wherein the aerial vehicle comprises a drone, a quadcopter, or an Unmanned Aerial Vehicle (UAV).

[0352] Example 40 includes an aerial vehicle comprising a battery; one or more flight controllers to control movement of the aerial vehicle; a light receiver comprising a plurality of photodiodes to generate a plurality of electric currents based on energy of a light beam to charge the battery; and a processor configured to process photodiode signal information, which corresponds to the plurality of photodiodes, to identify the plurality of electric currents, which are generated by the plurality of photodiodes based on the energy of the light beam; determine a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents, the vehicle-position displacement to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam; and provide position displacement information based on the vehicle-position displacement, the position displacement information to control displacement of the aerial vehicle by the one or more flight controllers.

[0353] Example 41 includes the aerial vehicle of Example 40, and optionally, including the subject matter of any of examples 1-39.

[0354] Example 42 includes a product comprising one or more tangible computer-readable non-transitory storage media comprising instructions operable to, when executed by at least one processor of an aerial vehicle, enable the at least one processor to process photodiode signal information, which corresponds to a plurality of photodiodes of the aerial vehicle, to identify a

plurality of electric currents, which are generated by the plurality of photodiodes based on energy of a light beam to charge a battery of the aerial vehicle; determine a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents, the vehicle-position displacement to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam; and provide position displacement information based on the vehicle-position displacement.

[0355] Example 43 includes the product of Example 42, and optionally, including the subject matter of any of examples 1-39.

[0356] Example 44 includes a method to be performed at an aerial vehicle, the method comprising processing photodiode signal information, which corresponds to a plurality of photodiodes of the aerial vehicle, to identify a plurality of electric currents, which are generated by the plurality of photodiodes based on energy of a light beam to charge a battery of the aerial vehicle; determining a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents, the vehicle-position displacement to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam; and providing position displacement information to control displacement of the aerial vehicle based on the vehicle-position displacement.

[0357] Example 45 includes the method of Example 44, and optionally, including the subject matter of any of examples 1-39.

[0358] Functions, operations, components and/or features described herein with reference to one or more aspects, may be combined with, or may be utilized in combination with, one or more other functions, operations, components and/or features described herein with reference to one or more other aspects, or vice versa.

[0359] While certain features have been illustrated and described herein, many modifications, substitutions, changes, and equivalents may occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

Claims

1. An apparatus comprising: a processor configured to: process photodiode signal information, which corresponds to a plurality of photodiodes of an aerial vehicle, to identify a plurality of electric currents, which are generated by the plurality of photodiodes based on energy of a light beam to charge a battery of the aerial vehicle; and determine a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents, the vehicle-position displacement to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam; and an output to provide position displacement information based on the vehicle-position displacement.
2. The apparatus of claim 1, wherein the processor is configured to determine the vehicle-position displacement based on a mapping between the plurality of electric currents and a plurality of photodiode positions of the plurality of photodiodes.
3. The apparatus of claim 2, wherein the processor is configured to determine the vehicle-position displacement based on a difference between a first electric current magnitude mapped to a first photodiode position and a second electric current magnitude mapped to a second photodiode location, and based on a displacement between the first photodiode position and the second photodiode position.
4. The apparatus of claim 3, wherein the processor is configured to determine a magnitude of the vehicle-position displacement based on the difference between the first electric current magnitude and the second electric current magnitude.
5. The apparatus of claim 3, wherein the processor is configured to determine a direction of the

vehicle-position displacement based on the displacement between the first photodiode position and the second photodiode position.

6. The apparatus of claim 3, wherein the processor is configured to determine a direction of the vehicle-position displacement based on sign of the difference between the first electric current magnitude and the second electric current magnitude.

7. The apparatus of claim 3, wherein the processor is configured to determine a first vehicle-position displacement based on a first difference between the first electric current magnitude and the second electric current magnitude, and to determine a second vehicle-position displacement based on a second difference between the first electric current magnitude and the second electric current magnitude, wherein the first difference is different from the second difference, the second vehicle-position displacement is different from the first vehicle-position displacement.

8. The apparatus of claim 2, wherein the processor is configured to determine a photodiode-beam relative position adjustment to adjust the photodiode-beam relative position based on the mapping between the plurality of electric currents and the plurality of photodiode positions, and to determine the vehicle-position displacement based on the photodiode-beam relative position adjustment.

9. The apparatus of claim 2, wherein the processor is configured to determine the vehicle-position displacement based on a geometrical arrangement of the plurality of photodiode positions.

10. The apparatus of claim 2, wherein the processor is configured to determine the vehicle-position displacement based on a comparison between magnitudes of two or more of the plurality of electric currents.

11. The apparatus of claim 2, wherein the processor is configured to determine the vehicle-position displacement based on a distribution of magnitudes of the plurality of electric currents.

12. The apparatus of claim 1, wherein the processor is configured to determine a first vehicle-position displacement based on a first plurality of electric currents, and to determine a second vehicle-position displacement based on a second plurality of electric currents, wherein the second vehicle-position displacement is different from the first vehicle-position displacement, and the second plurality of electric currents is different from the first plurality of electric currents.

13. The apparatus of claim 1, wherein the processor is configured to determine the vehicle-position displacement based on a comparison between a total current of the plurality of electric currents and a target charging current of the battery.

14. The apparatus of claim 13, wherein the processor is configured to determine the vehicle-position displacement to increase the total current of the plurality of electric currents based on a determination that the total current is lower than the target charging current.

15. The apparatus of claim 13, wherein the processor is configured to determine the vehicle-position displacement to reduce the total current of the plurality of electric currents based on a determination that the total current is higher than the target charging current.

16. The apparatus of claim 13, wherein the processor is configured to determine the target charging current according to a charging profile to charge the battery based on a State Of Charge (SOC) of the battery.

17. The apparatus of claim 13, wherein the processor is configured to, based on a determination that the target charging current comprises a maximal current, determine the vehicle-position displacement to adjust the photodiode-beam relative position such that the light beam substantially equally illuminates the plurality of photodiodes.

18. The apparatus of claim 1, wherein the plurality of photodiodes comprises at least three photodiodes.

19. The apparatus of claim 1 comprising the plurality of photodiodes.

20. The apparatus of claim 19 comprising a light receiver Silicon Integrated Circuit (SIC) configured to harvest the energy of the light beam, wherein the light receiver SIC comprises the plurality of photodiodes.

21. The apparatus of claim 19, wherein at least one photodiode of the plurality of photodiodes is

configured to provide a Quantum Efficiency (QE) of at least 45 percent.

22. An aerial vehicle comprising: a battery; one or more flight controllers to control movement of the aerial vehicle; a light receiver comprising a plurality of photodiodes to generate a plurality of electric currents based on energy of a light beam to charge the battery; and a processor configured to: process photodiode signal information, which corresponds to the plurality of photodiodes, to identify the plurality of electric currents, which are generated by the plurality of photodiodes based on the energy of the light beam; determine a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents, the vehicle-position displacement to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam; and provide position displacement information based on the vehicle-position displacement, the position displacement information to control displacement of the aerial vehicle by the one or more flight controllers.

23. The aerial vehicle of claim 22 comprising a drone, a quadcopter, or an Unmanned Aerial Vehicle (UAV).

24. A product comprising one or more tangible computer-readable non-transitory storage media comprising instructions operable to, when executed by at least one processor of an aerial vehicle, enable the at least one processor to: process photodiode signal information, which corresponds to a plurality of photodiodes of the aerial vehicle, to identify a plurality of electric currents, which are generated by the plurality of photodiodes based on energy of a light beam to charge a battery of the aerial vehicle; determine a vehicle-position displacement to displace the aerial vehicle based on the plurality of electric currents, the vehicle-position displacement to adjust a photodiode-beam relative position of the plurality of photodiodes relative to the light beam; and provide position displacement information based on the vehicle-position displacement.

25. The product of claim 24, wherein the instructions, when executed, cause the processor to determine the vehicle-position displacement based on a mapping between the plurality of electric currents and a plurality of photodiode positions of the plurality of photodiodes.
