

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283266

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

XIONG; Lining et al.

CLOTHING TREATMENT DEVICE

Abstract

A clothing treatment device is provided. The device includes a housing, a tub assembly, a first rod and a damping assembly. The damping assembly includes a first connection end and a second connection end. The first connection end is connected to the tub assembly, and the second connection end is connected to the first rod. At least one of the first connection end or the second connection end is provided with a through hole. In directions from axially opposite ends of the through hole to an middle position of the through hole along an axial direction thereof, a hole wall of the through hole extends toward an axis of the through hole.

Inventors: XIONG; Lining (WUXI, CN), SHI; Yacheng (WUXI, CN), WANG; Jia (WUXI, CN)

Applicant: WUXI LITTLE SWAN ELECTRIC CO., LTD. (WUXI, CN)

Family ID: 96931428

Assignee: WUXI LITTLE SWAN ELECTRIC CO., LTD. (WUXI, CN)

Appl. No.: 18/638993

Filed: April 18, 2024

Foreign Application Priority Data

CN

202410254055.9

Mar. 06, 2024

Publication Classification

Int. Cl.: D06F37/24 (20060101); D06F37/26 (20060101)

U.S. Cl.:

CPC D06F37/24 (20130101); D06F37/268 (20130101);

Background/Summary

FIELD

[0001] The disclosure relates to the field of clothing treatment, and in particular to a clothing treatment device.

BACKGROUND

[0002] A pulsator clothing treatment device is taken as an example, in case that an external size of a housing is unchanged, a gap between a tub assembly and the housing becomes smaller and smaller with the increase of a washing volume. During washing or spin-drying, the tub assembly may vibrate and deflect, and is prone to hitting the housing, which affects safety of the clothing treatment device during operation.

[0003] In order to reduce amplitude of the tub assembly, the clothing treatment device can be provided with a damper, an end of the damper is connected to the tub assembly, another end of the damper is connected to a suspender, the connection end of the damper rotates around a circumferential direction of the suspender or slides along the suspender, and when the tub assembly vibrates, the damper moves with the tub assembly to dissipate vibration energy. However, when the damper moves with vibration of the tub assembly, there is a high probability of sticking the damper, which affects damping effect and may even lead to damage of the damper.

SUMMARY

[0004] In view of this, it is desirable for embodiments of the disclosure to provide a clothing treatment device, in which a damping assembly has enough movement degree of freedom (DOF), high movement smoothness and high damping reliability.

[0005] An embodiment of the disclosure provides a clothing treatment device, and the clothing treatment device includes a housing, a tub assembly, a first rod, and a damping assembly.

[0006] The tub assembly is arranged in the housing.

[0007] The first rod is arranged out of the tub assembly.

[0008] The damping assembly includes a first connection end and a second connection end, the first connection end is connected to the tub assembly, and the second connection end is connected to the first rod.

[0009] At least one of the first connection end or the second connection end is provided with a through hole, and in directions from axially opposite ends of the through hole to an middle position of the through hole along an axial direction thereof, a hole wall of the through hole extends toward an axis of the through hole.

[0010] In some implementations, the through hole may be symmetrical with respect to a first plane, and the first plane is a plane perpendicular to the axis of the through hole and passing through the middle position of the through hole along the axial direction thereof.

[0011] In some implementations, in a longitudinal cross section passing through the axis of the through hole, at least a part of cross section of the hole wall of the through hole may be in a shape of an arc projecting toward the axis of the through hole.

[0012] In some implementations, at least a part of cross section of the hole wall of the through hole may be in a shape of a circular arc.

[0013] In some implementations, the damping assembly may include a first movement member, a second movement member and a friction member, the first movement member is connected to the second movement member, and the first movement member and the second movement member are relatively rotatable around their joint, the friction member is arranged at the rotation joint of the first movement member and the second movement member, to provide friction force to achieve damping when the first movement member and the second movement member rotate relatively, an end of the first movement member away from the friction member defines the first connection end,

and an end of the second movement member away from the friction member defines the second connection end.

[0014] In some implementations, an axis around which the first movement member and the second movement member rotate relatively may be substantially parallel to an axis of the tub assembly.

[0015] In some implementations, a first end of the first movement member may be connected to a first end of the second movement member, and when the tub assembly is in a stationary state, an angle between a line connecting centers of first and second ends of the first movement member and a line connecting centers of first and second ends of the second movement member is not less than 50° and not greater than 120° .

[0016] In some implementations, the clothing treatment device may include a second rod extending in a height direction and fixed to an outer circumferential side of the tub assembly, an end of the first movement member away from the friction member is sleeved on an outer circumference of the second rod, and the through hole is arranged at the second connection end.

[0017] In some implementations, the entire first movement member may be a rigid member and may have only one rotation DOF; and/or, the entire second movement member may be a rigid member.

[0018] In some implementations, the clothing treatment device may include multiple suspenders, an end of each of the suspenders is connected to the tub assembly, another end of each of the suspenders is connected to the housing, the tub assembly is suspended from the housing by multiple suspenders, the first rod is a part of the suspender, or the first rod is connected to the suspender.

[0019] Alternatively, the clothing treatment device may include an operation platform arranged at a top end of the housing, an end of the first rod is connected to the operation platform, and another end of the first rod extends downward from the operation platform.

[0020] Alternatively, the clothing treatment device may include a mounting seat arranged on the housing, and at least one end of the first rod is arranged on the mounting seat.

[0021] According to the clothing treatment device provided in the embodiments of the disclosure, when the tub assembly vibrates and deflects, the damping assembly achieves up-down movement, circumferential rotation and up-down swing relative to the tub assembly or the first rod through the through hole, to adapt to variation of vibration displacement of the tub assembly, an end of the damping assembly connected to the tub assembly or an end of the damping assembly connected to a component out of the tub assembly has at least three movement DOFs, and the damping assembly has high movement smoothness and low sticking probability, thereby facilitating the damping assembly to buffer vibration of the tub assembly, and reducing a probability of the tub assembly hitting the housing. Furthermore, the damping assembly has at least three movement DOFs through the structure of the through hole only, which also enables the overall structure of the damping assembly to be simpler and manufactured easily.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] FIG. 1 is a schematic structural diagram of a clothing treatment device according to an embodiment of the disclosure.

[0023] FIG. 2 is a schematic structural diagram of the structure shown in FIG. 1 from another perspective.

[0024] FIG. 3 is a schematic enlarged view at B of FIG. 2.

[0025] FIG. 4 is a schematic structural diagram of the structure shown in FIG. 1 from yet another perspective.

[0026] FIG. 5 is a schematic structural diagram of a damping assembly shown in FIG. 1.

[0027] FIG. 6 is a schematic exploded view of the structure shown in FIG. 5.

[0028] FIG. 7 is a schematic structural diagram of the structure shown in FIG. 5 from another perspective.

[0029] FIG. 8 is a schematic cross-sectional view of the structure shown in FIG. 7 along A-A.

[0030] FIG. 9 is a schematic structural diagram of a second connection end of a second movement member shown in FIG. 5.

[0031] FIG. 10 is a schematic structural diagram of a clothing treatment device according to another embodiment of the disclosure.

[0032] FIG. 11 is a schematic structural diagram of a clothing treatment device according to yet another embodiment of the disclosure.

[0033] FIG. 12 is a schematic enlarged view at C of FIG. 11.

[0034] FIG. 13 is a schematic structural diagram of fitting of a damping assembly and a mounting seat of FIG. 11.

[0035] Description of reference numerals is provided as follows: [0036] **100**—clothing treatment device; [0037] **1**—housing; **11**—mounting seat; [0038] **2**—tub assembly; **21**—mounting block; **2a**—connection slot; [0039] **3**—damping assembly; **31**—first movement member; **311**—first connection seat; **3111**—first annular portion; **3112**—first end plate; **3113**—elastic hook; **3114**—limit structure; **32**—second movement member; **321**—second connection seat; **3211**—second annular portion; **3212**—second end plate; **3212a**—penetration hole; **32a**—through hole; **33**—friction member; **3a**—first position; **3b**—second position; [0040] **4**—first rod; [0041] **5**—second rod; [0042] **6**—suspender; **62**—damping spring; **63**—damping cylinder; **64**—base; and [0043] **7**—operation platform.

DETAILED DESCRIPTION

[0044] In order to make the object, technical solutions and advantages of the disclosure more apparent, the disclosure will be further described in detail below with reference to the drawings and embodiments. It should be understood that specific embodiments described here are only intended to explain the disclosure and are not intended to limit the disclosure.

[0045] Various specific technical features described in the specific embodiments may be combined in any suitable manner without conflict, for example, different embodiments and technical solutions may be formed by combinations of different specific technical features. In order to avoid unnecessary repetition, various possible combinations of various specific technical features in the disclosure are not described any more.

[0046] Terms “first\second\ . . . ” involved in the following descriptions are only intended to distinguish different objects, and do not mean that there are similarities or relationships between objects. It should be understood that descriptions related to orientations “above”, “below”, “outside” and “inside” are all orientations in a normal usage state, and directions “left” and “right” indicate left and right directions shown in a specific corresponding schematic diagram, which may be or may not be left and right directions in a normal usage state.

[0047] It should be noted that terms “include”, “including” or any other variant thereof are intended to encompass non-exclusive inclusion, so that a process, method, article or device including a series of elements includes not only those elements, but also other elements which are not listed clearly, or elements inherent to such process, method, article or device. In absence of any further limitation, an element defined by a phrase “include a . . . ” does not preclude existence of another identical element in a process, method, article or device including this element. “Multiple” means equal to or greater than two.

[0048] Embodiments of the disclosure provide a clothing treatment device **100**, with reference to FIG. 1 to FIG. 13, the clothing treatment device **100** includes a housing **1**, a tub assembly **2**, a first rod **4**, and a damping assembly **3**.

[0049] It may be understood that specific form of the clothing treatment device **100** is not limited, and may be an existing pulsator washing machine, a drum washing machine or the like, which is

not limited here; preferably, the damping assembly **3** described in the embodiments of the disclosure has better usage effect on the pulsator washing machine.

[0050] The tub assembly **2** is arranged in the housing **1**.

[0051] It may be understood that the tub assembly **2** may include a drum and a tub, the drum is arranged inside the tub, and a space within the drum defines a clothing treatment chamber. The drum may be a perforated drum or a non-perforated drum. When the drum is a perforated drum, water is held by the tub; when the drum is a non-perforated drum, water is held by the drum itself, that is, both water and clothes may be held in the drum, and water in the drum may not enter the tub during washing. In some embodiments, the tub assembly **2** may be provided with only the drum and is not provided with the tub, and at this time, the drum is a non-perforated drum.

[0052] The housing **1** may provide an accommodation space and protection for the tub assembly **2**, isolate the tub assembly **2** from the external environment, and reduce a probability of impurities such as dust from the external environment or the like contacting the tub assembly **2**. When the clothing treatment device **100** is impacted, the housing **1** may also effectively resist impact from the external environment and reduce a probability of damage of the tub assembly **2**.

[0053] It may be understood that when the tub assembly **2** includes the drum and the tub, an end of the damping assembly **3** may be connected to the tub, and when the clothing treatment device **100** includes a suspender **6**, an end of the suspender **6** is connected to the tub, and another end of the suspender **6** is connected to the housing **1**, to bear weight of the tub assembly **2**; when the tub assembly **2** is provided with only the drum, the tub assembly **2** may include a water receiving tray arranged out of the drum, an end of the damping assembly **3** may be connected to the water receiving tray, and when the clothing treatment device **100** includes a suspender **6**, an end of the suspender **6** is connected to the water receiving tray, and another end of the suspender **6** is connected to the housing **1**, to bear weight of the tub assembly **2**.

[0054] In this embodiment, descriptions are made by an example of the tub assembly **2** including the drum and the tub.

[0055] It may be understood that when the clothing treatment device is in an operation condition of washing or spin-drying, the drum rotates, and clothes in the drum may shift during rotation of the drum, so that the center of gravity of the drum may shift, and thus the drum rotates eccentrically, resulting in vibration and deflection of the tub. When eccentricity of rotation of the drum increases, amplitude of the tub may also increase correspondingly, which makes the tub assembly easily hit the housing and affect the spin-drying process.

[0056] The damping assembly **3** is a structure with a damping function. The damping assembly **3** provided in this embodiment is intended to absorb vibration energy of the tub assembly **2** when the clothing treatment device **100** is in the operation condition of washing or spin-drying, to reduce vibration displacement of the tub assembly **2** and reduce a probability of the tub assembly **2** hitting the housing **1**.

[0057] With reference to FIG. **1** and FIG. **5**, the first rod **4** is arranged out of the tub assembly **2**, the damping assembly **3** includes a first connection end and a second connection end, the first connection end is connected to the tub assembly **2**, and the second connection end is connected to the first rod **4**.

[0058] That is, the damping assembly **3** is connected to the tub assembly **2** through the first connection end, and connected to a component out of the tub assembly **2** through the second connection end. It may be understood that the tub assembly **2** may also be provided with a rod, to achieve connection with the first connection end through the rod.

[0059] It should be noted that the first rod **4** arranged out of the tub assembly **2**, means that the first rod **4** is a component independent of the tub assembly **2** and arranged out of the tub assembly **2**. For example, the first rod **4** may be arranged on the suspender **6**, an operation platform **7** or the housing **1**, which is not limited here.

[0060] At least one of the first connection end or the second connection end is provided with a

through hole **32a**, and with reference to FIG. **9**, in directions from axially opposite ends of the through hole **32a** to an middle position of the through hole **32a** along an axial direction thereof, a hole wall of the through hole **32a** extends toward an axis E of the through hole **32a**.

[0061] Aperture of the through hole **32a** gradually decreases in directions from opposite ends of the through hole **32a** along the axial direction thereof to the middle position of the through hole **32a** along the axial direction thereof, the aperture of the through hole **32a** at the middle position along the axial direction is smaller than apertures of the through hole **32a** at two ends along the axial direction, and the aperture of the through hole **32a** is approximately distributed to be large at two ends and small in the middle.

[0062] It should be noted that the damping assembly **3** has at least a degree of freedom (DOF) of moving up and down, a DOF of swinging up and down and a DOF of rotating circumferentially, under action of the through hole **32a**.

[0063] When the through hole **32a** is arranged at the first connection end, the first connection end may move up and down, rotate circumferentially, and swing up and down relative to the tub assembly **2**. When the clothing treatment device **100** is in the operation condition of washing or spin-drying, the tub assembly **2** vibrates and deflects, and vibration energy is transmitted to the damping assembly **3**. Under action of vibration, the first connection end of the damping assembly **3** moves up and down, rotates circumferentially, and swings up and down relative to the tub assembly **2** under action of vibration, to adapt to variation of different vibration directions of the tub assembly **2**, and vibration of the tub assembly **2** forces the damping assembly **3** to absorb the vibration energy, to suppress vibration amplitude of the tub assembly **2**.

[0064] When the through hole **32a** is arranged at the second connection end, the second connection end may move up and down along the first rod **4**, rotate around a circumferential direction of the first rod **4**, and swing up and down relative to the first rod **4**. When the clothing treatment device **100** is in the operation condition of washing or spin-drying, the tub assembly **2** vibrates and deflects, and vibration energy is transmitted to the damping assembly **3**. Under action of vibration, the second connection end of the damping assembly **3** moves up and down, rotates circumferentially, and swings up and down relative to the first rod **4** under action of vibration, to adapt to variation of different vibration directions of the tub assembly **2**, and vibration of the tub assembly **2** forces the damping assembly **3** to absorb the vibration energy, to suppress vibration amplitude of the tub assembly **2**.

[0065] The through hole **32a** arranged at the second connection end is taken as an example, a gap between the first rod **4** and the hole wall of the through hole **32a** gradually increases in directions from the middle position of the through hole **32a** along the axial direction thereof to opposite ends of the through hole **32a** along the axial direction thereof, so that when the tub assembly **2** vibrates and deflects, the through hole **32a** implements that the second connection end moves up and down along the first rod **4** and rotates around the circumferential direction of the first rod **4**, while may also provide a movement space for the second connection end to swing up and down. In this way, the second connection end has multiple movement DOFs through the through hole **32a** only, and operation reliability of the damping assembly **3** is improved. Furthermore, the aperture of the through hole **32a** at the middle position along the axial direction is minimal, which also facilitates improving assembly stability of the through hole **32a** and the first rod **4**. It may be understood that in this embodiment, the first rod **4** has enough extension length to satisfy an up-down movement stroke of the second connection end.

[0066] A pulsator clothing treatment device is taken as an example, in case that an external size of a housing is unchanged, a gap between a tub assembly and the housing becomes smaller and smaller with the increase of a washing volume. During washing or spin-drying, the tub assembly may vibrate and deflect, and easily hit the housing, which affects usage safety of the clothing treatment device.

[0067] In the related art, in order to reduce amplitude of the tub assembly, the clothing treatment

device is provided with a damper, an end of the damper is connected to the tub assembly, another end of the damper is connected to a suspender, the connection end of the damper rotates around a circumferential direction of the suspender or slides along the suspender, and when the tub assembly vibrates, the damper moves with the tub assembly to dissipate vibration energy. However, when the damper moves with vibration of the tub assembly, there is a large probability of sticking the damper, which affects damping effect and may even lead to damage of the damper.

[0068] According to the clothing treatment device **100** provided in the embodiments of the disclosure, when the tub assembly **2** vibrates and deflects, the damping assembly **3** achieves up-down movement, circumferential rotation and up-down swing relative to the tub assembly **2** or the first rod **4** through the through hole **32a**, to adapt to variation of vibration displacement of the tub assembly **2**, an end of the damping assembly **3** connected to the tub assembly **2** or an end of the damping assembly **3** connected to a component out of the tub assembly **2** has at least three movement DOFs, and the damping assembly **3** has high movement smoothness and low sticking probability, thereby facilitating the damping assembly **3** to buffer vibration of the tub assembly **2**, and reducing a probability of the tub assembly **2** hitting the housing **1**. Furthermore, the damping assembly **3** has at least three movement DOFs through the structure of the through hole **32a** only, which also enables the overall structure of the damping assembly **3** to be simpler and manufactured easily.

[0069] In some embodiments, with reference to FIG. **9**, the through hole **32a** is symmetrical with respect to a first plane F, and the first plane F is a plane perpendicular to the axis E of the through hole **32a** and passing through the middle position of the through hole **32a** along the axial direction thereof.

[0070] That is, the through hole **32a** is symmetrical with respect to the axis E thereof, while also symmetrical with respect to the first plane F, and the through hole **32a** is a centrosymmetric structure, and a symmetrical center thereof is an intersection point of the first plane F and the axis E thereof.

[0071] In this embodiment, the configuration of the through hole **32a** enables movement ranges at different angles to be more uniform when the first connection end or the second connection end rotates circumferentially and swings up and down, thereby improving movement stability of the first connection end or the second connection end. When the tub assembly **2** returns to a stationary state, it also facilitates the damping assembly **3** to return to an initial position following the tub assembly **2**, improving movement reliability of the damping assembly **3**.

[0072] In some embodiments, in a longitudinal cross section passing through the axis E of the through hole **32a**, at least a part of cross section of the hole wall of the through hole **32a** is in a shape of an arc projecting toward the axis E of the through hole **32a**.

[0073] In this embodiment, the cross section of the hole wall of the through hole **32a** is in a shape of an arc projecting toward the axis E of the through hole **32a**, and the shape may be an entire arc, or a pattern formed by a combination of an arc section and a linear section or a combination of an arc section and a curve section, which is not limited here.

[0074] In this way, enough movement space is provided for the first connection end or the second connection end, while it may also facilitate the first connection end to achieve stable assembly with the tub assembly **2** through the through hole **32a**, or it may also facilitate the second connection end to achieve stable assembly with the first rod **4** through the through hole **32a**.

[0075] Exemplarily, in some embodiments, with reference to FIG. **9**, the cross section of the hole wall of the through hole **32a** is in a shape of an arc projecting toward the axis E of the through hole **32a**, and the arc may also reduce movement resistance of the first connection end or the second connection end, so that movement of the first connection end is smoother.

[0076] It may be understood that at least a part of the cross section may be a part of the cross section or all of the cross section.

[0077] In some embodiments, with reference to FIG. **9**, at least a part of cross section of the hole

wall of the through hole **32a** is in a shape of a circular arc. In this way, when it enables movement of the first connection end or the second connection end to be smoother, it may also reduce difficulty of forming the through hole **32a** and difficulty of manufacturing the damping assembly **3**. [0078] In some embodiments, with reference to FIG. **9**, the through hole **32a** is arranged at the second connection end. The circular arc is a semicircular arc, and diameter **D1** of the semicircular arc is equal to thickness **D2** of the second connection end, that is, $D1=D2$.

[0079] In this embodiment, the diameter of the cross section of the through hole **32a** is equal to the thickness of the second connection end, so that when the tub assembly **2** vibrates and deflects, the second connection end has enough up-down swing range relative to the first rod **4**, to adapt to vibration displacements of the tub assembly **2** in different vibration directions, to reduce a probability of sticking movement of the second connection end, improve movement stability of the damping assembly **3**, and also reduce difficulty of manufacturing the damping assembly **3**.

[0080] Specific configuration of the damping assembly **3** is not limited.

[0081] In some embodiments, with reference to FIG. **5** and FIG. **6**, the damping assembly **3** includes a first movement member **31**, a second movement member **32** and a friction member **33**, the first movement member **31** is connected to the second movement member **32**, and the first movement member **31** and the second movement member **32** are relatively rotatable around their joint, the friction member **33** is arranged at the rotation joint of the first movement member **31** and the second movement member **32**, to provide friction force to achieve damping when the first movement member **31** and the second movement member **32** rotate relatively, an end of the first movement member **31** away from the friction member **33** defines the first connection end, and an end of the second movement member **32** away from the friction member **33** defines the second connection end.

[0082] That is, the end of the first movement member **31** away from the friction member **33** is connected to the tub assembly **2**, and the end of the second movement member **32** away from the friction member **33** is connected to the first rod **4**. When the through hole **32a** is arranged at the first connection end, the first movement member **31** may have a DOF of moving up and down, a DOF of rotating circumferentially and a DOF of swinging up and down through the through hole **32a**; when the through hole **32a** is arranged at the second connection end, the second movement member **32** may have a DOF of moving up and down, a DOF of rotating circumferentially and a DOF of swinging up and down through the through hole **32a**.

[0083] It should be noted that the friction member **33** refers to a structure of which the material itself has friction damping characteristics.

[0084] It should be noted that the first movement member **31** and the second movement member **32** relatively rotatable around their joint, means that at least one of the first movement member **31** or the second movement member **32** may rotate with their joint as a center, so that the first movement member **31** and the second movement member **32** may rotate relatively.

[0085] When the tub assembly **2** vibrates and deflects, the first movement member **31** or the second movement member **32** have a DOF of moving up and down, a DOF of rotating circumferentially and a DOF of swinging up and down, while the first movement member **31** and the second movement member **32** may also relatively rotate around their joint. The damping assembly **3** has at least four movement DOFs and has high movement smoothness, further reducing a probability of sticking the damping assembly **3**. Furthermore, when the first movement member **31** and the second movement member **32** rotate relatively, they rub against the friction member **33** to generate friction damping, and the friction damping may be used as damping force for the damping assembly **3** to reduce vibration of the tub assembly **2**, so that buffering vibration of the tub assembly **2** is achieved.

[0086] In this embodiment, the first movement member **31** and the second movement member **32** rotate relatively, to rub against the friction member **33** to generate friction force, thereby limiting vibration amplitude of the tub assembly **2** and reducing vibration displacement of the tub assembly

2. The friction member **33** is arranged between the first movement member **31** and the second movement member **32**, that is, the friction member **33** does not directly contact the tub assembly **2** or the first rod **4**, so that abrasion generated by the friction member **33** may be small. Furthermore, when the first movement member **31** and the second movement member **32** rotate relatively, the friction member **33** may also isolate the first movement member **31** from the second movement member **32**, to reduce abrasion generated by direct friction when the first movement member **31** and the second movement member **32** rotate, so that service life of the damping assembly **3** may be prolonged.

[0087] Material of the friction member **33** is not limited. For example, the friction member **33** may be made of a polyurethane foam material with high abrasion resistance or a soft rubber material with high abrasion resistance, has a high friction coefficient on its surface, and may generate deformation to fit with the first movement member **31** and the second movement member **32**. The friction member **33** may also be made of a semi-metallic friction material or the like, which is not limited here.

[0088] In some embodiments, with reference to FIG. **1** and FIG. **8**, an axis **L2** around which the first movement member **31** and the second movement member **32** rotate relatively is substantially parallel to an axis **L1** of the tub assembly **2**. That is, the axis **L2** around which the first movement member **31** and the second movement member **32** rotate relatively is substantially parallel to a height direction.

[0089] “Substantially parallel to” means that an angle between the axis **L2** around which the first movement member **31** and the second movement member **32** rotate relatively and the axis **L1** of the tub assembly **2** may be 0° or close to 0° , that is, certain machining and assembly errors are allowed. Exemplarily, the angle between the axis **L2** around which the first movement member **31** and the second movement member **32** rotate relatively and the axis **L1** of the tub assembly **2** is $0^\circ \sim 5^\circ$, such as 0° , 0.3° , 0.5° , 0.7° , 0.9° , 1° , 1.2° , 1.4° , 1.6° , 1.8° , 2° , 3° , 4° , 5° , etc.

[0090] It may be understood that in the operation condition of washing or spin-drying, the tub assembly may vibrate in a horizontal direction and in the height direction, and mainly vibrates in the horizontal direction. Vibration displacement of the tub assembly in the height direction is small and is not easy to hit the tub, while vibration displacement of the tub assembly in the horizontal direction is large and is easy to exceed a horizontal gap between the housing and the tub assembly to hit the housing. Therefore, it is necessary to effectively suppress horizontal vibration of the tub assembly. Rotation axes of a first movement member and a second movement member of a damping component provided in the related art are substantially parallel to the horizontal direction, that is, the first movement member and the second movement member mainly swing along a vertical plane, damping force against vibration is mainly decomposed into force along the height direction, and component force along the horizontal direction is small, so that horizontal vibration of the tub assembly cannot be effectively absorbed, and damping effect is limited.

[0091] It may be understood that the horizontal direction refers to a direction parallel to a horizontal plane after the clothing treatment device **100** is placed on the horizontal ground, such as a left-right direction, a front-back direction, and other horizontal directions intersecting the left-right direction and the front-back direction.

[0092] In this embodiment, when the tub assembly **2** vibrates and deflects, the first movement member **31** and the second movement member **32** of the damping assembly **3** may relatively rotate around their joint. Since the axis **L2** around which the first movement member **31** and the second movement member **32** rotate relatively is substantially parallel to the height direction, that is, the first movement member **31** and the second movement member **32** relatively rotate in the horizontal direction, friction force generated by the friction member **33** is substantially in the horizontal direction, which may be substantially used to reduce horizontal vibration of the tub assembly **2**, effectively suppress the horizontal vibration of the tub assembly **2**, reduce vibration displacement of the tub assembly **2**, and reduce a probability of the tub assembly **2** hitting the housing **1**.

[0093] In some embodiments, with reference to FIG. 1, the clothing treatment device **100** includes a second rod **5** extending in a height direction and fixed to an outer circumferential side of the tub assembly **2**, an end of the first movement member **31** away from the friction member **33** is sleeved on an outer circumference of the second rod **5** and is rotatable around a circumferential direction of the second rod **5**, and the through hole **32a** is arranged at the second connection end.

[0094] In this embodiment, the through hole **32a** is arranged at the second connection end, that is, the second movement member **32** may have a DOF of rotating circumferentially, a DOF of swinging up and down and a DOF of sliding up and down through the through hole **32a**.

[0095] In this embodiment, when the tub assembly **2** vibrates and deflects, vibration energy of the tub assembly **2** is transmitted to the damping assembly **3**, the end of the first movement member **31** sleeved on the second rod **5** rotates around the circumferential direction of the second rod **5**, and an end of the second movement member **32** away from the first movement member **31** rotates around the circumferential direction of the first rod **4**, and swings and moves up and down relative to the first rod **4**. Furthermore, the first movement member **31** and the second movement member **32** may relatively rotate around their joint, the damping assembly **3** has at least five movement DOFs, and a probability of sticking its movement is low.

[0096] In some embodiments, the entire first movement member **31** is a rigid member and has only one rotation DOF; and/or, the entire second movement member **32** is a rigid member.

[0097] It should be noted that the rigid member is a single element forming a mechanism, and is a rigid body with equivalent movement to an adjacent member. The rigid member is a basic unit forming the mechanism in mechanism and having a determined relative movement relationship there-between. DOF refers to a number of independent coordinates required to describe a mechanical system. A movement DOF means that the first movement member **31** is movable in only one direction and movements in other directions are constrained.

[0098] The first movement member **31** has only one rotation DOF, i.e., a rotation DOF around the circumferential direction of the second rod **5**, so that the entire damping assembly **3** may be adaptively changed with variation of the position of the tub assembly **2** under action of vibration, while the entire damping assembly **3** also has enough mounting stability.

[0099] The entire first movement member **31** is a rigid member, and when an end of the first movement member **31** away from the second movement member **32** rotates around the circumferential direction of the second rod **5**, the entire first movement member **31** may be driven to rotate around the circumferential direction of the second rod **5**. When the entire second movement member **32** is a rigid member, and when an end of the second movement member **32** away from the first movement member **31** rotates around the circumferential direction of the first rod **4**, the entire second movement member **32** may be driven to rotate around the circumferential direction of the first rod **4**, so that the first movement member **31** and the second movement member **32** may relatively rotate around their joint.

[0100] Each of the first movement member **31** and the second movement member **32** may be an integrated member, which has a simple structure and is manufactured and molded easily.

[0101] The position where the first rod **4** is arranged, is not limited.

[0102] For example, in some examples, with reference to FIG. 1, the clothing treatment device **100** includes multiple suspenders **6**, an end of each of the suspenders **6** is connected to the tub assembly **2**, another end of each of the suspenders **6** is connected to the housing **1**, the tub assembly **2** is suspended from the housing **1** by multiple suspenders **6**.

[0103] Top ends of the suspenders **6** are fixed to the housing **1**, bottom ends of the suspenders **6** are fixed to the tub assembly **2**, there are four suspenders **6** in number, top ends of the four suspenders **6** correspond to four corners at a top end of the housing **1**, and bottom ends of the four suspenders **6** are fixed to side walls of the tub assembly **2** corresponding to the four corners of the housing **1**. In this way, each suspender **6** may uniformly share weight of the tub assembly **2** and improve mounting stability of the clothing treatment device **100**.

[0104] With reference to FIG. 1, the first rod 4 is a part of the suspender 6.

[0105] In this embodiment, the first movement member 31 is connected to the tub assembly 2, the second movement member 32 is connected to the suspender 6 through the through hole 32a, there is enough mounting space between the tub assembly 2 and the suspender 6 to arrange the damping assembly 3, the suspender 6 has enough structural strength to facilitate providing enough movement support for the damping assembly 3, and the second movement member 32 may not disengage from the suspender 6, thereby improving mounting stability of the damping assembly 3. Furthermore, the damping assembly 3 is not directly connected to the housing 1, and vibration energy of the tub assembly 2 is transmitted to the housing 1 through the damping assembly 3 and the suspenders 6, so that vibration energy received by the housing 1 may be reduced, and operation stability of the clothing treatment device 100 may be improved.

[0106] In this embodiment, the second movement member 32 is sleeved on the suspender 6, and when the tub assembly 2 vibrates and deflects, an end of the second movement member 32 away from the first movement member 31 may slide along an extension direction of the suspender 6, rotate around a circumferential direction of the suspender 6, and swing up and down relative to the suspender 6, and the first movement member 31 rotates around the circumferential direction of the second rod 5, to adapt to variation of different vibration positions of the tub assembly 2, and reduce a probability of sticking movements of the first movement member 31 and the second movement member 32, so that the damping assembly 3 have high operation reliability.

[0107] In some other embodiments, the first rod 4 may also be connected to the suspender 6. The suspender 6 may provide support for the first rod 4, thereby providing enough support for the second movement member 32.

[0108] It may be understood that the suspender 6 may also be provided with a damping structure to buffer vibration of the tub assembly 2. Exemplarily, with reference to FIG. 1, the clothing treatment device 100 includes a damping cylinder 63, a base 64 arranged at a bottom end of the suspender 6, and a damping spring 62 arranged on the suspender 6 and sandwiched between the damping cylinder 63 and the base 64. A connection slot 2a is formed on an outer circumferential wall at a bottom end of the tub assembly 2, and the connection slot 2a is sleeved on the damping cylinder 63. The damping cylinder 63 is sleeved on the suspender 6, the damping spring 62 is a compression spring, an end of the damping spring 62 abuts against a bottom end of the damping cylinder 63, and another end of the damping spring 62 abuts against the base 64. In this way, when the tub assembly 2 vibrates during washing or spin-drying, the damping spring 62 slides up and down along the suspender 6 to absorb longitudinal vibration energy of the tub assembly 2, thereby reducing vibration noise of the housing 1 and improving operation stability of the clothing treatment device 100.

[0109] The number of damping assemblies 3 is not limited. Exemplarily, with reference to FIG. 1, there are four damping assemblies 3 in number, there are four second rods 5 in number, an end of each of the four damping assemblies 3 is connected to a respective one of the second rods 5, and another end of each of the four damping assemblies 3 is connected to a respective one of the suspenders 6, so that the damping assemblies 3 may uniformly and sufficiently buffer vibration of the tub assembly 2 from different directions, increase damping effect, and improve operation safety of the clothing treatment device 100.

[0110] In some other examples, with reference to FIG. 10, the clothing treatment device 10 includes an operation platform 7 arranged at a top end of the housing 1, an end of the first rod 4 is connected to the operation platform 7, and another end of the first rod 4 extends downward from the operation platform 7 to form a suspended free end, or extends downward and then is connected to a lower part or a bottom plate of the housing 1.

[0111] It may be understood that the operation platform 7 is located at a top side of the housing 1, and the operation platform 7 is provided with a clothing access port communicated with the clothing treatment chamber, that is, to-be-cleaned clothes may be put into the clothing treatment

chamber from the top side through the clothing access port, and cleaned clothes may also be taken out from the clothing treatment chamber through the clothing access port.

[0112] In this embodiment, the second movement member **32** is connected to the operation platform **7** through the first rod **4**, the first movement member **31** is connected to the tub assembly **2**, and the tub assembly **2** and the operation platform **7** jointly provide mounting support for the damping assembly **3**, to improve mounting stability and movement stability of the damping assembly **3**. Furthermore, the damping assembly **3** is not directly connected to the housing **1**, vibration energy of the tub assembly **2** is transmitted to the housing **1** through the damping assembly **3** and the operation platform **7**, and the operation platform **7** may share a part of the vibration energy for the housing **1**, which may reduce vibration noise of the housing **1** and improve operation stability of the clothing treatment device **100**.

[0113] Furthermore, the first rod **4** extends downward from the operation platform **7**, and an axis of the first rod **4** is in the height direction, so that resistance of movement of the second movement member **32** around the first rod **4** may be reduced.

[0114] In some other examples, with reference to FIG. **11** to FIG. **13**, the clothing treatment device **100** includes a mounting seat **11** arranged on the housing **1**, and at least one end of the first rod **4** is arranged on the mounting seat **11**.

[0115] In this embodiment, the first movement member **31** is connected to the housing **1**, the second movement member **32** is connected to the tub assembly **2**, and the tub assembly **2** and the housing **1** jointly provide support for the damping assembly **3**. In this way, the damping assembly **3** has enough mounting space and movement space, to facilitate buffering vibration of the tub assembly **2**.

[0116] Manners used to implement that the first movement member **31** has only one rotation DOF, are not limited.

[0117] In some embodiments, with reference to FIG. **1**, the tub assembly **2** includes at least two mounting blocks **21** projecting from an outer circumferential wall of the tub assembly **2**, the two mounting blocks **21** are arranged at an interval in the height direction, two ends of the second rod **5** are fixed to the mounting blocks **21**, and the first movement member **31** is sleeved on a portion of the second rod **5** between the two mounting blocks **21**, and abuts against the two mounting blocks **21** respectively.

[0118] In this way, on one hand, it may improve stability of the second rod **5** fixed to the tub assembly **2** and reduce a probability of the second rod **5** disengaging from the tub assembly **2**, and it may also reduce a probability of the first movement member **31** disengaging from the second rod **5**; on the other hand, the two mounting blocks **21** constrain sliding DOF of the first movement member **31** in an extension direction of the second rod **5**, so that the first movement member **31** has only movement DOF of rotating around the circumferential direction of the second rod **5**.

[0119] Specific configurations of the first movement member **31** and the second movement member **32** are not limited.

[0120] In some embodiments, with reference to FIG. **5** to FIG. **8**, the first movement member **31** includes a first connection seat **311**, the second movement member **32** includes a second connection seat **321**, the first connection seat **311** includes a first annular portion **3111**, the second connection seat **321** includes a second annular portion **3211**, the first annular portion **3111** and the second annular portion **3211** are nested with each other and provided with an annular space in a radial direction, and the friction member **33** is arranged in the annular space.

[0121] It should be noted that each of the first annular portion **3111** and the second annular portion **3211** is an annular structure which is connected end-to-end and is not provided with notches in a circumferential direction. Nested arrangement of the first annular portion **3111** and the second annular portion **3211** means that the first annular portion **3111** is embedded in the second annular portion **3211**, or the second annular portion **3211** is embedded in the first annular portion **3111**; the annular space is a space between the first annular portion **3111** and the second annular portion

3211, the friction member **33** is arranged in the annular space, that is, the friction member **33** is arranged between the first annular portion **3111** and the second annular portion **3211**. When the first movement member **31** and the second movement member **32** rotate relatively, the first annular portion **3111** and the second annular portion **3211** rotate relatively, and thus rub against the friction member **33** to generate friction force.

[0122] In this embodiment, the first movement member **31**, the second movement member **32** and the friction member **33** are connected together by the nested fitting of the first annular portion **3111** and the second annular portion **3211**, so that the overall structure of the damping assembly **3** is simple and mounted easily, and a probability of damage of the friction member **33** during assembly may also be reduced.

[0123] In some embodiments, with reference to FIG. 5 to FIG. 8, the first connection seat **311** includes a first end plate **3112** connected to the first annular portion **3111**, the second connection seat **321** includes a second end plate **3212** connected to the second annular portion **3211**, the first end plate **3112** and the second end plate **3212** are arranged in parallel, and the first annular portion **3111** and the second annular portion **3211** are located between the first end plate **3112** and the second end plate **3212**.

[0124] It should be noted that the first end plate **3112** and the second end plate **3212** arranged in parallel, refers to a position relationship provided by the first end plate **3112** and the second end plate **3212** after docking of the first movement member **31** and the second movement member **32** is completed.

[0125] In this embodiment, the first end plate **3112** and the second end plate **3212** may provide support for the first annular portion **3111** and the second annular portion **3211**, and the first annular portion **3111** and the second annular portion **3211** are defined between the first end plate **3112** and the second end plate **3212**, so that docking stability of the first annular portion **3111** and the second annular portion **3211** may be improved, a loosening probability of docking of the first annular portion **3111** and the second annular portion **3211** may be reduced, while a probability of the friction member **33** disengaging from the annular space may also be reduced, and the friction member **33** may be isolated from other components out of the damping assembly **3**, so that there is satisfactory mounting stability of the damping assembly **3**. Furthermore, the first end plate **3112** and the second end plate **3212** are arranged in parallel, so that smoothness of the first movement member **31** and the second movement member **32** when they rotate relatively may be further increased.

[0126] In some embodiments, with reference to FIG. 5 to FIG. 8, the second annular portion **3211** surrounds an outer circumference of the first annular portion **3111**, the second end plate **3212** is provided with a penetration hole **3212a**, the first connection seat **311** further includes one or more elastic hooks **3113** arranged into an inner space of the first annular portion **3111**, an end of the elastic hook **3113** is connected to the first end plate **3112**, and another end of the elastic hook **3113** passes through the penetration hole **3212a** and is connected to a surface at a side of the second end plate **3212** away from the first end plate **3112**.

[0127] The elastic hook **3113** refers to a structure which plays an elastic function and may be deformed.

[0128] When the first movement member **31** is docked with the second movement member **32**, the friction member **33** is arranged on the outer circumference of the first annular portion **3111**, then the penetration hole **3212a** of the second annular portion **3211** passes through the elastic hook **3113** from top to bottom, and the elastic hook **3113** is deformed elastically during pass. When the second annular portion **3211** completely surrounds the outer circumference of the first annular portion **3111**, the elastic hook **3113** extends out of the penetration hole **3212a**, recovers from deformation, and abuts against the side of the second end plate **3212** away from the first end plate **3112**, thereby connecting the first connection seat **311** and the second connection seat **321** together, reducing a probability of the second connection seat **321** disengaging from the first connection seat **311**, and

improving mounting stability of the damping assembly 3.

[0129] The number of elastic hooks **3113** is not limited, and there may be one, two, or more than three elastic hooks. Exemplarily, with reference to FIG. 6, there are three elastic hooks **3113** in number.

[0130] In some other embodiments, the first annular portion **3111** surrounds an outer circumference of the second annular portion **3211**, the first connection seat **311** is provided with a penetration hole, the second connection seat **321** includes one or more elastic hooks arranged into an inner space of the second annular portion **3211**, an end of the elastic hook is connected to the second end plate **3212**, and another end of the elastic hook passes through the penetration hole and is connected to a surface at a side of the first end plate **3112** away from the second end plate **3212**.

[0131] In some embodiments, with reference to FIG. 5 to FIG. 8, the first connection seat **311** further includes a limit structure **3114** arranged on the first end plate **3112** and located at an outer circumferential side of the first annular portion **3111**, and the limit structure **3114** is configured to form stop-fitting with the second movement member **32** in a circumferential direction, to limit a maximum rotation angle when the second movement member **32** rotates relative to the first movement member **31**.

[0132] It should be noted that in an initial state, an angle between the first movement member **31** and the second movement member **32** is a first angle, and the initial state is a position where the first movement member **31** and the second movement member **32** are located when the tub assembly **2** is in a stationary state. The second movement member **32** rotates relative to the first movement member **31** when the tub assembly **2** vibrates and deflects, an angle between the second movement member **32** and the first movement member **31** is a second angle when the second movement member **32** abuts against the limit structure **3114**, and a maximum rotation angle of the second movement member **32** rotating relative to the first movement member **31** is a difference between the second angle and the first angle.

[0133] It may be understood that a first end of the first movement member **31** is connected to a first end of the second movement member **32**, and the angle between the first movement member **31** and the second movement member **32** is an angle between a line connecting centers of first and second ends of the first movement member **31** and a line connecting centers of first and second ends of the second movement member **32**. The second end of the first movement member **31** is an end of the first movement member **31** away from the friction member **33**, and the second end of the second movement member **32** is an end of the second movement member **32** away from the friction member **33**.

[0134] It may be understood that when the tub assembly vibrates and deflects, the first movement member and the second movement member rotate relatively under action of vibration, and when the position of the second movement member rotating relative to the first movement member exceeds a critical position, resistance of the first movement member and the second movement member returning to the initial state is increased greatly, so that the first movement member and the second movement member cannot adaptively move according to variation of the vibration position of the tub assembly, resulting in that vibration of the tub assembly cannot be suppressed effectively, reducing damping reliability of the damping assembly.

[0135] In this embodiment, when the second movement member **32** rotates to the maximum rotation angle relative to the first movement member **31**, the second movement member **32** forms stop-fitting with the limit structure **3114**, and the limit structure **3114** prevents the second movement member **32** from rotating in a direction of increasing the relative rotation angle, to control the angle of the second movement member **32** rotating relative to the first movement member **31** to be within a suitable range, thereby reducing resistance of the first movement member **31** and the second movement member **32** returning to the initial state and improving damping reliability of the damping assembly **3**.

[0136] In some other embodiments, the limit structure may be arranged at the second connection

seat **321**, the limit structure is arranged on the second end plate **3212** and located at an outer circumferential side of the second annular portion **3211**, and the limit structure is configured to form stop-fitting with the first movement member **31** in a circumferential direction, to limit a maximum rotation angle when the first movement member **31** rotates relative to the second movement member **32**.

[0137] In some examples, the angle between the first movement member **31** and the second movement member **32** does not exceed 180° . That is, an angle between a line connecting centers of first and second ends of the first movement member **31** and a line connecting centers of first and second ends of the second movement member **32** does not exceed 180° .

[0138] It may be understood that “the angle does not exceed 180° ” means that before or during the first movement member **31** and the second movement member **32** rotate relatively, one of the first movement member **31** and the second movement member **32** is taken as a reference, then an angle between the line connecting centers of first and second ends of the first movement member **31** and the line connecting centers of first and second ends of the second movement member **32** in the same direction does not exceed 180° . For example, with reference to FIG. 7, the first movement member **31** is taken as a reference, then an angle between the line connecting centers of first and second ends of the first movement member **31** and the line connecting centers of first and second ends of the second movement member **32** in a counter-clockwise direction shown in the figure does not exceed 180° at all times.

[0139] In this embodiment, the angle between the first movement member **31** and the second movement member **32** is configured so that relative position variation of the first movement member **31** and the second movement member **32** may be limited to a reasonable range, to facilitate the first movement member **31** and the second movement member **32** to adaptively move with variation of the vibration position of the tub assembly **2**, and improve damping reliability of the damping assembly **3**.

[0140] In some examples, with reference to FIG. 7, when the tub assembly **2** is in a stationary state, the angle between the first movement member **31** and the second movement member **32**, i.e., an angle α between a line **A1** connecting centers of first and second ends of the first movement member **31** and a line **A2** connecting centers of first and second ends of the second movement member **32** is not less than 50° and not greater than 120° , that is, $50^\circ \leq \alpha \leq 120^\circ$, such as 50° , 55° , 60° , 63° , 69° , 72° , 75° , 86° , 90° , 95° , 100° , 110° , 120° , etc.

[0141] In this embodiment, when the tub assembly **2** is in a stationary state, the angle between the first movement member **31** and the second movement member **32** is within a suitable range, which on one hand, facilitates the first movement member **31** and the second movement member **32** to rotate relatively under vibration of the tub assembly **2**, and on the other hand, enables the second movement member **32** to have enough rotation range when it rotates relative to the first movement member **31**, improving damping reliability of the damping assembly **3**.

[0142] In some examples, a position where the first movement member **31** is connected to the second rod **5** is a first position **3a**, a position where the second movement member **32** is connected to the first rod **4** is a second position **3b**, and in a planar projection perpendicular to a height direction of the clothing treatment device **100**, when the tub assembly **2** is in a stationary state, a line **L3** connecting centers of projections of the first position **3a** and the second position **3b** is substantially perpendicular to a tangent line **L4** of the tub assembly **2** at the first position **3a**.

[0143] “Substantially perpendicular to” means that an angle between the line **L3** connecting centers of projections of the first position **3a** and the second position **3b** and the tangent line **L4** of the tub assembly **2** at the first position **3a** may be 90° or close to 90° , that is, certain machining and assembly errors are allowed. Exemplarily, the angle β between the line **L3** connecting centers of projections of the first position **3a** and the second position **3b** and the tangent line **L4** of the tub assembly **2** at the first position **3a** is $85^\circ \sim 95^\circ$, that is, $85^\circ \leq \beta \leq 95^\circ$, such as 85° , 86° , 87° , 88° , 89° , 90° , 91° , 92° , 93° , 94° , 95° , etc.

[0144] FIG. 4 is taken as an example, the second rod 5 is connected to the tub assembly 2, the first rod 4 is a part of the suspender 6, and the angle β is the angle between the line L3 connecting centers of projections of the first position 3a and the second position 3b and the tangent line L4 of the tub assembly 2 at the first position 3a.

[0145] In this embodiment, the range of the angle β enables the damping assembly 3 to be in a relatively stable state when the tub assembly 2 is in a stationary state, and resistance of the damping assembly 3 moving with vibration of the tub assembly 2 may be small when the tub assembly 2 vibrates and deflects, which facilitates improving operation reliability of the damping assembly 3.

[0146] Movement mode of the damping assembly 3 according to an embodiment of the disclosure will be briefly described below with reference to FIG. 1.

[0147] The first movement member 31 is sleeved on the second rod 5, the second rod 5 is fixed to the tub assembly 2, the first rod 4 is a part of the suspender 6, the through hole 32a is a part of the second movement member 32, and the second movement member 32 is sleeved on the suspender 6 through the through hole 32a. When the tub assembly 2 vibrates, an end of the second movement member 32 away from the first movement member 31 may rotate around the circumferential direction of the suspender 6, swing up and down relative to the suspender 6, and slide along the extension direction of the suspender 6, and the first movement member 31 may rotate around the circumferential direction of the second rod 5.

[0148] In this embodiment, the damping assembly 3 has five movement DOFs in total, i.e., a rotation DOF of rotating around the circumferential direction of the second rod 5, a rotation DOF of rotating around the circumferential direction of the suspender 6, a swing DOF of swinging up and down relative to the suspender 6, a sliding DOF of sliding along the suspender 6, and a DOF of the first movement member 31 and the second movement member 32 rotating relatively. The damping assembly 3 has a low probability of sticking its movement, may adapt to vibration displacements of the tub assembly 2 in different vibration directions, and has high damping reliability.

[0149] In descriptions of the disclosure, descriptions of reference terms “an embodiment”, “some embodiments”, “example”, “specific example”, or “some examples” or the like, mean that specific features, structures, materials or characteristics described in combination with the embodiment or example are included in at least one embodiment or example of the embodiments of the disclosure. In the disclosure, schematic representations of the above terms are not necessarily directed to the same embodiment or example. Furthermore, specific features, structures, materials or characteristics as described may be combined in a suitable manner in any one or more embodiments or examples. Furthermore, those skilled in the art may combine different embodiments or examples described in the disclosure and features of different embodiments or examples, without mutual conflict.

[0150] The above descriptions are only preferred embodiments of the disclosure, and are not intended to limit the disclosure. For those skilled in the art, various modifications and variations may be made to the disclosure. Any modification, equivalent replacement, improvement, or the like made within the spirit and principle of the disclosure should be included in the scope of protection of the disclosure.

Claims

1. A clothing treatment device comprising: a housing; a tub assembly, arranged in the housing; a first rod, arranged out of the tub assembly; and a damping assembly, comprising a first connection end and a second connection end, wherein the first connection end is connected to the tub assembly, and the second connection end is connected to the first rod, wherein at least one of the first connection end or the second connection end is provided with a through hole, and in directions from axially opposite ends of the through hole to an middle position of the through hole along an

- axial direction thereof, a hole wall of the through hole extends toward an axis of the through hole.
2. The clothing treatment device of claim 1, wherein the through hole is symmetrical with respect to a first plane, and wherein the first plane is a plane perpendicular to the axis of the through hole and passing through the middle position of the through hole along the axial direction thereof.
 3. The clothing treatment device of claim 1, wherein in a longitudinal cross section passing through the axis of the through hole, at least a part of cross section of the hole wall of the through hole is in a shape of an arc projecting toward the axis of the through hole.
 4. The clothing treatment device of claim 3, wherein at least a part of cross section of the hole wall of the through hole is in a shape of a circular arc.
 5. The clothing treatment device of claim 1, wherein the damping assembly comprises a first movement member, a second movement member and a friction member, the first movement member is connected to the second movement member, and the first movement member and the second movement member are relatively rotatable around their joint, the friction member is arranged at the rotation joint of the first movement member and the second movement member, to provide friction force to achieve damping when the first movement member and the second movement member rotate relatively, an end of the first movement member away from the friction member defines the first connection end, and an end of the second movement member away from the friction member defines the second connection end.
 6. The clothing treatment device of claim 5, wherein an axis around which the first movement member and the second movement member rotate relatively is substantially parallel to an axis of the tub assembly.
 7. The clothing treatment device of claim 5, wherein a first end of the first movement member is connected to a first end of the second movement member, and when the tub assembly is in a stationary state, an angle between a line connecting centers of first and second ends of the first movement member and a line connecting centers of first and second ends of the second movement member is not less than 50° and not greater than 120° .
 8. The clothing treatment device of claim 5, wherein the clothing treatment device comprises a second rod extending in a height direction and fixed to an outer circumferential side of the tub assembly, an end of the first connection end away from the friction member is sleeved on an outer circumference of the second rod and is rotatable around a circumferential direction of the second rod, and the through hole is arranged at the second connection end.
 9. The clothing treatment device of claim 8, wherein the first movement member is a rigid member and has only one rotation degree of freedom.
 10. The clothing treatment device of claim 8, wherein the second movement member is a rigid member.
 11. The clothing treatment device of claim 8, further comprising a plurality of suspenders, wherein an end of each of the suspenders is connected to the tub assembly, another end of each of the suspenders is connected to the housing, the tub assembly is suspended from the housing by the plurality of suspenders, and the first rod is a part of the suspender or the first rod is connected to the suspender.
 12. The clothing treatment device of claim 8, further comprising an operation platform arranged at a top end of the housing, wherein an end of the first rod is connected to the operation platform, and another end of the first rod extends downward from the operation platform.
 13. The clothing treatment device of claim 8, further comprising a mounting seat arranged on the housing, wherein at least one end of the first rod is arranged on the mounting seat.
-