

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283327

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

GUZZARDI; DOMENICO

PARTITION SYSTEM FOR DIVIDING A ROOM OF A BUILDING INTO A PLURALITY OF ROOMS

Abstract

A partition system (10) for dividing a space, comprising a frame (11) and one or more partition panels (12) mountable on the frame, wherein the frame comprises a plurality of main profiles (100) which comprises at least one plurality of perimetric profiles (110) configured to be fixed to a surface of the space; one or more perimetric profiles are constituted of a main material which is thermoplastic polyolefin mixture-based. Each main profile delimits a first front hollow (102) which, in use, receives an edge (13) of at least one of the partition panels. The frame comprises a plurality of covering profiles (200) which are couplable by means of a snap joint to the plurality of main profiles, and which comprises a plurality of first covers (201) couplable in such a way as to close the first front hollow at the first lateral side obstructing removal of the partition panel.

Inventors: GUZZARDI; DOMENICO (Edgewater, NJ)

Applicant: FOURHUNDREDFIFTY INC. (New York, NY)

Family ID: 94870666

Appl. No.: 18/599511

Filed: March 08, 2024

Publication Classification

Int. Cl.: E04B2/74 (20060101); E06B3/36 (20060101); E06B3/46 (20060101); E06B3/70 (20060101); E06B3/72 (20060101)

U.S. Cl.:

CPC E04B2/7448 (20130101); E06B3/36 (20130101); E06B3/4636 (20130101); E06B3/725 (20130101); E04B2002/7461 (20130101); E06B2003/7059 (20130101)

Background/Summary

DESCRIPTION

[0001] This invention relates to a partition system for dividing a space of a building into a plurality of rooms. The partition system of this invention is in particular a partition system alternative to the traditional masonry or plasterboard walls. Prior art partition systems for dividing spaces are widely used for making rooms and/or corridors, for example for conference rooms and offices, and comprise a frame made with aluminium extruded profiles which are fixed to the floor, to the walls, and to the ceiling (or to the false ceiling) of the space, and one or more partition panels which are mounted on the profiles so as to make the walls; often there are one or more doorways made in the partition wall(s) with which hinged or sliding doors may be associated.

[0002] This invention was devised in particular in the context of glazed partition wall partition systems, in which one or more glass partition panels are used which define glazing with single or double panes, transparent or semi-transparent. Such partition systems have the advantage of allowing light diffusion through the partition walls and so making the rooms into which the space is divided brighter.

[0003] However, this invention is advantageously also applicable for making half-glazed or solid partition walls.

[0004] All prior art partition systems have the disadvantage of having limited soundproofing performance and so not being able to guarantee good sound insulation of one room relative to another.

[0005] In this context, the technical purpose which forms the basis of this invention is to obtain a partition system which at least partly overcomes the disadvantages of the prior art.

[0006] In particular, the technical purpose of this invention is to provide a partition system which allows one or more partition walls to be made with higher soundproofing performance.

[0007] The technical purpose specified and the aims indicated are substantially achieved by a partition system as defined in independent claim **1**. Particular embodiments of this invention are defined in the corresponding dependent claims.

[0008] Further features and the advantages of this invention will be more apparent in the detailed description of several preferred, non-limiting embodiments of a partition system for dividing a space of a building into a plurality of rooms.

Description

[0009] Reference will be made to the accompanying drawings, in which:

[0010] FIGS. **1** to **3** show, in cross-section, respectively a perimetric profile, an intermediate profile, and a jamb according to an embodiment of the partition system;

[0011] FIG. **4** shows, in cross-section, a horizontal crosspiece for a doorway according to an embodiment of the partition system;

[0012] FIG. **5** shows, in cross-section, a horizontal member of a door and a plurality of inserts couplable to it according to an embodiment of the partition system;

[0013] FIG. **6** shows, in cross-section, a different horizontal crosspiece for a doorway according to an embodiment of the partition system;

[0014] FIG. **7** shows, in cross-section, a different jamb according to an embodiment of the partition system;

[0015] FIG. **8** shows, in vertical section, a double-panel partition wall which can be made with an embodiment of the partition system;

[0016] FIG. **9** is an enlarged view of the detail IX of FIG. **8**;

[0017] FIG. **10** shows, in vertical section, a single-panel partition wall which can be made with an embodiment of the partition system;

[0018] FIG. **11** is an enlarged view of the detail XI of FIG. **10**;

[0019] FIGS. **12** and **13** show, in horizontal section, respectively a double-panel partition wall and a single-panel partition wall which can be made with an embodiment of the partition system;

[0020] FIG. **14** shows, in vertical section, a double-panel partition wall which can be made with an embodiment of the partition system;

[0021] FIG. **15** is an enlarged view of the detail XV of FIG. **14**;

[0022] FIG. **16** shows, in vertical section, a single-panel partition wall which can be made with an embodiment of the partition system;

[0023] FIG. **17** is an enlarged view of the detail XVII of FIG. **16**;

[0024] FIG. **18** shows, in horizontal section, a double-panel partition wall at a doorway and a double-panel hinged door in the closed position, according to an embodiment of the partition system;

[0025] FIGS. **19** and **20** show, enlarged, the details XIX and XX of FIG. **18**;

[0026] FIG. **21** shows, in vertical section at the doorway, the partition wall of FIG. **18**;

[0027] FIGS. **22** and **23** show, enlarged, the details XXII and XXIII of FIG. **21**;

[0028] FIG. **24** shows, in horizontal section, a double-panel partition wall at a doorway and a single-panel hinged door in the closed position, according to an embodiment of the partition system;

[0029] FIGS. **25** and **26** show, enlarged, the details XXV and XXVI of FIG. **24**;

[0030] FIG. **27** shows, in vertical section at the doorway, the partition wall of FIG. **24**;

[0031] FIGS. **28** and **29** show, enlarged, the details XXVIII and XXIX of FIG. **27**;

[0032] FIG. **30** shows, in an axonometric view, a double-panel partition wall with a doorway and a sliding door in the closed position;

[0033] FIG. **31** shows, in horizontal section, the partition wall of FIG. **30** at the doorway;

[0034] FIGS. **32** and **33** show, enlarged, the details XXXII and XXXIII of FIG. **31**;

[0035] FIG. **34** shows, in vertical section at the doorway, the partition wall of FIG. **30** with the sliding door in the closed position;

[0036] FIG. **35** is an enlarged view of the detail XXXV of FIG. **34**;

[0037] FIG. **36** shows, in vertical section next to the doorway, the partition wall of FIG. **30** with the sliding door in the open position;

[0038] FIG. **37** is an enlarged view of the detail XXXVII of FIG. **36**;

[0039] FIG. **38** shows a single-panel partition wall with a doorway and a sliding door, in the closed position, according to a horizontal section at the doorway;

[0040] FIGS. **39** and **40** show, enlarged, the details XXXIX and XL of FIG. **38**;

[0041] FIG. **41** shows, in vertical section next to the doorway, the partition wall of FIG. **38** with the sliding door in the open position;

[0042] FIG. **42** is an enlarged view of the detail XLII of FIG. **41**.

[0043] With reference to the above-mentioned figures, the reference number **10** denotes in its entirety a partition system according to this invention.

[0044] The partition system **10** comprises a frame **11** and one or more partition panels **12** which are mountable on the frame **11**. Depending on the type of partition wall **20** (glazed, half-glazed, solid), the one or more partition panels **12** may be made of glass or of a different type of material.

[0045] The frame **11** comprises a plurality of main profiles **100**, each of which has a main line of extension along which it has a cross-section-perpendicularly to the main line of extension-which is substantially constant. Each main profile **100** has a front side **101**, a first lateral flank **103**, a rear side **105** which is opposite to the front side **101**, and a second lateral flank **107** which is opposite to the first lateral flank **103** which all extend parallel to the main line of extension (examples of several embodiments of the main profiles **100** are illustrated in FIGS. **1** to **3**, **6** and **7**).

[0046] The front side **101** of each main profile **100** is associable, in use, with at least one of the one or more partition panels **12** and is advantageously configured for that purpose. Each partition panel **12** extends in a planar fashion and, when it is mounted on the frame **11**, defines its own lying plane (ideal and infinite) which is advantageously parallel to the main line of extension of each main profile **100** with which the partition panel **12** is associated.

[0047] The plurality of main profiles **100** comprises at least one plurality of perimetric profiles **110**, each of which is configured to be fixed, at its rear side **105**, to a surface of the space. In the embodiments illustrated (for example, in FIG. 1), each perimetric profile **110** has, at the rear side **105**, a flat surface which in use mates with the floor, or a wall, or the ceiling of the space to be divided up. When the partition system **10** is installed to form a partition wall **20**, the perimetric profiles **110** are advantageously positioned in such a way as to define a perimetric frame of the partition wall **20** (see for example FIGS. 8, 12, 14 and 30).

[0048] Each main profile **100** delimits a first front hollow **102** which is open both on the first lateral flank **103**, and on the front side **101**; in use, the first front hollow **102** receives an edge **13** of at least one of the one or more partition panels **12**. In the embodiments illustrated, the first front hollow **102** is advantageously delimited by two surfaces of the main profile **100** which, seen in cross-section, are positioned in an L shape.

[0049] In addition to the plurality of main profiles **100**, the frame **11** comprises a plurality of covering profiles **200** which are couplable, by means of a snap joint, to the plurality of main profiles **100** in the ways described in more detail below and illustrated in the accompanying figures. In use, each covering profile **200** is advantageously couplable either to a single main profile **100**, or to multiple main profiles **100** positioned with their main lines of extension coincident. In the embodiments illustrated (for example, in FIG. 9), the snap joint is made by inserting a projection **210** of the covering profile **200** into an elastic element **211** constrained to the main profile **100**. Advantageously, the snap joint is reversible and the covering profiles **200** can be uncoupled from the main profiles **100**, for example to be substituted with covering profiles **200** with a different colour or surface finish. Advantageously, the covering profiles **200** allow in use the colour and surface finish of the frame **11** visible to the user to be adapted to user needs, irrespective of the colour and surface finish of the main profiles **100** to which the covering profiles **200** are coupled. Preferably, each covering profile **200** is constituted of a material which is acrylonitrile butadiene styrene (ABS)-based and which comprises reinforcing fibres, for example glass fibres. Advantageously, the surface finish of each covering profile **200** is obtained by means of painting or other surface processing.

[0050] Advantageously, as illustrated in the accompanying figures, the partition system **10** comprises a plurality of types of covering profiles **200**, each of which is usable in one or more contexts.

[0051] The plurality of covering profiles **200** comprises a plurality of first covers **201**. Each first cover **201** is couplable to one of the main profiles **100** at the first lateral flank **103** in such a way as to at least partly cover the first lateral flank **103**, and in such a way as to close the first front hollow **102** at the first lateral flank **103** obstructing removal of the partition panel **12** from the first front hollow **102**. In detail, the first cover **201** is couplable in such a way as to obstruct removal of the partition panel **12** along a line perpendicular to the lying plane of the partition panel **12** (coming out relative to the first lateral flank **103**).

[0052] In the partition system **10**, in accordance with this invention, one or more of the perimetric profiles **110** are constituted of a main material which is thermoplastic polyolefin mixture-based; preferably, all of the perimetric profiles **110** are constituted of the main material. The thermoplastic polyolefin mixture comprises two or more thermoplastic polymers which belong to the class of polyolefins.

[0053] In some preferred embodiments, the thermoplastic polyolefin mixture comprises at least two polymers selected from low density polyethylene (low density polyethylene, LDPE, and/or linear

low density polyethylene, LLDPE), high density polyethylene (HDPE) and polypropylene (PP). [0054] Preferably, the thermoplastic polyolefin mixture comprises, or is constituted of, between 55% and 75% low density polyethylene (LDPE and/or LLDPE), between 20% and 40% high density polyethylene (HDPE), and between 1% and 10% polypropylene (PP); the percentages are by weight.

[0055] In one preferred embodiment, the thermoplastic polyolefin mixture is a mixture of recycled polymers to reduce the environmental impact of the partition system **10**.

[0056] Advantageously, the main material also comprises reinforcing fibres to improve the mechanical properties and, preferably, the soundproofing performance of the partition system **10**. For example, it is possible to use fibres made of glass or other material, continuous fibres aligned with the main line of extension of the perimetric profile **110**, or randomly aligned short fibres. In some embodiments, one or more of the main profiles **100** are constituted of a material which is acrylonitrile butadiene styrene (ABS)-based and which comprises reinforcing fibres; those one or more of the main profiles **100** are main profiles **100** which are different from the one or more perimetric profiles **110** constituted of the main material.

[0057] In some embodiments in which one or more of the main profiles **100** and/or the covering profiles **200** are constituted of an acrylonitrile butadiene styrene (ABS)-based material, the acrylonitrile butadiene styrene (ABS) is advantageously of the recycled type to reduce the environmental impact of the partition system **10**.

[0058] In some embodiments, at least one main profile **100** also delimits a second front hollow **108** which is open both on the second lateral flank **107**, and on the front side **101**; the second front hollow **108** is suitable for receiving, in use, an edge **13** of at least one of the one or more partition panels **12**. In the embodiments illustrated, the second front hollow **108** is advantageously delimited by two surfaces of the main profile **100** which, seen in cross-section, are positioned in an L shape, and is symmetrical relative to the first front hollow **102**; in the case of a perimetric profile **130**, the perimetric profile **130** is advantageously a T-shaped profile. Advantageously, a plurality of main profiles **100** each delimits the second front hollow **108**, preferably all of them. At least one covering profile **200** is a second cover **202** couplable to the main profile **100** at the second lateral flank **107** in such a way as to at least partly cover the second lateral flank **107**, and in such a way as to close the second front hollow **108** at the second lateral flank **107** obstructing removal of the partition panel **12** from the second front hollow **108**. That second cover **202** is couplable in such a way as to obstruct removal along a line perpendicular to the lying plane of the partition panel **12** (coming out relative to the second lateral flank **107**) whose edge **13** is received in the second front hollow **108**. In some embodiments, the first covers **201** and the second covers **202** are identical and interchangeable (see for example FIG. 9).

[0059] In some embodiments, the partition system **10** comprises a plurality of partition panels **12**, and the plurality of main profiles **100** also comprises an intermediate profile **120** whose rear side **105** is associable in use with at least one of the plurality of partition panels **12**. In addition to the first front hollow **102**, the intermediate profile **120** also delimits a first rear hollow **104** which is open both on the first lateral flank **103**, and on the rear side **105**; the first rear hollow **104** receives, in use, an edge **13** of said at least one of the plurality of partition panels **12** associable with the rear side **105** of the intermediate profile **120**. In the embodiments illustrated, the first rear hollow **104** is advantageously delimited by two surfaces of the intermediate profile **120** which, seen in cross-section, are positioned in an L shape, and is symmetrical relative to the first front hollow **102**.

[0060] At least one covering profile **200** is a third cover **203** couplable to the intermediate profile **120** at the first lateral flank **103** in such a way as to close the first rear hollow **104** at the first lateral flank **103** obstructing removal of the partition panel **12** from the first rear hollow **104**. That third cover **203** is couplable in such a way as to obstruct removal along a line perpendicular to the lying plane of the partition panel **12** (coming out relative to the first lateral flank **103**) whose edge **13** is received in the first rear hollow **104**.

[0061] In some embodiments, the third cover **203** is couplable to the intermediate profile **120** at the first lateral flank **103** and is configured in such a way as to close at the first lateral flank **103** both the first front hollow **102**, and the first rear hollow **104**, obstructing removal, from each of the first front hollow **102** and the first rear hollow **104**, of the respective partition panel **12**.

[0062] In the assembled partition wall **20**, the intermediate profile **120** may be positioned horizontally or vertically in an intermediate position between two perimetric profiles **110** opposite each other (one fixed to the ceiling and the other to the floor, or fixed to two opposite lateral walls of the space), separating two or more partition panels **50** (see for example FIG. 14).

[0063] In some embodiments, the intermediate profile **120** also itself delimits a second front hollow **108** and a second rear hollow **106** which is open both on the second lateral flank **107**, and on the rear side **105**; the second rear hollow **106** is suitable for receiving, in use, an edge **13** of at least one of the one or more partition panels **12**. In the embodiments illustrated, the second rear hollow **106** is advantageously delimited by two surfaces of the intermediate profile **120** which, seen in cross-section, are positioned in an L shape, and is symmetrical relative to the second front hollow **108** and to the first rear hollow **104**; advantageously the intermediate profile **120** is a cross-shaped profile (FIG. 2).

[0064] At least one covering profile **200** is couplable to the main profile **100** at the second lateral flank **107** in such a way as to at least partly cover the second lateral flank **107**, and in such a way as to close the second rear hollow **106** at the second lateral flank **107** obstructing removal of the partition panel **12** from the second rear hollow **106**. That covering profile **200** is couplable in such a way as to obstruct removal along a line perpendicular to the lying plane of the partition panel **12** (coming out relative to the second lateral flank **107**) whose edge **13** is received in the second rear hollow **106**.

[0065] In some embodiments, that covering profile is couplable to the intermediate profile **120** at the first lateral flank **103** and is configured in such a way as to close at the first lateral flank **103** both the second front hollow **108**, and the second rear hollow **106**, obstructing removal, from each of the second front hollow **108** and the second rear hollow **106**, of the respective partition panel **12**. In some embodiments the covering profile in question is a third cover **203** (FIG. 15).

[0066] Advantageously, when there is a plurality of main profiles **100** which each delimit a respective second front hollow **108**, and if necessary a respective first rear hollow **104** and a respective second rear hollow **106**, those main profiles **100** may be used to make, for example, a partition wall **20** with double partition panels **12** (for example with double panes), or alternatively a wall with a single partition panel (see for example FIGS. 8 to 17).

[0067] In some embodiments, at least one covering profile **200** is a fourth cover **204** couplable to one of the main profiles **100** in such a way as to partly cover at least one of either the front side **101** or the rear side **105** of the one of the main profiles **100**. In some embodiments, the fourth cover **204** is couplable to one of the main profiles **100** in such a way as to also cover, at least partly, the second lateral flank **107** of the one of the main profiles **100** and, if present, the second front hollow **108** or the second rear hollow **106** (advantageous solution in the case of walls with single partition panel).

[0068] When coupled to partly cover the front side **101** of a main profile **100**, the fourth cover **204** leaves open on the front side **101** the first front hollow **102** allowing the edge **13** of a partition panel **12** to be received in the first front hollow **102**. When coupled to partly cover the front side **101** of a main profile **100** which delimits a second front cover **108**, the fourth cover **204** may leave open on the front side **101** the first front hollow **102** and the second front hollow **108** allowing an edge **13** of a partition panel **12** to be received in each of them (for example to make a wall with double panes; see FIGS. 9 and 15). In some embodiments, the fourth cover **204** may in contrast close the second front hollow **102** on the front side **101** and on the second lateral flank **107** hiding it from view (for example to make a wall with single pane; see FIGS. 11 and 17).

[0069] When coupled to partly cover the rear side **105** of an intermediate profile **120**, the fourth

cover **204** leaves open on the rear side **105** the first rear hollow **104** allowing an edge **13** of a partition panel **12** to be received in the first front hollow **102**. When coupled to partly cover the rear side **105** of an intermediate profile **120** which delimits a second rear hollow **106**, the fourth cover **204** may leave open on the rear side **105** the first rear hollow **104** and the second rear hollow **106** allowing an edge **13** of a partition panel **12** to be received in each of them (for example to make a wall with double panes; see FIG. 15). In some embodiments, the fourth cover **204** may in contrast close the second rear hollow **106** on the rear side **105** and on the second lateral flank **107** hiding it from view (for example to make a wall with single pane; see FIG. 17).

[0070] In general, when a main profile **100** is in use associated with a plurality of partition panels **12** (at the front side **101** and if necessary at the rear side **105**), and when the same main profile **100** delimits—in addition to the first front hollow **102**—also the second front hollow **108** and/or the first rear hollow **104** and/or the second rear hollow **106**, each of the partition panels **12** is received at the respective edge **13** in only one of those hollows delimited by that main profile **100**.

Advantageously, each of those hollows delimited by that main profile **100** may in use receive an edge **13** of a plurality of partition panels **12** positioned coplanar, for example to make a partition wall **20** in which a plurality of vertical partition panels **12** are mounted alongside each other without them being separated by a component of the frame **11** but, if necessary, only by a connecting joint such as a polycarbonate profile **15** (as illustrated in FIGS. 12 and 13).

[0071] In some embodiments, the frame **11** comprises a first jamb **131** and a second jamb **132**, which are part of the plurality of main profiles **100**, and a horizontal crosspiece **140**; the first jamb **131**, the second jamb **132** and the horizontal crosspiece **140** are connectable to each other to define in use a doorway **30**, with the rear sides **105** of the first and of the second jambs **131**, **132** positioned at an inner edge of the doorway **30**. In the context of this invention, doorway **30** means an opening in the partition wall **20** which allows passage from one side of the partition wall **20** to the other. For each of the first and the second jambs **131**, **132**, at least one of the covering profiles **200** is couplable to the jamb **131**, **132** in such a way as to at least partly cover the rear side **105**. In use, each of the first and the second jambs **131**, **132** is covered at the rear side **105** by a respective covering profile **200**.

[0072] In some embodiments, the partition system **10** also comprises a door **40** which, in use, is associated with the doorway **30** and is movable between an open position, in which it allows passage through the doorway **30**, and a closed position, in which it is coupled to the doorway **30** and prevents passage through the doorway **30**.

[0073] In some embodiments (see for example FIGS. 18 to 29), the door **40** comprises a supporting structure **41**, which comprises two vertical uprights **411** and two horizontal members **412**, at least one door panel **42** mounted on the supporting structure **41**, and a plurality of inserts **43**. Each of the two vertical uprights **411** and of the two horizontal members **412** has an inner side **401**, a first flank **403**, an outer side **405** which is opposite to the inner side **401**, and a second flank **407** which is opposite to the first flank **403**; the outer side **405** of each upright/member **411**, **412** is at an outer edge **410** of the door **40**. Each of the two vertical uprights **411** and of the two horizontal members **412** delimits a first inner hollow **402**, which is open on the inner side **401** and on the first flank **403**, and a second inner hollow **408**, which is open on the inner side **401** and on the second flank **407**. Each first inner hollow **402** and each second inner hollow **408** receives one of the inserts **43**. The plurality of inserts **43** is coupled by means of a snap joint (in the embodiments illustrated, in the ways already described) to the supporting structure **41**, and at least one part of the plurality of inserts **43** defines a housing **430** in which, in use, an edge of the at least one door panel **42** is inserted and retained.

[0074] The door **40** may be of the single-panel or double-panel type. The plurality of inserts **43** advantageously comprises hollow inserts **431** and covering inserts **432**, in such a way that, when the door **40** comprises a single door panel **42**, a plurality of hollow inserts **431** coupled to the first inner hollow **402** defines the housing **430** for the door panel **42**, whilst a plurality of covering

inserts **432** coupled to the second inner hollows **408** hides the latter from view. When the door **40** comprises two door panels **42**, a plurality of hollow inserts **431** is coupled both to the first inner hollows **402**, and to the second inner hollows **408** defining two housings **430** for two door panels **42** (one at the first inner hollows **402**, and one at the second inner hollows **408**).

[0075] In some embodiments the door **40** is connectable to the doorway **30** by means of a hinge and, if necessary, by means of a return arm **31**.

[0076] In some embodiments (see for example FIGS. **30** to **42**), the partition system **10** comprises a door **40** which is slidable between the open position and the closed position. In those embodiments, the horizontal crosspiece **140** is a main profile **100**, and comprises a first portion **141**, which in use extends between the first and the second jambs **131,132** (along the main line of extension), and a second portion **142** which in use extends cantilever-style beyond the second jamb **132** (along the main line of extension). Moreover, the horizontal crosspiece **140** delimits a channel **143** which extends along the first portion **141** and the second portion **142**: the channel **143** is open on the front side **101** (which in use is directed downwards) and is configured to receive in use a sliding mechanism **144** for the (sliding) door **40**. The channel **143** extends along the main line of extension preferably parallel to the first front hollow **102** of the horizontal crosspiece **140**. At least one covering profile **200** is couplable to the first portion **141** of the horizontal crosspiece **140** for closing the first front hollow **102** at the doorway **30** and at the front side **101** (FIGS. **34** and **35**). In contrast, the first front hollow **102** of the horizontal crosspiece **140** receives, in use, the edge **13** of one or more partition panels **12** at the second portion **142** (FIGS. **36** and **37**). The door **40**, when in use it slides between the open position and the closed position, slides parallel to the one or more partition panels **12** received in the first front hollow **102**.

[0077] Advantageously, in order to make for example a double-panel partition wall **20**, the horizontal crosspiece **140** also delimits a central hollow **109** which is open on the front side **101**; advantageously, the central hollow is interposed between the first front hollow **102** and the channel **143**, for receiving in use further one or more partition panels **12** (FIGS. **6**, **36** and **37**).

[0078] Preferably, the first jamb **131** also delimits, at the rear side **105**, a seat **134** which is open and which, in use, receives an outer edge **410** of the (sliding) door **40** when the latter is in the closed position.

[0079] At least in these embodiments, in use both the part of the horizontal crosspiece **140** which delimits the channel **143**, and the seat **134** are advantageously positioned cantilever-style relative to the rest of the wall to which they belong.

[0080] Advantageously, and similarly to some embodiments of the horizontal crosspiece **140**, the first jamb **131** delimits a central hollow **109** which is open on the front side **101** for receiving in use further one or more partition panels **12**.

[0081] Preferably, at least one of each main profile **100** and the one or more covering profiles **200** couplable to it in such a way as to obstruct removal of the partition panels **12** from the respective hollows, is equipped with a gasket **14** by means of which it makes contact with the respective partition panels **12**.

[0082] One advantage of different embodiments of the partition system **10** described above is its modularity: by using a limited number of elements, the partition system **10** can allow partition walls to be made which differ from each other based on the combination of those elements. For example, with the same partition system **10** it is possible to make a single-panel or double-panel (glazed or solid) partition wall **20**, with a doorway **30** and with a single-panel or double-panel door **40**, sliding or fixed by means of hinges.

[0083] The invention described above may be modified and adapted in several ways without thereby departing from the scope of the inventive concept as defined in the independent claims.

[0084] All details may be substituted with other technically equivalent elements and the materials used, as well as the shapes and dimensions of the various components, may vary according to requirements.

Claims

1. A partition system (10) for dividing a space of a building into a plurality of rooms, comprising a frame (11) and one or more partition panels (12) mountable on the frame (11), wherein: the frame (11) comprises a plurality of main profiles (100), each main profile (100) having a front side (101) in use associable with at least one of the one or more partition panels (12), a first lateral flank (103), a rear side (105) which is opposite to the front side (101), and a second lateral flank (107) which is opposite to the first lateral flank (103); the plurality of main profiles (100) comprises at least one plurality of perimetric profiles (110), each perimetric profile being configured to be fixed at the rear side (105) to a surface of the space; each main profile (100) delimits a first front hollow (102) which is open both on the first lateral flank (103), and on the front side (101); in use, the first front hollow (102) receives an edge (13) of at least one of the one or more partition panels (12); the frame (11) also comprises a plurality of covering profiles (200) which are couplable by means of a snap joint to the plurality of main profiles (100); the plurality of covering profiles (200) comprises a plurality of first covers (201), each first cover (201) being couplable to one of the main profiles (100) at the first lateral flank (103) in such a way as to at least partly cover the first lateral flank (103) and to close said first front hollow (102) at the first lateral flank (103) obstructing removal of the partition panel (12) from the first front hollow (102); and one or more of the perimetric profiles (110) are constituted of a main material which is thermoplastic polyolefin mixture-based.
2. The partition system (10) according to claim 1, wherein the thermoplastic polyolefin mixture comprises at least two polymers selected from low density polyethylene, high density polyethylene and polypropylene.
3. The partition system (10) according to claim 2, wherein the thermoplastic polyolefin mixture comprises, or is constituted of, between 55% and 75% low density polyethylene, between 20% and 40% high density polyethylene, and between 1% and 10% polypropylene.
4. The partition system (10) according to claim 1, wherein the main material also comprises reinforcing fibres.
5. The partition system (10) according to claim 1, wherein one or more of the main profiles (100) are constituted of a material which is acrylonitrile butadiene styrene-based and which comprises reinforcing fibres.
6. The partition system (10) according to claim 1, wherein: at least one main profile (100) also delimits a second front hollow (108) which is open both on the second lateral flank (107), and on the front side (101); that second front hollow (108) is suitable for receiving, in use, an edge (13) of at least one of the one or more partition panels (12); and at least one covering profile (200) is a second cover (202) couplable to said at least one main profile (100) at the second lateral flank (107) in such a way as to at least partly cover the second lateral flank (107) and to close said second front hollow (108) at the second lateral flank (107) obstructing removal of the partition panel (12) from the second front hollow (108).
7. The partition system (10) according to claim 1, comprising a plurality of partition panels (12), wherein moreover: the plurality of main profiles (100) also comprises an intermediate profile (120); the rear side (105) of the intermediate profile (120) is associable in use with at least one of the plurality of partition panels (12); the intermediate profile (120) also delimits a first rear hollow (104) which is open both on the first lateral flank (103), and on the rear side (105); in use, that first rear hollow (104) receives an edge (13) of said at least one of the plurality of partition panels (12) associable with the rear side (105) of the intermediate profile (120); and at least one covering profile (200) is a third cover (203) couplable to the intermediate profile (120) at the first lateral flank (103) in such a way as to close the first rear hollow (104) at the first lateral flank (103) obstructing removal of the partition panel from the first rear hollow (104).
8. The partition system (10) according to claim 7, wherein the third cover (203) is couplable to the

intermediate profile (120) at the first lateral flank (103) and is configured in such a way as to close at the first lateral flank (103) both the first front hollow (102), and the first rear hollow (104), obstructing removal, from each of the first front hollow (102) and the first rear hollow (104), of the respective partition panel (12).

9. The partition system (10) according to claim 1, wherein at least one covering profile (200) is a fourth cover (204) couplable to one of the main profiles (100) in such a way as to partly cover at least one of either the front side (101) or the rear side (105) of the one of the main profiles (100).

10. The partition system (10) according to claim 9, wherein the fourth cover (204) is couplable to one of the main profiles (100) in such a way as to also cover, at least partly, the second lateral flank (107) of the one of the main profiles (100).

11. The partition system (10) according to claim 1, wherein each covering profile (200) is constituted of a material which is acrylonitrile butadiene styrene-based and which comprises reinforcing fibres.

12. The partition system (10) according to claim 1, wherein: the plurality of main profiles (100) also comprises a first jamb (131) and a second jamb (132); the frame (11) also comprises a horizontal crosspiece (140); the first jamb (131), the second jamb (132) and the horizontal crosspiece (140) are connectable to each other to define in use a doorway (30), with the rear sides (105) of the first and of the second jambs (131, 132) at an inner edge of the doorway (30); and for each of the first and the second jambs (131, 132), at least one of the covering profiles (200) is couplable to the jamb in such a way as to at least partly cover the rear side (105).

13. The partition system (10) according to claim 12, also comprising a door (40) which in use is associated with the doorway (30) and is movable between an open position in which it allows passage through the doorway (30) and a closed position in which it is coupled to the doorway (30) and prevents passage through the doorway (30); wherein moreover: the door (40) comprises a supporting structure (41) which comprises two vertical uprights (411) and two horizontal members (412), at least one door panel (42) mounted on the supporting structure (41), and a plurality of inserts (43); each of the two vertical uprights (411) and of the two horizontal members (412) has an inner side (401), a first flank (403), an outer side (405) which is opposite to the inner side (401), and a second flank (407) which is opposite to the first flank (403); the outer side (405) being at an outer edge (410) of the door (40); each of the two vertical uprights (411) and of the two horizontal members (412) delimits a first inner hollow (402) and a second inner hollow (408), the first inner hollow (402) being open on the inner side (401) and on the first flank (403), the second inner hollow (408) being open on the inner side (401) and on the second flank (407); each first inner hollow (402) and each second inner hollow (408) receives one of the inserts (43); the plurality of inserts (43) is coupled by means of a snap joint to the supporting structure (41); and at least one part of the plurality of inserts (43) defines a housing (430) in which an edge of the at least one door panel (42) is inserted and retained.

14. The partition system (10) according to claim 12, also comprising a door (40) which in use is associated with the doorway (30) and which is slidable between an open position in which it allows passage through the doorway (30) and a closed position in which it is coupled to the doorway (30) and prevents passage through the doorway (30), wherein moreover: the horizontal crosspiece (140) is a main profile (100); the horizontal crosspiece (140) comprises a first portion (141) which in use extends between the first and the second jambs (132), and a second portion (142) which in use extends cantilever-style beyond the second jamb (132); the horizontal crosspiece (140) delimits a channel (143) which extends along the first portion (141) and the second portion (142); the channel (143) is open on the front side (101) and is configured to receive in use a sliding mechanism (144) for the door (40); at least one covering profile (200) is couplable to the first portion (141) of the horizontal crosspiece (140) for closing the first front hollow (102) at the doorway (30) and at the front side (101), the first front hollow (102) of the horizontal crosspiece (140) receiving, in use, the edge (13) of the at least one of the one or more partition panels (12) at the second portion (142).

15. The partition system (**10**) according to claim 14, wherein the first jamb (**131**), at the rear side (**105**), also delimits a seat (**134**) which is open and which, in use, receives an outer edge (**410**) of the door (**40**) when the latter is in the closed position.
